

1 Solution Requirements

1.1 User Accounts

1.1.1 Account Registration

Type	Functional
Description	New users must be able to create an account which is stored on the server.
Priority	High
Input	The user will give a username, email address and password.
Operations	The server will check that the username and password conform to any length and composition restraints, the email is structured correctly, and that the username and email address are both unique.
Expected Results	If the given information is valid, a new account with the details entered by the user will be stored.
Pass / Fail Remarks	

1.1.2 Account Activation

Type	Functional
Description	New accounts must have their email addresses verified with a verification email. The account will not be 'active' - it will not provide access to restricted resources - until the user verifies their email.
Priority	Medium
Pre-conditions	Account Registration
Input	The user will click a link on the verification email to activate the account.
Operations	The server will check to see if the account has already been activated, or if the account has expired because it had not been activated for an amount of time.
Expected Results	The account will be marked as active if the account exists and has not yet been activated. If the account is not activated within a set amount of time of the email being sent, the account is removed from the system.
Pass / Fail Remarks	

1.1.3 Administrator Accounts

Type	Functional
Description	It must be possible to mark an account as being owned by an Administrator. These accounts will be authorised to perform more actions than normal user accounts.
Priority	Medium
Pre-conditions	Account Registration
Expected Results	An account marked as being an Administrator account will have additional abilities as defined by later requirements.
Pass / Fail Remarks	

1.1.4 Resend Activation Email

Type	Functional
Description	A user must be able to request that the activation email is resent. This will invalidate the previously sent email.
Priority	Low
Pre-conditions	Account Activation
Input	The user will supply their email address, which is where the activation email will be sent.
Operations	The server will check that the email address is registered to an existing account that is not already active.
Expected Results	If the email is registered to an inactivated account, an activation email is sent to the user with a link to activate the account.
Pass / Fail Remarks	

1.1.5 User Authentication

Type	Functional
Description	A user with an activated account must be able to authenticate themselves in order to access resources restricted to account owners.
Priority	High
Pre-conditions	Account Registration
Input	The user will give their username and password.
Operations	The server will look for an account in the database which matches the username and password provided.
Expected Results	If a matching account is found, the user is authenticated as the account owner and they may access some otherwise restricted parts of the system. Otherwise, the user will be informed that the credentials that they supplied are incorrect.
Pass / Fail Remarks	

1.1.6 Account Removal

Type	Functional
Description	An authenticated user must be able to request the deletion of that account along with all personal data. This request must be confirmed by the user through a confirmation email within a week.
Priority	Medium
Pre-conditions	User Authentication
Input	The user will need to be authenticated and also click on a link in a confirmation email.
Operations	The request will only be fulfilled when the user has clicked a link in a confirmation email that was sent when they initiated the request and it has been under a week since it was sent.
Expected Results	When the user has confirmed the action, their account will be deleted from the server along with any related personal data.
Pass / Fail Remarks	

1.1.7 Administrator Account Removal

Type	Functional
Description	A user authenticated as an administrator must be able to delete any non-administrator account.
Priority	Medium
Pre-conditions	Administrator Accounts
Input	The administrator will select which account they wish to delete.
Operations	The server will check that the selected account exists and the user making the request is an authenticated administrator.
Expected Results	The selected account will be removed from the system.
Pass / Fail Remarks	

1.1.8 Password Reset

Type	Functional
Description	A user should be able to request to reset their password. They do not need to be authenticated to do so. Upon initiating the request, an email will be sent to confirm the action and allow them to choose a new password.
Priority	Low
Pre-conditions	Account Registration
Input	The user will enter their email address.
Operations	The given email address will be checked to see if it is registered to a user account.
Expected Results	If the email address does not match an account, the user is informed with a message. Otherwise, an email will be sent to the given email address containing a link to reset their password.
Pass / Fail Remarks	

1.1.9 Activation Email Delay

Type	Non - Functional
Description	After a user requests an activation email or password reset email, the email must have been sent to them within a minute.
Pass / Fail Remarks	

1.1.10 Ease of Account Creation

Type	Non - Functional
Description	A user with no experience of the system but with at least basic knowledge of operating a computer must be able to create an account including activation unassisted and within 5 minutes.
Pass / Fail Remarks	

1.1.11 Response Times

Type	Non - Functional
Description	The server must not take longer than 2 seconds on average to process each individual request.
Pass / Fail Remarks	

1.2 Game Mechanics

1.2.1 Account Balance

Type	Functional
Description	Each user account must have a point balance associated with it. When authenticated, the user that owns the account must be able to view the balance at any time.
Priority	High
Pre-conditions	Account Registration
Operations	The server will check that the user is authenticated.
Expected Results	An authenticated user will be able to view their account balance.
Pass / Fail Remarks	

1.2.2 Account Transactions

Type	Functional
Description	It must be possible for points to be added and removed from a user's account balance by other components of the system.
Priority	High
Pre-conditions	Account Balance
Input	The amount of points to be added or removed is specified.
Operations	A withdrawal transaction will not occur if the number of points to remove exceeds the number of points stored in the account.
Expected Results	When a withdrawal or deposit occurs, the updated amount of points in the account will be updated immediately.
Pass / Fail Remarks	

1.2.3 Cache Ownership

Type	Functional
Description	A cache is able to be owned by at most one user at a time. Users must be able to see which caches are owned, and who owns them.
Priority	High
Pre-conditions	Account Registration
Input	A user makes a request to view the owner of a cache.
Operations	The server will check to see if the cache has an owner.
Expected Results	If the cache has an owner, the current owner will be displayed.
Pass / Fail Remarks	

1.2.4 Cache Balance

Type	Functional
Description	A cache must have a point balance associated with it, which must be visible to authorised users, including the owner of the cache, when requested.
Priority	High
Input	A user makes a request to view the point balance of a cache.
Operations	The server checks to see if the user is authorized to view the point balance of the cache.
Expected Results	The balance of a cache will be displayed to authorised users when requested.
Pass / Fail	
Remarks	

1.2.5 Cache Transactions

Type	Functional
Description	It must be possible for points be added or removed from the cache by other components of the system.
Priority	High
Pre-conditions	Cache Balance
Input	When points are being added or removed, the amount is specified.
Operations	A withdrawal transaction will not occur if the number of points to remove exceeds the number of points stored in the cache.
Expected Results	When a withdrawal or deposit occurs, the updated amount of points in the cache will be visible to authorised users when requested.
Pass / Fail	
Remarks	

1.2.6 Cache Withdrawal

Type	Functional
Description	The owner of a cache must be able to transfer points from the cache to their account when they physically visit the location of the cache. An owned cache becomes unowned if the owning user withdraws all points from the cache.
Priority	High
Pre-conditions	Account Balance, Cache Balance
Input	The user will specify how many points to withdraw.
Operations	The server will check to see if the user performing the transaction is within a given radius of the cache. The server will also check to ensure the point balance of the cache has at least the number they wish to withdraw.
Expected Results	If the user is not within a given radius of the cache or the cache has less points stored in it than the requested amount to withdraw, the user will be informed and the transaction will not occur. Otherwise, the cache and user account balances are updated after the transaction. If a withdrawal leaves a cache empty then the cache is marked as unowned.
Pass / Fail Remarks	

1.2.7 Cache Depositing

Type	Functional
Description	When they physically visit the location of a cache that is owned by them or does not have an owner, a user must be able to transfer points to the cache from their account. After transferring one or more points to an unowned cache, the unowned cache will become owned by the user.
Priority	High
Pre-conditions	Account Balance, Cache Balance
Input	The user will specify how many points to deposit.
Operations	The server will check to see if the user performing the transaction is within a given radius of the cache. The server also checks to see if the user has enough points.
Expected Results	If the user is not within a given radius of the cache or the user owns less points than they requested to deposit, the user is informed and the transaction does not occur. Otherwise the cache and user account balances are updated after the transaction. If a deposit leaves a previously empty cache populated then the cache is marked as owned.
Pass / Fail Remarks	

1.2.8 Cache Placement Cost

Type	Functional
Description	When placing a cache, a number of points must be deducted from the user's account balance.
Priority	High
Pre-conditions	Account Balance, Cache Placement
Input	A user attempts to place a cache.
Operations	The server will check to see if the user has enough points in their account to place the cache.
Expected Results	If the user can afford it, the cache is placed and points are removed from the placing user's account.
Pass / Fail Remarks	

1.2.9 Cache Scouting

Type	Functional
Description	If a user physically visits the location of a cache owned by a different user, they must be able to view the current point balance of that cache.
Priority	Medium
Pre-conditions	Find Location, Cache Balance
Input	The location of the user is supplied.
Operations	The distance of the user from the cache is checked to ensure they are sufficiently near the cache.
Expected Results	If the user is within a given radius of the cache, they will be shown the number of points that is stored in the cache.
Pass / Fail Remarks	

1.2.10 Cache Attacking

Type	Functional
Description	After scouting a cache, a user must be given the option to trigger an attack on that cache using points from their account.
Priority	High
Pre-conditions	Cache Scouting
Input	The attacker chooses how many points from their account they will attack with.
Operations	The server checks that the attacker's distance to the cache is less than a given radius, and has input a number of points between one and the number of points in their account. The server will decide which party survives the encounter, and how many points they lost in the conflict.
Expected Results	If the request was valid, an attack is initiated on the cache by that user with the specified number of points.
Pass / Fail Remarks	

1.2.11 Successful Attack

Type	Functional
Description	If the attacker wins, the ownership of the cache must pass to them. All defending points will be lost, and the surviving attacking points will transferred to the balance of the cache.
Priority	High
Pre-conditions	Cache Attacking
Expected Results	The surviving points from their attack will be moved to the cache's point balance, and the cache becomes owned by the attacker.
Pass / Fail Remarks	

1.2.12 Successful Defence

Type	Functional
Description	If the defender wins, the cache must remains theirs. All attacking points are lost, and the surviving defenders remain in the cache.
Priority	High
Pre-conditions	Cache Attacking
Expected Results	The surviving defenders remain in the cache, which remains owned by the defending user.
Pass / Fail Remarks	

1.2.13 Battle Breakdown

Type	Functional
Description	After an attack on a cache, the attacking user will be able to view a breakdown of the results of the attack.
Priority	Low
Pre-conditions	Cache Attacking
Input Operations	An attack on a cache has concluded. The server will provide information such as the number of units lost by each side, and the reward for winning if the attacker was victorious.
Expected Results	A breakdown of the results of the battle will be displayed to the attacking user.
Pass / Fail Remarks	

1.2.14 Cache Operation Chronology

Type	Functional
Description	All operations on a given cache (transactions, attacks and deletions) must occur in chronological order in respect to when they were received by the server.
Priority	High
Pre-conditions	Cache Transactions, Cache Attacking
Input	An operation on a cache performed by a user or administrator.
Operations	The server will only process one request concerning operations on a cache at time.
Expected Results	An operation will not be initiated until all previously received requests concerning operations on that cache have been completed.
Pass / Fail Remarks	

1.2.15 Point Generation

Type	Functional
Description	Points must be periodically supplied to each user based on their current performance in the game.
Priority	High
Pre-conditions	Account Balance
Input	The point allocation system will use a user's current cache number, the events of recent battles involving the user, and other relevant data.
Operations	The server will use the given information to decide how many points to give the user.
Expected Results	Each user will periodically receive points based on their performance in the game.
Pass / Fail Remarks	

1.2.16 Administrator Placed Caches

Type	Functional
Description	It must be possible for administrators to place caches without needing to be at the location. These caches behave as normal, and the administrator can place it with as many points in them as they wish, including none.
Priority	Medium
Pre-conditions	Cache Attacking
Input	Administrators will specify the longitude and latitude of a new cache to place, along with how many points will be stored there.
Operations	The server will validate the location given and if the number of units placed is non-negative.
Expected Results	The cache will immediately be placed at the given location with the specified number of points in its balance.
Pass / Fail Remarks	

1.2.17 Non-Player Caches

Type	Functional
Description	It must be possible for administrators to place caches which may be attacked by users, but not claimed after a victory.
Priority	Medium
Pre-conditions	Cache Attacking
Input	Administrators will specify the longitude and latitude of a new cache to place, along with how many points will be stored there.
Operations	The server will validate the location given and the point balance given is non-negative.
Expected Results	The cache will immediately be placed at the given location with the specified number of points in its balance.
Pass / Fail Remarks	

1.2.18 Attacking Non-Player Caches

Type	Functional
Description	A user attacking a non-player cache must receive a number of points if they are victorious, but it will not become theirs. After the victory, the number of points in the cache balance should be reset.
Priority	Medium
Pre-conditions	Non-Player Caches
Input	Users may trigger an attack in the same was as they would on a user controlled cache.
Operations	The process for deciding the outcome of an attack on a non-player cache will take the same form as one on a user cache. Each attack is treated as a separate instance and each user will have to wait a period of time before they can attack the same non-player cache again.
Expected Results	The attacking player will receive a point reward directly to their account if they are deemed to have won the battle, and the point balance in the cache will be reset.
Pass / Fail Remarks	

1.2.19 Scouting Non-Player Caches

Type	Functional
Description	If a user that has attacked a non-player cache and the minimum delay between attacks on a non-player cache has not elapsed for that cache, the user will not be allowed to scout (and by extension, attack) the cache.
Priority	Medium
Pre-conditions	Attacking Non-Player Caches
Input	A user attempts to scout a non-player cache that they attacked a period of time ago that is less than the minimum amount of time that they must wait in between attacking non-player caches.
Operations	The server will check the amount of time since that user last attacked the cache (if at all).
Expected Results	If the user has never attacked that cache, or the time since the last attack is greater than the amount of time a user must wait between attacks on a non-player cache, they are able to scout the cache as normal. Otherwise they cannot.
Pass / Fail Remarks	

1.2.20 Special Event Placement

Type	Functional
Description	It should be possible for administrators to define areas by the MAC address of a nearby wireless network. This area will define a collection point for a one-time-only reward which will be limited to a given number of users.
Priority	Low
Pre-conditions	Find MAC Address
Input	Administrators will specify the MAC address of the new cache, the reward, and how many users may claim that reward.
Operations	The server will validate that the given address is a valid MAC address, and that the reward and number of users which can claim it are greater than zero.
Expected Results	A new special event area will be available for users to be notified of and claim rewards from.
Pass / Fail Remarks	

1.2.21 Special Event Rewards

Type	Functional
Description	When a user enters the effective range of a wireless network whose MAC address has been designated as a special event placement, they must be able to claim a reward from it. If it is still available, they will receive points directly to their account balance.
Priority	Low
Pre-conditions	Special Event Placement
Input	A user claims a reward at a given wireless network.
Operations	The server will check to see if the reward is still available.
Expected Results	If the reward is still available, a user can claim the reward. The value is credited directly to their point balance and the special event area is removed after the reward has been claimed by a designated number of users.
Pass / Fail Remarks	

1.2.22 Cache Reporting

Type	Functional
Description	Users should have the ability to mark a cache as being placed unfairly. Administrators will be alerted to the reported cache.
Priority	Medium
Pre-conditions	Cache Placement
Input	A user will select a cache that they wish to report.
Operations	The server will check that the cache is not owned by the user themselves, has not already been reported, and is not a non-player cache.
Expected Results	If the report is valid, an administrator will be alerted to the reported cache, with information including the owner, location, and who reported it.
Pass / Fail Remarks	

1.2.23 Administrator Cache Deletion

Type	Functional
Description	Administrators must have the ability to delete any cache from the system.
Priority	Medium
Pre-conditions	Administrator Accounts
Input	An administrator will select a cache that they wish to remove from the system.
Operations	The server will check that the selected cache exists and that the user making the request is an authenticated administrator.
Expected Results	The selected cache will be deleted from the server and will no longer be visible to users.
Pass / Fail Remarks	

1.2.24 Account Deletion Cache Removal

Type	Functional
Description	When a player account is removed from the system, all caches owned by them must also be deleted.
Priority	Medium
Pre-conditions	Cache Ownership, Account Removal
Input	The process will be triggered by a user account being removed
Operations	The server will find all caches owned by that account.
Expected Results	All caches owned by the deleted player will be removed from the system.
Pass / Fail Remarks	

1.2.25 Distinguishing Cache Owners

Type Description	Non - Functional A new user must be able to identify which caches are owned by themselves, which are owned by opponents, and which have no owners at all without assistance.
Pass / Fail Remarks	

1.2.26 Difficulty Curve

Type Description	Non - Functional It should be relatively easy for a player with a small amount of caches to expand their territory (own new caches), and get progressively more difficult to protect them as they own a larger amount of caches.
Pass / Fail Remarks	

1.2.27 New Player Protection

Type Description	Non - Functional There must be some form of protection for new players to deter older ones from easily eliminating them, or a disincentive to make preying on new players unprofitable.
Pass / Fail Remarks	

1.2.28 Cache Action Delay

Type Description	Non - Functional Any action performed by an administrator or user on a cache (such as placement, transactions or an attack) must take effect within 10 seconds.
Pass / Fail Remarks	

1.2.29 Anti-Cheating Measures

Type Description	Non - Functional It should be almost impossible for someone without knowledge of the internal workings of the application to fake their position to the server and be able to perform location dependent actions without actually being at the required location.
Pass / Fail Remarks	

1.2.30 Data Usage

Type	Non - Functional
Description	The application should, while in active use, transfer on average less than 5MB an hour with the server.
Pass / Fail	
Remarks	

1.3 Application

1.3.1 Display Location

Type	Functional
Description	The application must allow the user to have displayed to them their current location in the context of a map provided by the Google Maps API.
Priority	High
Pre-conditions	Find Location
Input	The user will request for the Google Maps API powered map to navigate to their current location.
Operations	The application will check to see if the user has an Internet connection and that their GPS antenna is enabled.
Expected Results	If the user has an internet connection and their GPS antenna is enabled, the application will show the user's location on a map provided by the Google Maps API.
Pass / Fail	
Remarks	

1.3.2 Nearby Caches

Type	Functional
Description	The application must be able to show the user, on the map, the locations of caches near to a specified location.
Priority	High
Pre-conditions	Find Location, Display Location, Server Connectivity
Input	The user will request to see the locations of caches near to a specified position.
Operations	The application will check that the device's GPS antenna is enabled and there is Internet connectivity. If there is a connection and the antenna is enabled, the application will send a request to the Server for a list of coordinates of caches near to the specified position.
Expected Results	The application will mark on the map, provided by the Google Maps API, all caches near to the specified position.
Pass / Fail	
Remarks	

1.3.3 Map Zooming

Type	Functional
Description	The application should allow the user to view a larger or smaller area of the map.
Priority	Medium
Pre-conditions	Nearby Caches
Input	The user will be able to specify the 'zoom level'.
Operations	The application will ensure that the specified zoom level is within defined limits, and if so will request from the server a list of caches within the portion of the map that is currently visible.
Expected Results	The map is displayed at different levels of zoom, as specified by the user, along with any caches that should be visible at that level of zoom.
Pass / Fail Remarks	

1.3.4 Path Finding

Type	Functional
Description	The application should allow the user to view a path between the user's current position and a target cache they specify.
Priority	Low
Pre-conditions	Find Location, Display Location, Nearby Caches
Input	The user will select which cache they want to navigate to.
Operations	The application will use the Google Directions API to find a path to the target cache.
Expected Results	A path will be drawn on a map to show which route to take.
Pass / Fail Remarks	

1.3.5 Cache Placement

Type	Functional
Description	The application must allow the user to request the placement of a cache at their current location.
Priority	High
Pre-conditions	Find Location, Server Connectivity
Input	The user will trigger a request to place a cache at their current position.
Operations	The server will validate the request to place a new cache.
Expected Results	The application will send a cache placement request to the central server, and if it is successful all users will be able to see the new cache.
Pass / Fail Remarks	

1.3.6 Activity Recording

Type	Functional
Description	Any game activity performed by a registered user should be recorded and can be viewed by that user when requested. Users will also be able to view activities by other users which have a direct effect on them.
Priority	Medium
Pre-conditions	User Accounts
Input	A user can request the activities that have occurred since a specified time and date.
Operations	The server will locate all activities related to that user since they time they gave.
Expected Results	Any activities that occurred since the given time and date will be displayed to the user.
Pass / Fail Remarks	

1.3.7 Interface Style Uniformity

Type	Non - Functional
Description	The application's graphical user interface must have a consistent overall style, including colour scheme, usage of images, and structure.
Pass / Fail Remarks	

1.3.8 Interface Scaling

Type	Non - Functional
Description	All elements of the user interface should adhere to the screen dimensions of the host device. No elements of the interface should not be visible due to being cropped off-screen.
Pass / Fail Remarks	

1.3.9 Interface Feedback Delay

Type	Non - Functional
Description	The user interface should provide feedback of some form for all user actions that require a response within 0.25 seconds.
Pass / Fail Remarks	

1.3.10 Start-up Time

Type	Non - Functional
Description	The application should, on average, be ready for user input in less than 10 seconds after starting.
Pass / Fail	
Remarks	

1.3.11 Battery Usage

Type	Non - Functional
Description	The application should be optimised such that, when started on a device with a full battery, it can be active for at least 4 hours without completely depleting the host device's battery.
Pass / Fail	
Remarks	

1.4 Peripheral Functionality

1.4.1 User Communication

Type	Functional
Description	Users may be able to send messages to other users.
Priority	Low
Pre-conditions	User Accounts
Input	An authenticated user will specify the message subject, and the message to send.
Operations	The server will check that the subject and message body are not empty.
Expected Results	A message will be created which is visible to all intended recipients.
Pass / Fail	
Remarks	

1.4.2 Communication Reporting

Type	Functional
Description	Users should have the ability to report communications sent between users as being inappropriate. Administrators will be alerted to the reported communication.
Priority	Low
Pre-conditions	User Communication
Input	The user will specify which message to report.
Expected Results	An administrator will be alerted to the reported message, including information such as the sender, message content and who reported it.
Pass / Fail Remarks	

1.4.3 Website

Type	Functional
Description	There must be a website that is accessible by users.
Priority	Medium
Pre-conditions	User Accounts
Input	A user will make a request to access a certain page of the website through a web browser.
Operations	The server will provide the requested page if it exists.
Expected Results	A user will be able to view a requested web page if it exists.
Pass / Fail Remarks	

1.4.4 Website Authentication

Type	Functional
Description	A user must be able to authenticate themselves to their account through the website to be able to access restricted content on the site.
Priority	Medium
Pre-conditions	Website, User Authentication
Input	The user will give their username and password.
Operations	The server will look for an account in the database which matches the username and password provided.
Expected Results	If a matching account is found, the user is authenticated as the account owner and they may access some otherwise restricted parts of the website. Otherwise, the user will be informed that the credentials that they supplied are incorrect.
Pass / Fail Remarks	

1.4.5 Viewing Owned Caches

Type	Functional
Description	A user, when authenticated on the website, must be able to view a list of all caches that are currently owned by them, and details about each one, including the number of points stored inside and its location.
Priority	Medium
Pre-conditions	Website Authentication, Cache Ownership
Input	A user will request to view the web page containing a list of the caches they own.
Operations	The server will ensure the user is authenticated.
Expected Results	If the user is authenticated, a web page containing a list of all caches owned by that user's account is displayed.
Pass / Fail Remarks	

1.4.6 Viewing Cache Details

Type	Functional
Description	On the website, an authenticated user must be able to view information about a specified cache. This information will include a graphical representation of the location of that cache on a map. If the cache is owned by the user that made the request, further information such as the number of points in the cache and a history of attacks made against the cache while it was owned by that user are also displayed.
Priority	Low
Pre-conditions	Website Authentication, Cache Ownership
Input	A user will request to view a web page containing additional information about a specified cache.
Operations	The server will check that the user is authenticated, the specified cache exists, and if currently owned by the user.
Expected Results	A web page with details about that cache will be displayed, including a graphical representation of the cache's location on a map and the current owner. If the cache is owned by the user that made the request, additional information will be displayed including the number of points in the cache and a history of its recent events.
Pass / Fail Remarks	

1.4.7 Overview Map

Type	Functional
Description	An authenticated user must be able to view a map, using the Google Maps API, which displays a subset of all caches. The user will be able to specify a filter to decide which caches are displayed. The user should also be able to use this map to select a cache to view information about it.
Priority	Medium
Pre-conditions	Viewing Cache Details
Input	A user requests to view a web page containing the overview map using a specified filter.
Operations	The server will ensure that the user is authenticated. If they are authenticated, the server will find the collection of caches that matches the specified filter.
Expected Results	If the user is authenticated, they will be provided with a web page containing the overview map. The map will only contain the caches that match the given filter, and will allow the user to select caches on the map to access the cache details page for that cache.
Pass / Fail Remarks	

1.4.8 Website-Application Style Uniformity

Type	Non - Functional
Description	The overall style of the website must match that chosen for the Android application, with the exception of the general structure which may differ.
Pass / Fail Remarks	

1.4.9 Page Request Response Time

Type	Non - Functional
Description	The server must, on average, take less than 2 seconds to produce a requested web page after receiving a request.
Pass / Fail Remarks	

1.4.10 Ease of Navigation

Type	Non - Functional
Description	It must be possible to travel between any two pages in no more than three page transitions (assuming the user attempting to access the desired page is authorised to).
Pass / Fail Remarks	