

LOGICS

Public API Documentation

Version 4 (V4) · Endpoint Reference

Base URL

<https://valortax.logiqsapi.com/publicapi/V4/>

Prepared: September 26, 2026

Contents

This document is organized by feature area. Each entry below groups its GET/POST endpoints together.

Category	Endpoints	Required Scopes
Appointment	4	case.read / case.write
Billing	10	payments.read / payments.write
Case	6	case.read / case.write
Case Activity	3	case.read / activity.write
Documents	1	case.write
Fax	1	fax.write
Find	3	case.read
Report	1	reports.activityreport.read
Services	1	case.read
Task	3	task.read / task.write
User	1	user.write

API Authentication Guide

Overview

The Logics Public API uses Basic Authentication to secure all requests. You'll need two credentials:

- **Username:** Your API Key
- **Password:** Your Secret Token

1. Getting Your API Key (Username)

Your API Key serves as the username for Basic Authentication. To retrieve it:

1. Log in to the Logics Dashboard
2. Navigate to Security → API Key
3. Review the available API keys
4. Select an appropriate key based on your needs — GET permissions for read operations, POST permissions for write operations

Important: Ensure your selected API Key has the necessary permissions for your intended operations.

2. Getting Your Secret Token (Password)

Your Secret Token serves as the password for Basic Authentication. To generate it:

1. Navigate to Settings → Integrations
2. Click Generate Token
3. Copy and securely store the generated token

Security Note: Treat your Secret Token like a password. Store it securely and never share it publicly.

Using Your Credentials

Include both credentials in the Basic Authentication header of every request:

```
Authorization: Basic base64("<API Key>:<Secret Token>")
```

```
Username: Your API Key
```

```
Password: Your Secret Token
```

Best Practices

- Use API Keys with minimal required permissions
- Rotate your Secret Tokens regularly
- Never expose credentials in client-side code
- Store credentials in environment variables or secure key management systems

Need Help?

If you encounter authentication issues:

- Verify your API Key has the correct permissions
- Ensure your Secret Token is current and correctly copied
- Check that both credentials are properly formatted in your request headers

Appointment

4 endpoints · Scopes used: **case.read** / **case.write**

GET Get Available Slots

Get available time slots for an agent on a given date.

<https://valortax.logiqsapi.com/publicapi/V4/Appointment/GetAvailableSlots>

Required scope: **case.read**

Header Parameters

Parameter	Type	Description	Required
email	String	Email of the agent	Required
date	Date	Date on which the slot has to be checked. Format: mm/dd/yyyy	Required
timezone	String	Current timezone (e.g. PST, EST, CST)	Optional
timeSlot	String	Slot length in minutes. Default is 30. Value can be 30/60/90	Optional

Example Response (200)

```
{
  "Success": true,
  "data": [
    "Available time slots in CST",
    "8:00 AM-8:30 AM",
    "8:30 AM-9:00 AM",
    "9:00 AM-9:30 AM",
    "9:30 AM-10:00 AM",
    "10:00 AM-10:30 AM",
    "10:30 AM-11:00 AM",
    "11:00 AM-11:30 AM",
    "11:30 AM-12:00 PM",
    "12:00 PM-12:30 PM"
  ],
  "message": "Data retrieved successfully.",
  "StatusCode": 200,
  "Timestamp": "2025-05-29T09:03:39.0291509Z"
}
```

Response Codes

Status	Meaning
200	Returns a JSON array of available time slots.
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: case.read
500	Internal Server Error. Please try again later or contact support.

POST Book Appointment

Book an appointment with an agent.

<https://valortax.logiqsapi.com/publicapi/V4/Appointment/BookAppointment>

Required scope: **case.write**

Body Request

Parameter	Type	Description	Required
AgentEmail	String	Email of agent to book appointment with	Required
Date	DateTime	Date/time to book. Format: MM/dd/yyyy HH:mm AM/PM	Required
CaseID	String	Case to which the appointment is booked	Required
Comments	String	Description regarding the appointment	Optional
TimeZone	String	Current timezone (e.g. PST, EST, CST)	Optional
TimeSlot	String	Slot length in minutes. Default is 30. Value can be 30/60/90	Optional
Subject	String	Subject	Optional
EventTypeID	Integer	Event type, corresponds to TaskCategoryID	Optional

Example Response (200)

```
{
  "status": "success",
  "data": "null",
  "message": "Your appointment has been booked with James Iddings on 11/16/2023 at 2:30 PM to 3:00 PM.",
  "StatusCode": 200,
  "Timestamp": "2025-05-01T08:15:23.1234567Z"
}
```

Response Codes

Status	Meaning
200	Returns a response containing the appointment details.
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: case.write
500	Internal Server Error. Please try again later or contact support.

POST Update Appointment

Update an existing appointment with an agent.

<https://valortax.logiqsapi.com/publicapi/V4/Appointment/UpdateAppointment>

Required scope: **case.write**

Body Request

Parameter	Type	Description	Required
TaskID	Integer	TaskID of the appointment to update	Required
AgentEmail	String	Email of agent to reassign the appointment to	Optional
Date	DateTime	Updated date/time. Format: MM/dd/yyyy HH:mm AM/PM	Optional
Comments	String	Description regarding the appointment	Optional
TimeZone	String	Current timezone (e.g. PST, EST, CST)	Optional
TimeSlot	String	Slot length in minutes. Default is 30. Value can be 30/60/90	Optional
Subject	String	Subject	Optional
EventTypeID	Integer	Event type, corresponds to TaskCategoryID	Optional

Example Response (200)

```
{
  "status": "success",
  "data": "",
  "message": "Appointment 1122 has updated successfully.",
  "StatusCode": 200,
  "Timestamp": "2025-05-01T08:15:23.1234567Z"
}
```

Response Codes

Status	Meaning
200	Returns a response containing the appointment details.
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: case.write
500	Internal Server Error. Please try again later or contact support.

GET Get Settlement Officer Email

Get the settlement officer's email for a case.

<https://valortax.logiqsapi.com/publicapi/V4/Appointment/GetSetOfficerEmail>

Required scope: **case.read**

Header Parameters

Parameter	Type	Description	Required
CaseID	String	Case for which the settlement officer's email is retrieved	Required

Example Response (200)

```
{
```

```
"status": "success",
"data": "Settlement Officer: none@irslogics.com",
"message": "Data retrieved successfully.",
"StatusCode": 200,
"Timestamp": "2025-05-02T12:47:59.9876543Z"
}
```

Response Codes

Status	Meaning
200	Returns the settlement officer's email.
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: case.read
500	Internal Server Error. Please try again later or contact support.

Billing

10 endpoints · Scopes used: **payments.read** / **payments.write**

GET Get Case Account

Gets a list of case accounts for the provided CaseID.

<https://valortax.logiqsapi.com/publicapi/V4/Billing/CaseAccount>

Required scope: **payments.read**

Note: The property list in the data node grows over time — handle it defensively.

Header Parameters

Parameter	Type	Description	Required
CaseID	Integer	ID of the case for which accounts are to be fetched	Required

Example Response (200)

```
{
  "Success": true,
  "data": [
    {
      "CaseAccountID": 62252,
      "AccountType": 2,
      "PrimaryAccount": true,
      "BankName": "",
      "BankRoutingNo": "",
      "BankAccountNo": "**** * 1111",
      "CCType": 1,
      "CCNo": "**** * 1111",
      "CCExpDate": "102024",
      "CCSecurityNo": "",
      "BillingAddressSameAsCase": false,
      "Address": null,
      "AptNo": null,
      "City": null,
      "State": "",
      "Zip": "",
      "NameOnAccount": "",
      "CaseID": 284514,
      "PhoneNo": "",
      "EmailID": "",
      "CreatedDate": "2021-03-05T04:04:23.547",
      "ModifiedDate": "2021-03-05T04:04:23.547"
    }
  ],
  "message": "Data retrieved successfully.",
  "StatusCode": 200,
  "Timestamp": "2025-05-08T11:25:30.5566778Z"
}
```

Response Codes

Status	Meaning
200	Returns the case's accounts (list grows over time).

Status	Meaning
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: payments.read
500	Internal Server Error. Please try again later or contact support.

POST Create Case Account

Creates a case account (credit card or bank account) with default values.

<https://valortax.logicsapi.com/publicapi/V4/Billing/CaseAccount>

Required scope: **payments.write**

Body Request

Parameter	Type	Description	Required
CaseID	Integer	Case to which the account is added	Required
AccountType	Integer	Type of case account	Required
PrimaryAccount	Boolean	Whether this is the primary account	Optional
BankName	String	Name of the bank	Optional
BankRoutingNo	String	Bank routing number	Optional
BankAccountNo	String	Bank account number	Optional
CCType	Integer	Credit card type	Optional
CCNo	String	Credit card number, format xxxxxxxxxxxxxxxx	Optional
CCExpDate	Date	Credit card expiry date, format MMYYYY	Optional
CCSecurityNo	String	Credit card CVV	Optional
BillingAddressSameAsCase	Boolean	Whether billing address matches case address	Optional
State	String	State — must be 2 characters (e.g. 'CA', 'NY')	Optional
City	String	City	Optional
Zip	String	Zip code	Optional
Address	String	Address	Optional
AptNo	String	Apartment number	Optional
NameOnAccount	String	Name on credit card or bank account	Optional
PhoneNo	String	Phone number, format (xxx)xxx-xxxx	Optional
EmailID	String	Email address	Optional

AccountType: Checking = 1, CreditCard = 2, Savings = 3, BusinessChecking = 4

CCType: Visa = 1, MasterCard = 2, AmExp = 3, Discover = 4

Example Response (200)

```
{
  "Success": true,
```

```
{
  "data": { "CaseAccountID": 128346 },
  "message": "Case Account created successfully by User: Kim Danner",
  "StatusCode": 200,
  "Timestamp": "2025-05-11T01:03:27.111111Z"
}
```

Response Codes

Status	Meaning
200	Returns the created CaseAccountID — store it for future reference.
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: payments.write
500	Internal Server Error. Please try again later or contact support.

GET Get Case Payment

Gets a list of case payments for the provided CaseID.

<https://valortax.logiqsapi.com/publicapi/V4/Billing/CasePayment>

Required scope: `payments.read`

Header Parameters

Parameter	Type	Description	Required
CaseID	Integer	ID of the case for which payments are to be fetched	Required

Example Response (200)

```
{
  "Success": true,
  "data": [
    {
      "CasePaymentID": 227072,
      "CaseID": 297271,
      "PaymentTypeID": null,
      "PaidDate": "2021-08-23T00:00:00",
      "CaseAccountID": null,
      "CheckNumber": null,
      "Amount": 100.0000,
      "Comment": "Manual Cash Payment Was Successful.",
      "TransactionID": null,
      "TransactionStatus": "SUCCESS",
      "TransactionComment": null,
      "AuthorizationCode": null,
      "CreatedDate": "2021-08-25T05:58:46.7738667Z",
      "CreatedByUserFullName": "Joseph Christopher",
      "CreatedBy": null,
      "MerchantAccountID": null,
      "CustomerIP": "::1",
      "AccountUsed": null,
      "GatewayRawReponse": null,
      "Balance": 11021.1100,
    }
  ]
}
```

```

    "TagID": 1,
    "TagName": null
  },
  "message": "Data retrieved successfully.",
  "StatusCode": 200,
  "Timestamp": "2025-05-14T15:59:59.4444444Z"
}

```

Response Codes

Status	Meaning
200	Returns the case's payments (list grows over time).
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: payments.read
500	Internal Server Error. Please try again later or contact support.

POST Create Case Payment

Create a case payment with default values.

<https://valortax.logiqsapi.com/publicapi/V4/Billing/CasePayment>

Required scope: **payments.write**

Body Request

Parameter	Type	Description	Required
CaseID	Integer	Case to which payment is added	Required
PaymentTypeID	Integer	Type of case payment	Optional
CaseAccountID	Integer	Case Account ID (defaults to primary account)	Optional
MerchantAccountID	Integer	Merchant Account ID (defaults to primary)	Optional
Amount	Money	Payment amount	Optional
PaidDate	Date	Payment date	Optional
Comment	String	Payment comments	Optional
TagID	Integer	Payment tag ID	Optional
TagName	String	Tag name	Optional
InvoiceIds	String	Invoice ID(s) to apply. Single: "123". Multiple: "111,222,333" (no spaces)	Optional

PaymentTypeID: CreditCard = 1, Checking = 2, Cash = 3, Refund = 4, Offset = 5, ChargeBack = 6, Loan = 8, Loan Offset = 9

PaymentTypeID = 3 only posts a record and does not run a payment.

PaymentTypeID = 1 or 2 charges the credit card or bank account via the default merchant account provider.

Example Response (200)

```
{
  "Success": true,
  "data": { "CasePaymentID": 128346 },
  "message": "Case Payment created successfully by User: Thomas Duff",
  "StatusCode": 200,
  "Timestamp": "2025-05-22T12:12:12.3453453Z"
}
```

Response Codes

Status	Meaning
200	Returns the created CasePaymentID — store it for future reference.
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: payments.write
500	Internal Server Error. Please try again later or contact support.

GET Get Case Invoice

Gets a list of case invoices for the provided CaseID.

<https://valortax.logiqsapi.com/publicapi/V4/Billing/CaseInvoice>

Required scope: **payments.read**

Header Parameters

Parameter	Type	Description	Required
CaseID	Integer	ID of the case for which invoices are to be fetched	Required

Example Response (200)

```
{
  "Success": true,
  "data": [
    {
      "CaseInvoiceID": 163964,
      "CaseID": 297269,
      "Date": "2021-07-20T00:00:00",
      "InvoiceTypeID": 7,
      "InvoiceTypeName": null,
      "UnitPrice": 23.0000,
      "Quantity": 1,
      "Description": "",
      "CreatedBy": 4133,
      "CreatedByUserFullName": null,
      "CreatedDate": "2021-07-20T00:00:00",
      "ModifiedDate": null,
      "ModifiedBy": null,
      "ModifiedByUserFullName": null,
      "TagID": 0,
      "TagName": null
    }
  ],
}
```

```

{
  "message": "Data retrieved successfully.",
  "StatusCode": 200,
  "Timestamp": "2025-05-27T22:22:22.8908908Z"
}

```

Response Codes

Status	Meaning
200	Returns the case's invoices (list grows over time).
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: payments.read
500	Internal Server Error. Please try again later or contact support.

POST Create Case Invoice

Create a case invoice with default values.

<https://valortax.logiqsapi.com/publicapi/V4/Billing/CaseInvoice>

Required scope: **payments.write**

Body Request

Parameter	Type	Description	Required
CaseID	Integer	Case to which the invoice is added	Required
Quantity	Integer	Total items	Required
UnitPrice	Money	Price per item	Required
InvoiceTypeID	Integer	Type of case invoice	Optional
Date	Date	Invoice date	Optional
InvoiceTypeName	String	Invoice type name	Optional
Description	String	Invoice description	Optional
TagID	Integer	Payment tag ID	Optional
TagName	String	Tag name	Optional
RelatedInvoiceId	Integer	Invoice ID a discount is applied to. Required for discount-related invoice types.	Conditional

Example Response (200)

```

{
  "Success": true,
  "data": { "CaseInvoiceID": 128346 },
  "message": "Case Payment created successfully by User: Rochelle Cole",
  "StatusCode": 200,
  "Timestamp": "2025-05-30T00:00:00.0000000Z"
}

```

Response Codes

Status	Meaning
200	Returns the created CaseInvoiceID — store it for future reference.
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: payments.write
500	Internal Server Error. Please try again later or contact support.

GET Get Case Amortization

Gets a list of case amortization schedules for the provided CaseID.

<https://valortax.logiqsapi.com/publicapi/V4/Billing/CaseAmortization>

Required scope: **payments.read**

Header Parameters

Parameter	Type	Description	Required
CaseID	Integer	ID of the case for which amortizations are to be fetched	Required

Example Response (200)

```
{
  "Success": true,
  "data": [
    {
      "CaseAmortizationID": 347307,
      "CaseID": 297269,
      "Amount": 1.0000,
      "ScheduledDate": "2021-07-24T00:00:00",
      "CreatedBy": 4133,
      "CreatedByUserFullName": "Shreha Didwania",
      "AutopayStatusID": 1,
      "AutoSchedulerList": null
    }
  ],
  "message": "Data retrieved successfully.",
  "StatusCode": 200,
  "Timestamp": "2025-05-25T09:09:09.6786786Z"
}
```

Response Codes

Status	Meaning
200	Returns the case's amortization schedule (list grows over time).
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: payments.read
500	Internal Server Error. Please try again later or contact support.

POST Create Case Amortization

Create a case amortization schedule entry with default values.

<https://valortax.logiqsapi.com/publicapi/V4/Billing/CaseAmortization>

Required scope: **payments.write**

Body Request

Parameter	Type	Description	Required
CaseID	Integer	Case to which the amortization is added	Required
Amount	Money	Amount	Required
ScheduledDate	Date	Amortization date	Required

Example Response (200)

```
{
  "Success": true,
  "data": { "CaseAmortizationID": 128346 },
  "message": "",
  "StatusCode": 200,
  "Timestamp": "2025-05-28T05:05:05.9019019Z"
}
```

Response Codes

Status	Meaning
200	Returns the created CaseAmortizationID — store it for future reference.
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: payments.write
500	Internal Server Error. Please try again later or contact support.

POST Update Case Amortization

Update an existing case amortization (payment schedule). Supports single and bulk updates.

<https://valortax.logiqsapi.com/publicapi/V4/Billing/UpdateCaseAmortization>

Required scope: **payments.write**

Note: Bulk Update: pass CaseID plus an AutoSchedulerList array, each item containing CaseAmortizationID (required) and Amount and/or ScheduledDate (at least one required). Example: { "CaseID": 349786, "AutoSchedulerList": [{ "CaseAmortizationID": 345355, "Amount": 400.00, "ScheduledDate": "01/04/2026" }] }

Body Request — Single Update

Parameter	Type	Description	Required
CaseID	Integer	Case to which the amortization belongs	Required
CaseAmortizationID	Integer	ID of the amortization record to update	Required

Parameter	Type	Description	Required
Amount	Money	Updated amount. At least one of Amount / ScheduledDate is required.	Conditional
ScheduledDate	Date	Updated date, format mm/dd/yyyy. At least one of Amount / ScheduledDate is required.	Conditional

Example Response (200)

```
Single update:
{
  "Success": true,
  "data": { "CaseAmortizationID": 342607 },
  "message": "Case Amortization updated successfully by User: Thomas Duff",
  "StatusCode": 200,
  "Timestamp": "2026-04-28T10:30:45.1234567Z"
}

Bulk update:
{
  "Success": true,
  "data": { "UpdatedCaseAmortizationIDs": "345353,345354,345355" },
  "message": "Case Amortization updated successfully by User: Thomas Duff",
  "StatusCode": 200,
  "Timestamp": "2026-04-28T10:35:12.9876543Z"
}
```

Response Codes

Status	Meaning
200	Single update returns the updated CaseAmortizationID; bulk update returns a comma-separated list of updated IDs.
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: payments.write
500	Internal Server Error. Please try again later or contact support.

GET Get Case Billing Summary

Get the case billing summary for the provided CaseID.

<https://valortax.logiqsapi.com/publicapi/V4/Billing/CaseBillingsummary>

Required scope: **payments.read**

Header Parameters

Parameter	Type	Description	Required
CaseID	Integer	ID of the case for which the billing summary is fetched	Required

Example Response (200)

```
{
  "Success": true,
  "data": {
    "TotalFees": 2000.00,
    "PaidAmount": 600.00,
    "PaidPercentage": "30.00%",
    "Balance": 1400.00,
    "AmountDue": 1400.00,
    "DueDate": "04/06/2023",
    "PastDue": 900.00
  },
  "message": "Data retrieved successfully.",
  "StatusCode": 200,
  "Timestamp": "2025-05-22T12:12:12.3453453Z"
}
```

Response Codes

Status	Meaning
200	Returns a summary of case billing (property list grows over time).
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: payments.read
500	Internal Server Error. Please try again later or contact support.

Case

6 endpoints · Scopes used: **case.read** / **case.write**

GET Get Case

Get case values.

<https://valortax.logiqsapi.com/publicapi/V4/Case/CaseInfo>

Required scope: **case.read**

Header Parameters

Parameter	Type	Description	Required
CaseID	Integer	ID of the case to fetch	Required
details	String	Comma-separated field names added to the current Case object. Accepted values: setofficerid, attorneyid, casemanagerid, ctecid, caseworkerid, taxpreparerid, assignment1id, enrolledagentid, cpaid	Optional
udf	String	UDF value	Optional

Example Response (200)

```
{
  "Success": true,
  "data": {
    "CaseID": 128346,
    "FirstName": "first name",
    "LastName": "last name",
    "DOB": "07/24/1995",
    "Status": 1,
    "SaleDate": null,
    "CellPhone": "",
    "HomePhone": "",
    "WorkPhone": "",
    "Email": "test@test.com",
    "City": "",
    "State": "",
    "Zip": "",
    "Address": "",
    "AptNo": "",
    "MaritalStatus": "",
    "BusinessName": "",
    "BusinessType": "",
    "BusinessAddress": "",
    "TaxLiability": "",
    "ServiceID": 89,
    "ServiceID2": 62,
    "ServiceID3": 29,
    "ServiceID4": 2,
    "ServiceID5": 4,
    "ServiceID6": 25
  },
  "message": "Data retrieved successfully.",
  "StatusCode": 200,
  "Timestamp": "2025-05-13T15:33:03.4444444Z"
}
```

Response Codes

Status	Meaning
200	Returns the case's core properties (list grows over time).
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: case.read
500	Internal Server Error. Please try again later or contact support.

POST Create Case

Creates a case with default values.

<https://valortax.logiqsapi.com/publicapi/V4/Case/CaseFile>

Required scope: **case.write**

Body Request

Parameter	Type	Description	Required
LastName	String	Last name	Required
StatusID	Integer	Status to assign to the case	Optional
ProductID	Integer	Product the case belongs to (e.g. 1 for TR Case)	Optional
FirstName	String	First name	Optional
Email	String	Email	Optional
CellPhone	String	Cell phone, format (xxx)xxx-xxxx	Optional
WorkPhone	String	Work phone, format (xxx)xxx-xxxx	Optional
HomePhone	String	Home phone, format (xxx)xxx-xxxx	Optional
State	String	State — must be 2 characters (e.g. 'CA', 'NY')	Optional
City	String	City	Optional
Zip	String	Zip code	Optional
Address	String	Address	Optional
AptNo	String	Apartment number	Optional
SSN	String	SSN, format xxx-xx-xxxx	Optional
Marital_Status	String	single married filing jointly married filing separately head of household qualifying widow(er)	Optional
TAX_RELIEF_TAX_AGENCY	String	Agency for tax support. Comma-separated. Accepted: FEDERAL, STATE	Optional
TAX_RELIEF_TAX_AMOUNT	String	Tax relief amount requested by the client	Optional
Opener	String	Opener	Optional
CPA/Attorney/EA	String	CPA / Attorney / EA	Optional
Set. Officer	String	Settlement officer	Optional
Tax Prep Coordinator	String	Tax prep coordinator	Optional
Language	String	Language	Optional

Parameter	Type	Description	Required
Notes	String	Notes	Optional
UDF	Array	UDF fields, e.g. [{"UDFName1": "UDFValue1"}]	Optional
DistributionId	Integer	Lead distribution ID	Optional
TaxProblem	String	See accepted values below	Optional
TAX_RELIEF_TAX_TYPE	String	Personal Business Personal and Business Payroll and Other	Optional
DOB	DateTime	Date of birth, format MM/dd/yyyy	Optional
SourceName	String	Source name	Optional
BusinessType	String	sole proprietorship partnership llp llc (single) llc (multiple) s corp c corp trust	Optional
BusinessName	String	Business name	Optional
BusinessAddress	String	Business address	Optional
BusinessAptNo	String	Business apartment number	Optional
BusinessCity	String	Business city	Optional
BusinessState	String	Business state — 2 characters	Optional
BusinessZip	String	Business zip code	Optional
EIN	String	Employer ID number	Optional
SMSPermit	Bool	Opt-in for SMS	Optional
DuplicateCheck	String	Not posted into Logics — checks for duplicates using comma-separated fields: FirstName, LastName, MiddleName, DOB, Email, SSN, CellPhone, WorkPhone, HomePhone, BusinessName, EIN, Phones	Optional

TaxProblem accepted values: ACCOUNTING, ASSETS_SEIZED, BANK_ACCOUNT_LEVY, CANT_PAY_UNPAID_TAXES, INNOCENT_SPOUSE, License_Suspension_Revocation, LIEN_FILED, Passport_Suspension_Revocation, RECEIVED_AUDIT_NOTICE, UNPAID_PENALTIES_AND_INTEREST, WAGE_GARNISHMENT, RECEIVED_IRS_LETTER, ISSUE_CLAIMING_DEPENDENTS, ID_THEFT, IRS_REFUND, OTHER

Example Response (200)

```
{
  "Success": true,
  "data": { "CaseID": 344685 },
  "message": "Case created successfully by User: Frankie Smith",
  "StatusCode": 200,
  "Timestamp": "2025-05-16T11:18:18.777777Z"
}
```

Response Codes

Status	Meaning
200	Returns the created CaseID — store it for future reference.
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: case.write
500	Internal Server Error. Please try again later or contact support.

POST Update Case

Update a case with new values.

<https://valortax.logiqsapi.com/publicapi/V4/UpdateCase/UpdateCase>

Required scope: **case.write**

Note: Either CaseID or SearchPhone is required — provide at least one.

Body Request

Parameter	Type	Description	Required
CaseID	Integer	Case to update	Required
SearchPhone	String	Search phone number, format (xxx)xxx-xxxx	Required
SetOfficerID	Integer	Settlement officer	Optional
CasemanagerID	Integer	Case manager	Optional
CaseworkerID	Integer	Case worker	Optional
AttorneyID	Integer	Attorney	Optional
CTECID	Integer	Opener ID / CTEC	Optional
TaxpreparerID	Integer	Tax preparer	Optional
Assignment1ID	Integer	Assignment 1	Optional
EnrolledAgentID	Integer	Enrolled agent	Optional
HomePhone	String	Home phone, format (xxx)xxx-xxxx	Optional
CellPhone	String	Cell phone, format (xxx)xxx-xxxx	Optional
WorkPhone	String	Work phone, format (xxx)xxx-xxxx	Optional
StatusID	Integer	Status to assign to the case	Optional
TeamID	Integer	Team to assign to the case	Optional
FirstName	String	First name	Optional
MiddleName	String	Middle name	Optional
LastName	String	Last name	Optional
TaxAmount	Integer	Tax liability	Optional
DistributionId	Integer	Lead distribution ID	Optional
AptNo	String	Apartment number	Optional
Address	String	Address	Optional
State	String	State — 2 characters	Optional
City	String	City	Optional
Zip	String	Zip code	Optional
SSN	String	SSN, format xxx-xx-xxxx	Optional
DOB	DateTime	Date of birth, format MM/dd/yyyy	Optional
SourceID	Integer	Source	Optional
Email	String	Email	Optional

Parameter	Type	Description	Required
BusinessName	String	Business name	Optional
BusinessAddress	String	Business address	Optional
BusinessAptNo	String	Business apartment number	Optional
BusinessCity	String	Business city	Optional
BusinessState	String	Business state — 2 characters	Optional
BusinessZip	String	Business zip code	Optional
EmploymentTypeID	Integer	Employment type	Optional
BusinessOwnershipType	Integer	N/A (0), sole proprietorship (1), partnership (2), llp (3), llc single (4), llc multiple (5), s corp (6), c corp (7), trust (8)	Optional
EmployerIDNo	String	Business employer ID number	Optional
SpouseFirstName	String	Spouse first name	Optional
SpouseLastName	String	Spouse last name	Optional
SpouseMaidenName	String	Spouse maiden name	Optional
MaritalStatus	Integer	single (0), married filing jointly (1), married filing separately (3), head of household (4), qualifying widow(er) (5)	Optional
SpouseDOB	DateTime	Spouse date of birth, format MM/dd/yyyy	Optional
SpouseDOM	DateTime	Spouse date of marriage, format MM/dd/yyyy	Optional
SpouseEmail	String	Spouse email	Optional
SpouseSSN	String	Spouse SSN, format xxx-xx-xxxx	Optional
ServiceID	Integer	Service 1	Optional
ServiceID2	Integer	Service 2	Optional
ServiceID3	Integer	Service 3	Optional
ServiceID4	Integer	Service 4	Optional
ServiceID5	Integer	Service 5	Optional
ServiceID6	Integer	Service 6	Optional
ServiceOther	String	Other service	Optional
ServiceDetailIDs	String	Service detail IDs, e.g. "273,274"	Optional
UDF	Array	UDF fields, e.g. "UDF": [{"udf232": "Approved", "udf231": 295}]	Optional
TaxType	String	Personal Business Personal and Business Payroll Other	Optional
TaxProblem	String	See accepted values below	Optional

TaxProblem accepted values: ACCOUNTING, ASSETS_SEIZED, BANK_ACCOUNT_LEVY, CANT_PAY_UNPAID_TAXES, INNOCENT_SPOUSE, License_Suspension_Revocation, LIEN_FILED, Passport_Suspension_Revocation, RECEIVED_AUDIT_NOTICE, UNPAID_PENALTIES_AND_INTEREST, WAGE_GARNISHMENT, RECEIVED_IRS_LETTER, ISSUE_CLAIMING_DEPENDENTS, ID_THEFT, IRS_REFUND, OTHER

Example Response (200)

```
{
  "Success": true,
  "data": { "CaseID": 344689 },
  "message": "Case updated successfully by User: George Remy",
  "StatusCode": 200,
  "Timestamp": "2025-05-20T16:16:16.2342342Z"
}
```

Response Codes

Status	Meaning
200	Returns case details with update status and user information.
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: case.write
500	Internal Server Error. Please try again later or contact support.

GET Get Cases By Status

Get case IDs for a given status.

<https://valortax.logiqsapi.com/publicapi/V4/Case/GetCasesByStatus>

Required scope: **case.read**

Header Parameters

Parameter	Type	Description	Required
StatusID	Integer	StatusID value to retrieve all associated cases	Required
orderByCreateDate	Boolean	Sorts results by CaseID when true. Default false (sorted by ModifiedDate)	Optional
page	Integer	Page number of results to retrieve. Default 1	Optional

Example Response (200)

```
{
  "Success": true,
  "data": [344683, 344667, 344655],
  "message": "Data retrieved successfully.",
  "StatusCode": 200,
  "Timestamp": "2025-05-22T12:12:12.4564564Z"
}
```

Response Codes

Status	Meaning
200	Returns matching case IDs.
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: case.read

Status	Meaning
500	Internal Server Error. Please try again later or contact support.

POST Stop SMS Permission

Stop SMS permission for the provided CaseID.

<https://valortax.logiqsapi.com/publicapi/V4/Case/StopSMS>

Required scope: **case.write**

Body Parameters

Parameter	Type	Description	Required
CaseID	Integer	ID of the case for which SMS permission is stopped	Required

Example Response (200)

```
{
  "Success": true,
  "data": "null",
  "message": "SMS successfully stopped by User: ",
  "StatusCode": 200,
  "Timestamp": "2025-05-25T09:09:09.7897897Z"
}
```

Response Codes

Status	Meaning
200	Returns confirmation that SMS was stopped.
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: case.write
500	Internal Server Error. Please try again later or contact support.

GET Get Case Status Information

Gets case status information for a given StatusID.

<https://valortax.logiqsapi.com/publicapi/V4/Case/CaseStatusInfo>

Required scope: **case.read**

Header Parameters

Parameter	Type	Description	Required
StatusID	Integer	ID of the status of a particular case	Required

Example Response (200)

```
{
  "Success": true,
  "data": [
    {
      "StatusID": 355,
      "StatusName": "Status 1",
      "CPStatus": null,
      "StatusDesc": "Edit Description",
      "OrderNo": null,
      "FolderID": 61,
      "IsDefault": false,
      "ProductID": null,
      "FolderName": "Initial Payment Default",
      "EnableFolderApproval": null,
      "StageID": null,
      "NextWorkFlow": "Next Work flow of the status"
    }
  ],
  "message": "Data retrieved successfully.",
  "StatusCode": 200,
  "Timestamp": "2025-05-10T22:10:15.111111Z"
}
```

Response Codes

Status	Meaning
200	Returns the status details (list grows over time).
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: case.read
500	Internal Server Error. Please try again later or contact support.

Case Activity

3 endpoints · Scopes used: **case.read** / **activity.write**

GET Get an Activity

Gets all activities on a case.

<https://valortax.logiqsapi.com/publicapi/V4/CaseActivity/Activity>

Required scope: **case.read**

Header Parameters

Parameter	Type	Description	Required
CaseID	Integer	ID of the case whose activities are fetched	Required

Example Response (200)

```
{
  "Success": true,
  "data": {
    "CaseID": 264001,
    "ActivityID": 8172803,
    "Subject": "Assigned to SO: Case Analyst",
    "Comment": "",
    "Popup": null,
    "Pin": null,
    "ActivityType": "General",
    "CreatedDate": "2015-03-06T17:45:33.233"
  },
  "message": "Data retrieved successfully.",
  "StatusCode": 200,
  "Timestamp": "2025-05-29T13:13:13.8765432Z"
}
```

Response Codes

Status	Meaning
200	Returns the case's activities (list grows over time).
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: case.read
500	Internal Server Error. Please try again later or contact support.

POST Create an Activity

Create an activity with default values.

<https://valortax.logiqsapi.com/publicapi/V4/CaseActivity/Activity>

Required scope: **activity.write**

Body Request

Parameter	Type	Description	Required
CaseID	Integer	Case to which the activity is added	Required
ActivityType	String	Type of activity to add to the case	Required
Subject	String	Activity subject	Required
Comment	String	Activity comment	Optional
Popup	Boolean	Whether the activity pops up	Optional
Pin	Boolean	Whether the activity is pinned	Optional

Example Response (200)

```
{
  "Success": true,
  "data": { "ActivityID": 9164821 },
  "message": "Case activity created successfully created by User: Hazel Smith",
  "StatusCode": 200,
  "Timestamp": "2025-05-24T06:06:06.6786786Z"
}
```

Response Codes

Status	Meaning
200	Returns the created CaseActivity record along with user details.
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: activity.write
500	Internal Server Error. Please try again later or contact support.

POST Update an Activity

Update an existing activity.

<https://valortax.logiqsapi.com/publicapi/V4/CaseActivity/Activity>

Required scope: **activity.write**

Body Request

Parameter	Type	Description	Required
ActivityID	Integer	Activity to update	Required
CaseID	Integer	Case the activity belongs to	Required
Comment	String	Activity comment	Optional
Popup	Boolean	Whether the activity pops up	Optional
Pin	Boolean	Whether the activity is pinned	Optional

Example Response (200)

```
{
```

```
"Success": true,  
"data": { "ActivityID": 878787 },  
"message": "Case activity Updated successfully created by User: Anita Bonner",  
"StatusCode": 200,  
"Timestamp": "2025-05-29T13:13:13.8765432Z"  
}
```

Response Codes

Status	Meaning
200	Returns the updated CaseActivity record along with user details.
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: activity.write
500	Internal Server Error. Please try again later or contact support.

Documents

1 endpoint · Scopes used: **case.write**

POST Create Case Document

Uploads a file to a specific case as a Case Document. This endpoint accepts multipart/form-data.

<https://valortax.logicsapi.com/publicapi/V4/Documents/CaseDocument>

Required scope: **case.write**

Note: Maximum uploaded file size is 6 MB per file — compress or optimize PDFs beforehand.

Body Parameters

Parameter	Type	Description	Required
CaseID	Integer	Case to which the document is added	Required
Comment	String	Comment to add to the document	Optional
FileCategoryID	Integer	ID of the file category	Optional
File	File (form-data)	The file to upload	Required

Example Response (200)

```
{
  "Success": true,
  "data": { "CaseDocumentID": 128346 },
  "message": "File uploaded successfully by User: Pedro Medina",
  "StatusCode": 200,
  "Timestamp": "2025-05-18T04:20:10.99999999Z"
}
```

Response Codes

Status	Meaning
200	Returns case document details with upload status and user information.
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: case.write
500	Internal Server Error. Please try again later or contact support.

Fax

1 endpoint · Scopes used: **fax.write**

POST Send Fax

Send a fax with default values. This endpoint accepts multipart/form-data.

<https://valortax.logiqsapi.com/publicapi/V4/Fax/SendFax>

Required scope: **fax.write**

Body Parameters

Parameter	Type	Description	Required
CaseID	Integer	Case to which the fax is sent	Required
faxNumber	String	Fax number	Required
faxMessage	String	Fax message	Optional
contentSummary	String	Fax content summary	Optional

Example Response (200)

```
{
  "Success": true,
  "data": null,
  "message": "Fax initiated: 79ca211a-88e8 by User: Sam Peterson",
  "StatusCode": 200,
  "Timestamp": "2025-05-09T19:44:01.6543210Z"
}
```

Response Codes

Status	Meaning
200	Returns confirmation that the fax was initiated.
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: fax.write
500	Internal Server Error. Please try again later or contact support.

Find

3 endpoints · Scopes used: **case.read**

GET Find Case By Phone

Gets case details using a phone number.

<https://valortax.logiqsapi.com/publicapi/V4/Find/FindCaseByPhone>

Required scope: **case.read**

Header Parameters

Parameter	Type	Description	Required
phone	String	Phone number of the case to fetch details for	Required

Example Response (200)

```
{
  "Success": true,
  "data": [
    {
      "CaseID": 344624,
      "CreatedDate": "2023-04-21T06:52:18",
      "FirstName": "Steve",
      "LastName": "Joe",
      "StatusID": 191,
      "SaleDate": "2025-01-09T00:00:00",
      "CellPhone": "234234232",
      "HomePhone": "(121)121-2121",
      "WorkPhone": "934543554",
      "Email": "steve1234@hotmail.com",
      "City": "city details",
      "State": "NY",
      "Zip": "66666-6666",
      "Address": "",
      "AptNo": "",
      "Language": "",
      "TaxAmount": 0.0000,
      "TeamID": 0
    }
  ],
  "message": "Data retrieved successfully.",
  "StatusCode": 200,
  "Timestamp": "2025-05-17T23:45:00.8888888Z"
}
```

Response Codes

Status	Meaning
200	Returns matching cases with details (list grows over time).
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: case.read
500	Internal Server Error. Please try again later or contact support.

GET Find Case By Last Name & Phone

Gets case details using a phone number and last name.

<https://valortax.logiqsapi.com/publicapi/V4/Find/FindCase>

Required scope: **case.read**

Header Parameters

Parameter	Type	Description	Required
lastName	String	Last name for fetching the case details	Required
phone	String	Phone number for fetching the case details	Required

Example Response (200)

```
{
  "Success": true,
  "data": [
    {
      "CaseID": 344624,
      "CreatedDate": "2023-04-21T06:52:18",
      "FirstName": "Steve",
      "LastName": "Joe",
      "StatusID": 191,
      "SaleDate": "2025-01-09T00:00:00",
      "CellPhone": "234234232",
      "HomePhone": "(121)121-2121",
      "WorkPhone": "934543554",
      "Email": "steve1234@hotmail.com",
      "City": "city details",
      "State": "NY",
      "Zip": "66666-6666",
      "Address": "",
      "AptNo": "",
      "Language": "",
      "TaxAmount": 0.0000,
      "TeamID": 0
    }
  ],
  "message": "Data retrieved successfully.",
  "StatusCode": 200,
  "Timestamp": "2025-05-13T15:33:03.4444444Z"
}
```

Response Codes

Status	Meaning
200	Returns matching cases with details (list grows over time).
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: case.read
500	Internal Server Error. Please try again later or contact support.

GET Find Case By Email

Find case details using an email address.

<https://valortax.logiqsapi.com/publicapi/V4/Find/FindCaseByEmail>

Required scope: **case.read**

Header Parameters

Parameter	Type	Description	Required
email	String	Email of the case to fetch details for	Required

Example Response (200)

```
{
  "Success": true,
  "data": [
    {
      "CaseID": 344624,
      "CreatedDate": "2023-04-21T06:52:18",
      "FirstName": "Steve",
      "LastName": "Joe",
      "StatusID": 191,
      "SaleDate": "2025-01-09T00:00:00",
      "CellPhone": "234234232",
      "HomePhone": "(121)121-2121",
      "WorkPhone": "934543554",
      "Email": "steve1234@hotmail.com",
      "City": "city details",
      "State": "NY",
      "Zip": "66666-6666",
      "Address": "",
      "AptNo": "",
      "Language": "",
      "TaxAmount": 0.0000,
      "TeamID": 0
    }
  ],
  "message": "Data retrieved successfully.",
  "StatusCode": 200,
  "Timestamp": "2025-05-13T15:33:03.4444444Z"
}
```

Response Codes

Status	Meaning
200	Returns matching cases with details (list grows over time).
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: case.read
500	Internal Server Error. Please try again later or contact support.

Report

1 endpoint · Scopes used: **reports.activityreport.read**

POST Get Activity Report

Gets an activity report for a time period. The report is emailed to the address supplied.

<https://valortax.logiqsapi.com/publicapi/V4/Report/ActivityReport>

Required scope: **reports.activityreport.read**

Body Request

Parameter	Type	Description	Required
StartDate	Date	Start date	Required
EndDate	Date	End date	Required
ReportName	String	Must be set to 'ActivityReport'	Required
Email	String	Email address the report is sent to	Required

Example Response (200)

```
{
  "Success": true,
  "data": {
    "CaseID": 344625,
    "ClientName": "Irene Flores",
    "Type": "Document sent",
    "ActivitySubject": "subject",
    "Created": "01/21/2021 6:24:00 PM",
    "CreatedBy": "Logics Support",
    "TaskOrActivity": "Activity",
    "LastModifiedDate": "01/21/2021 6:24:00 PM",
    "LastModifiedBy": "Affiliate Self"
  },
  "message": "Data exported successfully.",
  "StatusCode": 200,
  "Timestamp": "2025-05-04T21:03:39.0291509Z"
}
```

Response Codes

Status	Meaning
200	Returns the report; the same report is emailed to the address supplied.
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: reports.activityreport.read
500	Internal Server Error. Please try again later or contact support.

Services

1 endpoint · Scopes used: **case.read**

GET Get Service Details

Get service details by IDs.

<https://valortax.logiqsapi.com/publicapi/V4/Services/GetServiceDetails>

Required scope: **case.read**

Header Parameters

Parameter	Type	Description	Required
caseID	Integer	ID of the case for which services are fetched	Required
serviceIds	String	Comma-separated service IDs to fetch details for, e.g. "12,44,11"	Optional

Example Response (200)

```
{
  "Success": true,
  "data": [
    {
      "ServiceId": 78,
      "Name": "Service 1",
      "ServiceDetails": [
        {
          "Id": 27,
          "Name": "ServiceDetailsName",
          "Description": "Service Description"
        }
      ]
    }
  ],
  "message": "Data retrieved successfully.",
  "StatusCode": 200,
  "Timestamp": "2025-05-01T08:15:23.1234567Z"
}
```

Response Codes

Status	Meaning
200	Returns services with details (list grows over time).
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: case.read
500	Internal Server Error. Please try again later or contact support.

Task

3 endpoints · Scopes used: **task.read** / **task.write**

GET Get a Task or Event

Gets a list of tasks/events for the provided CaseID.

<https://valortax.logiqsapi.com/publicapi/V4/Task/Task>

Required scope: **task.read**

Header Parameters

Parameter	Type	Description	Required
CaseID	Integer	ID of the case for which tasks/events are fetched	Required

Example Response (200)

```
{
  "Success": true,
  "data": [
    {
      "TaskID": 577642,
      "CreateBy": 2127,
      "CreatedByName": "Saumendra P",
      "DueDate": "2020-11-09T00:00:00",
      "PriorityID": 0,
      "CreateDate": "2020-11-09T12:45:42.75",
      "CaseID": 288599,
      "StatusID": 0,
      "Subject": "test1",
      "Comments": null,
      "Reminder": null,
      "ModifiedDate": "2020-11-09T12:46:13.027",
      "ModifiedBy": 2127,
      "Deleted": false,
      "TaskType": 1,
      "EndDate": null,
      "LastReminded": null,
      "Location": null,
      "AllDayEvent": null,
      "TaskCategoryID": null,
      "TaskCategoryName": null,
      "UserID": null,
      "Users": [
        { "UserID": 357, "FullName": "A William" }
      ]
    }
  ],
  "message": "Data retrieved successfully.",
  "StatusCode": 200,
  "Timestamp": "2025-05-05T17:22:11.7654321Z"
}
```

Response Codes

Status	Meaning
200	Returns the case's tasks/events (list grows over time).
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: task.read
500	Internal Server Error. Please try again later or contact support.

POST Create a Task or Event

Create a task/event with default values. A task only has a Due Date; an event also requires an EndDate. All date-times should be passed as UTC.

<https://valortax.logicsapi.com/publicapi/V4/Task/Task>

Required scope: **task.write**

Note: If TaskType is 2 (Event), EndDate is required.

Body Request

Parameter	Type	Description	Required
CaseID	Integer	Case to which the task is added	Required
Subject	String	Subject	Required
Reminder	DateTime	Reminder time	Required
TaskType	Integer	Task type	Required
DueDate	DateTime	Task due date	Required
UserID	Array	Array of user IDs	Required
EndDate	DateTime	Task end date	Optional
PriorityID	Integer	Priority ID	Optional
StatusID	Integer	Status ID	Optional
TaskCategoryID	Integer	Category ID	Optional
Comments	String	Comments	Optional
AllDayEvent	Boolean	Whether this is an all-day event	Optional

StatusID: 1 = Mark Complete, 0 = Mark Incomplete

PriorityID: 0 = Normal, 1 = Medium, 2 = High, 3 = Urgent

TaskType: 1 = Task, 2 = Event

Example Response (200)

```
{
  "Success": true,
  "data": { "TaskID": 128346 },
  "message": "Task/Event created successfully by User: Frankie Smith",
  "StatusCode": 201,
  "Timestamp": "2025-05-30T00:00:00.000000Z"
}
```

Response Codes

Status	Meaning
200	Returns the created TaskID — store it for future reference.
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: task.write
500	Internal Server Error. Please try again later or contact support.

GET Get Tasks or Events by Date Range

Gets a list of tasks/events within the specified date range.

<https://valortax.logiqsapi.com/publicapi/V4/Task/GetTasksByDateRange>

Required scope: **task.read**

Header Parameters

Parameter	Type	Description	Required
StartDate	String	Start date for filtering by DueDate, format mm/dd/yyyy	Required
EndDate	String	End date for filtering by DueDate, format mm/dd/yyyy	Required

Example Response (200)

```
{
  "Success": true,
  "data": [
    {
      "TaskID": 576745,
      "CreateBy": 2127,
      "CreatedByName": "Rob P",
      "DueDate": "2025-04-04T02:30:00",
      "PriorityID": 0,
      "CreateDate": "2025-04-04T17:39:45.467",
      "CaseID": 345692,
      "StatusID": 0,
      "Subject": "sssssssss",
      "Comments": null,
      "Reminder": "2025-04-04T02:00:00",
      "ModifiedDate": "2025-04-04T17:39:45.467",
      "ModifiedBy": 2127,
      "Deleted": false,
      "TaskType": 2,
      "EndDate": "2025-05-04T03:30:00",
      "LastReminded": null,
      "Location": null,
      "AllDayEvent": false,
      "TaskCategoryID": null,
      "TaskCategoryName": null,
      "UserID": null,
      "Users": [
```

```
    { "UserID": 2127, "FullName": "Rob P" }  
  ]  
},  
"message": "Data retrieved successfully.",  
"StatusCode": 200,  
"Timestamp": "2025-05-05T17:22:11.7654321Z"  
}
```

Response Codes

Status	Meaning
200	Returns tasks/events matching the date range (list grows over time).
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: task.read
500	Internal Server Error. Please try again later or contact support.

User

1 endpoint · Scopes used: **user.write**

POST Disable User

Disable a user by their email address.

<https://valortax.logicsapi.com/publicapi/V4/Users/DisableUser>

Required scope: **user.write**

Body Parameters

Parameter	Type	Description	Required
email	Email	User's email address	Required

Example Response (200)

```
{
  "Success": true,
  "data": "",
  "message": "The User Kenny Davis has been disabled by User: Frankie Smith",
  "StatusCode": 200,
  "Timestamp": "2025-05-30T00:00:00.000000Z"
}
```

Response Codes

Status	Meaning
200	Returns the name of the user that was disabled.
401	Unauthorized. Missing or invalid Authorization header. Expected Basic authentication.
403	Access denied. Missing required scope: user.write
500	Internal Server Error. Please try again later or contact support.