

**TDS 65LG RAL 7035, singlepack**

Art. Number 120501

**TRIAX TD Dishes** The difference is clear

Manufactured and tested to the highest standards of precision and quality, TRIAX's easy-to-install dishes offer outstanding performance, durability and reliability.

TDS: Steel TDA: Aluminium

- Unrivalled build quality, whether Steel or Aluminium
  - Hot-dip galvanized steel OR long lasting Aluminium - for extra corrosion protection
  - TRIAX's unique cable protection system
  - Every part, every accessory is weatherproofed
  - 2 years corrosion warranty
  - 5 years functionality warranty
- Outstanding performance
  - High gain for an exceptional signal
- Quick and easy installation
  - One-click mounting system
  - Self-locking screw & nuts
- Logistic friendly
  - Single or Bulk packaging, according to customer needs

TRIAX is your reliable partner, with comprehensive service and support.

[Click here](#) to see our guide on how to install TRIAX satellite dishes.

**Technical Specifications****ORDER INFORMATION**

EAN Number

5702661205019



# TRIAx

connecting the future

## Technical Specifications

### CHARACTERISTICS

F/D ratio	0,62
G/T LNB 0.7   dB/K	16.0 dB/K
X-polarisation   dB	≤ -25 dB
Offset angle   °	26 °
Elevation range   °	0...90 °

### FREQUENCY RANGE

Frequency range   GHz	10.7...12.75 GHz
-----------------------	------------------

### GAIN

Gain @ 11.7 GHz   dBi	36 dBi
-----------------------	--------

### MECHANICAL

Height (cm)   cm	66 cm
Width (cm)   cm	60 cm
LNB holder	40
Mast bracket diameter   mm	30...60 mm
Reflector type	Offset
Beamwidth   °	3.1 °
Main material	Galvanized steel (hot-dip)
Arm Colour	Raw
Colour	RAL 7035 - Light grey
Packing QTY	1
Product Height   mm	40 mm
Product Width   mm	623 mm
Product Depth   mm	682 mm
Packaging Height   m	0.105 m
Packaging Width   m	0.713 m
Packaging Depth   m	0.740 m
Packaging Volume   m3	0.050 m3
Net Weight   kg	3.050 kg
Tara Weight   kg	1.100 kg
Total Weight   kg	4.150 kg