
pyrad library reference for developers

Release 0.0.1

meteoswiss-mdr

Feb 19, 2020

CONTENTS

Contents:

PYRAD.FLOW.FLOW_AUX

Auxiliary functions to control the Pyrad data processing flow

toctree generated/

`_initialize_listener` `_user_input_listener` `_get_times_and_traj` `_initialize_datasets` `_process_datasets` `_post-process_datasets` `_wait_for_files` `_get_radars_data` `_generate_dataset` `_generate_prod` `_create_cfg_dict` `_create_datacfg_dict` `_create_dscfg_dict` `_create_prdcfg_dict` `_get_datatype_list` `_get_datasets_list` `_get_masterfile_list` `_add_dataset` `_warning_format`

`pyrad.flow.flow_aux._add_dataset (*args, **kwargs)`
wrapper

Parameters

args, kwargs [arguments] The arguments of the function

Returns

func [function] The original function if no profiling has to be performed or the function decorated with the memory decorator

`pyrad.flow.flow_aux._create_cfg_dict (*args, **kwargs)`
wrapper

Parameters

args, kwargs [arguments] The arguments of the function

Returns

func [function] The original function if no profiling has to be performed or the function decorated with the memory decorator

`pyrad.flow.flow_aux._create_datacfg_dict (*args, **kwargs)`
wrapper

Parameters

args, kwargs [arguments] The arguments of the function

Returns

func [function] The original function if no profiling has to be performed or the function decorated with the memory decorator

`pyrad.flow.flow_aux._create_dscfg_dict (*args, **kwargs)`
wrapper

Parameters

args, kwargs [arguments] The arguments of the function

Returns

func [function] The original function if no profiling has to be performed or the function decorated with the memory decorator

`pyrad.flow.flow_aux._create_prdcfg_dict(*args, **kwargs)`
wrapper

Parameters

args, kwargs [arguments] The arguments of the function

Returns

func [function] The original function if no profiling has to be performed or the function decorated with the memory decorator

`pyrad.flow.flow_aux._generate_dataset(*args, **kwargs)`
wrapper

Parameters

args, kwargs [arguments] The arguments of the function

Returns

func [function] The original function if no profiling has to be performed or the function decorated with the memory decorator

`pyrad.flow.flow_aux._generate_prod(*args, **kwargs)`
wrapper

Parameters

args, kwargs [arguments] The arguments of the function

Returns

func [function] The original function if no profiling has to be performed or the function decorated with the memory decorator

`pyrad.flow.flow_aux._get_datasets_list(*args, **kwargs)`
wrapper

Parameters

args, kwargs [arguments] The arguments of the function

Returns

func [function] The original function if no profiling has to be performed or the function decorated with the memory decorator

`pyrad.flow.flow_aux._get_datatype_list(*args, **kwargs)`
wrapper

Parameters

args, kwargs [arguments] The arguments of the function

Returns

func [function] The original function if no profiling has to be performed or the function decorated with the memory decorator

`pyrad.flow.flow_aux._get_masterfile_list(*args, **kwargs)`
wrapper

Parameters

args, kwargs [arguments] The arguments of the function

Returns

func [function] The original function if no profiling has to be performed or the function decorated with the memory decorator

`pyrad.flow.flow_aux._get_radars_data(*args, **kwargs)`
wrapper

Parameters

args, kwargs [arguments] The arguments of the function

Returns

func [function] The original function if no profiling has to be performed or the function decorated with the memory decorator

`pyrad.flow.flow_aux._get_times_and_traj(*args, **kwargs)`
wrapper

Parameters

args, kwargs [arguments] The arguments of the function

Returns

func [function] The original function if no profiling has to be performed or the function decorated with the memory decorator

`pyrad.flow.flow_aux._initialize_datasets(dataset_levels, cfg, traj=None, infostr=None)`
Initializes datasets. Creates the data set configuration dictionary

Parameters

dataset_levels [dict] dictionary containing the list of data sets to be generated at each processing level

cfg [dict] processing configuration dictionary

traj [trajectory object] object containing the trajectory

infostr [str] Information string about the actual data processing (e.g. 'RUN57'). This string is added to product files.

Returns

dscfg [dict] dictionary containing the configuration data for each dataset

traj [trajectory object] the modified trajectory object

`pyrad.flow.flow_aux._initialize_listener()`
initialize the input listener

Returns

input_queue [queue object] the queue object where to put the quit signal

`pyrad.flow.flow_aux._postprocess_datasets(dataset_levels, cfg, dscfg, traj=None, infostr=None)`

Processes the radar volumes for a particular time stamp.

Parameters

dataset_levels [dict] dictionary containing the list of data sets to be generated at each processing level

cfg [dict] processing configuration dictionary

dscfg [dict] dictionary containing the configuration data for each dataset

traj [trajectory object] and object containing the trajectory

infostr [str] Information string about the actual data processing (e.g. 'RUN57'). This string is added to product files.

Returns

dscfg [dict] the modified configuration dictionary

traj [trajectory object] the modified trajectory object

`pyrad.flow.flow_aux._process_datasets(*args, **kwargs)`
wrapper

Parameters

args, kwargs [arguments] The arguments of the function

Returns

func [function] The original function if no profiling has to be performed or the function decorated with the memory decorator

`pyrad.flow.flow_aux._user_input_listener(input_queue)`
Permanently listens to the keyword input until the user types "Return"

Parameters

input_queue [queue object] the queue object where to put the quit signal

`pyrad.flow.flow_aux._wait_for_files(nowtime, datacfg, datatype_list, last_processed=None)`
Waits for the master file and all files in a volume scan to be present returns the masterfile if the volume scan can be processed.

Parameters

nowtime [datetime object] the current time

datacfg [dict] dictionary containing the parameters to get the radar data

last_processed [datetime or None] The end time of the previously processed radar volume

Returns

masterfile [str or None] name of the master file. None if the volume was not complete

masterdatatype_descr [str] the description of the master data type

last_processed [datetime] True of all scans found

`pyrad.flow.flow_aux._wait_for_rainbow_datatypes(rainbow_files, period=30)`
waits until the files for all rainbow data types are present.

Parameters

rainbow_files [list of strings] a list containing the names of all the rainbow files to wait for

period [int] the time it has to wait (s)

Returns

found_all [Boolean] True if all files were present. False otherwise

`pyrad.flow.flow_aux._warning_format` (*message*, *category*, *filename*, *lineno*, *file=None*,
line=None)

`pyrad.flow.flow_aux.profiler` (*level=1*)

Function to be used as decorator for memory debugging. The function will be profiled or not according to its level respect to the global variable PROFILE_LEVEL

Parameters

level [int] profiling level

Returns

func or func wrapper [function] The function or its wrapper for profiling

PYRAD.FLOW.FLOW_CONTROL

functions to control the Pyrad data processing flow

<i>main</i> (cfgfile[, starttime, endtime, ...])	Main flow control.
<i>main_rt</i> (cfgfile_list[, starttime, endtime, ...])	main flow control.
<i>main_cosmo</i> (cfgfile[, starttime, endtime, ...])	Main flow control.
<i>main_cosmo_rt</i> (cfgfile_list[, starttime, ...])	main flow control.

```
pyrad.flow.flow_control.main(cfgfile,      starttime=None,      endtime=None,      trajfile="",
                              trajtype='plane',      flashnr=0,      infostr="",      MULTI-
                              PROCESSING_DSET=False,      MULTIPROCESS-
                              ING_PROD=False,      PROFILE_MULTIPROCESSING=False,
                              USE_CHILD_PROCESS=False)
```

Main flow control. Processes radar data off-line over a period of time given either by the user, a trajectory file, or determined by the last volume processed and the current time. Multiple radars can be processed simultaneously

Parameters

cfgfile [str] path of the main config file

starttime, endtime [datetime object] start and end time of the data to be processed

trajfile [str] path to file describing the trajectory

trajtype [str] type of trajectory file. Can be either 'plane', 'lightning' or 'proc_periods'

flashnr [int] If larger than 0 will select a flash in a lightning trajectory file. If 0 the data corresponding to the trajectory of all flashes will be plotted

infostr [str] Information string about the actual data processing (e.g. 'RUN57'). This string is added to product files.

MULTIPROCESSING_DSET [Bool] If true the generation of datasets at the same processing level will be parallelized

MULTIPROCESSING_PROD [Bool] If true the generation of products from each dataset will be parallelized

PROFILE_MULTIPROCESSING [Bool] If true and code parallelized the multiprocessing is profiled

USE_CHILD_PROCESS [Bool] If true the reading and processing of the data will be performed by a child process controlled by dask. This is done to make sure all memory used is released.

```
pyrad.flow.flow_control.main_cosmo(cfgfile, starttime=None, endtime=None, trajfile="", infostr="")
```

Main flow control. Processes radar data off-line over a period of time given either by the user, a trajectory file, or

determined by the last volume processed and the current time. Multiple radars can be processed simultaneously

Parameters

cfgfile [str] path of the main config file

starttime, endtime [datetime object] start and end time of the data to be processed

trajfile [str] path to file describing the trajectory

infostr [str] Information string about the actual data processing (e.g. 'RUN57'). This string is added to product files.

`pyrad.flow.flow_control.main_cosmo_rt(cfgfile_list, starttime=None, endtime=None, infostr_list=None, proc_period=60, proc_finish=None)`

main flow control. Processes radar data in real time. The start and end processing times can be determined by the user. This function is intended for a single radar

Parameters

cfgfile_list [list of str] path of the main config files

starttime, endtime [datetime object] start and end time of the data to be processed

infostr_list [list of str] Information string about the actual data processing (e.g. 'RUN57'). This string is added to product files.

proc_period [int] period of time before starting a new processing round (seconds)

proc_finish [int or None] if set to a value the program will be forced to shut down after the value (in seconds) from start time has been exceeded

Returns

end_proc [Boolean] If true the program has ended successfully

`pyrad.flow.flow_control.main_rt(cfgfile_list, starttime=None, endtime=None, infostr_list=None, proc_period=60, proc_finish=None)`

main flow control. Processes radar data in real time. The start and end processing times can be determined by the user. This function is intended for a single radar

Parameters

cfgfile_list [list of str] path of the main config files

starttime, endtime [datetime object] start and end time of the data to be processed

infostr_list [list of str] Information string about the actual data processing (e.g. 'RUN57'). This string is added to product files.

proc_period [int] period of time before starting a new processing round (seconds)

proc_finish [int or None] if set to a value the program will be forced to shut down after the value (in seconds) from start time has been exceeded

Returns

end_proc [Boolean] If true the program has ended successfully

PYRAD.PROC.PROCESS_AUX

Auxiliary functions. Functions to determine the process type, pass raw data to the product generation functions, save radar data and extract data at determined points or regions of interest.

<i>get_process_func</i> (dataset_type, dsname)	Maps the dataset type into its processing function and data set format associated.
<i>process_raw</i> (procstatus, dscfg[, radar_list])	Dummy function that returns the initial input data set
<i>process_save_radar</i> (procstatus, dscfg[, ...])	Dummy function that allows to save the entire radar object
<i>process_fixed_rng</i> (procstatus, dscfg[, ...])	Obtains radar data at a fixed range
<i>process_fixed_rng_span</i> (procstatus, dscfg[, ...])	For each azimuth-elevation gets the data within a fixed range span and computes a user-defined statistic: mean, min, max, mode, median
<i>process_roi</i> (procstatus, dscfg[, radar_list])	Obtains the radar data at a region of interest defined by a TRT file or by the user.
<i>process_azimuthal_average</i> (procstatus, dscfg)	Averages radar data in azimuth obtaining and RHI as a result
<i>process_radar_resampling</i> (procstatus, dscfg)	Resamples the radar data to mimic another radar with different geometry and antenna pattern
<i>_get_values_antenna_pattern</i> (radar, tadict, ...)	Get the values of a synthetic radar
<i>_create_target_radar</i> (radar, dscfg, ...[, ...])	Creates the target radar

pyrad.proc.process_aux.**_create_target_radar** (*radar*, *dscfg*, *fixed_angle_val*,
info, *field_names*,
change_antenna_pattern=False, *quantiles*=[50])

Creates the target radar

Parameters

- radar** [radar object] the radar object containing the observed data
- dscfg** [dict] dict with the configuration
- fixed_angle_val** [array of floats] array containing the fixed angles
- info** [str] String with info on the type of antenna
- field_names** [list of str] the list of field names that the target radar will contain
- change_antenna_pattern** [bool] Whether the antenna pattern of the target radar is different from the observations radar
- quantiles** [list of floats] the quantiles to be computed if the target radar has a different antenna

pattern

Returns

target_radar [radar object] The target radar

`pyrad.proc.process_aux._get_values_antenna_pattern(radar, tadict, field_names)`

Get the values of a synthetic radar

Parameters

radar [radar object] The radar volume with the data

tadict [dict] A dictionary containing parameters useful for radar re-sampling

field_names [list of str] list of names of the radar field

Returns

target_radar [radar object] The synthetic radar

`pyrad.proc.process_aux.get_process_func(dataset_type, dsname)`

Maps the dataset type into its processing function and data set format associated.

Parameters

dataset_type [str] The following is a list of data set types ordered by type of output dataset with the function they call. For details of what they do check the function documentation:

‘VOL’ format output: ‘ATTENUATION’: process_attenuation ‘AZI_AVG’: process_azimuthal_average ‘BIAS_CORRECTION’: process_correct_bias ‘BIRDS_ID’: process_birds_id ‘BIRD_DENSITY’: process_bird_density ‘CCOR’: process_ccor ‘CDF’: process_cdf ‘CDR’: process_cdr ‘CLT_TO_SAN’: process_clt_to_echo_id ‘COSMO’: process_cosmo ‘COSMO_LOOKUP’: process_cosmo_lookup_table ‘DEM’: process_dem ‘DEALIAS_FOURDD’: process_dealias_fourdd ‘DEALIAS_REGION’: process_dealias_region_based ‘DEALIAS_UNWRAP’: process_dealias_unwrap_phase ‘DOPPLER_VELOCITY’: process_Doppler_velocity ‘DOPPLER_VELOCITY_IQ’: process_Doppler_velocity_iq ‘DOPPLER_WIDTH’: process_Doppler_width ‘DOPPLER_WIDTH_IQ’: process_Doppler_width_iq ‘ECHO_FILTER’: process_echo_filter ‘FIELDS_DIFF’: process_fields_diff ‘FIXED_RNG’: process_fixed_rng ‘FIXED_RNG_SPAN’: process_fixed_rng_span ‘HYDROCLASS’: process_hydroclass ‘HGT’: process_hgt ‘HGT_LOOKUP’: process_hgt_lookup_table ‘KDP_LEASTSQUARE_1W’: process_kdp_leastsquare_single_window ‘KDP_LEASTSQUARE_2W’: process_kdp_leastsquare_double_window ‘L’: process_l ‘MEAN_PHASE_IQ’: process_mean_phase_iq ‘NCVOL’: process_save_radar ‘NOISE_POWER’: process_noise_power ‘OUTLIER_FILTER’: process_outlier_filter ‘PhiDP’: process_differential_phase ‘PHIDP0_CORRECTION’: process_correct_phidp0 ‘PHIDP0_ESTIMATE’: process_estimate_phidp0 ‘PhiDP_IQ’: process_differential_phase_iq ‘PHIDP_KDP_KALMAN’: process_phidp_kdp_Kalman ‘PHIDP_KDP_LP’: process_phidp_kdp_lp ‘PHIDP_KDP_VULPIANI’: process_phidp_kdp_Vulpiani ‘PHIDP_SMOOTH_1W’: process_smooth_phidp_single_window ‘PHIDP_SMOOTH_2W’: process_smooth_phidp_double_window ‘POL_VARIABLES’: process_pol_variables ‘POL_VARIABLES_IQ’: process_pol_variables_iq ‘PWR’: process_signal_power ‘RADAR_RESAMPLING’: process_radar_resampling ‘RADIAL_NOISE_HS’: process_radial_noise_hs ‘RADIAL_NOISE_IVIC’: process_radial_noise_ivic ‘RAINRATE’: process_rainrate ‘RAW’: process_raw ‘REFLECTIVITY’: process_reflectivity

'REFLECTIVITY_IQ': process_reflectivity_iq 'RCS': process_rcs 'RCS_PR':
 process_rcs_pr 'RhoHV': process_rhohv 'RhoHV_IQ': process_rhohv_iq
 'RHOHV_CORRECTION': process_correct_noise_rhohv 'RHOHV_RAIN':
 process_rhohv_rain 'ROI': process_roi 'SAN': process_echo_id 'SELFCONSIS-
 TENCY_BIAS': process_selfconsistency_bias 'SELFCONSISTENCY_BIAS2':
 process_selfconsistency_bias2 'SELFCONSISTENCY_KDP_PHIDP': pro-
 cess_selfconsistency_kdp_phidp 'SNR': process_snr 'SNR_FILTER': pro-
 cess_filter_snr 'ST1_IQ': process_st1_iq 'ST2_IQ': process_st2_iq 'TRAJ_TRT'
 : process_traj_trt 'TRAJ_TRT_CONTOUR' : process_traj_trt_contour 'TUR-
 BULENCE': process_turbulence 'VAD': process_vad 'VEL_FILTER':
 process_filter_vel_diff 'VIS': process_visibility 'VIS_FILTER': pro-
 cess_filter_visibility 'VOL_REFL': process_vol_refl 'WBN': process_wbn_iq
 'WIND_VEL': process_wind_vel 'WINDSHEAR': process_windshear 'ZDR':
 process_differential_reflectivity 'ZDR_IQ': process_differential_reflectivity_iq
 'ZDR_PREC': process_zdr_precip 'ZDR_SNOW': process_zdr_snow

'SPECTRA' format output: 'FFT': process_fft 'FILTER_0DOPPLER': pro-
 cess_filter_0Doppler 'FILTER_SPECTRA_NOISE': process_filter_spectra_noise
 'IFFT': process_ifft 'RAW_IQ': process_raw_iq 'RAW_SPECTRA': pro-
 cess_raw_spectra 'SPECTRA_ANGULAR_AVERAGE': process_spectra_ang_avg
 'SPECTRA_POINT': process_spectra_point 'SPECTRAL_NOISE': pro-
 cess_spectral_noise 'SPECTRAL_PHASE': process_spectral_phase 'SPEC-
 TRAL_POWER': process_spectral_power 'SPECTRAL_REFLECTIVITY': pro-
 cess_spectral_reflectivity 'sPhiDP': process_spectral_differential_phase 'sRhoHV':
 process_spectral_RhoHV 'SRHOHV_FILTER': process_filter_srhoHV 'sZDR':
 process_spectral_differential_reflectivity

'COLOCATED_GATES' format output: 'COLOCATED_GATES': process_collocated_gates

'COSMO_COORD' format output: 'COSMO_COORD': process_cosmo_coord
 'HGT_COORD': process_hgt_coord

'COSMO2RADAR' format output: 'COSMO2RADAR': process_cosmo_to_radar

'GRID' format output: 'RAW_GRID': process_raw_grid 'GRID': process_grid

'GRID_TIMEAVG' format output: 'GRID_TIME_STATS': process_grid_time_stats
 'GRID_TIME_STATS2': process_grid_time_stats2

'INTERCOMP' format output: 'INTERCOMP': process_intercomp 'INTER-
 COMP_FIELDS': process_intercomp_fields 'INTERCOMP_TIME_AVG':
 process_intercomp_time_avg

'ML' format output: 'ML_DETECTION': process_melting_layer

'MONITORING' format output: 'GC_MONITORING': process_gc_monitoring
 'MONITORING': process_monitoring

'OCCURRENCE' format output: 'OCCURRENCE': process_occurrence 'OC-
 CURRENCE_PERIOD': process_occurrence_period 'TIMEAVG_STD': pro-
 cess_time_avg_std

'QVP' format output: 'EVP': process_evp 'QVP': process_qvp 'rQVP':
 process_rqvp 'SVP': process_svp 'TIME_HEIGHT': process_time_height
 'TIME_ALONG_COORD': process_ts_along_coord

'SPARSE_GRID' format output: 'ZDR_COLUMN': process_zdr_column

'SUN_HITS' format output: 'SUN_HITS': process_sun_hits

'TIMEAVG' format output: 'FLAG_TIME_AVG': process_time_avg_flag
'TIME_AVG': process_time_avg 'WEIGHTED_TIME_AVG': process_weighted_time_avg
'TIME_STATS': process_time_stats 'TIME_STATS2': process_time_stats2
'RAIN_ACCU': process_rainfall_accumulation

'TIMESERIES' format output: 'GRID_POINT_MEASUREMENT': process_grid_point
'POINT_MEASUREMENT': 'process_point_measurement'
'TRAJ_ANTENNA_PATTERN': process_traj_antenna_pattern
'TRAJ_ATPLANE': process_traj_atplane 'TRAJ_LIGHTNING': process_traj_lightning

'TRAJ_ONLY' format output: 'TRAJ': process_trajectory

dsname [str] Name of dataset

Returns

func_name [str or processing function] pyrad function used to process the data set type

dsformat [str] data set format, i.e.: 'VOL', etc.

`pyrad.proc.process_aux.process_azimuthal_average` (*procstatus, dscfg, radar_list=None*)
Averages radar data in azimuth obtaining and RHI as a result

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The data type where we want to extract the point measurement

angle [float or None. Dataset keyword] The

delta_azi : float. Dataset keyword

avg_type : str. Dataset keyword

nvalid_min [int. Dataset keyword] the (minimum) radius of the region of interest in m.
Default half the largest resolution

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the gridded data

ind_rad [int] radar index

`pyrad.proc.process_aux.process_fixed_rng` (*procstatus, dscfg, radar_list=None*)
Obtains radar data at a fixed range

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of strings. Dataset keyword] The fields we want to extract

rng [float. Dataset keyword] The fixed range [m]

RngTol [float. Dataset keyword] The tolerance between the nominal range and the radar range

ele_min, ele_max, azi_min, azi_max [floats. Dataset keyword] The azimuth and elevation limits of the data [deg]

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the data and metadata at the point of interest

ind_rad [int] radar index

`pyrad.proc.process_aux.process_fixed_rng_span(procstatus, dscfg, radar_list=None)`

For each azimuth-elevation gets the data within a fixed range span and computes a user-defined statistic: mean, min, max, mode, median

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of strings. Dataset keyword] The fields we want to extract

rmin, rmax [float. Dataset keyword] The range limits [m]

ele_min, ele_max, azi_min, azi_max [floats. Dataset keyword] The azimuth and elevation limits of the data [deg]

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the data and metadata at the point of interest

ind_rad [int] radar index

`pyrad.proc.process_aux.process_radar_resampling(procstatus, dscfg, radar_list=None)`

Resamples the radar data to mimic another radar with different geometry and antenna pattern

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries]

datatype [list of string. Dataset keyword] The input data types

antennaType [str. Dataset keyword] Type of antenna of the radar we want to get the view from. Can be AZIMUTH, ELEVATION, LOWBEAM, HIGHBEAM

par_azimuth_antenna [dict. Global ekeyword] Dictionary containing the parameters of the PAR azimuth antenna, i.e. name of the file with the antenna elevation pattern and fixed antenna angle

par_elevation_antenna [dict. Global keyword] Dictionary containing the parameters of the PAR elevation antenna, i.e. name of the file with the antenna azimuth pattern and fixed antenna angle

asr_lowbeam_antenna [dict. Global keyword] Dictionary containing the parameters of the ASR low beam antenna, i.e. name of the file with the antenna elevation pattern and fixed antenna angle

asr_highbeam_antenna [dict. Global keyword] Dictionary containing the parameters of the ASR high beam antenna, i.e. name of the file with the antenna elevation pattern and fixed antenna angle

target_radar_pos [dict. Global keyword] Dictionary containing the latitude, longitude and altitude of the radar we want to get the view from. If not specifying it will assume the radar is collocated

change_antenna_pattern [Bool. Dataset keyword] If true the target radar has a different antenna pattern than the observations radar

rhi_resolution [Bool. Dataset keyword] Resolution of the synthetic RHI used to compute the data as viewed from the synthetic radar [deg]. Default 0.5

max_altitude [float. Dataset keyword] Max altitude of the data to use when computing the view from the synthetic radar [m MSL]. Default 12000.

latlon_tol [float. Dataset keyword] The tolerance in latitude and longitude to determine which synthetic radar gates are co-located with real radar gates [deg]. Default 0.04

alt_tol [float. Dataset keyword] The tolerance in altitude to determine which synthetic radar gates are co-located with real radar gates [m]. Default 1000.

pattern_thres [float. Dataset keyword] The minimum of the sum of the weights given to each value in order to consider the weighted quantile valid. It is related to the number of valid data points

data_is_log [dict. Dataset keyword] Dictionary specifying for each field if it is in log (True) or linear units (False). Default False

use_nans [dict. Dataset keyword] Dictionary specifying whether the nans have to be used in the computation of the statistics for each field. Default False

nan_value [dict. Dataset keyword] Dictionary with the value to use to substitute the NaN values when computing the statistics of each field. Default 0

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [Trajectory object] dictionary containing the new radar

ind_rad [int] radar index

`pyrad.proc.process_aux.process_raw(procstatus, dscfg, radar_list=None)`

Dummy function that returns the initial input data set

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_aux.process_roi(procstatus, dscfg, radar_list=None)`

Obtains the radar data at a region of interest defined by a TRT file or by the user.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The data type where we want to extract the point measurement

trtfile [str. Dataset keyword] TRT file from which to extract the region of interest

lon_roi, lat_roi [float array. Dataset keyword] latitude and longitude positions defining a region of interest

alt_min, alt_max [float. Dataset keyword] Minimum and maximum altitude of the region of interest. Can be None

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the data and metadata at the point of interest

ind_rad [int] radar index

`pyrad.proc.process_aux.process_save_radar(procstatus, dscfg, radar_list=None)`

Dummy function that allows to save the entire radar object

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

PYRAD.PROC.PROCESS_CALIB

Functions for monitoring data quality and correct bias and noise effects

<i>process_correct_bias</i> (procstatus, dscfg[, ...])	Corrects a bias on the data
<i>process_correct_noise_rho_hv</i> (procstatus, dscfg)	identifies echoes as 0: No data, 1: Noise, 2: Clutter, 3: Precipitation
<i>process_gc_monitoring</i> (procstatus, dscfg[, ...])	computes ground clutter monitoring statistics
<i>process_occurrence</i> (procstatus, dscfg[, ...])	computes the frequency of occurrence of data.
<i>process_time_avg_std</i> (procstatus, dscfg[, ...])	computes the average and standard deviation of data.
<i>process_occurrence_period</i> (procstatus, dscfg)	computes the frequency of occurrence over a long period of time by adding together shorter periods
<i>process_sun_hits</i> (procstatus, dscfg[, radar_list])	monitoring of the radar using sun hits

pyrad.proc.process_calib.**process_correct_bias** (*procstatus*, *dscfg*, *radar_list=None*)
Corrects a bias on the data

Parameters

- procstatus** [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
- dscfg** [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
 - datatype** [string. Dataset keyword] The data type to correct for bias
 - bias** [float. Dataset keyword] The bias to be corrected [dB]. Default 0
- radar_list** [list of Radar objects] Optional. list of radar objects

Returns

- new_dataset** [dict] dictionary containing the output
- ind_rad** [int] radar index

pyrad.proc.process_calib.**process_correct_noise_rho_hv** (*procstatus*, *dscfg*, *radar_list=None*)
identifies echoes as 0: No data, 1: Noise, 2: Clutter, 3: Precipitation

Parameters

- procstatus** [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
- dscfg** [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
 - datatype** [list of string. Dataset keyword] The data types used in the correction
- radar_list** [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_calib.process_gc_monitoring(procstatus, dscfg, radar_list=None)`
computes ground clutter monitoring statistics

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

excessgatespath [str. Config keyword] The path to the gates in excess of quantile location

excessgates_fname [str. Dataset keyword] The name of the gates in excess of quantile file

datatype [list of string. Dataset keyword] The input data types

step [float. Dataset keyword] The width of the histogram bin. Default is None. In that case the default step in function `get_histogram_bins` is used

regular_grid [Boolean. Dataset keyword] Whether the radar has a Boolean grid or not.
Default False

val_min [Float. Dataset keyword] Minimum value to consider that the gate has signal.
Default None

filter_prec [str. Dataset keyword] Give which type of volume should be filtered. None, no filtering; keep_wet, keep wet volumes; keep_dry, keep dry volumes.

rmax_prec [float. Dataset keyword] Maximum range to consider when looking for wet gates [m]

percent_prec_max [float. Dataset keyword] Maxim percentage of wet gates to consider the volume dry

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [Radar] radar object containing histogram data

ind_rad [int] radar index

`pyrad.proc.process_calib.process_occurrence(procstatus, dscfg, radar_list=None)`
computes the frequency of occurrence of data. It looks only for gates where data is present.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

regular_grid [Boolean. Dataset keyword] Whether the radar has a Boolean grid or not.
Default False

rmin, rmax [float. Dataset keyword] minimum and maximum ranges where the computation takes place. If -1 the whole range is considered. Default is -1

val_min [Float. Dataset keyword] Minimum value to consider that the gate has signal.
Default None

filter_prec [str. Dataset keyword] Give which type of volume should be filtered. None, no filtering; keep_wet, keep wet volumes; keep_dry, keep dry volumes.

rmax_prec [float. Dataset keyword] Maximum range to consider when looking for wet gates [m]

percent_prec_max [float. Dataset keyword] Maxim percentage of wet gates to consider the volume dry

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_calib.process_occurrence_period` (*procstatus*, *dscfg*,
radar_list=None)
computes the frequency of occurrence over a long period of time by adding together shorter periods

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

regular_grid [Boolean. Dataset keyword] Whether the radar has a Boolean grid or not.
Default False

rmin, rmax [float. Dataset keyword] minimum and maximum ranges where the computation takes place. If -1 the whole range is considered. Default is -1

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_calib.process_sun_hits` (*procstatus*, *dscfg*, *radar_list=None*)
monitoring of the radar using sun hits

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

delev_max [float. Dataset keyword] maximum elevation distance from nominal radar elevation where to look for a sun hit signal [deg]. Default 1.5

dazim_max [float. Dataset keyword] maximum azimuth distance from nominal radar elevation where to look for a sun hit signal [deg]. Default 1.5

elmin [float. Dataset keyword] minimum radar elevation where to look for sun hits [deg]. Default 1.

attg [float. Dataset keyword] gaseous attenuation. Default None

sun_position [string. Dataset keyword] The function to compute the sun position to use.
Can be 'MF' or 'pysolar'

sun_hit_method [str. Dataset keyword] Method used to estimate the power of the sun hit. Can be HS (Hildebrand and Sekhon 1974) or Ivic (Ivic 2013)

rmin [float. Dataset keyword] minimum range where to look for a sun hit signal [m]. Used in HS method. Default 50000.

hmin [float. Dataset keyword] minimum altitude where to look for a sun hit signal [m MSL]. Default 10000. The actual range from which a sun hit signal will be search will be the minimum between rmin and the range from which the altitude is higher than hmin. Used in HS method. Default 10000.

nbins_min [int. Dataset keyword.] minimum number of range bins that have to contain signal to consider the ray a potential sun hit. Default 20 for HS and 8000 for Ivic.

npulses_ray [int] Default number of pulses used in the computation of the ray. If the number of pulses is not in radar.instrument_parameters this will be used instead. Used in Ivic method. Default 30

flat_reg_wlen [int] Length of the flat region window [m]. Used in Ivic method. Default 8000.

iterations: int number of iterations in step 7 of Ivic method. Default 10.

max_std_pwr [float. Dataset keyword] maximum standard deviation of the signal power to consider the data a sun hit [dB]. Default 2. Used in HS method

max_std_zdr [float. Dataset keyword] maximum standard deviation of the ZDR to consider the data a sun hit [dB]. Default 2.

az_width_co [float. Dataset keyword] co-polar antenna azimuth width (convoluted with sun width) [deg]. Default None

el_width_co [float. Dataset keyword] co-polar antenna elevation width (convoluted with sun width) [deg]. Default None

az_width_cross [float. Dataset keyword] cross-polar antenna azimuth width (convoluted with sun width) [deg]. Default None

el_width_cross [float. Dataset keyword] cross-polar antenna elevation width (convoluted with sun width) [deg]. Default None

ndays [int. Dataset keyword] number of days used in sun retrieval. Default 1

coeff_band [float. Dataset keyword] multiply coefficient to transform pulse width into receiver bandwidth

frequency [float. Dataset keyword] the radar frequency [Hz]. If None that of the key frequency in attribute instrument_parameters of the radar object will be used. If the key or the attribute are not present frequency dependent parameters will not be computed

beamwidth [float. Dataset keyword] the antenna beamwidth [deg]. If None that of the keys radar_beam_width_h or radar_beam_width_v in attribute instrument_parameters of the radar object will be used. If the key or the attribute are not present the beamwidth dependent parameters will not be computed

pulse_width [float. Dataset keyword] the pulse width [s]. If None that of the key pulse_width in attribute instrument_parameters of the radar object will be used. If the key or the attribute are not present the pulse width dependent parameters will not be computed

ray_angle_res [float. Dataset keyword] the ray angle resolution [deg]. If None that of the key ray_angle_res in attribute instrument_parameters of the radar object will be used. If

the key or the attribute are not present the ray angle resolution parameters will not be computed

AntennaGainH, AntennaGainV [float. Dataset keyword] the horizontal (vertical) polarization antenna gain [dB]. If None that of the attribute `instrument_parameters` of the radar object will be used. If the key or the attribute are not present the ray angle resolution parameters will not be computed

radar_list [list of Radar objects] Optional. list of radar objects

Returns

sun_hits_dict [dict] dictionary containing a radar object, a `sun_hits` dict and a `sun_retrieval` dictionary

ind_rad [int] radar index

`pyrad.proc.process_calib.process_time_avg_std(procstatus, dscfg, radar_list=None)`
computes the average and standard deviation of data. It looks only for gates where data is present.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

regular_grid [Boolean. Dataset keyword] Whether the radar has a Boolean grid or not.
Default False

rmin, rmax [float. Dataset keyword] minimum and maximum ranges where the computation takes place. If -1 the whole range is considered. Default is -1

val_min [Float. Dataset keyword] Minimum reflectivity value to consider that the gate has signal. Default None

filter_prec [str. Dataset keyword] Give which type of volume should be filtered. None, no filtering; `keep_wet`, keep wet volumes; `keep_dry`, keep dry volumes.

rmax_prec [float. Dataset keyword] Maximum range to consider when looking for wet gates [m]

percent_prec_max [float. Dataset keyword] Maxim percentage of wet gates to consider the volume dry

lin_trans [Boolean. Dataset keyword] If True the data will be transformed into linear units.
Default False

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

PYRAD.PROC.PROCESS_COSMO

Functions to manage COSMO data

<i>process_cosmo</i> (procstatus, dscfg[, radar_list])	Gets COSMO data and put it in radar coordinates
<i>process_hzt</i> (procstatus, dscfg[, radar_list])	Gets iso0 degree data in HZT format and put it in radar coordinates
<i>process_cosmo_lookup_table</i> (procstatus, dscfg)	Gets COSMO data and put it in radar coordinates using look up tables computed or loaded when initializing
<i>process_hzt_lookup_table</i> (procstatus, dscfg)	Gets HZT data and put it in radar coordinates using look up tables computed or loaded when initializing
<i>process_cosmo_to_radar</i> (procstatus, dscfg[, ...])	Gets COSMO data and put it in radar coordinates using look up tables
<i>process_cosmo_coord</i> (procstatus, dscfg[, ...])	Gets the COSMO indices corresponding to each cosmo coordinates
<i>process_hzt_coord</i> (procstatus, dscfg[, ...])	Gets the HZT indices corresponding to each HZT coordinates

`pyrad.proc.process_cosmo.process_cosmo (procstatus, dscfg, radar_list=None)`

Gets COSMO data and put it in radar coordinates

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] arbitrary data type

keep_in_memory [int. Dataset keyword] if set keeps the COSMO data dict, the COSMO coordinates dict and the COSMO field in radar coordinates in memory

regular_grid [int. Dataset keyword] if set it is assume that the radar has a grid constant in time and there is no need to compute a new COSMO field if the COSMO data has not changed

cosmo_type [str. Dataset keyword] name of the COSMO field to process. Default TEMP

cosmo_variables [list of strings. Dataset keyword] Py-art name of the COSMO fields. Default temperature

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_cosmo.process_cosmo_coord(procstatus, dscfg, radar_list=None)`

Gets the COSMO indices corresponding to each cosmo coordinates

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] arbitrary data type

cosmopath [string. General keyword] path where to store the look up table

model [string. Dataset keyword] The COSMO model to use. Can be cosmo-1, cosmo-2, cosmo-7

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_cosmo.process_cosmo_lookup_table(procstatus, dscfg, radar_list=None)`

Gets COSMO data and put it in radar coordinates using look up tables computed or loaded when initializing

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] arbitrary data type

lookup_table [int. Dataset keyword] if set a pre-computed look up table for the COSMO coordinates is loaded. Otherwise the look up table is computed taking the first radar object as reference

regular_grid [int. Dataset keyword] if set it is assume that the radar has a grid constant in time and therefore there is no need to interpolate the COSMO field in memory to the current radar grid

cosmo_type [str. Dataset keyword] name of the COSMO field to process. Default TEMP

cosmo_variables [list of strings. Dataset keyword] Py-art name of the COSMO fields. Default temperature

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_cosmo.process_cosmo_to_radar(procstatus, dscfg, radar_list=None)`

Gets COSMO data and put it in radar coordinates using look up tables

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] arbitrary data type

cosmo_type [str. Dataset keyword] name of the COSMO field to process. Default TEMP

cosmo_variables [list of strings. Dataset keyword] Py-art name of the COSMO fields.
Default temperature

cosmo_time_index_min, cosmo_time_index_max [int] minimum and maximum indices
of the COSMO data to retrieve. If a value is provided only data corresponding to the time
indices within the interval will be used. If None all data will be used. Default None

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_cosmo.process_hzt(procstatus, dscfg, radar_list=None)`

Gets iso0 degree data in HZT format and put it in radar coordinates

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

metranet_read_lib [str. Global keyword] Type of METRANET reader library used to read
the data. Can be 'C' or 'python'

datatype [string. Dataset keyword] arbitrary data type

keep_in_memory [int. Dataset keyword] if set keeps the COSMO data dict, the COSMO
coordinates dict and the COSMO field in radar coordinates in memory

regular_grid [int. Dataset keyword] if set it is assume that the radar has a grid constant in
time and there is no need to compute a new COSMO field if the COSMO data has not
changed

cosmo_type [str. Dataset keyword] name of the COSMO field to process. Default TEMP

cosmo_variables [list of strings. Dataset keyword] Py-art name of the COSMO fields.
Default temperature

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_cosmo.process_hzt_coord(procstatus, dscfg, radar_list=None)`

Gets the HZT indices corresponding to each HZT coordinates

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

metranet_read_lib [str. Global keyword] Type of METRANET reader library used to read
the data. Can be 'C' or 'python'

datatype [string. Dataset keyword] arbitrary data type

cosmopath [string. General keyword] path where to store the look up table

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_cosmo.process_hzt_lookup_table` (*procstatus*, *dscfg*,
radar_list=None)

Gets HZT data and put it in radar coordinates using look up tables computed or loaded when initializing

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

metranet_read_lib [str. Global keyword] Type of METRANET reader library used to read the data. Can be 'C' or 'python'

datatype [string. Dataset keyword] arbitrary data type

lookup_table [int. Dataset keyword] if set a pre-computed look up table for the COSMO coordinates is loaded. Otherwise the look up table is computed taking the first radar object as reference

regular_grid [int. Dataset keyword] if set it is assume that the radar has a grid constant in time and therefore there is no need to interpolate the COSMO field in memory to the current radar grid

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

PYRAD.PROC.PROCESS_DEM

Functions to manage DEM data

<code>process_dem(procstatus, dscfg[, radar_list])</code>	Gets COSMO data and put it in radar coordinates
<code>process_visibility(procstatus, dscfg[, ...])</code>	Gets the visibility in percentage from the minimum visible elevation.

`pyrad.proc.process_dem.process_dem(procstatus, dscfg, radar_list=None)`
Gets COSMO data and put it in radar coordinates

Parameters

- procstatus** [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
- dscfg** [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
- datatype** [string. Dataset keyword] arbitrary data type
 - keep_in_memory** [int. Dataset keyword] if set keeps the COSMO data dict, the COSMO coordinates dict and the COSMO field in radar coordinates in memory. Default False
 - regular_grid** [int. Dataset keyword] if set it is assume that the radar has a grid constant in time and there is no need to compute a new COSMO field if the COSMO data has not changed. Default False
 - dem_field** [str. Dataset keyword] name of the DEM field to process
 - demfile** [str. Dataset keyword] Name of the file containing the DEM data
- radar_list** [list of Radar objects] Optional. list of radar objects

Returns

- new_dataset** [dict] dictionary containing the output
- ind_rad** [int] radar index

`pyrad.proc.process_dem.process_visibility(procstatus, dscfg, radar_list=None)`
Gets the visibility in percentage from the minimum visible elevation. Anything with elevation lower than the minimum visible elevation plus and offset is set to 0 while above is set to 100.

Parameters

- procstatus** [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
- dscfg** [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
- datatype** [string. Dataset keyword] arbitrary data type
 - offset** [float. Dataset keyword] The offset above the minimum visibility that must be filtered

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

PYRAD.PROC.PROCESS_DOPPLER

Functions for processing Doppler related parameters

<code>process_turbulence(procstatus, dscfg[, ...])</code>	Computes turbulence from the Doppler spectrum width and reflectivity using the PyTDA package
<code>process_dealias_fourdd(procstatus, dscfg[, ...])</code>	Dealiases the Doppler velocity field using the 4DD technique from Curtis and Houze, 2001
<code>process_dealias_region_based(procstatus, dscfg)</code>	Dealiases the Doppler velocity field using a region based algorithm
<code>process_dealias_unwrap_phase(procstatus, dscfg)</code>	Dealiases the Doppler velocity field using multi-dimensional phase unwrapping
<code>process_wind_vel(procstatus, dscfg[, radar_list])</code>	Estimates the horizontal or vertical component of the wind from the radial velocity
<code>process_windshear(procstatus, dscfg[, ...])</code>	Estimates the wind shear from the wind velocity
<code>process_vad(procstatus, dscfg[, radar_list])</code>	Estimates vertical wind profile using the VAD (velocity Azimuth Display) technique

`pyrad.proc.process_Doppler.process_dealias_fourdd` (*procstatus*, *dscfg*,
radar_list=None)
Dealiases the Doppler velocity field using the 4DD technique from Curtis and Houze, 2001

Parameters

- procstatus** [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
- dscfg** [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
 - datatype** [string. Dataset keyword] The input data type
 - filt** [int. Dataset keyword] Flag controlling Bergen and Albers filter, 1 = yes, 0 = no.
 - sign** [int. Dataset keyword] Sign convention which the radial velocities in the volume created from the sounding data will will. This should match the convention used in the radar data. A value of 1 represents when positive values velocities are towards the radar, -1 represents when negative velocities are towards the radar.
- radar_list** [list of Radar objects] Optional. list of radar objects

Returns

- new_dataset** [dict] dictionary containing the output
- ind_rad** [int] radar index

`pyrad.proc.process_Doppler.process_dealias_region_based` (*procstatus*, *dscfg*,
radar_list=None)
Dealiases the Doppler velocity field using a region based algorithm

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The input data type

interval_splits [int, optional] Number of segments to split the nyquist interval into when finding regions of similar velocity. More splits creates a larger number of initial regions which takes longer to process but may result in better dealiasing. The default value of 3 seems to be a good compromise between performance and artifact free dealiasing. This value is not used if the `interval_limits` parameter is not None.

skip_between_rays, skip_along_ray [int, optional] Maximum number of filtered gates to skip over when joining regions, gaps between region larger than this will not be connected. Parameters specify the maximum number of filtered gates between and along a ray. Set these parameters to 0 to disable unfolding across filtered gates.

centered [bool, optional] True to apply centering to each sweep after the dealiasing algorithm so that the average number of unfolding is near 0. False does not apply centering which may results in individual sweeps under or over folded by the nyquist interval.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_Doppler.process_dealias_unwrap_phase` (*procstatus*, *dscfg*,
radar_list=None)

Dealiases the Doppler velocity field using multi-dimensional phase unwrapping

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The input data type

unwrap_unit [{ 'ray', 'sweep', 'volume' }, optional] Unit to unwrap independently. 'ray' will unwrap each ray individually, 'sweep' each sweep, and 'volume' will unwrap the entire volume in a single pass. 'sweep', the default, often gives superior results when the lower sweeps of the radar volume are contaminated by clutter. 'ray' does not use the `gatefilter` parameter and rays where gates are masked will result in poor dealiasing for that ray.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_Doppler.process_turbulence` (*procstatus*, *dscfg*, *radar_list=None*)

Computes turbulence from the Doppler spectrum width and reflectivity using the PyTDA package

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The input data type

radius [float. Dataset keyword] Search radius for calculating Eddy Dissipation Rate (EDR). Default 2

split_cut [Bool. Dataset keyword] Set to True for split-cut volumes. Default False

max_split_cut [Int. Dataset keyword] Total number of tilts that are affected by split cuts. Only relevant if split_cut=True. Default 2

xran, yran [float array. Dataset keyword] Spatial range in X,Y to consider. Default [-100, 100] for both X and Y

beamwidth [Float. Dataset keyword] Radar beamwidth. Default None. If None it will be obtained from the radar object metadata. If cannot be obtained defaults to 1 deg.

compute_gate_pos [Bool. Dataset keyword] If True the gate position is going to be computed in PyTDA. Otherwise the position from the radar object is used. Default False

verbose [Bool. Dataset keyword] True for verbose output. Default False

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_Doppler.process_vad(procstatus, dscfg, radar_list=None)`
Estimates vertical wind profile using the VAD (velocity Azimuth Display) technique

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The input data type

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_Doppler.process_wind_vel(procstatus, dscfg, radar_list=None)`
Estimates the horizontal or vertical component of the wind from the radial velocity

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The input data type

vert_proj [Boolean] If true the vertical projection is computed. Otherwise the horizontal projection is computed

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_Doppler.process_windshear` (*procstatus, dscfg, radar_list=None*)
Estimates the wind shear from the wind velocity

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
 datatype [string. Dataset keyword] The input data type
 az_tol [float] The tolerance in azimuth when looking for gates on top of the gate when computation is performed
radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output
ind_rad [int] radar index

PYRAD.PROC.PROCESS_ECHOCCLASS

Functions for echo classification and filtering

<i>process_echo_id</i> (procstatus, dscfg[, radar_list])	identifies echoes as 0: No data, 1: Noise, 2: Clutter, 3: Precipitation
<i>process_birds_id</i> (procstatus, dscfg[, radar_list])	identifies echoes as 0: No data, 1: Noise, 2: Clutter, 3: Birds
<i>process_clt_to_echo_id</i> (procstatus, dscfg[, ...])	Converts clutter exit code from rad4alp into pyrad echo ID
<i>process_echo_filter</i> (procstatus, dscfg[, ...])	Masks all echo types that are not of the class specified in keyword <i>echo_type</i>
<i>process_cdf</i> (procstatus, dscfg[, radar_list])	Collects the fields necessary to compute the Cumulative Distribution Function
<i>process_filter_snr</i> (procstatus, dscfg[, ...])	filters out low SNR echoes
<i>process_filter_vel_diff</i> (procstatus, dscfg[, ...])	filters out range gates that could not be used for Doppler velocity estimation
<i>process_filter_visibility</i> (procstatus, dscfg)	filters out rays gates with low visibility and corrects the reflectivity
<i>process_outlier_filter</i> (procstatus, dscfg[, ...])	filters out gates which are outliers respect to the surrounding
<i>process_hydroclass</i> (procstatus, dscfg[, ...])	Classifies precipitation echoes
<i>process_melting_layer</i> (procstatus, dscfg[, ...])	Detects the melting layer
<i>process_zdr_column</i> (procstatus, dscfg[, ...])	Detects ZDR columns

`pyrad.proc.process_echoclass.process_birds_id` (*procstatus*, *dscfg*, *radar_list=None*)
 identifies echoes as 0: No data, 1: Noise, 2: Clutter, 3: Birds

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
 datatype [list of string. Dataset keyword] The input data types
radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output
ind_rad [int] radar index

`pyrad.proc.process_echoclass.process_cdf` (*procstatus*, *dscfg*, *radar_list=None*)
 Collects the fields necessary to compute the Cumulative Distribution Function

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
 datatype [list of string. Dataset keyword] The input data types
radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output
ind_rad [int] radar index

`pyrad.proc.process_echoclass.process_clt_to_echo_id(procstatus, dscfg, radar_list=None)`

Converts clutter exit code from rad4alp into pyrad echo ID

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
 datatype [list of string. Dataset keyword] The input data types
radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output
ind_rad [int] radar index

`pyrad.proc.process_echoclass.process_echo_filter(procstatus, dscfg, radar_list=None)`
 Masks all echo types that are not of the class specified in keyword echo_type

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
 datatype [list of string. Dataset keyword] The input data types
 echo_type [int or list of ints] The type of echoes to keep: 1 noise, 2 clutter, 3 precipitation.
 Default 3
radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output
ind_rad [int] radar index

`pyrad.proc.process_echoclass.process_echo_id(procstatus, dscfg, radar_list=None)`
 identifies echoes as 0: No data, 1: Noise, 2: Clutter, 3: Precipitation

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
 datatype [list of string. Dataset keyword] The input data types
radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_echoclass.process_filter_snr` (*procstatus*, *dscfg*, *radar_list=None*)
filters out low SNR echoes

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

SNRmin [float. Dataset keyword] The minimum SNR to keep the data.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_echoclass.process_filter_vel_diff` (*procstatus*, *dscfg*,
radar_list=None)
filters out range gates that could not be used for Doppler velocity estimation

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_echoclass.process_filter_visibility` (*procstatus*, *dscfg*,
radar_list=None)
filters out rays gates with low visibility and corrects the reflectivity

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

VISmin [float. Dataset keyword] The minimum visibility to keep the data.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_echoclass.process_hydroclass` (*procstatus, dscfg, radar_list=None*)
Classifies precipitation echoes

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

- datatype** [list of string. Dataset keyword] The input data types
- HYDRO_METHOD** [string. Dataset keyword] The hydrometeor classification method. One of the following: SEMISUPERVISED
- RADARCENTROIDS** [string. Dataset keyword] Used with HYDRO_METHOD SEMISUPERVISED. The name of the radar of which the derived centroids will be used. One of the following: A Albis, L Lema, P Plaine Morte, DX50
- compute_entropy** [bool. Dataset keyword] If true the entropy is computed and the field `hydroclass_entropy` is output
- output_distances** [bool. Dataset keyword] If true the de-mixing algorithm based on the distances to the centroids is computed and the field proportions of each hydrometeor in the radar range gate is output
- vectorize** [bool. Dataset keyword] If true a vectorized version of the algorithm is used

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_echoclass.process_melting_layer` (*procstatus, dscfg, radar_list=None*)

Detects the melting layer

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

- datatype** [list of string. Dataset keyword] The input data types

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_echoclass.process_outlier_filter` (*procstatus, dscfg, radar_list=None*)

filters out gates which are outliers respect to the surrounding

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

- datatype** [list of string. Dataset keyword] The input data types

threshold [float. Dataset keyword] The distance between the value of the examined range gate and the median of the surrounding gates to consider the gate an outlier

nb [int. Dataset keyword] The number of neighbours (to one side) to analyse. i.e. 2 would correspond to 24 gates

nb_min [int. Dataset keyword] Minimum number of neighbouring gates to consider the examined gate valid

percentile_min, percentile_max [float. Dataset keyword] gates below (above) these percentiles (computed over the sweep) are considered potential outliers and further examined

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_echoclass.process_zdr_column(procstatus, dscfg, radar_list=None)`
Detects ZDR columns

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

PYRAD.PROC.PROCESS_GRID

Functions to processes gridded data.

<i>process_raw_grid</i> (procstatus, dscfg[, radar_list])	Dummy function that returns the initial input data set
<i>process_grid</i> (procstatus, dscfg[, radar_list])	Puts the radar data in a regular grid
<i>process_grid_point</i> (procstatus, dscfg[, ...])	Obtains the grid data at a point location.
<i>process_grid_time_stats</i> (procstatus, dscfg[, ...])	computes the temporal statistics of a field
<i>process_grid_time_stats2</i> (procstatus, dscfg)	computes the temporal mean of a field

pyrad.proc.process_grid.**process_grid** (*procstatus, dscfg, radar_list=None*)
 Puts the radar data in a regular grid

Parameters

- procstatus** [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
- dscfg** [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
 - datatype** [string. Dataset keyword] The data type where we want to extract the point measurement
 - gridconfig** [dictionary. Dataset keyword] Dictionary containing some or all of this keywords: xmin, xmax, ymin, ymax, zmin, zmax : floats
 - minimum and maximum horizontal distance from grid origin [km] and minimum and maximum vertical distance from grid origin [m] Defaults -40, 40, -40, 40, 0., 10000.
 - hres, vres** [floats] horizontal and vertical grid resolution [m] Defaults 1000., 500.
 - latorig, lonorig, altorig** [floats] latitude and longitude of grid origin [deg] and altitude of grid origin [m MSL] Defaults the latitude, longitude and altitude of the radar
- wfunc** [str. Dataset keyword] the weighting function used to combine the radar gates close to a grid point. Possible values BARNES, BARNES2, CRESSMAN, NEAREST Default NEAREST
- roif_func** [str. Dataset keyword] the function used to compute the region of interest. Possible values: dist_beam, constant
- roi** [float. Dataset keyword] the (minimum) radius of the region of interest in m. Default half the largest resolution

beamwidth [float. Dataset keyword] the radar antenna beamwidth [deg]. If None that of the key `radar_beam_width_h` in attribute `instrument_parameters` of the radar object will be used. If the key or the attribute are not present a default 1 deg value will be used

beam_spacing [float. Dataset keyword] the beam spacing, i.e. the ray angle resolution [deg]. If None, that of the attribute `ray_angle_res` of the radar object will be used. If the attribute is None a default 1 deg value will be used

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the gridded data

ind_rad [int] radar index

`pyrad.proc.process_grid.process_grid_point` (*procstatus, dscfg, radar_list=None*)

Obtains the grid data at a point location.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The data type where we want to extract the point measurement

latlon [boolean. Dataset keyword] if True position is obtained from latitude, longitude information, otherwise position is obtained from grid index (*iz, iy, ix*).

lon [float. Dataset keyword] the longitude [deg]. Use when `latlon` is True.

lat [float. Dataset keyword] the latitude [deg]. Use when `latlon` is True.

alt [float. Dataset keyword] altitude [m MSL]. Use when `latlon` is True.

iz, iy, ix [int. Dataset keyword] The grid indices. Use when `latlon` is False

latlonTol [float. Dataset keyword] latitude-longitude tolerance to determine which grid point to use [deg]

altTol [float. Dataset keyword] Altitude tolerance to determine which grid point to use [deg]

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the data and metadata at the point of interest

ind_rad [int] radar index

`pyrad.proc.process_grid.process_grid_time_stats` (*procstatus, dscfg, radar_list=None*)

computes the temporal statistics of a field

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

period [float. Dataset keyword] the period to average [s]. If -1 the statistics are going to be performed over the entire data. Default 3600.

start_average [float. Dataset keyword] when to start the average [s from midnight UTC]. Default 0.

lin_trans: int. Dataset keyword If 1 apply linear transformation before averaging

use_nan [bool. Dataset keyword] If true non valid data will be used

nan_value [float. Dataset keyword] The value of the non valid data. Default 0

stat: string. Dataset keyword Statistic to compute: Can be mean, std, cov, min, max. Default mean

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_grid.process_grid_time_stats2` (*procstatus, dscfg, radar_list=None*)
computes the temporal mean of a field

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

period [float. Dataset keyword] the period to average [s]. If -1 the statistics are going to be performed over the entire data. Default 3600.

start_average [float. Dataset keyword] when to start the average [s from midnight UTC]. Default 0.

stat: string. Dataset keyword Statistic to compute: Can be median, mode, percentileXX

use_nan [bool. Dataset keyword] If true non valid data will be used

nan_value [float. Dataset keyword] The value of the non valid data. Default 0

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_grid.process_raw_grid` (*procstatus, dscfg, radar_list=None*)
Dummy function that returns the initial input data set

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

PYRAD.PROC.PROCESS_INTERCOMP

Functions used in the inter-comparison between radars

<i>process_time_stats</i> (procstatus, dscfg[, ...])	computes the temporal statistics of a field
<i>process_time_stats2</i> (procstatus, dscfg[, ...])	computes the temporal mean of a field
<i>process_time_avg</i> (procstatus, dscfg[, radar_list])	computes the temporal mean of a field
<i>process_weighted_time_avg</i> (procstatus, dscfg)	computes the temporal mean of a field weighted by the reflectivity
<i>process_time_avg_flag</i> (procstatus, dscfg[, ...])	computes a flag field describing the conditions of the data used while averaging
<i>process_colocated_gates</i> (procstatus, dscfg[, ...])	Find colocated gates within two radars
<i>process_intercomp</i> (procstatus, dscfg[, ...])	intercomparison between two radars
<i>process_intercomp_time_avg</i> (procstatus, dscfg)	intercomparison between the average reflectivity of two radars
<i>process_fields_diff</i> (procstatus, dscfg[, ...])	Computes the field difference between RADAR001 and radar002, i.e.
<i>process_intercomp_fields</i> (procstatus, dscfg)	intercomparison between two radars

pyrad.proc.process_intercomp.**process_colocated_gates** (*procstatus*, *dscfg*,
radar_list=None)
Find colocated gates within two radars

Parameters

- procstatus** [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
- dscfg** [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
 - datatype** [list of string. Dataset keyword] The input data types
 - h_tol** [float. Dataset keyword] Tolerance in altitude difference between radar gates [m]. Default 100.
 - latlon_tol** [float. Dataset keyword] Tolerance in latitude and longitude position between radar gates [deg]. Default 0.0005
 - vol_d_tol** [float. Dataset keyword] Tolerance in pulse volume diameter [m]. Default 100.
 - vismin** [float. Dataset keyword] Minimum visibility [percent]. Default None.
 - hmin** [float. Dataset keyword] Minimum altitude [m MSL]. Default None.
 - hmax** [float. Dataset keyword] Maximum altitude [m MSL]. Default None.
 - rmin** [float. Dataset keyword] Minimum range [m]. Default None.

rmax [float. Dataset keyword] Maximum range [m]. Default None.

elmin [float. Dataset keyword] Minimum elevation angle [deg]. Default None.

elmax [float. Dataset keyword] Maximum elevation angle [deg]. Default None.

azrad1min [float. Dataset keyword] Minimum azimuth angle [deg] for radar 1. Default None.

azrad1max [float. Dataset keyword] Maximum azimuth angle [deg] for radar 1. Default None.

azrad2min [float. Dataset keyword] Minimum azimuth angle [deg] for radar 2. Default None.

azrad2max [float. Dataset keyword] Maximum azimuth angle [deg] for radar 2. Default None.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [radar object] radar object containing the flag field

ind_rad [int] radar index

`pyrad.proc.process_intercomp.process_fields_diff(procstatus, dscfg, radar_list=None)`

Computes the field difference between RADAR001 and radar002, i.e. RADAR001-RADAR002. Assumes both radars have the same geometry

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing a radar object containing the field differences

ind_rad [int] radar index

`pyrad.proc.process_intercomp.process_intercomp(procstatus, dscfg, radar_list=None)`

intercomparison between two radars

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

coloc_data_dir [string. Dataset keyword] name of the directory containing the csv file with colocated data

coloc_radars_name [string. Dataset keyword] string identifying the radar names

azi_tol [float. Dataset keyword] azimuth tolerance between the two radars. Default 0.5 deg

ele_tol [float. Dataset keyword] elevation tolerance between the two radars. Default 0.5 deg

rng_tol [float. Dataset keyword] range tolerance between the two radars. Default 50 m

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing a dictionary with intercomparison data and the key “final” which contains a boolean that is true when all volumes have been processed

ind_rad [int] radar index

`pyrad.proc.process_intercomp.process_intercomp_fields` (*procstatus*, *dscfg*,
radar_list=None)

intercomparison between two radars

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing a dictionary with intercomparison data

ind_rad [int] radar index

`pyrad.proc.process_intercomp.process_intercomp_time_avg` (*procstatus*, *dscfg*,
radar_list=None)

intercomparison between the average reflectivity of two radars

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

coloc_data_dir [string. Dataset keyword] name of the directory containing the csv file with colocated data

coloc_radars_name [string. Dataset keyword] string identifying the radar names

azi_tol [float. Dataset keyword] azimuth tolerance between the two radars. Default 0.5 deg

ele_tol [float. Dataset keyword] elevation tolerance between the two radars. Default 0.5 deg

rng_tol [float. Dataset keyword] range tolerance between the two radars. Default 50 m

clt_max [int. Dataset keyword] maximum number of samples that can be clutter contaminated. Default 100 i.e. all

phi_excess_max [int. Dataset keyword] maximum number of samples that can have excess instantaneous PhiDP. Default 100 i.e. all

non_rain_max [int. Dataset keyword] maximum number of samples that can be no rain. Default 100 i.e. all

phi_avg_max [float. Dataset keyword] maximum average PhiDP allowed. Default 600 deg i.e. any

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing a dictionary with intercomparison data and the key “final” which contains a boolean that is true when all volumes have been processed

ind_rad [int] radar index

`pyrad.proc.process_intercomp.process_time_avg(procstatus, dscfg, radar_list=None)`
computes the temporal mean of a field

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

period [float. Dataset keyword] the period to average [s]. Default 3600.

start_average [float. Dataset keyword] when to start the average [s from midnight UTC]. Default 0.

lin_trans: int. Dataset keyword If 1 apply linear transformation before averaging

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_intercomp.process_time_avg_flag(procstatus, dscfg, radar_list=None)`
computes a flag field describing the conditions of the data used while averaging

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

period [float. Dataset keyword] the period to average [s]. Default 3600.

start_average [float. Dataset keyword] when to start the average [s from midnight UTC]. Default 0.

phidpmax: float. Dataset keyword maximum PhiDP

beamwidth [float. Dataset keyword] the antenna beamwidth [deg]. If None that of the keys `radar_beam_width_h` or `radar_beam_width_v` in attribute `instrument_parameters` of the radar object will be used. If the key or the attribute are not present the beamwidth will be set to None

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [Radar] radar object

ind_rad [int] radar index

`pyrad.proc.process_intercomp.process_time_stats(procstatus, dscfg, radar_list=None)`
computes the temporal statistics of a field

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

period [float. Dataset keyword] the period to average [s]. If -1 the statistics are going to be performed over the entire data. Default 3600.

start_average [float. Dataset keyword] when to start the average [s from midnight UTC]. Default 0.

lin_trans: int. Dataset keyword If 1 apply linear transformation before averaging

use_nan [bool. Dataset keyword] If true non valid data will be used

nan_value [float. Dataset keyword] The value of the non valid data. Default 0

stat: string. Dataset keyword Statistic to compute: Can be mean, std, cov, min, max. Default mean

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_intercomp.process_time_stats2(procstatus, dscfg, radar_list=None)`
computes the temporal mean of a field

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

period [float. Dataset keyword] the period to average [s]. If -1 the statistics are going to be performed over the entire data. Default 3600.

start_average [float. Dataset keyword] when to start the average [s from midnight UTC]. Default 0.

stat: string. Dataset keyword Statistic to compute: Can be median, mode, percentileXX

use_nan [bool. Dataset keyword] If true non valid data will be used

nan_value [float. Dataset keyword] The value of the non valid data. Default 0

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_intercomp.process_weighted_time_avg(procstatus, dscfg, radar_list=None)`
computes the temporal mean of a field weighted by the reflectivity

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

period [float. Dataset keyword] the period to average [s]. Default 3600.

start_average [float. Dataset keyword] when to start the average [s from midnight UTC].
Default 0.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [Radar] radar object

ind_rad [int] radar index

PYRAD.PROC.PROCESS_IQ

Functions to processes IQ data.

<i>process_raw_iq</i> (procstatus, dscfg[, radar_list])	Dummy function that returns the initial input data set
<i>process_pol_variables_iq</i> (procstatus, dscfg)	Computes the polarimetric variables from the IQ data
<i>process_reflectivity_iq</i> (procstatus, dscfg[, ...])	Computes reflectivity from the IQ data
<i>process_st1_iq</i> (procstatus, dscfg[, radar_list])	Computes the statistical test one lag fluctuation from the horizontal or vertical IQ data
<i>process_st2_iq</i> (procstatus, dscfg[, radar_list])	Computes the statistical test two lag fluctuation from the horizontal or vertical IQ data
<i>process_wbn_iq</i> (procstatus, dscfg[, radar_list])	Computes the wide band noise from the horizontal or vertical IQ data
<i>process_differential_reflectivity_iq</i> (...)	Computes differential reflectivity from the horizontal and vertical IQ data
<i>process_mean_phase_iq</i> (procstatus, dscfg[, ...])	Computes the mean phase from the horizontal or vertical IQ data
<i>process_differential_phase_iq</i> (procstatus, dscfg)	Computes the differential phase from the horizontal and vertical IQ data
<i>process_rhoHV_iq</i> (procstatus, dscfg[, radar_list])	Computes RhoHV from the horizontal and vertical IQ data
<i>process_Doppler_velocity_iq</i> (procstatus, dscfg)	Compute the Doppler velocity from the spectral reflectivity
<i>process_Doppler_width_iq</i> (procstatus, dscfg)	Compute the Doppler spectrum width from the spectral reflectivity
<i>process_fft</i> (procstatus, dscfg[, radar_list])	Compute the Doppler spectra form the IQ data with a Fourier transform

pyrad.proc.process_iq.**process_Doppler_velocity_iq**(*procstatus*, *dscfg*,
radar_list=None)

Compute the Doppler velocity from the spectral reflectivity

Parameters

- procstatus** [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
- dscfg** [dictionary of dictionaries] data set configuration. Accepted configuration keywords:
 - datatype** [list of string. Dataset keyword] The input data types
 - direction** [str] The convention used in the Doppler mean field. Can be negative_away or negative_towards
- radar_list** [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_iq.process_Doppler_width_iq(procstatus, dscfg, radar_list=None)`

Compute the Doppler spectrum width from the spectral reflectivity

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:

datatype [list of string. Dataset keyword] The input data types

subtract_noise [Bool] If True noise will be subtracted from the signals

lag [int] Time lag used in the denominator of the computation

radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_iq.process_differential_phase_iq(procstatus, dscfg, radar_list=None)`

Computes the differential phase from the horizontal and vertical IQ data

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:

datatype [list of string. Dataset keyword] The input data types

phase_offset [float. Dataset keyword] The system differential phase offset to remove

radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_iq.process_differential_reflectivity_iq(procstatus, dscfg, radar_list=None)`

Computes differential reflectivity from the horizontal and vertical IQ data

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:

datatype [list of string. Dataset keyword] The input data types

subtract_noise [Bool] If True noise will be subtracted from the signal

lag [int] The time lag to use in the estimators

radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_iq.process_fft(procstatus, dscfg, radar_list=None)`

Compute the Doppler spectra from the IQ data with a Fourier transform

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:

datatype [list of string. Dataset keyword] The input data types

window [list of str] Parameters of the window used to obtain the spectra. The parameters are the ones corresponding to function `scipy.signal.windows.get_window`. It can also be `['None']`.

radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_iq.process_mean_phase_iq(procstatus, dscfg, radar_list=None)`

Computes the mean phase from the horizontal or vertical IQ data

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:

datatype [list of string. Dataset keyword] The input data types

radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_iq.process_pol_variables_iq(procstatus, dscfg, radar_list=None)`

Computes the polarimetric variables from the IQ data

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:

datatype [list of string. Dataset keyword] The input data types

subtract_noise [Bool] If True noise will be subtracted from the signal

lag [int] The time lag to use in the estimators

direction [str] The convention used in the Doppler mean field. Can be `negative_away` or `negative_towards`

variables [list of str] list of variables to compute. Default dBZ

phase_offset [float. Dataset keyword] The system differential phase offset to remove

radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output
ind_rad [int] radar index

`pyrad.proc.process_iq.process_raw_iq(procstatus, dscfg, radar_list=None)`
Dummy function that returns the initial input data set

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
dscfg [dictionary of dictionaries] data set configuration
radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output
ind_rad [int] radar index

`pyrad.proc.process_iq.process_reflectivity_iq(procstatus, dscfg, radar_list=None)`
Computes reflectivity from the IQ data

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:
 datatype [list of string. Dataset keyword] The input data types
 subtract_noise [Bool] If True noise will be subtracted from the signal
radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output
ind_rad [int] radar index

`pyrad.proc.process_iq.process_rhoHV_iq(procstatus, dscfg, radar_list=None)`
Computes RhoHV from the horizontal and vertical IQ data

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:
 datatype [list of string. Dataset keyword] The input data types
 subtract_noise [Bool] If True noise will be subtracted from the signal
 lag [int] Time lag used in the computation
radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output
ind_rad [int] radar index

`pyrad.proc.process_iq.process_st1_iq(procstatus, dscfg, radar_list=None)`
Computes the statistical test one lag fluctuation from the horizontal or vertical IQ data

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:
 datatype [list of string. Dataset keyword] The input data types
radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output
ind_rad [int] radar index

`pyrad.proc.process_iq.process_st2_iq(procstatus, dscfg, radar_list=None)`
Computes the statistical test two lag fluctuation from the horizontal or vertical IQ data

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:
 datatype [list of string. Dataset keyword] The input data types
radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output
ind_rad [int] radar index

`pyrad.proc.process_iq.process_wbn_iq(procstatus, dscfg, radar_list=None)`
Computes the wide band noise from the horizontal or vertical IQ data

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:
 datatype [list of string. Dataset keyword] The input data types
radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output
ind_rad [int] radar index

PYRAD.PROC.PROCESS_MONITORING

Functions for monitoring of the polarimetric variables

<i>process_selfconsistency_kdp_phidp</i> (..., ...)	Computes specific differential phase and differential phase in rain using the selfconsistency between Zdr, Zh and KDP
<i>process_selfconsistency_bias</i> (procstatus, dscfg)	Estimates the reflectivity bias by means of the selfconsistency algorithm by Gourley
<i>process_selfconsistency_bias2</i> (procstatus, dscfg)	Estimates the reflectivity bias by means of the selfconsistency algorithm by Gourley
<i>process_estimate_phidp0</i> (procstatus, dscfg[, ...])	estimates the system differential phase offset at each ray
<i>process_rhohv_rain</i> (procstatus, dscfg[, ...])	Keeps only suitable data to evaluate the 80 percentile of RhoHV in rain
<i>process_zdr_precip</i> (procstatus, dscfg[, ...])	Keeps only suitable data to evaluate the differential reflectivity in moderate rain or precipitation (for vertical scans)
<i>process_zdr_snow</i> (procstatus, dscfg[, radar_list])	Keeps only suitable data to evaluate the differential reflectivity in snow
<i>process_monitoring</i> (procstatus, dscfg[, ...])	computes monitoring statistics

`pyrad.proc.process_monitoring.process_estimate_phidp0` (*procstatus*, *dscfg*,
radar_list=None)
estimates the system differential phase offset at each ray

Parameters

- procstatus** [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
- dscfg** [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
- datatype** [list of string. Dataset keyword] The input data types
 - rmin** [float. Dataset keyword] The minimum range where to look for valid data [m]
 - rmax** [float. Dataset keyword] The maximum range where to look for valid data [m]
 - rcell** [float. Dataset keyword] The length of a continuous cell to consider it valid precip [m]
 - Zmin** [float. Dataset keyword] The minimum reflectivity [dBZ]
 - Zmax** [float. Dataset keyword] The maximum reflectivity [dBZ]
- radar_list** [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_monitoring.process_monitoring(procstatus, dscfg, radar_list=None)`
computes monitoring statistics

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

step [float. Dataset keyword] The width of the histogram bin. Default is None. In that case the default step in function `get_histogram_bins` is used

max_rays [int. Dataset keyword] The maximum number of rays per sweep used when computing the histogram. If set above 0 the number of rays per sweep will be checked and if above **max_rays** the last rays of the sweep will be removed

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [Radar] radar object containing histogram data

ind_rad [int] radar index

`pyrad.proc.process_monitoring.process_rhoHV_rain(procstatus, dscfg, radar_list=None)`
Keeps only suitable data to evaluate the 80 percentile of RhoHV in rain

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

rmin [float. Dataset keyword] minimum range where to look for rain [m]. Default 1000.

rmax [float. Dataset keyword] maximum range where to look for rain [m]. Default 50000.

Zmin [float. Dataset keyword] minimum reflectivity to consider the bin as precipitation [dBZ]. Default 20.

Zmax [float. Dataset keyword] maximum reflectivity to consider the bin as precipitation [dBZ] Default 40.

ml_thickness [float. Dataset keyword] assumed thickness of the melting layer. Default 700.

fzl [float. Dataset keyword] The default freezing level height. It will be used if no temperature field name is specified or the temperature field is not in the radar object. Default 2000.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_monitoring.process_selfconsistency_bias` (*procstatus*, *dscfg*,
radar_list=None)

Estimates the reflectivity bias by means of the selfconsistency algorithm by Gourley

Parameters

- procstatus** [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
- dscfg** [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
- datatype** [list of string. Dataset keyword] The input data types
 - parametrization** [str] The type of parametrization for the self-consistency curves. Can be 'None', 'Gourley', 'Wolfensberger', 'Louf', 'Gorgucci' or 'Vaccarono' 'None' will use tables from config files. Default 'None'.
 - fzl** [float. Dataset keyword] Default freezing level height. Default 2000.
 - rsmooth** [float. Dataset keyword] length of the smoothing window [m]. Default 2000.
 - min_rhohv** [float. Dataset keyword] minimum valid RhoHV. Default 0.92
 - filter_rain** [Bool. Dataset keyword] If True the hydrometeor classification is used to filter out gates that are not rain. Default True
 - max_phidp** [float. Dataset keyword] maximum valid PhiDP [deg]. Default 20.
 - ml_thickness** [float. Dataset keyword] Melting layer thickness [m]. Default 700.
 - rcell** [float. Dataset keyword] length of continuous precipitation to consider the precipitation cell a valid phidp segment [m]. Default 15000.
 - dphidp_min** [float. Dataset keyword] minimum phase shift [deg]. Default 2.
 - dphidp_max** [float. Dataset keyword] maximum phase shift [deg]. Default 16.
 - frequency** [float. Dataset keyword] the radar frequency [Hz]. If None that of the key frequency in attribute `instrument_parameters` of the radar object will be used. If the key or the attribute are not present the selfconsistency will not be computed
 - check_wet_radome** [Bool. Dataset keyword] if True the average reflectivity of the closest gates to the radar is going to be check to find out whether there is rain over the radome. If there is rain no bias will be computed. Default True.
 - wet_radome_refl** [Float. Dataset keyword] Average reflectivity [dBZ] of the gates close to the radar to consider the radome as wet. Default 25.
 - wet_radome_rng_min, wet_radome_rng_max** [Float. Dataset keyword] Min and max range [m] of the disk around the radar used to compute the average reflectivity to determine whether the radome is wet. Default 2000 and 4000.
 - wet_radome_ngates_min** [int] Minimum number of valid gates to consider that the radome is wet. Default 180
 - valid_gates_only** [Bool] If True the reflectivity bias obtained for each valid ray is going to be assigned only to gates of the segment used. That will give more weight to longer segments when computing the total bias. Default False
 - keep_points** [Bool] If True the ZDR, ZH and KDP of the gates used in the self-consistency algorithm are going to be stored for further analysis. Default False
 - rkdp** [float] The length of the window used to compute KDP with the single window least square method [m]. Default 6000.
 - radar_list** [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_monitoring.process_selfconsistency_bias2` (*procstatus*, *dscfg*,
radar_list=None)

Estimates the reflectivity bias by means of the selfconsistency algorithm by Gourley

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

parametrization [str] The type of parametrization for the self-consistency curves. Can be 'None', 'Gourley', 'Wolfensberger', 'Louf', 'Gorgucci' or 'Vaccarono' 'None' will use tables from config files. Default 'None'.

fzl [float. Dataset keyword] Default freezing level height. Default 2000.

rsmooth [float. Dataset keyword] length of the smoothing window [m]. Default 2000.

min_rhohv [float. Dataset keyword] minimum valid RhoHV. Default 0.92

filter_rain [Bool. Dataset keyword] If True the hydrometeor classification is used to filter out gates that are not rain. Default True

max_phidp [float. Dataset keyword] maximum valid PhiDP [deg]. Default 20.

ml_thickness [float. Dataset keyword] Melting layer thickness [m]. Default 700.

rcell [float. Dataset keyword] length of continuous precipitation to consider the precipitation cell a valid phidp segment [m]. Default 15000.

frequency [float. Dataset keyword] the radar frequency [Hz]. If None that of the key frequency in attribute `instrument_parameters` of the radar object will be used. If the key or the attribute are not present the selfconsistency will not be computed

check_wet_radome [Bool. Dataset keyword] if True the average reflectivity of the closest gates to the radar is going to be check to find out whether there is rain over the radome. If there is rain no bias will be computed. Default True.

wet_radome_refl [Float. Dataset keyword] Average reflectivity [dBZ] of the gates close to the radar to consider the radome as wet. Default 25.

wet_radome_rng_min, wet_radome_rng_max [Float. Dataset keyword] Min and max range [m] of the disk around the radar used to compute the average reflectivity to determine whether the radome is wet. Default 2000 and 4000.

wet_radome_ngates_min [int] Minimum number of valid gates to consider that the radome is wet. Default 180

keep_points [Bool] If True the ZDR, ZH and KDP of the gates used in the self-consistency algorithm are going to be stored for further analysis. Default False

bias_per_gate [Bool] If True the bias per gate will be computed

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_monitoring.process_selfconsistency_kdp_phidp` (*procstatus*,
dscfg,
radar_list=None)

Computes specific differential phase and differential phase in rain using the selfconsistency between Zdr, Zh and KDP

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of strings. Dataset keyword] The input data types

parametrization [str] The type of parametrization for the self-consistency curves. Can be 'None', 'Gourley', 'Wolfensberger', 'Louf', 'Gorgucci' or 'Vaccarono' 'None' will use tables from config files. Default 'None'.

rsmooth [float. Dataset keyword] length of the smoothing window [m]. Default 2000.

min_rhohv [float. Dataset keyword] minimum valid RhoHV. Default 0.92

filter_rain [Bool. Dataset keyword] If True the hydrometeor classification is used to filter out gates that are not rain. Default True

max_phidp [float. Dataset keyword] maximum valid PhiDP [deg]. Default 20.

ml_thickness [float. Dataset keyword] assumed melting layer thickness [m]. Default 700.

fzl [float. Dataset keyword] The default freezing level height. It will be used if no temperature field name is specified or the temperature field is not in the radar object. Default 2000.

frequency [float. Dataset keyword] the radar frequency [Hz]. If None that of the key frequency in attribute `instrument_parameters` of the radar object will be used. If the key or the attribute are not present the selfconsistency will not be computed

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_monitoring.process_zdr_precip` (*procstatus*, *dscfg*, *radar_list=None*)

Keeps only suitable data to evaluate the differential reflectivity in moderate rain or precipitation (for vertical scans)

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

ml_filter [boolean. Dataset keyword] indicates if a filter on data in and above the melting layer is applied. Default True.

rmin [float. Dataset keyword] minimum range where to look for rain [m]. Default 1000.

rmax [float. Dataset keyword] maximum range where to look for rain [m]. Default 50000.

Zmin [float. Dataset keyword] minimum reflectivity to consider the bin as precipitation [dBZ]. Default 20.

Zmax [float. Dataset keyword] maximum reflectivity to consider the bin as precipitation [dBZ] Default 22.

RhoHVmin [float. Dataset keyword] minimum RhoHV to consider the bin as precipitation Default 0.97

PhiDPmax [float. Dataset keyword] maximum PhiDP to consider the bin as precipitation [deg] Default 10.

elmax [float. Dataset keyword] maximum elevation angle where to look for precipitation [deg] Default None.

ml_thickness [float. Dataset keyword] assumed thickness of the melting layer. Default 700.

fzl [float. Dataset keyword] The default freezing level height. It will be used if no temperature field name is specified or the temperature field is not in the radar object. Default 2000.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_monitoring.process_zdr_snow(procstatus, dscfg, radar_list=None)`

Keeps only suitable data to evaluate the differential reflectivity in snow

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

rmin [float. Dataset keyword] minimum range where to look for rain [m]. Default 1000.

rmax [float. Dataset keyword] maximum range where to look for rain [m]. Default 50000.

Zmin [float. Dataset keyword] minimum reflectivity to consider the bin as snow [dBZ]. Default 0.

Zmax [float. Dataset keyword] maximum reflectivity to consider the bin as snow [dBZ] Default 30.

SNRmin [float. Dataset keyword] minimum SNR to consider the bin as snow [dB]. Default 10.

SNRmax [float. Dataset keyword] maximum SNR to consider the bin as snow [dB] Default 50.

RhoHVmin [float. Dataset keyword] minimum RhoHV to consider the bin as snow Default 0.97

PhiDPmax [float. Dataset keyword] maximum PhiDP to consider the bin as snow [deg] Default 10.

elmax [float. Dataset keyword] maximum elevation angle where to look for snow [deg] Default None.

KDPmax [float. Dataset keyword] maximum KDP to consider the bin as snow [deg] Default None

TEMPmin [float. Dataset keyword] minimum temperature to consider the bin as snow [deg C]. Default None

TEMPmax [float. Dataset keyword] maximum temperature to consider the bin as snow [deg C] Default None

hydroclass [list of ints. Dataset keyword] list of hydrometeor classes to keep for the analysis Default [2] (dry snow)

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

PYRAD.PROC.PROCESS_PHASE

Functions for PhiDP and KDP processing and attenuation correction

<i>process_correct_phidp0</i> (procstatus, dscfg[, ...])	corrects phidp of the system phase
<i>process_smooth_phidp_single_window</i> (...[, ...])	corrects phidp of the system phase and smoothes it using one window
<i>process_smooth_phidp_double_window</i> (...[, ...])	corrects phidp of the system phase and smoothes it using one window
<i>process_kdp_leastsquare_single_window</i> (...[, ...])	Computes specific differential phase using a piecewise least square method
<i>process_kdp_leastsquare_double_window</i> (...[, ...])	Computes specific differential phase using a piecewise least square method
<i>process_phidp_kdp_Vulpiani</i> (procstatus, dscfg)	Computes specific differential phase and differential phase using the method developed by Vulpiani et al.
<i>process_phidp_kdp_Kalman</i> (procstatus, dscfg)	Computes specific differential phase and differential phase using the Kalman filter as proposed by Schneebeli et al.
<i>process_phidp_kdp_Maesaka</i> (procstatus, dscfg)	Estimates PhiDP and KDP using the method by Maesaka.
<i>process_phidp_kdp_lp</i> (procstatus, dscfg[, ...])	Estimates PhiDP and KDP using a linear programming algorithm.
<i>process_selfconsistency_kdp_phidp</i>	
<i>process_selfconsistency_bias</i>	
<i>process_attenuation</i> (procstatus, dscfg[, ...])	Computes specific attenuation and specific differential attenuation using the Z-Phi method and corrects reflectivity and differential reflectivity

pyrad.proc.process_phase.**process_attenuation** (*procstatus, dscfg, radar_list=None*)

Computes specific attenuation and specific differential attenuation using the Z-Phi method and corrects reflectivity and differential reflectivity

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

ATT_METHOD [float. Dataset keyword] The attenuation estimation method used. One of the following: ZPhi, Philin

fzl [float. Dataset keyword] The default freezing level height. It will be used if no temper-

ature field name is specified or the temperature field is not in the radar object. Default 2000.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_phase.process_correct_phidp0` (*procstatus, dscfg, radar_list=None*)
corrects phidp of the system phase

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

rmin [float. Dataset keyword] The minimum range where to look for valid data [m]

rmax [float. Dataset keyword] The maximum range where to look for valid data [m]

rcell [float. Dataset keyword] The length of a continuous cell to consider it valid precip [m]

Zmin [float. Dataset keyword] The minimum reflectivity [dBZ]

Zmax [float. Dataset keyword] The maximum reflectivity [dBZ]

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_phase.process_kdp_leastsquare_double_window` (*procstatus, dscfg, radar_list=None*)

Computes specific differential phase using a piecewise least square method

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

rwinds [float. Dataset keyword] The length of the short segment for the least square method [m]

rwindl [float. Dataset keyword] The length of the long segment for the least square method [m]

Zthr [float. Dataset keyword] The threshold defining which estimated data to use [dBZ]

vectorize [Bool. Dataset keyword] Whether to vectorize the KDP processing. Default false

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_phase.process_kdp_leastsquare_single_window` (*procstatus*,
dscfg,
radar_list=None)

Computes specific differential phase using a piecewise least square method

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
datatype [list of string. Dataset keyword] The input data types
rwind [float. Dataset keyword] The length of the segment for the least square method [m]
vectorize [bool. Dataset keyword] Whether to vectorize the KDP processing. Default false
radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output
ind_rad [int] radar index

`pyrad.proc.process_phase.process_phidp_kdp_Kalman` (*procstatus*,
radar_list=None) *dscfg*,

Computes specific differential phase and differential phase using the Kalman filter as proposed by Schneebeli et al. The data is assumed to be clutter free and continous

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
datatype [list of string. Dataset keyword] The input data types
parallel [boolean. Dataset keyword] if set use parallel computing
get_phidp [boolean. Dataset keyword] if set the PhiDP computed by integrating the resultant KDP is added to the radar field
frequency [float. Dataset keyword] the radar frequency [Hz]. If None that of the key frequency in attribute `instrument_parameters` of the radar object will be used. If the key or the attribute are not present it will be assumed that the radar is C band
radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output
ind_rad [int] radar index

`pyrad.proc.process_phase.process_phidp_kdp_Maesaka` (*procstatus*,
radar_list=None) *dscfg*,

Estimates PhiDP and KDP using the method by Maesaka. This method only retrieves data in rain (i.e. below the melting layer)

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
datatype [list of string. Dataset keyword] The input data types
rmin [float. Dataset keyword] The minimum range where to look for valid data [m]

rmax [float. Dataset keyword] The maximum range where to look for valid data [m]
rcell [float. Dataset keyword] The length of a continuous cell to consider it valid precip [m]
Zmin [float. Dataset keyword] The minimum reflectivity [dBZ]
Zmax [float. Dataset keyword] The maximum reflectivity [dBZ]
fzl [float. Dataset keyword] The freezing level height [m]. Default 2000.
ml_thickness [float. Dataset keyword] The melting layer thickness in meters. Default 700.
beamwidth [float. Dataset keyword] the antenna beamwidth [deg]. If None that of the keys `radar_beam_width_h` or `radar_beam_width_v` in attribute `instrument_parameters` of the radar object will be used. If the key or the attribute are not present the beamwidth will be set to None

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_phase.process_phidp_kdp_Vulpiani` (*procstatus*, *dscfg*,
radar_list=None)

Computes specific differential phase and differential phase using the method developed by Vulpiani et al. The data is assumed to be clutter free and monotonous

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

rwind [float. Dataset keyword] The length of the segment [m]

n_iter [int. Dataset keyword] number of iterations

interp [boolean. Dataset keyword] if set non valid values are interpolated using neighbouring valid values

parallel [boolean. Dataset keyword] if set use parallel computing

get_phidp [boolean. Dataset keyword] if set the PhiDP computed by integrating the resultant KDP is added to the radar field

frequency [float. Dataset keyword] the radar frequency [Hz]. If None that of the key `frequency` in attribute `instrument_parameters` of the radar object will be used. If the key or the attribute are not present it will be assumed that the radar is C band

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_phase.process_phidp_kdp_lp` (*procstatus*, *dscfg*, *radar_list=None*)

Estimates PhiDP and KDP using a linear programming algorithm. This method only retrieves data in rain (i.e. below the melting layer)

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

fzl [float. Dataset keyword] The freezing level height [m]. Default 2000.

ml_thickness [float. Dataset keyword] The melting layer thickness in meters. Default 700.

beamwidth [float. Dataset keyword] the antenna beamwidth [deg]. If None that of the keys radar_beam_width_h or radar_beam_width_v in attribute instrument_parameters of the radar object will be used. If the key or the attribute are not present the beamwidth will be set to None

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_phase.process_smooth_phidp_double_window` (*procstatus*, *dscfg*,
radar_list=None)

corrects phidp of the system phase and smoothes it using one window

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

rmin [float. Dataset keyword] The minimum range where to look for valid data [m]

rmax [float. Dataset keyword] The maximum range where to look for valid data [m]

rcell [float. Dataset keyword] The length of a continuous cell to consider it valid precip [m]

rwinds [float. Dataset keyword] The length of the short smoothing window [m]

rwindl [float. Dataset keyword] The length of the long smoothing window [m]

Zmin [float. Dataset keyword] The minimum reflectivity [dBZ]

Zmax [float. Dataset keyword] The maximum reflectivity [dBZ]

Zthr [float. Dataset keyword] The threshold defining wich smoothed data to used [dBZ]

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_phase.process_smooth_phidp_single_window` (*procstatus*, *dscfg*,
radar_list=None)

corrects phidp of the system phase and smoothes it using one window

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

rmin [float. Dataset keyword] The minimum range where to look for valid data [m]
rmax [float. Dataset keyword] The maximum range where to look for valid data [m]
rcell [float. Dataset keyword] The length of a continuous cell to consider it valid precip [m]
rwind [float. Dataset keyword] The length of the smoothing window [m]
Zmin [float. Dataset keyword] The minimum reflectivity [dBZ]
Zmax [float. Dataset keyword] The maximum reflectivity [dBZ]
radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output
ind_rad [int] radar index

PYRAD.PROC.PROCESS_RETRIEVE

Functions for retrieving new moments and products

<i>process_ccor</i> (procstatus, dscfg[, radar_list])	Computes the Clutter Correction Ratio, i.e.
<i>process_signal_power</i> (procstatus, dscfg[, ...])	Computes the signal power in dBm
<i>process_rcs_pr</i> (procstatus, dscfg[, radar_list])	Computes the radar cross-section (assuming a point target) from radar reflectivity by first computing the received power and then the RCS from it.
<i>process_rcs</i> (procstatus, dscfg[, radar_list])	Computes the radar cross-section (assuming a point target) from radar reflectivity.
<i>process_vol_refl</i> (procstatus, dscfg[, radar_list])	Computes the volumetric reflectivity in $10\log_{10}(\text{cm}^2 \text{ km}^{-3})$
<i>process_snr</i> (procstatus, dscfg[, radar_list])	Computes SNR
<i>process_radial_noise_hs</i> (procstatus, dscfg[, ...])	Computes the radial noise from the signal power using the Hildebrand and Sekhon 1974 method
<i>process_radial_noise_ivic</i> (procstatus, dscfg)	Computes the radial noise from the signal power using the Ivic 2013 method
<i>process_l</i> (procstatus, dscfg[, radar_list])	Computes L parameter
<i>process_cdr</i> (procstatus, dscfg[, radar_list])	Computes Circular Depolarization Ratio
<i>process_rainrate</i> (procstatus, dscfg[, radar_list])	Estimates rainfall rate from polarimetric moments
<i>process_rainfall_accumulation</i> (procstatus, dscfg)	Computes rainfall accumulation fields
<i>process_bird_density</i> (procstatus, dscfg[, ...])	Computes the bird density from the volumetric reflectivity

`pyrad.proc.process_retrieve.process_bird_density` (*procstatus, dscfg, radar_list=None*)
Computes the bird density from the volumetric reflectivity

Parameters

- procstatus** [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
- dscfg** [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
 - datatype** [list of string. Dataset keyword] The input data types
 - sigma_bird** [float. Dataset keyword] The bird radar cross section
- radar_list** [list of Radar objects] Optional. list of radar objects

Returns

- new_dataset** [dict] dictionary containing the output
- ind_rad** [int] radar index

`pyrad.proc.process_retrieve.process_ccor (procstatus, dscfg, radar_list=None)`

Computes the Clutter Correction Ratio, i.e. the ratio between the signal without Doppler filtering and the signal with Doppler filtering

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_retrieve.process_cdr (procstatus, dscfg, radar_list=None)`

Computes Circular Depolarization Ratio

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The input data type

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_retrieve.process_l (procstatus, dscfg, radar_list=None)`

Computes L parameter

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The input data type

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_retrieve.process_radial_noise_hs (procstatus, dscfg, radar_list=None)`

Computes the radial noise from the signal power using the Hildebrand and Sekhon 1974 method

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The input data type

rmin [float. Dataset keyword] The minimum range from which to start the computation

nbins_min [int. Dataset keyword] The minimum number of noisy gates to consider the estimation valid

max_std_pwr [float. Dataset keyword] The maximum standard deviation of the noise power to consider the estimation valid

get_noise_pos [bool. Dataset keyword] If True a field flagging the position of the noisy gets will be returned

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

```
pyrad.proc.process_retrieve.process_radial_noise_ivic(procstatus,          dscfg,  
                                                    radar_list=None)
```

Computes the radial noise from the signal power using the Ivic 2013 method

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The input data type

npulses_ray [int] Default number of pulses used in the computation of the ray. If the number of pulses is not in radar.instrument_parameters this will be used instead. Default 30

flat_reg_wlen [int] range of window considered to find flat regions [m]. Default 8000.

ngates_min: int minimum number of gates with noise to consider the retrieval valid. Default 800

iterations: int number of iterations in step 7. Default 10.

get_noise_pos [bool] If true an additional field with gates containing noise according to the algorithm is produced

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

```
pyrad.proc.process_retrieve.process_rainfall_accumulation(procstatus,          dscfg,  
                                                         radar_list=None)
```

Computes rainfall accumulation fields

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

period [float. Dataset keyword] the period to average [s]. If -1 the statistics are going to be performed over the entire data. Default 3600.

start_average [float. Dataset keyword] when to start the average [s from midnight UTC]. Default 0.

use_nan [bool. Dataset keyword] If true non valid data will be used

nan_value [float. Dataset keyword] The value of the non valid data. Default 0

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_retrieve.process_rainrate` (*procstatus*, *dscfg*, *radar_list=None*)
Estimates rainfall rate from polarimetric moments

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The input data type

RR_METHOD [string. Dataset keyword] The rainfall rate estimation method. One of the following: Z, ZPoly, KDP, A, ZKDP, ZA, hydro

alpha, beta [float] factor and exponent of the R-Var power law $R = \alpha * Var^{\beta}$. Default value depending on RR_METHOD. Z (0.0376, 0.6112), KDP (None, None), A (None, None)

alphaz, betaz [float] factor and exponent of the R-Z power law $R = \alpha * Z^{\beta}$. Default value (0.0376, 0.6112)

alphazr, betazr [float] factor and exponent of the R-Z power law $R = \alpha * Z^{\beta}$ applied to rain in method hydro. Default value (0.0376, 0.6112)

alphazs, betazs [float] factor and exponent of the R-Z power law $R = \alpha * Z^{\beta}$ applied to solid precipitation in method hydro. Default value (0.1, 0.5)

alphakdp, betakdp [float] factor and exponent of the R-KDP power law $R = \alpha * KDP^{\beta}$. Default value (None, None)

alphaa, betaa [float] factor and exponent of the R-Ah power law $R = \alpha * Ah^{\beta}$. Default value (None, None)

thresh [float] In hybrid methods, Rainfall rate threshold at which the retrieval method used changes [mm/h]. Default value depending on RR_METHOD. ZKDP 10, ZA 10, hydro 10

mp_factor [float] Factor by which the Z-R relation is multiplied in the melting layer in method hydro. Default 0.6

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_retrieve.process_rcs` (*procstatus*, *dscfg*, *radar_list=None*)
Computes the radar cross-section (assuming a point target) from radar reflectivity.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

kw2 [float. Dataset keyword] The water constant

pulse_width [float. Dataset keyword] The pulse width [s]

beamwidthv [float. Global keyword] The vertical polarization antenna beamwidth [deg].
Used if input is vertical reflectivity

beamwidthh [float. Global keyword] The horizontal polarization antenna beamwidth [deg].
Used if input is horizontal reflectivity

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_retrieve.process_rcs_pr(procstatus, dscfg, radar_list=None)`

Computes the radar cross-section (assuming a point target) from radar reflectivity by first computing the received power and then the RCS from it.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

AntennaGainH, AntennaGainV [float. Dataset keyword] The horizontal (vertical) polarization antenna gain [dB]. If None it will be obtained from the attribute `instrument_parameters` of the radar object

txpwrh, txpwrv [float. Dataset keyword] The transmitted power of the horizontal (vertical) channel [dBm]. If None it will be obtained from the attribute `radar_calibration` of the radar object

mflossh, mflossv [float. Dataset keyword] The matching filter losses of the horizontal (vertical) channel [dB]. If None it will be obtained from the attribute `radar_calibration` of the radar object. Defaults to 0

radconsth, radconstv [float. Dataset keyword] The horizontal (vertical) channel radar constant. If None it will be obtained from the attribute `radar_calibration` of the radar object

lrhx, lrxv [float. Global keyword] The horizontal (vertical) receiver losses from the antenna feed to the reference point. [dB] positive value. Default 0

ltxh, ltxv [float. Global keyword] The horizontal (vertical) transmitter losses from the output of the high power amplifier to the antenna feed. [dB] positive value. Default 0

lradomeh, lradomev [float. Global keyword] The 1-way dry radome horizontal (vertical) channel losses. [dB] positive value. Default 0.

attg [float. Dataset keyword] The gas attenuation [dB/km]. If none it will be obtained from the attribute `radar_calibration` of the radar object or assigned according to the radar frequency. Defaults to 0.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_retrieve.process_signal_power` (*procstatus*, *dscfg*, *radar_list=None*)

Computes the signal power in dBm

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

mflossh, **mflossv** [float. Dataset keyword] The matching filter losses of the horizontal (vertical) channel [dB]. If None it will be obtained from the attribute `radar_calibration` of the radar object. Defaults to 0

radconsth, **radconstv** [float. Dataset keyword] The horizontal (vertical) channel radar constant. If None it will be obtained from the attribute `radar_calibration` of the radar object

lrhx, **lrxv** [float. Global keyword] The horizontal (vertical) receiver losses from the antenna feed to the reference point. [dB] positive value. Default 0

lradomeh, **lradomev** [float. Global keyword] The 1-way dry radome horizontal (vertical) channel losses. [dB] positive value. Default 0.

attg [float. Dataset keyword] The gas attenuation [dB/km]. If none it will be obtained from the attribute `radar_calibration` of the radar object or assigned according to the radar frequency. Defaults to 0.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_retrieve.process_snr` (*procstatus*, *dscfg*, *radar_list=None*)

Computes SNR

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The input data type

output_type [string. Dataset keyword] The output data type. Either SNRh or SNRv

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_retrieve.process_vol_refl` (*procstatus*, *dscfg*, *radar_list=None*)

Computes the volumetric reflectivity in $10\log_{10}(\text{cm}^2 \text{ km}^{-3})$

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

- datatype** [list of string. Dataset keyword] The input data types
- freq** [float. Dataset keyword] The radar frequency
- kw** [float. Dataset keyword] The water constant

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

PYRAD.PROC.PROCESS_SPECTRA

Functions to processes spectral data.

<i>process_raw_spectra</i> (procstatus, dscfg[, ...])	Dummy function that returns the initial input data set
<i>process_ifft</i> (procstatus, dscfg[, radar_list])	Compute the Doppler spectrum width from the spectral reflectivity
<i>process_spectra_point</i> (procstatus, dscfg[, ...])	Obtains the spectra or IQ data at a point location.
<i>process_filter_0Doppler</i> (procstatus, dscfg[, ...])	Function to filter the 0-Doppler line bin and neighbours of the Doppler spectra
<i>process_filter_srhov</i> (procstatus, dscfg[, ...])	Filter Doppler spectra as a function of spectral RhoHV
<i>process_filter_spectra_noise</i> (procstatus, dscfg)	Filter the noise of the Doppler spectra by clipping any data below the noise level plus a margin
<i>process_spectra_ang_avg</i> (procstatus, dscfg[, ...])	Function to average the spectra over the rays.
<i>process_spectral_power</i> (procstatus, dscfg[, ...])	Computes the spectral power
<i>process_spectral_noise</i> (procstatus, dscfg[, ...])	Computes the spectral noise
<i>process_spectral_phase</i> (procstatus, dscfg[, ...])	Computes the spectral phase
<i>process_spectral_reflectivity</i> (procstatus, dscfg)	Computes spectral reflectivity
<i>process_spectral_differential_reflectivity</i> (procstatus, dscfg)	Computes spectral differential reflectivity
<i>process_spectral_differential_phase</i> (procstatus, dscfg[, ...])	Computes the spectral differential phase
<i>process_spectral_rhov</i> (procstatus, dscfg[, ...])	Computes the spectral RhoHV
<i>process_pol_variables</i> (procstatus, dscfg[, ...])	Computes the polarimetric variables from the complex spectra
<i>process_noise_power</i> (procstatus, dscfg[, ...])	Computes the noise power from the spectra
<i>process_reflectivity</i> (procstatus, dscfg[, ...])	Computes reflectivity from the spectral reflectivity
<i>process_differential_reflectivity</i> (procstatus, dscfg[, ...])	Computes differential reflectivity from the horizontal and vertical spectral reflectivity
<i>process_differential_phase</i> (procstatus, dscfg)	Computes the differential phase from the spectral differential phase and the spectral reflectivity
<i>process_rhov</i> (procstatus, dscfg[, radar_list])	Computes RhoHV from the complex spectras
<i>process_Doppler_velocity</i> (procstatus, dscfg)	Compute the Doppler velocity from the spectral reflectivity

Continued on next page

Table 1 – continued from previous page

<code>process_Doppler_width(procstatus,</code>	<code>dscfg[,</code>	Compute the Doppler spectrum width from the spectral
<code>...)]</code>		reflectivity

`pyrad.proc.process_spectra.process_Doppler_velocity` (*procstatus*, *dscfg*,
radar_list=None)

Compute the Doppler velocity from the spectral reflectivity

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:

datatype [list of string. Dataset keyword] The input data types

radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_spectra.process_Doppler_width` (*procstatus*, *dscfg*, *radar_list=None*)

Compute the Doppler spectrum width from the spectral reflectivity

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:

datatype [list of string. Dataset keyword] The input data types

radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_spectra.process_differential_phase` (*procstatus*, *dscfg*,
radar_list=None)

Computes the differential phase from the spectral differential phase and the spectral reflectivity

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:

datatype [list of string. Dataset keyword] The input data types

radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_spectra.process_differential_reflectivity` (*procstatus*, *dscfg*,
radar_list=None)

Computes differential reflectivity from the horizontal and vertical spectral reflectivity

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:
 datatype [list of string. Dataset keyword] The input data types
radar_list [list of spectra objects] Optional. list of spectra objects

Parameters

Returns

Parameters

Returns

Parameters

sRhoHV_threshold [float] Data with sRhoHV module above this threshold will be filtered.
Default 1.

radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_spectra.process_ifft` (*procstatus*, *dscfg*, *radar_list=None*)

Compute the Doppler spectrum width from the spectral reflectivity

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:

datatype [list of string. Dataset keyword] The input data types

radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_spectra.process_noise_power` (*procstatus*, *dscfg*, *radar_list=None*)

Computes the noise power from the spectra

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:

datatype [list of string. Dataset keyword] The input data types

units [str] The units of the returned signal. Can be 'ADU', 'dBADU' or 'dBm'

navg [int] Number of spectra averaged

rmin [int] Range from which the data is used to estimate the noise

nnoise_min [int] Minimum number of samples to consider the estimated noise power valid

radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_spectra.process_pol_variables` (*procstatus*, *dscfg*, *radar_list=None*)

Computes the polarimetric variables from the complex spectra

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:

datatype [list of string. Dataset keyword] The input data types

subtract_noise [Bool] If True noise will be subtracted from the signal

smooth_window [int or None] Size of the moving Gaussian smoothing window. If none no smoothing will be applied

variables [list of str] list of variables to compute. Default dBZ

radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_spectra.process_raw_spectra(procstatus, dscfg, radar_list=None)`

Dummy function that returns the initial input data set

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration

radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_spectra.process_reflectivity(procstatus, dscfg, radar_list=None)`

Computes reflectivity from the spectral reflectivity

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:

datatype [list of string. Dataset keyword] The input data types

radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_spectra.process_rhoHV(procstatus, dscfg, radar_list=None)`

Computes RhoHV from the complex spectras

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:

datatype [list of string. Dataset keyword] The input data types

subtract_noise [Bool] If True noise will be subtracted from the signal

radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_spectra.process_spectra_ang_avg` (*procstatus*, *dscfg*,
radar_list=None)

Function to average the spectra over the rays. This function is intended mainly for vertically pointing scans. The function assumes the volume is composed of a single sweep, it averages over the number of rays specified by the user and produces a single ray output.

Parameters

- procstatus** [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
- dscfg** [dictionary of dictionaries] data set configuration. Accepted configuration keywords:
 - datatype** [list of string. Dataset keyword] The input data types
 - navg** [int] Number of spectra to average. If -1 all spectra will be averaged. Default -1.
 - radar_list** [list of spectra objects] Optional. list of spectra objects

Returns

- new_dataset** [dict] dictionary containing the output
- ind_rad** [int] radar index

`pyrad.proc.process_spectra.process_spectra_point` (*procstatus*, *dscfg*, *radar_list=None*)

Obtains the spectra or IQ data at a point location.

Parameters

- procstatus** [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
- dscfg** [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
 - datatype** [string. Dataset keyword] The data type where we want to extract the point measurement
 - latlon** [boolean. Dataset keyword] if True position is obtained from latitude, longitude information, otherwise position is obtained from antenna coordinates (range, azimuth, elevation). Default False
 - truealt** [boolean. Dataset keyword] if True the user input altitude is used to determine the point of interest. if False use the altitude at a given radar elevation *ele* over the point of interest. Default True
 - lon** [float. Dataset keyword] the longitude [deg]. Use when *latlon* is True.
 - lat** [float. Dataset keyword] the latitude [deg]. Use when *latlon* is True.
 - alt** [float. Dataset keyword] altitude [m MSL]. Use when *latlon* is True. Default 0.
 - ele** [float. Dataset keyword] radar elevation [deg]. Use when *latlon* is False or when *latlon* is True and *truealt* is False
 - azi** [float. Dataset keyword] radar azimuth [deg]. Use when *latlon* is False
 - rng** [float. Dataset keyword] range from radar [m]. Use when *latlon* is False
 - AziTol** [float. Dataset keyword] azimuthal tolerance to determine which radar azimuth to use [deg]. Default 0.5
 - EleTol** [float. Dataset keyword] elevation tolerance to determine which radar elevation to use [deg]. Default 0.5
 - RngTol** [float. Dataset keyword] range tolerance to determine which radar bin to use [m]. Default 50.
- radar_list** [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the data and metadata at the point of interest

ind_rad [int] radar index

```
pyrad.proc.process_spectra.process_spectral_differential_phase(procstatus,  
                                                             dscfg,  
                                                             radar_list=None)
```

Computes the spectral differential phase

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:

datatype [list of string. Dataset keyword] The input data types

radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

```
pyrad.proc.process_spectra.process_spectral_differential_reflectivity(procstatus,  
                                                                    dscfg,  
                                                                    radar_list=None)
```

Computes spectral differential reflectivity

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:

datatype [list of string. Dataset keyword] The input data types

subtract_noise [Bool] If True noise will be subtracted from the signal

smooth_window [int or None] Size of the moving Gaussian smoothing window. If none no smoothing will be applied

radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

```
pyrad.proc.process_spectra.process_spectral_noise(procstatus,  
                                                  dscfg,  
                                                  radar_list=None)
```

Computes the spectral noise

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:

datatype [list of string. Dataset keyword] The input data types

units [str] The units of the returned signal. Can be 'ADU', 'dBADU' or 'dBm'

navg [int] Number of spectra averaged

rmin [int] Range from which the data is used to estimate the noise

nnoise_min [int] Minimum number of samples to consider the estimated noise power valid
radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output
ind_rad [int] radar index

pyrad.proc.process_spectra.**process_spectral_phase** (*procstatus*, *dscfg*,
radar_list=None)

Computes the spectral phase

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:
datatype [list of string. Dataset keyword] The input data types
radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output
ind_rad [int] radar index

pyrad.proc.process_spectra.**process_spectral_power** (*procstatus*, *dscfg*,
radar_list=None)

Computes the spectral power

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:
datatype [list of string. Dataset keyword] The input data types
units [str] The units of the returned signal. Can be 'ADU', 'dBADU' or 'dBm'
subtract_noise [Bool] If True noise will be subtracted from the signal
smooth_window [int or None] Size of the moving Gaussian smoothing window. If none
no smoothing will be applied
radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output
ind_rad [int] radar index

pyrad.proc.process_spectra.**process_spectral_reflectivity** (*procstatus*, *dscfg*,
radar_list=None)

Computes spectral reflectivity

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:
datatype [list of string. Dataset keyword] The input data types
subtract_noise [Bool] If True noise will be subtracted from the signal

smooth_window [int or None] Size of the moving Gaussian smoothing window. If none no smoothing will be applied

radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

`pyrad.proc.process_spectra.process_spectral_rhoHV` (*procstatus*, *dscfg*,
radar_list=None)

Computes the spectral RhoHV

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted configuration keywords:

datatype [list of string. Dataset keyword] The input data types

subtract_noise [Bool] If True noise will be subtracted from the signal

radar_list [list of spectra objects] Optional. list of spectra objects

Returns

new_dataset [dict] dictionary containing the output

ind_rad [int] radar index

PYRAD.PROC.PROCESS_TIMESERIES

Functions to obtain time series of radar data

<i>process_point_measurement</i> (procstatus, dscfg)	Obtains the radar data at a point location.
<i>process_qvp</i> (procstatus, dscfg[, radar_list])	Computes quasi vertical profiles, by averaging over height levels PPI data.
<i>process_rqvp</i> (procstatus, dscfg[, radar_list])	Computes range defined quasi vertical profiles, by averaging over height levels PPI data.
<i>process_evp</i> (procstatus, dscfg[, radar_list])	Computes enhanced vertical profiles, by averaging over height levels PPI data.
<i>process_svp</i> (procstatus, dscfg[, radar_list])	Computes slanted vertical profiles, by averaging over height levels PPI data.
<i>process_time_height</i> (procstatus, dscfg[, ...])	Produces time height radar objects at a point of interest defined by latitude and longitude.
<i>process_ts_along_coord</i> (procstatus, dscfg[, ...])	Produces time series along a particular antenna coordinate

`pyrad.proc.process_timeseries.process_evp (procstatus, dscfg, radar_list=None)`

Computes enhanced vertical profiles, by averaging over height levels PPI data.

Parameters

- procstatus** [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
- dscfg** [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
 - datatype** [string. Dataset keyword] The data type where we want to extract the point measurement
 - lat, lon** [float] latitude and longitude of the point of interest [deg]
 - latlon_tol** [float] tolerance in latitude and longitude in deg. Default 0.0005
 - delta_rng, delta_azi** [float] maximum range distance [m] and azimuth distance [degree] from the central point of the evp containing data to average. Default 5000. and 10.
 - hmax** [float] The maximum height to plot [m]. Default 10000.
 - hres** [float] The height resolution [m]. Default 250.
 - avg_type** [str] The type of averaging to perform. Can be either “mean” or “median” Default “mean”
 - nvalid_min** [int] Minimum number of valid points to consider the data valid when performing the averaging. Default 1

interp_kind [str] type of interpolation when projecting to vertical grid: 'none', or 'nearest', etc. Default 'none'. 'none' will select from all data points within the regular grid height bin the closest to the center of the bin. 'nearest' will select the closest data point to the center of the height bin regardless if it is within the height bin or not. Data points can be masked values If another type of interpolation is selected masked values will be eliminated from the data points before the interpolation

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the EVP and a keyboard stating whether the processing has finished or not.

ind_rad [int] radar index

`pyrad.proc.process_timeseries.process_point_measurement` (*procstatus*, *dscfg*,
radar_list=None)

Obtains the radar data at a point location.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The data type where we want to extract the point measurement

latlon [boolean. Dataset keyword] if True position is obtained from latitude, longitude information, otherwise position is obtained from antenna coordinates (range, azimuth, elevation).

truealt [boolean. Dataset keyword] if True the user input altitude is used to determine the point of interest. if False use the altitude at a given radar elevation ele over the point of interest.

lon [float. Dataset keyword] the longitude [deg]. Use when latlon is True.

lat [float. Dataset keyword] the latitude [deg]. Use when latlon is True.

alt [float. Dataset keyword] altitude [m MSL]. Use when latlon is True.

ele [float. Dataset keyword] radar elevation [deg]. Use when latlon is False or when latlon is True and truealt is False

azi [float. Dataset keyword] radar azimuth [deg]. Use when latlon is False

rng [float. Dataset keyword] range from radar [m]. Use when latlon is False

AziTol [float. Dataset keyword] azimuthal tolerance to determine which radar azimuth to use [deg]

EleTol [float. Dataset keyword] elevation tolerance to determine which radar elevation to use [deg]

RngTol [float. Dataset keyword] range tolerance to determine which radar bin to use [m]

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the data and metadata at the point of interest

ind_rad [int] radar index

`pyrad.proc.process_timeseries.process_qvp(procstatus, dscfg, radar_list=None)`

Computes quasi vertical profiles, by averaging over height levels PPI data.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The data type where we want to extract the point measurement

angle [int or float] If the radar object contains a PPI volume, the sweep number to use, if it contains an RHI volume the elevation angle. Default 0.

ang_tol [float] If the radar object contains an RHI volume, the tolerance in the elevation angle for the conversion into PPI

hmax [float] The maximum height to plot [m]. Default 10000.

hres [float] The height resolution [m]. Default 50

avg_type [str] The type of averaging to perform. Can be either “mean” or “median” Default “mean”

nvalid_min [int] Minimum number of valid points to accept average. Default 30.

interp_kind [str] type of interpolation when projecting to vertical grid: ‘none’, or ‘nearest’, etc. Default ‘none’ ‘none’ will select from all data points within the regular grid height bin the closest to the center of the bin. ‘nearest’ will select the closest data point to the center of the height bin regardless if it is within the height bin or not. Data points can be masked values If another type of interpolation is selected masked values will be eliminated from the data points before the interpolation

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the QVP and a keyboard stating whether the processing has finished or not.

ind_rad [int] radar index

`pyrad.proc.process_timeseries.process_rqvp(procstatus, dscfg, radar_list=None)`

Computes range defined quasi vertical profiles, by averaging over height levels PPI data.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The data type where we want to extract the point measurement

anglenr [int] The sweep number to use. It assumes the radar volume consists on PPI scans

hmax [float] The maximum height to plot [m]. Default 10000.

hres [float] The height resolution [m]. Default 2.

avg_type [str] The type of averaging to perform. Can be either “mean” or “median” Default “mean”

nvalid_min [int] Minimum number of valid points to accept average. Default 30.

interp_kind [str] type of interpolation when projecting to vertical grid: 'none', or 'nearest', etc. Default 'nearest' 'none' will select from all data points within the regular grid height bin the closest to the center of the bin. 'nearest' will select the closest data point to the center of the height bin regardless if it is within the height bin or not. Data points can be masked values If another type of interpolation is selected masked values will be eliminated from the data points before the interpolation

rmax [float] ground range up to which the data is intended for use [m]. Default 50000.

weight_power [float] Power p of the weighting function $1/(\text{abs}(\text{grng}-(\text{rmax}-1)))^{**p}$ given to the data outside the desired range. -1 will set the weight to 0. Default 2.

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the QVP and a keyboard stating whether the processing has finished or not.

ind_rad [int] radar index

`pyrad.proc.process_timeseries.process_svp(procstatus, dscfg, radar_list=None)`

Computes slanted vertical profiles, by averaging over height levels PPI data.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The data type where we want to extract the point measurement

angle [int or float] If the radar object contains a PPI volume, the sweep number to use, if it contains an RHI volume the elevation angle. Default 0.

ang_tol [float] If the radar object contains an RHI volume, the tolerance in the elevation angle for the conversion into PPI. Default 1.

lat, lon [float] latitude and longitude of the point of interest [deg]

latlon_tol [float] tolerance in latitude and longitude in deg. Default 0.0005

delta_rng, delta_azi [float] maximum range distance [m] and azimuth distance [degree] from the central point of the svp containing data to average. Default 5000. and 10.

hmax [float] The maximum height to plot [m]. Default 10000.

hres [float] The height resolution [m]. Default 250.

avg_type [str] The type of averaging to perform. Can be either "mean" or "median" Default "mean"

nvalid_min [int] Minimum number of valid points to consider the data valid when performing the averaging. Default 1

interp_kind [str] type of interpolation when projecting to vertical grid: 'none', or 'nearest', etc. Default 'none' 'none' will select from all data points within the regular grid height bin the closest to the center of the bin. 'nearest' will select the closest data point to the center of the height bin regardless if it is within the height bin or not. Data points can be masked values If another type of interpolation is selected masked values will be eliminated from the data points before the interpolation

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the svp and a keyboard stating whether the processing has finished or not.

ind_rad [int] radar index

`pyrad.proc.process_timeseries.process_time_height` (*procstatus*, *dscfg*,
radar_list=None)

Produces time height radar objects at a point of interest defined by latitude and longitude. A time-height contains the evolution of the vertical structure of radar measurements above the location of interest.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The data type where we want to extract the point measurement

lat, lon [float] latitude and longitude of the point of interest [deg]

latlon_tol [float] tolerance in latitude and longitude in deg. Default 0.0005

hmax [float] The maximum height to plot [m]. Default 10000.

hres [float] The height resolution [m]. Default 50

interp_kind [str] type of interpolation when projecting to vertical grid: 'none', or 'nearest', etc. Default 'none' 'none' will select from all data points within the regular grid height bin the closest to the center of the bin. 'nearest' will select the closest data point to the center of the height bin regardless if it is within the height bin or not. Data points can be masked values If another type of interpolation is selected masked values will be eliminated from the data points before the interpolation

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the QVP and a keyboard stating whether the processing has finished or not.

ind_rad [int] radar index

`pyrad.proc.process_timeseries.process_ts_along_coord` (*procstatus*, *dscfg*,
radar_list=None)

Produces time series along a particular antenna coordinate

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [string. Dataset keyword] The data type where we want to extract the time series

mode [str] coordinate to extract data along. Can be ALONG_AZI, ALONG_ELE or ALONG_RNG

fixed_range, fixed_azimuth, fixed_elevation [float] The fixed range [m], azimuth [deg] or elevation [deg] to extract. In each mode two of these parameters have to be defined. If they are not defined they default to 0.

ang_tol, rng_tol [float] The angle tolerance [deg] and range tolerance [m] around the fixed range or azimuth/elevation

value_start, value_stop [float] The minimum and maximum value at which the data along a coordinate start and stop

radar_list [list of Radar objects] Optional. list of radar objects

Returns

new_dataset [dict] dictionary containing the data and a keyboard stating whether the processing has finished or not.

ind_rad [int] radar index

PYRAD.PROC.PROCESS_TRAJ

Trajectory functions. Functions to pass trajectory dataset data to the product generation functions.

<code>process_trajectory(procstatus, dscfg[, ...])</code>	Return trajectory
<code>process_traj_trt(procstatus, dscfg[, ...])</code>	Processes data according to TRT trajectory
<code>process_traj_trt_contour(procstatus, dscfg)</code>	Gets the TRT cell contour corresponding to each radar volume
<code>process_traj_lightning(procstatus, dscfg[, ...])</code>	Return time series according to lightning trajectory
<code>process_traj_atplane(procstatus, dscfg[, ...])</code>	Return time series according to trajectory
<code>process_traj_antenna_pattern(procstatus, dscfg)</code>	Process a new array of data volumes considering a plane trajectory.
<code>_get_ts_values_antenna_pattern(radar, ...)</code>	Get the time series values of a trajectory using a synthetic antenna pattern
<code>_get_contour_trt(radar, trajectory, voltime)</code>	Get the TRT cell contour corresponding to the current radar
<code>_get_gates(radar, az, el, rr, tt, trajdict)</code>	Find the gates of the radar object that have to be used to compute the data of a trajectory
<code>_get_gates_trt(radar, trajectory, voltime[, ...])</code>	Find the gates of the radar object that belong to a TRT cell
<code>_get_gates_antenna_pattern(radar_sel, ...[, ...])</code>	Find the gates of the radar object that have to be used to compute the data of a trajectory as seen by another radar system
<code>_get_closest_bin(az, el, rr, tt, radar, tdict)</code>	Get the radar bin closest to a certain trajectory position
<code>_sample_out_of_sector(az, el, rr, radar_sel, ...)</code>	Check if trajectory sample is within radar sector
<code>TargetRadar(latitude, longitude, altitude)</code>	A class for dummy target radar object

class `pyrad.proc.process_traj.TargetRadar` (*latitude, longitude, altitude*)

Bases: `object`

A class for dummy target radar object

Attributes

latitude, longitude, altitude [float] Position of the dummy radar

__class__

alias of `builtins.type`

__delattr__ (*self, name, /*)

Implement `delattr(self, name)`.

__dict__ = `mappingproxy({'__module__': 'pyrad.proc.process_traj', '__doc__': '\n A c`

`__dir__` (*self*, /)
Default dir() implementation.

`__eq__` (*self*, *value*, /)
Return self==value.

`__format__` (*self*, *format_spec*, /)
Default object formatter.

`__ge__` (*self*, *value*, /)
Return self>=value.

`__getattr__` (*self*, *name*, /)
Return getattr(self, name).

`__gt__` (*self*, *value*, /)
Return self>value.

`__hash__` (*self*, /)
Return hash(self).

`__init__` (*self*, *latitude*, *longitude*, *altitude*)
Initialize self. See help(type(self)) for accurate signature.

`__init_subclass__` ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

`__le__` (*self*, *value*, /)
Return self<=value.

`__lt__` (*self*, *value*, /)
Return self<value.

`__module__` = 'pyrad.proc.process_traj'

`__ne__` (*self*, *value*, /)
Return self!=value.

`__new__` (*args, **kwargs)
Create and return a new object. See help(type) for accurate signature.

`__reduce__` (*self*, /)
Helper for pickle.

`__reduce_ex__` (*self*, *protocol*, /)
Helper for pickle.

`__repr__` (*self*, /)
Return repr(self).

`__setattr__` (*self*, *name*, *value*, /)
Implement setattr(self, name, value).

`__sizeof__` (*self*, /)
Size of object in memory, in bytes.

`__str__` (*self*, /)
Return str(self).

`__subclasshook__` ()
Abstract classes can override this to customize issubclass().

This is invoked early on by `abc.ABCMeta.__subclasscheck__()`. It should return `True`, `False` or `NotImplemented`. If it returns `NotImplemented`, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

`__weakref__`

list of weak references to the object (if defined)

`pyrad.proc.process_traj._get_closest_bin` (*az, el, rr, tt, radar, tdict*)

Get the radar bin closest to a certain trajectory position

Parameters

az, el, rr [floats] The trajectory position respect to the radar
tt [float] the trajectory time respect to the beginning of the radar scan
radar [radar object] the current radar object
tdict [dict] Dictionary containing trajectory parameters

Returns

radar_sel [radar object] The selected radar (Current or one of the two previous ones)
ray_sel, rr_ind [int] The selected ray and range indices of the radar field
el_vec_rnd, az_vec_rnd [array of floats] The elevation and azimuth fields of the selected radar rounded to the first decimal

`pyrad.proc.process_traj._get_contour_trt` (*radar, trajectory, voltime, time_tol=100.0*)

Get the TRT cell contour corresponding to the current radar

Parameters

radar [radar object] The radar containing
trajectory [trajectory object] Object containing the TRT cell position and dimensions
voltime [datetime object] The radar volume reference time
time_tol [float] Time tolerance where to look for data [s]

Returns

lon_roi, lat_roi [array of floats] The lat/lon defining the TRT cell contour

`pyrad.proc.process_traj._get_gates` (*radar, az, el, rr, tt, trajdict, ang_tol=1.2*)

Find the gates of the radar object that have to be used to compute the data of a trajectory

Parameters

radar [radar object] The radar containing
az, el, rr [floats] The trajectory position respect to the radar
tt [float] the trajectory time respect to the beginning of the radar scan
trajdict [dict] Dictionary containing the trajectory parameters
ang_tol [float] Factor that multiplies the angle resolution. Used when determining the neighbouring rays

Returns

radar_sel [radar object] The radar volume selected as closest to trajectory point
ray_sel, rr_ind [ints] ray and range indices of the radar gate closest to the trajectory position
cell_ind [array of ints] indices of the surrounding rays

rr_min [int] index of the minimum range of the surrounding gates

rr_max [int] index of the maximum range of the surrounding gates

```
pyrad.proc.process_traj._get_gates_antenna_pattern(radar_sel, target_radar,  
                                                    az, rr, tt, scan_angles,  
                                                    alt_tol=1000.0, latlon_tol=0.04,  
                                                    max_altitude=12000.0)
```

Find the gates of the radar object that have to be used to compute the data of a trajectory as seen by another radar system

Parameters

radar_sel [radar object] The radar containing real data

target_radar [radar object] The virtual radar

az, rr [floats] The trajectory position respect to the radar

tt [float] the trajectory time respect to the beginning of the radar scan

scan_angles [array] The scan angles of the virtual radar object

alt_tol [float] The tolerance in altitude [m]

latlon_tol [float] The tolerance in latitude and longitude [deg]

max_altitude [float] The maximum altitude where to look for radar data

Returns

ray_ind, rng_ind [array of ints] the indices of the radar data to use

w_ind [array of ints] The indices of the one-dimensional antenna pattern to use

```
pyrad.proc.process_traj._get_gates_trt(radar, trajectory, voltime, time_tol=100.0,  
                                       alt_min=None, alt_max=None, cell_center=False,  
                                       latlon_tol=0.0005)
```

Find the gates of the radar object that belong to a TRT cell

Parameters

radar [radar object] The radar containing

trajectory [trajectory object] Object containing the TRT cell position and dimensions

voltime [datetime object] The radar volume reference time

time_tol [float] Time tolerance where to look for data [s]

alt_min, alt_max [float] Minimum and maximum altitude where to look for data [m]

Returns

inds_ray, inds_rng [array of ints] The indices of the radar data inside the TRT cell

```
pyrad.proc.process_traj._get_ts_values_antenna_pattern(radar, trajectory, tadict,  
                                                       traj_ind, field_names)
```

Get the time series values of a trajectory using a synthetic antenna pattern

Parameters

radar [radar object] The radar volume with the data

trajectory [trajectory object] The plane trajectory

tadict [dict] A dictionary containing parameters useful for trajectory computation

traj_ind [array] The indices of trajectory data within the current radar volume time

field_names [list of str] list of names of the radar field

Returns

result [Bool] A flag signaling whether radar data matching the trajectory was found

`pyrad.proc.process_traj._sample_out_of_sector` (*az, el, rr, radar_sel, ray_sel, rr_ind, el_vec_rnd, az_vec_rnd*)

Check if trajectory sample is within radar sector

Parameters

az, el, rr [floats] The trajectory position respect to the radar

radar_sel [radar object] The selected radar (Current or one of the two previous ones)

ray_sel, rr_ind [int] The selected ray and range indices of the radar field

el_vec_rnd, az_vec_rnd [array of floats] The elevation and azimuth fields of the selected radar rounded to the first decimal

Returns

result [bool] False if the sample is out of sector. True otherwise

`pyrad.proc.process_traj.process_traj_antenna_pattern` (*procstatus, dscfg, radar_list=None, trajectory=None*)

Process a new array of data volumes considering a plane trajectory. As result a timeseries with the values transposed for a given antenna pattern is created. The result is created when the LAST flag is set.

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries]

datatype [list of string. Dataset keyword] The input data types

antennaType [str. Dataset keyword] Type of antenna of the radar we want to get the view from. Can be AZIMUTH, ELEVATION, LOWBEAM, HIGHBEAM

par_azimuth_antenna [dict. Global ekyword] Dictionary containing the parameters of the PAR azimuth antenna, i.e. name of the file with the antenna elevation pattern and fixed antenna angle

par_elevation_antenna [dict. Global keyword] Dictionary containing the parameters of the PAR elevation antenna, i.e. name of the file with the antenna azimuth pattern and fixed antenna angle

asr_lowbeam_antenna [dict. Global keyword] Dictionary containing the parameters of the ASR low beam antenna, i.e. name of the file with the antenna elevation pattern and fixed antenna angle

asr_highbeam_antenna [dict. Global keyword] Dictionary containing the parameters of the ASR high beam antenna, i.e. name of the file with the antenna elevation pattern and fixed antenna angle

target_radar_pos [dict. Global keyword] Dictionary containing the latitude, longitude and altitude of the radar we want to get the view from. If not specifying it will assume the radar is collocated

range_all [Bool. Dataset keyword] If the real radar and the synthetic radar are co-located and this parameter is true the statistics are going to be computed using all the data from range 0 to the position of the plane. Default False

rhi_resolution [Bool. Dataset keyword] Resolution of the synthetic RHI used to compute the data as viewed from the synthetic radar [deg]. Default 0.5

max_altitude [float. Dataset keyword] Max altitude of the data to use when computing the view from the synthetic radar [m MSL]. Default 12000.

latlon_tol [float. Dataset keyword] The tolerance in latitude and longitude to determine which synthetic radar gates are co-located with real radar gates [deg]. Default 0.04

alt_tol [float. Dataset keyword] The tolerance in altitude to determine which synthetic radar gates are co-located with real radar gates [m]. Default 1000.

pattern_thres [float. Dataset keyword] The minimum of the sum of the weights given to each value in order to consider the weighted quantile valid. It is related to the number of valid data points

data_is_log [dict. Dataset keyword] Dictionary specifying for each field if it is in log (True) or linear units (False). Default False

use_nans [dict. Dataset keyword] Dictionary specifying whether the nans have to be used in the computation of the statistics for each field. Default False

nan_value [dict. Dataset keyword] Dictionary with the value to use to substitute the NaN values when computing the statistics of each field. Default 0

radar_list [list of Radar objects] Optional. list of radar objects

trajectory [Trajectory object] containing trajectory samples

Returns

trajectory [Trajectory object] Object holding time series

ind_rad [int] radar index

`pyrad.proc.process_traj.process_traj_atplane(procstatus, dscfg, radar_list=None, trajectory=None)`

Return time series according to trajectory

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

data_is_log [dict. Dataset keyword] Dictionary specifying for each field if it is in log (True) or linear units (False). Default False

ang_tol [float. Dataset keyword] Factor that multiplies the angle resolution. Used when determining the neighbouring rays. Default 1.2

radar_list [list of Radar objects] Optional. list of radar objects

trajectory [Trajectory object] containing trajectory samples

Returns

trajectory [Trajectory object] Object holding time series

ind_rad [int] radar index

`pyrad.proc.process_traj.process_traj_lightning(procstatus, dscfg, radar_list=None, trajectory=None)`

Return time series according to lightning trajectory

Parameters

- procstatus** [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
- dscfg** [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
- datatype** [list of string. Dataset keyword] The input data types
 - data_is_log** [dict. Dataset keyword] Dictionary specifying for each field if it is in log (True) or linear units (False). Default False
 - ang_tol** [float. Dataset keyword] Factor that multiplies the angle resolution. Used when determining the neighbouring rays. Default 1.2
- radar_list** [list of Radar objects] Optional. list of radar objects
- trajectory** [Trajectory object] containing trajectory samples

Returns

- trajectory** [Trajectory object] Object holding time series
- ind_rad** [int] radar index

`pyrad.proc.process_traj.process_traj_trt` (*procstatus*, *dscfg*, *radar_list=None*, *trajectory=None*)

Processes data according to TRT trajectory

Parameters

- procstatus** [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
- dscfg** [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:
- datatype** [list of string. Dataset keyword] The input data types
 - time_tol** [float. Dataset keyword] tolerance between reference time of the radar volume and that of the TRT cell [s]. Default 100.
 - alt_min, alt_max** [float. Dataset keyword] Minimum and maximum altitude of the data inside the TRT cell to retrieve [m MSL]. Default None
 - cell_center** [Bool. Dataset keyword] If True only the range gate closest to the center of the cell is extracted. Default False
 - latlon_tol** [Float. Dataset keyword] Tolerance in lat/lon when extracting data only from the center of the TRT cell. Default 0.01
- radar_list** [list of Radar objects] Optional. list of radar objects
- trajectory** [Trajectory object] containing trajectory samples

Returns

- new_dataset** [dictionary] Dictionary containing radar_out, a radar object containing only data from inside the TRT cell
- ind_rad** [int] radar index

`pyrad.proc.process_traj.process_traj_trt_contour` (*procstatus*, *dscfg*, *radar_list=None*, *trajectory=None*)

Gets the TRT cell contour corresponding to each radar volume

Parameters

- procstatus** [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing
- dscfg** [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

time_tol [float. Dataset keyword] tolerance between reference time of the radar volume and that of the TRT cell [s]. Default 100.

radar_list [list of Radar objects] Optional. list of radar objects

trajectory [Trajectory object] containing trajectory samples

Returns

new_dataset [dict] Dictionary containing radar_out and roi_dict. Radar out is the current radar object. roi_dict contains the positions defining the TRT cell contour

ind_rad [int] radar index

`pyrad.proc.process_traj.process_trajectory` (*procstatus*, *dscfg*, *radar_list=None*, *trajectory=None*)

Return trajectory

Parameters

procstatus [int] Processing status: 0 initializing, 1 processing volume, 2 post-processing

dscfg [dictionary of dictionaries] data set configuration. Accepted Configuration Keywords:

datatype [list of string. Dataset keyword] The input data types

radar_list [list of Radar objects] Optional. list of radar objects

trajectory [Trajectory object] containing trajectory samples

Returns

new_dataset [Trajectory object] radar object

ind_rad [int] None

PYRAD.PROD.PRODUCT_AUX

Auxiliary functions to generate products

`get_prodgen_func(dsformat, dsname, dstype)` maps the dataset format into its processing function

`pyrad.prod.product_aux.get_prodgen_func(dsformat, dsname, dstype)`
maps the dataset format into its processing function

Parameters

dsformat [str] dataset group. The following is a list of dataset groups with the function that is called to generate their products. For details about what the functions do check the function documentation:

'VOL':	generate_vol_products	'COLOCATED_GATES':	generate_colocated_gates_products
'COSMO_COORD':	generate_cosmo_coord_products	'GRID':	generate_grid_products
'COSMO2RADAR':	generate_cosmo_to_radar_products	'SPECTRA':	generate_spectra_products
'GRID_TIMEAVG':	generate_grid_time_avg_products	'INTERCOMP':	generate_intercomp_products
'ML':	generate_ml_products	'MONITORING':	generate_monitoring_products
'OC-CURRENCE':	generate_occurrence_products	'QVP':	generate_qvp_products
'SPARSE_GRID':	generate_sparse_grid_products	'SUN_HITS':	generate_sun_hits_products
'TIMEAVG':	generate_time_avg_products	'TIMESERIES':	generate_timeseries_products
'TRAJ_ONLY':	generate_traj_product		

Returns

func [function] pyrad function used to generate the products

PYRAD.PROD.PROCESS_PRODUCT

Functions for obtaining Pyrad products from the datasets

<code>generate_occurrence_products(dataset, prdcfg)</code>	generates occurrence products. Accepted product types:
<code>generate_cosmo_coord_products(dataset, prdcfg)</code>	generates COSMO coordinates products. Accepted product types:
<code>generate_cosmo_to_radar_products(dataset, prdcfg)</code>	generates COSMO data in radar coordinates products.
<code>generate_sun_hits_products(dataset, prdcfg)</code>	generates sun hits products. Accepted product types:
<code>generate_qvp_products(dataset, prdcfg)</code>	Generates quasi vertical profile-like products.
<code>generate_ml_products(dataset, prdcfg)</code>	Generates melting layer products. Accepted product types:

`pyrad.prod.process_product.generate_cosmo_coord_products(dataset, prdcfg)`

generates COSMO coordinates products. Accepted product types:

‘SAVEVOL’: Save an object containing the index of the COSMO model grid that corresponds to each radar gate in a C/F radial file. User defined parameters:

file_type: **str** The type of file used to save the data. Can be ‘nc’ or ‘h5’. Default ‘nc’

physical: **Bool** If True the data will be saved in physical units (floats). Otherwise it will be quantized and saved as binary

compression: **str** For ODIM file formats, the type of compression. Can be any of the allowed compression types for hdf5 files. Default gzip

compression_opts: **any** The compression options allowed by the hdf5. Depends on the type of compression. Default 6 (The gzip compression level).

Parameters

dataset [tuple] radar object containing the COSMO coordinates

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

filename [str] the name of the file created. None otherwise

`pyrad.prod.process_product.generate_cosmo_to_radar_products(dataset, prdcfg)`

generates COSMO data in radar coordinates products. Accepted product types:

‘SAVEVOL’: Save an object containing the COSMO data in radar

coordinates in a C/F radial or ODIM file. User defined parameters: `file_type`: str

The type of file used to save the data. Can be 'nc' or 'h5'. Default 'nc'

physical: **Bool** If True the data will be saved in physical units (floats). Otherwise it will be quantized and saved as binary

compression: **str** For ODIM file formats, the type of compression. Can be any of the allowed compression types for hdf5 files. Default gzip

compression_opts: **any** The compression options allowed by the hdf5. Depends on the type of compression. Default 6 (The gzip compression level).

All the products of the 'VOL' dataset group

Parameters

dataset [tuple] radar object containing the COSMO coordinates

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

filename [str] the name of the file created. None otherwise

`pyrad.prod.process_product.generate_ml_products(dataset, prdcfg)`

Generates melting layer products. Accepted product types:

'ML_TS': Plots and writes a time series of the melting layer, i.e. the evolution of the average and standard deviation of the melting layer top and thickness and the the number of rays used in the retrieval. User defined parameters:

dpi: **int** The pixel density of the plot. Default 72

'SAVE_ML': Saves an object containing the melting layer retrieval information in a C/F radial file

All the products of the 'VOL' dataset group

Parameters

dataset [dict] dictionary containing the radar object and a keyword stating the status of the processing

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

filename [str] the name of the file created. None otherwise

`pyrad.prod.process_product.generate_occurrence_products(dataset, prdcfg)`

generates occurrence products. Accepted product types:

'WRITE_EXCESS_GATES': Write the data that identifies radar gates with clutter that has a frequency of occurrence above a certain threshold. User defined parameters:

quant_min: **float** Minimum frequency of occurrence in percentage to keep the gate as valid. Default 95.

All the products of the 'VOL' dataset group

Parameters

dataset [tuple] radar object and metadata dictionary

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

filename [str] the name of the file created. None otherwise

`pyrad.prod.process_product.generate_qvp_products(dataset, prdcfg)`

Generates quasi vertical profile-like products. Quasi vertical profiles come from azimuthal averaging of polarimetric radar data. With the variable 'qvp_type' the user decides if the product has to be generated at the end of the processing period ('final') or instantaneously ('instant') Accepted product types:

All the products of the 'VOL' dataset group

Parameters

dataset [dict] dictionary containing the radar object and a keyword stating the status of the processing

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

filename [str] the name of the file created. None otherwise

`pyrad.prod.process_product.generate_sun_hits_products(dataset, prdcfg)`

generates sun hits products. Accepted product types:

'PLOT_SUN_HITS': Plots in a sun-radar azimuth difference-sun-radar elevation difference grid the values of all sun hits obtained during the processing period

'PLOT_SUN_RETRIEVAL': Plots in a sun-radar azimuth difference-sun- radar elevation difference grid the retrieved sun pattern

'PLOT_SUN_RETRIEVAL_TS': Plots time series of the retrieved sun pattern parameters User defined parameters:

dpi: int The pixel density of the plot. Default 72

add_date_in_fname: Bool If true the year is added in the plot file name

'WRITE_SUN_HITS': Writes the information concerning possible sun hits in a csv file

'WRITE_SUN_RETRIEVAL': Writes the retrieved sun pattern parameters in a csv file. User defined parameters:

add_date_in_fname: Bool If true the year is added in the csv file name

All the products of the 'VOL' dataset group

Parameters

dataset [tuple] radar object and sun hits dictionary

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

filename [str] the name of the file created. None otherwise

PYRAD.PROD.PROCESS_VOL_PRODUCTS

Functions for obtaining Pyrad products from a radar volume dataset

<i>generate_vol_products</i> (dataset, prdcfg)	Generates radar volume products. Accepted product types:
--	--

`pyrad.prod.process_vol_products.generate_vol_products(dataset, prdcfg)`

Generates radar volume products. Accepted product types:

‘CDF’: plots and writes the cumulative density function of data

User defined parameters:

quantiles: list of floats The quantiles to compute in percent. Default None

sector: dict dictionary defining the sector where to compute the CDF. Default is None and the CDF is computed over all the data May contain:

rmin, rmax: float min and max range [m]

azmin, azmax: float min and max azimuth angle [deg]

elmin, elmax: float min and max elevation angle [deg]

hmin, hmax: float min and max altitude [m MSL]

vismin: float The minimum visibility to use the data. Default None

absolute: Bool If true the absolute values of the data will be used. Default False

use_nans: Bool If true NaN values will be used. Default False

nan_value: Bool The value by which the NaNs are substituted if NaN values are to be used in the computation

filterclt: Bool If True the gates containing clutter are filtered

filterprec: list of ints The hydrometeor types that are filtered from the analysis. Default empty list.

‘BSCOPE_IMAGE’: Creates a B-scope image (azimuth, range)

User defined parameters:

anglenr [int] The elevation angle number to use

ray_dim [str] the ray dimension. Can be ‘ang’ or ‘time’. Default ‘ang’

axis_rng [bool] if True the range will be in the x-axis. Otherwise it will be in the y-axis. Default True

vmin, vmax: float or None The minimum and maximum values of the color scale. If None the scale is going to be set according to the Py-ART config file

‘CAPPI_IMAGE’: Creates a CAPPI image

User defined parameters:

altitude: flt CAPPI altitude [m MSL]

wfunc: str The function used to produce the CAPPI as defined in `pyart.map.grid_from_radars`. Default ‘NEAREST’

cappi_res: float The CAPPI resolution [m]. Default 500.

‘FIELD_COVERAGE’: Gets the field coverage over a certain sector

User defined parameters:

threshold: float or None Minimum value to consider the data valid. Default None

nvalid_min: float Minimum number of valid gates in the ray to consider it valid. Default 5

ele_res, azi_res: float Elevation and azimuth resolution of the sectors [deg]. Default 1. and 2.

ele_min, ele_max: float Min and max elevation angle defining the sector [deg]. Default 0. and 30.

ele_step: float Elevation step [deg]. Default 5.

ele_sect_start, ele_sect_stop: float or None start and stop angles of the sector coverage. Default None

quantiles: list of floats The quantiles to compute in the sector. Default 10. to 90. by steps of 10.

AngTol: float The tolerance in elevation angle when putting the data in a fixed grid

‘FIXED_RNG_IMAGE’: Plots a fixed range image

User defined parameters:

AngTol [float] The tolerance between the nominal angles and the actual radar angles. Default 1.

ele_res, azi_res: float or None The resolution of the fixed grid [deg]. If None it will be obtained from the separation between angles

vmin, vmax [float or None] Min and Max values of the color scale. If None the values are taken from the Py-ART config file

‘FIXED_RNG_SPAN_IMAGE’: Plots a user-defined statistic over a fixed range image User defined parameters:

AngTol [float] The tolerance between the nominal angles and the actual radar angles. Default 1.

ele_res, azi_res: float or None The resolution of the fixed grid [deg]. If None it will be obtained from the separation between angles

stat [str] The statistic to compute. Can be ‘min’, ‘max’, ‘mean’, ‘mode’. Default ‘max’

‘HISTOGRAM’: Computes a histogram of the radar volum data

User defined parameters:

step: float or None the data quantization step. If none it will be obtained from the Py-ART configuration file

write_data: Bool If true the histogram data is written in a csv file

‘PLOT_ALONG_COORD’: Plots the radar volume data along a particular coordinate User defined parameters:

colors: list of str or None The colors of each plotted line

mode: str Plotting mode. Can be ‘ALONG_RNG’, ‘ALONG_AZI’ or ‘ALONG_ELE’

value_start, value_stop: float The starting and ending points of the data to plot. According to the mode it may refer to the range, azimuth or elevation. If not specified the minimum and maximum possible values are used

fix_elevations, fix_azimuths, fix_ranges: list of floats The elevations, azimuths or ranges to plot for each mode. ‘ALONG_RNG’ would use fix_elevations and fix_azimuths ‘ALONG_AZI’ fix_ranges and fix_elevations ‘ALONG_ELE’ fix_ranges and fix_azimuths

AngTol: float The tolerance to match the radar angle to the fixed angles Default 1.

RngTol: float The tolerance to match the radar range to the fixed ranges Default 50.

‘PPI_CONTOUR’: Plots a PPI countour plot

User defined parameters:

contour_values: list of floats or None The list of contour values to plot. If None the contour values are going to be obtained from the Py-ART config file either with the dictionary key ‘contour_values’ or from the minimum and maximum values of the field with an assumed division of 10 levels.

anglenr: float The elevation angle number

‘PPI_CONTOUR_OVERPLOT’: Plots a PPI of a field with another field overplotted as a contour plot. User defined parameters:

contour_values: list of floats or None The list of contour values to plot. If None the contour values are going to be obtained from the Py-ART config file either with the dictionary key ‘contour_values’ or from the minimum and maximum values of the field with an assumed division of 10 levels.

anglenr: float The elevation angle number

‘PPI_IMAGE’: Plots a PPI image. It can also plot the histogram and the quantiles of the data in the PPI. User defined parameters:

anglenr: float The elevation angle number

plot_type: str The type of plot to perform. Can be ‘PPI’, ‘QUANTILES’ or ‘HISTOGRAM’

step: float or None If the plot type is ‘HISTOGRAM’, the width of the histogram bin. If None it will be obtained from the Py-ART config file

quantiles: list of float or None If the plot type is ‘QUANTILES’, the list of quantiles to compute. If None a default list of quantiles will be computed

vmin, vmax: float or None The minimum and maximum values of the color scale. If None the scale is going to be set according to the Py-ART config file

‘PPI_MAP’: Plots a PPI image over a map. The map resolution and the type of maps used are defined in the variables ‘mapres’ and ‘maps’ in ‘ppiMapImageConfig’ in the loc config file. User defined parameters:

anglenr: float The elevation angle number

‘PPIMAP_ROI_OVERPLOT’: Over plots a polygon delimiting a region of interest on a PPI map. The map resolution and the type of maps used are defined in the variables ‘mapres’ and ‘maps’ in ‘ppiMapImageConfig’ in the loc config file. User defined parameters:

anglenr: float The elevation angle number

‘PROFILE_STATS’: Computes and plots a vertical profile statistics. The statistics are saved in a csv file User defined parameters:

heightResolution: float The height resolution of the profile [m]. Default 100.

heightMin, heightMax: float or None The minimum and maximum altitude of the profile [m MSL]. If None the values will be obtained from the minimum and maximum gate altitude.

quantity: str The type of statistics to plot. Can be ‘quantiles’, ‘mode’, ‘regression_mean’ or ‘mean’.

quantiles: list of floats If quantity type is ‘quantiles’ the list of quantiles to compute. Default 25., 50., 75.

nvalid_min: int The minimum number of valid points to consider the statistic valid. Default 4

make_linear: Bool If true the data is converted from log to linear before computing the stats

include_nans: Bool If true NaN values are included in the statistics

fixed_span: Bool If true the profile plot has a fix X-axis

vmin, vmax: float or None If fixed_span is set, the minimum and maximum values of the X-axis. If None, they are obtained from the Py-ART config file

‘PSEUDOPPI_CONTOUR’: Plots a pseudo-PPI countour plot

User defined parameters:

contour_values: list of floats or None The list of contour values to plot. If None the contour values are going to be obtained from the Py-ART config file either with the dictionary key ‘contour_values’ or from the minimum and maximum values of the field with an assumed division of 10 levels.

angle: float The elevation angle at which compute the PPI

EleTol: float The tolerance between the actual radar elevation angle and the nominal pseudo-PPI elevation angle.

‘PSEUDOPPI_CONTOUR_OVERPLOT’: Plots a pseudo-PPI of a field with another field over-plotted as a contour plot User defined parameters:

contour_values: list of floats or None The list of contour values to plot. If None the contour values are going to be obtained from the Py-ART config file either with the dictionary key ‘contour_values’ or from the minimum and maximum values of the field with an assumed division of 10 levels.

angle: float The elevation angle at which compute the PPI

EleTol: float The tolerance between the actual radar elevation angle and the nominal pseudo-PPI elevation angle.

‘PSEUDOPPI_IMAGE’: Plots a pseudo-PPI image. It can also plot the histogram and the quantiles of the data in the pseudo-PPI. User defined parameters:

angle: float The elevation angle of the pseudo-PPI

EleTol: float The tolerance between the actual radar elevation angle and the nominal pseudo-PPI elevation angle.

plot_type: str The type of plot to perform. Can be 'PPI', 'QUANTILES' or 'HISTOGRAM'

step: float or None If the plot type is 'HISTOGRAM', the width of the histogram bin. If None it will be obtained from the Py-ART config file

quantiles: list of float or None If the plot type is 'QUANTILES', the list of quantiles to compute. If None a default list of quantiles will be computed

vmin, vmax [float or None] Min and Max values of the color scale. If None the values are taken from the Py-ART config file

'PSEUDOPPI_MAP': Plots a pseudo-PPI image over a map. The map resolution and the type of maps used are defined in the variables 'mapres' and 'maps' in 'ppiMapImageConfig' in the loc config file. User defined parameters:

angle: float The elevation angle of the pseudo-PPI

EleTol: float The tolerance between the actual radar elevation angle and the nominal pseudo-PPI elevation angle.

'PSEUDORHI_CONTOUR': Plots a pseudo-RHI countour plot

User defined parameters:

contour_values: list of floats or None The list of contour values to plot. If None the contour values are going to be obtained from the Py-ART config file either with the dictionary key 'contour_values' or from the minimum and maximum values of the field with an assumed division of 10 levels.

angle: float The azimuth angle at which to compute the RPI

AziTol: float The tolerance between the actual radar azimuth angle and the nominal pseudo-RHI azimuth angle.

'PSEUDORHI_CONTOUR_OVERPLOT': Plots a pseudo-RHI of a field with another field over-plotted as a contour plot User defined parameters:

contour_values: list of floats or None The list of contour values to plot. If None the contour values are going to be obtained from the Py-ART config file either with the dictionary key 'contour_values' or from the minimum and maximum values of the field with an assumed division of 10 levels.

angle: float The azimuth angle at which to compute the RPI

AziTol: float The tolerance between the actual radar azimuth angle and the nominal pseudo-RHI azimuth angle.

'PSEUDORHI_IMAGE': Plots a pseudo-RHI image. It can also plot the histogram and the quantiles of the data in the pseudo-RHI. User defined parameters:

angle: float The azimuth angle at which to compute the RPI

AziTol: float The tolerance between the actual radar azimuth angle and the nominal pseudo-RHI azimuth angle.

plot_type: str The type of plot to perform. Can be 'RHI', 'QUANTILES' or 'HISTOGRAM'

step: float or None If the plot type is 'HISTOGRAM', the width of the histogram bin. If None it will be obtained from the Py-ART config file

quantiles: list of float or None If the plot type is 'QUANTILES', the list of quantiles to compute. If None a default list of quantiles will be computed

vmin, vmax [float or None] Min and Max values of the color scale. If None the values are taken from the Py-ART config file

'QUANTILES': Plots and writes the quantiles of a radar volume

User defined parameters:

quantiles: list of floats or None the list of quantiles to compute. If None a default list of quantiles will be computed.

write_data: Bool If True the computed data will be also written in a csv file

fixed_span: Bool If true the quantile plot has a fix Y-axis

vmin, vmax: float or None If fixed_span is set, the minimum and maximum values of the Y-axis. If None, they are obtained from the Py-ART config file

'RHI_CONTOUR': Plots an RHI countour plot

User defined parameters:

contour_values: list of floats or None The list of contour values to plot. If None the contour values are going to be obtained from the Py-ART config file either with the dictionary key 'contour_values' or from the minimum and maximum values of the field with an assumed division of 10 levels.

anglenr: int The azimuth angle number

'RHI_CONTOUR_OVERPLOT': Plots an RHI of a field with another field over-plotted as a contour plot User defined parameters:

contour_values: list of floats or None The list of contour values to plot. If None the contour values are going to be obtained from the Py-ART config file either with the dictionary key 'contour_values' or from the minimum and maximum values of the field with an assumed division of 10 levels.

anglenr: int The azimuth angle number

'RHI_IMAGE': Plots an RHI image. It can also plot the histogram and the quantiles of the data in the RHI. User defined parameters:

anglenr: int The azimuth angle number

plot_type: str The type of plot to perform. Can be 'RHI', 'QUANTILES' or 'HISTOGRAM'

step: float or None If the plot type is 'HISTOGRAM', the width of the histogram bin. If None it will be obtained from the Py-ART config file

quantiles: list of float or None If the plot type is 'QUANTILES', the list of quantiles to compute. If None a default list of quantiles will be computed

vmin, vmax: float or None The minimum and maximum values of the color scale. If None the scale is going to be set according to the Py-ART config file

'RHI_PROFILE': Computes and plots a vertical profile statistics out of an RHI. The statistics are saved in a csv file User defined parameters:

rangeStart, rangeStop: float The range start and stop of the data to extract from the RHI to compute the statistics [m]. Default 0., 25000.

heightResolution: float The height resolution of the profile [m]. Default 100.

heightMin, heightMax: float or None The minimum and maximum altitude of the profile [m MSL]. If None the values will be obtained from the minimum and maximum gate altitude.

quantity: str The type of statistics to plot. Can be 'quantiles', 'mode', 'regression_mean' or 'mean'.

quantiles: list of floats If quantity type is 'quantiles' the list of quantiles to compute. Default 25., 50., 75.

nvalid_min: int The minimum number of valid points to consider the statistic valid. Default 4

make_linear: Bool If true the data is converted from log to linear before computing the stats

include_nans: Bool If true NaN values are included in the statistics

fixed_span: Bool If true the profile plot has a fix X-axis

vmin, vmax: float or None If fixed_span is set, the minimum and maximum values of the X-axis. If None, they are obtained from the Py-ART config file

'SAVEALL': Saves radar volume data including all or a list of user- defined fields in a C/F radial or ODIM file User defined parameters:

file_type: str The type of file used to save the data. Can be 'nc' or 'h5'. Default 'nc'

datatypes: list of str or None The list of data types to save. If it is None, all fields in the radar object will be saved

physical: Bool If True the data will be saved in physical units (floats). Otherwise it will be quantized and saved as binary

compression: str For ODIM file formats, the type of compression. Can be any of the allowed compression types for hdf5 files. Default gzip

compression_opts: any The compression options allowed by the hdf5. Depends on the type of compression. Default 6 (The gzip compression level).

'SAVESTATE': Saves the last processed data in a file. Used for real- time data processing

'SAVEVOL': Saves one field of a radar volume data in a C/F radial or ODIM file User defined parameters:

file_type: str The type of file used to save the data. Can be 'nc' or 'h5'. Default 'nc'

physical: Bool If True the data will be saved in physical units (floats). Otherwise it will be quantized and saved as binary

compression: str For ODIM file formats, the type of compression. Can be any of the allowed compression types for hdf5 files. Default gzip

compression_opts: any The compression options allowed by the hdf5. Depends on the type of compression. Default 6 (The gzip compression level).

'SAVE_FIXED_ANGLE': Saves the position of the first fix angle in a csv file

'SELFCONSISTENCY': Plots a ZDR versus KDP/ZH histogram of data.

User defined parameters:

retrieve_relation [bool] If True plots also the retrieved relationship. Default True

plot_theoretical [bool] If True plots also the theoretical relationship. Default True

normalize [bool] If True the occurrence density of ZK/KDP for each ZDR bin is going to be represented. Otherwise it will show the number of gates at each bin. Default True

‘SELFCONSISTENCY2’: Plots a ZH measured versus ZH inferred from a self-consistency
relation histogram of data. User defined parameters:

normalize [bool] If True the occurrence density of ZK/KDP for each ZDR bin is going to be represented. Otherwise it will show the number of gates at each bin. Default True

‘TIME_RANGE’: Plots a time-range/azimuth/elevation plot

User defined parameters:

anglenr: float The number of the fixed angle to plot

vmin, vmax: float or None The minimum and maximum values of the color scale. If None the scale is going to be set according to the Py-ART config file

‘VOL_TS’: Writes and plots a value corresponding to a time series. Meant primarily for writing and plotting the results of the SELFCONSISTENCY2 algorithm User defined parameters:

ref_value: float The reference value. Default 0

sort_by_date: Bool If true when reading the csv file containing the statistics the data is sorted by date. Default False

rewrite: Bool If true the csv file containing the statistics is rewritten

add_data_in_fname: Bool If true and the data used is cumulative the year is written in the csv file name and the plot file name

npoints_min: int Minimum number of points to use the data point in the plotting and to send an alarm. Default 0

vmin, vmax: float or None Limits of the Y-axis (data value). If None the limits are obtained from the Py-ART config file

alarm: Bool If true an alarm is sent

tol_abs: float Margin of tolerance from the reference value. If the current value is above this margin an alarm is sent. If the margin is not specified it is not possible to send any alarm

tol_trend: float Margin of tolerance from the reference value. If the trend of the last X events is above this margin an alarm is sent. If the margin is not specified it is not possible to send any alarm

nevents_min: int Minimum number of events with sufficient points to send an alarm related to the trend. If not specified it is not possible to send any alarm

sender: str The mail of the alarm sender. If not specified it is not possible to send any alarm

receiver_list: list of str The list of emails of the people that will receive the alarm.. If not specified it is not possible to send any alarm

‘WIND_PROFILE’: Plots vertical profile of wind data (U, V, W components and wind velocity and direction) out of a radar volume containing the retrieved U,V and W components of the wind, the standard deviation of the retrieval and the velocity difference between the estimated radial velocity (assuming the wind to be uniform) and the actual measured radial velocity. User defined parameters:

heightResolution: float The height resolution of the profile [m]. Default 100.

heightMin, heightMax: float or None The minimum and maximum altitude of the profile [m MSL]. If None the values will be obtained from the minimum and maximum gate altitude.

min_ele: float The minimum elevation to be used in the computation of the vertical velocities. Default 5.

max_ele: float The maximum elevation to be used in the computation of the horizontal velocities. Default 85.

fixed_span: Bool If true the profile plot has a fix X-axis

vmin, vmax: float or None If fixed_span is set, the minimum and maximum values of the X-axis. If None, they are obtained from the span of the U component defined in the Py-ART config file

Parameters

dataset [dict] dictionary with key radar_out containing a radar object

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

The list of created fields or None

PYRAD.PROD.PROCESS_GRID_PRODUCTS

Functions for obtaining Pyrad products from gridded datasets

<i>generate_grid_time_avg_products</i> (dataset, prdcfg)	generates time average products. Accepted product types:
<i>generate_sparse_grid_products</i> (dataset, prdcfg)	generates products defined by sparse points. Accepted product types:
<i>generate_grid_products</i> (dataset, prdcfg)	generates grid products. Accepted product types:

`pyrad.prod.process_grid_products.generate_grid_products (dataset, prdcfg)`

generates grid products. Accepted product types:

‘CROSS_SECTION’: Plots a cross-section of gridded data

User defined parameters:

coord1, coord2: dict The two lat-lon coordinates marking the limits. They have the keywords ‘lat’ and ‘lon’ [degree]. The altitude limits are defined by the parameters in ‘rhiImageConfig’ in the ‘loc’ configuration file

‘HISTOGRAM’: Computes a histogram of the radar volum data

User defined parameters:

step: float or None the data quantization step. If none it will be obtained from the Py-ART configuration file

write_data: Bool If true the histogram data is written in a csv file

‘LATITUDE_SLICE’: Plots a cross-section of gridded data over a constant latitude. User defined parameters:

lon, lat: floats The starting point of the cross-section. The ending point is defined by the parameters in ‘rhiImageConfig’ in the ‘loc’ configuration file

‘LONGITUDE_SLICE’: Plots a cross-ection of gridded data over a constant longitude. User defined parameters:

lon, lat: floats The starting point of the cross-section. The ending point is defined by the parameters in ‘rhiImageConfig’ in the ‘loc’ configuration file

‘SAVEALL’: Saves a gridded data object including all or a list of user-defined fields in a netcdf file
User defined parameters:

datatypes: list of str or None The list of data types to save. If it is None, all fields in the radar object will be saved

‘SAVEVOL’: Saves on field of a gridded data object in a netcdf file. ‘SURFACE_IMAGE’: Plots a surface image of gridded data.

User defined parameters:

level: int The altitude level to plot. The rest of the parameters are defined by the parameters in ‘ppiImageConfig’ and ‘ppiMapImageConfig’ in the ‘loc’ configuration file

‘SURFACE_CONTOUR’: Plots a surface image of gridded data.

User defined parameters:

level: int The altitude level to plot. The rest of the parameters are defined by the parameters in ‘ppiImageConfig’ and ‘ppiMapImageConfig’ in the ‘loc’ configuration file

Parameters

dataset [grid] grid object

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

None or name of generated files

`pyrad.prod.process_grid_products.generate_grid_time_avg_products(dataset, prdcfg)`

generates time average products. Accepted product types: All the products of the ‘VOL’ dataset group

Parameters

dataset [tuple] radar objects and colocated gates dictionary

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

filename [str] the name of the file created. None otherwise

`pyrad.prod.process_grid_products.generate_sparse_grid_products(dataset, prdcfg)`

generates products defined by sparse points. Accepted product types:

‘SURFACE_IMAGE’: Generates a surface image

User defined parameters:

‘field_limits’: list of floats The limits of the surface to plot [deg] lon0, lon1, lat0, lat1

Parameters

dataset [dictionary containing the points and their values]

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

no return

PYRAD.PROD.PROCESS_TIMESERIES_PRODUCTS

Functions for obtaining Pyrad products from a time series datasets

`generate_timeseries_products(dataset, prd- Generates time series products. Accepted product types:
cfg)`

`pyrad.prod.process_timeseries_products.generate_timeseries_products(dataset,
prdcfg)`

Generates time series products. Accepted product types:

‘COMPARE_CUMULATIVE_POINT’: Plots in the same graph 2 time series of data accumulation (typically rainfall rate). One time series is a point measurement of radar data while the other is from a co-located instrument (rain gauge or disdrometer) User defined parameters:

dpi: int The pixel density of the plot. Default 72

vmin, vmax: float The limits of the Y-axis. If none they will be obtained from the Py-ART config file.

sensor: str The sensor type. Can be ‘rgage’ or ‘disdro’

sensorid: str The sensor ID.

location: str A string identifying the location of the disdrometer

freq: float The frequency used to retrieve the polarimetric variables of a disdrometer

ele: float The elevation angle used to retrieve the polarimetric variables of a disdrometer

ScanPeriod: float The scanning period of the radar in seconds. This parameter is defined in the ‘loc’ config file

‘COMPARE_POINT’: Plots in the same graph 2 time series of data . One time series is a point measurement of radar data while the other is from a co-located instrument (rain gauge or disdrometer) User defined parameters:

dpi: int The pixel density of the plot. Default 72

vmin, vmax: float The limits of the Y-axis. If none they will be obtained from the Py-ART config file.

sensor: str The sensor type. Can be ‘rgage’ or ‘disdro’

sensorid: str The sensor ID.

location: str A string identifying the location of the disdrometer

freq: float The frequency used to retrieve the polarimetric variables of a disdrometer

ele: float The elevation angle used to retrieve the polarimetric variables of a disdrometer

‘COMPARE_TIME_AVG’: Creates a scatter plot of average radar data versus average sensor data.
User defined parameters:

dpi: int The pixel density of the plot. Default 72

sensor: str The sensor type. Can be ‘rgage’ or ‘disdro’

sensorid: str The sensor ID.

location: str A string identifying the location of the disdrometer

freq: float The frequency used to retrieve the polarimetric variables of a disdrometer

ele: float The elevation angle used to retrieve the polarimetric variables of a disdrometer

cum_time: float Data accumulation time [s]. Default 3600.

base_time: float Starting moment of the accumulation [s from midnight]. Default 0.

‘PLOT_AND_WRITE’: Writes and plots a trajectory time series.

User defined parameters:

ymin, ymax: float The minimum and maximum value of the Y-axis. If none it will be obtained from the Py-ART config file.

‘PLOT_AND_WRITE_POINT’: Plots and writes a time series of radar data at a particular point
User defined parameters:

dpi: int The pixel density of the plot. Default 72

vmin, vmax: float The limits of the Y-axis. If none they will be obtained from the Py-ART config file.

‘PLOT_CUMULATIVE_POINT’: Plots a time series of radar data accumulation at a particular point. User defined parameters:

dpi: int The pixel density of the plot. Default 72

vmin, vmax: float The limits of the Y-axis. If none they will be obtained from the Py-ART config file.

ScanPeriod: float The scanning period of the radar in seconds. This parameter is defined in the ‘loc’ config file

‘PLOT_HIST’: plots and writes a histogram of all the data gathered during the trajectory processing
User defined parameters:

step: float or None The quantization step of the data. If None it will be obtained from the Py-ART config file

‘TRAJ_CAPPI_IMAGE’: Creates a CAPPI image with the trajectory position overplot on it. User defined parameters:

color_ref: str The meaning of the color code with which the trajectory is plotted. Can be ‘None’, ‘altitude’ (the absolute altitude), ‘rel_altitude’ (altitude relative to the CAPPI altitude), ‘time’ (trajectory time respect of the start of the radar scan leading to the CAPPI)

altitude: float The CAPPI altitude [m]

wfunc: str Function used in the gridding of the radar data. The function types are defined in `pyart.map.grid_from_radars`. Default ‘NEAREST’

res: float The CAPPI resolution [m]. Default 500.

Parameters

dataset [dictionary] radar object

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

no return

PYRAD.PROD.PROCESS_MONITORING_PRODUCTS

Functions for obtaining Pyrad products from monitoring datasets

`generate_monitoring_products(dataset, prdcfg)` generates a monitoring product.

`pyrad.prod.process_monitoring_products.generate_monitoring_products(dataset, prdcfg)`
generates a monitoring product. With the parameter 'hist_type' the user may define if the product is computed for each radar volume ('instant') or at the end of the processing period ('cumulative'). Default is 'cumulative'. Accepted product types:

'ANGULAR_DENSITY': For a specified elevation angle, plots a 2D histogram with the azimuth angle in the X-axis and the data values in the Y-axis. The reference values and the user defined quantiles are also plot on the same figure User defined parameters:

anglenr: int The elevation angle number to plot

quantiles: list of floats The quantiles to plot. Default 25., 50., 75.

ref_value: float The reference value

vmin, vmax [floats or None] The minimum and maximum values of the data points.
If not specified they are obtained from the Py-ART config file

'CUMUL_VOL_TS': Plots time series of the average of instantaneous quantiles stored in a csv file. User defined parameters:

quantiles: list of 3 floats the quantiles to compute. Default 25., 50., 75.

ref_value: float The reference value. Default 0

sort_by_date: Bool If true when reading the csv file containing the statistics the data is sorted by date. Default False

rewrite: Bool If true the csv file containing the statistics is rewritten

add_data_in_fname: Bool If true and the data used is cumulative the year is written in the csv file name and the plot file name

npoints_min: int Minimum number of points to use the data point in the plotting and to send an alarm. Default 0

vmin, vmax: float or None Limits of the Y-axis (data value). If None the limits are obtained from the Py-ART config file

alarm: Bool If true an alarm is sent

tol_abs: float Margin of tolerance from the reference value. If the current value is above this margin an alarm is sent. If the margin is not specified it is not possible to send any alarm

tol_trend: float Margin of tolerance from the reference value. If the trend of the last X events is above this margin an alarm is sent. If the margin is not specified it is not possible to send any alarm

nevents_min: int Minimum number of events with sufficient points to send an alarm related to the trend. If not specified it is not possible to send any alarm

sender: str The mail of the alarm sender. If not specified it is not possible to send any alarm

receiver_list: list of str The list of emails of the people that will receive the alarm.. If not specified it is not possible to send any alarm

‘PPI_HISTOGRAM’: Plots a histogram of data at a particular elevation angle. User defined parameters:

anglenr: int The elevation angle number to plot

‘SAVEVOL’: Saves the monitoring data in a C/F radar file. The data field contains histograms of data for each pair of azimuth and elevation angles

‘VOL_HISTOGRAM’: Plots a histogram of data collected from all the radar volume. User defined parameters:

write_data: bool If true the resultant histogram is also saved in a csv file. Default True.

‘VOL_TS’: Computes statistics of the gathered data and writes them in a csv file and plots a time series of those statistics. User defined parameters:

quantiles: list of 3 floats the quantiles to compute. Default 25., 50., 75.

ref_value: float The reference value. Default 0

sort_by_date: Bool If true when reading the csv file containing the statistics the data is sorted by date. Default False

rewrite: Bool If true the csv file containing the statistics is rewritten

add_data_in_fname: Bool If true and the data used is cumulative the year is written in the csv file name and the plot file name

npoints_min: int Minimum number of points to use the data point in the plotting and to send an alarm. Default 0

vmin, vmax: float or None Limits of the Y-axis (data value). If None the limits are obtained from the Py-ART config file

alarm: Bool If true an alarm is sent

tol_abs: float Margin of tolerance from the reference value. If the current value is above this margin an alarm is sent. If the margin is not specified it is not possible to send any alarm

tol_trend: float Margin of tolerance from the reference value. If the trend of the last X events is above this margin an alarm is sent. If the margin is not specified it is not possible to send any alarm

nevents_min: int Minimum number of events with sufficient points to send an alarm related to the trend. If not specified it is not possible to send any alarm

sender: str The mail of the alarm sender. If not specified it is not possible to send any alarm

receiver_list: list of str The list of emails of the people that will receive the alarm.. If not specified it is not possible to send any alarm

Parameters

dataset [dictionary] dictionary containing a histogram object and some metadata

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

filename [str] the name of the file created. None otherwise

PYRAD.PROD.PROCESS_INTERCOMP_PRODUCTS

Functions for obtaining Pyrad products from datasets used in the intercomparison process

<i>generate_intercomp_products</i> (dataset, prd-cfg)	Generates radar intercomparison products. Accepted product types:
<i>generate_colocated_gates_products</i> (dataset, ...)	Generates colocated gates products. Accepted product types:
<i>generate_time_avg_products</i> (dataset, prdcfg)	generates time average products. Accepted product types:

`pyrad.prod.process_intercomp_products.generate_colocated_gates_products` (*dataset*,
prd-cfg)

Generates colocated gates products. Accepted product types:

‘WRITE_COLOCATED_GATES’: Writes the position of the co-located gates in a csv file

All the products of the ‘VOL’ dataset group

Parameters

dataset [tuple] radar objects and colocated gates dictionary

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

filename [str] the name of the file created. None otherwise

`pyrad.prod.process_intercomp_products.generate_intercomp_products` (*dataset*,
prdcfg)

Generates radar intercomparison products. Accepted product types:

‘PLOT_AND_WRITE_INTERCOMP_TS’: Writes statistics of radar intercomparison in a file and plots the time series of the statistics. User defined parameters:

‘add_date_in_fname’: Bool If true adds the year in the csv file containing the statistics.
Default False

‘sort_by_date’: Bool If true sorts the statistics by date when reading the csv file containing the statistics. Default False

‘rewrite’: Bool If true rewrites the csv file containing the statistics. Default False

‘npoints_min’: int The minimum number of points to consider the statistics valid and therefore use the data point in the plotting. Default 0

‘corr_min’: float The minimum correlation to consider the statistics valid and therefore use the data point in the plotting. Default 0.

‘PLOT_SCATTER_INTERCOMP’: Plots a density plot with the points of radar 1 versus the points of radar 2 User defined parameters:

‘step’: float The quantization step of the data. If none it will be computed using the Py-ART config file. Default None

‘scatter_type’: str Type of scatter plot. Can be a plot for each radar volume (‘instant’) or at the end of the processing period (‘cumulative’). Default is ‘cumulative’

‘WRITE_INTERCOMP’: Writes the instantaneously intercompared data (gate positions, values, etc.) in a csv file.

‘WRITE_INTERCOMP_TIME_AVG’: Writes the time-averaged intercompared data (gate positions, values, etc.) in a csv file.

Parameters

dataset [tuple] values of colocated gates dictionary

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

filename [str] the name of the file created. None otherwise

`pyrad.prod.process_intercomp_products.generate_time_avg_products(dataset, prdcfg)`

generates time average products. Accepted product types: All the products of the ‘VOL’ dataset group

Parameters

dataset [tuple] radar objects and colocated gates dictionary

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

filename [str] the name of the file created. None otherwise

PYRAD.PROD.PROCESS_SPECTRA_PRODUCTS

Functions for obtaining Pyrad products from spectra datasets

generate_spectra_products(dataset, prdcfg) generates spectra products. Accepted product types:

`pyrad.prod.process_spectra_products.generate_spectra_products` (*dataset, prdcfg*)

generates spectra products. Accepted product types:

‘AMPLITUDE_PHASE_ANGLE_DOPPLER’: Makes an angle Doppler plot of complex spectra or IQ data. The plot can be along azimuth or along range. It is plotted separately the module and the phase of the signal. User defined parameters:

along_azi [bool] If true the plot is performed along azimuth, otherwise along elevation.
Default true

ang [float] The fixed angle (deg). Default 0.

rng [float] The fixed range (m). Default 0.

ang_tol [float] The fixed angle tolerance (deg). Default 1.

rng_tol [float] The fixed range tolerance (m). Default 50.

xaxis_info [str] The xaxis type. Can be ‘Doppler_velocity’, ‘Doppler_frequency’ or ‘pulse_number’

ampli_vmin, ampli_vmax, phase_vmin, phase_vmax [float or None] Minimum and maximum of the color scale for the module and phase

‘AMPLITUDE_PHASE_DOPPLER’: Plots a complex Doppler spectrum or IQ data making two separate plots for the module and phase of the signal User defined parameters:

azi, ele, rng [float] azimuth and elevation (deg) and range (m) of the ray to plot

azi_to, ele_tol, rng_tol [float] azimuth and elevation (deg) and range (m) tolerance respect to nominal position to plot. Default 1, 1, 50.

ind_ray, ind_rng [int] index of the ray and range to plot. Alternative to defining its antenna coordinates

xaxis_info [str] The xaxis type. Can be ‘Doppler_velocity’, ‘Doppler_frequency’ or ‘pulse_number’

ampli_vmin, ampli_vmax, phase_vmin, phase_vmax [float or None] Minimum and maximum of the color scale for the module and phase

‘AMPLITUDE_PHASE_RANGE_DOPPLER’: Plots a complex spectra or IQ data range-Doppler making two separate plots for the module and phase of the signal User defined parameters:

azi, ele [float] azimuth and elevation (deg) of the ray to plot

azi_to, ele_tol [float] azimuth and elevation (deg) tolerance respect to nominal position to plot. Default 1, 1.

ind_ray [int] index of the ray to plot. Alternative to defining its antenna coordinates

axis_info [str] The axis type. Can be 'Doppler_velocity', 'Doppler_frequency' or 'pulse_number'

ampli_vmin, ampli_vmax, phase_vmin, phase_vmax [float or None] Minimum and maximum of the color scale for the module and phase

'AMPLITUDE_PHASE_TIME_DOPPLER': Plots a complex spectra or IQ data time-Doppler making two separate plots for the module and phase of the signal User defined parameters:

axis_info [str] The axis type. Can be 'Doppler_velocity' or 'Doppler frequency'

ampli_vmin, ampli_vmax, phase_vmin, phase_vmax [float or None] Minimum and maximum of the color scale for the module and phase

plot_type [str] Can be 'final' or 'temporal'. If final the data is only plotted at the end of the processing

'ANGLE_DOPPLER': Makes an angle Doppler plot. The plot can be along azimuth or along range User defined parameters:

along_azi [bool] If true the plot is performed along azimuth, otherwise along elevation. Default true

ang [float] The fixed angle (deg). Default 0.

rng [float] The fixed range (m). Default 0.

ang_tol [float] The fixed angle tolerance (deg). Default 1.

rng_tol [float] The fixed range tolerance (m). Default 50.

axis_info [str] The axis type. Can be 'Doppler_velocity', 'Doppler_frequency' or 'pulse_number'

vmin, vmax [float or None] Minimum and maximum of the color scale

'COMPLEX_ANGLE_DOPPLER': Makes an angle Doppler plot of complex spectra or IQ data. The plot can be along azimuth or along range. The real and imaginary parts are plotted separately User defined parameters:

along_azi [bool] If true the plot is performed along azimuth, otherwise along elevation. Default true

ang [float] The fixed angle (deg). Default 0.

rng [float] The fixed range (m). Default 0.

ang_tol [float] The fixed angle tolerance (deg). Default 1.

rng_tol [float] The fixed range tolerance (m). Default 50.

axis_info [str] The axis type. Can be 'Doppler_velocity', 'Doppler_frequency' or 'pulse_number'

vmin, vmax [float or None] Minimum and maximum of the color scale

'COMPLEX_DOPPLER': Plots a complex Doppler spectrum or IQ data making two separate plots for the real and imaginary parts User defined parameters:

azi, ele, rng [float] azimuth and elevation (deg) and range (m) of the ray to plot

azi_to, ele_tol, rng_tol [float] azimuth and elevation (deg) and range (m) tolerance respect to nominal position to plot. Default 1, 1, 50.

ind_ray, ind_rng [int] index of the ray and range to plot. Alternative to defining its antenna coordinates

xaxis_info [str] The xaxis type. Can be 'Doppler_velocity', 'Doppler_frequency' or 'pulse_number'

vmin, vmax [float or None] Minimum and maximum of the color scale

'COMPLEX_RANGE_DOPPLER': Plots the complex spectra or IQ data range-Doppler making two separate plots for the real and imaginary parts User defined parameters:

azi, ele [float] azimuth and elevation (deg) of the ray to plot

azi_to, ele_tol [float] azimuth and elevation (deg) tolerance respect to nominal position to plot. Default 1, 1.

ind_ray [int] index of the ray to plot. Alternative to defining its antenna coordinates

xaxis_info [str] The xaxis type. Can be 'Doppler_velocity', 'Doppler_frequency' or 'pulse_number'

vmin, vmax [float or None] Minimum and maximum of the color scale

'COMPLEX_TIME_DOPPLER': Plots the complex spectra or IQ data time-Doppler making two separate plots for the real and imaginary parts User defined parameters:

xaxis_info [str] The xaxis type. Can be 'Doppler_velocity' or 'Doppler frequency'

vmin, vmax [float or None] Minimum and maximum of the color scale

plot_type [str] Can be 'final' or 'temporal'. If final the data is only plotted at the end of the processing

'DOPPLER': Plots a Doppler spectrum variable or IQ data variable

User defined parameters:

azi, ele, rng [float] azimuth and elevation (deg) and range (m) of the ray to plot

azi_to, ele_tol, rng_tol [float] azimuth and elevation (deg) and range (m) tolerance respect to nominal position to plot. Default 1, 1, 50.

ind_ray, ind_rng [int] index of the ray and range to plot. Alternative to defining its antenna coordinates

xaxis_info [str] The xaxis type. Can be 'Doppler_velocity', 'Doppler_frequency' or 'pulse_number'

vmin, vmax [float or None] Minimum and maximum of the color scale

'RANGE_DOPPLER': Makes a range-Doppler plot of spectral or IQ data

User defined parameters:

azi, ele [float] azimuth and elevation (deg) of the ray to plot

azi_to, ele_tol [float] azimuth and elevation (deg) tolerance respect to nominal position to plot. Default 1, 1.

ind_ray [int] index of the ray to plot. Alternative to defining its antenna coordinates

xaxis_info [str] The xaxis type. Can be 'Doppler_velocity', 'Doppler_frequency' or 'pulse_number'

vmin, vmax [float or None] Minimum and maximum of the color scale

‘SAVEALL’: Saves radar spectra or IQ volume data including all or a list of userdefined fields in a netcdf file User defined parameters:

datatypes: list of str or None The list of data types to save. If it is None, all fields in the radar object will be saved

physical: Bool If True the data will be saved in physical units (floats). Otherwise it will be quantized and saved as binary

‘SAVEVOL’: Saves one field of a radar spectra or IQ volume data in a netcdf file User defined parameters:

physical: Bool If True the data will be saved in physical units (floats). Otherwise it will be quantized and saved as binary

‘TIME_DOPPLER’: Makes a time-Doppler plot of spectral or IQ data at a point of interest. User defined parameters:

xaxis_info [str] The xaxis type. Can be ‘Doppler_velocity’, ‘Doppler_frequency’ or ‘pulse_number’

vmin, vmax [float or None] Minimum and maximum of the color scale

plot_type [str] Can be ‘final’ or ‘temporal’. If final the data is only plotted at the end of the processing

Parameters

dataset [spectra] spectra object

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

None or name of generated files

PYRAD.PROD.PROCESS_PRODUCT

Functions for obtaining Pyrad products from the datasets

generate_traj_product(traj, prdcfg) Generates trajectory products. Accepted product types:

`pyrad.prod.process_traj_products.generate_traj_product` (*traj*, *prdcfg*)

Generates trajectory products. Accepted product types:

‘TRAJ_MAP’: Plots the trajectory on a lat-lon map with the altitude color coded

‘TRAJ_PLOT’: Plots time series of the trajectory respect to the radar elevation, azimuth or range
User defined parameters:

‘datatype’: str The type of parameter: ‘EL’, ‘AZ’, or ‘RANGE’

‘TRAJ_TEXT’: Writes the trajectory information in a csv file

Parameters

traj [Trajectory object]

prdcfg [dictionary of dictionaries] product configuration dictionary of dictionaries

Returns

None

PYRAD.IO.IO_AUX

Auxiliary functions for reading/writing files

<i>get_rad4alp_prod_fname</i> (datatype)	Given a datatype find the corresponding start and termination of the METRANET product file name
<i>map_hydro</i> (hydro_data_op)	maps the operational hydrometeor classification identifiers to the ones used by Py-ART
<i>map_Doppler</i> (Doppler_data_bin, Nyquist_vel)	maps the binary METRANET Doppler data to actual Doppler velocity
<i>get_save_dir</i> (basepath, procname, dsname, prd-name)	obtains the path to a product directory and eventually creates it
<i>make_filename</i> (prdtype, dstype, dsname, ext_list)	creates a product file name
<i>generate_field_name_str</i> (datatype)	Generates a field name in a nice to read format.
<i>get_datatype_metrانet</i> (datatype)	maps the config file radar data type name into the corresponding metranet data type name and Py-ART field name
<i>get_datatype_odim</i> (datatype)	maps the config file radar data type name into the corresponding odim data type name and Py-ART field name
<i>get_fieldname_pyart</i> (datatype)	maps the config file radar data type name into the corresponding rainbow Py-ART field name
<i>get_fieldname_cosmo</i> (field_name)	maps the Py-ART field name into the corresponding COSMO variable name
<i>get_field_unit</i> (datatype)	Return unit of datatype.
<i>get_field_name</i> (datatype)	Return long name of datatype.
<i>get_file_list</i> (datadescriptor, starttimes, ...)	gets the list of files with a time period
<i>get_rad4alp_dir</i> (basepath, voltime[, ...])	gets the directory where rad4alp data is stored
<i>get_rad4alp_grid_dir</i> (basepath, voltime, ...)	gets the directory where rad4alp grid data is stored
<i>get_trtfile_list</i> (basepath, starttime, endtime)	gets the list of TRT files with a time period
<i>get_scan_list</i> (scandescrptor_list)	determine which is the scan list for each radar
<i>get_new_rainbow_file_name</i> (master_fname, ...)	get the rainbow file name containing datatype from a master file name and data type
<i>get_datatype_fields</i> (datadescriptor)	splits the data type descriptor and provides each individual member
<i>get_dataset_fields</i> (datasetdescr)	splits the dataset type descriptor and provides each individual member
<i>get_datetime</i> (fname, datadescriptor)	Given a data descriptor gets date and time from file name
<i>find_raw_cosmo_file</i> (voltime, datatype, cfg)	Search a COSMO file in netcdf format
<i>find_cosmo_file</i> (voltime, datatype, cfg, scanid)	Search a COSMO file in Rainbow format
<i>find_hzt_file</i> (voltime, cfg[, ind_rad])	Search an ISO-0 degree file in HZT format

Continued on next page

Table 1 – continued from previous page

<code>find_rad4alpcosmo_file(voltime, datatype, ...)</code>	Search a COSMO file
<code>find_pyradcosmo_file(basepath, voltime, ...)</code>	Search a COSMO file in CFRadial or ODIM format
<code>_get_datetime(fname, datagroup[, ftime_format])</code>	Given a data group gets date and time from file name
<code>find_date_in_file_name(filename[, date_format])</code>	Find a date with date format defined in date_format in a file name.

`pyrad.io.io_aux._get_datetime(fname, datagroup, ftime_format=None)`

Given a data group gets date and time from file name

Parameters

fname [str] file name

datadescriptor [str] radar field type. Format : [radar file type]:[datatype]

ftime_format [str or None] if the file is of type ODIM this contain the file time format

Returns

fdatetime [datetime object] date and time in file name

`pyrad.io.io_aux.find_cosmo_file(voltime, datatype, cfg, scanid, ind_rad=0)`

Search a COSMO file in Rainbow format

Parameters

voltime [datetime object] volume scan time

datatype [str] type of COSMO data to look for

cfg [dictionary of dictionaries] configuration info to figure out where the data is

scanid [str] name of the scan

ind_rad [int] radar index

Returns

fname [str] Name of COSMO file if it exists. None otherwise

`pyrad.io.io_aux.find_date_in_file_name(filename, date_format='%Y%m%d%H%M%S')`

Find a date with date format defined in date_format in a file name. If no date is found returns None

Parameters

filename [str] file name

date_format [str] The time format

Returns

fdatetime [datetime object] date and time in file name

`pyrad.io.io_aux.find_hzt_file(voltime, cfg, ind_rad=0)`

Search an ISO-0 degree file in HZT format

Parameters

voltime [datetime object] volume scan time

cfg [dictionary of dictionaries] configuration info to figure out where the data is

ind_rad [int] radar index

Returns

fname [str] Name of HZT file if it exists. None otherwise

`pyrad.io.io_aux.find_pyradcosmo_file(basepath, voltime, datatype, cfg, dataset)`
Search a COSMO file in CFRadial or ODIM format

Parameters

basepath [str] base path to the COSMO file

voltime [datetime object] volume scan time

datatype [str] type of COSMO data to look for

cfg [dictionary of dictionaries] configuration info to figure out where the data is

dataset [str] name of the folder where the data is stored

Returns

fname [str] Name of COSMO file if it exists. None otherwise

`pyrad.io.io_aux.find_rad4alpcosmo_file(voltime, datatype, cfg, scanid, ind_rad=0)`
Search a COSMO file

Parameters

voltime [datetime object] volume scan time

datatype [str] type of COSMO data to look for

cfg: dictionary of dictionaries configuration info to figure out where the data is

ind_rad: int radar index

Returns

fname [str] Name of COSMO file if it exists. None otherwise

scanid: str name of the scan

`pyrad.io.io_aux.find_raw_cosmo_file(voltime, datatype, cfg, ind_rad=0)`
Search a COSMO file in netcdf format

Parameters

voltime [datetime object] volume scan time

datatype [str] type of COSMO data to look for

cfg [dictionary of dictionaries] configuration info to figure out where the data is

ind_rad [int] radar index

Returns

fname [str] Name of COSMO file if it exists. None otherwise

`pyrad.io.io_aux.generate_field_name_str(datatype)`
Generates a field name in a nice to read format.

Parameters

datatype [str] The data type

Returns

field_str [str] The field name

`pyrad.io.io_aux.get_dataset_fields(datasetdescr)`
splits the dataset type descriptor and provides each individual member

Parameters

datasetdescr [str] dataset type. Format : [processing level]:[dataset type]

Returns

proclevel [str] dataset processing level

dataset [str] dataset type, i.e. dBZ, ZDR, ISO0, ...

`pyrad.io.io_aux.get_datatype_fields(datadescriptor)`
splits the data type descriptor and provides each individual member

Parameters

datadescriptor [str] radar field type. Format : [radar file type]:[datatype]

Returns

radarnr [str] radar number, i.e. RADAR1, RADAR2, ...

datagroup [str] data type group, i.e. RAINBOW, RAD4ALP, ODIM, CFRADIAL, COSMO, MXPOL ...

datatype [str] data type, i.e. dBZ, ZDR, ISO0, ...

dataset [str] dataset type (for saved data only)

product [str] product type (for saved data only)

`pyrad.io.io_aux.get_datatype_metranet(datatype)`
maps de config file radar data type name into the corresponding metranet data type name and Py-ART field name

Parameters

datatype [str] config file radar data type name

Returns

metranet type [dict] dictionary containing the metranet data type name and its corresponding Py-ART field name

`pyrad.io.io_aux.get_datatype_odim(datatype)`
maps the config file radar data type name into the corresponding odim data type name and Py-ART field name

Parameters

datatype [str] config file radar data type name

Returns

metranet type [dict] dictionary containing the odim data type name and its corresponding Py-ART field name

`pyrad.io.io_aux.get_datetime(fname, datadescriptor)`
Given a data descriptor gets date and time from file name

Parameters

fname [str] file name

datadescriptor [str] radar field type. Format : [radar file type]:[datatype]

Returns

fdatetime [datetime object] date and time in file name

`pyrad.io.io_aux.get_field_name(datatype)`

Return long name of datatype.

Parameters

datatype [str] The data type

Returns

name [str] The name

`pyrad.io.io_aux.get_field_unit(datatype)`

Return unit of datatype.

Parameters

datatype [str] The data type

Returns

unit [str] The unit

`pyrad.io.io_aux.get_fieldname_cosmo(field_name)`

maps the Py-ART field name into the corresponding COSMO variable name

Parameters

field_name [str] Py-ART field name

Returns

cosmo_name [str] Py-ART variable name

`pyrad.io.io_aux.get_fieldname_pyart(datatype)`

maps the config file radar data type name into the corresponding rainbow Py-ART field name

Parameters

datatype [str] config file radar data type name

Returns

field_name [str] Py-ART field name

`pyrad.io.io_aux.get_file_list(datadescriptor, starttimes, endtimes, cfg, scan=None)`

gets the list of files with a time period

Parameters

datadescriptor [str] radar field type. Format : [radar file type]:[datatype]

starttimes [array of datetime objects] start of time periods

endtimes [array of datetime object] end of time periods

cfg: dictionary of dictionaries configuration info to figure out where the data is

scan [str] scan name

Returns

filelist [list of strings] list of files within the time period

`pyrad.io.io_aux.get_new_rainbow_file_name(master_fname, master_datadescriptor, datatype)`

get the rainbow file name containing datatype from a master file name and data type

Parameters

master_fname [str] the master file name

master_datadescriptor [str] the master data type descriptor

datatype [str] the data type of the new file name to be created

Returns

new_fname [str] the new file name

`pyrad.io.io_aux.get_rad4alp_dir(basepath, voltime, radar_name='A', radar_res='L', scan='001', path_convention='MCH')`
gets the directory where rad4alp data is stored

Parameters

basepath [str] base path

voltime [datetime object] nominal time

radar_name [str] radar name (A, D, L, P, W)

radar_res [str] radar resolution (H, L)

scan [str] scan

path_convention [str] The path convention. Can be 'LTE', 'MCH' or 'RT'

Returns

datapath [str] The data path

basename [str] The base name. ex: PHA17213

`pyrad.io.io_aux.get_rad4alp_grid_dir(basepath, voltime, datatype, acronym, path_convention='MCH')`
gets the directory where rad4alp grid data is stored

Parameters

basepath [str] base path

voltime [datetime object] nominal time

datatype [str] data type

acronym [str] acronym identifying the data type

path_convention [str] The path convention. Can be 'LTE', 'MCH' or 'RT'

Returns

datapath [str] The data path

`pyrad.io.io_aux.get_rad4alp_prod_fname(datatype)`
Given a datatype find the corresponding start and termination of the METRANET product file name

Parameters

datatype [str] the data type

Returns

acronym [str] The start of the METRANET file name

termination [str] The end of the METRANET file name

`pyrad.io.io_aux.get_save_dir(basepath, procname, dsname, prdname, timeinfo=None, timeformat='%Y-%m-%d', create_dir=True)`
obtains the path to a product directory and eventually creates it

Parameters

basepath [str] product base path

procname [str] name of processing space

dsname [str] data set name

prdname [str] product name

timeinfo [datetime] time info to generate the date directory. If None there is no time format in the path

timeformat [str] Optional. The time format.

create_dir [boolean] If True creates the directory

Returns

savedir [str] path to product

`pyrad.io.io_aux.get_scan_list(scandescrptor_list)`
determine which is the scan list for each radar

Parameters

scandescrptor [list of string] the list of all scans for all radars

Returns

scan_list [list of lists] the list of scans corresponding to each radar

`pyrad.io.io_aux.get_trtfile_list(basepath, starttime, endtime)`
gets the list of TRT files with a time period

Parameters

datapath [str] directory where to look for data

starttime [datetime object] start of time period

endtime [datetime object] end of time period

Returns

filelist [list of strings] list of files within the time period

`pyrad.io.io_aux.make_filename(prdtype, dstype, dsname, ext_list, prdcfginfo=None, timeinfo=None, timeformat='%Y%m%d%H%M%S', runinfo=None)`
creates a product file name

Parameters

timeinfo [datetime] time info to generate the date directory

prdtype [str] product type, i.e. 'ppi', etc.

dstype [str] data set type, i.e. 'raw', etc.

dsname [str] data set name

ext_list [list of str] file name extensions, i.e. 'png'

prdcfginfo [str] Optional. string to add product configuration information, i.e. 'el0.4'

timeformat [str] Optional. The time format

runinfo [str] Optional. Additional information about the test (e.g. 'RUN01', 'TS011')

Returns

fname_list [list of str] list of file names (as many as extensions)

`pyrad.io.io_aux.map_Doppler(Doppler_data_bin, Nyquist_vel)`
maps the binary METRANET Doppler data to actual Doppler velocity

Parameters

Doppler_data_bin [numpy array] The binary METRANET data

Returns

Doppler_data [numpy array] The Doppler velocity in [m/s]

`pyrad.io.io_aux.map_hydro(hydro_data_op)`
maps the operational hydrometeor classification identifiers to the ones used by Py-ART

Parameters

hydro_data_op [numpy array] The operational hydrometeor classification data

Returns

hydro_data_py [numpy array] The pyart hydrometeor classification data

PYRAD.IO.CONFIG

Functions for reading pyrad config files

<i>read_config</i> (fname[, cfg])	Read a pyrad config file.
<i>get_num_elements</i> (dtype, nelstr)	Checks if data type is an array or a structure.
<i>string_to_datatype</i> (dtype, strval)	Converts a string containing a value into its Python value
<i>get_array</i> (cfgfile, pos, nel, valtype)	reads an array in a config file
<i>get_struct</i> (cfgfile, pos, nels, fname)	reads an struct in a config file
<i>get_array_type</i> (dtype)	Determines Python array type from the config file array type
<i>init_array</i> (nel, dtype)	Initializes a Python array

`pyrad.io.config.get_array` (*cfgfile*, *pos*, *nel*, *valtype*)
reads an array in a config file

Parameters

cfgfile [file object] config file
pos [int] position in file object
nel [int] number of elements of the ray
valtype [str] type of array

Returns

arr [array] array values
newpos [int] new position in file object

`pyrad.io.config.get_array_type` (*dtype*)
Determines Python array type from the config file array type

Parameters

dtype [str] config file data type

Returns

pytype [str] Python array type

`pyrad.io.config.get_num_elements` (*dtype*, *nelstr*)
Checks if data type is an array or a structure.

Parameters

dtype [str] data type specifier

nelstr [str] number of elements

Returns

nel [int] number of elements if type is *ARR or STRUCT. 0 otherwise

isstruct [bool] true if the type is STRUCT

`pyrad.io.config.get_struct(cfgfile, pos, nels, fname)`
reads an struct in a config file

Parameters

cfgfile [file object] config file

pos [int] position in file object

nel [int] number of elements of the ray

fname [str] config file name

Returns

struct [dict] dictionary of struct values

newpos [int] new position in file object

`pyrad.io.config.init_array(nel, dtype)`
Initializes a Python array

Parameters

nel [int] number of elements in the array

dtype [str] config file data type

Returns

pyarr [array] Python array

`pyrad.io.config.read_config(fname, cfg=None)`
Read a pyrad config file.

Parameters

fname [str] Name of the configuration file to read.

cfg [dict of dicts, optional] dictionary of dictionaries containing configuration parameters where the new parameters will be placed

Returns

cfg [dict of dicts] dictionary of dictionaries containing the configuration parameters

`pyrad.io.config.string_to_datatype(dtype, strval)`
Converts a string containing a value into its Python value

Parameters

dtype [str] data type specifier

strval [str] string value

Returns

val [scalar] value contained in the string

PYRAD.IO.READ_DATA_RADAR

Functions for reading radar data files

<i>get_data</i> (voltime, datatypesdescr, cfg)	Reads pyrad input data.
<i>merge_scans_rainbow</i> (basepath, scan_list, ...)	merge rainbow scans
<i>merge_scans_psr</i> (basepath, basepath_psr, ...)	merge rainbow scans
<i>merge_scans_psr_spectra</i> (basepath, ...[, radarnr])	merge rainbow scans
<i>merge_scans_dem</i> (basepath, scan_list, ...[, ...])	merge rainbow scans
<i>merge_scans_rad4alp</i> (basepath, scan_list, ...)	merge rad4alp data.
<i>merge_scans_odim</i> (basepath, scan_list, ...[, ...])	merge odim data.
<i>merge_scans_nexrad2</i> (basepath, scan_list, ...)	merge NEXRAD level 2 data.
<i>merge_scans_cfradial2</i> (basepath, scan_list, ...)	merge CFRADIAL2 data.
<i>merge_scans_cf1</i> (basepath, scan_list, ...[, ...])	merge CF1 data.
<i>merge_scans_cosmo</i> (voltime, datatype_list, cfg)	merge rainbow scans
<i>merge_scans_cosmo_rad4alp</i> (voltime, datatype, cfg)	merge cosmo rad4alp scans.
<i>merge_scans_dem_rad4alp</i> (voltime, datatype, cfg)	merge DEM rad4alp scans.
<i>merge_scans_other_rad4alp</i> (voltime, datatype, cfg)	merge other rad4alp polar products not contained in the basic M or P files, i.e.
<i>merge_scans_iq_rad4alp</i> (basepath, ...[, ...])	merge rad4alp IQ scans
<i>merge_fields_rainbow</i> (basepath, scan_name, ...)	merge Rainbow fields into a single radar object.
<i>merge_fields_psr</i> (basepath, basepath_psr, ...)	merge Rainbow fields into a single radar object.
<i>merge_fields_psr_spectra</i> (basepath, ...[, ...])	merge Rainbow fields into a single radar object.
<i>merge_fields_rad4alp_grid</i> (voltime, ...[, ...])	merge rad4alp Cartesian products
<i>merge_fields_pyrad</i> (basepath, loadname, ...)	merge fields from Pyrad-generated files into a single radar object.
<i>merge_fields_pyradcosmo</i> (basepath, voltime, ...)	merge fields from Pyrad-generated files into a single radar object.
<i>merge_fields_pyradgrid</i> (basepath, loadname, ...)	merge fields from Pyrad-generated files into a single radar object.
<i>merge_fields_pyrad_spectra</i> (basepath, ...[, ...])	merge fields from Pyrad-generated files into a single radar spectra object.
<i>merge_fields_dem</i> (basepath, scan_name, ...)	merge DEM fields into a single radar object.
<i>merge_fields_cosmo</i> (filename_list)	merge COSMO fields in Rainbow file format

Continued on next page

Table 1 – continued from previous page

<code>get_data_rainbow(filename, datatype)</code>	gets rainbow radar data
<code>get_data_rad4alp(filename, datatype_list, ...)</code>	gets rad4alp radar data
<code>get_data_odim(filename, datatype_list, ...)</code>	gets ODIM radar data
<code>add_field(radar_dest, radar_orig)</code>	adds the fields from orig radar into dest radar.
<code>interpol_field(radar_dest, radar_orig, ...)</code>	interpolates field field_name contained in radar_orig to the grid in radar_dest
<code>crop_grid(grid[, lat_min, lat_max, lon_min, ...])</code>	crops a grid object
<code>merge_grids(grid1, grid2)</code>	Merges two grids

`pyrad.io.read_data_radar.add_field(radar_dest, radar_orig)`

adds the fields from orig radar into dest radar. If they are not in the same grid, interpolates them to dest grid

Parameters

radar_dest [radar object] the destination radar

radar_orig [radar object] the radar object containing the original field

Returns

field_dest [dict] interpolated field and metadata

`pyrad.io.read_data_radar.crop_grid(grid, lat_min=None, lat_max=None, lon_min=None, lon_max=None, alt_min=None, alt_max=None)`

crops a grid object

Parameters

grid [grid object] the grid object to crop

lat_min, lat_max, lon_min, lon_max [float] the lat/lon limits of the object (deg)

alt_min, alt_max [float] the altitude limits of the object (m MSL)

Returns

grid_crop [grid object] The cropped grid

`pyrad.io.read_data_radar.get_data(voltime, datatypesdescr, cfg)`

Reads pyrad input data.

Parameters

voltime [datetime object] volume scan time

datatypesdescr [list] list of radar field types to read. Format :
[radarnr]:[datagroup]:[datatype],[dataset],[product] 'dataset' is only specified for data groups 'ODIM', 'CFRADIAL', 'CFRADIAL2', 'CF1', 'ODIMPYRAD' 'PYRAD-GRID' and 'NETCDFSPECTRA'. 'product' is only specified for data groups 'CFRADIAL', 'ODIMPYRAD', 'PYRADGRID' and 'NETCDFSPECTRA' The data group specifies the type file from which data is extracted. It can be:

'RAINBOW': Proprietary Leonardo format 'COSMO': COSMO model data saved in Rainbow file format 'DEM': Visibility data saved in Rainbow file format 'PSR': Reads PSR data file to extract range gate information

(Noise and transmitted power)

'RAD4ALP': METRANET format used for the operational MeteoSwiss data. To find out which datatype to use to match a particular METRANET field name check the function 'get_datatype_metrnet' in `pyrad/io/io_aux.py`

‘RAD4ALPCOSMO’: COSMO model data saved in a binary file format.

Used by operational MeteoSwiss radars

‘RAD4ALPDEM’: Visibility data saved in a binary format used by operational MeteoSwiss radars

‘RAD4ALPHYDRO’: Used to read the MeteoSwiss operational hydrometeor classification

‘RAD4ALPDOPPLER’: Used to read the MeteoSwiss operational dealiased Doppler velocity

‘ODIM’: Generic ODIM file format. For such types ‘dataset’ specifies the directory and file name date convention. Example: ODIM:dBZ,D{%Y-%m-%d}-F{%Y%m%d%H%M%S}. To find out which datatype to use to match a particular ODIM field name check the function ‘get_datatype_odim’ in pyrad/io/io_aux.py

‘NEXRADII’: Nexrad-level II file format.

‘CFRADIAL2’: CFRADIAL2 file format. For such types ‘dataset’ specifies the directory and file name date convention. Example: ODIM:dBZ,D{%Y-%m-%d}-F{%Y%m%d%H%M%S}. To find out which datatype to use to match a particular ODIM field name check the function ‘get_datatype_odim’ in pyrad/io/io_aux.py

‘CF1’: CF1 file format. For such types ‘dataset’ specifies the directory and file name date convention. Example: ODIM:dBZ,D{%Y-%m-%d}-F{%Y%m%d%H%M%S}. To find out which datatype to use to match a particular ODIM field name check the function ‘get_datatype_odim’ in pyrad/io/io_aux.py

‘MXPOL’: MXPOL (EPFL) data written in a netcdf file

‘CFRADIAL’: CFRadial format with the naming convention and directory structure in which Pyrad saves the data. For such datatypes ‘dataset’ specifies the directory where the dataset is stored and ‘product’ specifies the directory where the product is stored. Example: CFRADIAL:dBZc,Att_ZPhi,SAVEVOL_dBZc

‘CFRADIALCOSMO’: COSMO data in radar coordinates in a CFRadial file format. **‘ODIMPYRAD’:** ODIM file format with the naming convention and

directory structure in which Pyrad saves the data. For such datatypes ‘dataset’ specifies the directory where the dataset is stored and ‘product’ specifies the directory where the product is stored. Example: ODIMPYRAD:dBZc,Att_ZPhi,SAVEVOL_dBZc

‘RAD4ALPGRID’: METRANET format used for the operational MeteoSwiss Cartesian products.

‘RAD4ALPGIF’: Format used for operational MeteoSwiss Cartesian products stored as gif files

‘PYRADGRID’: Pyrad generated Cartesian grid products. For such datatypes ‘dataset’ specifies the directory where the dataset is stored and ‘product’ specifies the directory where the product is stored. Example: ODIMPYRAD:RR,RZC,SAVEVOL

‘PSRSPECTRA’: Format used to store Rainbow power spectra recordings.

‘NETCDFSPECTRA’: Format analogous to CFRadial and used to store
Doppler spectral

‘RAD4ALPIQ’: Format used to store rad4alp IQ data

‘RAINBOW’, ‘RAD4ALP’, ‘ODIM’, ‘CFRADIAL2’, ‘CF1’ and ‘MXPOL’ are primary data file sources and they cannot be mixed for the same radar. It is also the case for their complementary data files, i.e. ‘COSMO’ and ‘RAD4ALPCOSMO’, etc. ‘CFRADIAL’ and ‘ODIMPYRAD’ are secondary data file sources and they can be combined with any other datagroup type. For a list of accepted datatypes and how they map to the Py-ART name convention check function ‘get_field_name_pyart’ in pyrad/io/io_aux.py

cfg: dictionary of dictionaries configuration info to figure out where the data is

Returns

radar [Radar] radar object

`pyrad.io.read_data_radar.get_data_mxpole(filename, datatype_list)`
gets MXPOL radar data

Parameters

filename [str] name of file containing MXPOL data

datatype_list [list of strings] list of data fields to get

Returns

radar [Radar] radar object

`pyrad.io.read_data_radar.get_data_odim(filename, datatype_list, scan_name, cfg, ind_rad=0)`
gets ODIM radar data

Parameters

filename [str] name of file containing odim data

datatype_list [list of strings] list of data fields to get

scan_name [str] name of the elevation (001 to 020)

cfg [dict] configuration dictionary

ind_rad [int] radar index

Returns

radar [Radar] radar object. None if the reading has not been successful

`pyrad.io.read_data_radar.get_data_rad4alpe(filename, datatype_list, scan_name, cfg, ind_rad=0)`
gets rad4alp radar data

Parameters

filename [str] name of file containing rainbow data

datatype_list [list of strings] list of data fields to get

scan_name [str] name of the elevation (001 to 020)

cfg [dict] configuration dictionary

ind_rad [int] radar index

Returns

radar [Radar] radar object. None if the reading has not been successful

`pyrad.io.read_data_radar.get_data_rainbow(filename, datatype)`
gets rainbow radar data

Parameters

filename [str] name of file containing rainbow data

datatype [str] field name

Returns

radar [Radar or None] radar object if the reading of the data has been successful. None otherwise

`pyrad.io.read_data_radar.interpolate_field(radar_dest, radar_orig, field_name, fill_value=None, ang_tol=0.5)`
interpolates field field_name contained in radar_orig to the grid in radar_dest

Parameters

radar_dest [radar object] the destination radar

radar_orig [radar object] the radar object containing the original field

field_name: str name of the field to interpolate

fill_value: float The fill value

ang_tol [float] angle tolerance to determine whether the radar origin sweep is the radar destination sweep

Returns

field_dest [dict] interpolated field and metadata

`pyrad.io.read_data_radar.merge_fields_cosmo(filename_list)`
merge COSMO fields in Rainbow file format

Parameters

filename_list [str] list of file paths where to find the data

Returns

radar [Radar] radar object

`pyrad.io.read_data_radar.merge_fields_dem(basepath, scan_name, datatype_list)`
merge DEM fields into a single radar object.

Parameters

basepath [str] name of the base path where to find the data

scan_name: str name of the scan

datatype_list [list] lists of data types to get

Returns

radar [Radar] radar object

```
pyrad.io.read_data_radar.merge_fields_psr(basepath,      basepath_psr,      scan_name,
                                           voltime,      datatype_list,  undo_txcorr=True,
                                           cpi='low_prf',  ang_tol=0.5,  azi_min=None,
                                           azi_max=None,      ele_min=None,
                                           ele_max=None,      rng_min=None,
                                           rng_max=None)
```

merge Rainbow fields into a single radar object.

Parameters

basepath [str] name of the base path where to find the data

basepath_psr [str] name of the base path where to find the PSR data

scan_name: str name of the scan

voltime [datetime object] reference time of the scan

datatype_list [list] lists of data types to get

undo_txcorr [Bool] If true the correction for transmitted power is undone when getting the noise

cpi [str] The CPI to use. Can be 'low_prf', 'intermediate_prf', 'high_prf', 'mean', 'all'. If 'mean' the mean within the angle step is taken

ang_tol [float] Tolerated angle distance between nominal radar angle and angle in PSR files

azi_min, azi_max, ele_min, ele_max [float or None] The minimum and maximum angles to keep (deg)

rng_min, rng_max [float or None] The minimum and maximum ranges to keep (m)

Returns

radar [Radar] radar object

```
pyrad.io.read_data_radar.merge_fields_psr_spectra(basepath,      basepath_psr,
                                                    scan_name, voltime, datatype_list,
                                                    undo_txcorr=True, fold=True, positive_away=True,
                                                    cpi='low_prf',
                                                    ang_tol=0.5,      azi_min=None,
                                                    azi_max=None,      ele_min=None,
                                                    ele_max=None,      rng_min=None,
                                                    rng_max=None)
```

merge Rainbow fields into a single radar object.

Parameters

basepath [str] name of the base path where to find the data

basepath_psr [str] name of the base path where to find the PSR data

scan_name: str name of the scan

voltime [datetime object] reference time of the scan

datatype_list [list] lists of data types to get

undo_txcorr: Bool If True the correction of the transmitted power is removed from the noise signal

fold: Bool If True the spectra is folded so that 0-Doppler is in the middle

positive_away: Bool If True the spectra is reversed so that positive velocities are away from the radar

cpi [str] The CPI to use. Can be 'low_prf', 'intermediate_prf', 'high_prf' or 'all'

ang_tol [float] Tolerated angle distance between nominal radar angle and angle in PSR files

azi_min, azi_max, ele_min, ele_max [float or None] The minimum and maximum angles to keep (deg)

rng_min, rng_max [float or None] The minimum and maximum ranges to keep (m)

Returns

psr [radar spectra object] radar spectra object

`pyrad.io.read_data_radar.merge_fields_pyrad` (*basepath, loadname, voltime, datatype_list, dataset_list, product_list, rng_min=None, rng_max=None, azi_min=None, azi_max=None, ele_min=None, ele_max=None, termination='.nc'*)

merge fields from Pyrad-generated files into a single radar object. Accepted file types are CFRadial and ODIM.

Parameters

basepath [str] name of the base path where to find the data

loadname: str name of the saving directory

voltime [datetime object] reference time of the scan

datatype_list [list] list of data types to get

dataset_list [list] list of datasets that produced the data type to get. Used to get path.

product_list [list] list of products. Used to get path

rng_min, rng_max [float] The range limits [m]. If None the entire coverage of the radar is going to be used

ele_min, ele_max, azi_min, azi_max [float or None] The limits of the grid [deg]. If None the limits will be the limits of the radar volume

termination [str] file termination type. Can be '.nc' or '.h*'

Returns

radar [Radar] radar object

`pyrad.io.read_data_radar.merge_fields_pyrad_spectra` (*basepath, loadname, voltime, datatype_list, dataset_list, product_list, rng_min=None, rng_max=None, azi_min=None, azi_max=None, ele_min=None, ele_max=None, termination='.nc'*)

merge fields from Pyrad-generated files into a single radar spectra object. Accepted file types are netcdf

Parameters

basepath [str] name of the base path where to find the data

loadname: str name of the saving directory

voltime [datetime object] reference time of the scan

datatype_list [list] list of data types to get

dataset_list [list] list of datasets that produced the data type to get. Used to get path.

product_list [list] list of products. Used to get path

rng_min, rng_max [float] The range limits [m]. If None the entire coverage of the radar is going to be used

ele_min, ele_max, azi_min, azi_max [float or None] The limits of the grid [deg]. If None the limits will be the limits of the radar volume

termination [str] file termination type. Can be '.nc' or '.h*'

Returns

radar [Radar] radar object

```
pyrad.io.read_data_radar.merge_fields_pyradcosmo(basepath, voltime, datatype_list,  
                                                dataset_list, cfg, rng_min=None,  
                                                rng_max=None, azi_min=None,  
                                                azi_max=None, ele_min=None,  
                                                ele_max=None, termination='.nc')
```

merge fields from Pyrad-generated files into a single radar object. Accepted file types are CFRadial and ODIM.

Parameters

basepath [str] name of the base path where to find the data

voltime [datetime object] reference time of the scan

datatype_list [list] list of data types to get

dataset_list [list] list of datasets that produced the data type to get. Used to get path.

cfg [dictionary of dictionaries] configuration info

rng_min, rng_max [float] The range limits [m]. If None the entire coverage of the radar is going to be used

ele_min, ele_max, azi_min, azi_max [float or None] The limits of the grid [deg]. If None the limits will be the limits of the radar volume

termination [str] file termination type. Can be '.nc' or '.h*'

Returns

radar [Radar] radar object

```
pyrad.io.read_data_radar.merge_fields_pyradgrid(basepath, loadname, voltime,  
                                                datatype_list, dataset_list, prod-  
                                                uct_list, cfg, termination='.nc')
```

merge fields from Pyrad-generated files into a single radar object. Accepted file types are CFRadial and ODIM.

Parameters

basepath [str] name of the base path where to find the data

loadname: str name of the saving directory

voltime [datetime object] reference time of the scan

datatype_list [list] list of data types to get

dataset_list [list] list of datasets that produced the data type to get. Used to get path.

product_list [list] list of products. Used to get path

cfg [dict] dictionary containing configuration parameters

termination [str] file termination type. Can be '.nc' or '.h*'

Returns

grid [Grid] grid object

`pyrad.io.read_data_radar.merge_fields_rad4alp_grid`(*voltime*, *datatype_list*, *cfg*,
ind_rad=0,*ftype*='METRANET')

merge rad4alp Cartesian products

Parameters

voltime: datetime object reference time of the scan

datatype [str] name of the data type to read

cfg [dict] configuration dictionary

ind_rad [int] radar index

ftype [str] File type. Can be 'METRANET', 'gif' or 'bin'

Returns

radar [Radar] radar object

`pyrad.io.read_data_radar.merge_fields_rainbow`(*basepath*, *scan_name*, *voltime*,
datatype_list)

merge Rainbow fields into a single radar object.

Parameters

basepath [str] name of the base path where to find the data

scan_name: str name of the scan

voltime [datetime object] reference time of the scan

datatype_list [list] lists of data types to get

Returns

radar [Radar] radar object

`pyrad.io.read_data_radar.merge_grids`(*grid1*, *grid2*)

Merges two grids

Parameters

grid1, grid2 [grid object] the grid objects to merge

Returns

grid [grid object] The merged grid

`pyrad.io.read_data_radar.merge_scans_cf1`(*basepath*, *scan_list*, *radar_name*, *radar_res*,
voltime, *datatype_list*, *dataset_list*, *cfg*,
ind_rad=0)

merge CF1 data.

Parameters

basepath [str] base path of CF1 radar data

scan_list [list] list of scans

voltime: datetime object reference time of the scan

datatype_list [list] lists of data types to get

dataset_list [list] list of datasets. Used to get path

cfg [dict] configuration dictionary

ind_rad [int] radar index

Returns

radar [Radar] radar object

`pyrad.io.read_data_radar.merge_scans_cfradial2` (*basepath, scan_list, radar_name, radar_res, voltime, datatype_list, dataset_list, cfg, ind_rad=0*)

merge CFRADIAL2 data.

Parameters

basepath [str] base path of CFRADIAL2 radar data

scan_list [list] list of scans

voltime: datetime object reference time of the scan

datatype_list [list] lists of data types to get

dataset_list [list] list of datasets. Used to get path

cfg [dict] configuration dictionary

ind_rad [int] radar index

Returns

radar [Radar] radar object

`pyrad.io.read_data_radar.merge_scans_cosmo` (*voltime, datatype_list, cfg, ind_rad=0*)
merge rainbow scans

Parameters

voltime: datetime object reference time of the scan

datatype_list [list] lists of data types to get

cfg [dict] configuration dictionary

ind_rad [int] radar index

Returns

radar [Radar] radar object

`pyrad.io.read_data_radar.merge_scans_cosmo_rad4alp` (*voltime, datatype, cfg, ind_rad=0*)
merge cosmo rad4alp scans. If data for all the scans cannot be retrieved returns None

Parameters

voltime: datetime object reference time of the scan

datatype [str] name of the data type to read

cfg [dict] configuration dictionary

ind_rad [int] radar index

Returns

radar [Radar] radar object


```
pyrad.io.read_data_radar.merge_scans_dem(basepath, scan_list, datatype_list,  
                                         rng_min=None, rng_max=None, azi_min=None,  
                                         azi_max=None, ele_min=None, ele_max=None)
```

merge rainbow scans

Parameters

basepath [str] base path of rad4alp radar data
scan_list [list] list of scans
datatype_list [list] lists of data types to get
radarnr [str] radar identifier number
rng_min, rng_max [float] The range limits [m]. If None the entire coverage of the radar is going to be used
ele_min, ele_max, azi_min, azi_max [float or None] The limits of the grid [deg]. If None the limits will be the limits of the radar volume

Returns

radar [Radar] radar object

```
pyrad.io.read_data_radar.merge_scans_dem_rad4alp(voltime, datatype, cfg, ind_rad=0)
```

merge DEM rad4alp scans. If data for all the scans cannot be retrieved returns None

Parameters

voltime: datetime object reference time of the scan
datatype [str] name of the data type to read
cfg [dict] configuration dictionary
ind_rad [int] radar index

Returns

radar [Radar] radar object

```
pyrad.io.read_data_radar.merge_scans_iq_rad4alp(basepath, basepath_iq, scan_list,  
                                                radar_name, radar_res, voltime,  
                                                datatype_list, cfg, ang_tol=0.1,  
                                                ang_step=0.01, ind_rad=0)
```

merge rad4alp IQ scans

Parameters

basepath [str] base path of rad4alp radar data
basepath_iq [str] base path of rad4alp IQ data
scan_list [list] list of scans (001 to 020)
radar_name [str] radar_name (A, D, L, ...)
radar_res [str] radar resolution (H or L)
voltime: datetime object reference time of the scan
datatype_list [list] lists of data types to get
cfg [dict] configuration dictionary
ang_tol [float] Tolerance between nominal elevation and actual elevation
ang_step [float] The elevation angular step used when checking valid ray files

ind_rad [int] radar index

Returns

radar [Radar] radar object

`pyrad.io.read_data_radar.merge_scans_mxpola(basepath, scan_list, voltime, datatype_list, cfg)`

merge rad4alp data.

Parameters

basepath [str] base path of mxpol radar data

scan_list [list] list of scans, in the case of mxpol, the elevation or azimuth denoted as 005 or 090 (for 5 or 90 degrees elevation) or 330 (for 330 degrees azimuth respectively)

voltime: datetime object reference time of the scan

datatype_list [list] lists of data types to get

cfg [dict] configuration dictionary

Returns

radar [Radar] radar object

`pyrad.io.read_data_radar.merge_scans_nexrad2(basepath, scan_list, radar_name, radar_res, voltime, datatype_list, dataset_list, cfg, ind_rad=0)`

merge NEXRAD level 2 data.

Parameters

basepath [str] base path of nexrad radar data

scan_list [list] list of scans

voltime: datetime object reference time of the scan

datatype_list [list] lists of data types to get

dataset_list [list] list of datasets. Used to get path

cfg [dict] configuration dictionary

ind_rad [int] radar index

Returns

radar [Radar] radar object

`pyrad.io.read_data_radar.merge_scans_odim(basepath, scan_list, radar_name, radar_res, voltime, datatype_list, dataset_list, cfg, ind_rad=0)`

merge odim data.

Parameters

basepath [str] base path of odim radar data

scan_list [list] list of scans

voltime: datetime object reference time of the scan

datatype_list [list] lists of data types to get

dataset_list [list] list of datasets. Used to get path

cfg [dict] configuration dictionary

ind_rad [int] radar index

Returns

radar [Radar] radar object

`pyrad.io.read_data_radar.merge_scans_other_rad4alp` (*voltime*, *datatype*, *cfg*,
ind_rad=0)

merge other rad4alp polar products not contained in the basic M or P files, i.e. hydro, dealiased velocity or precip. If data for all the scans cannot be retrieved returns None

Parameters

voltime: datetime object reference time of the scan

datatype [str] name of the data type to read

cfg [dict] configuration dictionary

ind_rad [int] radar index

Returns

radar [Radar] radar object

`pyrad.io.read_data_radar.merge_scans_psr` (*basepath*, *basepath_psr*, *scan_list*,
voltime, *scan_period*, *datatype_list*, *cfg*,
radarnr='RADAR001')

merge rainbow scans

Parameters

basepath [str] base path of rainbow radar data

basepath_psr [str] name of the base path where to find the PSR data

scan_list [list] list of scans

voltime: datetime object reference time of the scan

scan_period [float] time from reference time where to look for other scans data

datatype_list [list] lists of data types to get

cfg [dict] configuration dictionary

radarnr [str] radar identifier number

Returns

radar [Radar] radar object

`pyrad.io.read_data_radar.merge_scans_psr_spectra` (*basepath*, *basepath_psr*, *scan_list*,
voltime, *scan_period*, *datatype_list*,
cfg, *radarnr='RADAR001'*)

merge rainbow scans

Parameters

basepath [str] base path of rad4alp radar data

basepath_psr [str] name of the base path where to find the PSR data

scan_list [list] list of scans

voltime: datetime object reference time of the scan

scan_period [float] time from reference time where to look for other scans data

datatype_list [list] lists of data types to get

cfg [dict] configuration dictionary

radarnr [str] radar identifier number

Returns

radar [Radar] radar object

```
pyrad.io.read_data_radar.merge_scans_rad4alp(basepath, scan_list, radar_name,  
                                              radar_res, voltime, datatype_list, cfg,  
                                              ind_rad=0)
```

merge rad4alp data.

Parameters

basepath [str] base path of rad4alp radar data

scan_list [list] list of scans (001 to 020)

radar_name [str] radar_name (A, D, L, ...)

radar_res [str] radar resolution (H or L)

voltime: datetime object reference time of the scan

datatype_list [list] lists of data types to get

cfg [dict] configuration dictionary

ind_rad [int] radar index

Returns

radar [Radar] radar object

```
pyrad.io.read_data_radar.merge_scans_rainbow(basepath, scan_list, voltime, scan_period,  
                                              datatype_list, cfg, radarnr='RADAR001')
```

merge rainbow scans

Parameters

basepath [str] base path of rad4alp radar data

scan_list [list] list of scans

voltime: datetime object reference time of the scan

scan_period [float] time from reference time where to look for other scans data

datatype_list [list] lists of data types to get

cfg [dict] configuration dictionary

radarnr [str] radar identifier number

Returns

radar [Radar] radar object

PYRAD.IO.READ_DATA_MXPOL

Functions for reading radar mxpol data files .. autosummary:

```
:toctree: generated/
classes - MXPOL:
    pyrad_MXPOL
classes - MCH:
    pyrad_MCH
utilities - read:
    row_stack
    findTimes
    int2float_radar
    readMXPOLRadData
    readCHRadData
utilities - config:
    load_myconfig
    get_mymetadata
    get_elevation_metadata
    generate_radar_table
    generate_polvar_metadata
    convert_polvar_name
```

exception `pyrad.io.read_data_mxpol.MissingOptionalDependency`

Bases: `Exception`

Exception raised when a optional dependency is needed but not found.

__cause__

exception cause

__class__

alias of `builtins.type`

__context__

exception context

__delattr__ (*self*, *name*, /)

Implement `delattr(self, name)`.

__dict__ = `mappingproxy({'__module__': 'pyrad.io.read_data_mxpol', '__doc__': 'Exc`

__dir__ (*self*, /)

Default `dir()` implementation.

__eq__ (*self*, *value*, /)

Return `self==value`.

`__format__` (*self, format_spec, /*)
Default object formatter.

`__ge__` (*self, value, /*)
Return self>=value.

`__getattr__` (*self, name, /*)
Return getattr(self, name).

`__gt__` (*self, value, /*)
Return self>value.

`__hash__` (*self, /*)
Return hash(self).

`__init__` (*self, /, *args, **kwargs*)
Initialize self. See help(type(self)) for accurate signature.

`__init_subclass__` ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

`__le__` (*self, value, /*)
Return self<=value.

`__lt__` (*self, value, /*)
Return self<value.

`__module__` = `'pyrad.io.read_data_mxp01'`

`__ne__` (*self, value, /*)
Return self!=value.

`__new__` (**args, **kwargs*)
Create and return a new object. See help(type) for accurate signature.

`__reduce__` ()
Helper for pickle.

`__reduce_ex__` (*self, protocol, /*)
Helper for pickle.

`__repr__` (*self, /*)
Return repr(self).

`__setattr__` (*self, name, value, /*)
Implement setattr(self, name, value).

`__setstate__` ()

`__sizeof__` (*self, /*)
Size of object in memory, in bytes.

`__str__` (*self, /*)
Return str(self).

`__subclasshook__` ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

`__suppress_context__`

__traceback__

__weakref__

list of weak references to the object (if defined)

args

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

`pyrad.io.read_data_mxpolar.convert_polvar_name(convention, polvar)`

Finds the correct variable name for a given convention (MXPOL, MCH) and a given variable name which was spelled with a different case or according to a different convention. For example, MXPOL convention uses 'Z' for the reflectivity variable, but if a user inserted 'Zh' this function will convert it to 'Z'. Parameters ——— convention : str, destination convention; either MCH or LTE polvar : str, key of polarimetric variable to be converted Returns ——— mykey : str, polarimetric variable key as used within the ProfileLab

toolbox context

`pyrad.io.read_data_mxpolar.findTimes(num_sweep)`

Finds the times at the beginning and at the end of each sweep. Information comes from the elapsed time since the beginning of the volume scan, from the Rad4Alp: Specifications/ Request for Proposal (RFP) document. Inputs ——— num_sweep: int

rank of the sweep

elapsed_times[num_sweep][0]: float the elapsed time since the beginning of the volume scan at the beginning of the sweep

elapsed_times[num_sweep][1]: float the elapsed time since the beginning of the volume scan at the end of the sweep

`pyrad.io.read_data_mxpolar.generate_polvar_metadata(polvar, filename=None)`

Generates a dictionary with metadata for a polarimetric variable Parameters ——— polvar: str

polarimetric variable of interest

filename: str Filename of the configuration file. If None the default configuration file is loaded from the directory.

polvar_metadata: dict dictionary with metadata for polarimetric variable of interest

`pyrad.io.read_data_mxpolar.generate_radar_table(radarname, filename=None)`

Generates a table with basic radar info, based on the given (or default) configfile Parameters ——— radarname: str

name of the radar (i.e. 'ALB' or 'A', 'MXPOL' etc)

filename: str path and name of the configfile, if None, the default configfile is used

radar_table: dict table containing basic radar info

`pyrad.io.read_data_mxpolar.get_elevation_metadata(radarname, filename=None)`

Gets the elevation angles for each sweep from the configuration file Inputs ——— radarname: str

name of the radar for which to retrieve elevation angles

filename: str name of the configuration file, if None, the default configuration file is used

_DEFAULT_RADAR_INFO['elevations'][radarname]: list list of elevation angles in degrees

or None if not available

`pyrad.io.read_data_mxpul.get_mymetadata(p, filename=None)`

Return a dictionary of metadata for a given parameter, p. An empty dictionary will be returned if no metadata dictionary exists for parameter p. Parameters ——— p: str

parameter name (i.e. Polvar) for which to return metadata

filename: str Filename of the configuration file. If None the default configuration file is loaded from the directory.

_DEFAULT_METADATA[p].copy(): dict a copy of the parameter of interest from the metadata dictionary

`pyrad.io.read_data_mxpul.int2float_radar(data, varname, index_angle)`

Converts radar moments from bit to float Inputs ——— data: np.array

moment data as loaded from h5 file

varname: str name of the moment (i.e. 'ZH')

index_angle: int rank of the sweep-1 (converted to base 0)

output: np.array moment data converted to float

`pyrad.io.read_data_mxpul.load_myconfig(filename=None)`

Load configuration from a config file. Parameters ——— filename: str

Filename of the configuration file. If None the default configuration file is loaded from the directory.

_DEFAULT_METADATA: dict Dictionary with metadata

class `pyrad.io.read_data_mxpul.pyrad_IDL(filename, field_names=None, max_range=inf, min_range=10000)`

Bases: `pyart.core.radar.Radar`

Methods

<code>add_field(self, field_name, dic[, ...])</code>	Add a field to the object.
<code>add_field_like(self, existing_field_name, ...)</code>	Add a field to the object with metadata from a existing field.
<code>check_field_exists(self, field_name)</code>	Check that a field exists in the fields dictionary.
<code>extract_sweeps(self, sweeps)</code>	Create a new radar contains only the data from select sweeps.
<code>get_azimuth(self, sweep[, copy])</code>	Return an array of azimuth angles for a given sweep.
<code>get_elevation(self, sweep[, copy])</code>	Return an array of elevation angles for a given sweep.
<code>get_end(self, sweep)</code>	Return the ending ray for a given sweep.
<code>get_field(self, sweep, field_name[, copy])</code>	Return the field data for a given sweep.
<code>get_gate_lat_lon_alt(self, sweep[, ...])</code>	Return the longitude, latitude and altitude gate locations.
<code>get_gate_x_y_z(self, sweep[, edges, ...])</code>	Return the x, y and z gate locations in meters for a given sweep.

Continued on next page

Table 1 – continued from previous page

<i>get_nyquist_vel</i> (self, sweep[, check_uniform])	Return the Nyquist velocity in meters per second for a given sweep.
<i>get_slice</i> (self, sweep)	Return a slice for selecting rays for a given sweep.
<i>get_start</i> (self, sweep)	Return the starting ray index for a given sweep.
<i>get_start_end</i> (self, sweep)	Return the starting and ending ray for a given sweep.
<i>info</i> (self[, level, out])	Print information on radar.
<i>init_gate_altitude</i> (self)	Initialize the <i>gate_altitude</i> attribute.
<i>init_gate_longitude_latitude</i> (self)	Initialize or reset the <i>gate_longitude</i> and <i>gate_latitude</i> attributes.
<i>init_gate_x_y_z</i> (self)	Initialize or reset the <i>gate_{x, y, z}</i> attributes.
<i>init_rays_per_sweep</i> (self)	Initialize or reset the <i>rays_per_sweep</i> attribute.
<i>iter_azimuth</i> (self)	Return an iterator which returns sweep azimuth data.
<i>iter_elevation</i> (self)	Return an iterator which returns sweep elevation data.
<i>iter_end</i> (self)	Return an iterator over the sweep end indices.
<i>iter_field</i> (self, field_name)	Return an iterator which returns sweep field data.
<i>iter_slice</i> (self)	Return an iterator which returns sweep slice objects.
<i>iter_start</i> (self)	Return an iterator over the sweep start indices.
<i>iter_start_end</i> (self)	Return an iterator over the sweep start and end indices.

__class__alias of `builtins.type`**__delattr__**(self, name, /)Implement `delattr(self, name)`.**__dict__** = `mappingproxy({'__module__': 'pyrad.io.read_data_mxpole', '__init__': <func`**__dir__**(self, /)Default `dir()` implementation.**__eq__**(self, value, /)Return `self==value`.**__format__**(self, format_spec, /)

Default object formatter.

__ge__(self, value, /)Return `self>=value`.**__getattr__**(self, name, /)Return `getattr(self, name)`.**__getstate__**(self)

Return object's state which can be pickled.

__gt__(self, value, /)Return `self>value`.**__hash__**(self, /)Return `hash(self)`.**__init__**(self, filename, field_names=None, max_range=inf, min_range=10000)Initialize self. See `help(type(self))` for accurate signature.**__init_subclass__**()

This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

```
__le__ (self, value, /)
    Return self<=value.

__lt__ (self, value, /)
    Return self<value.

__module__ = 'pyrad.io.read_data_mxp01'

__ne__ (self, value, /)
    Return self!=value.

__new__ (*args, **kwargs)
    Create and return a new object. See help(type) for accurate signature.

__reduce__ (self, /)
    Helper for pickle.

__reduce_ex__ (self, protocol, /)
    Helper for pickle.

__repr__ (self, /)
    Return repr(self).

__setattr__ (self, name, value, /)
    Implement setattr(self, name, value).

__setstate__ (self, state)
    Restore unpicklable entries from pickled object.

__sizeof__ (self, /)
    Size of object in memory, in bytes.

__str__ (self, /)
    Return str(self).

__subclasshook__ ()
    Abstract classes can override this to customize issubclass().

    This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
    list of weak references to the object (if defined)

__check_sweep_in_range (self, sweep)
    Check that a sweep number is in range.

__dic_info (self, attr, level, out, dic=None, ident_level=0)
    Print information on a dictionary attribute.

add_field (self, field_name, dic, replace_existing=False)
    Add a field to the object.
```

Parameters

field_name [str] Name of the field to add to the dictionary of fields.

dic [dict] Dictionary contain field data and metadata.

replace_existing [bool, optional] True to replace the existing field with key field_name if it exists, losing any existing data. False will raise a ValueError when the field already exists.

add_field_like (*self, existing_field_name, field_name, data, replace_existing=False*)

Add a field to the object with metadata from an existing field.

Note that the data parameter is not copied by this method. If data refers to a 'data' array from an existing field dictionary, a copy should be made within or prior to using this method. If this is not done the 'data' key in both field dictionaries will point to the same NumPy array and modification of one will change the second. To copy NumPy arrays use the copy() method. See the Examples section for how to create a copy of the 'reflectivity' field as a field named 'reflectivity_copy'.

Parameters

existing_field_name [str] Name of an existing field to take metadata from when adding the new field to the object.

field_name [str] Name of the field to add to the dictionary of fields.

data [array] Field data. A copy of this data is not made, see the note above.

replace_existing [bool, optional] True to replace the existing field with key field_name if it exists, losing any existing data. False will raise a ValueError when the field already exists.

Examples

```
>>> radar.add_field_like('reflectivity', 'reflectivity_copy',  
...                      radar.fields['reflectivity']['data'].copy())
```

check_field_exists (*self, field_name*)

Check that a field exists in the fields dictionary.

If the field does not exist raise a KeyError.

Parameters

field_name [str] Name of field to check.

extract_sweeps (*self, sweeps*)

Create a new radar contains only the data from select sweeps.

Parameters

sweeps [array_like] Sweeps (0-based) to include in new Radar object.

Returns

radar [Radar] Radar object which contains a copy of data from the selected sweeps.

get_azimuth (*self, sweep, copy=False*)

Return an array of azimuth angles for a given sweep.

Parameters

sweep [int] Sweep number to retrieve data for, 0 based.

copy [bool, optional] True to return a copy of the azimuths. False, the default, returns a view of the azimuths (when possible), changing this data will change the data in the underlying Radar object.

Returns

azimuths [array] Array containing the azimuth angles for a given sweep.

get_elevation (*self, sweep, copy=False*)

Return an array of elevation angles for a given sweep.

Parameters

sweep [int] Sweep number to retrieve data for, 0 based.

copy [bool, optional] True to return a copy of the elevations. False, the default, returns a view of the elevations (when possible), changing this data will change the data in the underlying Radar object.

Returns

azimuths [array] Array containing the elevation angles for a given sweep.

get_end (*self*, *sweep*)

Return the ending ray for a given sweep.

get_field (*self*, *sweep*, *field_name*, *copy=False*)

Return the field data for a given sweep.

When used with *get_gate_x_y_z* () this method can be used to obtain the data needed for plotting a radar field with the correct spatial context.

Parameters

sweep [int] Sweep number to retrieve data for, 0 based.

field_name [str] Name of the field from which data should be retrieved.

copy [bool, optional] True to return a copy of the data. False, the default, returns a view of the data (when possible), changing this data will change the data in the underlying Radar object.

Returns

data [array] Array containing data for the requested sweep and field.

get_gate_lat_lon_alt (*self*, *sweep*, *reset_gate_coords=False*, *filter_transitions=False*)

Return the longitude, latitude and altitude gate locations. Longitude and latitude are in degrees and altitude in meters.

With the default parameter this method returns the same data as contained in the *gate_latitude*, *gate_longitude* and *gate_altitude* attributes but this method performs the gate location calculations only for the specified sweep and therefore is more efficient than accessing this data through these attribute. If coordinates have at all, please use the *reset_gate_coords* parameter.

Parameters

sweep [int] Sweep number to retrieve gate locations from, 0 based.

reset_gate_coords [bool, optional] Optional to reset the gate latitude, gate longitude and gate altitude attributes before using them in this function. This is useful when the geographic coordinates have changed and gate latitude, gate longitude and gate altitude need to be reset.

filter_transitions [bool, optional] True to remove rays where the antenna was in transition between sweeps. False will include these rays. No rays will be removed if the *antenna_transition* attribute is not available (set to None).

Returns

lat, lon, alt [2D array] Array containing the latitude, longitude and altitude, for all gates in the sweep.

get_gate_x_y_z (*self*, *sweep*, *edges=False*, *filter_transitions=False*)

Return the x, y and z gate locations in meters for a given sweep.

With the default parameter this method returns the same data as contained in the `gate_x`, `gate_y` and `gate_z` attributes but this method performs the gate location calculations only for the specified sweep and therefore is more efficient than accessing this data through these attribute.

When used with `get_field()` this method can be used to obtain the data needed for plotting a radar field with the correct spatial context.

Parameters

sweep [int] Sweep number to retrieve gate locations from, 0 based.

edges [bool, optional] True to return the locations of the gate edges calculated by interpolating between the range, azimuths and elevations. False (the default) will return the locations of the gate centers with no interpolation.

filter_transitions [bool, optional] True to remove rays where the antenna was in transition between sweeps. False will include these rays. No rays will be removed if the `antenna_transition` attribute is not available (set to None).

Returns

x, y, z [2D array] Array containing the x, y and z, distances from the radar in meters for the center (or edges) for all gates in the sweep.

get_nyquist_vel (*self*, *sweep*, *check_uniform=True*)

Return the Nyquist velocity in meters per second for a given sweep.

Raises a `LookupError` if the Nyquist velocity is not available, an `Exception` is raised if the velocities are not uniform in the sweep unless `check_uniform` is set to False.

Parameters

sweep [int] Sweep number to retrieve data for, 0 based.

check_uniform [bool] True to check to perform a check on the Nyquist velocities that they are uniform in the sweep, False will skip this check and return the velocity of the first ray in the sweep.

Returns

nyquist_velocity [float] Array containing the Nyquist velocity in m/s for a given sweep.

get_slice (*self*, *sweep*)

Return a slice for selecting rays for a given sweep.

get_start (*self*, *sweep*)

Return the starting ray index for a given sweep.

get_start_end (*self*, *sweep*)

Return the starting and ending ray for a given sweep.

info (*self*, *level='standard'*, *out=<_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>*)

Print information on radar.

Parameters

level [{ 'compact', 'standard', 'full', 'c', 's', 'f' }, optional] Level of information on radar object to print, compact is minimal information, standard more and full everything.

out [file-like, optional] Stream to direct output to, default is to print information to standard out (the screen).

init_gate_altitude (*self*)

Initialize the `gate_altitude` attribute.

init_gate_longitude_latitude (*self*)
Initialize or reset the gate_longitude and gate_latitude attributes.

init_gate_x_y_z (*self*)
Initialize or reset the gate_{x, y, z} attributes.

init_rays_per_sweep (*self*)
Initialize or reset the rays_per_sweep attribute.

iter_azimuth (*self*)
Return an iterator which returns sweep azimuth data.

iter_elevation (*self*)
Return an iterator which returns sweep elevation data.

iter_end (*self*)
Return an iterator over the sweep end indices.

iter_field (*self*, *field_name*)
Return an iterator which returns sweep field data.

iter_slice (*self*)
Return an iterator which returns sweep slice objects.

iter_start (*self*)
Return an iterator over the sweep start indices.

iter_start_end (*self*)
Return an iterator over the sweep start and end indices.

class pyrad.io.read_data_mxpole.pyrad_MCH (*filename*, *field_names=None*, *max_range=inf*)
Bases: pyart.core.radar.Radar

Methods

<i>add_field</i> (<i>self</i> , <i>field_name</i> , <i>dic</i> [, ...])	Add a field to the object.
<i>add_field_like</i> (<i>self</i> , <i>existing_field_name</i> , ...)	Add a field to the object with metadata from a existing field.
<i>check_field_exists</i> (<i>self</i> , <i>field_name</i>)	Check that a field exists in the fields dictionary.
<i>extract_sweeps</i> (<i>self</i> , <i>sweeps</i>)	Create a new radar contains only the data from select sweeps.
<i>get_azimuth</i> (<i>self</i> , <i>sweep</i> [, <i>copy</i>])	Return an array of azimuth angles for a given sweep.
<i>get_elevation</i> (<i>self</i> , <i>sweep</i> [, <i>copy</i>])	Return an array of elevation angles for a given sweep.
<i>get_end</i> (<i>self</i> , <i>sweep</i>)	Return the ending ray for a given sweep.
<i>get_field</i> (<i>self</i> , <i>sweep</i> , <i>field_name</i> [, <i>copy</i>])	Return the field data for a given sweep.
<i>get_gate_lat_lon_alt</i> (<i>self</i> , <i>sweep</i> [, ...])	Return the longitude, latitude and altitude gate locations.
<i>get_gate_x_y_z</i> (<i>self</i> , <i>sweep</i> [, <i>edges</i> , ...])	Return the x, y and z gate locations in meters for a given sweep.
<i>get_nyquist_vel</i> (<i>self</i> , <i>sweep</i> [, <i>check_uniform</i>])	Return the Nyquist velocity in meters per second for a given sweep.
<i>get_slice</i> (<i>self</i> , <i>sweep</i>)	Return a slice for selecting rays for a given sweep.
<i>get_start</i> (<i>self</i> , <i>sweep</i>)	Return the starting ray index for a given sweep.
<i>get_start_end</i> (<i>self</i> , <i>sweep</i>)	Return the starting and ending ray for a given sweep.
<i>info</i> (<i>self</i> [, <i>level</i> , <i>out</i>])	Print information on radar.
<i>init_gate_altitude</i> (<i>self</i>)	Initialize the gate_altitude attribute.

Continued on next page

Table 2 – continued from previous page

<i>init_gate_longitude_latitude</i> (self)	Initialize or reset the <i>gate_longitude</i> and <i>gate_latitude</i> attributes.
<i>init_gate_x_y_z</i> (self)	Initialize or reset the <i>gate_{x, y, z}</i> attributes.
<i>init_rays_per_sweep</i> (self)	Initialize or reset the <i>rays_per_sweep</i> attribute.
<i>iter_azimuth</i> (self)	Return an iterator which returns sweep azimuth data.
<i>iter_elevation</i> (self)	Return an iterator which returns sweep elevation data.
<i>iter_end</i> (self)	Return an iterator over the sweep end indices.
<i>iter_field</i> (self, <i>field_name</i>)	Return an iterator which returns sweep field data.
<i>iter_slice</i> (self)	Return an iterator which returns sweep slice objects.
<i>iter_start</i> (self)	Return an iterator over the sweep start indices.
<i>iter_start_end</i> (self)	Return an iterator over the sweep start and end indices.

__class__

alias of `builtins.type`

__delattr__ (*self*, *name*, /)

Implement `delattr(self, name)`.

__dict__ = `mappingproxy({'__module__': 'pyrad.io.read_data_mxpole', '__init__': <func`

__dir__ (*self*, /)

Default `dir()` implementation.

__eq__ (*self*, *value*, /)

Return `self==value`.

__format__ (*self*, *format_spec*, /)

Default object formatter.

__ge__ (*self*, *value*, /)

Return `self>=value`.

__getattr__ (*self*, *name*, /)

Return `getattr(self, name)`.

__getstate__ (*self*)

Return object's state which can be pickled.

__gt__ (*self*, *value*, /)

Return `self>value`.

__hash__ (*self*, /)

Return `hash(self)`.

__init__ (*self*, *filename*, *field_names=None*, *max_range=inf*)

Initialize self. See `help(type(self))` for accurate signature.

__init_subclass__ ()

This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self*, *value*, /)

Return `self<=value`.

__lt__ (*self*, *value*, /)

Return `self<value`.

__module__ = 'pyrad.io.read_data_mxp1'

__ne__ (*self*, *value*, /)
Return self!=value.

__new__ (*args, **kwargs)
Create and return a new object. See help(type) for accurate signature.

__reduce__ (*self*, /)
Helper for pickle.

__reduce_ex__ (*self*, *protocol*, /)
Helper for pickle.

__repr__ (*self*, /)
Return repr(self).

__setattr__ (*self*, *name*, *value*, /)
Implement setattr(self, name, value).

__setstate__ (*self*, *state*)
Restore unpicklable entries from pickled object.

__sizeof__ (*self*, /)
Size of object in memory, in bytes.

__str__ (*self*, /)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

__check_sweep_in_range (*self*, *sweep*)
Check that a sweep number is in range.

__dic_info (*self*, *attr*, *level*, *out*, *dic=None*, *ident_level=0*)
Print information on a dictionary attribute.

add_field (*self*, *field_name*, *dic*, *replace_existing=False*)
Add a field to the object.

Parameters

field_name [str] Name of the field to add to the dictionary of fields.

dic [dict] Dictionary contain field data and metadata.

replace_existing [bool, optional] True to replace the existing field with key field_name if it exists, loosing any existing data. False will raise a ValueError when the field already exists.

add_field_like (*self*, *existing_field_name*, *field_name*, *data*, *replace_existing=False*)
Add a field to the object with metadata from a existing field.

Note that the data parameter is not copied by this method. If data refers to a 'data' array from an existing field dictionary, a copy should be made within or prior to using this method. If this is not done the 'data' key in both field dictionaries will point to the same NumPy array and modification of one will change the

second. To copy NumPy arrays use the `copy()` method. See the Examples section for how to create a copy of the 'reflectivity' field as a field named 'reflectivity_copy'.

Parameters

existing_field_name [str] Name of an existing field to take metadata from when adding the new field to the object.

field_name [str] Name of the field to add to the dictionary of fields.

data [array] Field data. A copy of this data is not made, see the note above.

replace_existing [bool, optional] True to replace the existing field with key `field_name` if it exists, losing any existing data. False will raise a `ValueError` when the field already exists.

Examples

```
>>> radar.add_field_like('reflectivity', 'reflectivity_copy',  
...                      radar.fields['reflectivity']['data'].copy())
```

check_field_exists (*self*, *field_name*)

Check that a field exists in the fields dictionary.

If the field does not exist raise a `KeyError`.

Parameters

field_name [str] Name of field to check.

extract_sweeps (*self*, *sweeps*)

Create a new radar contains only the data from select sweeps.

Parameters

sweeps [array_like] Sweeps (0-based) to include in new Radar object.

Returns

radar [Radar] Radar object which contains a copy of data from the selected sweeps.

get_azimuth (*self*, *sweep*, *copy=False*)

Return an array of azimuth angles for a given sweep.

Parameters

sweep [int] Sweep number to retrieve data for, 0 based.

copy [bool, optional] True to return a copy of the azimuths. False, the default, returns a view of the azimuths (when possible), changing this data will change the data in the underlying Radar object.

Returns

azimuths [array] Array containing the azimuth angles for a given sweep.

get_elevation (*self*, *sweep*, *copy=False*)

Return an array of elevation angles for a given sweep.

Parameters

sweep [int] Sweep number to retrieve data for, 0 based.

copy [bool, optional] True to return a copy of the elevations. False, the default, returns a view of the elevations (when possible), changing this data will change the data in the underlying Radar object.

Returns

azimuths [array] Array containing the elevation angles for a given sweep.

get_end (*self*, *sweep*)

Return the ending ray for a given sweep.

get_field (*self*, *sweep*, *field_name*, *copy=False*)

Return the field data for a given sweep.

When used with *get_gate_x_y_z* () this method can be used to obtain the data needed for plotting a radar field with the correct spatial context.

Parameters

sweep [int] Sweep number to retrieve data for, 0 based.

field_name [str] Name of the field from which data should be retrieved.

copy [bool, optional] True to return a copy of the data. False, the default, returns a view of the data (when possible), changing this data will change the data in the underlying Radar object.

Returns

data [array] Array containing data for the requested sweep and field.

get_gate_lat_lon_alt (*self*, *sweep*, *reset_gate_coords=False*, *filter_transitions=False*)

Return the longitude, latitude and altitude gate locations. Longitude and latitude are in degrees and altitude in meters.

With the default parameter this method returns the same data as contained in the *gate_latitude*, *gate_longitude* and *gate_altitude* attributes but this method performs the gate location calculations only for the specified sweep and therefore is more efficient than accessing this data through these attribute. If coordinates have at all, please use the *reset_gate_coords* parameter.

Parameters

sweep [int] Sweep number to retrieve gate locations from, 0 based.

reset_gate_coords [bool, optional] Optional to reset the gate latitude, gate longitude and gate altitude attributes before using them in this function. This is useful when the geographic coordinates have changed and gate latitude, gate longitude and gate altitude need to be reset.

filter_transitions [bool, optional] True to remove rays where the antenna was in transition between sweeps. False will include these rays. No rays will be removed if the *antenna_transition* attribute is not available (set to None).

Returns

lat, lon, alt [2D array] Array containing the latitude, longitude and altitude, for all gates in the sweep.

get_gate_x_y_z (*self*, *sweep*, *edges=False*, *filter_transitions=False*)

Return the x, y and z gate locations in meters for a given sweep.

With the default parameter this method returns the same data as contained in the *gate_x*, *gate_y* and *gate_z* attributes but this method performs the gate location calculations only for the specified sweep and therefore is more efficient than accessing this data through these attribute.

When used with `get_field()` this method can be used to obtain the data needed for plotting a radar field with the correct spatial context.

Parameters

sweep [int] Sweep number to retrieve gate locations from, 0 based.

edges [bool, optional] True to return the locations of the gate edges calculated by interpolating between the range, azimuths and elevations. False (the default) will return the locations of the gate centers with no interpolation.

filter_transitions [bool, optional] True to remove rays where the antenna was in transition between sweeps. False will include these rays. No rays will be removed if the `antenna_transition` attribute is not available (set to None).

Returns

x, y, z [2D array] Array containing the x, y and z, distances from the radar in meters for the center (or edges) for all gates in the sweep.

get_nyquist_vel (*self*, *sweep*, *check_uniform=True*)

Return the Nyquist velocity in meters per second for a given sweep.

Raises a `LookupError` if the Nyquist velocity is not available, an `Exception` is raised if the velocities are not uniform in the sweep unless `check_uniform` is set to False.

Parameters

sweep [int] Sweep number to retrieve data for, 0 based.

check_uniform [bool] True to check to perform a check on the Nyquist velocities that they are uniform in the sweep, False will skip this check and return the velocity of the first ray in the sweep.

Returns

nyquist_velocity [float] Array containing the Nyquist velocity in m/s for a given sweep.

get_slice (*self*, *sweep*)

Return a slice for selecting rays for a given sweep.

get_start (*self*, *sweep*)

Return the starting ray index for a given sweep.

get_start_end (*self*, *sweep*)

Return the starting and ending ray for a given sweep.

info (*self*, *level='standard'*, *out=<_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>*)

Print information on radar.

Parameters

level [{ 'compact', 'standard', 'full', 'c', 's', 'f' }, optional] Level of information on radar object to print, compact is minimal information, standard more and full everything.

out [file-like, optional] Stream to direct output to, default is to print information to standard out (the screen).

init_gate_altitude (*self*)

Initialize the `gate_altitude` attribute.

init_gate_longitude_latitude (*self*)

Initialize or reset the `gate_longitude` and `gate_latitude` attributes.

init_gate_x_y_z (*self*)
Initialize or reset the gate_{x, y, z} attributes.

init_rays_per_sweep (*self*)
Initialize or reset the rays_per_sweep attribute.

iter_azimuth (*self*)
Return an iterator which returns sweep azimuth data.

iter_elevation (*self*)
Return an iterator which returns sweep elevation data.

iter_end (*self*)
Return an iterator over the sweep end indices.

iter_field (*self*, *field_name*)
Return an iterator which returns sweep field data.

iter_slice (*self*)
Return an iterator which returns sweep slice objects.

iter_start (*self*)
Return an iterator over the sweep start indices.

iter_start_end (*self*)
Return an iterator over the sweep start and end indices.

```
class pyrad.io.read_data_mxppol.pyrad_MXPOL (filename, field_names=None, max_range=inf,  
                                              min_range=10000, pyrad_names=True)  
    Bases: pyart.core.radar.Radar
```

Methods

<i>add_field</i> (self, field_name, dic[, ...])	Add a field to the object.
<i>add_field_like</i> (self, existing_field_name, ...)	Add a field to the object with metadata from a existing field.
<i>check_field_exists</i> (self, field_name)	Check that a field exists in the fields dictionary.
<i>extract_sweeps</i> (self, sweeps)	Create a new radar contains only the data from select sweeps.
<i>get_azimuth</i> (self, sweep[, copy])	Return an array of azimuth angles for a given sweep.
<i>get_elevation</i> (self, sweep[, copy])	Return an array of elevation angles for a given sweep.
<i>get_end</i> (self, sweep)	Return the ending ray for a given sweep.
<i>get_field</i> (self, sweep, field_name[, copy])	Return the field data for a given sweep.
<i>get_gate_lat_lon_alt</i> (self, sweep[, ...])	Return the longitude, latitude and altitude gate locations.
<i>get_gate_x_y_z</i> (self, sweep[, edges, ...])	Return the x, y and z gate locations in meters for a given sweep.
<i>get_nyquist_vel</i> (self, sweep[, check_uniform])	Return the Nyquist velocity in meters per second for a given sweep.
<i>get_slice</i> (self, sweep)	Return a slice for selecting rays for a given sweep.
<i>get_start</i> (self, sweep)	Return the starting ray index for a given sweep.
<i>get_start_end</i> (self, sweep)	Return the starting and ending ray for a given sweep.
<i>info</i> (self[, level, out])	Print information on radar.
<i>init_gate_altitude</i> (self)	Initialize the gate_altitude attribute.
<i>init_gate_longitude_latitude</i> (self)	Initialize or reset the gate_longitude and gate_latitude attributes.

Continued on next page

Table 3 – continued from previous page

<code>init_gate_x_y_z(self)</code>	Initialize or reset the <code>gate_{x, y, z}</code> attributes.
<code>init_rays_per_sweep(self)</code>	Initialize or reset the <code>rays_per_sweep</code> attribute.
<code>iter_azimuth(self)</code>	Return an iterator which returns sweep azimuth data.
<code>iter_elevation(self)</code>	Return an iterator which returns sweep elevation data.
<code>iter_end(self)</code>	Return an iterator over the sweep end indices.
<code>iter_field(self, field_name)</code>	Return an iterator which returns sweep field data.
<code>iter_slice(self)</code>	Return an iterator which returns sweep slice objects.
<code>iter_start(self)</code>	Return an iterator over the sweep start indices.
<code>iter_start_end(self)</code>	Return an iterator over the sweep start and end indices.

```

__class__
    alias of builtins.type

__delattr__(self, name, /)
    Implement delattr(self, name).

__dict__ = mappingproxy({'__module__': 'pyrad.io.read_data_mxp01', '__init__': <func
__dir__(self, /)
    Default dir() implementation.

__eq__(self, value, /)
    Return self==value.

__format__(self, format_spec, /)
    Default object formatter.

__ge__(self, value, /)
    Return self>=value.

__getattr__(self, name, /)
    Return getattr(self, name).

__getstate__(self)
    Return object's state which can be pickled.

__gt__(self, value, /)
    Return self>value.

__hash__(self, /)
    Return hash(self).

__init__(self, filename, field_names=None, max_range=inf, min_range=10000,
        pyrad_names=True)
    Initialize self. See help(type(self)) for accurate signature.

__init_subclass__()
    This method is called when a class is subclassed.

    The default implementation does nothing. It may be overridden to extend subclasses.

__le__(self, value, /)
    Return self<=value.

__lt__(self, value, /)
    Return self<value.

__module__ = 'pyrad.io.read_data_mxp01'

```

__ne__ (*self*, *value*, /)
Return self!=value.

__new__ (*args, **kwargs)
Create and return a new object. See help(type) for accurate signature.

__reduce__ (*self*, /)
Helper for pickle.

__reduce_ex__ (*self*, *protocol*, /)
Helper for pickle.

__repr__ (*self*, /)
Return repr(self).

__setattr__ (*self*, *name*, *value*, /)
Implement setattr(self, name, value).

__setstate__ (*self*, *state*)
Restore unpicklable entries from pickled object.

__sizeof__ (*self*, /)
Size of object in memory, in bytes.

__str__ (*self*, /)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

__check_sweep_in_range (*self*, *sweep*)
Check that a sweep number is in range.

__dic_info (*self*, *attr*, *level*, *out*, *dic=None*, *ident_level=0*)
Print information on a dictionary attribute.

add_field (*self*, *field_name*, *dic*, *replace_existing=False*)
Add a field to the object.

Parameters

field_name [str] Name of the field to add to the dictionary of fields.

dic [dict] Dictionary contain field data and metadata.

replace_existing [bool, optional] True to replace the existing field with key field_name if it exists, losing any existing data. False will raise a ValueError when the field already exists.

add_field_like (*self*, *existing_field_name*, *field_name*, *data*, *replace_existing=False*)
Add a field to the object with metadata from an existing field.

Note that the data parameter is not copied by this method. If data refers to a 'data' array from an existing field dictionary, a copy should be made within or prior to using this method. If this is not done the 'data' key in both field dictionaries will point to the same NumPy array and modification of one will change the second. To copy NumPy arrays use the copy() method. See the Examples section for how to create a copy of the 'reflectivity' field as a field named 'reflectivity_copy'.

Parameters

existing_field_name [str] Name of an existing field to take metadata from when adding the new field to the object.

field_name [str] Name of the field to add to the dictionary of fields.

data [array] Field data. A copy of this data is not made, see the note above.

replace_existing [bool, optional] True to replace the existing field with key field_name if it exists, losing any existing data. False will raise a ValueError when the field already exists.

Examples

```
>>> radar.add_field_like('reflectivity', 'reflectivity_copy',  
...                      radar.fields['reflectivity']['data'].copy())
```

check_field_exists (*self*, *field_name*)

Check that a field exists in the fields dictionary.

If the field does not exist raise a KeyError.

Parameters

field_name [str] Name of field to check.

extract_sweeps (*self*, *sweeps*)

Create a new radar contains only the data from select sweeps.

Parameters

sweeps [array_like] Sweeps (0-based) to include in new Radar object.

Returns

radar [Radar] Radar object which contains a copy of data from the selected sweeps.

get_azimuth (*self*, *sweep*, *copy=False*)

Return an array of azimuth angles for a given sweep.

Parameters

sweep [int] Sweep number to retrieve data for, 0 based.

copy [bool, optional] True to return a copy of the azimuths. False, the default, returns a view of the azimuths (when possible), changing this data will change the data in the underlying Radar object.

Returns

azimuths [array] Array containing the azimuth angles for a given sweep.

get_elevation (*self*, *sweep*, *copy=False*)

Return an array of elevation angles for a given sweep.

Parameters

sweep [int] Sweep number to retrieve data for, 0 based.

copy [bool, optional] True to return a copy of the elevations. False, the default, returns a view of the elevations (when possible), changing this data will change the data in the underlying Radar object.

Returns

azimuths [array] Array containing the elevation angles for a given sweep.

get_end (*self*, *sweep*)

Return the ending ray for a given sweep.

get_field (*self*, *sweep*, *field_name*, *copy=False*)

Return the field data for a given sweep.

When used with *get_gate_x_y_z* () this method can be used to obtain the data needed for plotting a radar field with the correct spatial context.

Parameters

sweep [int] Sweep number to retrieve data for, 0 based.

field_name [str] Name of the field from which data should be retrieved.

copy [bool, optional] True to return a copy of the data. False, the default, returns a view of the data (when possible), changing this data will change the data in the underlying Radar object.

Returns

data [array] Array containing data for the requested sweep and field.

get_gate_lat_lon_alt (*self*, *sweep*, *reset_gate_coords=False*, *filter_transitions=False*)

Return the longitude, latitude and altitude gate locations. Longitude and latitude are in degrees and altitude in meters.

With the default parameter this method returns the same data as contained in the *gate_latitude*, *gate_longitude* and *gate_altitude* attributes but this method performs the gate location calculations only for the specified sweep and therefore is more efficient than accessing this data through these attribute. If coordinates have at all, please use the *reset_gate_coords* parameter.

Parameters

sweep [int] Sweep number to retrieve gate locations from, 0 based.

reset_gate_coords [bool, optional] Optional to reset the gate latitude, gate longitude and gate altitude attributes before using them in this function. This is useful when the geographic coordinates have changed and gate latitude, gate longitude and gate altitude need to be reset.

filter_transitions [bool, optional] True to remove rays where the antenna was in transition between sweeps. False will include these rays. No rays will be removed if the *antenna_transition* attribute is not available (set to None).

Returns

lat, lon, alt [2D array] Array containing the latitude, longitude and altitude, for all gates in the sweep.

get_gate_x_y_z (*self*, *sweep*, *edges=False*, *filter_transitions=False*)

Return the x, y and z gate locations in meters for a given sweep.

With the default parameter this method returns the same data as contained in the *gate_x*, *gate_y* and *gate_z* attributes but this method performs the gate location calculations only for the specified sweep and therefore is more efficient than accessing this data through these attribute.

When used with *get_field*() this method can be used to obtain the data needed for plotting a radar field with the correct spatial context.

Parameters

sweep [int] Sweep number to retrieve gate locations from, 0 based.

edges [bool, optional] True to return the locations of the gate edges calculated by interpolating between the range, azimuths and elevations. False (the default) will return the locations of the gate centers with no interpolation.

filter_transitions [bool, optional] True to remove rays where the antenna was in transition between sweeps. False will include these rays. No rays will be removed if the `antenna_transition` attribute is not available (set to None).

Returns

x, y, z [2D array] Array containing the x, y and z, distances from the radar in meters for the center (or edges) for all gates in the sweep.

get_nyquist_vel (*self*, *sweep*, *check_uniform=True*)

Return the Nyquist velocity in meters per second for a given sweep.

Raises a `LookupError` if the Nyquist velocity is not available, an `Exception` is raised if the velocities are not uniform in the sweep unless `check_uniform` is set to False.

Parameters

sweep [int] Sweep number to retrieve data for, 0 based.

check_uniform [bool] True to check to perform a check on the Nyquist velocities that they are uniform in the sweep, False will skip this check and return the velocity of the first ray in the sweep.

Returns

nyquist_velocity [float] Array containing the Nyquist velocity in m/s for a given sweep.

get_slice (*self*, *sweep*)

Return a slice for selecting rays for a given sweep.

get_start (*self*, *sweep*)

Return the starting ray index for a given sweep.

get_start_end (*self*, *sweep*)

Return the starting and ending ray for a given sweep.

info (*self*, *level='standard'*, *out=<_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>*)

Print information on radar.

Parameters

level [{ 'compact', 'standard', 'full', 'c', 's', 'f' }, optional] Level of information on radar object to print, compact is minimal information, standard more and full everything.

out [file-like, optional] Stream to direct output to, default is to print information to standard out (the screen).

init_gate_altitude (*self*)

Initialize the `gate_altitude` attribute.

init_gate_longitude_latitude (*self*)

Initialize or reset the `gate_longitude` and `gate_latitude` attributes.

init_gate_x_y_z (*self*)

Initialize or reset the `gate_{x, y, z}` attributes.

init_rays_per_sweep (*self*)

Initialize or reset the `rays_per_sweep` attribute.

iter_azimuth (*self*)
Return an iterator which returns sweep azimuth data.

iter_elevation (*self*)
Return an iterator which returns sweep elevation data.

iter_end (*self*)
Return an iterator over the sweep end indices.

iter_field (*self*, *field_name*)
Return an iterator which returns sweep field data.

iter_slice (*self*)
Return an iterator which returns sweep slice objects.

iter_start (*self*)
Return an iterator over the sweep start indices.

iter_start_end (*self*)
Return an iterator over the sweep start and end indices.

`pyrad.io.read_data_mxpola.readCHRadData` (*filename*, *radar_name*, *variableList*, *radial_resolution*, *max_range=inf*, *min_range=0*)
Reads a HDF5 file containing processed radar data in polar coordinates Parameters ——— filename: str
complete path of the file

radar_name: str name of MCH radar

variableList: list list of variables to be read

radial_resolution: float resolution of the radar in metres (i.e. high: 83.3, low: 500.)

max_range: float maximum range upto which to read data

min_range: float minimum range from which to read data

varPol: dict the projected variables, the azimuth and the range

`pyrad.io.read_data_mxpola.readIDLRadData` (*filename*, *variableList*, *max_range=inf*, *min_range=0*)
Reads a netcdf containing IDL processed radar data in polar coordinates Parameters ——— filename: str
complete path of the file

variableList: list list of variables to be read

varPol: dict dictionary containing the variables, the azimuth and the range

metadata: dict dictionary containing the metadata of the file

`pyrad.io.read_data_mxpola.readMXPOLRadData` (*filename*, *variableList*, *max_range=inf*, *min_range=0*)
Reads a netcdf containing processed radar data in polar coordinates Parameters ——— filename: str
complete path of the file

variableList: list list of variables to be read

varPol: dict dictionary containing the variables, the azimuth and the range

metadata: dict dictionary containing the metadata of the file

`pyrad.io.read_data_mxpole.row_stack(a1, a2)`

Stacks data from subsequent sweeps, while padding “empty” columns from subsequent sweeps. Inputs —— a1:
np.array

destination array

a2: np.array array which is added onto the first array

out: np.array stacked destination and additional array, with uniform shape

Created on Wed Dec 7 10:48:31 2016

@author: fvanden

Configuration file for mxpol pyart.core.Radar class. Some information may be redundant because this file is a copy from the ProfileLab toolkit.

Functions to retrieve data from this file may be found in `pyrad.io.read_data_mxpole` under the utilities section

PYRAD.IO.READ_DATA_COSMO

Functions for reading COSMO data

<code>cosmo2radar_data(radar, cosmo_coord, cosmo_data)</code>	get the COSMO value corresponding to each radar gate using nearest neighbour interpolation
<code>cosmo2radar_coord(radar, cosmo_coord[, ...])</code>	Given the radar coordinates find the nearest COSMO model pixel
<code>get_cosmo_fields(cosmo_data, cosmo_ind[, ...])</code>	Get the COSMO data corresponding to each radar gate using a precomputed look up table of the nearest neighbour
<code>read_cosmo_data(fname[, field_names, celsius])</code>	Reads COSMO data from a netcdf file
<code>read_cosmo_coord(fname[, zmin])</code>	Reads COSMO coordinates from a netcdf file
<code>_ncvar_to_dict(ncvar[, dtype])</code>	Convert a NetCDF Dataset variable to a dictionary.
<code>_prepare_for_interpolation(x_radar, y_radar, ...)</code>	prepares the COSMO 3D volume for interpolation:
<code>_put_radar_in_swiss_coord(radar)</code>	puts the Cartesian grid of the radar coordinates in Swiss coordinates

`pyrad.io.read_data_cosmo._ncvar_to_dict(ncvar, dtype=<class 'numpy.float32'>)`

Convert a NetCDF Dataset variable to a dictionary.

`pyrad.io.read_data_cosmo._prepare_for_interpolation(x_radar, y_radar, z_radar, cosmo_coord, slice_xy=True, slice_z=False)`

prepares the COSMO 3D volume for interpolation:

1. if set slices the cosmo data to the area (or volume)

covered by the radar

2. creates the x, y, z grid for the interpolation

Parameters

x_radar, y_radar, z_radar [arrays] The Swiss coordinates of the radar

cosmo_coord [dict] dictionary containing the COSMO coordinates

slice_xy [boolean] if true the horizontal plane of the COSMO field is cut to the dimensions of the radar field

slice_z [boolean] if true the vertical plane of the COSMO field is cut to the dimensions of the radar field

Returns

x_cosmo, y_cosmo, z_cosmo [1D arrays] arrays containing the flatten swiss coordinates of the COSMO data in the area of interest

ind_xmin, ind_ymin, ind_zmin, ind_xmax, ind_ymax, ind_zmax [ints] the minimum and maximum indices of each dimension

`pyrad.io.read_data_cosmo._put_radar_in_swiss_coord(radar)`

puts the Cartesian grid of the radar coordinates in Swiss coordinates

Parameters

radar [Radar] the radar object containing the information on the position of the radar gates

Returns

x_radar, y_radar, z_radar [2D arrays] arrays containing swiss coordinates of the radar [in m]

`pyrad.io.read_data_cosmo.cosmo2radar_coord(radar, cosmo_coord, slice_xy=True, slice_z=False, field_name=None)`

Given the radar coordinates find the nearest COSMO model pixel

Parameters

radar [Radar] the radar object containing the information on the position of the radar gates

cosmo_coord [dict] dictionary containing the COSMO coordinates

slice_xy [boolean] if true the horizontal plane of the COSMO field is cut to the dimensions of the radar field

slice_z [boolean] if true the vertical plane of the COSMO field is cut to the dimensions of the radar field

field_name [str] name of the field

Returns

cosmo_ind_field [dict] dictionary containing a field of COSMO indices and metadata

`pyrad.io.read_data_cosmo.cosmo2radar_data(radar, cosmo_coord, cosmo_data, time_index=0, slice_xy=True, slice_z=False, field_names=['temperature'], dtype=<class 'numpy.float32'>)`

get the COSMO value corresponding to each radar gate using nearest neighbour interpolation

Parameters

radar [Radar] the radar object containing the information on the position of the radar gates

cosmo_coord [dict] dictionary containing the COSMO coordinates

cosmo_data [dict] dictionary containing the COSMO data

time_index [int] index of the forecasted data

slice_xy [boolean] if true the horizontal plane of the COSMO field is cut to the dimensions of the radar field

slice_z [boolean] if true the vertical plane of the COSMO field is cut to the dimensions of the radar field

field_names [str] names of COSMO fields to convert (default temperature)

dtype [numpy data type object] the data type of the output data

Returns

cosmo_fields [list of dict] list of dictionary with the COSMO fields and metadata

```
pyrad.io.read_data_cosmo.get_cosmo_fields(cosmo_data, cosmo_ind, time_index=0,  
                                           field_names=['temperature'])
```

Get the COSMO data corresponding to each radar gate using a precomputed look up table of the nearest neighbour

Parameters

cosmo_data [dict] dictionary containing the COSMO data and metadata

cosmo_ind [dict] dictionary containing a field of COSMO indices and metadata

time_index [int] index of the forecasted data

field_names [str] names of COSMO parameters (default temperature)

Returns

cosmo_fields [list of dict] dictionary with the COSMO fields and metadata

```
pyrad.io.read_data_cosmo.read_cosmo_coord(fname, zmin=None)
```

Reads COSMO coordinates from a netcdf file

Parameters

fname [str] name of the file to read

Returns

cosmo_coord [dictionary] dictionary with the data and metadata

```
pyrad.io.read_data_cosmo.read_cosmo_data(fname, field_names=['temperature'], cel-  
                                          sious=True)
```

Reads COSMO data from a netcdf file

Parameters

fname [str] name of the file to read

field_names [str] name of the variable to read

celsius [Boolean] if True and variable temperature converts data from Kelvin to Centigrade

Returns

cosmo_data [dictionary] dictionary with the data and metadata

PYRAD.IO.READ_DATA_HZT

Functions for reading HZT data

<code>hzt2radar_data(radar, hzt_coord, hzt_data[, ...])</code>	get the HZT value corresponding to each radar gate using nearest neighbour interpolation
<code>hzt2radar_coord(radar, hzt_coord[, ...])</code>	Given the radar coordinates find the nearest HZT pixel
<code>get_iso0_field(hzt_data, hzt_ind, z_radar[, ...])</code>	Get the height over iso0 data corresponding to each radar gate using a precomputed look up table of the nearest neighbour
<code>read_hzt_data(fname[, chy0, chx0, read_lib])</code>	Reads iso-0 degree data from an HZT file
<code>_prepare_for_interpolation(x_radar, y_radar, ...)</code>	prepares the HZT 2D volume for interpolation:

```
pyrad.io.read_data_hzt._prepare_for_interpolation(x_radar, y_radar, hzt_coord,
                                                    slice_xy=True)
```

prepares the HZT 2D volume for interpolation:

1. if set slices the cosmo data to the area covered by the radar
2. creates the x, y grid for the interpolation

Parameters

x_radar, y_radar [arrays] The Swiss coordinates of the radar

hzt_coord [dict] dictionary containing the HZT coordinates

slice_xy [boolean] if true the horizontal plane of the HZT field is cut to the dimensions of the radar field

Returns

x_hzt, y_hzt [1D arrays] arrays containing the flatten swiss coordinates of the HZT data in the area of interest [m]

ind_xmin, ind_ymin, ind_xmax, ind_ymax [ints] the minimum and maximum indices of each dimension

```
pyrad.io.read_data_hzt.get_iso0_field(hzt_data, hzt_ind, z_radar,
                                       field_name='height_over_iso0')
```

Get the height over iso0 data corresponding to each radar gate using a precomputed look up table of the nearest neighbour

Parameters

hzt_data [dict] dictionary containing the HZT data and metadata

hzt_ind [dict] dictionary containing a field of HZT indices and metadata

z_radar [ndarray] gates altitude [m MSL]

field_name [str] names of HZT parameters (default height_over_iso0)

Returns

iso0_field [list of dict] dictionary with the height over iso0 field and metadata

```
pyrad.io.read_data_hzt.hzt2radar_coord(radar,          hzt_coord,          slice_xy=True,
                                         field_name=None)
```

Given the radar coordinates find the nearest HZT pixel

Parameters

radar [Radar] the radar object containing the information on the position of the radar gates

hzt_coord [dict] dictionary containing the HZT coordinates

slice_xy [boolean] if true the horizontal plane of the HZT field is cut to the dimensions of the radar field

field_name [str] name of the field

Returns

hzt_ind_field [dict] dictionary containing a field of HZT indices and metadata

```
pyrad.io.read_data_hzt.hzt2radar_data(radar,  hzt_coord,  hzt_data,  slice_xy=True,
                                         field_name='height_over_iso0')
```

get the HZT value corresponding to each radar gate using nearest neighbour interpolation

Parameters

radar [Radar] the radar object containing the information on the position of the radar gates

hzt_coord [dict] dictionary containing the HZT coordinates

hzt_data [dict] dictionary containing the HZT data

slice_xy [boolean] if true the horizontal plane of the COSMO field is cut to the dimensions of the radar field

field_name [str] name of HZT fields to convert (default height_over_iso0)

Returns

hzt_fields [list of dict] list of dictionary with the HZT fields and metadata

```
pyrad.io.read_data_hzt.read_hzt_data(fname, chy0=255.0, chx0=-160.0, read_lib='C')
```

Reads iso-0 degree data from an HZT file

Parameters

fname [str] name of the file to read

chy0, chx0: float south west point of grid in Swiss coordinates [km]

read_lib [str] Type of METRANET read library used. Can be 'C' or 'python'

Returns

hzt_data [dictionary] dictionary with the data and metadata

PYRAD.IO.READ_DATA_DEM

Functions for reading data derived from Digital Elevation Models (DEM)

<code>dem2radar_data(radar, dem_data[, slice_xy, ...])</code>	get the DEM value corresponding to each radar gate using nearest neighbour interpolation
<code>read_idrisi_data(fname, field_name[, fill_value])</code>	Reads DEM data from an IDRISI .rst file
<code>read_idrisi_metadata(fname)</code>	Reads DEM metadata from a IDRISI .rdc file
<code>_prepare_for_interpolation(x_radar, y_radar, ...)</code>	prepares the DEM 2D volume for interpolation:

```
pyrad.io.read_data_dem._prepare_for_interpolation(x_radar, y_radar, dem_coord,
                                                    slice_xy=True)
```

prepares the DEM 2D volume for interpolation:

1. if set slices the DEM data to the area

covered by the radar

2. creates the x, y grid for the interpolation

Parameters

x_radar, y_radar [arrays] The Swiss coordinates of the radar

dem_coord [dict] dictionary containing the DEM coordinates

slice_xy [boolean] if true the horizontal plane of the DEM field is cut to the dimensions of the radar field

Returns

x_dem, y_dem [1D arrays] arrays containing the flatten swiss coordinates of the DEM data in the area of interest

ind_xmin, ind_ymin, ind_xmax, ind_ymax [ints] the minimum and maximum indices of each dimension

```
pyrad.io.read_data_dem.dem2radar_data(radar, dem_data, slice_xy=True,
                                         field_name='visibility')
get the DEM value corresponding to each radar gate using nearest neighbour interpolation
```

Parameters

radar [Radar] the radar object containing the information on the position of the radar gates

dem_data [dict] dictionary containing the DEM data

slice_xy [boolean] if true the horizontal plane of the DEM field is cut to the dimensions of the radar field

field_names [str] names of DEM fields to convert

Returns

dem_field [dict] Dictionary with the DEM fields and metadata

`pyrad.io.read_data_dem.read_idrиси_data` (*fname*, *field_name*, *fill_value=-99.0*)

Reads DEM data from an IDRISI .rst file

Parameters

fname [str] name of the file to read

field_name [str] name of the readed variable

fill_value [float] The fill value

Returns

dem_data [dictionary] dictionary with the data and metadata

`pyrad.io.read_data_dem.read_idrиси_metadata` (*fname*)

Reads DEM metadata from a IDRISI .rdc file

Parameters

fname [str] name of the file to read

Returns

metadata [dictionary] dictionary with the metadata

PYRAD.IO.READ_DATA_SENSOR

Functions for reading data from other sensors

<i>read_windmills_data</i> (fname)	Read the wind mills data csv file
<i>read_thundertracking_info</i> (fname)	Reads the TRT info used for thundertracking
<i>read_trt_info_all</i> (info_path)	Reads all the TRT info files
<i>read_trt_info_all2</i> (info_path)	Reads all the TRT info files
<i>read_trt_info</i> (fname)	Reads the TRT info used for thundertracking and contained in a text file.
<i>read_trt_info2</i> (fname)	Reads the TRT info used for thundertracking and contained in a text file.
<i>read_trt_scores</i> (fname)	Reads the TRT scores contained in a text file.
<i>read_trt_cell_lightning</i> (fname)	Reads the lightning data of a TRT cell.
<i>read_trt_data</i> (fname)	Reads the TRT data contained in a text file.
<i>read_trt_traj_data</i> (fname)	Reads the TRT cell data contained in a text file.
<i>read_trt_thundertracking_traj_data</i> (fname)	Reads the TRT cell data contained in a text file.
<i>read_lightning</i> (fname[, filter_data])	Reads lightning data contained in a text file.
<i>read_meteorage</i> (fname)	Reads METEORAGE lightning data contained in a text file.
<i>read_lightning_traj</i> (fname)	Reads lightning trajectory data contained in a csv file.
<i>read_lightning_all</i> (fname[, labels])	Reads a file containing lightning data and co-located polarimetric data.
<i>get_sensor_data</i> (date, datatype, cfg)	Gets data from a point measurement sensor (rain gauge or disdrometer)
<i>read_smn</i> (fname)	Reads SwissMetNet data contained in a csv file
<i>read_smn2</i> (fname)	Reads SwissMetNet data contained in a csv file with format station,time,value
<i>read_disdro_scattering</i> (fname)	Reads scattering parameters computed from disdrometer data contained in a text file
<i>read_disdro</i> (fname)	Reads scattering parameters computed from disdrometer data contained in a text file

`pyrad.io.read_data_sensor.get_sensor_data` (*date*, *datatype*, *cfg*)
Gets data from a point measurement sensor (rain gauge or disdrometer)

Parameters

- date** [datetime object] measurement date
- datatype** [str] name of the data type to read
- cfg** [dictionary] dictionary containing sensor information

Returns

sensordate , sensorvalue, label, period [tuple] date, value, type of sensor and measurement period

`pyrad.io.read_data_sensor.read_disdro (fname)`

Reads scattering parameters computed from disdrometer data contained in a text file

Parameters

fname [str] path of time series file

Returns

date, precipitype, variable, scattering temperature: tuple The read values

`pyrad.io.read_data_sensor.read_disdro_scattering (fname)`

Reads scattering parameters computed from disdrometer data contained in a text file

Parameters

fname [str] path of time series file

Returns

date, precipitype, lwc, rr, zh, zv, zdr, ldr, ah, av, adiff, kdp, deltaco, rhohv [tuple] The read values

`pyrad.io.read_data_sensor.read_lightning (fname, filter_data=True)`

Reads lightning data contained in a text file. The file has the following fields:

flashnr: (0 is for noise) UTC seconds of the day Time within flash (in seconds) Latitude (decimal degrees) Longitude (decimal degrees) Altitude (m MSL) Power (dBm)

Parameters

fname [str] path of time series file

filter_data [Boolean] if True filter noise (flashnr = 0)

Returns

flashnr, time_data, time_in_flash, lat, lon, alt, dBm [tuple] A tuple containing the read values. None otherwise

`pyrad.io.read_data_sensor.read_lightning_all (fname, labels=['hydro [-]', 'KDPc [deg/Km]', 'dBZc [dBZ]', 'RhoHvc [-]', 'TEMP [deg C]', 'ZDRc [dB]'])`

Reads a file containing lightning data and co-located polarimetric data. fields:

flashnr time data Time within flash (in seconds) Latitude (decimal degrees) Longitude (decimal degrees) Altitude (m MSL) Power (dBm) Polarimetric values at flash position

Parameters

fname [str] path of time series file

labels [list of str] The polarimetric variables labels

Returns

flashnr, time_data, time_in_flash, lat, lon, alt, dBm,

pol_vals_dict [tuple] A tuple containing the read values. None otherwise

`pyrad.io.read_data_sensor.read_lightning_traj(fname)`

Reads lightning trajectory data contained in a csv file. The file has the following fields:

Date UTC [seconds since midnight] # Flash Flash Power (dBm) Value at flash Mean value in a 3x3x3 polar box Min value in a 3x3x3 polar box Max value in a 3x3x3 polar box # valid values in the polar box

Parameters

fname [str] path of time series file

Returns

time_flash, flashnr, dBm, val_at_flash, val_mean, val_min, val_max,

nval [tuple] A tuple containing the read values. None otherwise

`pyrad.io.read_data_sensor.read_meteorage(fname)`

Reads METEORAGE lightning data contained in a text file. The file has the following fields:

date: date + time + time zone lon: longitude [degree] lat: latitude [degree] intens: amplitude [kilo amperes] ns: number of strokes of the flash mode: kind of localization [0,15] intra: 1 = intra-cloud , 0 = cloud-to-ground ax: length of the semi-major axis of the ellipse [km] ki2: standard deviation on the localization computation (K_i^2) ecc: eccentricity (major-axis / minor-axis) incl: ellipse inclination (angle with respect to the North, +90° is

East) [degrees]

sind: stroke index within the flash

Parameters

fname [str] path of time series file

Returns

stroke_time, lon, lat, intens, ns, mode, intra, ax, ki2, ecc, incl,

sind [tuple] A tuple containing the read values. None otherwise

`pyrad.io.read_data_sensor.read_smn(fname)`

Reads SwissMetNet data contained in a csv file

Parameters

fname [str] path of time series file

Returns

smn_id, date , pressure, temp, rh, precip, wspeed, wdir [tuple] The read values

`pyrad.io.read_data_sensor.read_smn2(fname)`

Reads SwissMetNet data contained in a csv file with format station,time,value

Parameters

fname [str] path of time series file

Returns

smn_id, date , value [tuple] The read values

`pyrad.io.read_data_sensor.read_thundertracking_info(fname)`

Reads the TRT info used for thundertracking

Parameters

fname [str] Name of the file containing the info

Returns

A tuple containing the read values. None otherwise. The read values are

id, max_rank, nscans_Xband, time_start, time_end

`pyrad.io.read_data_sensor.read_trt_cell_lightning(fname)`

Reads the lightning data of a TRT cell. The file has the following fields:

traj_ID yyyyymmddHHMM lon lat area RANKr nflashes flash_dens

Parameters

fname [str] path of the TRT data file

Returns

A tuple containing the read values. None otherwise

`pyrad.io.read_data_sensor.read_trt_data(fname)`

Reads the TRT data contained in a text file. The file has the following fields:

traj_ID yyyyymmddHHMM

Description of ellipsis: lon [deg] lat [deg] ell_L [km] long ell_S [km] short ell_or [deg] orientation area [km2]

Cell speed: vel_x [km/h] vel_y [km/h] det [dBZ]: detection threshold RANKr from 0 to 40 (int)

Lightning information: CG- number (int) CG+ number (int) CG number (int) %CG+ [%]

Echo top information: ET45 [km] echotop 45 max ET45m [km] echotop 45 median ET15 [km] echotop 15 max ET15m [km] echotop 15 median

VIL and max echo: VIL [kg/m2] vertical integrated liquid content maxH [km] height of maximum reflectivity (maximum on the cell) maxHm [km] height of maximum reflectivity (median per cell)

POH [%] RANK (deprecated)

standard deviation of the current time step cell velocity respect to the previous time: Dvel_x [km/h] Dvel_y [km/h]

cell_contour_lon-lat

Parameters

fname [str] path of the TRT data file

Returns

A tuple containing the read values. None otherwise

`pyrad.io.read_data_sensor.read_trt_info(fname)`

Reads the TRT info used for thundertracking and contained in a text file.

Parameters

fname [str] path of the TRT info file

Returns

A tuple containing the read values. None otherwise. The read values are

**trt_time, id, rank, nscans, azi, rng, lat, lon, ell_l, ell_s, ell_or,
vel_x, vel_y, det**

`pyrad.io.read_data_sensor.read_trt_info2(fname)`

Reads the TRT info used for thundertracking and contained in a text file.

Parameters

fname [str] path of the TRT info file

Returns

A tuple containing the read values. None otherwise. The read values are

**trt_time, id, rank, scan_time, azi, rng, lat, lon, ell_l, ell_s, ell_or,
vel_x, vel_y, det**

`pyrad.io.read_data_sensor.read_trt_info_all(info_path)`

Reads all the TRT info files

Parameters

info_path [str] directory where the files are stored

Returns

A tuple containing the read values. None otherwise. The read values are

**trt_time, id, rank, nscans, azi, rng, lat, lon, ell_l, ell_s, ell_or,
vel_x, vel_y, det**

`pyrad.io.read_data_sensor.read_trt_info_all2(info_path)`

Reads all the TRT info files

Parameters

info_path [str] directory where the files are stored

Returns

A tuple containing the read values. None otherwise. The read values are

**trt_time, id, rank, scan_time, azi, rng, lat, lon, ell_l, ell_s, ell_or,
vel_x, vel_y, det**

`pyrad.io.read_data_sensor.read_trt_scores(fname)`

Reads the TRT scores contained in a text file. The file has the following fields:

traj ID max flash density time max flash density rank max flash density max rank time max rank

Parameters

fname [str] path of the TRT data file

Returns

A tuple containing the read values. None otherwise

`pyrad.io.read_data_sensor.read_trt_thundertracking_traj_data(fname)`

Reads the TRT cell data contained in a text file. The file has the following fields:

traj_ID scan_ordered_time scan_time azi rng yyyyymmddHHMM
lon [deg] lat [deg] ell_L [km] long ell_S [km] short ell_or [deg] orientation area [km2]
vel_x [km/h] cell speed vel_y [km/h] det [dBZ] detection threshold RANKr from 0 to 40 (int)
CG- number (int) CG+ number (int) CG number (int) %CG+ [%]
ET45 [km] echotop 45 max ET45m [km] echotop 45 median ET15 [km] echotop 15 max ET15m [km] echotop 15 median VIL [kg/m2] vertical integrated liquid content maxH [km] height of maximum reflectivity (maximum on the cell) maxHm [km] height of maximum reflectivity (median per cell) POH [%] RANK (deprecated)
Standard deviation of the current time step cell velocity respect to the previous time: Dvel_x [km/h] Dvel_y [km/h]
cell_contour_lon-lat

Parameters

fname [str] path of the TRT data file

Returns

A tuple containing the read values. None otherwise

`pyrad.io.read_data_sensor.read_trt_traj_data(fname)`

Reads the TRT cell data contained in a text file. The file has the following fields:

traj_ID yyyyymmddHHMM
lon [deg] lat [deg] ell_L [km] long ell_S [km] short ell_or [deg] orientation area [km2]
vel_x [km/h] cell speed vel_y [km/h] det [dBZ] detection threshold RANKr from 0 to 40 (int)
CG- number (int) CG+ number (int) CG number (int) %CG+ [%]
ET45 [km] echotop 45 max ET45m [km] echotop 45 median ET15 [km] echotop 15 max ET15m [km] echotop 15 median VIL [kg/m2] vertical integrated liquid content maxH [km] height of maximum reflectivity (maximum on the cell) maxHm [km] height of maximum reflectivity (median per cell) POH [%] RANK (deprecated)
Standard deviation of the current time step cell velocity respect to the previous time: Dvel_x [km/h] Dvel_y [km/h]
cell_contour_lon-lat

Parameters

fname [str] path of the TRT data file

Returns

A tuple containing the read values. None otherwise

`pyrad.io.read_data_sensor.read_windmills_data(fname)`

Read the wind mills data csv file

Parameters

fname [str] path of the windmill data file

Returns

windmill_dict [dict] A dictionary containing all the parameters or None

PYRAD.IO.READ_DATA_SUN

Functions for reading data used in sun monitoring

<code>read_sun_hits_multiple_days(cfg, time_ref[, ...])</code>	Reads sun hits data from multiple file sources
<code>read_sun_hits(fname)</code>	Reads sun hits data contained in a csv file
<code>read_sun_retrieval(fname)</code>	Reads sun retrieval data contained in a csv file
<code>read_solar_flux(fname)</code>	Reads solar flux data from the DRAO observatory in Canada

`pyrad.io.read_data_sun.read_solar_flux(fname)`
Reads solar flux data from the DRAO observatory in Canada

Parameters

fname [str] path of time series file

Returns

flux_datetime [datetime array] the date and time of the solar flux retrievals

flux_value [array] the observed solar flux

`pyrad.io.read_data_sun.read_sun_hits(fname)`
Reads sun hits data contained in a csv file

Parameters

fname [str] path of time series file

Returns

date, ray, nrng, rad_el, rad_az, sun_el, sun_az, ph, ph_std, npv, nvalh,

pv, pv_std, npv, nvalv, zdr, zdr_std, nzdr, nvalzdr [tuple] Each parameter is an array containing a time series of information on a variable

`pyrad.io.read_data_sun.read_sun_hits_multiple_days(cfg, time_ref, nfiles=1)`
Reads sun hits data from multiple file sources

Parameters

cfg [dict] dictionary with configuration data to find out the right file

time_ref [datetime object] reference time

nfiles [int] number of files to read

Returns

date, ray, nrng, rad_el, rad_az, sun_el, sun_az, ph, ph_std, nph, nvalh,
pv, pv_std, npv, nvalv, zdr, zdr_std, nzdr, nvalzdr [tuple] Each parameter is an array containing a time series of information on a variable

`pyrad.io.read_data_sun.read_sun_retrieval` (*fname*)

Reads sun retrieval data contained in a csv file

Parameters

fname [str] path of time series file

Returns

first_hit_time, last_hit_time, nhits_h, el_width_h, az_width_h, el_bias_h,
az_bias_h, dBm_sun_est, std_dBm_sun_est, sf_h,
nhits_v, el_width_v, az_width_v, el_bias_v, az_bias_v, dBmv_sun_est,
std_dBmv_sun_est, sf_v,
nhits_zdr, zdr_sun_est, std_zdr_sun_est,
sf_ref, ref_time [tuple] Each parameter is an array containing a time series of information on a variable

PYRAD.IO.READ_DATA_OTHER

Functions for reading auxiliary data

<i>read_proc_periods</i> (fname)	Reads a file containing the start and stop times of periods to process
<i>read_profile_ts</i> (fname_list, labels[, hres, ...])	Reads a collection of profile data file and creates a time series
<i>read_histogram_ts</i> (fname_list, datatype[, t_res])	Reads a collection of histogram data file and creates a time series
<i>read_quantiles_ts</i> (fname_list[, step, qmin, ...])	Reads a collection of quantiles data file and creates a time series
<i>read_rhi_profile</i> (fname[, labels])	Reads a monitoring time series contained in a csv file
<i>read_last_state</i> (fname)	Reads a file containing the date of acquisition of the last volume processed
<i>read_status</i> (votime, cfg[, ind_rad])	Reads rad4alp xml status file.
<i>read_rad4alp_cosmo</i> (fname, datatype[, ngates])	Reads rad4alp COSMO data binary file.
<i>read_rad4alp_vis</i> (fname, datatype)	Reads rad4alp visibility data binary file.
<i>read_histogram</i> (fname)	Reads a histogram contained in a csv file
<i>read_quantiles</i> (fname)	Reads quantiles contained in a csv file
<i>read_excess_gates</i> (fname)	Reads a csv files containing the position of gates exceeding a given percentile of frequency of occurrence
<i>read_colocated_gates</i> (fname)	Reads a csv files containing the position of colocated gates
<i>read_colocated_data</i> (fname)	Reads a csv files containing colocated data
<i>read_colocated_data_time_avg</i> (fname)	Reads a csv files containing time averaged colocated data
<i>read_timeseries</i> (fname)	Reads a time series contained in a csv file
<i>read_ts_cum</i> (fname)	Reads a time series of precipitation accumulation contained in a csv file
<i>read_ml_ts</i> (fname)	Reads a melting layer time series contained in a csv file
<i>read_monitoring_ts</i> (fname[, sort_by_date])	Reads a monitoring time series contained in a csv file
<i>read_monitoring_ts_old</i> (fname)	Reads an old format of the monitoring time series contained in a text file
<i>read_intercomp_scores_ts</i> (fname[, sort_by_date])	Reads a radar intercomparison scores csv file
<i>read_intercomp_scores_ts_old</i> (fname)	Reads a radar intercomparison scores csv file in old format
<i>read_intercomp_scores_ts_old_v0</i> (fname[, ...])	Reads a radar intercomparison scores csv file in the oldest format

Continued on next page

Table 1 – continued from previous page

<code>read_selfconsistency(fname)</code>	Reads a self-consistency table with Zdr, Kdp/Zh columns
<code>read_antenna_pattern(fname[, linear, twoway])</code>	Read antenna pattern from file

`pyrad.io.read_data_other.read_antenna_pattern(fname, linear=False, twoway=False)`

Read antenna pattern from file

Parameters

fname [str] path of the antenna pattern file

linear [boolean] if true the antenna pattern is given in linear units

twoway [boolean] if true the attenuation is two-way

Returns

pattern [dict] dictionary with the fields angle and attenuation

`pyrad.io.read_data_other.read_colocated_data(fname)`

Reads a csv files containing colocated data

Parameters

fname [str] path of time series file

Returns

rad1_time, rad1_ray_ind, rad1_rng_ind, rad1_ele, rad1_azi, rad1_rng,

rad1_val, rad2_time, rad2_ray_ind, rad2_rng_ind, rad2_ele, rad2_azi,

rad2_rng, rad2_val [tuple] A tuple with the data read. None otherwise

`pyrad.io.read_data_other.read_colocated_data_time_avg(fname)`

Reads a csv files containing time averaged colocated data

Parameters

fname [str] path of time series file

Returns

rad1_time, rad1_ray_ind, rad1_rng_ind, rad1_ele, rad1_azi, rad1_rng,

rad1_val, rad2_time, rad2_ray_ind, rad2_rng_ind, rad2_ele, rad2_azi,

rad2_rng, rad2_val [tuple] A tuple with the data read. None otherwise

`pyrad.io.read_data_other.read_colocated_gates(fname)`

Reads a csv files containing the position of colocated gates

Parameters

fname [str] path of time series file

Returns

rad1_ray_ind, rad1_rng_ind, rad1_ele, rad1_azi, rad1_rng,

rad2_ray_ind, rad2_rng_ind, rad2_ele, rad2_azi, rad2_rng [tuple] A tuple with the data read. None otherwise

`pyrad.io.read_data_other.read_excess_gates(fname)`

Reads a csv files containing the position of gates exceeding a given percentile of frequency of occurrence

Parameters

fname [str] path of time series file

Returns

rad1_ray_ind, rad1_rng_ind, rad1_ele, rad1_az, rad1_rng,

rad2_ray_ind, rad2_rng_ind, rad2_ele, rad2_az, rad2_rng [tuple] A tuple with the data read. None otherwise

`pyrad.io.read_data_other.read_histogram(fname)`

Reads a histogram contained in a csv file

Parameters

fname [str] path of time series file

Returns

hist, bin_edges [tuple] The read data. None otherwise

`pyrad.io.read_data_other.read_histogram_ts(fname_list, datatype, t_res=300.0)`

Reads a collection of histogram data file and creates a time series

Parameters

fname_list [str] list of files to read

datatype [str] The data type (dBZ, ZDR, etc.)

t_res [float] time resolution [s]. If None the time resolution is taken as the median

Returns

tbin_edges, bin_edges, data_ma, datetime_arr [tuple] The read data. None otherwise

`pyrad.io.read_data_other.read_intercomp_scores_ts(fname, sort_by_date=False)`

Reads a radar intercomparison scores csv file

Parameters

fname [str] path of time series file

sort_by_date [bool] if True, the read data is sorted by date prior to exit

Returns

date_vec, np_vec, meanbias_vec, medianbias_vec, quant25bias_vec,

quant75bias_vec, modebias_vec, corr_vec, slope_vec, intercep_vec,

intercep_slope1_vec [tuple] The read data. None otherwise

`pyrad.io.read_data_other.read_intercomp_scores_ts_old(fname)`

Reads a radar intercomparison scores csv file in old format

Parameters

fname [str] path of time series file

Returns

date_vec, np_vec, meanbias_vec, medianbias_vec, quant25bias_vec,

quant75bias_vec, modebias_vec, corr_vec, slope_vec, intercep_vec,

intercep_slope1_vec [tuple] The read data. None otherwise

`pyrad.io.read_data_other.read_intercomp_scores_ts_old_v0(fname, corr_min=0.6,
np_min=9)`

Reads a radar intercomparison scores csv file in the oldest format

Parameters

fname [str] path of time series file

Returns

date_vec, np_vec, meanbias_vec, medianbias_vec, quant25bias_vec, quant75bias_vec, modebias_vec, corr_vec, slope_vec, intercep_vec, intercep_slope1_vec [tuple] The read data. None otherwise

`pyrad.io.read_data_other.read_last_state(fname)`

Reads a file containing the date of acquisition of the last volume processed

Parameters

fname [str] name of the file to read

Returns

last_state [datetime object] the date

`pyrad.io.read_data_other.read_ml_ts(fname)`

Reads a melting layer time series contained in a csv file

Parameters

fname [str] path of time series file

Returns

dt_ml, ml_top_avg, ml_top_std, thick_avg, thick_std, nrays_valid, nrays_total [tuple] The read data. None otherwise

`pyrad.io.read_data_other.read_monitoring_ts(fname, sort_by_date=False)`

Reads a monitoring time series contained in a csv file

Parameters

fname [str] path of time series file

sort_by_date [bool] if True, the read data is sorted by date prior to exit

Returns

date, np_t, central_quantile, low_quantile, high_quantile [tuple] The read data. None otherwise

`pyrad.io.read_data_other.read_monitoring_ts_old(fname)`

Reads an old format of the monitoring time series contained in a text file

Parameters

fname [str] path of time series file

Returns

date, np_t, central_quantile, low_quantile, high_quantile [tuple] The read data in the current format. None otherwise

`pyrad.io.read_data_other.read_proc_periods(fname)`

Reads a file containing the start and stop times of periods to process

Parameters

fname [str] name of the file to read

Returns

starttimes, endtimes [array of datetime objects or None] The start and end times of the periods to process if the reading has been successful

`pyrad.io.read_data_other.read_profile_ts` (*fname_list*, *labels*, *hres=None*, *label_nr=0*, *t_res=300.0*)

Reads a collection of profile data file and creates a time series

Parameters

fname_list [str] list of files to read

labels [list of str] The data labels

hres [float] Height resolution

label_nr [int] the label nr of the data that will be used in the time series

t_res [float] time resolution [s]. If None the time resolution is taken as the median

Returns

tbin_edges, hbin_edges, np_ma, data_ma, datetime_arr [tuple] The read data. None otherwise

`pyrad.io.read_data_other.read_quantiles` (*fname*)

Reads quantiles contained in a csv file

Parameters

fname [str] path of time series file

Returns

quantiles, values [tuple] The read data. None otherwise

`pyrad.io.read_data_other.read_quantiles_ts` (*fname_list*, *step=5.0*, *qmin=0.0*, *qmax=100.0*, *t_res=300.0*)

Reads a collection of quantiles data file and creates a time series

Parameters

fname_list [str] list of files to read

step, qmin, qmax [float] The minimum, maximum and step quantiles

t_res [float] time resolution [s]. If None the time resolution is taken as the median

Returns

tbin_edges, qbin_edges, data_ma, datetime_arr [tuple] The read data. None otherwise

`pyrad.io.read_data_other.read_rad4alp_cosmo` (*fname*, *datatype*, *ngates=0*)

Reads rad4alp COSMO data binary file.

Parameters

fname [str] name of the file to read

datatype [str] name of the data type

ngates [int] maximum number of range gates per ray. If larger than 0 the radar field will be cut accordingly.

Returns

field [dictionary] The data field

`pyrad.io.read_data_other.read_rad4alp_vis` (*fname*, *datatype*)

Reads rad4alp visibility data binary file.

Parameters

fname [str] name of the file to read

datatype [str] name of the data type

Returns

field_list [list of dictionaries] A data field. Each element of the list corresponds to one elevation

`pyrad.io.read_data_other.read_rhi_profile` (*fname*, *labels*=['50.0-percentile', '25.0-percentile', '75.0-percentile'])

Reads a monitoring time series contained in a csv file

Parameters

fname [str] path of time series file

labels [list of str] The data labels

Returns

height, np_t, vals [tuple] The read data. None otherwise

`pyrad.io.read_data_other.read_selfconsistency` (*fname*)

Reads a self-consistency table with Zdr, Kdp/Zh columns

Parameters

fname [str] path of time series file

Returns

zdr, kdpzh [arrays] The read values

`pyrad.io.read_data_other.read_status` (*voltime*, *cfg*, *ind_rad=0*)

Reads rad4alp xml status file.

Parameters

voltime [datetime object] volume scan time

cfg: dictionary of dictionaries configuration info to figure out where the data is

ind_rad: int radar index

Returns

root [root element object] The information contained in the status file

`pyrad.io.read_data_other.read_timeseries` (*fname*)

Reads a time series contained in a csv file

Parameters

fname [str] path of time series file

Returns

date, value [tuple] A datetime object array containing the time and a numpy masked array containing the value. None otherwise

`pyrad.io.read_data_other.read_ts_cum` (*fname*)

Reads a time series of precipitation accumulation contained in a csv file

Parameters

fname [str] path of time series file

Returns

date, np_radar, radar_value, np_sensor, sensor_value [tuple] The data read

PYRAD.IO.WRITE_DATA

Functions for writing pyrad output data

<i>write_proc_periods</i> (start_times, end_times, fname)	writes an output file containing start and stop times of periods to process
<i>write_fixed_angle</i> (time_data, fixed_angle, ...)	writes an output file with the fixed angle data
<i>write_ts_lightning</i> (flashnr, time_data, ...)	writes the LMA sources data and the value of the collocated polarimetric variables
<i>send_msg</i> (sender, receiver_list, subject, fname)	sends the content of a text file by email
<i>write_alarm_msg</i> (radar_name, param_name_unit, ...)	writes an alarm file
<i>write_last_state</i> (datetime_last, fname)	writes SwissMetNet data in format datetime,avg_value, std_value
<i>write_smn</i> (datetime_vec, value_avg_vec, ...)	writes SwissMetNet data in format datetime,avg_value, std_value
<i>write_trt_info</i> (ids, max_rank, nscans, ...)	writes TRT info of the thundertracking
<i>write_trt_cell_data</i> (traj_ID, yyyymmddHHMM, ...)	writes TRT cell data
<i>write_trt_thundertracking_data</i> (traj_ID, ...)	writes TRT cell data of the thundertracking scan
<i>write_trt_cell_scores</i> (traj_ID, ...)	writes TRT cells scores
<i>write_trt_cell_lightning</i> (cell_ID, cell_time, ...)	writes the lightning data for each TRT cell
<i>write_trt_rpc</i> (cell_ID, cell_time, lon, lat, ...)	writes the rimed particles column data for a TRT cell
<i>write_rhi_profile</i> (hvec, data, nvalid_vec, ...)	writes the values of an RHI profile in a text file
<i>write_field_coverage</i> (quantiles, values, ...)	writes the quantiles of the coverage on a particular sector
<i>write_cdf</i> (quantiles, values, ntot, nnan, ...)	writes a cumulative distribution function
<i>write_histogram</i> (bin_edges, values, fname[, ...])	writes a histogram
<i>write_quantiles</i> (quantiles, values, fname[, ...])	writes quantiles
<i>write_ts_polar_data</i> (dataset, fname)	writes time series of data
<i>write_ts_grid_data</i> (dataset, fname)	writes time series of data
<i>write_ts_ml</i> (dt_ml, ml_top_avg, ml_top_std, ...)	writes time series of melting layer data
<i>write_ts_cum</i> (dataset, fname)	writes time series accumulation of data
<i>write_monitoring_ts</i> (start_time, np_t, ...[, ...])	writes time series of data
<i>write_excess_gates</i> (excess_dict, fname)	Writes the position and values of gates that have a frequency of occurrence higher than a particular threshold
<i>write_intercomp_scores_ts</i> (start_time, stats, ...)	writes time series of radar intercomparison scores

Continued on next page

Table 1 – continued from previous page

<code>write_colocated_gates(coloc_gates, fname)</code>	Writes the position of gates colocated with two radars
<code>write_colocated_data(coloc_data, fname)</code>	Writes the data of gates colocated with two radars
<code>write_colocated_data_time_avg(coloc_data, fname)</code>	Writes the time averaged data of gates colocated with two radars
<code>write_sun_hits(sun_hits, fname)</code>	Writes sun hits data.
<code>write_sun_retrieval(sun_retrieval, fname)</code>	Writes sun retrieval data.

`pyrad.io.write_data.send_msg(sender, receiver_list, subject, fname)`
sends the content of a text file by email

Parameters

sender [str] the email address of the sender
receiver_list [list of string] list with the email addresses of the receiver
subject [str] the subject of the email
fname [str] name of the file containing the content of the email message

Returns

fname [str] the name of the file containing the content

`pyrad.io.write_data.write_alarm_msg(radar_name, param_name_unit, date_last, target, tol_abs, np_trend, value_trend, tol_trend, nevents, np_last, value_last, fname)`

writes an alarm file

Parameters

radar_name [str] Name of the radar being controlled
param_name_unit [str] Parameter and units
date_last [datetime object] date of the current event
target, tol_abs [float] Target value and tolerance
np_trend [int] Total number of points in trend
value_trend, tol_trend [float] Trend value and tolerance
nevents: int Number of events in trend
np_last [int] Number of points in the current event
value_last [float] Value of the current event
fname [str] Name of file where to store the alarm information

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_data.write_cdf(quantiles, values, ntot, nnan, nclut, nblocked, nprec_filter, noutliers, ncdf, fname, use_nans=False, nan_value=0.0, filterprec=[], vismin=None, sector=None, datatype=None, timeinfo=None)`

writes a cumulative distribution function

Parameters

quantiles [datetime array] array containing the measurement time
values [float array] array containing the average value

fname [float array] array containing the standard deviation

sector [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_data.write_colocated_data(coloc_data, fname)`

Writes the data of gates colocated with two radars

Parameters

coloc_data [dict] dictionary containing the colocated data parameters

fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_data.write_colocated_data_time_avg(coloc_data, fname)`

Writes the time averaged data of gates colocated with two radars

Parameters

coloc_data [dict] dictionary containing the colocated data parameters

fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_data.write_colocated_gates(coloc_gates, fname)`

Writes the position of gates colocated with two radars

Parameters

coloc_gates [dict] dictionary containing the colocated gates parameters

fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_data.write_excess_gates(excess_dict, fname)`

Writes the position and values of gates that have a frequency of occurrence higher than a particular threshold

Parameters

excess_dict [dict] dictionary containing the gates parameters

fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_data.write_field_coverage(quantiles, values, ele_start, ele_stop, azi_start,
 azi_stop, threshold, nvalid_min, datatype, time-
 info, fname)`

writes the quantiles of the coverage on a particular sector

Parameters

quantiles [datetime array] array containing the quantiles computed

values [float array] quantile value

ele_start, ele_stop, azi_start, azi_stop [float] The limits of the sector
threshold [float] The minimum value to consider the data valid
nvalid_min [int] the minimum number of points to consider that there are values in a ray
datatype [str] data type and units
timeinfo [datetime object] the time stamp of the data
fname [str] name of the file where to write the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_data.write_fixed_angle`(*time_data*, *fixed_angle*, *rad_lat*, *rad_lon*, *rad_alt*,
fname)

writes an output file with the fixed angle data

Parameters

time_data [datetime object] The scan time
fixed_angle [float] The first fixed angle in the scan
rad_lat, rad_lon, rad_alt [float] Latitude, longitude [deg] and altitude [m MSL] of the radar
fname [str] The name of the file where to write

Returns

fname [str] the name of the file containing the content

`pyrad.io.write_data.write_histogram`(*bin_edges*, *values*, *fname*, *datatype*='undefined',
step=0)

writes a histogram

Parameters

bin_edges [float array] array containing the histogram bin edges
values [int array] array containing the number of points in each bin
fname [str] file name
datatype: str The data type
step [str] The bin step

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_data.write_intercomp_scores_ts`(*start_time*, *stats*, *field_name*,
fname, *rad1_name*='RADAR001',
rad2_name='RADAR002',
rewrite=False)

writes time series of radar intercomparison scores

Parameters

start_time [datetime object or array of date time objects] the time of the intercomparison
stats [dict] dictionary containing the statistics
field_name [str] The name of the field
fname [str] file name where to store the data

rad1_name, rad2_name [str] Name of the radars intercompared

rewrite [bool] if True a new file is created

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_data.write_last_state(datetime_last, fname)`
writes SwissMetNet data in format datetime, avg_value, std_value

Parameters

datetime_last [datetime object] date and time of the last state

fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_data.write_monitoring_ts(start_time, np_t, values, quantiles, datatype, fname, rewrite=False)`
writes time series of data

Parameters

start_time [datetime object or array of date time objects] the time of the monitoring

np_t [int or array of ints] the total number of points

values: float array with 3 elements of array of arrays the values at certain quantiles

quantiles: float array with 3 elements the quantiles computed

datatype [str] The data type

fname [str] file name where to store the data

rewrite [bool] if True a new file is created

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_data.write_proc_periods(start_times, end_times, fname)`
writes an output file containing start and stop times of periods to process

Parameters

start_times, end_times [datetime object] The starting and ending times of the periods

fname [str] The name of the file where to write

Returns

fname [str] the name of the file containing the content

`pyrad.io.write_data.write_quantiles(quantiles, values, fname, datatype='undefined')`
writes quantiles

Parameters

quantiles [float array] array containing the quantiles to write

values [float array] array containing the value of each quantile

fname [str] file name

datatype: str The data type

Returns

fname [str] the name of the file where data has written

```
pyrad.io.write_data.write_rhi_profile (hvec, data, nvalid_vec, labels, fname, datatype=None,  
                                         timeinfo=None, sector=None)
```

writes the values of an RHI profile in a text file

Parameters

hvec [float array] array containing the altitude in m MSL

data [list of float array] the quantities at each altitude

nvalid_vec [int array] number of valid data points used to compute the quantiles

labels [list of strings] label specifying the quantities in data

fname [str] file name where to store the data

datatype [str] the data type

timeinfo [datetime object] time of the rhi profile

sector [dict] dictionary specyng the sector limits

Returns

fname [str] the name of the file where data has been written

```
pyrad.io.write_data.write_smn (datetime_vec, value_avg_vec, value_std_vec, fname)
```

writes SwissMetNet data in format datetime,avg_value, std_value

Parameters

datetime_vec [datetime array] array containing the measurement time

value_avg_vec [float array] array containing the average value

value_std_vec [float array] array containing the standard deviation

fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

```
pyrad.io.write_data.write_sun_hits (sun_hits, fname)
```

Writes sun hits data.

Parameters

sun_hits [dict] dictionary containing the sun hits parameters

fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

```
pyrad.io.write_data.write_sun_retrieval (sun_retrieval, fname)
```

Writes sun retrieval data.

Parameters

sun_retrieval [dict] dictionary containing the sun retrieval parameters

fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

```
pyrad.io.write_data.write_trt_cell_data(traj_ID, yyyyymmddHHMM, lon, lat, ell_L, ell_S,  
                                         ell_or, area, vel_x, vel_y, det, RANKr, CG_n,  
                                         CG_p, CG, CG_percent_p, ET45, ET45m, ET15,  
                                         ET15m, VIL, maxH, maxHm, POH, RANK, Dvel_x,  
                                         Dvel_y, cell_contour, fname)
```

writes TRT cell data

Parameters

traj_ID, yyyyymmddHHMM, lon, lat, ell_L, ell_S, ell_or, area,
vel_x, vel_y, det, RANKr, CG_n, CG_p, CG, CG_percent_p, ET45,
ET45m, ET15, ET15m, VIL, maxH, maxHm, POH, RANK, Dvel_x,
Dvel_y, cell_contour: the cell parameters
fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

```
pyrad.io.write_data.write_trt_cell_lightning(cell_ID, cell_time, lon, lat, area, rank,  
                                              nflash, flash_density, fname, timefor-  
                                              mat='%Y%m%d%H%M')
```

writes the lightning data for each TRT cell

Parameters

cell_ID [array of ints] the cell ID
cell_time [array of datetime] the time step
lon, lat [array of floats] the latitude and longitude of the center of the cell
area [array of floats] the area of the cell
rank [array of floats] the rank of the cell
nflash [array of ints] the number of flashes/sources within the cell
flash_density [array of floats] the flash/source density
fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

```
pyrad.io.write_data.write_trt_cell_scores(traj_ID, flash_density_max_time,  
                                           flash_density_max_rank, nflashes_max_list,  
                                           area_flash_max_list, flash_density_max,  
                                           rank_max_time, rank_max, fname)
```

writes TRT cells scores

Parameters

traj_ID [array of ints] The ID of the cells
flash_density_max_time [array of date times] The time at which the maximum flash density
was reached for each cell
flash_density_max_rank [array of floats] The rank when the maximum flash density was
reached for each cell

nflashes_max_list [array of ints] the number of flashes when the max flash density was reached

area_flash_max_list [array of floats] The area when the max flash density was reached

flash_density_max [array of floats] The maximum flash density for each cell

rank_max_time [array of datetime] the time at wich the maximum rank of each cell was reached

rank_max [array of float] the rank when the maximum rank of each cell was reached

fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_data.write_trt_info(ids, max_rank, nscans, time_start, time_end, fname)`
writes TRT info of the thundertracking

Parameters

ids, max_rank, nscans, time_start, time_end: array the cell parameters

fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_data.write_trt_rpc(cell_ID, cell_time, lon, lat, area, rank, hmin, hmax, freq, fname, timeformat='%Y%m%d%H%M')`
writes the rimed particles column data for a TRT cell

Parameters

cell_ID [array of ints] the cell ID

cell_time [array of datetime] the time step

lon, lat [array of floats] the latitude and longitude of the center of the cell

area [array of floats] the area of the cell

rank [array of floats] the rank of the cell

hmin, hmax [array of floats] Minimum and maximum altitude of the rimed particle column

freq [array of floats] Frequency of the species constituting the rime particle column within the limits of it

fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_data.write_trt_thundertracking_data(traj_ID, scan_ordered_time, scan_time, azi, rng, yyymmd-dHHMM, lon, lat, ell_L, ell_S, ell_or, area, vel_x, vel_y, det, RANKr, CG_n, CG_p, CG, CG_percent_p, ET45, ET45m, ET15, ET15m, VIL, maxH, maxHm, POH, RANK, Dvel_x, Dvel_y, cell_contour, fname)`

writes TRT cell data of the thundertracking scan

Parameters

traj_ID, **scan_ordered_time**, **scan_time**, **azi**, **rng**, **yyyymmddHHMM**, **lon**, **lat**,
ell_L, **ell_S**, **ell_or**, **area**, **vel_x**, **vel_y**, **det**, **RANKr**, **CG_n**, **CG_p**, **CG**,
CG_percent_p, **ET45**, **ET45m**, **ET15**, **ET15m**, **VIL**, **maxH**, **maxHm**, **POH**, **RANK**,
Dvel_x, **Dvel_y**, **cell_contour**: the cell parameters
fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_data.write_ts_cum(dataset, fname)`
writes time series accumulation of data

Parameters

dataset [dict] dictionary containing the time series parameters
fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_data.write_ts_grid_data(dataset, fname)`
writes time series of data

Parameters

dataset [dict] dictionary containing the time series parameters
fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

`pyrad.io.write_data.write_ts_lightning(flashnr, time_data, time_in_flash, lat, lon, alt, dBm,
vals_list, fname, pol_vals_labels)`
writes the LMA sources data and the value of the colocated polarimetric variables

Parameters

flashnr [int] flash number
time_data [datetime object] flash source time
time_in_flash [float] seconds since start of flash
lat, **lon**, **alt** [float] latitude, longitude [deg] and altitude [m MSL] of the flash source
dBm [float] flash power
vals_list [list of arrays] List containing the data for each polarimetric variable
fname [str] the name of the file containing the content
pol_values_labels [list of strings] List containing strings identifying each polarimetric variable

Returns

fname [str] the name of the file containing the content

```
pyrad.io.write_data.write_ts_ml(dt_ml, ml_top_avg, ml_top_std, thick_avg, thick_std,  
                                nrays_valid, nrays_total, fname)
```

writes time series of melting layer data

Parameters

dt_ml [date time array] array of time steps

ml_top_avg, ml_top_std: float arrays the average and the standard deviation of the melting layer top height

thick_avg, thick_std: float arrays the average and the standard deviation of the metling layer thickness

nrays_valid, nrays_total: int arrays the number of rays where melting layer has been identified and the total number of arrays in the scan

fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

```
pyrad.io.write_data.write_ts_polar_data(dataset, fname)
```

writes time series of data

Parameters

dataset [dict] dictionary containing the time series parameters

fname [str] file name where to store the data

Returns

fname [str] the name of the file where data has written

PYRAD.IO.TIMESERIES

TimeSeries class implementation for holding timeseries data.

<i>TimeSeries</i> (desc[, timevec, timeformat, ...])	Holding timeseries data and metadata.
--	---------------------------------------

```
class pyrad.io.timeseries.TimeSeries (desc,          timevec=None,          timeformat=None,
                                     maxlen=None, datatype="")
```

Bases: `object`

Holding timeseries data and metadata.

Attributes

description [array of str] Description of the data of the time series.

time_vector [array of datetime objects]

timeformat [how to print the time (default:)] 'Date, UTC [seconds since midnight]'

dataseries [List of _dataSeries object holding the] data

Methods

<i>add_dataseries</i> (self, label, unit_name, unit)	Add a new data series to the timeseries object.
<i>add_timesample</i> (self, dt, values)	Add a new sample to the time series.
<i>plot</i> (self, fname[, ymin, ymax])	Make a figure of a time series
<i>plot_hist</i> (self, fname[, step])	Make histograms of time series
<i>write</i> (self, fname)	Write time series output

__class__

alias of `builtins.type`

__delattr__ (self, name, /)

Implement `delattr`(self, name).

__dict__ = `mappingproxy`({'__module__': 'pyrad.io.timeseries', '__doc__': "\n Holding

__dir__ (self, /)

Default `dir()` implementation.

__eq__ (self, value, /)

Return `self==value`.

__format__ (self, format_spec, /)

Default object formatter.

__ge__ (*self*, *value*, /)
Return self>=value.

__getattr__ (*self*, *name*, /)
Return getattr(self, name).

__gt__ (*self*, *value*, /)
Return self>value.

__hash__ (*self*, /)
Return hash(self).

__init__ (*self*, *desc*, *timevec*=None, *timeformat*=None, *maxlength*=None, *datatype*=")
Initialize the object.

Parameters

desc [array of str]
timevec [array of datetime]
timeformat [specifies time format]
maxlength [Maximal length of the time series]
num_el [Number of values in the time series]

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self*, *value*, /)
Return self<=value.

__lt__ (*self*, *value*, /)
Return self<value.

__module__ = 'pyrad.io.timeseries'

__ne__ (*self*, *value*, /)
Return self!=value.

__new__ (*args, **kwargs)
Create and return a new object. See help(type) for accurate signature.

__reduce__ (*self*, /)
Helper for pickle.

__reduce_ex__ (*self*, *protocol*, /)
Helper for pickle.

__repr__ (*self*, /)
Return repr(self).

__setattr__ (*self*, *name*, *value*, /)
Implement setattr(self, name, value).

__sizeof__ (*self*, /)
Size of object in memory, in bytes.

__str__ (*self*, /)
Return str(self).

__subclasshook__ ()

Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__

list of weak references to the object (if defined)

add_dataserries (*self*, *label*, *unit_name*, *unit*, *dataseries=None*, *plot=True*, *color=None*,
linestyle=None)

Add a new data series to the timeseries object. The length of the data vector must be the same as the length of the time vector.

add_timesample (*self*, *dt*, *values*)

Add a new sample to the time series.

plot (*self*, *fname*, *ymin=None*, *ymax=None*)

Make a figure of a time series

plot_hist (*self*, *fname*, *step=None*)

Make histograms of time series

write (*self*, *fname*)

Write time series output

class pyrad.io.timeseries._DataSeries (*label*, *unit_name*, *unit*, *data*, *plot=True*, *color=None*,
linestyle=None)

Bases: `object`

Hold a data vector and some meta information.

Methods

set_value(*self*, *i*, *val*)

Append value to array

__class__

alias of `builtins.type`

__delattr__ (*self*, *name*, /)

Implement `delattr`(*self*, *name*).

__dict__ = `mappingproxy({'__module__': 'pyrad.io.timeseries', '__doc__': '\n Hold a`

__dir__ (*self*, /)

Default `dir()` implementation.

__eq__ (*self*, *value*, /)

Return `self==value`.

__format__ (*self*, *format_spec*, /)

Default object formatter.

__ge__ (*self*, *value*, /)

Return `self>=value`.

__getattr__ (*self*, *name*, /)

Return `getattr`(*self*, *name*).

__gt__ (*self, value, /*)
Return self>value.

__hash__ (*self, /*)
Return hash(self).

__init__ (*self, label, unit_name, unit, data, plot=True, color=None, linestyle=None*)
Initialize the object.

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self, value, /*)
Return self<=value.

__lt__ (*self, value, /*)
Return self<value.

__module__ = 'pyrad.io.timeseries'

__ne__ (*self, value, /*)
Return self!=value.

__new__ (*args, **kwargs)
Create and return a new object. See help(type) for accurate signature.

__reduce__ (*self, /*)
Helper for pickle.

__reduce_ex__ (*self, protocol, /*)
Helper for pickle.

__repr__ (*self, /*)
Return repr(self).

__setattr__ (*self, name, value, /*)
Implement setattr(self, name, value).

__sizeof__ (*self, /*)
Size of object in memory, in bytes.

__str__ (*self, /*)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

set_value (*self, i, val*)
Append value to array

PYRAD.IO.TRAJECTORY

Trajectory class implementation for reading trajectory file. Converting to different coordinate systems.

<i>Trajectory</i> (filename[, starttime, endtime, ...])	A class for reading and handling trajectory data from a file.
<i>_Radar_Trajectory</i> (lat, lon, alt)	A class for holding the trajectory data assigned to a radar.

```
class pyrad.io.trajectory.Trajectory (filename,  starttime=None,  endtime=None,  traj-  
                                         type='plane', flashnr=0)
```

Bases: `object`

A class for reading and handling trajectory data from a file.

Attributes

filename [str] Path and name of the trajectory definition file

starttime [datetime] Start time of trajectory processing.

endtime [datetime] End time of trajectory processing.

trajtype [str]

Type of trajectory. Can be 'plane' or 'lightning'

time_vector [Array of datetime objects] Array containing the trajectory time samples

wgs84_lat_deg [Array of floats] WGS84 latitude samples in radian

wgs84_lon_deg [Array of floats] WGS84 longitude samples in radian

wgs84_alt_m [Array of floats] WGS84 altitude samples in m

nsamples [int]

Number of samples in the trajectory

_swiss_grid_done [Bool] Indicates that conversion to Swiss coordinates has been performed

swiss_chy, swiss_chx, swiss_chh [Array of floats] Swiss coordinates in m

radar_list [list] List of radars for which trajectories are going to be computed

flashnr [int] For 'lightning' only. Number of flash for which trajectory data is going to be computed. If 0 all all flashes are going to be considered.

time_in_flash [array of floats] For 'lightning' only. Time within flash (sec)

flashnr_vec [array of ints] For 'lightning' only. Flash number of each data sample

dBm [array of floats] For 'lightning' only. Lightning power (dBm)

Methods

<code>add_radar(self, radar)</code>	Add the coordinates (WGS84 longitude, latitude and non WGS84 altitude) of a radar to the radar_list.
<code>calculate_velocities(self, radar)</code>	Calculate velocities.
<code>get_end_time(self)</code>	Get time of last trajectory sample.
<code>get_samples_in_period(self[, start, end])</code>	"
<code>get_start_time(self)</code>	Get time of first trajectory sample.

`__class__`

alias of `builtins.type`

`__delattr__(self, name, /)`

Implement `delattr(self, name)`.

`__dict__ = mappingproxy({'__module__': 'pyrad.io.trajectory', '__doc__': "\n A class`

`__dir__(self, /)`

Default `dir()` implementation.

`__eq__(self, value, /)`

Return `self==value`.

`__format__(self, format_spec, /)`

Default object formatter.

`__ge__(self, value, /)`

Return `self>=value`.

`__getattr__(self, name, /)`

Return `getattr(self, name)`.

`__gt__(self, value, /)`

Return `self>value`.

`__hash__(self, /)`

Return `hash(self)`.

`__init__(self, filename, starttime=None, endtime=None, trajtype='plane', flashnr=0)`

Initialize the object.

Parameters

filename [str] Filename containing the trajectory samples.

starttime [datetime] Start time of trajectory processing. If not given, use the time of the first trajectory sample.

endtime [datetime] End time of trajectory processing. If not given, use the time of the last trajectory sample.

trajtype [str] type of trajectory. Can be plane or lightning

flashnr [int] If type of trajectory is lightning, the flash number to check the trajectory. 0 means all flash numbers included

`__init_subclass__()`

This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self*, *value*, /)
Return self<=value.

__lt__ (*self*, *value*, /)
Return self<value.

__module__ = 'pyrad.io.trajectory'

__ne__ (*self*, *value*, /)
Return self!=value.

__new__ (**args*, ***kwargs*)
Create and return a new object. See help(type) for accurate signature.

__reduce__ (*self*, /)
Helper for pickle.

__reduce_ex__ (*self*, *protocol*, /)
Helper for pickle.

__repr__ (*self*, /)
Return repr(self).

__setattr__ (*self*, *name*, *value*, /)
Implement setattr(self, name, value).

__sizeof__ (*self*, /)
Size of object in memory, in bytes.

__str__ (*self*, /)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

_convert_traj_to_swissgrid (*self*)
Convert trajectory samples from WGS84 to Swiss CH1903 coordinates

_get_total_seconds (*self*, *x*)
Return total seconds of timedelta object

_read_traj (*self*)
Read trajectory from file

_read_traj_lightning (*self*, *flashnr=0*)
Read trajectory from lightning file

Parameters

flashnr [int] the flash number to keep. If 0 data from all flashes will be kept

_read_traj_trt (*self*)
Read trajectory from TRT file

add_radar (*self*, *radar*)
Add the coordinates (WGS84 longitude, latitude and non WGS84 altitude) of a radar to the radar_list.

Parameters

radar [pyart radar object] containing the radar coordinates

calculate_velocities (*self*, *radar*)
Calculate velocities.

get_end_time (*self*)
Get time of last trajectory sample.

get_samples_in_period (*self*, *start=None*, *end=None*)
” Get indices of samples of the trajectory within given time period.

get_start_time (*self*)
Get time of first trajectory sample.

class pyrad.io.trajectory._Radar_Trajectory (*lat*, *lon*, *alt*)
Bases: `object`

A class for holding the trajectory data assigned to a radar.

Attributes

latitude [float] WGS84 radar latitude [deg]

longitude [float] WGS84 radar longitude [deg]

altitude [float] radar altitude [m] (non WGS84)

ch_y, ch_x, ch_alt [float] radar coordinates in swiss CH1903 coordinates

elevation_vec [float list] Elevation values of the trajectory samples

azimuth_vec [float list] Azimuth values of the trajectory samples

range_vec [float list] Range values of the trajectory samples

v_abs, v_r, v_el, v_az [array-like] Velocity vectors of the absolute [m/s], radial [m/s], elevation [deg/s] and azimuth [deg/s] velocities

Methods

<code>assign_trajectory(self, el, az, rr)</code>	Assign a trajectory to the radar in polar radar coordinates.
<code>assign_velocity_vecs(self, v_abs, v_r, v_el, ...)</code>	Assign velocity vectors to the radar.
<code>convert_radpos_to_swissgrid(self)</code>	Convert the radar location (in WGS84 coordinates) to swiss CH1903 coordinates.
<code>location_is_equal(self, lat, lon, alt)</code>	Check if the given coordinates are the same.

__class__
alias of `builtins.type`

__delattr__ (*self*, *name*, /)
Implement `delattr(self, name)`.

__dict__ = `mappingproxy({'__module__': 'pyrad.io.trajectory', '__doc__': '\n A class`

__dir__ (*self*, /)
Default `dir()` implementation.

__eq__ (*self*, *value*, /)
Return `self==value`.

__format__ (*self, format_spec, /*)
Default object formatter.

__ge__ (*self, value, /*)
Return self>=value.

__getattr__ (*self, name, /*)
Return getattr(self, name).

__gt__ (*self, value, /*)
Return self>value.

__hash__ (*self, /*)
Return hash(self).

__init__ (*self, lat, lon, alt*)
Initalize the object.

Parameters

lat, lon , alt [radar location coordinates]

nsamps [number of samples]

__init_subclass__ ()
This method is called when a class is subclassed.

The default implementation does nothing. It may be overridden to extend subclasses.

__le__ (*self, value, /*)
Return self<=value.

__lt__ (*self, value, /*)
Return self<value.

__module__ = 'pyrad.io.trajectory'

__ne__ (*self, value, /*)
Return self!=value.

__new__ (**args, **kwargs*)
Create and return a new object. See help(type) for accurate signature.

__reduce__ (*self, /*)
Helper for pickle.

__reduce_ex__ (*self, protocol, /*)
Helper for pickle.

__repr__ (*self, /*)
Return repr(self).

__setattr__ (*self, name, value, /*)
Implement setattr(self, name, value).

__sizeof__ (*self, /*)
Size of object in memory, in bytes.

__str__ (*self, /*)
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by `abc.ABCMeta.__subclasscheck__()`. It should return `True`, `False` or `NotImplemented`. If it returns `NotImplemented`, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

`__weakref__`

list of weak references to the object (if defined)

`assign_trajectory` (*self*, *el*, *az*, *rr*)

Assign a trajectory to the radar in polar radar coordinates.

Parameters

el*, *az*, *rr [array-like] elevation, azimuth and range vector

`assign_velocity_vecs` (*self*, *v_abs*, *v_r*, *v_el*, *v_az*)

Assign velocity vectors to the radar.

`convert_radpos_to_swissgrid` (*self*)

Convert the radar location (in WGS84 coordinates) to swiss CH1903 coordinates.

`location_is_equal` (*self*, *lat*, *lon*, *alt*)

Check if the given coordinates are the same.

Parameters

lat*, *lon* , *alt [radar location coordinates]

PYRAD.GRAPH.PLOTS_AUX

Auxiliary plotting functions

<i>generate_complex_range_Doppler_title</i> (<i>radar</i> , ...)	creates the fixed range plot title
<i>generate_angle_Doppler_title</i> (<i>radar</i> , <i>field</i> , ...)	creates the angle-Doppler plot title
<i>generate_complex_Doppler_title</i> (<i>radar</i> , <i>field</i> , ...)	creates the fixed range plot title
<i>generate_fixed_rng_span_title</i> (<i>radar</i> , <i>field</i> , <i>stat</i>)	creates the fixed range plot title
<i>generate_fixed_rng_title</i> (<i>radar</i> , <i>field</i> , <i>fixed_rng</i>)	creates the fixed range plot title
<i>get_colobar_label</i> (<i>field_dict</i> , <i>field_name</i>)	creates the colorbar label using field metadata
<i>get_field_name</i> (<i>field_dict</i> , <i>field</i>)	Return a nice field name for a particular field
<i>get_norm</i> (<i>field_name</i>)	Computes the normalization of the colormap, and gets the ticks and labels of the colorbar from the metadata of the field.

`pyrad.graph.plots_aux.generate_angle_Doppler_title`(*radar*, *field*, *ang*, *ind_rng*,
along_azi=*True*, *date-*
time_format=*None*)

creates the angle-Doppler plot title

Parameters

radar [radar] The radar object

field [str] name of the field

ang [float] The fixed angle

ind_rng [int] the index of the fixed range

along_azi [bool] If true the plot is performed along azimuth, otherwise it is performed along elevation

datetime_forat [str or None] The date time format to use

Returns

titl [str] The plot title

`pyrad.graph.plots_aux.generate_complex_Doppler_title`(*radar*, *field*, *ray*, *rng*, *date-*
time_format=*None*)

creates the fixed range plot title

Parameters

radar [radar] The radar object
field [str] name of the field
stat [str] The statistic computed
datetime_forat [str or None] The date time format to use

Returns

titl [str] The plot title

`pyrad.graph.plots_aux.generate_complex_range_Doppler_title(radar, field, ray, date-
time_format=None)`
creates the fixed range plot title

Parameters

radar [radar] The radar object
field [str] name of the field
stat [str] The statistic computed
datetime_forat [str or None] The date time format to use

Returns

titl [str] The plot title

`pyrad.graph.plots_aux.generate_fixed_rng_span_title(radar, field, stat, date-
time_format=None)`
creates the fixed range plot title

Parameters

radar [radar] The radar object
field [str] name of the field
stat [str] The statistic computed
datetime_forat [str or None] The date time format to use

Returns

titl [str] The plot title

`pyrad.graph.plots_aux.generate_fixed_rng_title(radar, field, fixed_rng, date-
time_format=None)`
creates the fixed range plot title

Parameters

radar [radar] The radar object
field [str] name of the field
fixed_rng [float] The fixed range [m]
datetime_forat [str or None] The date time format to use

Returns

titl [str] The plot title

`pyrad.graph.plots_aux.get_colobar_label(field_dict, field_name)`
creates the colorbar label using field metadata

Parameters

field_dict [dict] dictionary containing field metadata

field_name [str] name of the field

Returns

label [str] colorbar label

`pyrad.graph.plots_aux.get_field_name(field_dict, field)`

Return a nice field name for a particular field

Parameters

field_dict [dict] dictionary containing field metadata

field [str] name of the field

Returns

field_name [str] the field name

`pyrad.graph.plots_aux.get_norm(field_name)`

Computes the normalization of the colormap, and gets the ticks and labels of the colorbar from the metadata of the field. Returns None if the required parameters are not present in the metadata

Parameters

field_name [str] name of the field

Returns

norm [list] the colormap index

ticks [list] the list of ticks in the colorbar

labels [list] the list of labels corresponding to each tick

PYRAD.GRAPH.PLOTS

Functions to plot Pyrad datasets

<i>plot_pos</i> (lat, lon, alt, fname_list[, ax, ...])	plots a trajectory on a Cartesian surface
<i>plot_pos_map</i> (lat, lon, alt, fname_list[, ...])	plots a trajectory on a map
<i>plot_density</i> (hist_obj, hist_type, ...[, ...])	density plot (angle-values representation)
<i>plot_scatter</i> (bin_edges1, bin_edges2, ...[, ...])	2D histogram
<i>plot_quantiles</i> (quant, value, fname_list[, ...])	plots quantiles
<i>plot_histogram</i> (bin_edges, values, fname_list)	computes and plots histogram
<i>plot_histogram2</i> (bin_centers, hist, fname_list)	plots histogram
<i>plot_antenna_pattern</i> (antpattern, fname_list)	plots an antenna pattern
<i>plot_selfconsistency</i> (zdrkdp_table, fname_list)	plots a ZDR-KDP/ZH selfconsistency in rain relation
<i>plot_selfconsistency_instrument</i> (zdr, kdp, ...)	plots the ZDR-KDP/ZH relationship obtained by an instrument.
<i>plot_selfconsistency_instrument2</i> (zdr, kdp, ...)	plots the ZDR-KDP/ZH relationship obtained by an instrument.
<i>plot_scatter_comp</i> (value1, value2, fname_list)	plots the scatter between two time series
<i>plot_sun_hits</i> (field, field_name, fname_list, ...)	plots the sun hits
<i>_plot_time_range</i> (rad_time, rad_range, ...[, ...])	plots a time-range plot

`pyrad.graph.plots._plot_time_range` (*rad_time*, *rad_range*, *rad_data*, *field_name*, *fname_list*, *titl*=*'Time-Range plot'*, *xlabel*=*'time (s from start time)'*, *ylabel*=*'range (Km)'*, *clabel*=*None*, *vmin*=*None*, *vmax*=*None*, *figsize*=*[10, 8]*, *save_fig*=*True*, *dpi*=*72*)

plots a time-range plot

Parameters

- rad_time** [1D array] array containing the x dimension (typically time)
- rad_range** [1D array] array containing the y dimension (typically range)
- rad_data** [2D array] array containing the data to plot
- field_name** [str or None] field name. Used to define plot characteristics
- fname_list** [list of str] list of names of the files where to store the plot
- titl** [str] Plot title
- xlabel, ylabel** [str] x- and y-axis labels
- clabel** [str or None] colorbar label

vmin, vmax [float] min and max values of the color bar

figsize [list] figure size [xsize, ysize]

save_fig [bool] If true the figure is saved in files `fname_list`. Otherwise the fig and ax is returned

dpi [int] dpi

Returns

fname_list [list of str] list of names of the created plots or

fig, ax [object] handles to fig and ax objects

`pyrad.graph.plots.plot_antenna_pattern` (*antpattern, fname_list, labelx='Angle [Deg]', linear=False, twoway=False, title='Antenna Pattern', ymin=None, ymax=None, dpi=72*)

plots an antenna pattern

Parameters

antpattern [dict] dictionary with the angle and the attenuation

value [float array] values of the time series

fname_list [list of str] list of names of the files where to store the plot

labelx [str] The label of the X axis

linear [boolean] if true data is in linear units

linear [boolean] if true data represents the two way attenuation

titl [str] The figure title

ymin, ymax: float Lower/Upper limit of y axis

dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plots.plot_density` (*hist_obj, hist_type, field_name, ind_sweep, prdcfg, fname_list, quantiles=[25.0, 50.0, 75.0], ref_value=0.0, vmin=None, vmax=None*)

density plot (angle-values representation)

Parameters

hist_obj [histogram object] object containing the histogram data to plot

hist_type [str] type of histogram (instantaneous data or cumulative)

field_name [str] name of the radar field to plot

ind_sweep [int] sweep index to plot

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

quantiles [array] the quantile lines to plot

ref_value [float] the reference value

vmin, vmax [float] Minim and maximum extend of the vertical axis

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plots.plot_histogram(bin_edges, values, fname_list, labelx='bins', labely='Number of Samples', titl='histogram', dpi=72)`
computes and plots histogram

Parameters

bin_edges [array] histogram bin edges

values [array] data values

fname_list [list of str] list of names of the files where to store the plot

labelx [str] The label of the X axis

labely [str] The label of the Y axis

titl [str] The figure title

dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plots.plot_histogram2(bin_centers, hist, fname_list, width=None, labelx='bins', labely='Number of Samples', titl='histogram', dpi=72, ax=None, fig=None, save_fig=True, color=None, alpha=None, invert_xaxis=False)`
plots histogram

Parameters

bin_centers [array] histogram bin centers

hist [array] values for each bin

fname_list [list of str] list of names of the files where to store the plot

width [scalar or array-like] the width(s) of the bars. If None it is going to be estimated from the distances between centers

labelx [str] The label of the X axis

labely [str] The label of the Y axis

titl [str] The figure title

dpi [int] dots per inch

fig [Figure] Figure to add the colorbar to. If none a new figure will be created

ax [Axis] Axis to plot on. if fig is None a new axis will be created

save_fig [bool] if true save the figure. If false it does not close the plot and returns the handle to the figure

color [str] color of the bars

alpha [float] parameter controlling the transparency

invert_xaxis [bool] If true inverts the x axis

Returns

fname_list or fig, ax: list of str list of names of the created plots

```
pyrad.graph.plots.plot_pos(lat, lon, alt, fname_list, ax=None, fig=None, save_fig=True,
                           sort_altitude='No', dpi=72, alpha=1.0, cb_label='height [m MSL]',
                           titl='Position', xlabel='Lon [Deg]', ylabel='Lat [Deg]', limits=None,
                           vmin=None, vmax=None)
```

plots a trajectory on a Cartesian surface

Parameters

lat, lon, alt [float array] Points coordinates

fname_list [list of str] list of names of the files where to store the plot

fig [Figure] Figure to add the colorbar to. If none a new figure will be created

ax [Axis] Axis to plot on. if fig is None a new axis will be created

save_fig [bool] if true save the figure if false it does not close the plot and returns the handle to the figure

sort_altitude [str] String indicating whether to sort the altitude data. Can be 'No', 'Lowest_on_top' or 'Highest_on_top'

dpi [int] Pixel density

alpha [float] Transparency

cb_label [str] Color bar label

titl [str] Plot title

xlabel, ylabel [str] The labels of the X and Y axis

limits [tuple or None] The limits of the field to plot

vmin, vmax [float] The limits of the color scale

Returns

fname_list [list of str or]

fig, ax [tuple] list of names of the saved plots or handle of the figure and axes

```
pyrad.graph.plots.plot_pos_map(lat, lon, alt, fname_list, ax=None, fig=None, save_fig=True,
                               sort_altitude='No', dpi=72, alpha=1.0, cb_label='height
                               [m MSL]', titl='Position', xlabel='Lon [Deg]', ylabel='Lat
                               [Deg]', limits=None, vmin=None, vmax=None, lon_step=0.3,
                               lat_step=0.1, background_zoom=8)
```

plots a trajectory on a map

Parameters

lat, lon, alt [float array] Points coordinates

fname_list [list of str] list of names of the files where to store the plot

fig [Figure] Figure to add the colorbar to. If none a new figure will be created

ax [Axis] Axis to plot on. if fig is None a new axis will be created

save_fig [bool] if true save the figure if false it does not close the plot and returns the handle to the figure

sort_altitude [str] String indicating whether to sort the altitude data. Can be 'No', 'Lowest_on_top' or 'Highest_on_top'

dpi [int] Pixel density

alpha [float] Transparency

cb_label [str] Color bar label

titl [str] Plot title

xlabel, ylabel [str] The labels of the X and Y axis

limits [tuple or None] The limits of the field to plot

vmin, vmax [float] The limits of the color scale

lon_step, lat_step [float] The step interval of the latitude, longitude lines to plot

background_zoom [int] The zoom of the background image. A higher number will give more level of detail at the expense of speed.

Returns

fname_list [list of str or]

fig, ax [tuple] list of names of the saved plots or handle of the figure and axes

`pyrad.graph.plots.plot_quantiles` (*quant, value, fname_list, labelx='quantile', labely='value', titl='quantile', vmin=None, vmax=None, dpi=72*)

plots quantiles

Parameters

quant [array] quantiles to be plotted

value [array] values of each quantile

fname_list [list of str] list of names of the files where to store the plot

labelx [str] The label of the X axis

labely [str] The label of the Y axis

titl [str] The figure title

vmin, vmax: float Lower/Upper limit of data values

dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plots.plot_scatter` (*bin_edges1, bin_edges2, hist_2d, field_name1, field_name2, fname_list, prdcfg, metadata=None, lin_regr=None, lin_regr_slope1=None, rad1_name='RADAR001', rad2_name='RADAR002'*)

2D histogram

Parameters

bin_edges1, bin_edges2 [float array2] the bins of each field

hist_2d [ndarray 2D] the 2D histogram

field_name1, field_name2 [str] the names of each field

fname_list [list of str] list of names of the files where to store the plot

prdcfg [dict] product configuration dictionary

metadata [str] a string with metadata to write in the plot

lin_regr [tuple with 2 values] the coefficients for a linear regression

lin_regr_slope1 [float] the intercept point of a linear regression of slope 1

rad1_name, rad2_name [str] name of the radars which data is used

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plots.plot_scatter_comp(value1, value2, fname_list, labelx='Sensor 1',  
                                     labely='Sensor 2', titl='Scatter', axis=None,  
                                     metadata=None, dpi=72, ax=None, fig=None,  
                                     save_fig=True, point_format='bx')
```

plots the scatter between two time series

Parameters

value1 [float array] values of the first time series

value2 [float array] values of the second time series

fname_list [list of str] list of names of the files where to store the plot

labelx [str] The label of the X axis

labely [str] The label of the Y axis

titl [str] The figure title

axis [str] type of axis

metadata [string] a string containing metadata

dpi [int] dots per inch

fig [Figure] Figure to add the colorbar to. If none a new figure will be created

ax [Axis] Axis to plot on. if fig is None a new axis will be created

save_fig [bool] if true save the figure if false it does not close the plot and returns the handle to the figure

point_format [str] format of the scatter point

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plots.plot_selfconsistency(zdrkdp_table, fname_list, labelx='ZDR [dB]',  
                                        labely='KDP/Zh [(deg*m3)/(km*mm6)]', ti-  
                                        tle='Selfconsistency in rain', ymin=None,  
                                        ymax=None, dpi=72, save_fig=True, ax=None,  
                                        fig=None)
```

plots a ZDR-KDP/ZH selfconsistency in rain relation

Parameters

antpattern [dict] dictionary with the angle and the attenuation

value [float array] values of the time series

fname_list [list of str] list of names of the files where to store the plot

labelx [str] The label of the X axis

linear [boolean] if true data is in linear units

linear [boolean] if true data represents the two way attenuation

titl [str] The figure title

ymin, ymax: float Lower/Upper limit of y axis

dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plots.plot_selfconsistency_instrument(zdr, kdp, zh, fname_list,
                                                    bins_zdr_step=0.05,
                                                    bins_zdr_min=0.0,
                                                    bins_zdr_max=6.0,
                                                    bins_kdpzh_step=0.1,
                                                    bins_kdpzh_min=-2.0,
                                                    bins_kdpzh_max=20.0, normalize=True,
                                                    vmin=0.0, vmax=0.01,
                                                    parametrization='None',
                                                    zdr_kdpzh_dict=None,
                                                    retrieve_relation=True,
                                                    plot_theoretical=True, dpi=72)
```

plots the ZDR-KDP/ZH relationship obtained by an instrument. The theoretical curve and the retrieved curve

Parameters

zdr, kdp, zh [1D ndarray] The valid values of ZDR [dB], KDP [deg/km] and Zh [mm6/m3] collected by the instrument

fname_list [list of str] list of names of the files where to store the plot

bins_zdr_step [float] The step of the ZDR axis of the histogram [dB]

bins_zdr_min, bins_zdr_max [float] The limits of the ZDR axis of the histogram (bins center) [dB]

bins_kdpzh_step [float] The step of the $1e5 * KDP^a / ZH^b$ axis of the histogram [(deg*m3)/(km*mm6)]

bins_kdpzh_min, bins_kdpzh_max [float] The limits of the $1e5 * KDP^a / ZH^b$ axis of the histogram (bins center) [(deg*m3)/(km*mm6)]

normalize [Bool] If True the occurrence density of ZH/KDP for each ZDR bin is going to be represented. Otherwise it will show the number of gates at each bin

vmin, vmax [float] min and max values of the colorbar

parametrization [str] The type of parametrization for the self-consistency curves. Can be 'None', 'Gourley', 'Wolfensberger', 'Louf', 'Gorgucci' or 'Vaccarono'. 'None' will use tables contained in zdr_kdpzh_dict. The parametrized curves are obtained from literature except for Wolfensberger that was derived from disdrometer data obtained by MeteoSwiss and EPFL. All parametrizations are valid for C-band only except that of Gourley.

zdr_kdpzh_dict [dict] dictionary containing a look up table relating ZDR with KDP/Zh for different elevations and the frequency band of the radar

retrieve_relation [boolean] if true a zdr-kdp/zh relationship is retrieved from the data

plot_theoretical [bool] if true the theoretical relationship is retrieved

dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plots.plot_selfconsistency_instrument2(zdr, kdp, zh, fname_list,
                                                    bins_zh_step=0.5, bins_zh_min=-
                                                    30.0, bins_zh_max=80.0, normal-
                                                    ize=True, vmin=0.0, vmax=0.01,
                                                    parametrization='None',
                                                    zdr_kdpzh_dict=None, dpi=72)
```

plots the ZDR-KDP/ZH relationship obtained by an instrument. The theoretical curve and the retrieved curve

Parameters

zdr, kdp, zh [1D ndarray] The valid values of ZDR [dB], KDP [deg/km] and Zh [dBZ] collected by the instrument

fname_list [list of str] list of names of the files where to store the plot

bins_zh_step [float] The step of the ZH of the histogram [dB]

bins_zh_min, bins_zh_max [float] The limits of the ZH of the histograms (bins center) [dBZ]

normalize [Bool] If True the occurrence density of ZH/KDP for each ZDR bin is going to be represented. Otherwise it will show the number of gates at each bin

vmin, vmax [float] min and max values of the colorbar

parametrization [str] The type of parametrization for the self-consistency curves. Can be 'None', 'Gourley', 'Wolfensberger', 'Louf', 'Gorgucci' or 'Vaccarono'. 'None' will use tables contained in `zdr_kdpzh_dict`. The parametrized curves are obtained from literature except for Wolfensberger that was derived from disdrometer data obtained by MeteoSwiss and EPFL. All parametrizations are valid for C-band only except that of Gourley.

zdr_kdpzh_dict [dict] dictionary containing a look up table relating ZDR with KDP/Zh for different elevations and the frequency band of the radar

dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plots.plot_sun_hits(field, field_name, fname_list, prdcfg)
```

plots the sun hits

Parameters

radar [Radar object] object containing the radar data to plot

field_name [str] name of the radar field to plot

altitude [float] the altitude [m MSL] to be plotted

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

Returns

fname_list [list of str] list of names of the created plots

PYRAD.GRAPH.PLOTS_VOL

Functions to plot radar volume data

<i>plot_ray</i> (radar, field_name, ind_ray, prdcfg, ...)	plots a ray
<i>plot_ppi</i> (radar, field_name, ind_el, prdcfg, ...)	plots a PPI
<i>plot_ppi_map</i> (radar, field_name, ind_el, ...)	plots a PPI on a geographic map
<i>plot_rhi</i> (radar, field_name, ind_az, prdcfg, ...)	plots an RHI
<i>plot_bscope</i> (radar, field_name, ind_sweep, ...)	plots a B-Scope (angle-range representation)
<i>plot_time_range</i> (radar, field_name, ...[, ...])	plots a time-range plot
<i>plot_fixed_rng</i> (radar, field_name, prdcfg, ...)	plots a fixed range plot
<i>plot_fixed_rng_span</i> (radar, field_name, ...)	plots a fixed range plot
<i>plot_cappi</i> (radar, field_name, altitude, ...)	plots a Constant Altitude Plan Position Indicator CAPPI
<i>plot_traj</i> (rng_traj, azi_traj, ele_traj, ...)	plots a trajectory on a Cartesian surface
<i>plot_rhi_contour</i> (radar, field_name, ind_az, ...)	plots contour data on an RHI
<i>plot_ppi_contour</i> (radar, field_name, ind_el, ...)	plots contour data on a PPI
<i>plot_roi_contour</i> (roi_dict, prdcfg, fname_list)	plots the contour of a region of interest on a map
<i>plot_rhi_profile</i> (data_list, hvec, fname_list)	plots an RHI profile
<i>plot_along_coord</i> (xval_list, yval_list, ...)	plots data along a certain radar coordinate
<i>plot_field_coverage</i> (xval_list, yval_list, ...)	plots a time series

`pyrad.graph.plots_vol.plot_along_coord(xval_list, yval_list, fname_list, labelx='coord', labely='Value', labels=None, title='Plot along coordinate', colors=None, linestyle=None, ymin=None, ymax=None, dpi=72)`

plots data along a certain radar coordinate

Parameters

- xval_list** [list of float arrays] the x values, range, azimuth or elevation
- yval_list** [list of float arrays] the y values. Parameter to plot
- fname_list** [list of str] list of names of the files where to store the plot
- labelx** [str] The label of the X axis
- labely** [str] The label of the Y axis
- labels** [array of str] The label of the legend
- title** [str] The figure title
- colors** [array of str] Specifies the colors of each line
- linestyles** [array of str] Specifies the line style of each line
- ymin, ymax: float** Lower/Upper limit of y axis

dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plots_vol.plot_bscope(radar, field_name, ind_sweep, prdcfg, fname_list,  
                                   vmin=None, vmax=None, ray_dim='ang',  
                                   xaxis_rng=True)
```

plots a B-Scope (angle-range representation)

Parameters

radar [Radar object] object containing the radar data to plot

field_name [str] name of the radar field to plot

ind_sweep [int] sweep index to plot

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

vmin, vmax [float] Min and max values of the colorbar

ray_dim [str] the ray dimension. Can be 'ang' or 'time'

xaxis [bool] if true the range will be in the x-axis. Otherwise it will be in the y-axis.

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plots_vol.plot_cappi(radar, field_name, altitude, prdcfg, fname_list,  
                                 beamwidth=1.0, beam_spacing=1.0, save_fig=True)
```

plots a Constant Altitude Plan Position Indicator CAPPI

Parameters

radar [Radar object] object containing the radar data to plot

field_name [str] name of the radar field to plot

altitude [float] the altitude [m MSL] to be plotted

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

beamwidth [float] The radar beamwidth

beam_spacing [float] the ray angle resolution

save_fig [bool] if true save the figure. If false it does not close the plot and returns the handle to the figure

Returns

fname_list [list of str or]

fig, ax [tuple] list of names of the saved plots or handle of the figure an axes

```
pyrad.graph.plots_vol.plot_field_coverage(xval_list, yval_list, fname_list, labelx='Azimuth  
(deg)', labely='Range extension [m]', la-  
bels=None, title='Field coverage', ymin=None,  
ymax=None, xmeanval=None, ymeanval=None,  
labelmeanval=None, dpi=72)
```

plots a time series

Parameters

xval_list [list of float arrays] the x values, azimuth
yval_list [list of float arrays] the y values. Range extension
fname_list [list of str] list of names of the files where to store the plot
labelx [str] The label of the X axis
labely [str] The label of the Y axis
labels [array of str] The label of the legend
title [str] The figure title
ymin, ymax [float] Lower/Upper limit of y axis
xmeanval, ymeanval [float array] the x and y values of a mean along elevation
labelmeanval [str] the label of the mean
dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plots_vol.plot_fixed_rng(radar, field_name, prdcfg, fname_list, azi_res=None, ele_res=None, ang_tol=1.0, vmin=None, vmax=None)`
plots a fixed range plot

Parameters

radar [radar object] The radar object containing the fixed range data
field_name [str] The name of the field to plot
prdcfg [dict] dictionary containing the product configuration
fname_list [list of str] list of names of the files where to store the plot
azi_res, ele_res [float] The nominal azimuth and elevation angle resolution [deg]
ang_tol [float] The tolerance between the nominal and the actual radar angle
vmin, vmax [float] Min and Max values of the color scale. If None it is going to be taken from the Py-ART config files

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plots_vol.plot_fixed_rng_span(radar, field_name, prdcfg, fname_list, azi_res=None, ele_res=None, ang_tol=1.0, stat='max')`
plots a fixed range plot

Parameters

radar [radar object] The radar object containing the fixed range data
field_name [str] The name of the field to plot
prdcfg [dict] dictionary containing the product configuration
fname_list [list of str] list of names of the files where to store the plot
azi_res, ele_res [float] The nominal azimuth and elevation angle resolution [deg]

ang_tol [float] The tolerance between the nominal and the actual radar angle

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plots_vol.plot_ppi(radar, field_name, ind_el, prdcfg, fname_list, plot_type='PPI', titl=None, vmin=None, vmax=None, step=None, quantiles=None, save_fig=True)`

plots a PPI

Parameters

radar [Radar object] object containing the radar data to plot

field_name [str] name of the radar field to plot

ind_el [int] sweep index to plot

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

plot_type [str] type of plot (PPI, QUANTILES or HISTOGRAM)

titl [str] Plot title

vmin, vmax [float] The minimum and maximum value. If None the scale is going to be obtained from the Py-ART config file.

step [float] step for histogram plotting

quantiles [float array] quantiles to plot

save_fig [bool] if true save the figure. If false it does not close the plot and returns the handle to the figure

Returns

fname_list [list of str or]

fig, ax [tuple] list of names of the saved plots or handle of the figure an axes

`pyrad.graph.plots_vol.plot_ppi_contour(radar, field_name, ind_el, prdcfg, fname_list, contour_values=None, linewidths=1.5, ax=None, fig=None, save_fig=True)`

plots contour data on a PPI

Parameters

radar [Radar object] object containing the radar data to plot

field_name [str] name of the radar field to plot

ind_el [int] sweep index to plot

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

contour_values [float array] list of contours to plot

linewidths [float] width of the contour lines

fig [Figure] Figure to add the colorbar to. If none a new figure will be created

ax [Axis] Axis to plot on. if fig is None a new axis will be created

save_fig [bool] if true save the figure if false it does not close the plot and returns the handle to the figure

Returns

fname_list [list of str or]

fig, ax [tuple] list of names of the saved plots or handle of the figure an axes

```
pyrad.graph.plots_vol.plot_ppi_map(radar, field_name, ind_el, prdcfg, fname_list,  
                                     save_fig=True)
```

plots a PPI on a geographic map

Parameters

radar [Radar object] object containing the radar data to plot

field_name [str] name of the radar field to plot

ind_el [int] sweep index to plot

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

save_fig [bool] if true save the figure. If false it does not close the plot and returns the handle to the figure

Returns

fname_list [list of str or]

fig, ax, display [tuple] list of names of the saved plots or handle of the figure an axes

```
pyrad.graph.plots_vol.plot_ray(radar, field_name, ind_ray, prdcfg, fname_list, titl=None,  
                                vmin=None, vmax=None, save_fig=True)
```

plots a ray

Parameters

radar [Radar object] object containing the radar data to plot

field_name [str] name of the radar field to plot

ind_ray [int] ray index to plot

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

plot_type [str] type of plot (PPI, QUANTILES or HISTOGRAM)

titl [str] Plot title

vmin, vmax [float] min and max values of the y axis

save_fig [bool] if true save the figure. If false it does not close the plot and returns the handle to the figure

Returns

fname_list [list of str or]

fig, ax [tuple] list of names of the saved plots or handle of the figure an axes

```
pyrad.graph.plots_vol.plot_rhi(radar, field_name, ind_az, prdcfg, fname_list, plot_type='RHI',  
                                titl=None, vmin=None, vmax=None, step=None, quan-  
                                tiles=None, save_fig=True)
```

plots an RHI

Parameters

radar [Radar object] object containing the radar data to plot

field_name [str] name of the radar field to plot

ind_az [int] sweep index to plot

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

plot_type [str] type of plot (PPI, QUANTILES or HISTOGRAM)

titl [str] Plot title

vmin, vmax [float] The minimum and maximum value. If None the scale is going to be obtained from the Py-ART config file.

step [float] step for histogram plotting

quantiles [float array] quantiles to plot

save_fig [bool] if true save the figure. If false it does not close the plot and returns the handle to the figure

Returns

fname_list [list of str or]

fig, ax [tuple] list of names of the saved plots or handle of the figure an axes

```
pyrad.graph.plots_vol.plot_rhi_contour(radar, field_name, ind_az, prdcfg, fname_list,  
contour_values=None, linewidths=1.5, ax=None,  
fig=None, save_fig=True)
```

plots contour data on an RHI

Parameters

radar [Radar object] object containing the radar data to plot

field_name [str] name of the radar field to plot

ind_az [int] sweep index to plot

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

contour_values [float array] list of contours to plot

linewidths [float] width of the contour lines

fig [Figure] Figure to add the colorbar to. If none a new figure will be created

ax [Axis] Axis to plot on. if fig is None a new axis will be created

save_fig [bool] if true save the figure if false it does not close the plot and returns the handle to the figure

Returns

fname_list [list of str or]

fig, ax [tuple] list of names of the saved plots or handle of the figure an axes

```
pyrad.graph.plots_vol.plot_rhi_profile(data_list, hvec, fname_list, labelx='Value', labely='Height (m MSL)', labels=['Mean'], title='RHI profile', colors=None, linestyle=None, vmin=None, vmax=None, hmin=None, hmax=None, dpi=72)
```

plots an RHI profile

Parameters

data_list [list of float array] values of the profile
hvec [float array] height points of the profile
fname_list [list of str] list of names of the files where to store the plot
labelx [str] The label of the X axis
labely [str] The label of the Y axis
labels [array of str] The label of the legend
title [str] The figure title
colors [array of str] Specifies the colors of each line
linestyle [array of str] Specifies the line style of each line
vmin, vmax: float Lower/Upper limit of data values
hmin, hmax: float Lower/Upper limit of altitude
dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plots_vol.plot_roi_contour(roi_dict, prdcfg, fname_list, plot_center=True, xlabel='Lon [Deg]', ylabel='Lat [Deg]', title='TRT cell position', ax=None, fig=None, save_fig=True)
```

plots the contour of a region of interest on a map

Parameters

roi_dict [dict] dictionary containing lon_roi, lat_roi, the points defining the contour
prdcfg [dict] dictionary containing the product configuration
fname_list [list of str] list of names of the files where to store the plot
plot_center [bool] If True a marked with the center of the roi is plotted
fig [Figure] Figure to add the colorbar to. If none a new figure will be created
ax [Axis] Axis to plot on. if fig is None a new axis will be created
save_fig [bool] if true save the figure if false it does not close the plot and returns the handle to the figure

Returns

fname_list [list of str or]
fig, ax [tuple] list of names of the saved plots or handle of the figure an axes

```
pyrad.graph.plots_vol.plot_time_range(radar, field_name, ind_sweep, prdcfg, fname_list, vmin=None, vmax=None, ylabel='range (Km)')
```

plots a time-range plot

Parameters

radar [Radar object] object containing the radar data to plot
field_name [str] name of the radar field to plot
ind_sweep [int] sweep index to plot
prdcfg [dict] dictionary containing the product configuration
fname_list [list of str] list of names of the files where to store the plot
vmin, vmax [float] Min and max values of the colorbar
ylabel [str] The y-axis label

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plots_vol.plot_traj(rng_traj, azi_traj, ele_traj, time_traj, prdcfg, fname_list,
rad_alt=None, rad_tstart=None, ax=None, fig=None,
save_fig=True)`

plots a trajectory on a Cartesian surface

Parameters

rng_traj, azi_traj, ele_traj [float array] antenna coordinates of the trajectory [m and deg]
time_traj [datetime array] trajectory time
prdcfg [dict] dictionary containing the product configuration
fname_list [list of str] list of names of the files where to store the plot
rad_alt [float or None] radar altitude [m MSL]
rad_tstart [datetime object or None] start time of the radar scan
surface_alt [float] surface altitude [m MSL]
color_ref [str] What the color code represents. Can be 'None', 'rel_altitude', 'altitude' or 'time'
fig [Figure] Figure to add the colorbar to. If none a new figure will be created
ax [Axis] Axis to plot on. if fig is None a new axis will be created
save_fig [bool] if true save the figure if false it does not close the plot and returns the handle to the figure

Returns

fname_list [list of str or]
fig, ax [tuple] list of names of the saved plots or handle of the figure an axes

PYRAD.GRAPH.PLOTS_GRID

Functions to plot data in a Cartesian grid format

<i>plot_surface</i> (grid, field_name, level, ...[, ...])	plots a surface from gridded data
<i>plot_surface_contour</i> (grid, field_name, ...)	plots a surface from gridded data
<i>plot_latitude_slice</i> (grid, field_name, lon, ...)	plots a latitude slice from gridded data
<i>plot_longitude_slice</i> (grid, field_name, lon, ...)	plots a longitude slice from gridded data
<i>plot_latlon_slice</i> (grid, field_name, coord1, ...)	plots a croos section crossing two points in the grid

`pyrad.graph.plots_grid.plot_latitude_slice` (*grid*, *field_name*, *lon*, *lat*, *prdcfg*, *fname_list*)
plots a latitude slice from gridded data

Parameters

- grid** [Grid object] object containing the gridded data to plot
- field_name** [str] name of the radar field to plot
- lon, lat** [float] coordinates of the slice to plot
- prdcfg** [dict] dictionary containing the product configuration
- fname_list** [list of str] list of names of the files where to store the plot

Returns

- fname_list** [list of str] list of names of the created plots

`pyrad.graph.plots_grid.plot_latlon_slice` (*grid*, *field_name*, *coord1*, *coord2*, *prdcfg*, *fname_list*)
plots a croos section crossing two points in the grid

Parameters

- grid** [Grid object] object containing the gridded data to plot
- field_name** [str] name of the radar field to plot
- coord1** [tuple of floats] lat, lon of the first point
- coord2** [tuple of floats] lat, lon of the second point
- fname_list** [list of str] list of names of the files where to store the plot

Returns

- fname_list** [list of str] list of names of the created plots

`pyrad.graph.plots_grid.plot_longitude_slice` (*grid, field_name, lon, lat, prdcfg, fname_list*)
plots a longitude slice from gridded data

Parameters

grid [Grid object] object containing the gridded data to plot
field_name [str] name of the radar field to plot
lon, lat [float] coordinates of the slice to plot
prdcfg [dict] dictionary containing the product configuration
fname_list [list of str] list of names of the files where to store the plot

Returns

fname_list [list of str] list of names of the created plots

`pyrad.graph.plots_grid.plot_surface` (*grid, field_name, level, prdcfg, fname_list, titl=None, save_fig=True, use_basemap=False*)
plots a surface from gridded data

Parameters

grid [Grid object] object containing the gridded data to plot
field_name [str] name of the radar field to plot
level [int] level index
prdcfg [dict] dictionary containing the product configuration
fname_list [list of str] list of names of the files where to store the plot
titl [str] Plot title
save_fig [bool] if true save the figure. If false it does not close the plot and returns the handle to the figure

Returns

fname_list [list of str or]
fig, ax, display [tuple] list of names of the saved plots or handle of the figure an axes

`pyrad.graph.plots_grid.plot_surface_contour` (*grid, field_name, level, prdcfg, fname_list, contour_values=None, linewidths=1.5, ax=None, fig=None, display=None, save_fig=True, use_basemap=False*)
plots a surface from gridded data

Parameters

grid [Grid object] object containing the gridded data to plot
field_name [str] name of the radar field to plot
level [int] level index
prdcfg [dict] dictionary containing the product configuration
fname_list [list of str] list of names of the files where to store the plot
contour_values [float array] list of contours to plot
linewidths [float] width of the contour lines
fig [Figure] Figure to add the colorbar to. If none a new figure will be created

ax [Axis] Axis to plot on. if fig is None a new axis will be created

save_fig [bool] if true save the figure if false it does not close the plot and returns the handle to the figure

Returns

fname_list [list of str or]

fig, ax [tuple] list of names of the saved plots or handle of the figure an axes

PYRAD.GRAPH.PLOTS_SPECTRA

Functions to plot spectral data

<i>plot_range_Doppler</i> (spectra, field_name, ray, ...)	Makes a range-Doppler plot
<i>plot_angle_Doppler</i> (spectra, field_name, ang, ...)	Makes an angle-Doppler plot
<i>plot_time_Doppler</i> (spectra, field_name, ...)	Makes a time-Doppler plot
<i>plot_Doppler</i> (spectra, field_name, ray, rng, ...)	Makes a Doppler plot
<i>plot_complex_range_Doppler</i> (spectra, ...[, ...])	Makes a complex range-Doppler plot.
<i>plot_complex_angle_Doppler</i> (spectra, ...[, ...])	Makes an angle-Doppler plot of complex spectra
<i>plot_complex_time_Doppler</i> (spectra, ...[, ...])	Makes a complex time-Doppler plot.
<i>plot_amp_phase_range_Doppler</i> (spectra, ...[, ...])	Makes a complex range-Doppler plot plotting separately the module and the phase of the signal
<i>plot_amp_phase_angle_Doppler</i> (spectra, ...[, ...])	Makes an angle-Doppler plot of complex spectra
<i>plot_amp_phase_time_Doppler</i> (spectra, ...[, ...])	Makes a complex time-Doppler plot plotting separately the module and the phase of the signal
<i>plot_complex_Doppler</i> (spectra, field_name, ...)	Makes a complex Doppler plot plotting separately the real and the imaginary parts
<i>plot_amp_phase_Doppler</i> (spectra, field_name, ...)	Makes a complex Doppler plot plotting separately the module and the phase of the signal
<i>_create_irregular_grid</i> (xaxis, yaxis[, yaxis_pos])	Create an irregular grid to be able to plot data with variable x-axis
<i>_adapt_data_to_irregular_grid</i> (data, ...)	Adapts data to irregular grid to allow plotting

`pyrad.graph.plots_spectra._adapt_data_to_irregular_grid` (*data*, *xaxis_size*, *nxbin_lim*, *nybin_lim*)

Adapts data to irregular grid to allow plotting

Parameters

- data** [2D float array] The data to plot
- xaxis_size** [1D-array] The size of each x-axis
- nxbin_lim, nybin_lim** [float] number of gate limits at each axis

Returns

- zpoints** [2D float array] Matrix containing the data points.

`pyrad.graph.plots_spectra._create_irregular_grid` (*xaxis*, *yaxis*, *yaxis_pos*='start')

Create an irregular grid to be able to plot data with variable x-axis

Parameters

xaxis [2D float array] array containing the x points

yaxis [1D float array] array containing the y points

yaxis_pos [str] the position that the y point represents in the y-axis bin. Can be 'start', 'end' or 'centre'

Returns

xaxis_lim, **yaxis_lim** [2D float array] Matrix containing the edges of the X and Y axis

`pyrad.graph.plots_spectra.plot_Doppler` (*spectra*, *field_name*, *ray*, *rng*, *prdcfg*, *fname_list*,
xaxis_info='Doppler_velocity', *ylabel*=None,
titl=None, *vmin*=None, *vmax*=None)

Makes a Doppler plot

Parameters

spectra [radar spectra object] object containing the spectra or the IQ data to plot

field_name [str] name of the field to plot

ray, **rng** [int] ray and rng index

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

xaxis_info [str] Type of x-axis. Can be 'Doppler_velocity', 'Doppler_frequency' or 'pulse_number'

ylabel [str or None] The label of the y-axis

titl [str or None] The plot title

vmin, **vmax** [float or None] The value limits

Returns

fname_list [list of str] list of names of the saved plots

`pyrad.graph.plots_spectra.plot_amp_phase_Doppler` (*spectra*, *field_name*, *ray*,
rng, *prdcfg*, *fname_list*,
xaxis_info='Doppler_velocity',
titl=None, *ampli_vmin*=None, *ampli_vmax*=None, *phase_vmin*=None,
phase_vmax=None)

Makes a complex Doppler plot plotting separately the module and the phase of the signal

Parameters

spectra [radar spectra object] object containing the spectra or the IQ data to plot

field_name [str] name of the field to plot

ray, **rng** [int] ray and range index

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

xaxis_info [str] Type of x-axis. Can be 'Doppler_velocity', 'Doppler_frequency' or 'pulse_number'

titl [str or None] The plot title

ampli_vmin, ampli_vmax, phase_vmin, phase_vmax [float or None] The value limits

Returns

fname_list [list of str] list of names of the saved plots

```
pyrad.graph.plots_spectra.plot_amp_phase_angle_Doppler(spectra,          field_name,
                                                         ang,   ind_rays,  ind_rng,
                                                         prdcfg,         fname_list,
                                                         xaxis_info='Doppler_velocity',
                                                         yaxis_pos='centre',
                                                         along_azi=True, titl=None,
                                                         ampli_vmin=None,
                                                         ampli_vmax=None,
                                                         phase_vmin=None,
                                                         phase_vmax=None)
```

Makes an angle-Doppler plot of complex spectra

Parameters

spectra [radar spectra object] object containing the spectra or the IQ data to plot

field_name [str] name of the field to plot

ang [float] The fixed angle

ind_rays [1D int array] The indices of the rays to plot

ind_rng [int] The index of the range to plot

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

xaxis_info [str] Type of x-axis. Can be 'Doppler_velocity', 'Doppler_frequency' or 'pulse_number'

yaxis_pos [str] the position that the y point represents in the y-axis bin. Can be 'start', 'end' or 'centre'

along_azi [bool] If true the plot is performed along azimuth. If false it is performed along elevation

titl [str or None] The plot title

ampli_vmin, ampli_vmax, phase_vmin, phase_vmax [float or None] The value limits

Returns

fname_list [list of str] list of names of the saved plots

```
pyrad.graph.plots_spectra.plot_amp_phase_range_Doppler(spectra,          field_name,
                                                         ray,   prdcfg,  fname_list,
                                                         xaxis_info='Doppler_velocity',
                                                         titl=None,          am-
                                                         pli_vmin=None,      am-
                                                         pli_vmax=None,
                                                         phase_vmin=None,
                                                         phase_vmax=None)
```

Makes a complex range-Doppler plot plotting separately the module and the phase of the signal

Parameters

spectra [radar spectra object] object containing the spectra or the IQ data to plot

field_name [str] name of the field to plot

ray [int] ray index

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

xaxis_info [str] Type of x-axis. Can be 'Doppler_velocity', 'Doppler_frequency' or 'pulse_number'

titl [str or None] The plot title

ampli_vmin, ampli_vmax, phase_vmin, phase_vmax [float or None] The value limits

Returns

fname_list [list of str] list of names of the saved plots

`pyrad.graph.plots_spectra.plot_amp_phase_time_Doppler` (*spectra*, *field_name*,
prdcfg, *fname_list*,
xaxis_info= 'Doppler_velocity',
yaxis_pos= 'start', *titl*=None,
ampli_vmin=None,
ampli_vmax=None,
phase_vmin=None,
phase_vmax=None)

Makes a complex time-Doppler plot plotting separately the module and the phase of the signal

Parameters

spectra [radar spectra object] object containing the spectra or the IQ data to plot

field_name [str] name of the field to plot

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

xaxis_info [str] Type of x-axis. Can be 'Doppler_velocity', 'Doppler_frequency' or 'pulse_number'

yaxis_pos [str] the position that the y point represents in the y-axis bin. Can be 'start', 'end' or 'centre'

titl [str or None] The plot title

ampli_vmin, ampli_vmax, phase_vmin, phase_vmax [float or None] The value limits

Returns

fname_list [list of str] list of names of the saved plots

`pyrad.graph.plots_spectra.plot_angle_Doppler` (*spectra*, *field_name*, *ang*, *ind_rays*,
ind_rng, *prdcfg*, *fname_list*,
xaxis_info= 'Doppler_velocity',
yaxis_pos= 'centre', *along_azi*=True,
titl=None, *clabel*=None, *vmin*=None,
vmax=None)

Makes an angle-Doppler plot

Parameters

spectra [radar spectra object] object containing the spectra or the IQ data to plot

field_name [str] name of the field to plot
ang [float] The fixed angle
ind_rays [1D int array] The indices of the rays to plot
ind_rng [int] The index of the range to plot
prdcfg [dict] dictionary containing the product configuration
fname_list [list of str] list of names of the files where to store the plot
xaxis_info [str] Type of x-axis. Can be 'Doppler_velocity', 'Doppler_frequency' or 'pulse_number'
yaxis_pos [str] the position that the y point represents in the y-axis bin. Can be 'start', 'end' or 'centre'
along_azi [bool] If true the plot is performed along azimuth. If false it is performed along elevation
titl [str or None] The plot title
clabel [str or None] The color bar label
vmin, vmax [float or None] The value limits

Returns

fname_list [list of str] list of names of the saved plots

`pyrad.graph.plots_spectra.plot_complex_Doppler(spectra, field_name, ray, rng, prdcfg, fname_list, xaxis_info='Doppler_velocity', ylabel=None, titl=None, vmin=None, vmax=None)`

Makes a complex Doppler plot plotting separately the real and the imaginary parts

Parameters

spectra [radar spectra object] object containing the spectra or the IQ data to plot
field_name [str] name of the field to plot
ray, rng [int] ray and range index
prdcfg [dict] dictionary containing the product configuration
fname_list [list of str] list of names of the files where to store the plot
xaxis_info [str] Type of x-axis. Can be 'Doppler_velocity', 'Doppler_frequency' or 'pulse_number'
ylabel [str or None] The label of the y-axis
titl [str or None] The plot title
vmin, vmax [float or None] The value limits

Returns

fname_list [list of str] list of names of the saved plots

```
pyrad.graph.plots_spectra.plot_complex_angle_Doppler(spectra,          field_name,
                                                         ang,      ind_rays,   ind_rng,
                                                         prdcfg,      fname_list,
                                                         xaxis_info='Doppler_velocity',
                                                         yaxis_pos='centre',
                                                         along_azi=True,   titl=None,
                                                         clabel=None,     vmin=None,
                                                         vmax=None)
```

Makes an angle-Doppler plot of complex spectra

Parameters

spectra [radar spectra object] object containing the spectra or the IQ data to plot

field_name [str] name of the field to plot

ang [float] The fixed angle

ind_rays [1D int array] The indices of the rays to plot

ind_rng [int] The index of the range to plot

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

xaxis_info [str] Type of x-axis. Can be 'Doppler_velocity', 'Doppler_frequency' or 'pulse_number'

yaxis_pos [str] the position that the y point represents in the y-axis bin. Can be 'start', 'end' or 'centre'

along_azi [bool] If true the plot is performed along azimuth. If false it is performed along elevation

titl [str or None] The plot title

clabel [str or None] The color bar label

vmin, vmax [float or None] The value limits

Returns

fname_list [list of str] list of names of the saved plots

```
pyrad.graph.plots_spectra.plot_complex_range_Doppler(spectra,          field_name,
                                                         ray,      prdcfg,   fname_list,
                                                         xaxis_info='Doppler_velocity',
                                                         titl=None,   clabel=None,
                                                         vmin=None, vmax=None)
```

Makes a complex range-Doppler plot. Plotting separately the real and the imaginary part

Parameters

spectra [radar spectra object] object containing the spectra or the IQ data to plot

field_name [str] name of the field to plot

ray [int] ray index

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

xaxis_info [str] Type of x-axis. Can be 'Doppler_velocity', 'Doppler_frequency' or 'pulse_number'

titl [str or None] The plot title
clabel [str or None] The label of color bar
vmin, vmax [float or None] The value limits

Returns

fname_list [list of str] list of names of the saved plots

```
pyrad.graph.plots_spectra.plot_complex_time_Doppler(spectra,          field_name,  
                                                    prdcfg,          fname_list,  
                                                    xaxis_info='Doppler_velocity',  
                                                    yaxis_pos='start',    titl=None,  
                                                    clabel=None,         vmin=None,  
                                                    vmax=None)
```

Makes a complex time-Doppler plot. Plotting separately the real and the imaginary part

Parameters

spectra [radar spectra object] object containing the spectra or the IQ data to plot
field_name [str] name of the field to plot
prdcfg [dict] dictionary containing the product configuration
fname_list [list of str] list of names of the files where to store the plot
xaxis_info [str] Type of x-axis. Can be 'Doppler_velocity', 'Doppler_frequency' or 'pulse_number'
yaxis_pos [str] the position that the y point represents in the y-axis bin. Can be 'start', 'end' or 'centre'
titl [str or None] The plot title
clabel [str or None] The label of color bar
vmin, vmax [float or None] The value limits

Returns

fname_list [list of str] list of names of the saved plots

```
pyrad.graph.plots_spectra.plot_range_Doppler(spectra, field_name, ray, prdcfg, fname_list,  
                                              xaxis_info='Doppler_velocity', titl=None,  
                                              clabel=None, vmin=None, vmax=None)
```

Makes a range-Doppler plot

Parameters

spectra [radar spectra object] object containing the spectra or the IQ data to plot
field_name [str] name of the field to plot
ray [int] ray index
prdcfg [dict] dictionary containing the product configuration
fname_list [list of str] list of names of the files where to store the plot
xaxis_info [str] Type of x-axis. Can be 'Doppler_velocity', 'Doppler_frequency' or 'pulse_number'
titl [str or None] The plot title
clabel [str or None] The color bar label

vmin, vmax [float or None] The value limits

Returns

fname_list [list of str] list of names of the saved plots

```
pyrad.graph.plots_spectra.plot_time_Doppler(spectra, field_name, prdcfg, fname_list,  
                                              xaxis_info='Doppler_velocity',  
                                              yaxis_pos='start', titl=None, clabel=None,  
                                              vmin=None, vmax=None)
```

Makes a time-Doppler plot

Parameters

spectra [radar spectra object] object containing the spectra or the IQ data to plot

field_name [str] name of the field to plot

prdcfg [dict] dictionary containing the product configuration

fname_list [list of str] list of names of the files where to store the plot

xaxis_info [str] Type of x-axis. Can be 'Doppler_velocity', 'Doppler_frequency' or 'pulse_number'

yaxis_pos [str] the position that the y point represents in the y-axis bin. Can be 'start', 'end' or 'centre'

titl [str or None] The plot title

clabel [str or None] The color bar label

vmin, vmax [float or None] The value limits

Returns

fname_list [list of str] list of names of the saved plots

PYRAD.GRAPH.PLOT_TIMESERIES

Functions to plot Pyrad datasets

<i>plot_timeseries</i> (tvec, data_list, fname_list)	plots a time series
<i>plot_timeseries_comp</i> (date1, value1, date2, ...)	plots 2 time series in the same graph
<i>plot_monitoring_ts</i> (date, np_t, cquant, ...)	plots a time series of monitoring data
<i>plot_intercomp_scores_ts</i> (date_vec, np_vec, ...)	plots a time series of radar intercomparison scores
<i>plot_ml_ts</i> (dt_ml_arr, ml_top_avg_arr, ..., ...)	plots a time series of melting layer data
<i>plot_sun_retrieval_ts</i> (sun_retrieval, ..., ...)	plots sun retrieval time series series

```
pyrad.graph.plots_timeseries.plot_intercomp_scores_ts(date_vec, np_vec, mean-
                                                         bias_vec, median-
                                                         bias_vec, quant25bias_vec,
                                                         quant75bias_vec, mode-
                                                         bias_vec, corr_vec,
                                                         slope_vec, intercep_vec,
                                                         intercep_slope1_vec,
                                                         fname_list, ref_value=0.0,
                                                         np_min=0, corr_min=0.0,
                                                         labelx='Time UTC',
                                                         titl='RADAR001-RADAR002
                                                         intercomparison', dpi=72)
```

plots a time series of radar intercomparison scores

Parameters

- date_vec** [datetime object] time of the time series
- np_vec** [int array] number of points
- meanbias_vec, medianbias_vec, modebias_vec** [float array] mean, median and mode bias
- quant25bias_vec, quant75bias_vec:** 25th and 75th percentile of the bias
- corr_vec** [float array] correlation
- slope_vec, intercep_vec** [float array] slope and intercep of a linear regression
- intercep_slope1_vec** [float] the intercep point of a inear regression of slope 1
- ref_value** [float] the reference value
- np_min** [int] The minimum number of points to consider the result valid
- corr_min** [float] The minimum correlation to consider the results valid

labelx [str] The label of the X axis

titl [str] The figure title

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plots_timeseries.plot_ml_ts(dt_ml_arr, ml_top_avg_arr, ml_top_std_arr,  
                                         thick_avg_arr, thick_std_arr, nrays_valid_arr,  
                                         nrays_total_arr, fname_list, labelx='Time UTC',  
                                         titl='Melting layer time series', dpi=72)
```

plots a time series of melting layer data

Parameters

dt_ml_arr [datetime object] time of the time series

np_vec [int array] number of points

meanbias_vec, medianbias_vec, modebias_vec [float array] mean, median and mode bias

quant25bias_vec, quant75bias_vec: 25th and 75th percentile of the bias

corr_vec [float array] correlation

slope_vec, intercep_vec [float array] slope and intercep of a linear regression

intercep_slope1_vec [float] the intercep point of a inear regression of slope 1

ref_value [float] the reference value

np_min [int] The minimum number of points to consider the result valid

corr_min [float] The minimum correlation to consider the results valid

labelx [str] The label of the X axis

titl [str] The figure title

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plots_timeseries.plot_monitoring_ts(date, np_t, cquant, lquant,  
                                                hquant, field_name, fname_list,  
                                                ref_value=None, vmin=None,  
                                                vmax=None, np_min=0, labelx='Time  
[UTC]', labely='Value', titl='Time  
Series', dpi=72)
```

plots a time series of monitoring data

Parameters

date [datetime object] time of the time series

np_t [int array] number of points

cquant, lquant, hquant [float array] values of the central, low and high quantiles

field_name [str] name of the field

fname_list [list of str] list of names of the files where to store the plot

ref_value [float] the reference value

vmin, vmax [float] The limits of the y axis

np_min [int] minimum number of points to consider the sample plotable

labelx [str] The label of the X axis

labeledy [str] The label of the Y axis

titl [str] The figure title

dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plots_timeseries.plot_sun_retrieval_ts(sun_retrieval, data_type,  
                                                    fname_list, labelx='Date',  
                                                    titl='Sun retrieval Time Series',  
                                                    dpi=72)
```

plots sun retrieval time series series

Parameters

sun_retrieval [tuple] tuple containing the retrieved parameters

data_type [str] parameter to be plotted

fname_list [list of str] list of names of the files where to store the plot

labelx [str] the x label

titl [str] the title of the plot

dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plots_timeseries.plot_timeseries(tvec, data_list, fname_list, labelx='Time  
[UTC]', labeledy='Value', labels=['Sensor'],  
                                              title='Time Series', period=0, timeformat  
                                              mat=None, colors=None, linestyles=None,  
                                              markers=None, ymin=None, ymax=None,  
                                              dpi=72)
```

plots a time series

Parameters

tvec [datetime object] time of the time series

data_list [list of float array] values of the time series

fname_list [list of str] list of names of the files where to store the plot

labelx [str] The label of the X axis

labeledy [str] The label of the Y axis

labels [array of str] The label of the legend

title [str] The figure title

period [float] measurement period in seconds used to compute accumulation. If 0 no accumulation is computed

timeformat [str] Specifies the tvec and time format on the x axis

colors [array of str] Specifies the colors of each line

linestyles [array of str] Specifies the line style of each line

markers: array of str Specify the markers to be used for each line

ymin, ymax: float Lower/Upper limit of y axis

dpi [int] dots per inch

Returns

fname_list [list of str] list of names of the created plots

```
pyrad.graph.plots_timeseries.plot_timeseries_comp(date1, value1, date2, value2,
                                                    fname_list, labelx='Time [UTC]',
                                                    labely='Value', label1='Sensor
                                                    1', label2='Sensor 2', titl='Time
                                                    Series Comparison', period1=0, pe-
                                                    riode2=0, ymin=None, ymax=None,
                                                    dpi=72)
```

plots 2 time series in the same graph

Parameters

date1 [datetime object] time of the first time series

value1 [float array] values of the first time series

date2 [datetime object] time of the second time series

value2 [float array] values of the second time series

fname_list [list of str] list of names of the files where to store the plot

labelx [str] The label of the X axis

labely [str] The label of the Y axis

label1, label2 [str] legend label for each time series

titl [str]

The figure title

period1, period2 [float] measurement period in seconds used to compute accumulation.
If 0 no accumulation is computed

dpi [int] dots per inch

ymin, ymax [float] The limits of the Y-axis. None will keep the default limit.

Returns

fname_list [list of str] list of names of the created plots

PYRAD.UTIL.RADAR_UTILS

Miscellaneous functions dealing with radar data

<i>get_data_along_rng</i> (radar, field_name, ..., ...)	Get data at particular (azimuths, elevations)
<i>get_data_along_azi</i> (radar, field_name, ..., ...)	Get data at particular (ranges, elevations)
<i>get_data_along_ele</i> (radar, field_name, ..., ...)	Get data at particular (ranges, azimuths)
<i>get_ROI</i> (radar, fieldname, sector)	filter out any data outside the region of interest defined by sector
<i>rainfall_accumulation</i> (t_in_vec, val_in_vec)	Computes the rainfall accumulation of a time series over a given period
<i>time_series_statistics</i> (t_in_vec, val_in_vec)	Computes statistics over a time-averaged series.
<i>find_contiguous_times</i> (times[, step])	Given and array of ordered times, find those contiguous according to a maximum time step
<i>join_time_series</i> (t1, val1, t2, val2[, dropnan])	joins time_series.
<i>get_range_bins_to_avg</i> (rad1_rng, rad2_rng)	Compares the resolution of two radars and determines if and which radar has to be averaged and the length of the averaging window
<i>belongs_roi_indices</i> (lat, lon, roi)	Get the indices of points that belong to roi in a list of points
<i>find_ray_index</i> (ele_vec, azi_vec, ele, azi[, ...])	Find the ray index corresponding to a particular elevation and azimuth
<i>find_rng_index</i> (rng_vec, rng[, rng_tol])	Find the range index corresponding to a particular range
<i>find_ang_index</i> (ang_vec, ang[, ang_tol])	Find the angle index corresponding to a particular fixed angle
<i>find_nearest_gate</i> (radar, lat, lon[, latlon_tol])	Find the radar gate closest to a lat,lon point
<i>find_neighbour_gates</i> (radar, azi, rng[, ...])	Find the neighbouring gates within +-delta_azi and +-delta_rng
<i>find_colocated_indexes</i> (radar1, radar2, ...)	Given the theoretical elevation, azimuth and range of the co-located gates of two radars and a given tolerance returns the indices of the gates for the current radars
<i>get_target_elevations</i> (radar_in)	Gets RHI target elevations
<i>time_avg_range</i> (timeinfo, avg_starttime, ...)	finds the new start and end time of an averaging
<i>get_closest_solar_flux</i> (hit_datetime_list, ...)	finds the solar flux measurement closest to the sun hit
<i>get_fixed_rng_data</i> (radar, field_names, fixed_rng)	Creates a 2D-grid with (azi, ele) data at a fixed range

Continued on next page

Table 1 – continued from previous page

<code>create_sun_hits_field(rad_el, rad_az, ...)</code>	creates a sun hits field from the position and power of the sun hits
<code>create_sun_retrieval_field(par, field_name, ...)</code>	creates a sun retrieval field from the retrieval parameters
<code>compute_quantiles(field[, quantiles])</code>	computes quantiles
<code>compute_quantiles_from_hist(bin_centers, hist)</code>	computes quantiles from histograms
<code>compute_quantiles_sweep(field, ray_start, ...)</code>	computes quantiles of a particular sweep
<code>compute_histogram(field, field_name[, ...])</code>	computes histogram of the data
<code>compute_histogram_sweep(field, ray_start, ...)</code>	computes histogram of the data in a particular sweep
<code>get_histogram_bins(field_name[, step])</code>	gets the histogram bins using the range limits of the field as defined in the Py-ART config file.
<code>compute_2d_stats(field1, field2, ...[, ...])</code>	computes a 2D histogram and statistics of the data
<code>compute_1d_stats(field1, field2)</code>	returns statistics of data
<code>compute_2d_hist(field1, field2, field_name1, ...)</code>	computes a 2D histogram of the data
<code>quantize_field(field, field_name, step)</code>	quantizes data
<code>compute_profile_stats(field, gate_altitude, ...)</code>	Compute statistics of vertical profile
<code>compute_directional_stats(field[, avg_type, ...])</code>	Computes the mean or the median along one of the axis (ray or range)
<code>project_to_vertical(data_in, data_height, ...)</code>	Projects radar data to a regular vertical grid

`pyrad.util.radar_utils.belongs_roi_indices` (*lat, lon, roi*)

Get the indices of points that belong to roi in a list of points

Parameters

lat, lon [float arrays] latitudes and longitudes to check

roi [dict] Dictionary describing the region of interest

Returns

inds [array of ints] list of indices of points belonging to ROI

is_roi [str] Whether the list of points is within the region of interest. Can be 'All', 'None', 'Some'

`pyrad.util.radar_utils.compute_1d_stats` (*field1, field2*)

returns statistics of data

Parameters

field1, field2 [ndarray 1D] the two fields to compare

Returns

stats [dict] a dictionary with statistics

`pyrad.util.radar_utils.compute_2d_hist` (*field1, field2, field_name1, field_name2, step1=None, step2=None*)

computes a 2D histogram of the data

Parameters

field1, field2 [ndarray 2D] the radar fields

field_name1, field_name2 [str] field names

step1, step2 [float] size of the bins

Returns

H [float array 2D] The bi-dimensional histogram of samples x and y

xedges, yedges [float array] the bin edges along each dimension

`pyrad.util.radar_utils.compute_2d_stats` (*field1, field2, field_name1, field_name2, step1=None, step2=None*)

computes a 2D histogram and statistics of the data

Parameters

field1, field2 [ndarray 2D] the two fields

field_name1, field_name2: str the name of the fields

step1, step2 [float] size of bin

Returns

hist_2d [array] the histogram

bin_edges1, bin_edges2 [float array] The bin edges

stats [dict] a dictionary with statistics

`pyrad.util.radar_utils.compute_directional_stats` (*field, avg_type='mean', nvalid_min=1, axis=0*)

Computes the mean or the median along one of the axis (ray or range)

Parameters

field [ndarray] the radar field

avg_type: str the type of average: 'mean' or 'median'

nvalid_min [int] the minimum number of points to consider the stats valid. Default 1

axis [int] the axis along which to compute (0=ray, 1=range)

Returns

values [ndarray 1D] The resultant statistics

nvalid [ndarray 1D] The number of valid points used in the computation

`pyrad.util.radar_utils.compute_histogram` (*field, field_name, bin_edges=None, step=None, vmin=None, vmax=None*)

computes histogram of the data

Parameters

field [ndarray 2D] the radar field

field_name: str or none name of the field

bins_edges: ndarray 1D the bin edges

step [float] size of bin

vmin, vmax [float] The minimum and maximum value of the histogram

Returns

bin_edges [float array] interval of each bin

values [float array] values at each bin

`pyrad.util.radar_utils.compute_histogram_sweep` (*field, ray_start, ray_end, field_name, step=None*)

computes histogram of the data in a particular sweep

Parameters

field [ndarray 2D] the radar field
ray_start, ray_end [int] starting and ending ray indexes
field_name: str name of the field
step [float] size of bin

Returns

bin_edges [float array] interval of each bin
values [float array] values at each bin

`pyrad.util.radar_utils.compute_profile_stats` (*field, gate_altitude, h_vec, h_res, quantity='quantiles', quantiles=array([0.25, 0.5, 0.75]), nvalid_min=4, std_field=None, np_field=None, make_linear=False, include_nans=False*)

Compute statistics of vertical profile

Parameters

field [ndarray] the radar field
gate_altitude: ndarray the altitude at each radar gate [m MSL]
h_vec [1D ndarray] height vector [m MSL]
h_res [float] height resolution [m]
quantity [str] The quantity to compute. Can be ['quantiles', 'mode', 'regression_mean', 'mean']. If 'mean', the min, max, and average is computed.
quantiles [1D ndarray] the quantiles to compute
nvalid_min [int] the minimum number of points to consider the stats valid
std_field [ndarray] the standard deviation of the regression at each range gate
np_field [ndarray] the number of points used to compute the regression at each range gate
make_linear [Boolean] If true the data is transformed into linear coordinates before taking the mean
include_nans [Boolean] If true NaN will be considered as zeros

Returns

vals [ndarray 2D] The resultant statistics
val_valid [ndarray 1D] The number of points to compute the stats used at each height level

`pyrad.util.radar_utils.compute_quantiles` (*field, quantiles=None*)
computes quantiles

Parameters

field [ndarray 2D] the radar field
ray_start, ray_end [int] starting and ending ray indexes
quantiles: float array list of quantiles to compute

Returns

quantiles [float array] list of quantiles

values [float array] values at each quantile

`pyrad.util.radar_utils.compute_quantiles_from_hist` (*bin_centers*, *hist*, *quantiles=None*)

computes quantiles from histograms

Parameters

bin_centers [ndarray 1D] the bins

hist [ndarray 1D] the histogram

quantiles: float array list of quantiles to compute

Returns

quantiles [float array] list of quantiles

values [float array] values at each quantile

`pyrad.util.radar_utils.compute_quantiles_sweep` (*field*, *ray_start*, *ray_end*, *quantiles=None*)

computes quantiles of a particular sweep

Parameters

field [ndarray 2D] the radar field

ray_start, ray_end [int] starting and ending ray indexes

quantiles: float array list of quantiles to compute

Returns

quantiles [float array] list of quantiles

values [float array] values at each quantile

`pyrad.util.radar_utils.create_sun_hits_field` (*rad_el*, *rad_az*, *sun_el*, *sun_az*, *data*, *imgcfg*)

creates a sun hits field from the position and power of the sun hits

Parameters

rad_el, rad_az, sun_el, sun_az [ndarray 1D] azimuth and elevation of the radar and the sun respectively in degree

data [masked ndarray 1D] the sun hit data

imgcfg: dict a dictionary specifying the ranges and resolution of the field to create

Returns

field [masked ndarray 2D] the sun hit field

`pyrad.util.radar_utils.create_sun_retrieval_field` (*par*, *field_name*, *imgcfg*, *lant=0.0*)

creates a sun retrieval field from the retrieval parameters

Parameters

par [ndarray 1D] the 5 retrieval parameters

imgcfg: dict a dictionary specifying the ranges and resolution of the field to create

Returns

field [masked ndarray 2D] the sun retrieval field

`pyrad.util.radar_utils.find_ang_index(ang_vec, ang, ang_tol=0.0)`

Find the angle index corresponding to a particular fixed angle

Parameters

ang_vec [float array] The angle data array where to look for

ang [float] The angle to search

ang_tol [float] Tolerance [deg]

Returns

ind_ang [int] The angle index

`pyrad.util.radar_utils.find_colocated_indexes(radar1, radar2, rad1_ele, rad1_azi, rad1_rng, rad2_ele, rad2_azi, rad2_rng, ele_tol=0.5, azi_tol=0.5, rng_tol=50.0)`

Given the theoretical elevation, azimuth and range of the co-located gates of two radars and a given tolerance returns the indices of the gates for the current radars

Parameters

radar1, radar2 [radar objects] the two radar objects

rad1_ele, rad1_azi, rad1_rng [array of floats] the radar coordinates of the radar1 gates

rad2_ele, rad2_azi, rad2_rng [array of floats] the radar coordinates of the radar2 gates

ele_tol, azi_tol [floats] azimuth and elevation angle tolerance [deg]

rng_tol [float] range Tolerance [m]

Returns

ind_ray_rad1, ind_rng_rad1, ind_ray_rad2, ind_rng_rad2 [array of ints] the ray and range indexes of each radar gate

`pyrad.util.radar_utils.find_contiguous_times(times, step=600)`

Given and array of ordered times, find those contiguous according to a maximum time step

Parameters

times [array of datetimes] The array of times

step [float] The time step [s]

Returns

start_times, end_times [array of date times] The start and end of each consecutive time period

`pyrad.util.radar_utils.find_nearest_gate(radar, lat, lon, latlon_tol=0.0005)`

Find the radar gate closest to a lat,lon point

Parameters

radar [radar object] the radar object

lat, lon [float] The position of the point

latlon_tol [float] The tolerance around this point

Returns

ind_ray, ind_rng [int] The ray and range index

azi, rng [float] the range and azimuth position of the gate

`pyrad.util.radar_utils.find_neighbour_gates(radar, azi, rng, delta_azi=None, delta_rng=None)`

Find the neighbouring gates within +-delta_azi and +-delta_rng

Parameters

radar [radar object] the radar object

azi, rng [float] The azimuth [deg] and range [m] of the central gate

delta_azi, delta_rng [float] The extend where to look for

Returns

inds_ray_aux, ind_rng_aux [int] The indices (ray, rng) of the neighbouring gates

`pyrad.util.radar_utils.find_ray_index(ele_vec, azi_vec, ele, azi, ele_tol=0.0, azi_tol=0.0, nearest='azi')`

Find the ray index corresponding to a particular elevation and azimuth

Parameters

ele_vec, azi_vec [float arrays] The elevation and azimuth data arrays where to look for

ele, azi [floats] The elevation and azimuth to search

ele_tol, azi_tol [floats] Tolerances [deg]

nearest [str] criteria to define wich ray to keep if multiple rays are within tolerance. azi: nearest azimuth, ele: nearest elevation

Returns

ind_ray [int] The ray index

`pyrad.util.radar_utils.find_rng_index(rng_vec, rng, rng_tol=0.0)`

Find the range index corresponding to a particular range

Parameters

rng_vec [float array] The range data array where to look for

rng [float] The range to search

rng_tol [float] Tolerance [m]

Returns

ind_rng [int] The range index

`pyrad.util.radar_utils.get_ROI(radar, fieldname, sector)`

filter out any data outside the region of interest defined by sector

Parameters

radar [radar object] the radar object where the data is

fieldname [str] name of the field to filter

sector [dict] a dictionary defining the region of interest

Returns

roi_flag [ndarray] a field array with ones in gates that are in the Region of Interest

```
pyrad.util.radar_utils.get_closest_solar_flux(hit_datetime_list, flux_datetime_list,  
                                              flux_value_list)
```

finds the solar flux measurement closest to the sun hit

Parameters

hit_datetime_list [datetime array] the date and time of the sun hit

flux_datetime_list [datetime array] the date and time of the solar flux measurement

flux_value_list: ndarray 1D the solar flux values

Returns

flux_datetime_closest_list [datetime array] the date and time of the solar flux measurement closest to sun hit

flux_value_closest_list [ndarray 1D] the solar flux values closest to the sun hit time

```
pyrad.util.radar_utils.get_data_along_azi(radar, field_name, fix_ranges, fix_elevations,  
                                         rng_tol=50.0, ang_tol=1.0, azi_start=None,  
                                         azi_stop=None)
```

Get data at particular (ranges, elevations)

Parameters

radar [radar object] the radar object where the data is

field_name [str] name of the field to filter

fix_ranges, fix_elevations: list of floats List of ranges [m], elevations [deg] couples

rng_tol [float] Tolerance between the nominal range and the radar range [m]

ang_tol [float] Tolerance between the nominal angle and the radar angle [deg]

azi_start, azi_stop: float Start and stop azimuth angle of the data [deg]

Returns

xvals [list of float arrays] The ranges of each rng, ele pair

yvals [list of float arrays] The values

valid_rng, valid_ele [float arrays] The rng, ele pairs

```
pyrad.util.radar_utils.get_data_along_ele(radar, field_name, fix_ranges, fix_azimuths,  
                                         rng_tol=50.0, ang_tol=1.0, ele_min=None,  
                                         ele_max=None)
```

Get data at particular (ranges, azimuths)

Parameters

radar [radar object] the radar object where the data is

field_name [str] name of the field to filter

fix_ranges, fix_azimuths: list of floats List of ranges [m], azimuths [deg] couples

rng_tol [float] Tolerance between the nominal range and the radar range [m]

ang_tol [float] Tolerance between the nominal angle and the radar angle [deg]

ele_min, ele_max: float Min and max elevation angle [deg]

Returns

xvals [list of float arrays] The ranges of each rng, ele pair

yvals [list of float arrays] The values

valid_rng, valid_ele [float arrays] The rng, ele pairs

`pyrad.util.radar_utils.get_data_along_rng` (*radar, field_name, fix_elevations, fix_azimuths, ang_tol=1.0, rmin=None, rmax=None*)

Get data at particular (azimuths, elevations)

Parameters

radar [radar object] the radar object where the data is

field_name [str] name of the field to filter

fix_elevations, fix_azimuths: list of floats List of elevations, azimuths couples [deg]

ang_tol [float] Tolerance between the nominal angle and the radar angle [deg]

rmin, rmax: float Min and Max range of the obtained data [m]

Returns

xvals [list of float arrays] The ranges of each azi, ele pair

yvals [list of float arrays] The values

valid_azi, valid_ele [float arrays] The azi, ele pairs

`pyrad.util.radar_utils.get_fixed_rng_data` (*radar, field_names, fixed_rng, rng_tol=50.0, ele_min=None, ele_max=None, azi_min=None, azi_max=None*)

Creates a 2D-grid with (azi, ele) data at a fixed range

Parameters

radar [radar object] The radar object containing the data

field_name [str] The field name

fixed_rng [float] The fixed range [m]

rng_tol [float] The tolerance between the nominal range and the actual radar range [m]

ele_min, ele_max, azi_min, azi_max [float or None] The limits of the grid [deg]. If None the limits will be the limits of the radar volume

Returns

radar [radar object] The radar object containing only the desired data

`pyrad.util.radar_utils.get_histogram_bins` (*field_name, step=None*)
gets the histogram bins using the range limits of the field as defined in the Py-ART config file.

Parameters

field_name: str name of the field

step [float] size of bin

Returns

bin_edges [float array] The bin edges

`pyrad.util.radar_utils.get_range_bins_to_avg` (*rad1_rng, rad2_rng*)

Compares the resolution of two radars and determines if and which radar has to be averaged and the length of the averaging window

Parameters

rad1_rng [array] the range of radar 1

rad2_rng [datetime] the range of radar 2

Returns

avg_rad1, avg_rad2 [Boolean] Booleans specifying if the radar data has to be average in range

avg_rad_lim [array with two elements] the limits to the average (centered on each range gate)

`pyrad.util.radar_utils.get_target_elevations(radar_in)`

Gets RHI target elevations

Parameters

radar_in [Radar object] current radar object

Returns

target_elevations [1D-array] Azimuth angles

el_tol [float] azimuth tolerance

`pyrad.util.radar_utils.join_time_series(t1, val1, t2, val2, dropnan=False)`

joins time_series. Only of package pandas is available otherwise returns None.

Parameters

t1 [datetime array] time of first series

val1 [float array] value of first series

t2 [datetime array] time of second series

val2 [float array] value of second series

dropnan [boolean] if True remove NaN from the time series

Returns

t_out_vec [datetime array] the resultant date time after joining the series

val1_out_vec [float array] value of first series

val2_out_vec [float array] value of second series

`pyrad.util.radar_utils.project_to_vertical(data_in, data_height, grid_height, interp_kind='none', fill_value=-9999.0)`

Projects radar data to a regular vertical grid

Parameters

data_in [ndarray 1D] the radar data to project

data_height [ndarray 1D] the height of each radar point

grid_height [ndarray 1D] the regular vertical grid to project to

interp_kind [str] The type of interpolation to use: 'none' or 'nearest'

fill_value [float] The fill value used for interpolation

Returns

data_out [ndarray 1D] The projected data

`pyrad.util.radar_utils.quantize_field(field, field_name, step)`

quantizes data

Parameters

field [ndarray 2D] the radar field

field_name: str name of the field

step [float] size of bin

Returns

fieldq [ndarray 2D] The quantized field

values [float array] values at each bin

`pyrad.util.radar_utils.rainfall_accumulation(t_in_vec, val_in_vec, cum_time=3600.0, base_time=0.0, dropnan=False)`

Computes the rainfall accumulation of a time series over a given period

Parameters

t_in_vec [datetime array] the input date and time array

val_in_vec [float array] the input values array [mm/h]

cum_time [int] accumulation time [s]

base_time [int] base time [s]

dropnan [boolean] if True remove NaN from the time series

Returns

t_out_vec [datetime array] the output date and time array

val_out_vec [float array] the output values array

np_vec [int array] the number of samples at each period

`pyrad.util.radar_utils.time_avg_range(timeinfo, avg_starttime, avg_endtime, period)`

finds the new start and end time of an averaging

Parameters

timeinfo [datetime] the current volume time

avg_starttime [datetime] the current average start time

avg_endtime: datetime the current average end time

period: float the averaging period

Returns

new_starttime [datetime] the new average start time

new_endtime [datetime] the new average end time

`pyrad.util.radar_utils.time_series_statistics(t_in_vec, val_in_vec, avg_time=3600, base_time=1800, method='mean', dropnan=False)`

Computes statistics over a time-averaged series. Only of package pandas is available otherwise returns None

Parameters

t_in_vec [datetime array] the input date and time array

val_in_vec [float array] the input values array

avg_time [int] averaging time [s]

base_time [int] base time [s]

method [str] statistical method

dropnan [boolean] if True remove NaN from the time series

Returns

t_out_vec [datetime array] the output date and time array

val_out_vec [float array] the output values array

PYRAD.UTIL.STAT_UTILS

Miscellaneous functions dealing with statistics

<code>quantiles_weighted(values[, weight_vector, ...])</code>	Given a set of values and weights, compute the weighted quantile(s) and average.
<code>ratio_bootstrapping(nominator, denominator)</code>	Computes a set of samples obtained as $\text{sum}(\text{nominator})/\text{sum}(\text{denominator})$ where the nominator and the denominator are randomly sampled with replacement.

`pyrad.util.stat_utils.quantiles_weighted(values, weight_vector=None, quantiles=array([0.5]), weight_threshold=None, data_is_log=False, nvalid_min=3)`
Given a set of values and weights, compute the weighted quantile(s) and average.

Parameters

- values** [array of floats] Array containing the values. Can be 2-dimensional
- weight_vector** [array of floats or None] array containing the weights to apply. If None it will be an array of ones (uniform weight). If values is a 2D array it will be repeated for the second dimension
- quantiles** [array of floats] The quantiles to be computed
- weight_threshold** [float or None] If weight_threshold is set quantiles will be computed only if the total weight (sum of the weights of valid data) exceeds this threshold
- data_is_log** [Bool] If true the values will be considered to be in logarithmic scale and transformed into linear scale before computing the quantiles and average
- nvalid_min** [int] Minimum number of valid points to consider the computation valid

Returns

- avg** [float] the weighted average
- quants** [array of floats] an array containing the weighted quantiles in the same order as the quantiles vector
- nvalid** [int] Number of valid points in the computation of the statistics

`pyrad.util.stat_utils.ratio_bootstrapping(nominator, denominator, nsamples=1000)`
Computes a set of samples obtained as $\text{sum}(\text{nominator})/\text{sum}(\text{denominator})$ where the nominator and the denominator are randomly sampled with replacement.

Parameters

nominator, denominator [1D array] The data points in the nominator and the denominator.
Nominator and denominator are not independent, i.e. data point i in the nominator is linked to data point i in the denominator

nsamples [int] Number of iteration, i.e. number of samples desired

Returns

samples [1D array] the resultant samples

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

p

pyrad.flow.flow_aux, ??
pyrad.flow.flow_control, ??
pyrad.graph.plots, ??
pyrad.graph.plots_aux, ??
pyrad.graph.plots_grid, ??
pyrad.graph.plots_spectra, ??
pyrad.graph.plots_timeseries, ??
pyrad.graph.plots_vol, ??
pyrad.io.config, ??
pyrad.io.io_aux, ??
pyrad.io.mxpole_config, ??
pyrad.io.read_data_cosmo, ??
pyrad.io.read_data_dem, ??
pyrad.io.read_data_hzt, ??
pyrad.io.read_data_mxpole, ??
pyrad.io.read_data_other, ??
pyrad.io.read_data_radar, ??
pyrad.io.read_data_sensor, ??
pyrad.io.read_data_sun, ??
pyrad.io.timeseries, ??
pyrad.io.trajectory, ??
pyrad.io.write_data, ??
pyrad.proc.process_aux, ??
pyrad.proc.process_calib, ??
pyrad.proc.process_cosmo, ??
pyrad.proc.process_dem, ??
pyrad.proc.process_Doppler, ??
pyrad.proc.process_echoclass, ??
pyrad.proc.process_grid, ??
pyrad.proc.process_intercomp, ??
pyrad.proc.process_iq, ??
pyrad.proc.process_monitoring, ??
pyrad.proc.process_phase, ??
pyrad.proc.process_retrieve, ??
pyrad.proc.process_spectra, ??
pyrad.proc.process_timeseries, ??
pyrad.proc.process_traj, ??
pyrad.prod.process_grid_products, ??
pyrad.prod.process_intercomp_products, ??
pyrad.prod.process_monitoring_products, ??
pyrad.prod.process_product, ??
pyrad.prod.process_spectra_products, ??
pyrad.prod.process_timeseries_products, ??
pyrad.prod.process_traj_products, ??
pyrad.prod.process_vol_products, ??
pyrad.prod.product_aux, ??
pyrad.util.radar_utils, ??
pyrad.util.stat_utils, ??