
pyart-mch library reference for users

Release 0.0.1

meteoswiss-mdr

Nov 08, 2017

1	Input and output (<code>pyart.io</code>)	3
1.1	Reading radar data	3
1.2	Writing radar data	3
1.3	Reading grid data	3
1.4	Writing grid data	3
1.5	Reading Sonde data	4
1.6	Special use	4
2	Auxiliary input and output (<code>pyart.aux_io</code>)	21
2.1	Reading radar data	21
3	Core (<code>pyart.core</code>)	29
3.1	Core classes	29
3.2	Coordinate transformations	29
4	Bridging to other toolkits (<code>pyart.bridge</code>)	47
4.1	Phase functions	47
5	Filters (<code>pyart.filters</code>)	49
5.1	Filtering radar data	49
6	Radar Corrections (<code>pyart.correct</code>)	61
6.1	Velocity unfolding	61
6.2	Other corrections	61
6.3	Helper functions	62
7	Radar Retrievals (<code>pyart.retrieve</code>)	93
7.1	Radar retrievals	93
8	Mapping (<code>pyart.map</code>)	111
9	Graphing (<code>pyart.graph</code>)	117
9.1	Plotting radar data	117
9.2	Plotting grid data	117
10	Utilities (<code>pyart.util</code>)	203
10.1	Direction statistics	203
10.2	Miscellaneous functions	203
11	Testing Utilities (<code>pyart.testing</code>)	211
11.1	Testing functions	211
11.2	Testing classes	211

12 Indices and tables	215
Bibliography	217
Python Module Index	219
Index	221

Contents:

INPUT AND OUTPUT (PYART.IO)

Functions to read and write radar and grid data to and from a number of file formats.

1.1 Reading radar data

In most cases the `pyart.io.read()` function should be used to read in radar data from a file. In certain cases the function the read function for the format in question should be used.

<code>read(filename[, use_rsl])</code>	Read a radar file and return a radar object.
<code>read_rsl(filename[, field_names, ...])</code>	Read a file supported by RSL
<code>read_mdv(filename[, field_names, ...])</code>	Read a MDV file.
<code>read_sigmet(filename[, field_names, ...])</code>	Read a Sigmet (IRIS) product file.
<code>read_cfradial(filename[, field_names, ...])</code>	Read a Cfradial netCDF file.
<code>read_chl(filename[, field_names, ...])</code>	Read a CSU-CHILL CHL file.
<code>read_nexrad_archive(filename[, field_names, ...])</code>	Read a NEXRAD Level 2 Archive file.
<code>read_nexrad_cdm(filename[, field_names, ...])</code>	Read a Common Data Model (CDM) NEXRAD Level 2 file.
<code>read_nexrad_level3(filename[, field_names, ...])</code>	Read a NEXRAD Level 3 product.
<code>read_uf(filename[, field_names, ...])</code>	Read a UF File.

1.2 Writing radar data

<code>write_cfradial(filename, radar[, format, ...])</code>	Write a Radar object to a CF/Radial compliant netCDF file.
<code>write_uf(filename, radar[, uf_field_names, ...])</code>	Write a Radar object to a UF file.

1.3 Reading grid data

<code>read_grid(filename[, exclude_fields])</code>	Read a netCDF grid file produced by Py-ART.
<code>read_grid_mdv(filename[, field_names, ...])</code>	Read a MDV file to a Grid Object.

1.4 Writing grid data

<code>write_grid(filename, grid[, format, ...])</code>	Write a Grid object to a CF-1.5 and ARM standard netCDF file
<code>write_grid_mdv(filename, grid[, ...])</code>	Write grid object to MDV file.
<code>write_grid_geotiff(grid, filename, field[, ...])</code>	Write a Py-ART Grid object to a GeoTIFF file.

1.5 Reading Sonde data

<code>read_arm_sonde(filename)</code>	Read a ARM sonde file returning a wind profile.
<code>read_arm_sonde_vap(filename[, radar, ...])</code>	Read a ARM interpolated or merged sonde returning a wind profile.

1.6 Special use

<code>prepare_for_read(filename)</code>	Return a file like object read for reading.
<code>make_time_unit_str(dtobj)</code>	Return a time unit string from a datetime object.

`pyart.io.make_time_unit_str(dtobj)`
Return a time unit string from a datetime object.

`pyart.io.prepare_for_read(filename)`
Return a file like object read for reading.

Open a file for reading in binary mode with transparent decompression of Gzip and BZip2 files. The resulting file-like object should be closed.

Parameters `filename` : str or file-like object

Filename or file-like object which will be opened. File-like objects will not be examined for compressed data.

Returns `file_like` : file-like object

File like object from which data can be read.

`pyart.io.read(filename, use_rsl=False, **kwargs)`
Read a radar file and return a radar object.

Additional parameters are passed to the underlying `read_*` function.

Parameters `filename` : str

Name of radar file to read

`use_rsl` : bool

True will use the TRMM RSL library to read files which are supported both natively and by RSL. False will choose the native read function. RSL will always be used to read a file if it is not supported natively.

Returns `radar` : Radar

Radar object. A `TypeError` is raised if the format cannot be determined.

Other Parameters `field_names` : dict, optional

Dictionary mapping file data type names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the metadata configuration file.

additional_metadata : dict of dicts, optional

Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the metadata configuration file will be used.

file_field_names : bool, optional

True to use the file data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields : list or None, optional

List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

delay_field_loading : bool

True to delay loading of field data from the file until the 'data' key in a particular field dictionary is accessed. In this case the field attribute of the returned Radar object will contain LazyLoadDict objects not dict objects. Not all file types support this parameter.

`pyart.io.read_arm_sonde(filename)`

Read a ARM sonde file returning a wind profile.

Parameters filename : str

Name of ARM sonde NetCDF file to read data from.

`pyart.io.read_arm_sonde_vap(filename, radar=None, target_datetime=None)`

Read a ARM interpolated or merged sonde returning a wind profile.

Parameters filename : str

Name of ARM interpolate or merged sonde NetCDF file to read data from.

radar : Radar, optional

If provided the profile returned is that which is closest in time to the first ray collected in this radar. Either radar or target_datetime must be provided.

target_datetime : datetime, optional

If specified the profile returned is that which is closest in time to this datetime.

`pyart.io.read_cfradial(filename, field_names=None, additional_metadata=None,
file_field_names=False, exclude_fields=None, delay_field_loading=False,
**kwargs)`

Read a Cfradial netCDF file.

Parameters filename : str

Name of CF/Radial netCDF file to read data from.

field_names : dict, optional

Dictionary mapping field names in the file names to radar field names. Unlike other read functions, fields not in this dictionary or having a value of None are still included

in the `radar.fields` dictionary, to exclude them use the `exclude_fields` parameter. Fields which are mapped by this dictionary will be renamed from key to value.

additional_metadata : dict of dicts, optional

This parameter is not used, it is included for uniformity.

file_field_names : bool, optional

True to force the use of the field names from the file in which case the `field_names` parameter is ignored. False will use to `field_names` parameter to rename fields.

exclude_fields : list or None, optional

List of fields to exclude from the radar object. This is applied after the `file_field_names` and `field_names` parameters.

delay_field_loading : bool

True to delay loading of field data from the file until the 'data' key in a particular field dictionary is accessed. In this case the field attribute of the returned Radar object will contain LazyLoadDict objects not dict objects. Delayed field loading will not provide any speedup in file where the number of gates vary between rays (`ngates_vary=True`) and is not recommended.

Returns radar : Radar

Radar object.

Notes

This function has not been tested on "stream" Cfradial files.

```
pyart.io.read_chl(filename, field_names=None, additional_metadata=None, file_field_names=None,
                  exclude_fields=None, use_file_field_attributes=True, **kwargs)
```

Read a CSU-CHILL CHL file.

Parameters filename : str

Name of CHL file.

field_names : dict, optional

Dictionary mapping CHL field names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the `radar.fields` dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata : dict of dicts, optional

Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names : bool, optional

True to use the CHL field names for the field names in the radar object. If this case the `field_names` parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in `additional_metadata`.

exclude_fields : list or None, optional

List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

use_file_field_attributes : bool, optional

True to use information provided by in the file to set the field attribute *long_name*, *units*, *valid_max*, and *valid_min*. False will not set these unless they are defined in the configuration file or in *additional_metadata*.

Returns radar : Radar

Radar object containing data from CHL file.

`pyart.io.read_grid(filename, exclude_fields=None, **kwargs)`

Read a netCDF grid file produced by Py-ART.

Parameters filename : str

Filename of netCDF grid file to read. This file must have been produced by *write_grid()* or have identical layout.

Returns grid : Grid

Grid object containing gridded data.

Other Parameters exclude_fields : list

A list of fields to exclude from the grid object.

`pyart.io.read_grid_mdv(filename, field_names=None, additional_metadata=None,
file_field_names=False, exclude_fields=None, delay_field_loading=False,
**kwargs)`

Read a MDV file to a Grid Object.

Parameters filename : str

Name of MDV file to read or file-like object pointing to the beginning of such a file.

field_names : dict, optional

Dictionary mapping MDV data type names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata : dict of dicts, optional

Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names : bool, optional

True to use the MDV data type names for the field names. If this case the *field_names* parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields : list or None, optional

List of fields to exclude from the grid object. This is applied after the *file_field_names* and *field_names* parameters.

delay_field_loading : bool

True to delay loading of field data from the file until the 'data' key in a particular field dictionary is accessed. In this case the field attribute of the returned Radar object will contain LazyLoadDict objects not dict objects.

Returns `grid` : Grid

Grid object containing data from MDV file.

Notes

This function can only read cartesian MDV files with fields compressed with gzip or zlib. For polar files see `pyart.io.read_mdv()`

MDV files and Grid object are not fully interchangeable. Specific limitation include:

- All fields must have the same shape and dimensions.
- All fields must have the same projection.
- Vlevels types must not vary.
- Projection must not be PROJ_POLAR_RADAR (9) or PROJ_RHI_RADAR (13).
- Correct unit in the Z axis are just available for 'vlevel_type' equal to VERT_TYPE_Z(4), VERT_TYPE_ELEV(9), VERT_TYPE_AZ(17), VERT_TYPE_PRESSURE(3) and VERT_TYPE_THETA(7).
- The behavior in cases of 2D data is unknown but most likely will not fail.

```
pyart.io.read_mdv(filename, field_names=None, additional_metadata=None, file_field_names=False,
                  exclude_fields=None, delay_field_loading=False, **kwargs)
```

Read a MDV file.

Parameters `filename` : str

Name of MDV file to read or file-like object pointing to the beginning of such a file.

field_names : dict, optional

Dictionary mapping MDV data type names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata : dict of dicts, optional

Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names : bool, optional

True to use the MDV data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields : list or None, optional

List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

delay_field_loading : bool

True to delay loading of field data from the file until the 'data' key in a particular field dictionary is accessed. In this case the field attribute of the returned Radar object will contain LazyLoadDict objects not dict objects. Not all file types support this parameter.

Returns radar : Radar

Radar object containing data from MDV file.

Notes

Currently this function can only read polar MDV files with fields compressed with gzip or zlib.

```
pyart.io.read_nexrad_archive(filename, field_names=None, additional_metadata=None,
                             file_field_names=False, exclude_fields=None, delay_field_loading=False,
                             station=None, scans=None, linear_interp=True, **kwargs)
```

Read a NEXRAD Level 2 Archive file.

Parameters filename : str

Filename of NEXRAD Level 2 Archive file. The files hosted by at the NOAA National Climate Data Center [\[R11\]](#) as well as on the UCAR THREDDS Data Server [\[R12\]](#) have been tested. Other NEXRAD Level 2 Archive files may or may not work. Message type 1 file and message type 31 files are supported.

field_names : dict, optional

Dictionary mapping NEXRAD moments to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the metadata configuration file.

additional_metadata : dict of dicts, optional

Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the metadata configuration file will be used.

file_field_names : bool, optional

True to use the NEXRAD field names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields : list or None, optional

List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

delay_field_loading : bool, optional

True to delay loading of field data from the file until the 'data' key in a particular field dictionary is accessed. In this case the field attribute of the returned Radar object will contain LazyLoadDict objects not dict objects.

station : str or None, optional

Four letter ICAO name of the NEXRAD station used to determine the location in the returned radar object. This parameter is only used when the location is not contained in the file, which occur in older NEXRAD message 1 files.

scans : list or None, optional

Read only specified scans from the file. None (the default) will read all scans.

linear_interp : bool, optional

True (the default) to perform linear interpolation between valid pairs of gates in low resolution rays in files mixed resolution rays. False will perform a nearest neighbor interpolation. This parameter is not used if the resolution of all rays in the file or requested sweeps is constant.

Returns radar : Radar

Radar object containing all moments and sweeps/cuts in the volume. Gates not collected are masked in the field data.

References

[R11], [R12]

`pyart.io.read_nexrad_cdm` (*filename*, *field_names=None*, *additional_metadata=None*,
file_field_names=False, *exclude_fields=None*, *station=None*, ***kwargs*)
Read a Common Data Model (CDM) NEXRAD Level 2 file.

Parameters filename : str

File name or URL of a Common Data Model (CDM) NEXRAD Level 2 file. File of in this format can be created using the NetCDF Java Library tools [R13]. A URL of a OPeNDAP file on the UCAR THREDDS Data Server [R14] is also accepted the netCDF4 library has been compiled with OPeNDAP support.

field_names : dict, optional

Dictionary mapping NEXRAD moments to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the metadata configuration file.

additional_metadata : dict of dicts, optional

Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the metadata configuration file will be used.

file_field_names : bool, optional

True to use the NEXRAD field names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields : list or None, optional

List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

station : str

Four letter ICAO name of the NEXRAD station used to determine the location in the returned radar object. This parameter is only used when the location is not contained in the file, which occur in older NEXRAD files. If the location is not provided in the file and this parameter is set to None the station name will be determined from the filename.

Returns radar : Radar

Radar object containing all moments and sweeps/cuts in the volume. Gates not collected are masked in the field data.

References

[R13], [R14]

```
pyart.io.read_nexrad_level3(filename, field_names=None, additional_metadata=None,
                           file_field_names=False, exclude_fields=None, **kwargs)
```

Read a NEXRAD Level 3 product.

Parameters filename : str

Filename of NEXRAD Level 3 product file. The files hosted by at the NOAA National Climate Data Center [R15] as well as on the NWS WSR-88D Level III Data Collection and Distribution Network have been tested. Other NEXRAD Level 3 files may or may not work. A file-like object pointing to the beginning of such a file is also supported.

field_names : dict, optional

Dictionary mapping NEXRAD level 3 product number to radar field names. If the product number of the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the metadata configuration file.

additional_metadata : dict of dicts, optional

Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the metadata configuration file will be used.

file_field_names : bool, optional

True to use the product number for the field name. In this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields : list or None, optional

List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

Returns radar : Radar

Radar object containing all moments and sweeps/cuts in the volume. Gates not collected are masked in the field data.

References

[R15], [R16]

```
pyart.io.read_rsl(filename, field_names=None, additional_metadata=None, file_field_names=False,
                 exclude_fields=None, delay_field_loading=False, radar_format=None, cal-
                 lid=None, skip_range_check=False)
```

Read a file supported by RSL

Parameters filename : str or RSL_radar

Name of file whose format is supported by RSL.

field_names : dict, optional

Dictionary mapping RSL data type names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata : dict of dicts, optional

Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names : bool, optional

True to use the RSL data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields : list or None, optional

List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

delay_field_loading : bool

True to delay loading of field data from the file until the 'data' key in a particular field dictionary is accessed. In this case the field attribute of the returned Radar object will contain LazyLoadDict objects not dict objects.

radar_format : str or None

Format of the radar file. Must be 'wsr88d' or None.

callid : str or None

Four letter NEXRAD radar Call ID, only used when radar_format is 'wsr88d'.

skip_range_check : bool, optional

True to skip check for uniform range bin location, the reported range locations will only be verified true for the first ray. False will perform the check and raise a IOError when the locations of the gates change between rays.

Returns radar : Radar

Radar object.

```
pyart.io.read_sigmet(filename, field_names=None, additional_metadata=None,
                    file_field_names=False, exclude_fields=None, time_ordered='none',
                    full_xhdr=None, noaa_hh_hdr=None, debug=False, ignore_xhdr=False,
                    ignore_sweep_start_ms=None, **kwargs)
```

Read a Sigmet (IRIS) product file.

Parameters filename : str

Name of Sigmet (IRIS) product file to read or file-like object pointing to the beginning of such a file.

field_names : dict, optional

Dictionary mapping Sigmet data type names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the metadata configuration file.

additional_metadata : dict of dicts, optional

Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the metadata configuration file will be used.

file_field_names : bool, optional

True to use the Sigmet data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields : list or None, optional

List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

time_ordered : 'none', 'sequential', 'full', ..., optional

Parameter controlling if and how the rays are re-ordered by time. The default, 'none' keeps the rays ordered in the same manner as they appear in the Sigmet file. 'sequential' will determine and apply an operation which maintains a sequential ray order in elevation or azimuth yet orders the rays according to time. If no operation can be found to accomplish this a warning is issued and the rays are returned in their original order. 'roll', 'reverse', and 'reverse_and_roll' will apply that operation to the rays in order to place them in time order, direct use of these is not recommended. 'full' will order the rays in strictly time increasing order, but the rays will likely become non-sequential, this option is not recommended unless strict time increasing order is required.

full_xhdr : bool or None

Flag to read in all extended headers for possible decoding. None will determine if extended headers should be read in automatically by examining the extended header type.

noaa_hh_hdr : bool or None

Flag indicating if the extended header should be decoded as those used by the NOAA Hurricane Hunters aircraft radars. None will determine if the extended header is of this type automatically by examining the header. The *full_xhdr* parameter is set to True when this parameter is True.

ignore_xhdr : bool, optional

True to ignore all data in the extended headers if they exist. False, the default, extracts milliseconds precision times and other parameter from the extended headers if they exist in the file.

ignore_sweep_start_ms : bool or None, optional

True to ignore the millisecond parameter in the start time for each sweep, False will use this parameter when determining the timing of each ray. None, the default, will ignore the millisecond sweep start timing only when the file does not contain extended headers or when the extended header has been explicitly ignored using the *ignore_xhdr* parameter. The TRMM RSL library ignores these times so setting this parameter to True is required to match the times determined when reading Sigmet files

with `pyart.io.read_rsl()`. When there are not extended headers ignoring the millisecond sweep times provides time data which is always prior to the actual collection time with an error from 0 to 2 seconds.

debug : bool, optional

Print debug information during read.

Returns radar : Radar

Radar object

`pyart.io.read UF (filename, field_names=None, additional_metadata=None, file_field_names=False, exclude_fields=None, delay_field_loading=False, **kwargs)`

Read a UF File.

Parameters filename : str or file-like

Name of Universal format file to read data from.

field_names : dict, optional

Dictionary mapping UF data type names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata : dict of dicts, optional

Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any addition metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names : bool, optional

True to force the use of the field names from the file in which case the *field_names* parameter is ignored. False will use to *field_names* parameter to rename fields.

exclude_fields : list or None, optional

List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

delay_field_loading : bool

This option is not implemented in the function but included for compatibility.

Returns radar : Radar

Radar object.

`pyart.io.write_cfradial (filename, radar, format='NETCDF4', time_reference=None, arm_time_variables=False)`

Write a Radar object to a CF/Radial compliant netCDF file.

The files produced by this routine follow the [CF/Radial standard](#). Attempts are also made to to meet many of the standards outlined in the [ARM Data File Standards](#).

To control how the netCDF variables are created, set any of the following keys in the radar attribute dictionaries.

- `_Zlib`
- `_DeflateLevel`
- `_Shuffle`

- `_Fletcher32`
- `_Contiguous`
- `_ChunkSizes`
- `_Endianness`
- `_Least_significant_digit`
- `_FillValue`

See the netCDF4 documentation for details on these settings.

Parameters `filename` : str

Filename to create.

radar : Radar

Radar object.

format : str, optional

NetCDF format, one of 'NETCDF4', 'NETCDF4_CLASSIC', 'NETCDF3_CLASSIC' or 'NETCDF3_64BIT'. See netCDF4 documentation for details.

time_reference : bool

True to include a time_reference variable, False will not include this variable. The default, None, will include the time_reference variable when the first time value is non-zero.

arm_time_variables : bool

True to create the ARM standard time variables base_time and time_offset, False will not create these variables.

```
pyart.io.write_grid(filename, grid, format='NETCDF4', write_proj_coord_sys=True,  
                    proj_coord_sys=None, arm_time_variables=False, write_point_x_y_z=False,  
                    write_point_lon_lat_alt=False)
```

Write a Grid object to a CF-1.5 and ARM standard netCDF file

To control how the netCDF variables are created, set any of the following keys in the grid attribute dictionaries.

- `_Zlib`
- `_DeflateLevel`
- `_Shuffle`
- `_Fletcher32`
- `_Contiguous`
- `_ChunkSizes`
- `_Endianness`
- `_Least_significant_digit`
- `_FillValue`

See the netCDF4 documentation for details on these settings.

Parameters `filename` : str

Filename to save grid to.

grid : Grid

Grid object to write.

format : str, optional

netCDF format, one of 'NETCDF4', 'NETCDF4_CLASSIC', 'NETCDF3_CLASSIC' or 'NETCDF3_64BIT'. See netCDF4 documentation for details.

write_proj_coord_sys bool, optional

True to write information on the coordinate transform used in the map projection to the ProjectionCoordinateSystem variable following the CDM Object Model. The resulting file should be interpreted as containing geographic grids by tools which use the Java NetCDF library (THREDDS, toolsUI, etc).

proj_coord_sys : dict or None, optional

Dictionary of parameters which will be written to the ProjectionCoordinateSystem NetCDF variable if write_proj_coord_sys is True. A value of None will attempt to generate an appropriate dictionary by examining the projection attribute of the grid object. If the projection is not understood a warnings will be issued.

arm_time_variables : bool, optional

True to write the ARM standard time variables base_time and time_offset. False will not write these variables.

write_point_x_y_z : bool, optional

True to include the point_x, point_y and point_z variables in the written file, False will not write these variables.

write_point_lon_lat_alt : bool, optional

True to include the point_longitude, point_latitude and point_altitude variables in the written file, False will not write these variables.

`pyart.io.write_grid_geotiff(grid, filename, field, rgb=False, level=None, cmap='viridis',
vmin=0, vmax=75, color_levels=None, warp=False, sld=False)`

Write a Py-ART Grid object to a GeoTIFF file.

The GeoTIFF can be the standard Azimuthal Equidistant projection used in Py-ART, or a lat/lon projection on a WGS84 sphere. The latter is typically more usable in web mapping applications. The GeoTIFF can contain a single float-point raster band, or three RGB byte raster bands. The former will require an SLD file for colorful display using standard GIS or web mapping software, while the latter will show colors “out-of-the-box” but lack actual data values. The function also can output an SLD file based on the user-specified inputs. User can specify the 2D vertical level to be output. If this is not specified, a 2D composite is created. User also can specify the field to output.

This function requires GDAL Python libraries to be installed. These are available via conda; e.g., ‘conda install gdal’

Parameters **grid** : pyart.core.Grid object

Grid object to write to file.

filename : str

Filename for the GeoTIFF.

field : str

Field name to output to file.

Other Parameters **rbg** : bool, optional

True - Output 3-band RGB GeoTIFF

False - Output single-channel, float-valued GeoTIFF. For display, likely will need an SLD file to provide a color table.

level: int or None, optional

Index for z-axis plane to output. None gives composite values (i.e., max in each vertical column).

cmap : str or matplotlib.colors.Colormap object, optional

Colormap to use for RGB output or SLD file.

vmin : int or float, optional

Minimum value to color for RGB output or SLD file.

vmax : int or float, optional

Maximum value to color for RGB output or SLD file.

color_levels : int or None, optional

Number of color levels in cmap. Useful for categorical colormaps with steps << 255 (e.g., hydrometeor ID).

warp : bool, optional

True - Use gdalwarp (called from command line using os.system) to warp to a lat/lon WGS84 grid.

False - No warping will be performed. Output will be Az. Equidistant.

sld : bool, optional

True - Create a Style Layer Descriptor file (SLD) mapped to vmin/vmax and cmap. File is named same as output TIFF, except for .sld extension.

False - Don't do this.

`pyart.io.write_grid_mdv(filename, grid, mdv_field_names=None, field_write_order=None)`

Write grid object to MDV file.

Create a MDV file containing data from the provided grid instance.

The MDV file will contain parameters from the 'source' key if contained in grid.metadata. If this key or parameters related to the radar location and name are not present in the grid a default or sentinel value. will be written in the MDV file in the place of the parameter.

Grid fields will be saved in float32 unless the `_Write_as_dtype` key is present.

Parameters filename : str or file-like object.

Filename of MDV file to create. If a file-like object is specified data will be written using the write method.

grid : Grid

Grid object from which to create MDV file.

mdv_field_names : dict or None, optional

Mapping between grid fields and MDV data type names. Field names mapped to None or with no mapping will be excluded from writing. If None, the same field names will be used.

field_write_order : list or None, optional

Order in which grid fields should be written out in the MDV file. None, the default, will determine a valid order automatically.

Notes

Do to limitations of the MDV format, not all grid objects are writable. To write a grid the following conditions must be satisfied:

- XY grid must be regular (equal spacing), Z can be irregular.
- The number of Z levels must not exceed 122.
- Fields can be encoded in the file using the ‘_Write_as_dtype’ key specifying one of ‘uint8’, ‘uint16’ or ‘float32’. Use the ‘scale_factor’ and ‘add_offset’ keys to specify scaling. Field data in the Grid object should be uncompressed, that is to say it has had the scaling applied.

```
pyart.io.write_uf(filename, radar, uf_field_names=None, radar_field_names=False, exclude_fields=None, field_write_order=None, volume_start=None, templates_extra=None)
```

Write a Radar object to a UF file.

Create a UF file containing data from the provided radar instance. The UF file will contain instrument parameters from the following dictionaries if they contained in radar.instrument_parameters:

- radar_beam_width_h
- radar_beam_width_v
- radar_receiver_bandwidth
- frequency
- pulse_width
- prt
- polarization_mode
- nyquist_velocity

If any of these parameter are not present a default or sentinel value will be written in the UF file in the place of the parameter. This is also true for the data in the scan_rate attribute.

Radar fields will be scaled and rounded to integer values when writing to UF files. The scale factor for each field can be specified in the `_UF_scale_factor` key for each field dictionary. If not specified the default scaling (100) will be used.

Parameters `filename` : str or file-like object.

Filename of UF file to create. If a file-like object is specified data will be written using the write method.

radar : Radar

Radar object from which to create UF file.

uf_field_names : dict or None, optional

Mapping between radar fields and two character UF data type names. Field names mapped to None or with no mapping will be excluded from writing. If None, the default mappings for UF files will be used.

radar_field_names : bool, optional

True to use the radar field names as the field names of the UF fields. False to use the `uf_field_names` mapping to generate UF field names. The `exclude_fields` argument can still be used to exclude fields from the UF file when this parameter is True. When reading a UF file using `file_field_names=True` set this parameter to True to write a UF file with the same field names.

exclude_fields : list or None, optional

List of radar fields to exclude from writing.

field_write_order : list or None, optional

Order in which radar fields should be written out in the UF file. None, the default, will determine a valid order automatically.

volume_start : datetime, optional

Start of volume used to set UF volume structure elements.

templates_extra : dict of dict or None

Advanced usage parameter for setting UF structure templates. Elements defined in dictionaries with keys 'mandatory_header', 'optional_header', and 'field_header' will be used to build the structure template.

AUXILIARY INPUT AND OUTPUT (PYART.AUX_IO)

Additional classes and functions for reading and writing data from a number of file formats.

These auxiliary input/output routines are not as well polished as those in `pyart.io`. They may require additional dependencies beyond those required for a standard Py-ART install, use non-standard function parameter and naming, are not supported by the `pyart.io.read()` function and are not fully tested if tested at all. Please use these at your own risk.

Bugs in these functions should be reported but fixing them may not be a priority.

2.1 Reading radar data

<code>read_d3r_gcpep_nc(filename[, field_names, ...])</code>	Read a D3R GCPEX netCDF file.
<code>read_gamic(filename[, field_names, ...])</code>	Read a GAMIC hdf5 file.
<code>read_kazr(filename[, field_names, ...])</code>	Read K-band ARM Zenith Radar (KAZR) NetCDF ingest data.
<code>read_noxp_iphex_nc(filename[, field_names, ...])</code>	Read a NOXP IPHEX netCDF file.
<code>read_odim_h5(filename[, field_names, ...])</code>	Read a ODIM_H5 file.
<code>read_pattern(filename, **kwargs)</code>	Read a netCDF file from a PATTERN project X-band radar.
<code>read_radx(filename[, radx_dir])</code>	Read a file by first converting it to Cf/Radial using Radx-Convert.
<code>read_rainbow_wrl(filename[, field_names, ...])</code>	Read a RAINBOW file.

`pyart.aux_io.metranet_read_cartesian(radar_file, physic_value=True)`

Reads a METRANET cartesian data file

Parameters `radar_file` : str

file name

physic_value : boolean

If true returns the physical value. Otherwise the digital value.

Returns `ret_data` : Radar_Metranet object

An object containing the information read from the file

`pyart.aux_io.read_d3r_gcpep_nc(filename, field_names=None, additional_metadata=None, file_field_names=False, exclude_fields=None, **kwargs)`

Read a D3R GCPEX netCDF file.

Parameters `filename` : str

Name of the ODIM_H5 file to read.

field_names : dict, optional

Dictionary mapping ODIM_H5 field names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata : dict of dicts, optional

Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names : bool, optional

True to use the MDV data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields : list or None, optional

List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

Returns radar : Radar

Radar object containing data from ODIM_H5 file.

```
pyart.aux_io.read_edge_netcdf(filename, **kwargs)
```

Read a EDGE NetCDF file.

Parameters filename : str

Name of EDGE NetCDF file to read data from.

Returns radar : Radar

Radar object.

```
pyart.aux_io.read_gamic(filename, field_names=None, additional_metadata=None,
                        file_field_names=False, exclude_fields=None,
                        valid_range_from_file=True, units_from_file=True, pulse_width=None,
                        **kwargs)
```

Read a GAMIC hdf5 file.

Parameters filename : str

Name of GAMIC HDF5 file to read data from.

field_names : dict, optional

Dictionary mapping field names in the file names to radar field names. Unlike other read functions, fields not in this dictionary or having a value of None are still included in the radar.fields dictionary, to exclude them use the *exclude_fields* parameter. Fields which are mapped by this dictionary will be renamed from key to value.

additional_metadata : dict of dicts, optional

This parameter is not used, it is included for uniformity.

file_field_names : bool, optional

True to force the use of the field names from the file in which case the *field_names* parameter is ignored. False will use to *field_names* parameter to rename fields.

exclude_fields : list or None, optional

List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

valid_range_from_file : bool, optional

True to extract valid range (*valid_min* and *valid_max*) for all field from the file when they are present. False will not extract these parameters.

units_from_file : bool, optional

True to extract the units for all fields from the file when available. False will not extract units using the default units for the fields.

pulse_width : list or None,

Mandatory for gamit radar processors which have pulsewidth enums. *pulse_width* should contain the pulsewidth' in us.

Returns radar : Radar

Radar object.

```
pyart.aux_io.read_kazr(filename, field_names=None, additional_metadata=None,
                      file_field_names=False, exclude_fields=None)
```

Read K-band ARM Zenith Radar (KAZR) NetCDF ingest data.

Parameters filename : str

Name of NetCDF file to read data from.

field_names : dict, optional

Dictionary mapping field names in the file names to radar field names. Unlike other read functions, fields not in this dictionary or having a value of None are still included in the *radar.fields* dictionary, to exclude them use the *exclude_fields* parameter. Fields which are mapped by this dictionary will be renamed from key to value.

additional_metadata : dict of dicts, optional

This parameter is not used, it is included for uniformity.

file_field_names : bool, optional

True to force the use of the field names from the file in which case the *field_names* parameter is ignored. False will use to *field_names* parameter to rename fields.

exclude_fields : list or None, optional

List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

Returns radar : Radar

Radar object.

```
pyart.aux_io.read_metranet(filename, field_names=None, additional_metadata=None,
                          file_field_names=False, exclude_fields=None, **kwargs)
```

Read a METRANET file.

Parameters filename : str

Name of the METRANET file to read.

field_names : dict, optional

Dictionary mapping METRANET field names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata : dict of dicts, optional

Dictionary of dictionaries to retrieve metadata during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names : bool, optional

True to use the MDV data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields : list or None, optional

List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

Returns radar : Radar

Radar object containing data from METRANET file.

```
pyart.aux_io.read_noxp_iphex_nc(filename, field_names=None, additional_metadata=None,  
                                file_field_names=False, exclude_fields=None, **kwargs)
```

Read a NOXP IPHEX netCDF file.

Parameters filename : str

Name of the netCDF file to read.

field_names : dict, optional

Dictionary mapping netCDF field names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata : dict of dicts, optional

Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names : bool, optional

True to use the netCDF data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields : list or None, optional

List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

Returns radar : Radar

Radar object containing data from netCDF file.

`pyart.aux_io.read_odim_h5(filename, field_names=None, additional_metadata=None,
file_field_names=False, exclude_fields=None, **kwargs)`

Read a ODIM_H5 file.

Parameters filename : str

Name of the ODIM_H5 file to read.

field_names : dict, optional

Dictionary mapping ODIM_H5 field names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata : dict of dicts, optional

Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names : bool, optional

True to use the MDV data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields : list or None, optional

List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

Returns radar : Radar

Radar object containing data from ODIM_H5 file.

`pyart.aux_io.read_pattern(filename, **kwargs)`

Read a netCDF file from a PATTERN project X-band radar.

Parameters filename : str

Name of netCDF file to read data from.

Returns radar : Radar

Radar object.

`pyart.aux_io.read_radx(filename, radx_dir=None, **kwargs)`

Read a file by first converting it to Cf/Radial using RadxConvert.

Parameters filename : str

Name of file to read using RadxConvert.

radx_dir : str, optional

path to the radx install

Returns radar : Radar

Radar object.

`pyart.aux_io.read_rainbow_wrl(filename, field_names=None, additional_metadata=None,
file_field_names=False, exclude_fields=None, **kwargs)`

Read a RAINBOW file. This routine has been tested to read rainbow5 files version 5.22.3, 5.34.16 and 5.35.1.

Since the rainbow file format is evolving constantly there is no guaranty that it can work with other versions. If necessary, the user should adapt to code according to its own file version.

Data types read by this routine: Reflectivity: dBZ, dBuZ, dBZv, dBuZv Velocity: V, Vu, Vv, Vvu Spectrum width: W, Wu, Wv, Wvu Differential reflectivity: ZDR, ZDRu Co-polar correlation coefficient: RhoHV, Rho-HVu Co-polar differential phase: PhiDP, uPhiDP, uPhiDPu Specific differential phase: KDP, uKDP, uKDPu Signal quality parameters: SQI, SQIu, SQIv, SQIvu Temperature: TEMP Position of the range bin respect to the ISO0: ISO0 radar visibility according to Digital Elevation Model (DEM): VIS

Parameters filename : str

Name of the RAINBOW file to read.

field_names : dict, optional

Dictionary mapping RAINBOW field names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata : dict of dicts, optional

Dictionary of dictionaries to retrieve metadata during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names : bool, optional

True to use the MDV data type names for the field names. If this case the field_names parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields : list or None, optional

List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

Returns radar : Radar

Radar object containing data from RAINBOW file.

```
pyart.aux_io.read_sinarame_h5(filename, field_names=None, additional_metadata=None,  
                             file_field_names=False, exclude_fields=None, **kwargs)
```

Read a SINARAME_H5 file.

Parameters filename : str

Name of the SINARAME_H5 file to read.

field_names : dict, optional

Dictionary mapping SINARAME_H5 field names to radar field names. If a data type found in the file does not appear in this dictionary or has a value of None it will not be placed in the radar.fields dictionary. A value of None, the default, will use the mapping defined in the Py-ART configuration file.

additional_metadata : dict of dicts, optional

Dictionary of dictionaries to retrieve metadata from during this read. This metadata is not used during any successive file reads unless explicitly included. A value of None, the default, will not introduce any additional metadata and the file specific or default metadata as specified by the Py-ART configuration file will be used.

file_field_names : bool, optional

True to use the MDV data type names for the field names. If this case the `field_names` parameter is ignored. The field dictionary will likely only have a 'data' key, unless the fields are defined in *additional_metadata*.

exclude_fields : list or None, optional

List of fields to exclude from the radar object. This is applied after the *file_field_names* and *field_names* parameters.

Returns radar : Radar

Radar object containing data from SINARAME_H5 file.

`pyart.aux_io.write_sinaram_e_cfradial(path)`

This function takes SINARAME_H5 files (where every file has only one field and one volume) from a folder and writes a CfRadial file for each volume including all fields.

Parameters path : str

Where the SINARAME_H5 files are.

CORE (PYART.CORE)

Core Py-ART classes and function for interacting with weather radar data.

3.1 Core classes

<i>Radar</i> (time, _range, fields, metadata, ...[, ...])	A class for storing antenna coordinate radar data.
<i>Grid</i> (time, fields, metadata, ...[, ...])	A class for storing rectilinear gridded radar data in Cartesian coordinate.
<i>HorizontalWindProfile</i> (height, speed, direction)	Horizontal wind profile.

3.2 Coordinate transformations

<i>antenna_to_cartesian</i> (ranges, azimuths, ...)	Return Cartesian coordinates from antenna coordinates.
<i>antenna_vectors_to_cartesian</i> (ranges, ...[, ...])	Calculate Cartesian coordinate for gates from antenna coordinate vectors.
<i>cartesian_to_geographic</i> (x, y, projparams)	Cartesian to Geographic coordinate transform.
<i>cartesian_vectors_to_geographic</i> (x, y, projparams)	Cartesian vectors to Geographic coordinate transform.
<i>cartesian_to_geographic_aeqd</i> (x, y, lon_0, lat_0)	Azimuthal equidistant Cartesian to geographic coordinate transform.
<i>cartesian_to_antenna</i> (x, y, z)	Returns antenna coordinates from Cartesian coordinates.
<i>geographic_to_cartesian</i> (lon, lat, projparams)	Geographic to Cartesian coordinate transform.
<i>geographic_to_cartesian_aeqd</i> (lon, lat, ...)	Azimuthal equidistant geographic to Cartesian coordinate transform.
<i>wgs84_to_swissCH1903</i> (lon, lat, alt[, ...])	Convert WGS84 coordinates to swiss coordinates (CH1903 / LV03)

```
class pyart.core.Grid(time, fields, metadata, origin_latitude, origin_longitude, origin_altitude,
                      x, y, z, projection=None, radar_latitude=None, radar_longitude=None,
                      radar_altitude=None, radar_time=None, radar_name=None)
```

Bases: object

A class for storing rectilinear gridded radar data in Cartesian coordinate.

Refer to the attribute section for information on the parameters.

To create a Grid object using legacy parameters present in Py-ART version 1.5 and before, use `from_legacy_parameters()`, `grid = Grid.from_legacy_parameters(fields, axes, metadata)`.

Attributes

time	(dict) Time of the grid.
fields: dict of dicts	Moments from radars or other variables.
metadata: dict	Metadata describing the grid.
origin_longitude, origin_latitude, origin_altitude	(dict) Geographic coordinate of the origin of the grid.
x, y, z	(dict, 1D) Distance from the grid origin for each Cartesian coordinate axis in a one dimensional array. Defines the spacing along the three grid axes which is repeated throughout the grid, making a rectilinear grid.
nx, ny, nz	(int) Number of grid points along the given Cartesian dimension.
projection	(dic or str) Projection parameters defining the map projection used to transform from Cartesian to geographic coordinates. None will use the default dictionary with the 'proj' key set to 'pyart_aeqd' indicating that the native Py-ART azimuthal equidistant projection is used. Other values should specify a valid pyproj.Proj projparams dictionary or string. The special key '_include_lon_0_lat_0' is removed when interpreting this dictionary. If this key is present and set to True, which is required when proj='pyart_aeqd', then the radar longitude and latitude will be added to the dictionary as 'lon_0' and 'lat_0'. Use the <code>get_projparams()</code> method to retrieve a copy of this attribute dictionary with this special key evaluated.
radar_longitude, radar_latitude, radar_altitude	(dict or None, optional) Geographic location of the radars which make up the grid.
radar_time	(dict or None, optional) Start of collection for the radar which make up the grid.
radar_name	(dict or None, optional) Names of the radars which make up the grid.
nradar	(int) Number of radars whose data was used to make the grid.
projection_proj	(Proj) pyproj.Proj instance for the projection specified by the projection attribute. If the 'pyart_aeqd' projection is specified accessing this attribute will raise a ValueError.
point_x, point_y, point_z	(LazyLoadDict) The Cartesian locations of all grid points from the origin in the three Cartesian coordinates. The three dimensional data arrays contained these attributes are calculated from the x, y, and z attributes. If these attributes are changed use <code>:py:func: init_point_x_y_z</code> to reset the attributes.
point_longitude, point_latitude	(LazyLoadDict) Geographic location of each grid point. The projection parameter(s) defined in the <i>projection</i> attribute are used to perform an inverse map projection from the Cartesian grid point locations relative to the grid origin. If these attributes are changed use <code>init_point_longitude_latitude()</code> to reset the attributes.
point_altitude	(LazyLoadDict) The altitude of each grid point as calculated from the altitude of the grid origin and the Cartesian z location of each grid point. If this attribute is changed use <code>init_point_altitude()</code> to reset the attribute.

Methods

<code>add_field(field_name, field_dict[, ...])</code>	Add a field to the object.
<code>get_point_longitude_latitude([level, edges])</code>	Return arrays of longitude and latitude for a given grid height level.
<code>get_projparams()</code>	Return a projparam dict from the projection attribute.
Continued on next page	

Table 3.3 – continued from previous page

<i>init_point_altitude()</i>	Initialize the point_altitude attribute.
<i>init_point_longitude_latitude()</i>	Initialize or reset the point_{longitude, latitudes} attributes.
<i>init_point_x_y_z()</i>	Initialize or reset the point_{x, y, z} attributes.
<i>write</i> (filename[, format, arm_time_variables])	Write the the Grid object to a NetCDF file.

__class__

alias of type

__delattr__

Implement delattr(self, name).

__dict__ = mappingproxy({'__dict__': <attribute '__dict__' of 'Grid' objects>, '__init__': <function Grid.__init__>, 'i**__dir__** () → list

default dir() implementation

__eq__

Return self==value.

__format__ ()

default object formatter

__ge__

Return self>=value.

__getattr__

Return getattr(self, name).

__getstate__ ()

Return object's state which can be pickled.

__gt__

Return self>value.

__hash__

Return hash(self).

__init__ (time, fields, metadata, origin_latitude, origin_longitude, origin_altitude, x, y, z,
 projection=None, radar_latitude=None, radar_longitude=None, radar_altitude=None,
 radar_time=None, radar_name=None)

Initialize object.

__le__

Return self<=value.

__lt__

Return self<value.

__module__ = 'pyart.core.grid'**__ne__**

Return self!=value.

__new__ ()

Create and return a new object. See help(type) for accurate signature.

__reduce__ ()

helper for pickle

__reduce_ex__ ()
helper for pickle

__repr__
Return repr(self).

__setattr__
Implement setattr(self, name, value).

__setstate__ (state)
Restore unpicklable entries from pickled object.

__sizeof__ () → int
size of object in memory, in bytes

__str__
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

_find_and_check_nradar ()
Return the number of radars which were used to create the grid.

Examine the radar attributes to determine the number of radars which were used to create the grid. If the size of the radar attributes are inconsistent a ValueError is raised by this method.

add_field (field_name, field_dict, replace_existing=False)
Add a field to the object.

Parameters **field_name** : str
Name of the field to the fields dictionary.

field_dict : dict
Dictionary containing field data and metadata.

replace_existing : bool, optional
True to replace the existing field with key field_name if it exists, overwriting the existing data. If False, a ValueError is raised if field_name already exists.

get_point_longitude_latitude (level=0, edges=False)
Return arrays of longitude and latitude for a given grid height level.

Parameters **level** : int, optional
Grid height level at which to determine latitudes and longitudes. This is not currently used as all height level have the same layout.

edges : bool, optional
True to calculate the latitude and longitudes of the edges by interpolating between Cartesian coordinates points and extrapolating at the boundaries. False to calculate the locations at the centers.

Returns **longitude, latitude** : 2D array

Arrays containing the latitude and longitudes, in degrees, of the grid points or edges between grid points for the given height.

get_projparams ()

Return a projparam dict from the projection attribute.

init_point_altitude ()

Initialize the point_altitude attribute.

init_point_longitude_latitude ()

Initialize or reset the point_{longitude, latitudes} attributes.

init_point_x_y_z ()

Initialize or reset the point_{x, y, z} attributes.

projection_proj

write (filename, format='NETCDF4', arm_time_variables=False)

Write the the Grid object to a NetCDF file.

Parameters filename : str

Filename to save to.

format : str, optional

NetCDF format, one of 'NETCDF4', 'NETCDF4_CLASSIC', 'NETCDF3_CLASSIC' or 'NETCDF3_64BIT'.

arm_time_variables : bool

True to write the ARM standard time variables base_time and time_offset. False will not write these variables.

class pyart.core.**HorizontalWindProfile** (height, speed, direction, latitude=None, longitude=None)

Bases: object

Horizontal wind profile.

Parameters height : array-like, 1D

Heights in meters above sea level at which horizontal winds were sampled.

speed : array-like, 1D

Horizontal wind speed in meters per second at each height sampled.

direction : array-like, 1D

Horizontal wind direction in degrees at each height sampled.

Other Parameters latitude : array-like, 1D, optional

Latitude in degrees north at each height sampled.

longitude : array-like, 1D, optional

Longitude in degrees east at each height sampled.

Attributes

<code>u_wind</code>	U component of horizontal wind in meters per second.
<code>v_wind</code>	V component of horizontal wind in meters per second.

height	(array, 1D) Heights in meters above sea level at which horizontal winds were sampled.
speed	(array, 1D) Horizontal wind speed in meters per second at each height.
direction	(array, 1D) Horizontal wind direction in degrees at each height.

Methods

from_u_and_v(height, u_wind, v_wind)Create a HorizontalWindProfile instance from U and V components.

```
__class__
    alias of type
__delattr__
    Implement delattr(self, name).
__dict__ = mappingproxy({'__dict__': <attribute '__dict__' of 'HorizontalWindProfile' objects>, '__init__': <function
__dir__ () → list
    default dir() implementation
__eq__
    Return self==value.
__format__ ()
    default object formatter
__ge__
    Return self>=value.
__getattr__
    Return getattr(self, name).
__gt__
    Return self>value.
__hash__
    Return hash(self).
__init__ (height, speed, direction, latitude=None, longitude=None)
    initialize
__le__
    Return self<=value.
__lt__
    Return self<value.
__module__ = 'pyart.core.wind_profile'
__ne__
    Return self!=value.
__new__ ()
    Create and return a new object. See help(type) for accurate signature.
__reduce__ ()
    helper for pickle
__reduce_ex__ ()
    helper for pickle
```

__repr__
Return repr(self).

__setattr__
Implement setattr(self, name, value).

__sizeof__ () → int
size of object in memory, in bytes

__str__
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

__parse_location_data (latitude, longitude)
Parse profile location data.

classmethod from_u_and_v (height, u_wind, v_wind)
Create a HorizontalWindProfile instance from U and V components.

Parameters **height** : array-like, 1D

Heights in meters above sea level at which horizontal winds were sampled.

u_wind : array-like, 1D

U component of horizontal wind speed in meters per second.

v_wind : array-like, 1D

V component of horizontal wind speed in meters per second.

u_wind
U component of horizontal wind in meters per second.

v_wind
V component of horizontal wind in meters per second.

class pyart.core.**Radar** (time, _range, fields, metadata, scan_type, latitude, longitude, altitude, sweep_number, sweep_mode, fixed_angle, sweep_start_ray_index, sweep_end_ray_index, azimuth, elevation, altitude_agl=None, target_scan_rate=None, rays_are_indexed=None, ray_angle_res=None, scan_rate=None, antenna_transition=None, instrument_parameters=None, radar_calibration=None, rotation=None, tilt=None, roll=None, drift=None, heading=None, pitch=None, georefs_applied=None)

Bases: object

A class for storing antenna coordinate radar data.

The structure of the Radar class is based on the CF/Radial Data file format. Global attributes and variables (section 4.1 and 4.3) are represented as a dictionary in the metadata attribute. Other required and optional variables are represented as dictionaries in a attribute with the same name as the variable in the CF/Radial standard. When an optional attribute not present the attribute has a value of None. The data for a given variable is stored in the dictionary under the 'data' key. Moment field data is stored as a dictionary of dictionaries in the fields attribute. Sub-convention variables are stored as a dictionary of dictionaries under the meta_group attribute.

Refer to the attribute section for information on the parameters.

Attributes

time	(dict) Time at the center of each ray.
range	(dict) Range to the center of each gate (bin).
fields	(dict of dicts) Moment fields.
metadata	(dict) Metadata describing the instrument and data.
scan_type	(str) Type of scan, one of 'ppi', 'rhi', 'sector' or 'other'. If the scan volume contains multiple sweep m
latitude	(dict) Latitude of the instrument.
longitude	(dict) Longitude of the instrument.
altitude	(dict) Altitude of the instrument, above sea level.
altitude_agl	(dict or None) Altitude of the instrument above ground level. If not provided this attribute is set to No
sweep_number	(dict) The number of the sweep in the volume scan, 0-based.
sweep_mode	(dict) Sweep mode for each mode in the volume scan.
fixed_angle	(dict) Target angle for thr sweep. Azimuth angle in RHI modes, elevation angle in all other modes.
sweep_start_ray_index	(dict) Index of the first ray in each sweep relative to the start of the volume, 0-based.
sweep_end_ray_index	(dict) Index of the last ray in each sweep relative to the start of the volume, 0-based.
rays_per_sweep	(LazyLoadDict) Number of rays in each sweep. The data key of this attribute is create upon first acces
target_scan_rate	(dict or None) Intended scan rate for each sweep. If not provided this attribute is set to None, indicatin
rays_are_indexed	(dict or None) Indication of whether ray angles are indexed to a regular grid in each sweep. If not prov
ray_angle_res	(dict or None) If rays_are_indexed is not None, this provides the angular resolution of the grid. If not
azimuth	(dict) Azimuth of antenna, relative to true North.
elevation	(dict) Elevation of antenna, relative to the horizontal plane.
gate_x, gate_y, gate_z	(LazyLoadDict) Location of each gate in a Cartesian coordinate system assuming a standard atmospher
gate_longitude, gate_latitude	(LazyLoadDict) Geographic location of each gate. The projection parameter(s) defined in the <i>projecti</i>
projection	(dic or str) Projection parameters defining the map projection used to transform from Cartesian to geo
gate_altitude	(LazyLoadDict) The altitude of each radar gate as calculated from the altitude of the radar and the Car
scan_rate	(dict or None) Actual antenna scan rate. If not provided this attribute is set to None, indicating this pa
antenna_transition	(dict or None) Flag indicating if the antenna is in transition, 1 = yes, 0 = no. If not provided this attrib
rotation	(dict or None) The rotation angle of the antenna. The angle about the aircraft longitudinal axis for a ve
tilt	(dict or None) The tilt angle with respect to the plane orthogonal (Z-axis) to aircraft longitudinal axis.
roll	(dict or None) The roll angle of platform, for aircraft right wing down is positive.
drift	(dict or None) Drift angle of antenna, the angle between heading and track.
heading	(dict or None) Heading (compass) angle, clockwise from north.
pitch	(dict or None) Pitch angle of antenna, for aircraft nose up is positive.
georefs_applied	(dict or None) Indicates whether the variables have had georeference calculation applied. Leading to E
instrument_parameters	(dict of dicts or None) Instrument parameters, if not provided this attribute is set to None, indicating th
radar_calibration	(dict of dicts or None) Instrument calibration parameters. If not provided this attribute is set to None,
ngates	(int) Number of gates (bins) in a ray.
nrays	(int) Number of rays in the volume.
nsweeps	(int) Number of sweep in the volume.

Methods

<code>add_field(field_name, dic[, replace_existing])</code>	Add a field to the object.
<code>add_field_like(existing_field_name, ..., ...)</code>	Add a field to the object with metadata from a existing field.

Continued on next page

Table 3.7 – continued from previous page

<code>check_field_exists(field_name)</code>	Check that a field exists in the fields dictionary.
<code>extract_sweeps(sweeps)</code>	Create a new radar contains only the data from select sweeps.
<code>get_azimuth(sweep[, copy])</code>	Return an array of azimuth angles for a given sweep.
<code>get_elevation(sweep[, copy])</code>	Return an array of elevation angles for a given sweep.
<code>get_end(sweep)</code>	Return the ending ray for a given sweep.
<code>get_field(sweep, field_name[, copy])</code>	Return the field data for a given sweep.
<code>get_gate_x_y_z(sweep[, edges, ...])</code>	Return the x, y and z gate locations in meters for a given sweep.
<code>get_nyquist_vel(sweep[, check_uniform])</code>	Return the Nyquist velocity in meters per second for a given sweep.
<code>get_slice(sweep)</code>	Return a slice for selecting rays for a given sweep.
<code>get_start(sweep)</code>	Return the starting ray index for a given sweep.
<code>get_start_end(sweep)</code>	Return the starting and ending ray for a given sweep.
<code>info([level, out])</code>	Print information on radar.
<code>init_gate_altitude()</code>	Initialize the gate_altitude attribute.
<code>init_gate_longitude_latitude()</code>	Initialize or reset the gate_longitude and gate_latitude attributes.
<code>init_gate_x_y_z()</code>	Initialize or reset the gate_{x, y, z} attributes.
<code>init_rays_per_sweep()</code>	Initialize or reset the rays_per_sweep attribute.
<code>iter_azimuth()</code>	Return an iterator which returns sweep azimuth data.
<code>iter_elevation()</code>	Return an iterator which returns sweep elevation data.
<code>iter_end()</code>	Return an iterator over the sweep end indices.
<code>iter_field(field_name)</code>	Return an iterator which returns sweep field data.
<code>iter_slice()</code>	Return an iterator which returns sweep slice objects.
<code>iter_start()</code>	Return an iterator over the sweep start indices.
<code>iter_start_end()</code>	Return an iterator over the sweep start and end indices.

__class__

alias of type

__delattr__

Implement delattr(self, name).

__dict__ = mappingproxy({'_check_sweep_in_range': <function Radar._check_sweep_in_range>, 'iter_start_end': <fu**__dir__** () → list

default dir() implementation

__eq__

Return self==value.

__format__ ()

default object formatter

__ge__

Return self>=value.

__getattr__

Return getattr(self, name).

__getstate__ ()

Return object's state which can be pickled.

__gt__

Return self>value.

__hash__
Return hash(self).

__init__ (*time, _range, fields, metadata, scan_type, latitude, longitude, altitude, sweep_number, sweep_mode, fixed_angle, sweep_start_ray_index, sweep_end_ray_index, azimuth, elevation, altitude_agl=None, target_scan_rate=None, rays_are_indexed=None, ray_angle_res=None, scan_rate=None, antenna_transition=None, instrument_parameters=None, radar_calibration=None, rotation=None, tilt=None, roll=None, drift=None, heading=None, pitch=None, georefs_applied=None*)

__le__
Return self<=value.

__lt__
Return self<value.

__module__ = 'pyart.core.radar'

__ne__
Return self!=value.

__new__ ()
Create and return a new object. See help(type) for accurate signature.

__reduce__ ()
helper for pickle

__reduce_ex__ ()
helper for pickle

__repr__
Return repr(self).

__setattr__
Implement setattr(self, name, value).

__setstate__ (*state*)
Restore unpicklable entries from pickled object.

__sizeof__ () → int
size of object in memory, in bytes

__str__
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

__check_sweep_in_range (*sweep*)
Check that a sweep number is in range.

__dic_info (*attr, level, out, dic=None, ident_level=0*)
Print information on a dictionary attribute.

add_field (*field_name, dic, replace_existing=False*)
Add a field to the object.

Parameters `field_name` : str

Name of the field to add to the dictionary of fields.

dic : dict

Dictionary contain field data and metadata.

replace_existing : bool

True to replace the existing field with key `field_name` if it exists, loosing any existing data. False will raise a `ValueError` when the field already exists.

add_field_like (*existing_field_name, field_name, data, replace_existing=False*)

Add a field to the object with metadata from a existing field.

Note that the data parameter is not copied by this method. If data refers to a 'data' array from an existing field dictionary, a copy should be made within or prior to using this method. If this is not done the 'data' key in both field dictionaries will point to the same NumPy array and modification of one will change the second. To copy NumPy arrays use the `copy()` method. See the Examples section for how to create a copy of the 'reflectivity' field as a field named 'reflectivity_copy'.

Parameters `existing_field_name` : str

Name of an existing field to take metadata from when adding the new field to the object.

field_name : str

Name of the field to add to the dictionary of fields.

data : array

Field data. A copy of this data is not made, see the note above.

replace_existing : bool

True to replace the existing field with key `field_name` if it exists, loosing any existing data. False will raise a `ValueError` when the field already exists.

Examples

```
>>> radar.add_field_like('reflectivity', 'reflectivity_copy',
...                      radar.fields['reflectivity']['data'].copy())
```

check_field_exists (*field_name*)

Check that a field exists in the fields dictionary.

If the field does not exist raise a `KeyError`.

Parameters `field_name` : str

Name of field to check.

extract_sweeps (*sweeps*)

Create a new radar contains only the data from select sweeps.

Parameters `sweeps` : array_like

Sweeps (0-based) to include in new Radar object.

Returns `radar` : Radar

Radar object which contains a copy of data from the selected sweeps.

get_azimuth (*sweep*, *copy=False*)

Return an array of azimuth angles for a given sweep.

Parameters *sweep* : int

Sweep number to retrieve data for, 0 based.

copy : bool, optional

True to return a copy of the azimuths. False, the default, returns a view of the azimuths (when possible), changing this data will change the data in the underlying Radar object.

Returns *azimuths* : array

Array containing the azimuth angles for a given sweep.

get_elevation (*sweep*, *copy=False*)

Return an array of elevation angles for a given sweep.

Parameters *sweep* : int

Sweep number to retrieve data for, 0 based.

copy : bool, optional

True to return a copy of the elevations. False, the default, returns a view of the elevations (when possible), changing this data will change the data in the underlying Radar object.

Returns *azimuths* : array

Array containing the elevation angles for a given sweep.

get_end (*sweep*)

Return the ending ray for a given sweep.

get_field (*sweep*, *field_name*, *copy=False*)

Return the field data for a given sweep.

When used with `get_gate_x_y_z()` this method can be used to obtain the data needed for plotting a radar field with the correct spatial context.

Parameters *sweep* : int

Sweep number to retrieve data for, 0 based.

field_name : str

Name of the field from which data should be retrieved.

copy : bool, optional

True to return a copy of the data. False, the default, returns a view of the data (when possible), changing this data will change the data in the underlying Radar object.

Returns *data* : array

Array containing data for the requested sweep and field.

get_gate_x_y_z (*sweep*, *edges=False*, *filter_transitions=False*)

Return the x, y and z gate locations in meters for a given sweep.

With the default parameter this method returns the same data as contained in the `gate_x`, `gate_y` and `gate_z` attributes but this method performs the gate location calculations only for the specified sweep and therefore is more efficient than accessing this data through these attribute.

When used with `get_field()` this method can be used to obtain the data needed for plotting a radar field with the correct spatial context.

Parameters `sweep` : int

Sweep number to retrieve gate locations from, 0 based.

edges : bool, optional

True to return the locations of the gate edges calculated by interpolating between the range, azimuths and elevations. False (the default) will return the locations of the gate centers with no interpolation.

filter_transitions : bool, optional

True to remove rays where the antenna was in transition between sweeps. False will include these rays. No rays will be removed if the `antenna_transition` attribute is not available (set to None).

Returns `x, y, z` : 2D array

Array containing the x, y and z, distances from the radar in meters for the center (or edges) for all gates in the sweep.

get_nyquist_vel (*sweep*, *check_uniform=True*)

Return the Nyquist velocity in meters per second for a given sweep.

Raises a `LookupError` if the Nyquist velocity is not available, an `Exception` is raised if the velocities are not uniform in the sweep unless `check_uniform` is set to False.

Parameters `sweep` : int

Sweep number to retrieve data for, 0 based.

check_uniform : bool

True to check to perform a check on the Nyquist velocities that they are uniform in the sweep, False will skip this check and return the velocity of the first ray in the sweep.

Returns `nyquist_velocity` : float

Array containing the Nyquist velocity in m/s for a given sweep.

get_slice (*sweep*)

Return a slice for selecting rays for a given sweep.

get_start (*sweep*)

Return the starting ray index for a given sweep.

get_start_end (*sweep*)

Return the starting and ending ray for a given sweep.

info (*level='standard'*, *out=<_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>*)

Print information on radar.

Parameters `level` : {'compact', 'standard', 'full', 'c', 's', 'f'}

Level of information on radar object to print, compact is minimal information, standard more and full everything.

out : file-like

Stream to direct output to, default is to print information to standard out (the screen).

init_gate_altitude ()

Initialize the `gate_altitude` attribute.

init_gate_longitude_latitude ()

Initialize or reset the `gate_longitude` and `gate_latitude` attributes.

init_gate_x_y_z()
Initialize or reset the gate_{x, y, z} attributes.

init_rays_per_sweep()
Initialize or reset the rays_per_sweep attribute.

iter_azimuth()
Return an iterator which returns sweep azimuth data.

iter_elevation()
Return an iterator which returns sweep elevation data.

iter_end()
Return an iterator over the sweep end indices.

iter_field(*field_name*)
Return an iterator which returns sweep field data.

iter_slice()
Return an iterator which returns sweep slice objects.

iter_start()
Return an iterator over the sweep start indices.

iter_start_end()
Return an iterator over the sweep start and end indices.

pyart.core.antenna_to_cartesian(*ranges, azimuths, elevations, debug=False*)
Return Cartesian coordinates from antenna coordinates.

Parameters **ranges** : array

Distances to the center of the radar gates (bins) in kilometers.

azimuths : array

Azimuth angle of the radar in degrees.

elevations : array

Elevation angle of the radar in degrees.

Returns **x, y, z** : array

Cartesian coordinates in meters from the radar.

Notes

The calculation for Cartesian coordinate is adapted from equations 2.28(b) and 2.28(c) of Doviak and Zrnic [R1] assuming a standard atmosphere (4/3 Earth's radius model).

$$\begin{aligned} z &= \sqrt{r^2 + R^2 + 2 * r * R * \sin(\theta_e)} - R \\ s &= R * \arcsin\left(\frac{r * \cos(\theta_e)}{R + z}\right) \\ x &= s * \sin(\theta_a) \\ y &= s * \cos(\theta_a) \end{aligned}$$

Where r is the distance from the radar to the center of the gate, θ_a is the azimuth angle, θ_e is the elevation angle, s is the arc length, and R is the effective radius of the earth, taken to be 4/3 the mean radius of earth (6371 km).

References

[R1]

`pyart.core.antenna_vectors_to_cartesian` (*ranges, azimuths, elevations, edges=False*)

Calculate Cartesian coordinate for gates from antenna coordinate vectors.

Calculates the Cartesian coordinates for the gate centers or edges for all gates from antenna coordinate vectors assuming a standard atmosphere (4/3 Earth's radius model). See `pyart.util.antenna_to_cartesian()` for details.

Parameters *ranges* : array, 1D.

Distances to the center of the radar gates (bins) in meters.

azimuths : array, 1D.

Azimuth angles of the rays in degrees.

elevations : array, 1D.

Elevation angles of the rays in degrees.

edges : bool, optional

True to calculate the coordinates of the gate edges by interpolating between gates and extrapolating at the boundaries. False to calculate the gate centers.

Returns *x, y, z* : array, 2D

Cartesian coordinates in meters from the center of the radar to the gate centers or edges.

`pyart.core.cartesian_to_antenna` (*x, y, z*)

Returns antenna coordinates from Cartesian coordinates.

Parameters *x, y, z* : array

Cartesian coordinates in meters from the radar.

Returns *ranges* : array

Distances to the center of the radar gates (bins) in m.

azimuths : array

Azimuth angle of the radar in degrees. [-180., 180]

elevations : array

Elevation angle of the radar in degrees.

`pyart.core.cartesian_to_geographic` (*x, y, projparams*)

Cartesian to Geographic coordinate transform.

Transform a set of Cartesian/Cartographic coordinates (*x, y*) to a geographic coordinate system (lat, lon) using `pyproj` or a build in Azimuthal equidistant projection.

Parameters *x, y* : array-like

Cartesian coordinates in meters unless *R* is defined in different units in the *projparams* parameter.

projparams : dict or str

Projection parameters passed to `pyproj.Proj`. If this parameter is a dictionary with a 'proj' key equal to 'pyart_aeqd' then an azimuthal equidistant projection will be used

that is native to Py-ART and does not require pyproj/basemap to be installed. In this case a non-default value of R can be specified by setting the 'R' key to the desired value.

Returns lon, lat : array

Longitude and latitude of the Cartesian coordinates in degrees.

`pyart.core.cartesian_to_geographic_aeqd(x, y, lon_0, lat_0, R=6370997.0)`

Azimuthal equidistant Cartesian to geographic coordinate transform.

Transform a set of Cartesian/Cartographic coordinates (x, y) to geographic coordinate system (lat, lon) using a azimuthal equidistant map projection [1].

$$\begin{aligned} lat &= \arcsin(\cos(c) * \sin(lat_0) + (y * \sin(c) * \cos(lat_0) / \rho)) \\ lon &= lon_0 + \arctan 2(x * \sin(c), \rho * \cos(lat_0) * \cos(c) - y * \sin(lat_0) * \sin(c)) \\ \rho &= \sqrt{x^2 + y^2} \\ c &= \rho / R \end{aligned}$$

Where x, y are the Cartesian position from the center of projection; lat, lon the corresponding latitude and longitude; lat_0, lon_0 are the latitude and longitude of the center of the projection; R is the radius of the earth (defaults to ~6371 km). lon is adjusted to be between -180 and 180.

Parameters x, y : array-like

Cartesian coordinates in the same units as R, typically meters.

lon_0, lat_0 : float

Longitude and latitude, in degrees, of the center of the projection.

R : float, optional

Earth radius in the same units as x and y. The default value is in units of meters.

Returns lon, lat : array

Longitude and latitude of Cartesian coordinates in degrees.

References

[R2]

`pyart.core.cartesian_vectors_to_geographic(x, y, projparams, edges=False)`

Cartesian vectors to Geographic coordinate transform.

Transform a set of Cartesian/Cartographic coordinate vectors (x, y) to a geographic coordinate system (lat, lon) using pyproj or a build in Azimuthal equidistant projection finding the coordinates edges in Cartesian space if requested.

Parameters x, y : array 1D.

Cartesian coordinate vectors in meters unless R is defined in different units in the projparams parameter.

projparams : dict or str

Projection parameters passed to pyproj.Proj. If this parameter is a dictionary with a 'proj' key equal to 'pyart_aeqd' then a azimuthal equidistant projection will be used that is native to Py-ART and does not require pyproj/basemap to be installed. In this case a non-default value of R can be specified by setting the 'R' key to the desired value.

edges : bool, optional

True to calculate the coordinates of the geographic edges by interpolating between Cartesian points and extrapolating at the boundaries. False to calculate the coordinate centers.

Returns *lon, lat* : array

Longitude and latitude of the Cartesian coordinates in degrees.

`pyart.core.geographic_to_cartesian(lon, lat, projparams)`

Geographic to Cartesian coordinate transform.

Transform a set of Geographic coordinate (*lat, lon*) to a Cartesian/Cartographic coordinate (*x, y*) using pyproj or a build in Azimuthal equidistant projection.

Parameters *lon, lat* : array-like

Geographic coordinates in degrees.

projparams : dict or str

Projection parameters passed to pyproj.Proj. If this parameter is a dictionary with a 'proj' key equal to 'pyart_aeqd' then a azimuthal equidistant projection will be used that is native to Py-ART and does not require pyproj/basemap to be installed. In this case a non-default value of R can be specified by setting the 'R' key to the desired value.

Returns *x, y* : array-like

Cartesian coordinates in meters unless projparams defines a value for R in different units

`pyart.core.geographic_to_cartesian_aeqd(lon, lat, lon_0, lat_0, R=6370997.0)`

Azimuthal equidistant geographic to Cartesian coordinate transform.

Transform a set of geographic coordinates (*lat, lon*) to Cartesian/Cartographic coordinates (*x, y*) using a azimuthal equidistant map projection [1].

$$\begin{aligned}x &= R * k * \cos(lat) * \sin(lon - lon_0) \\y &= R * k * [\cos(lat_0) * \sin(lat) - \sin(lat_0) * \cos(lat) * \cos(lon - lon_0)] \\k &= c / \sin(c) \\c &= \arccos(\sin(lat_0) * \sin(lat) + \cos(lat_0) * \cos(lat) * \cos(lon - lon_0))\end{aligned}$$

Where *x, y* are the Cartesian position from the center of projection; *lat, lon* the corresponding latitude and longitude; *lat_0, lon_0* are the latitude and longitude of the center of the projection; *R* is the radius of the earth (defaults to ~6371 km).

Parameters *lon, lat* : array-like

Longitude and latitude coordinates in degrees.

lon_0, lat_0 : float

Longitude and latitude, in degrees, of the center of the projection.

R : float, optional

Earth radius in the same units as *x* and *y*. The default value is in units of meters.

Returns *x, y* : array

Cartesian coordinates in the same units as *R*, typically meters.

References

[R3]

`pyart.core.wgs84_to_swissCH1903(lon, lat, alt, no_altitude_transform=False)`

Convert WGS84 coordinates to swiss coordinates (CH1903 / LV03)

The formulas for the coordinates transformation are taken from: “Formeln und Konstanten für die Berechnung der Schweizerischen schiefachsigen Zylinderprojektion und der Transformation zwischen Koordinatensystemen”, chapter 4. “Näherungslösungen CH1903 <=> WGS84” Bundesamt für Landestopografie swisstopo (<http://www.swisstopo.admin.ch>), Oktober 2008

Parameters `lon, lat` : array-like

Geographic coordinates WGS84 in degrees.

`alt` : array-like

Altitude in m

`no_altitude_transform` : bool

If set, do not convert altitude

Returns `chy, chx, chh` : array-like

Coordinates in swiss CH1903 coordinates in meter

BRIDGING TO OTHER TOOLKITS (PYART . BRIDGE)

Py-ART can act as bridge to other community software projects.

The functionality in this namespace is available in other pyart namespaces.

4.1 Phase functions

<code>texture_of_complex_phase(radar[, ...])</code>	Calculate the texture of the differential phase field.
---	--

FILTERS (PYART.FILTERS)

Classes for specifying what gates are included and excluded from routines.

5.1 Filtering radar data

<i>GateFilter</i> (radar[, exclude_based])	A class for building a boolean arrays for filtering gates based on a set of condition typically based on the values in the radar fields.
<i>moment_based_gate_filter</i> (radar[, ncp_field, ...])	Create a filter which removes undesired gates based on moments.
<i>moment_and_texture_based_gate_filter</i> (radar)	Create a filter which removes undesired gates based on texture of moments.
<i>snr_based_gate_filter</i> (radar[, snr_field, ...])	Create a filter which removes undesired gates based on SNR.
<i>visibility_based_gate_filter</i> (radar[, ...])	Create a filter which removes undesired gates based on visibility.
<i>class_based_gate_filter</i> (radar[, field, ...])	Create a filter which removes undesired gates based on class values
<i>temp_based_gate_filter</i> (radar[, temp_field, ...])	Create a filter which removes undesired gates based on temperature.
<i>iso0_based_gate_filter</i> (radar[, iso0_field, ...])	Create a filter which removes undesired gates based height over the iso0.
<i>calculate_velocity_texture</i> (radar[, ...])	Derive the texture of the velocity field

class `pyart.filters.GateFilter` (*radar*, *exclude_based=True*)

Bases: `object`

A class for building a boolean arrays for filtering gates based on a set of condition typically based on the values in the radar fields. These filter can be used in various algorithms and calculations within Py-ART.

See `pyart.correct.GateFilter.exclude_below()` for method parameter details.

Parameters `radar` : Radar

Radar object from which gate filter will be build.

exclude_based : bool, optional

True, the default and suggested method, will begin with all gates included and then use the exclude methods to exclude gates based on conditions. False will begin with all gates excluded from which a set of gates to include should be set using the include methods.

Examples

```
>>> import pyart
>>> radar = pyart.io.read('radar_file.nc')
>>> gatefilter = pyart.correct.GateFilter(radar)
>>> gatefilter.exclude_below('reflectivity', 10)
>>> gatefilter.exclude_below('normalized_coherent_power', 0.75)
```

Attributes

<code>gate_excluded</code>	array, dtype=bool) Boolean array indicating if a gate should be excluded from a calculation. Elements marked True indicate the corresponding gate should be excluded. Those marked False should be included. This is read-only attribute, any changes to the array will NOT be reflected in <code>gate_included</code> and will be lost when the attribute is accessed again.
<code>gate_included</code>	array, dtype=bool) Boolean array indicating if a gate should be included in a calculation. Elements marked True indicate the corresponding gate should be include. Those marked False should be excluded. This is read-only attribute, any changes to the array will NOT be reflected in <code>gate_excluded</code> and will be lost when the attribute is accessed again.

Methods

<code>copy()</code>	Return a copy of the gatefilter.
<code>exclude_above(field, value[, ...])</code>	Exclude gates where a given field is above a given value.
<code>exclude_all()</code>	Exclude all gates.
<code>exclude_below(field, value[, ...])</code>	Exclude gates where a given field is below a given value.
<code>exclude_equal(field, value[, exclude_masked, op])</code>	Exclude gates where a given field is equal to a value.
<code>exclude_gates(mask[, exclude_masked, op])</code>	Exclude gates where a given mask is equal True.
<code>exclude_inside(field, v1, v2[, ...])</code>	Exclude gates where a given field is inside a given interval.
<code>exclude_invalid(field[, exclude_masked, op])</code>	Exclude gates where an invalid value occurs in a field (NaNs or infs).
<code>exclude_masked(field[, exclude_masked, op])</code>	Exclude gates where a given field is masked.
<code>exclude_none()</code>	Exclude no gates, include all gates.
<code>exclude_not_equal(field, value[, ...])</code>	Exclude gates where a given field is not equal to a value.
<code>exclude_outside(field, v1, v2[, ...])</code>	Exclude gates where a given field is outside a given interval.
<code>exclude_transition([trans_value, ...])</code>	Exclude all gates in rays marked as in transition between sweeps.
<code>include_above(field, value[, ...])</code>	Include gates where a given field is above a given value.
<code>include_all()</code>	Include all gates.
<code>include_below(field, value[, ...])</code>	Include gates where a given field is below a given value.
<code>include_equal(field, value[, exclude_masked, op])</code>	Include gates where a given field is equal to a value.
<code>include_gates(mask[, exclude_masked, op])</code>	Include gates where a given mask is equal True.
<code>include_inside(field, v1, v2[, ...])</code>	Include gates where a given field is inside a given interval.
<code>include_none()</code>	Include no gates, exclude all gates.
<code>include_not_equal(field, value[, ...])</code>	Include gates where a given field is not equal to a value.
<code>include_not_masked(field[, exclude_masked, op])</code>	Include gates where a given field in not masked.

Continued on next page

Table 5.2 – continued from previous page

<i>include_not_transition</i> ([trans_value, ...])	Include all gates in rays not marked as in transition between sweeps.
<i>include_outside</i> (field, v1, v2[, ...])	Include gates where a given field is outside a given interval.
<i>include_valid</i> (field[, exclude_masked, op])	Include gates where a valid value occurs in a field (not NaN or inf).

__class__

alias of type

__delattr__

Implement delattr(self, name).

__dict__ = mappingproxy({'exclude_transition': <function GateFilter.exclude_transition>, 'include_above': <function**__dir__** () → list

default dir() implementation

__eq__

Return self==value.

__format__ ()

default object formatter

__ge__

Return self>=value.

__getattr__

Return getattr(self, name).

__gt__

Return self>value.

__hash__

Return hash(self).

__init__ (radar, exclude_based=True)

initialize

__le__

Return self<=value.

__lt__

Return self<value.

__module__ = 'pyart.filters.gatefilter'**__ne__**

Return self!=value.

__new__ ()

Create and return a new object. See help(type) for accurate signature.

__reduce__ ()

helper for pickle

__reduce_ex__ ()

helper for pickle

__repr__

Return repr(self).

__setattr__
Implement setattr(self, name, value).

__sizeof__ () → int
size of object in memory, in bytes

__str__
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

_get_fdata (field)
Check that the field exists and retrieve field data.

_merge (marked, op, exclude_masked)
Merge an array of marked gates with the exclude array.

copy ()
Return a copy of the gatefilter.

exclude_above (field, value, exclude_masked=True, op='or', inclusive=False)
Exclude gates where a given field is above a given value.

exclude_all ()
Exclude all gates.

exclude_below (field, value, exclude_masked=True, op='or', inclusive=False)
Exclude gates where a given field is below a given value.

Parameters **field** : str

Name of field compared against the value.

value : float

Gates with a value below this value in the specified field will be marked for exclusion in the filter.

exclude_masked : bool, optional

True to filter masked values in the specified field if the data is a masked array, False to include any masked values.

op : {'and', 'or', 'new'}

Operation to perform when merging the existing set of excluded gates with the excluded gates from the current operation. 'and' will perform a logical AND operation, 'or' a logical OR, and 'new' will replace the existing excluded gates with the one generated here. 'or', the default for exclude methods, is typically desired when building up a set of conditions for excluding gates where the desired effect is to exclude gates which meet any of the conditions. 'and', the default for include methods, is typically desired when building up a set of conditions where the desired effect is to include gates which meet any of the conditions. Note that the 'and' method MAY results in including gates which have previously been excluded because they were masked or invalid.

inclusive : bool

Indicates whether the specified value should also be excluded.

exclude_equal (*field, value, exclude_masked=True, op='or'*)

Exclude gates where a given field is equal to a value.

exclude_gates (*mask, exclude_masked=True, op='or'*)

Exclude gates where a given mask is equal True.

Parameters mask : numpy array

Boolean numpy array with same shape as a field array.

exclude_masked : bool, optional

True to filter masked values in the specified mask if it is a masked array, False to include any masked values.

op : {'and', 'or', 'new'}

Operation to perform when merging the existing set of excluded gates with the excluded gates from the current operation. 'and' will perform a logical AND operation, 'or' a logical OR, and 'new' will replace the existing excluded gates with the one generated here. 'or', the default for exclude methods, is typically desired when building up a set of conditions for excluding gates where the desired effect is to exclude gates which meet any of the conditions. 'and', the default for include methods, is typically desired when building up a set of conditions where the desired effect is to include gates which meet any of the conditions. Note that the 'and' method MAY results in including gates which have previously been excluded because they were masked or invalid.

exclude_inside (*field, v1, v2, exclude_masked=True, op='or', inclusive=True*)

Exclude gates where a given field is inside a given interval.

exclude_invalid (*field, exclude_masked=True, op='or'*)

Exclude gates where an invalid value occurs in a field (NaNs or infs).

exclude_masked (*field, exclude_masked=True, op='or'*)

Exclude gates where a given field is masked.

exclude_none ()

Exclude no gates, include all gates.

exclude_not_equal (*field, value, exclude_masked=True, op='or'*)

Exclude gates where a given field is not equal to a value.

exclude_outside (*field, v1, v2, exclude_masked=True, op='or', inclusive=False*)

Exclude gates where a given field is outside a given interval.

exclude_transition (*trans_value=1, exclude_masked=True, op='or'*)

Exclude all gates in rays marked as in transition between sweeps.

Exclude all gates in rays marked as "in transition" by the antenna_transition attribute of the radar used to construct the filter. If no antenna transition information is available no gates are excluded.

Parameters trans_value : int, optional

Value used in the antenna transition data to indicate that the instrument was between sweeps (in transition) during the collection of a specific ray. Typically a value of 1 is used to indicate this transition and the default can be used in these cases.

exclude_masked : bool, optional

True to filter masked values in antenna_transition if the data is a masked array, False to include any masked values.

op : { 'and', 'or', 'new' }

Operation to perform when merging the existing set of excluded gates with the excluded gates from the current operation. 'and' will perform a logical AND operation, 'or' a logical OR, and 'new' will replace the existing excluded gates with the one generated here. 'or', the default for exclude methods, is typically desired when building up a set of conditions for excluding gates where the desired effect is to exclude gates which meet any of the conditions. 'and', the default for include methods, is typically desired when building up a set of conditions where the desired effect is to include gates which meet any of the conditions. Note that the 'and' method MAY results in including gates which have previously been excluded because they were masked or invalid.

gate_excluded

gate_included

include_above (*field, value, exclude_masked=True, op='and', inclusive=False*)

Include gates where a given field is above a given value.

include_all ()

Include all gates.

include_below (*field, value, exclude_masked=True, op='and', inclusive=False*)

Include gates where a given field is below a given value.

include_equal (*field, value, exclude_masked=True, op='and'*)

Include gates where a given field is equal to a value.

include_gates (*mask, exclude_masked=True, op='and'*)

Include gates where a given mask is equal True.

Parameters mask : numpy array

Boolean numpy array with same shape as a field array.

exclude_masked : bool, optional

True to filter masked values in the specified mask if it is a masked array, False to include any masked values.

op : { 'and', 'or', 'new' }

Operation to perform when merging the existing set of excluded gates with the excluded gates from the current operation. 'and' will perform a logical AND operation, 'or' a logical OR, and 'new' will replace the existing excluded gates with the one generated here. 'or', the default for exclude methods, is typically desired when building up a set of conditions for excluding gates where the desired effect is to exclude gates which meet any of the conditions. 'and', the default for include methods, is typically desired when building up a set of conditions where the desired effect is to include gates which meet any of the conditions. Note that the 'or' method MAY results in excluding gates which have previously been included.

include_inside (*field, v1, v2, exclude_masked=True, op='and', inclusive=True*)

Include gates where a given field is inside a given interval.

include_none ()

Include no gates, exclude all gates.

include_not_equal (*field, value, exclude_masked=True, op='and'*)

Include gates where a given field is not equal to a value.

include_not_masked (*field, exclude_masked=True, op='and'*)

Include gates where a given field in not masked.

include_not_transition (*trans_value=0, exclude_masked=True, op='and'*)

Include all gates in rays not marked as in transition between sweeps.

Include all gates in rays not marked as “in transition” by the `antenna_transition` attribute of the radar used to construct the filter. If no antenna transition information is available all gates are included.

Parameters `trans_value` : int, optional

Value used in the antenna transition data to indicate that the instrument is not between sweeps (in transition) during the collection of a specific ray. Typically a value of 0 is used to indicate no transition and the default can be used in these cases.

exclude_masked : bool, optional

True to filter masked values in `antenna_transition` if the data is a masked array, False to include any masked values.

op : { 'and', 'or', 'new' }

Operation to perform when merging the existing set of excluded gates with the excluded gates from the current operation. 'and' will perform a logical AND operation, 'or' a logical OR, and 'new' will replace the existing excluded gates with the one generated here. 'or', the default for exclude methods, is typically desired when building up a set of conditions for excluding gates where the desired effect is to exclude gates which meet any of the conditions. 'and', the default for include methods, is typically desired when building up a set of conditions where the desired effect is to include gates which meet any of the conditions. Note that the 'or' method MAY result in excluding gates which have previously been included.

include_outside (*field, v1, v2, exclude_masked=True, op='and', inclusive=False*)

Include gates where a given field is outside a given interval.

include_valid (*field, exclude_masked=True, op='and'*)

Include gates where a valid value occurs in a field (not NaN or inf).

`pyart.filters.calculate_velocity_texture` (*radar, vel_field=None, wind_size=4, nyq=None, check_nyq_uniform=True*)

Derive the texture of the velocity field

Parameters `radar`: Radar

Radar object from which velocity texture field will be made.

vel_field_name : str

Name of the velocity field. A value of None will force Py-ART to automatically determine the name of the velocity field.

wind_size : int

The size of the window to calculate texture from. The window is defined to be a square of size `wind_size` by `wind_size`.

nyq : float

The nyquist velocity of the radar. A value of None will force Py-ART to try and determine this automatically.

check_nyquist_uniform : bool, optional

True to check if the Nyquist velocities are uniform for all rays within a sweep, False will skip this check. This parameter is ignored when the `nyq` parameter is not None.

Returns `vel_dict`: dict

A dictionary containing the field entries for the radial velocity texture.

`pyart.filters.class_based_gate_filter(radar, field=None, kept_values=None)`

Create a filter which removes undesired gates based on class values

Parameters `radar` : Radar

Radar object from which the gate filter will be built.

field : str

Name of the radar field which contains the classification. A value of None for will use the default field name for the hydrometeor classification as defined in the Py-ART configuration file.

kept_values : list of ints or none

The class values to keep

Returns `gatefilter` : *GateFilter*

A gate filter based upon the described criteria. This can be used as a gatefilter parameter to various functions in `pyart.correct`.

`pyart.filters.iso0_based_gate_filter(radar, iso0_field=None, max_h_iso0=0.0, thickness=400.0, beamwidth=None)`

Create a filter which removes undesired gates based height over the iso0. Used primarily to filter out the melting layer and gates above it.

Parameters `radar` : Radar

Radar object from which the gate filter will be built.

iso0_field : str

Name of the radar field which contains the height relative to the iso0. A value of None for will use the default field name as defined in the Py-ART configuration file.

max_h_iso0 : float

Maximum height relative to the iso0 in m. Gates below this limits as well as gates which are masked or contain invalid values will be excluded and not used in calculation which use the filter. A value of None will disable filtering based upon the field including removing masked or gates with an invalid value. To disable the thresholding but retain the masked and invalid filter set the parameter to a value below the lowest value in the field.

thickness : float

The estimated thickness of the melting layer in m

beamwidth : float

The radar antenna 3 dB beamwidth [deg]

Returns `gatefilter` : *GateFilter*

A gate filter based upon the described criteria. This can be used as a gatefilter parameter to various functions in `pyart.correct`.

```
pyart.filters.moment_and_texture_based_gate_filter(radar,
                                                    zdr_field=None,
                                                    rhv_field=None,
                                                    phi_field=None, refl_field=None,
                                                    textzdr_field=None,
                                                    textrhv_field=None,
                                                    textphi_field=None,      tex-
                                                    trefl_field=None,   wind_size=7,
                                                    max_textphi=20.0,
                                                    max_textrhv=0.3,
                                                    max_textzdr=2.85,
                                                    max_textrefl=8.0, min_rhv=0.6)
```

Create a filter which removes undesired gates based on texture of moments.

Creates a gate filter in which the following gates are excluded: * Gates where the instrument is transitioning between sweeps. * Gates where RhoHV is below min_rhv * Gates where the PhiDP texture is above max_textphi. * Gates where the RhoHV texture is above max_textrhv. * Gates where the ZDR texture is above max_textzdr * Gates where the reflectivity texture is above max_textrefl * If any of the thresholds is not set or the field (RhoHV, ZDR, PhiDP, reflectivity) do not exist in the radar the filter is not applied.

Parameters radar : Radar

Radar object from which the gate filter will be built.

zdr_field, rhv_field, phi_field, refl_field : str

Names of the radar fields which contain the differential reflectivity, cross correlation ratio, differential phase and reflectivity from which the textures will be computed. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file.

textzdr_field, textrhv_field, textphi_field, textrefl_field : str

Names of the radar fields given to the texture of the differential reflectivity, texture of the cross correlation ratio, texture of differential phase and texture of reflectivity. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file

wind_size : int

Size of the moving window used to compute the ray texture.

max_textphi, max_textrhv, max_textzdr, max_textrefl : float

Maximum value for the texture of the differential phase, texture of RhoHV, texture of Zdr and texture of reflectivity. Gates in these fields above these limits as well as gates which are masked or contain invalid values will be excluded and not used in calculation which use the filter. A value of None will disable filtering based upon the given field including removing masked or gates with an invalid value. To disable the thresholding but retain the masked and invalid filter set the parameter to a value above the highest value in the field.

min_rhv : float

Minimum value for the RhoHV. Gates below this limits as well as gates which are masked or contain invalid values will be excluded and not used in calculation which use the filter. A value of None will disable filtering based upon the given field including removing masked or gates with an invalid value. To disable the thresholding but retain the masked and invalid filter set the parameter to a value below the lowest value in the field.

Returns gatefilter : *GateFilter*

A gate filter based upon the described criteria. This can be used as a gatefilter parameter to various functions in `pyart.correct`.

```
pyart.filters.moment_based_gate_filter(radar, ncp_field=None, rhv_field=None,
                                       refl_field=None, min_ncp=0.5, min_rhv=None,
                                       min_refl=-20.0, max_refl=100.0)
```

Create a filter which removes undesired gates based on moments.

Creates a gate filter in which the following gates are excluded:

- Gates where the instrument is transitioning between sweeps.
- Gates where the reflectivity is outside the interval `min_refl`, `max_refl`.
- Gates where the normalized coherent power is below `min_ncp`.
- Gates where the cross correlation ratio is below `min_rhi`. Using the default parameter this filtering is disabled.
- Gates where any of the above three fields are masked or contain invalid values (NaNs or infs).
- If any of these three fields do not exist in the radar that fields filter criteria is not applied.

Parameters `radar` : Radar

Radar object from which the gate filter will be built.

refl_field, ncp_field, rhv_field : str

Names of the radar fields which contain the reflectivity, normalized coherent power (signal quality index) and cross correlation ratio (RhoHV) from which the gate filter will be created using the above criteria. A value of `None` for any of these parameters will use the default field name as defined in the Py-ART configuration file.

min_ncp, min_rhv : float

Minimum values for the normalized coherence power and cross correlation ratio. Gates in these fields below these limits as well as gates which are masked or contain invalid values will be excluded and not used in calculation which use the filter. A value of `None` will disable filtering based upon the given field including removing masked or gates with an invalid value. To disable the thresholding but retain the masked and invalid filter set the parameter to a value below the lowest value in the field.

min_refl, max_refl : float

Minimum and maximum values for the reflectivity. Gates outside of this interval as well as gates which are masked or contain invalid values will be excluded and not used in calculation which use this filter. A value or `None` for one of these parameters will disable the minimum or maximum filtering but retain the other. A value of `None` for both of these values will disable all filtering based upon the reflectivity including removing masked or gates with an invalid value. To disable the interval filtering but retain the masked and invalid filter set the parameters to values above and below the lowest and greatest values in the reflectivity field.

Returns `gatefilter` : *GateFilter*

A gate filter based upon the described criteria. This can be used as a gatefilter parameter to various functions in `pyart.correct`.

```
pyart.filters.snr_based_gate_filter(radar, snr_field=None, min_snr=10.0, max_snr=None)
```

Create a filter which removes undesired gates based on SNR.

Parameters `radar` : Radar

Radar object from which the gate filter will be built.

snr_field : str

Name of the radar field which contains the signal to noise ratio. A value of None for will use the default field name as defined in the Py-ART configuration file.

min_snr : float

Minimum value for the SNR. Gates below this limits as well as gates which are masked or contain invalid values will be excluded and not used in calculation which use the filter. A value of None will disable filtering based upon the field including removing masked or gates with an invalid value. To disable the thresholding but retain the masked and invalid filter set the parameter to a value below the lowest value in the field.

max_snr : float

Maximum value for the SNR

Returns *gatefilter* : *GateFilter*

A gate filter based upon the described criteria. This can be used as a gatefilter parameter to various functions in `pyart.correct`.

`pyart.filters.temp_based_gate_filter(radar, temp_field=None, min_temp=0.0, thickness=400.0, beamwidth=None)`

Create a filter which removes undesired gates based on temperature. Used primarily to filter out the melting layer and gates above it.

Parameters *radar* : Radar

Radar object from which the gate filter will be built.

temp_field : str

Name of the radar field which contains the temperature. A value of None for will use the default field name as defined in the Py-ART configuration file.

min_temp : float

Minimum value for the temperature in degrees. Gates below this limits as well as gates which are masked or contain invalid values will be excluded and not used in calculation which use the filter. A value of None will disable filtering based upon the field including removing masked or gates with an invalid value. To disable the thresholding but retain the masked and invalid filter set the parameter to a value below the lowest value in the field.

thickness : float

The estimated thickness of the melting layer in m

beamwidth : float

The radar antenna 3 dB beamwidth [deg]

Returns *gatefilter* : *GateFilter*

A gate filter based upon the described criteria. This can be used as a gatefilter parameter to various functions in `pyart.correct`.

`pyart.filters.visibility_based_gate_filter(radar, vis_field=None, min_vis=10.0)`

Create a filter which removes undesired gates based on visibility.

Parameters *radar* : Radar

Radar object from which the gate filter will be built.

vis_field : str

Name of the radar field which contains the visibility. A value of None for will use the default field name as defined in the Py-ART configuration file.

min_vis : float

Minimum value for the visibility. Gates below this limits as well as gates which are masked or contain invalid values will be excluded and not used in calculation which use the filter. A value of None will disable filtering based upon the field including removing masked or gates with an invalid value. To disable the thresholding but retain the masked and invalid filter set the parameter to a value below the lowest value in the field.

Returns **gatefilter** : *GateFilter*

A gate filter based upon the described criteria. This can be used as a gatefilter parameter to various functions in `pyart.correct`.

RADAR CORRECTIONS (PYART.CORRECT)

Correct radar fields.

6.1 Velocity unfolding

<code>dealias_fourdd(radar[, last_radar, ...])</code>	Dealias Doppler velocities using the 4DD algorithm.
<code>dealias_unwrap_phase(radar[, unwrap_unit, ...])</code>	Dealias Doppler velocities using multi-dimensional phase unwrapping.
<code>dealias_region_based(radar[, ref_vel_field, ...])</code>	Dealias Doppler velocities using a region based algorithm.

6.2 Other corrections

<code>calculate_attenuation_zphi(radar[, doc, ...])</code>	Calculate the attenuation and the differential attenuation from a polarimetric radar using Z-PHI method..
<code>calculate_attenuation_philinear(radar[, ...])</code>	Calculate the attenuation and the differential attenuation from a polarimetric radar using linear dependence with PhiDP.
<code>phase_proc_lp(radar, offset[, debug, ...])</code>	Phase process using a LP method [1].
<code>det_sys_phase_ray(radar[, ind_rmin, ...])</code>	Public method Alternative determination of the system phase.
<code>correct_sys_phase(radar[, ind_rmin, ...])</code>	correction of the system offset. Public method
<code>smooth_phidp_single_window(radar[, ...])</code>	correction of the system offset and smoothing using one window
<code>smooth_phidp_double_window(radar[, ...])</code>	correction of the system offset and smoothing using two window
<code>despeckle_field(radar, field[, label_dict, ...])</code>	Despeckle a radar volume by identifying small objects in each scan and masking them out.
<code>correct_noise_rhohv(radar[, urhohv_field, ...])</code>	Corrects RhoHV for noise according to eq.
<code>correct_bias(radar[, bias, field_name])</code>	Corrects a radar data bias.
<code>correct_visibility(radar[, vis_field, ...])</code>	Corrects the reflectivity according to visibility.
<code>est_rhohv_rain(radar[, ind_rmin, ind_rmax, ...])</code>	Estimates the quantiles of RhoHV in rain for each sweep
<code>est_zdr_precip(radar[, ind_rmin, ind_rmax, ...])</code>	Filters out all undesired data to be able to estimate ZDR bias, either in
<code>est_zdr_snow(radar[, ind_rmin, ind_rmax, ...])</code>	Filters out all undesired data to be able to estimate ZDR bias in snow

Continued on next page

Table 6.2 – continued from previous page

<code>selfconsistency_bias</code> (radar, zdr_kdpzh_dict)	Estimates reflectivity bias at each ray using the self-consistency
<code>selfconsistency_kdp_phidp</code> (radar, zdr_kdpzh_dict)	Estimates KDP and PhiDP in rain from Zh and ZDR using a selfconsistency relation between ZDR, Zh and KDP.
<code>get_sun_hits</code> (radar[, delev_max, dazim_max, ...])	get data from suspected sun hits
<code>sun_retrieval</code> (az_rad, az_sun, el_rad, ..., ...)	Estimates sun parameters from sun hits

6.3 Helper functions

<code>find_objects</code> (radar, field, threshold[, ...])	Find objects (i.e., contiguous gates) in one or more sweeps that match thresholds.
<code>get_mask_fzl</code> (radar[, fzl, doc, min_temp, ...])	constructs a mask to mask data placed thickness m below data at min_temp
<code>sun_power</code> (solar_flux, pulse_width, wavelen, ...)	computes the theoretical sun power detected at the antenna [dBm] as it

class `pyart.correct.GateFilter`(*radar*, *exclude_based=True*)

Bases: `object`

A class for building a boolean arrays for filtering gates based on a set of condition typically based on the values in the radar fields. These filter can be used in various algorithms and calculations within Py-ART.

See `pyart.correct.GateFilter.exclude_below()` for method parameter details.

Parameters `radar` : `Radar`

Radar object from which gate filter will be build.

exclude_based : `bool`, optional

True, the default and suggested method, will begin with all gates included and then use the exclude methods to exclude gates based on conditions. False will begin with all gates excluded from which a set of gates to include should be set using the include methods.

Examples

```
>>> import pyart
>>> radar = pyart.io.read('radar_file.nc')
>>> gatefilter = pyart.correct.GateFilter(radar)
>>> gatefilter.exclude_below('reflectivity', 10)
>>> gatefilter.exclude_below('normalized_coherent_power', 0.75)
```

Attributes

<code>gate_excluded</code>	ndarray, dtype=bool) Boolean array indicating if a gate should be excluded from a calculation. Elements marked True indicate the corresponding gate should be excluded. Those marked False should be included. This is read-only attribute, any changes to the array will NOT be reflected in <code>gate_included</code> and will be lost when the attribute is accessed again.
<code>gate_included</code>	ndarray, dtype=bool) Boolean array indicating if a gate should be included in a calculation. Elements marked True indicate the corresponding gate should be include. Those marked False should be excluded. This is read-only attribute, any changes to the array will NOT be reflected in <code>gate_excluded</code> and will be lost when the attribute is accessed again.

Methods

<code>copy()</code>	Return a copy of the gatefilter.
<code>exclude_above(field, value[, ...])</code>	Exclude gates where a given field is above a given value.
<code>exclude_all()</code>	Exclude all gates.
<code>exclude_below(field, value[, ...])</code>	Exclude gates where a given field is below a given value.
<code>exclude_equal(field, value[, exclude_masked, op])</code>	Exclude gates where a given field is equal to a value.
<code>exclude_gates(mask[, exclude_masked, op])</code>	Exclude gates where a given mask is equal True.
<code>exclude_inside(field, v1, v2[, ...])</code>	Exclude gates where a given field is inside a given interval.
<code>exclude_invalid(field[, exclude_masked, op])</code>	Exclude gates where an invalid value occurs in a field (NaNs or infs).
<code>exclude_masked(field[, exclude_masked, op])</code>	Exclude gates where a given field is masked.
<code>exclude_none()</code>	Exclude no gates, include all gates.
<code>exclude_not_equal(field, value[, ...])</code>	Exclude gates where a given field is not equal to a value.
<code>exclude_outside(field, v1, v2[, ...])</code>	Exclude gates where a given field is outside a given interval.
<code>exclude_transition([trans_value, ...])</code>	Exclude all gates in rays marked as in transition between sweeps.
<code>include_above(field, value[, ...])</code>	Include gates where a given field is above a given value.
<code>include_all()</code>	Include all gates.
<code>include_below(field, value[, ...])</code>	Include gates where a given field is below a given value.
<code>include_equal(field, value[, exclude_masked, op])</code>	Include gates where a given field is equal to a value.
<code>include_gates(mask[, exclude_masked, op])</code>	Include gates where a given mask is equal True.
<code>include_inside(field, v1, v2[, ...])</code>	Include gates where a given field is inside a given interval.
<code>include_none()</code>	Include no gates, exclude all gates.
<code>include_not_equal(field, value[, ...])</code>	Include gates where a given field is not equal to a value.
<code>include_not_masked(field[, exclude_masked, op])</code>	Include gates where a given field in not masked.
<code>include_not_transition([trans_value, ...])</code>	Include all gates in rays not marked as in transition between sweeps.
<code>include_outside(field, v1, v2[, ...])</code>	Include gates where a given field is outside a given interval.
<code>include_valid(field[, exclude_masked, op])</code>	Include gates where a valid value occurs in a field (not NaN or inf).

`__class__`
alias of type

__delattr__
Implement delattr(self, name).

__dict__ = mappingproxy({'exclude_transition': <function GateFilter.exclude_transition>, 'include_above': <function

__dir__ () → list
default dir() implementation

__eq__
Return self==value.

__format__ ()
default object formatter

__ge__
Return self>=value.

__getattr__
Return getattr(self, name).

__gt__
Return self>value.

__hash__
Return hash(self).

__init__ (radar, exclude_based=True)
initialize

__le__
Return self<=value.

__lt__
Return self<value.

__module__ = 'pyart.filters.gatefilter'

__ne__
Return self!=value.

__new__ ()
Create and return a new object. See help(type) for accurate signature.

__reduce__ ()
helper for pickle

__reduce_ex__ ()
helper for pickle

__repr__
Return repr(self).

__setattr__
Implement setattr(self, name, value).

__sizeof__ () → int
size of object in memory, in bytes

__str__
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by `abc.ABCMeta.__subclasscheck__()`. It should return `True`, `False` or `NotImplemented`. If it returns `NotImplemented`, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

`__weakref__`

list of weak references to the object (if defined)

`__get_fdata` (*field*)

Check that the field exists and retrieve field data.

`__merge` (*marked*, *op*, *exclude_masked*)

Merge an array of marked gates with the exclude array.

`copy` ()

Return a copy of the gatefilter.

`exclude_above` (*field*, *value*, *exclude_masked=True*, *op='or'*, *inclusive=False*)

Exclude gates where a given field is above a given value.

`exclude_all` ()

Exclude all gates.

`exclude_below` (*field*, *value*, *exclude_masked=True*, *op='or'*, *inclusive=False*)

Exclude gates where a given field is below a given value.

Parameters *field* : str

Name of field compared against the value.

value : float

Gates with a value below this value in the specified field will be marked for exclusion in the filter.

exclude_masked : bool, optional

True to filter masked values in the specified field if the data is a masked array, False to include any masked values.

op : {'and', 'or', 'new'}

Operation to perform when merging the existing set of excluded gates with the excluded gates from the current operation. 'and' will perform a logical AND operation, 'or' a logical OR, and 'new' will replace the existing excluded gates with the one generated here. 'or', the default for exclude methods, is typically desired when building up a set of conditions for excluding gates where the desired effect is to exclude gates which meet any of the conditions. 'and', the default for include methods, is typically desired when building up a set of conditions where the desired effect is to include gates which meet any of the conditions. Note that the 'and' method MAY results in including gates which have previously been excluded because they were masked or invalid.

inclusive : bool

Indicates whether the specified value should also be excluded.

`exclude_equal` (*field*, *value*, *exclude_masked=True*, *op='or'*)

Exclude gates where a given field is equal to a value.

`exclude_gates` (*mask*, *exclude_masked=True*, *op='or'*)

Exclude gates where a given mask is equal True.

Parameters *mask* : numpy array

Boolean numpy array with same shape as a field array.

exclude_masked : bool, optional

True to filter masked values in the specified mask if it is a masked array, False to include any masked values.

op : { 'and', 'or', 'new' }

Operation to perform when merging the existing set of excluded gates with the excluded gates from the current operation. 'and' will perform a logical AND operation, 'or' a logical OR, and 'new' will replace the existing excluded gates with the one generated here. 'or', the default for exclude methods, is typically desired when building up a set of conditions for excluding gates where the desired effect is to exclude gates which meet any of the conditions. 'and', the default for include methods, is typically desired when building up a set of conditions where the desired effect is to include gates which meet any of the conditions. Note that the 'and' method MAY results in including gates which have previously been excluded because they were masked or invalid.

exclude_inside (*field*, *v1*, *v2*, *exclude_masked=True*, *op='or'*, *inclusive=True*)

Exclude gates where a given field is inside a given interval.

exclude_invalid (*field*, *exclude_masked=True*, *op='or'*)

Exclude gates where an invalid value occurs in a field (NaNs or infs).

exclude_masked (*field*, *exclude_masked=True*, *op='or'*)

Exclude gates where a given field is masked.

exclude_none ()

Exclude no gates, include all gates.

exclude_not_equal (*field*, *value*, *exclude_masked=True*, *op='or'*)

Exclude gates where a given field is not equal to a value.

exclude_outside (*field*, *v1*, *v2*, *exclude_masked=True*, *op='or'*, *inclusive=False*)

Exclude gates where a given field is outside a given interval.

exclude_transition (*trans_value=1*, *exclude_masked=True*, *op='or'*)

Exclude all gates in rays marked as in transition between sweeps.

Exclude all gates in rays marked as "in transition" by the `antenna_transition` attribute of the radar used to construct the filter. If no antenna transition information is available no gates are excluded.

Parameters trans_value : int, optional

Value used in the antenna transition data to indicate that the instrument was between sweeps (in transition) during the collection of a specific ray. Typically a value of 1 is used to indicate this transition and the default can be used in these cases.

exclude_masked : bool, optional

True to filter masked values in `antenna_transition` if the data is a masked array, False to include any masked values.

op : { 'and', 'or', 'new' }

Operation to perform when merging the existing set of excluded gates with the excluded gates from the current operation. 'and' will perform a logical AND operation, 'or' a logical OR, and 'new' will replace the existing excluded gates with the one generated here. 'or', the default for exclude methods, is typically desired when building up a set of conditions for excluding gates where the desired effect is to exclude gates which meet any of the conditions. 'and', the default for include methods, is typically desired when building up a set of conditions where the desired effect is to include gates which meet

any of the conditions. Note that the ‘and’ method MAY results in including gates which have previously been excluded because they were masked or invalid.

gate_excluded

gate_included

include_above (*field, value, exclude_masked=True, op='and', inclusive=False*)

Include gates where a given field is above a given value.

include_all ()

Include all gates.

include_below (*field, value, exclude_masked=True, op='and', inclusive=False*)

Include gates where a given field is below a given value.

include_equal (*field, value, exclude_masked=True, op='and'*)

Include gates where a given field is equal to a value.

include_gates (*mask, exclude_masked=True, op='and'*)

Include gates where a given mask is equal True.

Parameters mask : numpy array

Boolean numpy array with same shape as a field array.

exclude_masked : bool, optional

True to filter masked values in the specified mask if it is a masked array, False to include any masked values.

op : {‘and’, ‘or’, ‘new’}

Operation to perform when merging the existing set of excluded gates with the excluded gates from the current operation. ‘and’ will perform a logical AND operation, ‘or’ a logical OR, and ‘new’ will replace the existing excluded gates with the one generated here. ‘or’, the default for exclude methods, is typically desired when building up a set of conditions for excluding gates where the desired effect is to exclude gates which meet any of the conditions. ‘and’, the default for include methods, is typically desired when building up a set of conditions where the desired effect is to include gates which meet any of the conditions. Note that the ‘or’ method MAY results in excluding gates which have previously been included.

include_inside (*field, v1, v2, exclude_masked=True, op='and', inclusive=True*)

Include gates where a given field is inside a given interval.

include_none ()

Include no gates, exclude all gates.

include_not_equal (*field, value, exclude_masked=True, op='and'*)

Include gates where a given field is not equal to a value.

include_not_masked (*field, exclude_masked=True, op='and'*)

Include gates where a given field in not masked.

include_not_transition (*trans_value=0, exclude_masked=True, op='and'*)

Include all gates in rays not marked as in transition between sweeps.

Include all gates in rays not marked as “in transition” by the antenna_transition attribute of the radar used to construct the filter. If no antenna transition information is available all gates are included.

Parameters trans_value : int, optional

Value used in the antenna transition data to indicate that the instrument is not between sweeps (in transition) during the collection of a specific ray. Typically a value of 0 is used to indicate no transition and the default can be used in these cases.

exclude_masked : bool, optional

True to filter masked values in antenna_transition if the data is a masked array, False to include any masked values.

op : {'and', 'or', 'new'}

Operation to perform when merging the existing set of excluded gates with the excluded gates from the current operation. 'and' will perform a logical AND operation, 'or' a logical OR, and 'new' will replace the existing excluded gates with the one generated here. 'or', the default for exclude methods, is typically desired when building up a set of conditions for excluding gates where the desired effect is to exclude gates which meet any of the conditions. 'and', the default for include methods, is typically desired when building up a set of conditions where the desired effect is to include gates which meet any of the conditions. Note that the 'or' method MAY results in excluding gates which have previously been included.

include_outside (*field*, *v1*, *v2*, *exclude_masked*=True, *op*='and', *inclusive*=False)

Include gates where a given field is outside a given interval.

include_valid (*field*, *exclude_masked*=True, *op*='and')

Include gates where a valid value occurs in a field (not NaN or inf).

```
pyart.correct.calculate_attenuation_philinear(radar, doc=None, fzl=None,
                                             pia_coef=None, pida_coef=None,
                                             refl_field=None, phidp_field=None,
                                             zdr_field=None, temp_field=None,
                                             iso0_field=None, spec_at_field=None,
                                             pia_field=None, corr_refl_field=None,
                                             spec_diff_at_field=None,
                                             pida_field=None, corr_zdr_field=None,
                                             temp_ref='temperature')
```

Calculate the attenuation and the differential attenuation from a polarimetric radar using linear dependence with PhiDP. The attenuation is computed up to a user defined freezing level height, where temperatures in a temperature field are positive or where the height relative to the iso0 is 0. The coefficients are either user-defined or radar frequency dependent.

Parameters radar : Radar

Radar object to use for attenuation calculations. Must have phidp and refl fields.

doc : float

Number of gates at the end of each ray to to remove from the calculation.

fzl : float

Freezing layer, gates above this point are not included in the correction.

pia_coef : float

Coefficient in path integrated attenuation calculation

pida_coeff : float

Coefficient in path integrated differential attenuation calculation

refl_field, phidp_field, zdr_field, temp_field, iso0_field : str

Field names within the radar object which represent the horizontal reflectivity, the differential phase shift, the differential reflectivity, the temperature and the height over the iso0. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file. The ZDR field and temperature field are going to be used only if available.

spec_at_field, pia_field, corr_refl_field : str

Names of the specific attenuation, the path integrated attenuation and the corrected reflectivity fields that will be used to fill in the metadata for the returned fields. A value of None for any of these parameters will use the default field names as defined in the Py-ART configuration file.

spec_diff_at_field, pida_field, corr_zdr_field : str

Names of the specific differential attenuation, the path integrated differential attenuation and the corrected differential reflectivity fields that will be used to fill in the metadata for the returned fields. A value of None for any of these parameters will use the default field names as defined in the Py-ART configuration file. These fields will be computed only if the ZDR field is available.

temp_ref : str

the field use as reference for temperature. Can be either temperature, height_over_iso0 or fixed_fzl

Returns spec_at : dict

Field dictionary containing the specific attenuation.

pia_dict : dict

Field dictionary containing the path integrated attenuation.

cor_z : dict

Field dictionary containing the corrected reflectivity.

spec_diff_at : dict

Field dictionary containing the specific differential attenuation.

pida_dict : dict

Field dictionary containing the path integrated differential attenuation.

cor_zdr : dict

Field dictionary containing the corrected differential reflectivity.

```
pyart.correct.calculate_attenuation_zphi(radar, doc=None, fzl=None,
                                         smooth_window_len=5, a_coef=None,
                                         beta=None, c=None, d=None, refl_field=None,
                                         phidp_field=None, zdr_field=None,
                                         temp_field=None, iso0_field=None,
                                         spec_at_field=None, pia_field=None,
                                         corr_refl_field=None, spec_diff_at_field=None,
                                         pida_field=None, corr_zdr_field=None,
                                         temp_ref='temperature')
```

Calculate the attenuation and the differential attenuation from a polarimetric radar using Z-PHI method.. The attenuation is computed up to a user defined freezing level height or up to where temperatures in a temperature field are positive. The coefficients are either user-defined or radar frequency dependent.

Parameters radar : Radar

Radar object to use for attenuation calculations. Must have phidp and refl fields.

doc : float

Number of gates at the end of each ray to to remove from the calculation.

fzl : float

Freezing layer, gates above this point are not included in the correction.

smooth_window_len : int

Size, in range bins, of the smoothing window

a_coef : float

A coefficient in attenuation calculation.

beta : float

Beta parameter in attenuation calculation.

c, d : float

coefficient and exponent of the power law that relates attenuation with differential attenuation

refl_field, phidp_field, zdr_field, temp_field, iso0_field : str

Field names within the radar object which represent the horizontal reflectivity, the differential phase shift, the differential reflectivity, the temperature field and the height over iso0. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file. The ZDR field and temperature field or iso0 field are going to be used only if available.

spec_at_field, pia_field, corr_refl_field : str

Names of the specific attenuation, path integrated attenuation and the corrected reflectivity fields that will be used to fill in the metadata for the returned fields. A value of None for any of these parameters will use the default field names as defined in the Py-ART configuration file.

spec_diff_at_field, pida_field, corr_zdr_field : str

Names of the specific differential attenuation, the path integrated differential attenuation and the corrected differential reflectivity fields that will be used to fill in the metadata for the returned fields. A value of None for any of these parameters will use the default field names as defined in the Py-ART configuration file. These fields will be computed only if the ZDR field is available.

temp_ref : str

the field use as reference for temperature. Can be either temperature, height_over_iso0 or fixed_fzl

Returns spec_at : dict

Field dictionary containing the specific attenuation.

pia_dict : dict

Field dictionary containing the path integrated attenuation.

cor_z : dict

Field dictionary containing the corrected reflectivity.

spec_diff_at : dict

Field dictionary containing the specific differential attenuation.

pida_dict : dict

Field dictionary containing the path integrated differential attenuation.

cor_zdr : dict

Field dictionary containing the corrected differential reflectivity.

References

Gu et al. Polarimetric Attenuation Correction in Heavy Rain at C Band, JAMC, 2011, 50, 39-58.

Ryzhkov et al. Potential Utilization of Specific Attenuation for Rainfall Estimation, Mitigation of Partial Beam Blockage, and Radar Networking, JAOT, 2014, 31, 599-619.

`pyart.correct.correct_bias` (*radar*, *bias*=0.0, *field_name*=None)

Corrects a radar data bias. If field name is none the correction is applied to horizontal reflectivity by default

Parameters **radar** : Radar

radar object

bias : float

the bias magnitude

field_name: str

names of the field to be corrected

Returns **corrected_field** : dict

The corrected field

`pyart.correct.correct_noise_rhohv` (*radar*, *urhohv_field*=None, *snr_field*=None,
zdr_field=None, *nh_field*=None, *nv_field*=None,
rhohv_field=None)

Corrects RhoHV for noise according to eq. 6 in Gourley et al. 2006. This correction should only be performed if noise has not been subtracted from the signal during the moments computation.

Parameters **radar** : Radar

radar object

urhohv_field : str

name of the RhoHV uncorrected for noise field

snr_field, zdr_field, nh_field, nv_field: str

names of the SNR, ZDR, horizontal channel noise in dBZ and vertical channel noise in dBZ used to correct RhoHV

rhohv_field: str

name of the rhohv field to output

Returns **rhohv** : dict

noise corrected RhoHV field

References

Gourley et al. Data Quality of the Meteo-France C-Band Polarimetric Radar, JAOT, 23, 1340-1356

```
pyart.correct.correct_sys_phase(radar, ind_rmin=10, ind_rmax=500, min_rcons=11,
                                zmin=20.0, zmax=40.0, psidp_field=None, refl_field=None,
                                phidp_field=None)
```

correction of the system offset. Public method

Parameters **radar** : Radar

Radar object for which to determine the system phase.

ind_rmin, ind_rmax : int

Min and max range index where to look for continuous precipitation

min_rcons : int

The minimum number of consecutive gates to consider it a rain cell.

zmin, zmax : float

Minimum and maximum reflectivity to consider it a rain cell

psidp_field : str

Field name within the radar object which represent the differential phase shift. A value of None will use the default field name as defined in the Py-ART configuration file.

refl_field : str

Field name within the radar object which represent the reflectivity. A value of None will use the default field name as defined in the Py-ART configuration file.

phidp_field : str

Field name within the radar object which represent the corrected differential phase shift. A value of None will use the default field name as defined in the Py-ART configuration file.

Returns **phidp_dict** : dict

The corrected phidp field

```
pyart.correct.correct_visibility(radar, vis_field=None, field_name=None)
```

Corrects the reflectivity according to visibility. Applied to horizontal reflectivity by default

Parameters **radar** : Radar

radar object

vis_field : str

the name of the visibility field

field_name: str

names of the field to be corrected

Returns **corrected_field** : dict

The corrected field

```
pyart.correct.dealias_fourdd(radar, last_radar=None, sonde_profile=None, gate-
                             filter=False, filt=1, rsl_badval=131072.0, keep_original=False,
                             set_limits=True, vel_field=None, corr_vel_field=None,
                             last_vel_field=None, debug=False, max_shear=0.05, sign=1,
                             **kwargs)
```

Dealias Doppler velocities using the 4DD algorithm.

Dealias the Doppler velocities field using the University of Washington 4DD algorithm utilizing information from a previous volume scan and/or sounding data. Either `last_radar` or `sonde_profile` must be provided. For best results provide both a previous volume scan and sounding data. Radar and `last_radar` must contain the same number of rays per sweep.

Additional arguments are passed to `_fourdd_interface.fourdd_dealias()`. These can be used to fine tune the behavior of the FourDD algorithm. See the documentation of `Other Parameters` for details. For the default values of these parameters see the documentation of `_fourdd_interface.fourdd_dealias()`.

Parameters `radar` : Radar

Radar object to use for dealiasing. Must have a Nyquist defined in the `instrument_parameters` attribute and have a `reflectivity_horizontal` and `mean_doppler_velocity` fields.

last_radar : Radar, optional

The previous radar volume, which has been successfully dealiased. Using a previous volume as an initial condition can greatly improve the dealiasing, and represents the final dimension in the 4DD algorithm.

sonde_profile : HorizontalWindProfile

Profile of horizontal winds from a sounding used for the initial condition of the dealiasing.

Returns `vr_corr` : dict

Field dictionary containing dealiased Doppler velocities. Dealiased array is stored under the 'data' key.

Other Parameters `gatefilter` : GateFilter, optional.

A GateFilter instance which specifies which gates should be ignored when performing velocity dealiasing. A value of None will create this filter from the radar moments using any additional arguments by passing them to `moment_based_gate_filter()`. The default value assumes all gates are valid.

filt : int, optional

Flag controlling Bergen and Albers filter, 1 = yes, 0 = no.

rsl_badval : float, optional

Value which represents a bad value in RSL.

keep_original : bool, optional

True to keep original doppler velocity values when the dealiasing procedure fails, otherwise these gates will be masked. NaN values are still masked.

set_limits : bool, optional

True to set `valid_min` and `valid_max` elements in the returned dictionary. False will not set these dictionary elements.

vel_field : str, optional

Field in radar to use as the Doppler velocities during dealiasing. None will use the default field name from the Py-ART configuration file.

corr_vel_field : str, optional

Name to use for the dealiased Doppler velocity field metadata. None will use the default field name from the Py-ART configuration file.

last_vel_field : str, optional

Name to use for the dealiased Doppler velocity field metadata in last_radar. None will use the corr_vel_field name.

maxshear : float, optional

Maximum vertical shear which will be incorporated into the created volume from the sounding data. Parameter not used when no sounding data is provided.

sign : int, optional

Sign convention which the radial velocities in the volume created from the sounding data will will. This should match the convention used in the radar data. A value of 1 represents when positive values velocities are towards the radar, -1 represents when negative velocities are towards the radar.

compthresh : float, optional

Fraction of the Nyquist velocity to use as a threshold when performing continuity (initial) dealiasing. Velocities differences above this threshold will not be marked as gate from which to begin unfolding during spatial dealiasing.

compthresh2 : float, optional

The same as compthresh but the value used during the second pass of dealiasing. This second pass is only performed in both a sounding and last volume are provided.

thresh : float, optional

Fraction of the Nyquist velocity to use as a threshold when performing spatial dealiasing. Horizontally adjacent gates with velocities above this threshold will count against assigning the gate in question the velocity value being tested.

ckval : float, optional

When the absolute value of the velocities are below this value they will not be marked as gates from which to begin unfolding during spatial dealiasing.

stdthresh : float, optional

Fraction of the Nyquist velocity to use as a standard deviation threshold in the window dealiasing portion of the algorithm.

epsilon : float, optional

Difference used when comparing a value to missing value, changing this from the default is not recommended.

maxcount : int, optional

Maximum allowed number of fold allowed when unfolding velocities.

pass2 : int, optional

Controls whether unfolded gates should be removed (a value of 0) or retained for unfolding during the second pass (a value of 1) when both a sounding volume and last volume are provided.

rm : int, optional

Determines what should be done with gates that are left unfolded after the first pass of dealiasing. A value of 1 will remove these gates, a value of 0 sets these gates to their initial velocity. If both a sounding volume and last volume are provided this parameter is ignored.

proximity : int, optional

Number of gates and rays to include of either side of the current gate during window dealiasing. This value may be doubled in cases where a standard sized window does not capture a sufficient number of good valued gates.

mingood : int, optional

Number of good valued gates required within the window before the current gate will be unfolded.

ba_mincount : int, optional

Number of neighbors required during Bergen and Albers filter for a given gate to be included, must be between 1 and 8, 5 recommended.

ba_edgecount : int, optional

Same as ba_mincount but used at ray edges, must be between 1 and 5, 3 recommended.

debug : bool, optional

Set True to return RSL Volume objects for debugging: usuccess, radialVelVolume, lastVelVolume, unfoldedVolume, sondVolume

Notes

Due to limitations in the C code do not call with sounding arrays over 999 elements long.

References

C. N. James and R. A. Houze Jr, A Real-Time Four-Dimensional Doppler Dealising Scheme, Journal of Atmospheric and Oceanic Technology, 2001, 18, 1674.

```
pyart.correct.dealias_region_based(radar, ref_vel_field=None, interval_splits=3, interval_limits=None, skip_between_rays=100, skip_along_ray=100, centered=True, nyquist_vel=None, check_nyquist_uniform=True, gatefilter=False, rays_wrap_around=None, keep_original=False, set_limits=True, vel_field=None, corr_vel_field=None, **kwargs)
```

Dealias Doppler velocities using a region based algorithm.

Performs Doppler velocity dealiasing by finding regions of similar velocities and unfolding and merging pairs of regions until all regions are unfolded. Unfolding and merging regions is accomplished by modeling the problem as a dynamic network reduction.

Parameters radar : Radar

Radar object containing Doppler velocities to dealias.

ref_vel_field : str or None, optional

Field in radar containing a reference velocity field used to anchor the unfolded velocities once the algorithm completes. Typically this field is created by simulating the radial velocities from wind data from an atmospheric sounding using `pyart.util.simulated_vel_from_profile()`.

interval_splits : int, optional

Number of segments to split the nyquist interval into when finding regions of similar velocity. More splits creates a larger number of initial regions which takes longer to process but may result in better dealiasing. The default value of 3 seems to be a good compromise between performance and artifact free dealiasing. This value is not used if the `interval_limits` parameter is not None.

interval_limits : array like or None, optional

Velocity limits used for finding regions of similar velocity. Should cover the entire nyquist interval. None, the default value, will split the Nyquist interval into `interval_splits` equal sized intervals.

skip_between_rays, skip_along_ray : int, optional

Maximum number of filtered gates to skip over when joining regions, gaps between region larger than this will not be connected. Parameters specify the maximum number of filtered gates between and along a ray. Set these parameters to 0 to disable unfolding across filtered gates.

centered : bool, optional

True to apply centering to each sweep after the dealiasing algorithm so that the average number of unfolding is near 0. False does not apply centering which may results in individual sweeps under or over folded by the nyquist interval.

nyquist_velocity : array like or float, optional

Nyquist velocity in unit identical to those stored in the radar's velocity field, either for each sweep or a single value which will be used for all sweeps. None will attempt to determine this value from the Radar object.

check_nyquist_uniform : bool, optional

True to check if the Nyquist velocities are uniform for all rays within a sweep, False will skip this check. This parameter is ignored when the `nyquist_velocity` parameter is not None.

gatefilter : GateFilter, None or False, optional.

A GateFilter instance which specified which gates should be ignored when performing de-aliasing. A value of None created this filter from the radar moments using any additional arguments by passing them to `moment_based_gate_filter()`. False, the default, disables filtering including all gates in the dealiasing.

rays_wrap_around : bool or None, optional

True when the rays at the beginning of the sweep and end of the sweep should be interpreted as connected when de-aliasing (PPI scans). False if they edges should not be interpreted as connected (other scan types). None will determine the correct value from the radar scan type.

keep_original : bool, optional

True to retain the original Doppler velocity values at gates where the dealiasing procedure fails or was not applied. False does not replacement and these gates will be masked in the corrected velocity field.

set_limits : bool, optional

True to set valid_min and valid_max elements in the returned dictionary. False will not set these dictionary elements.

vel_field : str, optional

Field in radar to use as the Doppler velocities during dealiasing. None will use the default field name from the Py-ART configuration file.

corr_vel_field : str, optional

Name to use for the dealiased Doppler velocity field metadata. None will use the default field name from the Py-ART configuration file.

Returns **corr_vel** : dict

Field dictionary containing dealiased Doppler velocities. Dealiased array is stored under the 'data' key.

```
pyart.correct.dealias_unwrap_phase(radar,      unwrap_unit='sweep',    nyquist_vel=None,
                                   check_nyquist_uniform=True,        gatefilter=False,
                                   rays_wrap_around=None,              keep_original=False,
                                   set_limits=True,  vel_field=None,    corr_vel_field=None,
                                   skip_checks=False, **kwargs)
```

Dealias Doppler velocities using multi-dimensional phase unwrapping.

Parameters **radar** : Radar

Radar object containing Doppler velocities to dealias.

unwrap_unit : {'ray', 'sweep', 'volume'}, optional

Unit to unwrap independently. 'ray' will unwrap each ray individually, 'sweep' each sweep, and 'volume' will unwrap the entire volume in a single pass. 'sweep', the default, often gives superior results when the lower sweeps of the radar volume are contaminated by clutter. 'ray' does not use the gatefilter parameter and rays where gates are masked will result in poor dealiasing for that ray.

nyquist_velocity : array like or float, optional

Nyquist velocity in unit identical to those stored in the radar's velocity field, either for each sweep or a single value which will be used for all sweeps. None will attempt to determine this value from the Radar object. The Nyquist velocity of the first sweep is used for all dealiasing unless the unwrap_unit is 'sweep' when the velocities of each sweep are used.

check_nyquist_uniform : bool, optional

True to check if the Nyquist velocities are uniform for all rays within a sweep, False will skip this check. This parameter is ignored when the nyquist_velocity parameter is not None.

gatefilter : GateFilter, None or False, optional.

A GateFilter instance which specified which gates should be ignored when performing de-aliasing. A value of None created this filter from the radar moments using any additional arguments by passing them to `moment_based_gate_filter()`. False, the default, disables filtering including all gates in the dealiasing.

rays_wrap_around : bool or None, optional

True when the rays at the beginning of the sweep and end of the sweep should be interpreted as connected when de-aliasing (PPI scans). False if they edges should not

be interpreted as connected (other scan types). None will determine the correct value from the radar scan type.

keep_original : bool, optional

True to retain the original Doppler velocity values at gates where the dealiasing procedure fails or was not applied. False does not replacement and these gates will be masked in the corrected velocity field.

set_limits : bool, optional

True to set valid_min and valid_max elements in the returned dictionary. False will not set these dictionary elements.

vel_field : str, optional

Field in radar to use as the Doppler velocities during dealiasing. None will use the default field name from the Py-ART configuration file.

corr_vel_field : str, optional

Name to use for the dealiased Doppler velocity field metadata. None will use the default field name from the Py-ART configuration file.

skip_checks : bool

True to skip checks verifying that an appropriate unwrap_unit is selected, False retains these checked. Setting this parameter to True is not recommended and is only offered as an option for extreme cases.

Returns **corr_vel** : dict

Field dictionary containing dealiased Doppler velocities. Dealiased array is stored under the 'data' key.

References

[R7], [R8]

`pyart.correct.despeckle_field(radar, field, label_dict=None, threshold=-100, size=10, gate-filter=None, delta=5.0)`

Despeckle a radar volume by identifying small objects in each scan and masking them out. User can define which field to investigate, as well as various thresholds to use on that field and any objects found within. Requires scipy to be installed, and returns a GateFilter object.

Parameters **radar** : pyart.core.Radar object

Radar object to query.

field : str

Name of field to investigate for speckles.

Returns **gatefilter** : pyart.filters.GateFilter object

Py-ART GateFilter object that includes the despeckling mask

Other Parameters **label_dict** : dict or None, optional

Dictionary that is produced by find_objects. If None, find_objects will be called to produce it.

threshold : int or float, or 2-element tuple of ints or floats

Threshold values above (if single value) or between (if tuple) for objects to be identified.
Default value assumes reflectivity.

size : int, optional

Number of contiguous gates in an object, below which it is a speckle.

gatefilter : None or pyart.filters.GateFilter object

Py-ART GateFilter object to which to add the despeckling mask. The GateFilter object will be permanently modified with the new filtering. If None, creates a new GateFilter.

delta : int or float, optional

Size of allowable gap near PPI edges, in deg, to consider it full 360. If gap is small, then PPI edges will be checked for matching objects.

```
pyart.correct.det_sys_phase_ray(radar, ind_rmin=10, ind_rmax=500, min_rcons=11,
                               zmin=20.0, zmax=40.0, phidp_field=None, refl_field=None)
```

Public method Alternative determination of the system phase. Assumes that the valid gates of phidp are only precipitation. A system phase value is found for each ray.

Parameters radar : Radar

Radar object for which to determine the system phase.

ind_rmin, ind_rmax : int

Min and max range index where to look for continuous precipitation

min_rcons : int

The minimum number of consecutive gates to consider it a rain cell.

zmin, zmax : float

The minimum and maximum reflectivity to consider the radar bin suitable precipitation

phidp_field : str

Field name within the radar object which represent the differential phase shift. A value of None will use the default field name as defined in the Py-ART configuration file.

refl_field : str

Field name within the radar object which represent the reflectivity. A value of None will use the default field name as defined in the Py-ART configuration file.

Returns phidp0_dict : dict

Estimate of the system phase at each ray and metadata

first_gates_dict : dict

The first gate where PhiDP is valid and metadata

```
pyart.correct.est_rhoHV_rain(radar, ind_rmin=10, ind_rmax=500, zmin=20.0, zmax=40.0,
                             thickness=700.0, doc=None, fzl=None, rhoHV_field=None,
                             temp_field=None, iso0_field=None, refl_field=None,
                             temp_ref='temperature')
```

Estimates the quantiles of RhoHV in rain for each sweep

Parameters radar : Radar

radar object

ind_rmin, ind_rmax : int

Min and max range index where to look for rain

zmin, zmax : float

The minimum and maximum reflectivity to consider the radar bin suitable rain

thickness : float

Assumed thickness of the melting layer

doc : float

Number of gates at the end of each ray to to remove from the calculation.

fzl : float

Freezing layer, gates above this point are not included in the correction.

temp_field, iso0_field, rhohv_field, refl_field : str

Field names within the radar object which represent the temperature, the height over the iso0, co-polar correlation and reflectivity fields. A value of None will use the default field name as defined in the Py-ART configuration file.

temp_ref : str

the field use as reference for temperature. Can be either temperature or height_over_iso0

Returns rhohv_rain_dict : dict

The estimated RhoHV in rain for each sweep and metadata

```
pyart.correct.est_zdr_precip(radar, ind_rmin=10, ind_rmax=500, zmin=20.0, zmax=22.0, rho-
                             hvmin=0.97, phidpmax=10.0, elmax=None, thickness=700.0,
                             doc=None, fzl=None, zdr_field=None, rhohv_field=None,
                             phidp_field=None, temp_field=None, iso0_field=None,
                             refl_field=None, temp_ref='temperature')
```

Filters out all undesired data to be able to estimate ZDR bias, either in moderate rain or from vertically pointing scans

Parameters radar : Radar

radar object

ind_rmin, ind_rmax : int

Min and max range index where to look for rain

zmin, zmax : float

The minimum and maximum reflectivity to consider the radar bin suitable rain

rhohvmin : float

Minimum RhoHV to consider the radar bin suitable rain

phidpmax : float

Maximum PhiDP to consider the radar bin suitable rain

elmax : float

Maximum elevation

thickness : float

Assumed thickness of the melting layer

doc : float

Number of gates at the end of each ray to to remove from the calculation.

fzl : float

Freezing layer, gates above this point are not included in the correction.

zdr_field, rhohv_field, refl_field, phidp_field, temp_field,

iso0_field : str Field names within the radar object which represent the differential reflectivity, co-polar correlation, reflectivity, differential phase, temperature and height relative to the iso0 fields. A value of None will use the default field name as defined in the Py-ART configuration file.

temp_ref : str

the field use as reference for temperature. Can be either temperature, height_over_iso0, fixed_fzl or None

Returns zdr_prec_dict : dict

The ZDR data complying with specifications and metadata

```
pyart.correct.est_zdr_snow(radar, ind_rmin=10, ind_rmax=500, zmin=0.0, zmax=30.0, snr-
                           min=10.0, snrmax=50.0, rhohvmin=0.97, kept_values=[1],
                           phidpmax=10.0, kdpmax=None, tempmin=None, temp-
                           max=None, elmax=None, zdr_field=None, rhohv_field=None,
                           phidp_field=None, temp_field=None, snr_field=None, hy-
                           dro_field=None, kdp_field=None, refl_field=None)
```

Filters out all undesired data to be able to estimate ZDR bias in snow

Parameters radar : Radar

radar object

ind_rmin, ind_rmax : int

Min and max range index where to look for snow

zmin, zmax : float

The minimum and maximum reflectivity to consider the radar bin suitable snow

snrmin, snrmax : float

The minimum and maximum SNR to consider the radar bin suitable snow

rhohvmin : float

Minimum RhoHV to consider the radar bin suitable snow

kept_values : list of int

The hydrometeor classification values to keep

phidpmax : float

Maximum PhiDP to consider the radar bin suitable snow

kdpmax : float or None

Maximum KDP. If not none this is the maximum KDP value to consider the radar bin suitable snow

tempmin, tempmax : float or None

If not None, the minimum and maximum temperature to consider the radar bin suitable snow

elmax : float

Maximum elevation

zdr_field, rhohv_field, refl_field, phidp_field, kdp_field, temp_field,

snr_field, hydro_field : str

Field names within the radar object which represent the differential reflectivity, co-polar correlation, reflectivity, differential phase, specific differential phase, signal to noise ratio, hydrometeor classification and temperature fields. A value of None will use the default field name as defined in the Py-ART configuration file.

Returns zdr_snow_dict : dict

The ZDR data complying with specifications and metadata

`pyart.correct.find_objects` (*radar, field, threshold, sweeps=None, smooth=None, gatefilter=None, delta=5.0*)

Find objects (i.e., contiguous gates) in one or more sweeps that match thresholds. Filtering & smoothing are available prior to labeling objects. In addition, periodic boundaries are accounted for if they exist (e.g., 360-deg PPIs). Requires scipy to be installed.

Parameters radar : `pyart.core.Radar` object

Radar object to query.

field : str

Name of field to investigate for objects.

threshold : int or float, or 2-element tuple of ints or floats

Threshold values above (if single value) or between (if tuple) for objects to be identified.

Returns label_dict : dict

Dictionary that contains all the labeled objects. If this function is performed on the full Radar object, then the dict is ready to be added as a field.

Other Parameters sweeps : int or array of ints or None, optional

Sweep numbers to examine. If None, all sweeps are examined.

smooth : int or None, optional

Number of gates included in a smoothing box filter along a ray. If None, no smoothing is done prior to labeling objects.

gatefilter : None or `pyart.filters.GateFilter` object

Py-ART GateFilter object to apply before labeling objects. If None, no filtering will be performed. Note: Filtering always occurs before smoothing.

delta : int or float, optional

Size of allowable gap near PPI edges, in deg, to consider it full 360. If gap is small, then PPI edges will be checked for matching objects along the periodic boundary.

`pyart.correct.get_mask_fz1` (*radar, fz1=None, doc=None, min_temp=0.0, max_h_iso0=0.0, thickness=None, beamwidth=None, temp_field=None, iso0_field=None, temp_ref='temperature'*)

constructs a mask to mask data placed thickness m below data at min_temp and beyond

Parameters radar : Radar

the radar object

doc : float

Number of gates at the end of each ray to to remove from the calculation.

fzl : float

Freezing layer, gates above this point are not included in the correction.

min_temp : float

minimum temperature below which the data is mask in degrees

max_h_iso0 : float

maximum height relative to the iso0 below which the data is mask in m

thickness : float

extent of the layer below the first gate where min_temp is reached that is going to be masked

beamwidth : float

the radar antenna 3 dB beamwidth

temp_field, iso0_field : str

Field names within the radar object which represent the temperature or the height over iso0 fields. A value of None will use the default field name as defined in the Py-ART configuration file. It is going to be used only if available.

temp_ref : str

the field use as reference for temperature. Can be either temperature, height_over_iso0 or fixed_fzl

Returns mask_fzl : 2D array

the values that should be masked

end_gate_arr : 1D array

the index of the last valid gate in the ray

`pyart.correct.get_sun_hits(radar, delev_max=2.0, dazim_max=2.0, elmin=1.0, ind_rmin=100, percent_bins=10.0, attg=None, max_std=1.0, pwrh_field=None, pwrv_field=None, zdr_field=None)`

get data from suspected sun hits

Parameters radar : Radar

radar object

delev_max, dazim_max : float

maximum difference in elevation and azimuth between sun position and antenna pointing

elmin : float

minimum radar elevation angle

ind_rmin : int

minimum range from which we can look for noise

percent_bins : float

percentage of bins with valid data to consider a ray as potentially sun hit

attg : float

gas attenuation coefficient (1-way)

pwrh_field, pwrv_field, zdr_field : str

names of the signal power in dBm for the H and V polarizations and the differential reflectivity

Returns sun_hits : dict

a dictionary containing information of the sun hits

new_radar : radar object

radar object containing sweeps that contain sun hits

`pyart.correct.moment_based_gate_filter(radar, ncp_field=None, rhv_field=None, refl_field=None, min_ncp=0.5, min_rhv=None, min_refl=-20.0, max_refl=100.0)`

Create a filter which removes undesired gates based on moments.

Creates a gate filter in which the following gates are excluded:

- Gates where the instrument is transitioning between sweeps.
- Gates where the reflectivity is outside the interval min_refl, max_refl.
- Gates where the normalized coherent power is below min_ncp.
- Gates where the cross correlation ratio is below min_rhi. Using the default parameter this filtering is disabled.
- Gates where any of the above three fields are masked or contain invalid values (NaNs or infs).
- If any of these three fields do not exist in the radar that fields filter criteria is not applied.

Parameters radar : Radar

Radar object from which the gate filter will be built.

refl_field, ncp_field, rhv_field : str

Names of the radar fields which contain the reflectivity, normalized coherent power (signal quality index) and cross correlation ratio (RhoHV) from which the gate filter will be created using the above criteria. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file.

min_ncp, min_rhv : float

Minimum values for the normalized coherence power and cross correlation ratio. Gates in these fields below these limits as well as gates which are masked or contain invalid values will be excluded and not used in calculation which use the filter. A value of None will disable filtering based upon the given field including removing masked or gates with an invalid value. To disable the thresholding but retain the masked and invalid filter set the parameter to a value below the lowest value in the field.

min_refl, max_refl : float

Minimum and maximum values for the reflectivity. Gates outside of this interval as well as gates which are masked or contain invalid values will be excluded and not used in calculation which use this filter. A value or None for one of these parameters will

disable the minimum or maximum filtering but retain the other. A value of None for both of these values will disable all filtering based upon the reflectivity including removing masked or gates with an invalid value. To disable the interval filtering but retain the masked and invalid filter set the parameters to values above and below the lowest and greatest values in the reflectivity field.

Returns `gatefilter` : *GateFilter*

A gate filter based upon the described criteria. This can be used as a `gatefilter` parameter to various functions in `pyart.correct`.

```
pyart.correct.phase_proc_lp(radar, offset, debug=False, self_const=60000.0, low_z=10.0,
                             high_z=53.0, min_phidp=0.01, min_ncp=0.5, min_rhv=0.8,
                             fzl=4000.0, sys_phase=0.0, override_sys_phase=False,
                             nowrap=None, really_verbose=False, LP_solver='cylp',
                             refl_field=None, ncp_field=None, rhv_field=None,
                             phidp_field=None, kdp_field=None, unf_field=None, win-
                             dow_len=35, proc=1, coef=0.914)
```

Phase process using a LP method [1].

Parameters `radar` : Radar

Input radar.

offset : float

Reflectivity offset in dBz.

debug : bool, optional

True to print debugging information.

self_const : float, optional

Self consistency factor.

low_z : float

Low limit for reflectivity. Reflectivity below this value is set to this limit.

high_z : float

High limit for reflectivity. Reflectivity above this value is set to this limit.

min_phidp : float

Minimum Phi differential phase.

min_ncp : float

Minimum normal coherent power.

min_rhv : float

Minimum copolar coefficient.

fzl :

Maximum altitude.

sys_phase : float

System phase in degrees.

override_sys_phase: bool.

True to use `sys_phase` as the system phase. False will calculate a value automatically.

nowrap : int or None.

Gate number to begin phase unwrapping. None will unwrap all phases.

really_verbose : bool

True to print LPX messaging. False to suppress.

LP_solver : 'pyglpk' or 'cvxopt', 'cylp', or 'cylp_mp'

Module to use to solve LP problem.

refl_field, ncp_field, rhv_field, phidp_field, kdp_field: str

Name of field in radar which contains the horizontal reflectivity, normal coherent power, copolar coefficient, differential phase shift, and differential phase. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file.

unf_field : str

Name of field which will be added to the radar object which will contain the unfolded differential phase. Metadata for this field will be taken from the phidp_field. A value of None will use the default field name as defined in the Py-ART configuration file.

window_len : int

Length of Sobel window applied to PhiDP field when prior to calculating KDP.

proc : int

Number of worker processes, only used when *LP_solver* is 'cylp_mp'.

coef : float

Exponent linking Z to KDP in self consistency. $kdp=(10^{**}(0.1z))^{*coef}$

Returns reproc_phase : dict

Field dictionary containing processed differential phase shifts.

sob_kdp : dict

Field dictionary containing recalculated differential phases.

References

- [1] Giangrande, S.E., R. McGraw, and L. Lei. An Application of Linear Programming to Polarimetric Radar Differential Phase Processing. J. Atmos. and Oceanic Tech, 2013, 30, 1716.

```
pyart.correct.selfconsistency_bias(radar,          zdr_kdpzh_dict,          min_rhohv=0.92,
                                   max_phidp=20.0,          smooth_wind_len=5,
                                   doc=None,          fzl=None,          thickness=700.0,
                                   min_rcons=20,          dphidp_min=2,          dphidp_max=16,
                                   refl_field=None,          phidp_field=None,          zdr_field=None,
                                   temp_field=None,          iso0_field=None,          rhohv_field=None,
                                   temp_ref='temperature')
```

Estimates reflectivity bias at each ray using the self-consistency algorithm by Gourley

Parameters radar : Radar

radar object

zdr_kdpzh_dict : dict

dictionary containing a look up table relating ZDR with KDP/Zh for different elevations

min_rhohv : float

minimum RhoHV value to consider the data valid

max_phidp : float

maximum PhiDP value to consider the data valid

smooth_wind_len : int

length of the smoothing window

doc : float

Number of gates at the end of each ray to to remove from the calculation.

fzl : float

Freezing layer, gates above this point are not included in the correction.

min_rcons : int

minimum number of consecutive gates to consider a valid segment of PhiDP

dphidp_min : float

minimum differential phase shift in a segment

dphidp_max : float

maximum differential phase shift in a segment

refl_field, phidp_field, zdr_field : str

Field names within the radar object which represent the reflectivity, differential phase and differential reflectivity fields. A value of None will use the default field name as defined in the Py-ART configuration file.

temp_field, iso0_field, rhohv_field : str

Field names within the radar object which represent the temperature, the height relative to the iso0 and the co-polar correlation fields. A value of None will use the default field name as defined in the Py-ART configuration file. They are going to be used only if available.

kdpsim_field, phidpsim_field : str

Field names which represent the estimated specific differential phase and differential phase. A value of None will use the default field name as defined in the Py-ART configuration file.

temp_ref : str

the field use as reference for temperature. Can be either temperature, height_over_iso0 or fixed_fzl

Returns **refl_bias_dict** : dict

the bias at each ray field and metadata

```
pyart.correct.selfconsistency_kdp_phidp(radar,      zdr_kdpzh_dict,      min_rhohv=0.92,
                                         max_phidp=20.0,      smooth_wind_len=5,
                                         doc=None,      fzl=None,      thickness=700.0,
                                         refl_field=None,      phidp_field=None,
                                         zdr_field=None,      temp_field=None,
                                         iso0_field=None,      rhohv_field=None,      kdp-
                                         sim_field=None,      phidpsim_field=None,
                                         temp_ref='temperature')
```

Estimates KDP and PhiDP in rain from Zh and ZDR using a selfconsistency relation between ZDR, Zh and KDP. Private method

Parameters **radar** : Radar

radar object

zdr_kdpzh_dict : dict

dictionary containing a look up table relating ZDR with KDP/Zh for different elevations

min_rhohv : float

minimum RhoHV value to consider the data valid

max_phidp : float

maximum PhiDP value to consider the data valid

smooth_wind_len : int

length of the smoothing window

doc : float

Number of gates at the end of each ray to to remove from the calculation.

fzl : float

Freezing layer, gates above this point are not included in the correction.

thickness : float

assumed melting layer thickness [m]

refl_field, phidp_field, zdr_field : str

Field names within the radar object which represent the reflectivity, differential phase and differential reflectivity fields. A value of None will use the default field name as defined in the Py-ART configuration file.

temp_field, iso0_field, rhohv_field : str

Field names within the radar object which represent the temperature, the height relative to the iso0 and the co-polar correlation fields. A value of None will use the default field name as defined in the Py-ART configuration file. They are going to be used only if available.

kdp sim_field, phidpsim_field : str

Field names which represent the estimated specific differential phase and differential phase. A value of None will use the default field name as defined in the Py-ART configuration file.

temp_ref : str

the field use as reference for temperature. Can be either temperature, height_over_iso0 or fixed_fzl

Returns `kdp_sim_dict, phidp_sim_dict` : dict

the KDP and PhiDP estimated fields and metadata

```
pyart.correct.smooth_phidp_double_window(radar, ind_rmin=10, ind_rmax=500,
                                         min_rcons=11, zmin=20.0, zmax=40,
                                         swind_len=11, smin_valid=6, lwind_len=31,
                                         lmin_valid=16, zthr=40.0, psidp_field=None,
                                         refl_field=None, phidp_field=None)
```

correction of the system offset and smoothing using two window

Parameters `radar` : Radar

Radar object for which to determine the system phase.

ind_rmin, ind_rmax : int

Min and max range index where to look for continuous precipitation

min_rcons : int

The minimum number of consecutive gates to consider it a rain cell.

zmin, zmax : float

Minimum and maximum reflectivity to consider it a rain cell

swind_len : int

Length of the short moving window used to smooth

smin_valid : int

Minimum number of valid bins to consider the short window smooth data valid

lwind_len : int

Length of the long moving window used to smooth

lmin_valid : int

Minimum number of valid bins to consider the long window smooth data valid

zthr : float

reflectivity value above which the short window is used

psidp_field : str

Field name within the radar object which represent the differential phase shift. A value of None will use the default field name as defined in the Py-ART configuration file.

refl_field : str

Field name within the radar object which represent the reflectivity. A value of None will use the default field name as defined in the Py-ART configuration file.

phidp_field : str

Field name within the radar object which represent the corrected differential phase shift. A value of None will use the default field name as defined in the Py-ART configuration file.

Returns `phidp_dict` : dict

The corrected phidp field

```
pyart.correct.smooth_phidp_single_window(radar, ind_rmin=10, ind_rmax=500,
                                         min_rcons=11, zmin=20.0, zmax=40,
                                         wind_len=11, min_valid=6, psidp_field=None,
                                         refl_field=None, phidp_field=None)
```

correction of the system offset and smoothing using one window

Parameters **radar** : Radar

Radar object for which to determine the system phase.

ind_rmin, ind_rmax : int

Min and max range index where to look for continuous precipitation

min_rcons : int

The minimum number of consecutive gates to consider it a rain cell.

zmin, zmax : float

Minimum and maximum reflectivity to consider it a rain cell

wind_len : int

Length of the moving window used to smooth

min_valid : int

Minimum number of valid bins to consider the smooth data valid

psidp_field : str

Field name within the radar object which represent the differential phase shift. A value of None will use the default field name as defined in the Py-ART configuration file.

refl_field : str

Field name within the radar object which represent the reflectivity. A value of None will use the default field name as defined in the Py-ART configuration file.

phidp_field : str

Field name within the radar object which represent the corrected differential phase shift. A value of None will use the default field name as defined in the Py-ART configuration file.

Returns **phidp_dict** : dict

The corrected phidp field

```
pyart.correct.sun_power(solar_flux, pulse_width, wavelen, antenna_gain, angle_step, beamwidth,
                        coeff_band=1.2)
```

computes the theoretical sun power detected at the antenna [dBm] as it would be without atmospheric attenuation (sun power at top of the atmosphere)

Parameters **solar_flux** : float array

the solar fluxes measured at 10.7 cm wavelength [10e-22 W/(m² Hz)]

pulse_width : float

pulse width [s]

wavelen : float

radar wavelength [m]

antenna_gain : float

the antenna gain [dB]

angle_step : float

integration angle [deg]

beamwidth : float

3 dB-beamwidth [deg]

coeff_band : float

multiplicative coefficient applied to the inverse of the pulse width to get the effective bandwidth

Returns **pwr_det** : float array

the detected power

References

Altube P., J. Bech, O. Argemi, T. Rigo, 2015: Quality Control of Antenna Alignment and Receiver Calibration Using the Sun: Adaptation to Midrange Weather Radar Observations at Low Elevation Angles

```
pyart.correct.sun_retrieval(az_rad, az_sun, el_rad, el_sun, sun_hit, sun_hit_std,  
                             az_width_co=None, el_width_co=None, az_width_cross=None,  
                             el_width_cross=None, is_zdr=False)
```

Estimates sun parameters from sun hits

Parameters **az_rad, az_sun, el_rad, el_sun** : float array

azimuth and elevation values of the sun and the radar

sun_hit : float array

sun hit value. Either power in dBm or ZDR in dB

sun_hit_std : float array

standard deviation of the sun hit value in dB

az_width_co, el_width_co, az_width_cross, el_width_cross : float

azimuth and elevation antenna width for each channel

is_zdr : boolean

boolean to signal that is ZDR data

Returns **val, val_std** : float

retrieved value and its standard deviation

az_bias, el_bias : float

retrieved azimuth and elevation antenna bias respect to the sun position

az_width, el_width : float

retrieved azimuth and elevation antenna widths

nhits : int

number of sun hits used in the retrieval

RADAR RETRIEVALS (PYART.RETRIEVE)

Radar retrievals.

7.1 Radar retrievals

<code>kdp_maesaka(radar[, gatefilter, method, ...])</code>	Compute the specific differential phase (KDP) from corrected (e.g., unfolded) total differential phase data based on the variational method outlined in Maesaka et al.
<code>kdp_schneebeli(radar[, gatefilter, ...])</code>	Estimates Kdp with the Kalman filter method by Schneebeli and al.
<code>kdp_vulpiani(radar[, gatefilter, ...])</code>	Estimates Kdp with the Vulpiani method for a 2D array of psidp measurements with the first dimension being the distance from radar and the second dimension being the angles (azimuths for PPI, elev for RHI).The input psidp is assumed to be pre-filtered (for ex.
<code>kdp_leastsquare_single_window(radar[, ...])</code>	Compute the specific differential phase (KDP) from differential phase data using a piecewise least square method.
<code>kdp_leastsquare_double_window(radar[, ...])</code>	Compute the specific differential phase (KDP) from differential phase data using a piecewise least square method.
<code>calculate_snr_from_reflectivity(radar[, ...])</code>	Calculate the signal to noise ratio, in dB, from the reflectivity field.
<code>compute_snr(radar[, refl_field, ...])</code>	Computes SNR from a reflectivity field and the noise in dBZ.
<code>compute_l(radar[, rhohv_field, l_field])</code>	Computes Rhohv in logarithmic scale according to $L = -\log_{10}(1 - \text{RhoHV})$
<code>compute_cdr(radar[, rhohv_field, zdr_field, ...])</code>	Computes the Circular Depolarization Ratio
<code>compute_noisedBZ(nrays, noisedBZ_val, range, ...)</code>	Computes noise in dBZ from reference noise value.
<code>fetch_radar_time_profile(sonde_dset, radar)</code>	Extract the correct profile from a interpolated sonde.
<code>map_profile_to_gates(profile, heights, radar)</code>	Given a profile of a variable map it to the gates of radar assuming 4/3Re.
<code>steiner_conv_strat(grid[, dx, dy, intense, ...])</code>	Partition reflectivity into convective-stratiform using the Steiner et al.
<code>hydroclass_semisupervised(radar[, ...])</code>	Classifies precipitation echoes following the approach by
<code>get_freq_band(freq)</code>	returns the frequency band name (S, C, X, ...)
<code>texture_of_complex_phase(radar[, ...])</code>	Calculate the texture of the differential phase field.
<code>grid_displacement_pc(grid1, grid2, field, level)</code>	Calculate the grid displacement using phase correlation.
<code>grid_shift(grid, advection[, trim_edges, ...])</code>	Shift a grid by a certain number of pixels.
Continued on next page	

Table 7.1 – continued from previous page

<code>est_rain_rate_zpoly</code> (radar[, refl_field, ...])	Estimates rainfall rate from reflectivity using a polynomial Z-R relation
<code>est_rain_rate_z</code> (radar[, alpha, beta, ...])	Estimates rainfall rate from reflectivity using a power law
<code>est_rain_rate_kdp</code> (radar[, alpha, beta, ...])	Estimates rainfall rate from kdp using alpha power law
<code>est_rain_rate_a</code> (radar[, alpha, beta, ...])	Estimates rainfall rate from specific attenuation using alpha power law
<code>est_rain_rate_zkdp</code> (radar[, alphaz, betaz, ...])	Estimates rainfall rate from a blending of power law r-kdp and r-z relations.
<code>est_rain_rate_za</code> (radar[, alphaz, betaz, ...])	Estimates rainfall rate from a blending of power law r-alpha and r-z relations.
<code>est_rain_rate_hydro</code> (radar[, alphazr, ...])	Estimates rainfall rate using different relations between R and the
<code>est_wind_vel</code> (radar[, vert_proj, vel_field, ...])	Estimates wind velocity.
<code>est_vertical_windshear</code> (radar[, az_tol, ...])	Estimates wind shear.
<code>get_coeff_attg</code> (freq)	get the 1-way gas attenuation for a particular frequency

`pyart.retrieve.calculate_snr_from_reflectivity` (radar, refl_field=None, snr_field=None, toa=25000.0)

Calculate the signal to noise ratio, in dB, from the reflectivity field.

Parameters radar : Radar

Radar object from which to retrieve reflectivity field.

refl_field : str, optional

Name of field in radar which contains the reflectivity. None will use the default field name in the Py-ART configuration file.

snr_field : str, optional

Name to use for snr metadata. None will use the default field name in the Py-ART configuration file.

toa : float, optional

Height above which to take noise floor measurements, in meters.

Returns snr : field dictionary

Field dictionary containing the signal to noise ratio.

`pyart.retrieve.compute_cdr` (radar, rhohv_field=None, zdr_field=None, cdr_field=None)

Computes the Circular Depolarization Ratio

Parameters radar : Radar

radar object

rhohv_field, zdr_field : str

name of the input RhoHV and ZDR fields

cdr_field : str

name of the CDR field

Returns cdr : dict

CDR field

`pyart.retrieve.compute_l(radar, rhohv_field=None, l_field=None)`

Computes Rhohv in logarithmic scale according to $L = -\log_{10}(1 - \text{RhoHV})$

Parameters `radar` : Radar

radar object

rhohv_field : str

name of the RhoHV field used for the calculation

l_field : str

name of the L field

Returns `l` : dict

L field

`pyart.retrieve.compute_noisedBZ(nrays, noisedBZ_val, range, ref_dist, noise_field=None)`

Computes noise in dBZ from reference noise value.

Parameters `nrays`: int

number of rays in the reflectivity field

noisedBZ_val: float

Estimated noise value in dBZ at reference distance

range: np array of floats

range vector in m

ref_dist: float

reference distance in Km

noise_field: str

name of the noise field to use

Returns `noisedBZ` : dict

the noise field

`pyart.retrieve.compute_signal_power(radar, lmf=None, attg=None, radconst=None, lrx=0.0, lradome=0.0, refl_field=None, pwr_field=None)`

Computes received signal power OUTSIDE THE RADOME in dBm from a reflectivity field.

Parameters `radar` : Radar

radar object

lmf : float

matched filter losses

attg : float

1-way gas attenuation

radconst : float

radar constant

lrx : float

receiver losses from the antenna feed to the reference point (positive value) [dB]

lradome : float

1-way losses due to the radome (positive value) [dB]

refl_field : str

name of the reflectivity used for the calculations

pwr_field : str

name of the signal power field

Returns **s_pwr_dict** : dict

power field and metadata

`pyart.retrieve.compute_snr(radar, refl_field=None, noise_field=None, snr_field=None)`

Computes SNR from a reflectivity field and the noise in dBZ.

Parameters **radar** : Radar

radar object

refl_field, noise_field : str

name of the reflectivity and noise field used for the calculations

snr_field : str

name of the SNR field

Returns **snr** : dict

the SNR field

`pyart.retrieve.est_rain_rate_a(radar, alpha=None, beta=None, a_field=None, rr_field=None)`

Estimates rainfall rate from specific attenuation using alpha power law

Parameters **radar** : Radar

Radar object

alpha,beta : floats

Optional. factor (alpha) and exponent (beta) of the power law. If not set the factors are going to be determined according to the radar frequency

a_field : str

name of the specific attenuation field to use

rr_field : str

name of the rainfall rate field

Returns **rain** : dict

Field dictionary containing the rainfall rate.

References

Diederich M., Ryzhkov A., Simmer C., Zhang P. and Tromel S., 2015: Use of Specific Attenuation for Rainfall Measurement at X-Band Radar Wavelengths. Part I: Radar Calibration and Partial Beam Blockage Estimation. Journal of Hydrometeorology, 16, 487-502.

Ryzhkov A., Diederich M., Zhang P. and Simmer C., 2014: Potential Utilization of Specific Attenuation for Rainfall Estimation, Mitigation of Partial Beam Blockage, and Radar Networking. Journal of Atmospheric and Oceanic Technology, 31, 599-619.

```
pyart.retrieve. est_rain_rate_hydro (radar, alphazr=0.0376, betazr=0.6112, alphazs=0.1,
                                     betazs=0.5, alphas=0.0376, betas=0.6112,
                                     refl_field=None, a_field=None, hydro_field=None,
                                     rr_field=None, master_field=None, thresh=None,
                                     thresh_max=False)
```

Estimates rainfall rate using different relations between R and the polarimetric variables depending on the hydrometeor type

Parameters radar : Radar

Radar object

alphazr,betazr : floats

factor (alpha) and exponent (beta) of the z-r power law for rain.

alphazs,betazs : floats

factor (alpha) and exponent (beta) of the z-s power law for snow.

alphas,betas : floats

Optional. factor (alpha) and exponent (beta) of the a-r power law. If not set the factors are going to be determined according to the radar frequency

mp_factor : float

factor applied to z-r relation in the melting layer

refl_field : str

name of the reflectivity field to use

a_field : str

name of the specific attenuation field to use

hydro_field : str

name of the hydrometeor classification field to use

rr_field : str

name of the rainfall rate field

master_field : str

name of the field that is going to act as master. Has to be either refl_field or kdp_field. Default is refl_field

thresh : float

value of the threshold that determines when to use the slave field.

thresh_max : Boolean

If true the master field is used up to the thresh value maximum. Otherwise the master field is not used below thresh value.

Returns rain : dict

Field dictionary containing the rainfall rate.

```
pyart.retrieve. est_rain_rate_kdp (radar, alpha=None, beta=None, kdp_field=None,
                                   rr_field=None)
```

Estimates rainfall rate from kdp using alpha power law

Parameters radar : Radar

Radar object

alpha,beta : floats

Optional. factor (alpha) and exponent (beta) of the power law. If not set the factors are going to be determined according to the radar frequency

kdp_field : str

name of the specific differential phase field to use

rr_field : str

name of the rainfall rate field

Returns rain : dict

Field dictionary containing the rainfall rate.

```
pyart.retrieve.estimate_rain_rate_z(radar, alpha=0.0376, beta=0.6112, refl_field=None,
                                   rr_field=None)
```

Estimates rainfall rate from reflectivity using a power law

Parameters radar : Radar

Radar object

alpha,beta : floats

factor (alpha) and exponent (beta) of the power law

refl_field : str

name of the reflectivity field to use

rr_field : str

name of the rainfall rate field

Returns rain : dict

Field dictionary containing the rainfall rate.

```
pyart.retrieve.estimate_rain_rate_za(radar, alphaz=0.0376, betaz=0.6112, alphaa=None, betaa=None,
                                   refl_field=None, a_field=None, rr_field=None,
                                   master_field=None, thresh=None, thresh_max=False)
```

Estimates rainfall rate from a blending of power law r-alpha and r-z relations.

Parameters radar : Radar

Radar object

alphaz,betaz : floats

factor (alpha) and exponent (beta) of the z-r power law.

alphaa,betaa : floats

Optional. factor (alpha) and exponent (beta) of the a-r power law. If not set the factors are going to be determined according to the radar frequency

refl_field : str

name of the reflectivity field to use

a_field : str

name of the specific attenuation field to use

rr_field : str

name of the rainfall rate field

master_field : str

name of the field that is going to act as master. Has to be either refl_field or kdp_field.
Default is refl_field

thresh : float

value of the threshold that determines when to use the slave field.

thresh_max : Boolean

If true the master field is used up to the thresh value maximum. Otherwise the master field is not used below thresh value.

Returns rain_master : dict

Field dictionary containing the rainfall rate.

```
pyart.retrieve.est_rain_rate_zkdp(radar, alphaz=0.0376, betaz=0.6112, alphakdp=None,  
                                   betakdp=None, refl_field=None, kdp_field=None,  
                                   rr_field=None, master_field=None, thresh=None,  
                                   thresh_max=True)
```

Estimates rainfall rate from a blending of power law r-kdp and r-z relations.

Parameters radar : Radar

Radar object

alphaz,betaz : floats

factor (alpha) and exponent (beta) of the z-r power law.

alphakdp, betakdp : floats

Optional. factor (alpha) and exponent (beta) of the kdp-r power law. If not set the factors are going to be determined according to the radar frequency

refl_field : str

name of the reflectivity field to use

kdp_field : str

name of the specific differential phase field to use

rr_field : str

name of the rainfall rate field

master_field : str

name of the field that is going to act as master. Has to be either refl_field or kdp_field.
Default is refl_field

thresh : float

value of the threshold that determines when to use the slave field.

thresh_max : Boolean

If true the master field is used up to the thresh value maximum. Otherwise the master field is not used below thresh value.

Returns rain_master : dict

Field dictionary containing the rainfall rate.

`pyart.retrieve.est_rain_rate_zpoly(radar, refl_field=None, rr_field=None)`

Estimates rainfall rate from reflectivity using a polynomial Z-R relation developed at McGill University

Parameters `radar` : Radar

Radar object

refl_field : str

name of the reflectivity field to use

rr_field : str

name of the rainfall rate field

Returns `rain` : dict

Field dictionary containing the rainfall rate.

`pyart.retrieve.est_vertical_windshear(radar, az_tol=0.5, wind_field=None, windshear_field=None)`

Estimates wind shear.

Parameters `radar` : Radar

Radar object

az_tol : float

azimuth tolerance to consider gate on top of selected one

wind_field : str

name of the horizontal wind velocity field

windshear_field : str

name of the vertical wind shear field

Returns `windshear` : dict

Field dictionary containing the wind shear field

`pyart.retrieve.est_wind_vel(radar, vert_proj=False, vel_field=None, wind_field=None)`

Estimates wind velocity. Projects the radial wind component to the horizontal or vertical of the azimuth plane. It assumes that the orthogonal component is negligible.

The horizontal wind component is given by: $v = v_r \cos(\text{el}) - v_{el} \sin(\text{el}) + v_{az}$

where: v_r is the radial wind component (measured by the radar) v_{el} is the perpendicular wind component in the azimuth plane. v_{az} is the horizontal component perpendicular to the radial direction and the azimuth plane el is the elevation

The horizontal wind component in the azimuth plane is given by: $v_h = v_r \cos(\text{el}) - v_{el} \sin(\text{el})$

which since we do not know v_{el} we assume: $v_h \sim v_r \cos(\text{el})$

This assumption holds for small elevation angles

The vertical wind component in the azimuth plane is given by: $v_v = v_r \sin(\text{el}) - v_{el} \cos(\text{el})$

which since we do not know v_{el} we assume: $v_v \sim v_r \sin(\text{el})$

This assumption holds for angles close to 90 deg

Parameters `radar` : Radar

Radar object

vert_proj : Boolean

If true estimates the vertical projection, otherwise the horizontal

vel_field : str

name of the velocity field

wind_field : str

name of the velocity field

Returns **wind** : dict

Field dictionary containing the estimated wind velocity

```
pyart.retrieve.fetch_radar_time_profile(sonde_dset, radar, time_key='time',  
                                         height_key='height', nvars=None)
```

Extract the correct profile from a interpolated sonde.

This is an ARM specific method which extract the correct profile out of netCDF Variables from a Interpolated Sonde VAP for the volume start time of a radar object.

Parameters **sonde_dset** : Dataset

Interpolate sonde Dataset.

radar : Radar

Radar object from which the nearest profile will be found.

time_key : string, optional

Key to find a CF startard time variable

height_key : string, optional

Key to find profile height data

nvars : list, optional

NetCDF variable to generated profiles for. If None (the default) all variables with dimension of time, height will be found in nvars.

Returns **return_dic** : dict

Profiles at the start time of the radar

```
pyart.retrieve.get_coeff_attg(freq)  
get the 1-way gas attenuation for a particular frequency
```

Parameters **freq** : float

radar frequency [Hz]

Returns **attg** : float

1-way gas attenuation

```
pyart.retrieve.get_freq_band(freq)  
returns the frequency band name (S, C, X, ...)
```

Parameters **freq** : float

radar frequency [Hz]

Returns **freq_band** : str

frequency band name

`pyart.retrieve.grid_displacement_pc(grid1, grid2, field, level, return_value='pixels')`

Calculate the grid displacement using phase correlation.

See: http://en.wikipedia.org/wiki/Phase_correlation

Implementation inspired by Christoph Gohlke: <http://www.lfd.uci.edu/~gohlke/code/imreg.py.html>

Note that the grid must have the same dimensions in x and y and assumed to have constant spacing in these dimensions.

Parameters `grid1, grid2` : Grid

Py-ART Grid objects separated in time and square in x/y.

field : string

Field to calculate advection from. Field must be in both grid1 and grid2.

level : integer

The vertical (z) level of the grid to use in the calculation.

return_value : str, optional

'pixels', 'distance' or 'velocity'. Distance in pixels (default) or meters or velocity vector in m/s.

Returns `displacement` : two-tuple

Calculated displacement in units of y and x. Value returned in integers if pixels, otherwise floats.

`pyart.retrieve.grid_shift(grid, advection, trim_edges=0, field_list=None)`

Shift a grid by a certain number of pixels.

Parameters `grid`: Grid

Py-ART Grid object.

advection : two-tuple of floats

Number of Pixels to shift the image by.

trim_edges: integer, optional

Edges to cut off the grid and axes, both x and y. Defaults to zero.

field_list : list, optional

List of fields to include in new grid. None, the default, includes all fields from the input grid.

Returns `shifted_grid` : Grid

Grid with fields shifted and, if requested, subset.

`pyart.retrieve.hydroclass_semisupervised(radar, mass_centers=None, weights=array([1., 1., 1., 0.75, 0.5]), refl_field=None, zdr_field=None, rhv_field=None, kdp_field=None, temp_field=None, iso0_field=None, hydro_field=None, temp_ref='temperature')`

Classifies precipitation echoes following the approach by Besic et al (2016)

Parameters `radar` : radar

radar object

Returns **hydro** : dict

hydrometeor classification field

Other Parameters **mass_centers** : ndarray 2D

The centroids for each variable and hydrometeor class in (nclasses, nvariables)

weights : ndarray 1D

The weight given to each variable.

refl_field, zdr_field, rhv_field, kdp_field, temp_field, iso0_field : str

Inputs. Field names within the radar object which represent the horizontal reflectivity, the differential reflectivity, the copolar correlation coefficient, the specific differential phase, the temperature and the height respect to the iso0 fields. A value of None for any of these parameters will use the default field name as defined in the Py-ART configuration file.

hydro_field : str

Output. Field name which represents the hydrometeor class field. A value of None will use the default field name as defined in the Py-ART configuration file.

temp_ref : str

the field use as reference for temperature. Can be either temperature or height_over_iso0

References

Besic, N., Figueras i Ventura, J., Grazioli, J., Gabella, M., Germann, U., and Berne, A.: Hydrometeor classification through statistical clustering of polarimetric radar measurements: a semi-supervised approach, Atmos. Meas. Tech., 9, 4425-4445, doi:10.5194/amt-9-4425-2016, 2016

```
pyart.retrieve.kdp_leastsquare_double_window(radar, swind_len=11, smin_valid=6,
                                              lwind_len=31, lmin_valid=16, zthr=40.0,
                                              phidp_field=None, refl_field=None,
                                              kdp_field=None)
```

Compute the specific differential phase (KDP) from differential phase data using a piecewise least square method. For optimal results PhiDP should be already smoothed and clutter filtered out.

Parameters **radar** : Radar

Radar object.

swind_len : int

The lenght of the short moving window.

smin_valid : int

Minimum number of valid bins to consider the retrieval valid when using the short moving window

lwind_len : int

The lenght of the long moving window.

lmin_valid : int

Minimum number of valid bins to consider the retrieval valid when using the long moving window

zthr : float

reflectivity value above which the short window is used

phidp_field : str

Field name within the radar object which represent the differential phase shift. A value of None will use the default field name as defined in the Py-ART configuration file.

refl_field : str

Field name within the radar object which represent the reflectivity. A value of None will use the default field name as defined in the Py-ART configuration file.

kdp_field : str

Field name within the radar object which represent the specific differential phase shift. A value of None will use the default field name as defined in the Py-ART configuration file.

Returns kdp_dict : dict

Retrieved specific differential phase data and metadata.

```
pyart.retrieve.kdp_leastsquare_single_window(radar, wind_len=11, min_valid=6,  
                                             phidp_field=None, kdp_field=None)
```

Compute the specific differential phase (KDP) from differential phase data using a piecewise least square method. For optimal results PhiDP should be already smoothed and clutter filtered out.

Parameters radar : Radar

Radar object.

wind_len : int

The length of the moving window.

min_valid : int

Minimum number of valid bins to consider the retrieval valid

phidp_field : str

Field name within the radar object which represent the differential phase shift. A value of None will use the default field name as defined in the Py-ART configuration file.

kdp_field : str

Field name within the radar object which represent the specific differential phase shift. A value of None will use the default field name as defined in the Py-ART configuration file.

Returns kdp_dict : dict

Retrieved specific differential phase data and metadata.

```
pyart.retrieve.kdp_maesaka(radar, gatefilter=None, method='cg', backscatter=None, Clpf=1.0,  
                           length_scale=None, first_guess=0.01, finite_order='low',  
                           fill_value=None, proc=1, psidp_field=None, kdp_field=None,  
                           phidp_field=None, debug=False, verbose=False, **kwargs)
```

Compute the specific differential phase (KDP) from corrected (e.g., unfolded) total differential phase data based on the variational method outlined in Maesaka et al. (2012). This method assumes a monotonically increasing propagation differential phase (PHIDP) with increasing range from the radar, and therefore is limited to rainfall below the melting layer and/or warm clouds at weather radar frequencies (e.g., S-, C-, and X-band). This method currently only supports radar data with constant range resolution.

Following the notation of Maesaka et al. (2012), the primary control variable k is proportional to KDP,

$$k^2 = 2 * KDP * dr$$

which, because of the square, assumes that KDP always takes a positive value.

Parameters radar : Radar

Radar containing differential phase field.

gatefilter : GateFilter

A GateFilter indicating radar gates that should be excluded when analysing differential phase measurements.

method : str, optional

Type of scipy.optimize method to use when minimizing the cost functional. The default method uses a nonlinear conjugate gradient algorithm. In Maesaka et al. (2012) they use the Broyden-Fletcher-Goldfarb-Shanno (BFGS) algorithm, however for large functional size (e.g., 100K+ variables) this algorithm is considerably slower than a conjugate gradient algorithm.

backscatter : optional

Define the backscatter differential phase. If None, the backscatter differential phase is set to zero for all range gates. Note that backscatter differential phase can be parameterized using attenuation corrected differential reflectivity.

Clpf : float, optional

The low-pass filter (radial smoothness) constraint weight as in equation (15) of Maesaka et al. (2012).

length_scale : float, optional

Length scale in meters used to bring the dimension and magnitude of the low-pass filter cost functional in line with the observation cost functional. If None, the length scale is set to the range resolution.

first_guess : float, optional

First guess for control variable k . Since k is proportional to the square root of KDP, the first guess should be close to zero to signify a KDP field close to 0 deg/km everywhere. However, the first guess should not be exactly zero in order to avoid convergence criteria after the first iteration. In fact it is recommended to use a value closer to one than zero.

finite_order : 'low' or 'high', optional

The finite difference accuracy to use when computing derivatives.

maxiter : int, optional

Maximum number of iterations to perform during cost functional minimization. The maximum number of iterations are only performed if convergence criteria are not met. For variational schemes such as this one, it is generally not recommended to try and achieve convergence criteria since the values of the cost functional and/or its gradient norm are somewhat arbitrary.

fill_value : float, optional

Value indicating missing or bad data in differential phase field.

proc : int, optional

The number of parallel threads (CPUs) to use. Currently no multiprocessing capability exists.

psidp_field : str, optional

Total differential phase field. If None, the default field name must be specified in the Py-ART configuration file.

kdp_field : str, optional

Specific differential phase field. If None, the default field name must be specified in the Py-ART configuration file.

phidp_field : str, optional

Propagation differential phase field. If None, the default field name must be specified in the Py-ART configuration file.

debug : bool, optional

True to print debugging information, False to suppress.

verbose : bool, optional

True to print relevant information, False to suppress.

Returns **kdp_dict** : dict

Retrieved specific differential phase data and metadata.

phidpf_dict, phidpr_dict : dict

Retrieved forward and reverse direction propagation differential phase data and metadata.

References

Maesaka, T., Iwanami, K. and Maki, M., 2012: “Non-negative KDP Estimation by Monotone Increasing PHIDP Assumption below Melting Layer”. The Seventh European Conference on Radar in Meteorology and Hydrology.

`pyart.retrieve.kdp_schneebeli` (*radar, gatefilter=None, fill_value=None, psidp_field=None, kdp_field=None, phidp_field=None, band='C', rcov=0, pcov=0, prefilter_psidp=False, filter_opt=None, parallel=True*)

Estimates Kdp with the Kalman filter method by Schneebeli and al. (2014) for a set of psidp measurements.

Parameters **radar** : Radar

Radar containing differential phase field.

gatefilter : GateFilter, optional

A GateFilter indicating radar gates that should be excluded when analysing differential phase measurements.

fill_value : float, optional

Value indicating missing or bad data in differential phase field, if not specified, the default in the Py-ART configuration file will be used

psidp_field : str, optional

Total differential phase field. If None, the default field name must be specified in the Py-ART configuration file.

kdp_field : str, optional

Specific differential phase field. If None, the default field name must be specified in the Py-ART configuration file.

phidp_field : str, optional

Propagation differential phase field. If None, the default field name must be specified in the Py-ART configuration file.

band : char, optional

Radar frequency band string. Accepted "X", "C", "S" (capital or not). The band is used to compute intercepts -c and slope b of the $\Delta = b \cdot Kdp + c$ relation

rcov : 3x3 float array, optional

Measurement error covariance matrix

pcov : 4x4 float array, optional

Scaled state transition error covariance matrix

prefilter_psidp : bool, optional

If set, the psidp measurements will first be filtered with the `filter_psidp` method, which can improve the quality of the final Kdp

filter_opt : dict, optional

The arguments for the `prefilter_psidp` method, if empty, the defaults arguments of this method will be used

parallel : bool, optional

Flag to enable parallel computation (one core for every psidp profile)

Returns kdp_dict : dict

Retrieved specific differential phase data and metadata.

kdp_std_dict : dict

Estimated specific differential phase standard dev. data and metadata.

phidp_dict : dict

Retrieved differential phase data and metadata.

References

Schneebeli, M., Grazioli, J., and Berne, A.: Improved Estimation of the Specific Differential Phase SHIFT Using a Compilation of Kalman Filter Ensembles, IEEE T. Geosci. Remote Sens., 52, 5137-5149, doi:10.1109/TGRS.2013.2287017, 2014.

```
pyart.retrieve.kdp_vulpiani(radar, gatefilter=None, fill_value=None, psidp_field=None,
                             kdp_field=None, phidp_field=None, band='C', windsize=10,
                             n_iter=10, interp=False, prefilter_psidp=False, filter_opt=None,
                             parallel=False)
```

Estimates Kdp with the Vulpiani method for a 2D array of psidp measurements with the first dimension being the distance from radar and the second dimension being the angles (azimuths for PPI, elev for RHI). The input psidp is assumed to be pre-filtered (for ex. with the `filter_psidp` function)

Parameters radar : Radar

Radar containing differential phase field.

gatefilter [GateFilter, optional] A GateFilter indicating radar gates that should be excluded when analysing differential phase measurements.

fill_value [float, optional] Value indicating missing or bad data in differential phase field, if not specified, the default in the Py-ART configuration file will be used

psidp_field [str, optional] Total differential phase field. If None, the default field name must be specified in the Py-ART configuration file.

kdp_field [str, optional] Specific differential phase field. If None, the default field name must be specified in the Py-ART configuration file.

phidp_field [str, optional] Propagation differential phase field. If None, the default field name must be specified in the Py-ART configuration file.

band [char, optional] Radar frequency band string. Accepted “X”, “C”, “S” (capital or not). It is used to set default boundaries for expected values of Kdp

windsize [int, optional] Size in # of gates of the range derivative window, should be even

n_iter [int, optional] Number of iterations of the method. Default is 10.

interp [bool, optional] If True, all the nans are interpolated. The advantage is that less data are lost (the iterations in fact are “eating the edges”) but some non-linear errors may be introduced

prefilter_psidp [bool, optional] If set, the psidp measurements will first be filtered with the filter_psidp method, which can improve the quality of the final Kdp

filter_opt [dict, optional] The arguments for the prefilter_psidp method, if empty, the defaults arguments of this method will be used

parallel [bool, optional] Flag to enable parallel computation (one core for every psidp profile)

Returns **kdp_dict** : dict

Retrieved specific differential phase data and metadata.

phidpr_dict,: dict Retrieved differential phase data and metadata.

`pyart.retrieve.map_profile_to_gates` (*profile, heights, radar, toa=None, profile_field=None, height_field=None*)

Given a profile of a variable map it to the gates of radar assuming 4/3R_e.

Parameters **profile** : array

Profile array to map.

heights : array

Monotonically increasing heights in meters with same shape as profile.

radar : Radar

Radar to map to

toa: float, optional

Top of atmosphere, where to use profile up to. If None check for mask and use lowest element, if no mask uses whole profile.

height_field : str

Name to use for height field metadata. None will use the default field name from the Py-ART configuration file.

profile_field : str

Name to use for interpolate profile field metadata. None will use the default field name from the Py-ART configuration file.

Returns **height_dict, profile_dict** : dict

Field dictionaries containing the height of the gates and the profile interpolated onto the radar gates.

```
pyart.retrieve.steiner_conv_strat(grid,          dx=None,          dy=None,          intense=42.0,
                                   work_level=3000.0,          peak_relation='default',
                                   area_relation='medium',          bkg_rad=11000.0,
                                   use_intense=True, fill_value=None, refl_field=None)
```

Partition reflectivity into convective-stratiform using the Steiner et al. (1995) algorithm.

Parameters **grid** : Grid

Grid containing reflectivity field to partition.

Returns **eclass** : dict

Steiner convective-stratiform classification dictionary.

Other Parameters **dx, dy** : float

The x- and y-dimension resolutions in meters, respectively. If None the resolution is determined from the first two axes values.

intense : float

The intensity value in dBZ. Grid points with a reflectivity value greater or equal to the intensity are automatically flagged as convective. See reference for more information.

work_level : float

The working level (separation altitude) in meters. This is the height at which the partitioning will be done, and should minimize bright band contamination. See reference for more information.

peak_relation : 'default' or 'sgp'

The peakedness relation. See reference for more information.

area_relation : 'small', 'medium', 'large', or 'sgp'

The convective area relation. See reference for more information.

bkg_rad : float

The background radius in meters. See reference for more information.

use_intense : bool

True to use the intensity criteria.

fill_value : float

Missing value used to signify bad data points. A value of None will use the default fill value as defined in the Py-ART configuration file.

refl_field : str

Field in grid to use as the reflectivity during partitioning. None will use the default reflectivity field name from the Py-ART configuration file.

References

Steiner, M. R., R. A. Houze Jr., and S. E. Yuter, 1995: Climatological Characterization of Three-Dimensional Storm Structure from Operational Radar and Rain Gauge Data. *J. Appl. Meteor.*, 34, 1978-2007.

MAPPING (PYART.MAP)

Py-ART has a robust function for mapping radar data from the collected radar coordinates to Cartesian coordinates.

<code>grid_from_radars(radars, grid_shape, grid_limits)</code>	Map one or more radars to a Cartesian grid returning a Grid object.
<code>map_to_grid(radars, grid_shape, grid_limits)</code>	Map one or more radars to a Cartesian grid.
<code>map_gates_to_grid(radars, grid_shape, ...[, ...])</code>	Map gates from one or more radars to a Cartesian grid.
<code>example_roi_func_constant(zg, yg, xg)</code>	Example RoI function which returns a constant radius.
<code>example_roi_func_dist(zg, yg, xg)</code>	Example RoI function which returns a radius which grows with distance.
<code>example_roi_func_dist_beam(zg, yg, xg)</code>	Example RoI function which returns a radius which grows with distance and whose parameters are based on virtual beam size.

`pyart.map.example_roi_func_constant(zg, yg, xg)`

Example RoI function which returns a constant radius.

Parameters `zg, yg, xg` : float

Distance from the grid center in meters for the x, y and z axes.

Returns `roi` : float

Radius of influence in meters

`pyart.map.example_roi_func_dist(zg, yg, xg)`

Example RoI function which returns a radius which grows with distance.

Parameters `zg, yg, xg` : float

Distance from the grid center in meters for the x, y and z axes.

Returns `roi` : float

`pyart.map.example_roi_func_dist_beam(zg, yg, xg)`

Example RoI function which returns a radius which grows with distance and whose parameters are based on virtual beam size.

Parameters `zg, yg, xg` : float

Distance from the grid center in meters for the x, y and z axes.

Returns `roi` : float

`pyart.map.grid_from_radars(radars, grid_shape, grid_limits, gridding_algo='map_gates_to_grid',
**kwargs)`

Map one or more radars to a Cartesian grid returning a Grid object.

Additional arguments are passed to `map_to_grid()` or `map_gates_to_grid()`.

Parameters **radars** : Radar or tuple of Radar objects.

Radar objects which will be mapped to the Cartesian grid.

grid_shape : 3-tuple of floats

Number of points in the grid (z, y, x).

grid_limits : 3-tuple of 2-tuples

Minimum and maximum grid location (inclusive) in meters for the z, y, x coordinates.

gridding_algo : 'map_to_grid' or 'map_gates_to_grid'

Algorithm to use for gridding. 'map_to_grid' finds all gates within a radius of influence for each grid point, 'map_gates_to_grid' maps each radar gate onto the grid using a radius of influence and is typically significantly faster.

Returns **grid** : Grid

A `pyart.io.Grid` object containing the gridded radar data.

See also:

[`map_to_grid`](#) Map to grid and return a dictionary of radar fields.

[`map_gates_to_grid`](#) Map each gate onto a grid returning a dictionary of radar fields.

```
pyart.map.map_gates_to_grid(radars, grid_shape, grid_limits, grid_origin=None,
                             grid_origin_alt=None, grid_projection=None, fields=None,
                             gatefilters=False, map_roi=True, weighting_function='Barnes',
                             toa=17000.0, roi_func='dist_beam', constant_roi=500.0,
                             z_factor=0.05, xy_factor=0.02, min_radius=500.0, h_factor=1.0,
                             nb=1.5, bsp=1.0, **kwargs)
```

Map gates from one or more radars to a Cartesian grid.

Generate a Cartesian grid of points for the requested fields from the collected points from one or more radars. For each radar gate that is not filtered a radius of influence is calculated. The weighted field values for that gate are added to all grid points within that radius. This routine scaled linearly with the number of radar gates and the effective grid size.

Parameters not defined below are identical to those in `map_to_grid()`.

Parameters **roi_func** : str or RoIFunction

Radius of influence function. A functions which takes an z, y, x grid location, in meters, and returns a radius (in meters) within which all collected points will be included in the weighting for that grid points. Examples can be found in the Typically following strings can use to specify a built in radius of influence function:

- constant: constant radius of influence.
- dist: radius grows with the distance from each radar.
- dist_beam: radius grows with the distance from each radar and parameter are based of virtual beam sizes.

A custom RoIFunction can be defined using the RoIFunction class and defining a `get_roi` method which returns the radius. For efficient mapping this class should be implemented in Cython.

Returns **grids** : dict

Dictionary of mapped fields. The keysof the dictionary are given by parameter fields.
Each elements is a *grid_size* float64 array containing the interpolated grid for that field.

See also:

grid_from_radars Map to a grid and return a Grid object

map_to_grid Create grid by finding the radius of influence around each grid point.

```
pyart.map.map_to_grid(radars, grid_shape, grid_limits, grid_origin=None, grid_origin_alt=None,
                      grid_projection=None, fields=None, gatefilters=False, map_roi=True,
                      weighting_function='Barnes', toa=17000.0, copy_field_data=True, algo-
                      rithm='kd_tree', leafsize=10.0, roi_func='dist_beam', constant_roi=500.0,
                      z_factor=0.05, xy_factor=0.02, min_radius=500.0, h_factor=1.0, nb=1.5,
                      bsp=1.0, **kwargs)
```

Map one or more radars to a Cartesian grid.

Generate a Cartesian grid of points for the requested fields from the collected points from one or more radars. The field value for a grid point is found by interpolating from the collected points within a given radius of influence and weighting these nearby points according to their distance from the grid points. Collected points are filtered according to a number of criteria so that undesired points are not included in the interpolation.

Parameters **radars** : Radar or tuple of Radar objects.

Radar objects which will be mapped to the Cartesian grid.

grid_shape : 3-tuple of floats

Number of points in the grid (z, y, x).

grid_limits : 3-tuple of 2-tuples

Minimum and maximum grid location (inclusive) in meters for the z, y, x coordinates.

grid_origin : (float, float) or None

Latitude and longitude of grid origin. None sets the origin to the location of the first radar.

grid_origin_alt: float or None

Altitude of grid origin, in meters. None sets the origin to the location of the first radar.

grid_projection : dic or str

Projection parameters defining the map projection used to transform the locations of the radar gates in geographic coordinate to Cartesian coordinates. None will use the default dictionary which uses a native azimuthal equidistance projection. See [pyart.core.Grid\(\)](#) for additional details on this parameter. The geographic coordinates of the radar gates are calculated using the projection defined for each radar. No transformation is used if a grid_origin and grid_origin_alt are None and a single radar is specified.

fields : list or None

List of fields within the radar objects which will be mapped to the cartesian grid. None, the default, will map the fields which are present in all the radar objects.

gatefilters : GateFilter, tuple of GateFilter objects, optional

Specify what gates from each radar will be included in the interpolation onto the grid. Only gates specified in each gatefilters will be included in the mapping to the grid. A single GateFilter can be used if a single Radar is being mapped. A value of False for a specific element or the entire parameter will apply no filtering of gates for a

specific radar or all radars (the default). Similarly a value of None will create a GateFilter from the radar moments using any additional arguments by passing them to `moment_based_gate_filter()`.

roi_func : str or function

Radius of influence function. A functions which takes an z, y, x grid location, in meters, and returns a radius (in meters) within which all collected points will be included in the weighting for that grid points. Examples can be found in the `example_roi_func_constant()`, `example_roi_func_dist()`, and `example_roi_func_dist_beam()`. Alternatively the following strings can use to specify a built in radius of influence function:

- constant: constant radius of influence.
- dist: radius grows with the distance from each radar.
- dist_beam: radius grows with the distance from each radar and parameter are based of virtual beam sizes.

The parameters which control these functions are listed in the *Other Parameters* section below.

map_roi : bool

True to include a radius of influence field in the returned dictionary under the 'ROI' key. This is the value of `roi_func` at all grid points.

weighting_function : 'Barnes' or 'Cressman'

Functions used to weight nearby collected points when interpolating a grid point.

toa : float

Top of atmosphere in meters. Collected points above this height are not included in the interpolation.

Returns grids : dict

Dictionary of mapped fields. The keysof the dictionary are given by parameter fields. Each elements is a `grid_size` float64 array containing the interpolated grid for that field.

Other Parameters constant_roi : float

Radius of influence parameter for the built in 'constant' function. This parameter is the constant radius in meter for all grid points. This parameter is only used when `roi_func` is *constant*.

z_factor, xy_factor, min_radius : float

Radius of influence parameters for the built in 'dist' function. The parameter correspond to the radius size increase, in meters, per meter increase in the z-dimension from the nearest radar, the same foreach meteter in the xy-distance from the nearest radar, and the minimum radius of influence in meters. These parameters are only used when `roi_func` is 'dist'.

h_factor, nb, bsp, min_radius : float

Radius of influence parameters for the built in 'dist_beam' function. The parameter correspond to the height scaling, virtual beam width, virtual beam spacing, and minimum radius of influence. These parameters are only used when `roi_func` is 'dist_mean'.

copy_field_data : bool

True to copy the data within the radar fields for faster gridding, the dtype for all fields in the grid will be float64. False will not copy the data which preserves the dtype of the fields in the grid, may use less memory but results in significantly slower gridding times. When False gates which are masked in a particular field but are not masked in the *refl_field* field will still be included in the interpolation. This can be prevented by setting this parameter to True or by gridding each field individually setting the *refl_field* parameter and the *fields* parameter to the field in question. It is recommended to set this parameter to True.

algorithm : 'kd_tree'.

Algorithms to use for finding the nearest neighbors. 'kd_tree' is the only valid option.

leafsize : int

Leaf size passed to the neighbor lookup tree. This can affect the speed of the construction and query, as well as the memory required to store the tree. The optimal value depends on the nature of the problem. This value should only effect the speed of the gridding, not the results.

See also:

[*grid_from_radars*](#) Map to grid and return a Grid object.

GRAPHING (PYART.GRAPH)

Creating plots of Radar and Grid fields.

9.1 Plotting radar data

<i>RadarDisplay</i> (radar[, shift])	A display object for creating plots from data in a radar object.
<i>RadarMapDisplay</i> (radar[, shift])	A display object for creating plots on a geographic map from data in a Radar object.
<i>AirborneRadarDisplay</i> (radar[, shift])	A display object for creating plots from data in a airborne radar object.
<i>RadarMapDisplayCartopy</i> (radar[, shift, ...])	A display object for creating plots on a geographic map from data in a Radar object.

9.2 Plotting grid data

<i>GridMapDisplay</i> (grid[, debug])	A class for creating plots from a grid object on top of a Basemap.
---------------------------------------	--

```
class pyart.graph.AirborneRadarDisplay (radar, shift=(0.0, 0.0))
```

Bases: `pyart.graph.radardisplay.RadarDisplay`

A display object for creating plots from data in a airborne radar object.

Parameters **radar** : Radar

Radar object to use for creating plots, should be an airborne radar.

shift : (float, float)

Shifts in km to offset the calculated x and y locations.

Attributes

plots	(list) List of plots created.
plot_vars	(list) List of fields plotted, order matches plot list.
cbs	(list) List of colorbars created.
origin	(str) 'Origin' or 'Radar'.
shift	((float, float)) Shift in meters.
loc	((float, float)) Latitude and Longitude of radar in degrees.
fields	(dict) Radar fields.
scan_type	(str) Scan type.
ranges	(array) Gate ranges in meters.
azimuths	(array) Azimuth angle in degrees.
elevations	(array) Elevations in degrees.
fixed_angle	(array) Scan angle in degrees.
rotation	(array) Rotation angle in degrees.
roll	(array) Roll angle in degrees.
drift	(array) Drift angle in degrees.
tilt	(array) Tilt angle in degrees.
heading	(array) Heading angle in degrees.
pitch	(array) Pitch angle in degrees.
altitude	(array) Altitude angle in meters.

Methods

<i>generate_az_rhi_title</i> (field, azimuth)	Generate a title for a ray plot.
<i>generate_filename</i> (field, sweep[, ext])	Generate a filename for a plot.
<i>generate_ray_title</i> (field, ray)	Generate a title for a ray plot.
<i>generate_title</i> (field, sweep)	Generate a title for a plot.
<i>generate_vpt_title</i> (field)	Generate a title for a VPT plot.
<i>label_xaxis_r</i> ([ax])	Label the xaxis with the default label for r units.
<i>label_xaxis_rays</i> ([ax])	Label the yaxis with the default label for rays.
<i>label_xaxis_time</i> ([ax])	Label the yaxis with the default label for rays.
<i>label_xaxis_x</i> ([ax])	Label the xaxis with the default label for x units.
<i>label_yaxis_field</i> (field[, ax])	Label the yaxis with the default label for a field units.
<i>label_yaxis_y</i> ([ax])	Label the yaxis with the default label for y units.
<i>label_yaxis_z</i> ([ax])	Label the yaxis with the default label for z units.
<i>plot</i> (field[, sweep])	Create a plot appropriate for the radar.
<i>plot_azimuth_to_rhi</i> (field, target_azimuth[, ...])	Plot pseudo-RHI scan by extracting the vertical field associated with the given azimuth.
<i>plot_colorbar</i> ([mappable, field, label, ...])	Plot a colorbar.
<i>plot_cross_hair</i> (size[, npts, ax])	Plot a cross-hair on a ppi plot.
<i>plot_grid_lines</i> ([ax, col, ls])	Plot grid lines.
<i>plot_label</i> (label, location[, symbol, ...])	Plot a single symbol and label at a given location.
<i>plot_labels</i> (labels, locations[, symbols, ...])	Plot symbols and labels at given locations.
<i>plot_ppi</i> (field[, sweep, mask_tuple, vmin, ...])	Plot a PPI.
<i>plot_range_ring</i> (range_ring_location_km[, ...])	Plot a single range ring.
<i>plot_range_rings</i> (range_rings[, ax, col, ls, lw])	Plot a series of range rings.
<i>plot_ray</i> (field, ray[, format_str, ...])	Plot a single ray.
<i>plot_rhi</i> (field[, sweep, mask_tuple, vmin, ...])	Plot a RHI.

Continued on next page

Table 9.3 – continued from previous page

<code>plot_sweep_grid(field[, sweep, mask_tuple, ...])</code>	Plot a sweep as a grid.
<code>plot_vpt(field[, mask_tuple, vmin, vmax, ...])</code>	Plot a VPT scan.
<code>set_aspect_ratio([aspect_ratio, ax])</code>	Set the aspect ratio for plot area.
<code>set_limits([xlim, ylim, ax])</code>	Set the display limits.

__class__alias of `type`**__delattr__**Implement `delattr(self, name)`.**__dict__** = `mappingproxy({'label_xaxis_x': <function AirborneRadarDisplay.label_xaxis_x>, '__init__': <function AirborneRadarDisplay.__init__>, ...})`**__dir__** () → listdefault `dir()` implementation**__eq__**Return `self==value`.**__format__** ()

default object formatter

__ge__Return `self>=value`.**__getattr__**Return `getattr(self, name)`.**__gt__**Return `self>value`.**__hash__**Return `hash(self)`.**__init__** (*radar*, *shift*=(0.0, 0.0))

Initialize the object.

__le__Return `self<=value`.**__lt__**Return `self<value`.**__module__** = `'pyart.graph.radardisplay_airborne'`**__ne__**Return `self!=value`.**__new__** ()Create and return a new object. See `help(type)` for accurate signature.**__reduce__** ()

helper for pickle

__reduce_ex__ ()

helper for pickle

__repr__Return `repr(self)`.**__setattr__**Implement `setattr(self, name, value)`.

__sizeof__ () → int
size of object in memory, in bytes

__str__
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

_get_azimuth_rhi_data_x_y_z (*field*, *target_azimuth*, *edges*, *mask_tuple*, *filter_transitions*, *gatefilter*)
Retrieve and return pseudo-RHI data from a plot function.

_get_colorbar_label (*field*)
Return a colorbar label for a given field.

_get_data (*field*, *sweep*, *mask_tuple*, *filter_transitions*, *gatefilter*)
Retrieve and return data from a plot function.

_get_ray_data (*field*, *ray*, *mask_tuple*, *gatefilter*)
Retrieve and return ray data from a plot function.

_get_vpt_data (*field*, *mask_tuple*, *filter_transitions*, *gatefilter*)
Retrieve and return vpt data from a plot function.

_get_x_y (*sweep*, *edges*, *filter_transitions*)
Retrieve and return x and y coordinate in km.

_get_x_y_z (*sweep*, *edges*, *filter_transitions*)
Retrieve and return x, y, and z coordinate in km.

_get_x_z (*sweep*, *edges*, *filter_transitions*)
Retrieve and return x and z coordinate in km.

_label_axes_ppi (*axis_labels*, *ax*)
Set the x and y axis labels for a PPI plot.

_label_axes_ray (*axis_labels*, *field*, *ax*)
Set the x and y axis labels for a ray plot.

_label_axes_rhi (*axis_labels*, *ax*)
Set the x and y axis labels for a RHI plot.

_label_axes_vpt (*axis_labels*, *time_axis_flag*, *ax*)
Set the x and y axis labels for a PPI plot.

_set_az_rhi_title (*field*, *azimuth*, *title*, *ax*)
Set the figure title for a ray plot using a default title.

_set_ray_title (*field*, *ray*, *title*, *ax*)
Set the figure title for a ray plot using a default title.

_set_title (*field*, *sweep*, *title*, *ax*)
Set the figure title using a default title.

_set_vpt_time_axis (*ax*, *date_time_form=None*, *tz=None*)
Set the x axis as a time formatted axis.

Parameters **ax** : Matplotlib axis instance

Axis to plot. None will use the current axis.

date_time_form : str

Format of the time string for x-axis labels.

tz : str

Time zone info to use when creating axis labels (see datetime).

_set_vpt_title (*field, title, ax*)

Set the figure title using a default title.

generate_az_rhi_title (*field, azimuth*)

Generate a title for a ray plot.

Parameters **field** : str

Field plotted.

azimuth : float

Azimuth plotted.

Returns **title** : str

Plot title.

generate_filename (*field, sweep, ext='png'*)

Generate a filename for a plot.

Generated filename has form: radar_name_field_sweep_time.ext

Parameters **field** : str

Field plotted.

sweep : int

Sweep plotted.

ext : str

Filename extension.

Returns **filename** : str

Filename suitable for saving a plot.

generate_ray_title (*field, ray*)

Generate a title for a ray plot.

Parameters **field** : str

Field plotted.

ray : int

Ray plotted.

Returns **title** : str

Plot title.

generate_title (*field, sweep*)

Generate a title for a plot.

Parameters **field** : str

Field plotted.

sweep : int

Sweep plotted.

Returns **title** : str

Plot title.

generate_vpt_title (*field*)

Generate a title for a VPT plot.

Parameters **field** : str

Field plotted.

Returns **title** : str

Plot title.

label_xaxis_r (*ax=None*)

Label the xaxis with the default label for r units.

label_xaxis_rays (*ax=None*)

Label the yaxis with the default label for rays.

label_xaxis_time (*ax=None*)

Label the yaxis with the default label for rays.

label_xaxis_x (*ax=None*)

Label the xaxis with the default label for x units.

label_yaxis_field (*field, ax=None*)

Label the yaxis with the default label for a field units.

label_yaxis_y (*ax=None*)

Label the yaxis with the default label for y units.

label_yaxis_z (*ax=None*)

Label the yaxis with the default label for z units.

plot (*field, sweep=0, **kwargs*)

Create a plot appropriate for the radar.

This function calls the plotting function corresponding to the `scan_type` of the radar. Additional keywords can be passed to customize the plot, see the appropriate plot function for the allowed keywords.

Parameters **field** : str

Field to plot.

sweep : int

Sweep number to plot, not used for VPT scans.

See also:

[*plot_ppi*](#) Plot a PPI scan

[*plot_sweep_grid*](#) Plot a RHI or VPT scan

plot_azimuth_to_rhi (*field*, *target_azimuth*, *mask_tuple*=None, *vmin*=None, *vmax*=None, *norm*=None, *cmap*=None, *mask_outside*=False, *title*=None, *title_flag*=True, *axislabels*=(None, None), *axislabels_flag*=True, *colorbar_flag*=True, *colorbar_label*=None, *colorbar_orient*='vertical', *edges*=True, *gatefilter*=None, *reverse_xaxis*=None, *filter_transitions*=True, *ax*=None, *fig*=None, *ticks*=None, *ticklabs*=None, *raster*=None, ***kwargs*)

Plot pseudo-RHI scan by extracting the vertical field associated with the given azimuth.

Additional arguments are passed to Matplotlib's `pcolormesh` function.

Parameters **field** : str

Field to plot.

target_azimuth : integer

Azimuthal angle in degrees where cross section will be taken.

Other Parameters **mask_tuple** : (str, float)

2-Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask to ['NCP', 0.5]. None performs no masking.

vmin : float

Luminance minimum value, None for default value. Parameter is ignored if norm is not None.

vmax : float

Luminance maximum value, None for default value. Parameter is ignored if norm is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the vmin and vmax parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

title : str

Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

reverse_xaxis : bool or None

True to reverse the x-axis so the plot reads east to west, False to have east to west. None (the default) will reverse the axis only when all the distances are negative.

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions : bool

True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

raster : bool

False by default. Set to True to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

plot_colorbar (*mappable=None, field=None, label=None, orient='vertical', cax=None, ax=None, fig=None, ticks=None, ticklabs=None*)

Plot a colorbar.

Parameters mappable : Image, ContourSet, etc.

Image, ContourSet, etc to which the colorbar applied. If None the last mappable object will be used.

field : str

Field to label colorbar with.

label : str

Colorbar label. None will use a default value from the last field plotted.

orient : str

Colorbar orientation, either 'vertical' [default] or 'horizontal'.

cax : Axis

Axis onto which the colorbar will be drawn. None is also valid.

ax : Axes

Axis onto which the colorbar will be drawn. None is also valid.

fig : Figure

Figure to place colorbar on. None will use the current figure.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

plot_cross_hair (*size, npts=100, ax=None*)

Plot a cross-hair on a ppi plot.

Parameters **size** : float

Size of cross-hair in km.

npts: int

Number of points in the cross-hair, higher for better resolution.

ax : Axis

Axis to plot on. None will use the current axis.

plot_grid_lines (*ax=None, col='k', ls=':'*)

Plot grid lines.

Parameters **ax** : Axis

Axis to plot on. None will use the current axis.

col : str or value

Color to use for grid lines.

ls : str

Linestyle to use for grid lines.

plot_label (*label, location, symbol='r+', text_color='k', ax=None*)

Plot a single symbol and label at a given location.

Transforms of the symbol location in latitude and longitude units to x and y plot units is performed using an azimuthal equidistance map projection centered at the radar.

Parameters **label** : str

Label text to place just above symbol.

location : 2-tuples

Tuple of latitude, longitude (in degrees) at which the symbol will be place. The label is placed just above the symbol.

symbol : str

Matplotlib color+marker strings defining the symbol to place at the given location.

text_color : str

Matplotlib color defining the color of the label text.

ax : Axis

Axis to plot on. None will use the current axis.

plot_labels (*labels, locations, symbols='r+', text_color='k', ax=None*)

Plot symbols and labels at given locations.

Parameters labels : list of str

List of labels to place just above symbols.

locations : list of 2-tuples

List of latitude, longitude (in degrees) tuples at which symbols will be place. Labels are placed just above the symbols.

symbols : list of str or str

List of matplotlib color+marker strings defining symbols to place at given locations. If a single string is provided, that symbol will be placed at all locations.

text_color : str

Matplotlib color defining the color of the label text.

ax : Axis

Axis to plot on. None will use the current axis.

plot_ppi (*field, sweep=0, mask_tuple=None, vmin=None, vmax=None, norm=None, cmap=None, mask_outside=False, title=None, title_flag=True, axislabels=(None, None), axislabels_flag=True, colorbar_flag=True, colorbar_label=None, colorbar_orient='vertical', edges=True, gatefilter=None, filter_transitions=True, ax=None, fig=None, ticks=None, ticklabs=None, raster=None, **kwargs*)

Plot a PPI.

Additional arguments are passed to Matplotlib's pcolormesh function.

Parameters field : str

Field to plot.

sweep : int, optional

Sweep number to plot.

Other Parameters mask_tuple : (str, float)

Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

vmin : float

Luminance minimum value, None for default value. Parameter is ignored is norm is not None.

vmax : float

Luminance maximum value, None for default value. Parameter is ignored is norm is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside : bool

True to mask data outside of vmin, vmax. False performs no masking.

title : str

Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions : bool

True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

raster : bool

False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

plot_range_ring (*range_ring_location_km, npts=100, ax=None, col='k', ls='-', lw=2*)

Plot a single range ring.

Parameters range_ring_location_km : float

Location of range ring in km.

npts: int

Number of points in the ring, higher for better resolution.

ax : Axis

Axis to plot on. None will use the current axis.

col : str or value

Color to use for range rings.

ls : str

Linestyle to use for range rings.

plot_range_rings (*range_rings, ax=None, col='k', ls='-', lw=2*)

Plot a series of range rings.

Parameters range_rings : list

List of locations in km to draw range rings.

ax : Axis

Axis to plot on. None will use the current axis.

col : str or value

Color to use for range rings.

ls : str

Linestyle to use for range rings.

plot_ray (*field, ray, format_str='k-', mask_tuple=None, ray_min=None, ray_max=None, mask_outside=False, title=None, title_flag=True, axislabels=(None, None), gate_filter=None, axislabels_flag=True, ax=None, fig=None*)

Plot a single ray.

Parameters field : str

Field to plot.

ray : int

Ray number to plot.

Other Parameters **format_str** : str

Format string defining the line style and marker.

mask_tuple : (str, float)

Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

ray_min : float

Minimum ray value, None for default value, ignored if mask_outside is False.

ray_max : float

Maximum ray value, None for default value, ignored if mask_outside is False.

mask_outside : bool

True to mask data outside of vmin, vmax. False performs no masking.

title : str

Title to label plot with, None to use default title generated from the field and ray parameters. Parameter is ignored if title_flag is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

plot_rhi (*field*, *sweep*=0, *mask_tuple*=None, *vmin*=None, *vmax*=None, *norm*=None, *cmap*=None, *mask_outside*=False, *title*=None, *title_flag*=True, *axislabels*=(None, None), *axislabels_flag*=True, *reverse_xaxis*=None, *colorbar_flag*=True, *colorbar_label*=None, *colorbar_orient*='vertical', *edges*=True, *gatefilter*=None, *filter_transitions*=True, *ax*=None, *fig*=None, *ticks*=None, *ticklabs*=None, *raster*=False, ***kwargs*)

Plot a RHI.

Additional arguments are passed to Matplotlib's pcolormesh function.

Parameters **field** : str

Field to plot.

sweep : int,

Sweep number to plot.

Other Parameters **mask_tuple** : (str, float)

2-Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask to ['NCP', 0.5]. None performs no masking.

vmin : float

Luminance minimum value, None for default value. Parameter is ignored is norm is not None.

vmax : float

Luminance maximum value, None for default value. Parameter is ignored is norm is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

title : str

Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

reverse_xaxis : bool or None

True to reverse the x-axis so the plot reads west to east, False to have east to west. None (the default) will reverse the axis only when all the distances are negative. (i.e) axis will be absolute distance without taking into consideration the orientation

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions : bool

True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

raster : bool

False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

plot_sweep_grid (*field*, *sweep*=0, *mask_tuple*=None, *vmin*=None, *vmax*=None, *cmap*=None, *norm*=None, *mask_outside*=False, *title*=None, *title_flag*=True, *ax_islabels*=(None, None), *axislabels_flag*=True, *colorbar_flag*=True, *colorbar_label*=None, *colorbar_orient*='vertical', *edges*=True, *filter_transitions*=True, *ax*=None, *fig*=None, *gatefilter*=None, *raster*=True, ***kwargs*)

Plot a sweep as a grid.

Additional arguments are passed to Matplotlib's pcolormesh function.

Parameters **field** : str

Field to plot.

sweep : int, optional

Sweep number to plot.

Other Parameters **mask_tuple** : (str, float)

Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

vmin : float

Luminance minimum value, None for default value. Parameter is ignored if norm is not None.

vmax : float

Luminance maximum value, None for default value. Parameter is ignored if norm is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside : bool

True to mask data outside of vmin, vmax. False performs no masking.

title : str

Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions : bool

True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

raster : bool

False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

plot_vpt (*field*, *mask_tuple*=None, *vmin*=None, *vmax*=None, *norm*=None, *cmap*=None, *mask_outside*=False, *title*=None, *title_flag*=True, *axislabels*=(None, None), *axislabels_flag*=True, *colorbar_flag*=True, *colorbar_label*=None, *colorbar_orient*='vertical', *edges*=True, *gatefilter*=None, *filter_transitions*=True, *time_axis_flag*=False, *date_time_form*=None, *tz*=None, *ax*=None, *fig*=None, *ticks*=None, *ticklabs*=None, *raster*=None, ***kwargs*)

Plot a VPT scan.

Additional arguments are passed to Matplotlib's pcolormesh function.

Parameters field : str

Field to plot.

Other Parameters mask_tuple : (str, float)

Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

vmin : float

Luminance minimum value, None for default value. Parameter is ignored if norm is not None.

vmax : float

Luminance maximum value, None for default value. Parameter is ignored if norm is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the vmin and vmax parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside : bool

True to mask data outside of vmin, vmax. False performs no masking.

title : str

Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if `axislabels_flag` is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions : bool

True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the `antenna_transition` attribute of the underlying radar is not present.

time_axis_flag : bool

True to plot the x-axis as time. False uses the index number. Default is False - index-based.

date_time_form : str, optional

Format of the time string for x-axis labels. Parameter is ignored if `time_axis_flag` is set to False.

tz : str, optional

Time zone info to use when creating axis labels (see `datetime`). Parameter is ignored if `time_axis_flag` is set to False.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

raster : bool

False by default. Set to true to render the display as a raster rather than a vector in call to `pcolormesh`. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

set_aspect_ratio (*aspect_ratio=0.75, ax=None*)

Set the aspect ratio for plot area.

set_limits (*xlim=None, ylim=None, ax=None*)

Set the display limits.

Parameters **xlim** : tuple, optional

2-Tuple containing y-axis limits in km. None uses default limits.

ylim : tuple, optional

2-Tuple containing x-axis limits in km. None uses default limits.

ax : Axis

Axis to adjust. None will adjust the current axis.

class `pyart.graph.GridMapDisplay` (*grid, debug=False*)

Bases: `object`

A class for creating plots from a grid object on top of a Basemap.

Parameters **grid** : Grid

Grid with data which will be used to create plots.

debug : bool

True to print debugging messages, False to suppress them.

Attributes

<code>grid</code>	(Grid) Grid object.
<code>debug</code>	(bool) True to print debugging messages, False to suppressed them.
<code>basemap</code>	(Basemap) Last plotted basemap, None when no basemap has been plotted.
<code>mappables</code>	(list) List of ContourSet, etc. which have been plotted, useful when adding colorbars.
<code>fields</code>	(list) List of fields which have been plotted.

Methods

<code>generate_filename</code> (field, level[, ext])	Generate a filename for a grid plot.
<code>generate_grid_title</code> (field, level)	Generate a title for a plot.
<code>generate_latitudinal_level_title</code> (field, level)	Generate a title for a plot.
<code>generate_longitudinal_level_title</code> (field, level)	Generate a title for a plot.
<code>get_basemap</code> ()	get basemap of the plot
<code>plot_basemap</code> ([lat_lines, lon_lines, ...])	Plot a basemap.
<code>plot_colorbar</code> ([mappable, orientation, ...])	Plot a colorbar.
<code>plot_crosshairs</code> ([lon, lat, line_style, ...])	Plot crosshairs at a given longitude and latitude.
Continued on next page	

Table 9.4 – continued from previous page

<code>plot_grid</code> (field[, level, vmin, vmax, norm, ...])	Plot the grid onto the current basemap.
<code>plot_latitude_slice</code> (field[, lon, lat])	Plot a slice along a given latitude.
<code>plot_latitudinal_level</code> (field, y_index[, ...])	Plot a slice along a given latitude.
<code>plot_latlon_level</code> (field, ind_1, ind_2[, ...])	Plot a slice along two points given by its lat, lon
<code>plot_latlon_slice</code> (field[, coord1, coord2])	Plot a slice along a given longitude.
<code>plot_longitude_slice</code> (field[, lon, lat])	Plot a slice along a given longitude.
<code>plot_longitudinal_level</code> (field, x_index[, ...])	Plot a slice along a given longitude.

__class__
alias of `type`

__delattr__
Implement `delattr(self, name)`.

__dict__ = `mappingproxy({‘plot_grid’: <function GridMapDisplay.plot_grid>, ‘_get_label_x’: <function GridMapDisp`

__dir__ () → list
default `dir()` implementation

__eq__
Return `self==value`.

__format__ ()
default object formatter

__ge__
Return `self>=value`.

__getattr__
Return `getattr(self, name)`.

__gt__
Return `self>value`.

__hash__
Return `hash(self)`.

__init__ (*grid, debug=False*)
italize the object.

__le__
Return `self<=value`.

__lt__
Return `self<value`.

__module__ = ‘`pyart.graph.gridmapdisplay`’

__ne__
Return `self!=value`.

__new__ ()
Create and return a new object. See `help(type)` for accurate signature.

__reduce__ ()
helper for pickle

__reduce_ex__ ()
helper for pickle

__repr__
Return repr(self).

__setattr__
Implement setattr(self, name, value).

__sizeof__ () → int
size of object in memory, in bytes

__str__
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

_find_nearest_grid_indices (lon, lat)
Find the nearest x, y grid indices for a given latitude and longitude.

_get_label_x ()
Get default label for x units.

_get_label_y ()
Get default label for y units.

_get_label_z ()
Get default label for z units.

_label_axes_grid (axis_labels, ax)
Set the x and y axis labels for a grid plot.

_label_axes_latitude (axis_labels, ax)
Set the x and y axis labels for a latitude slice.

_label_axes_latlon (axis_labels, ax)
Set the x and y axis labels for a lat-lon slice.

_label_axes_longitude (axis_labels, ax)
Set the x and y axis labels for a longitude slice.

_make_basemap (resolution='l', area_thresh=10000, auto_range=True, min_lon=-92, max_lon=-86, min_lat=40, max_lat=44, ax=None, **kwargs)
Make a basemap.

Parameters auto_range : bool

True to determine map ranges from the latitude and longitude limits of the grid. False will use the min_lon, max_lon, min_lat, and max_lat parameters for the map range.

min_lat, max_lat, min_lon, max_lon : float

Latitude and longitude ranges for the map projection region in degrees. These parameter are not used if auto_range is True.

resolution : 'c', 'l', 'i', 'h', or 'f'.

Resolution of boundary database to use. See Basemap documentation for details.

area_thresh : int

Basemap area_thresh parameter. See Basemap documentation.

ax : axes or None.

Axis to add the basemap to, if None the current axis is used.

kwargs: Basemap options

Options to be passed to Basemap. If projection is not specified here it uses proj='merc' (mercator).

generate_filename (*field, level, ext='png'*)

Generate a filename for a grid plot.

Generated filename has form: grid_name_field_level_time.ext

Parameters field : str

Field plotted.

level : int

Level plotted.

ext : str

Filename extension.

Returns filename : str

Filename suitable for saving a plot.

generate_grid_title (*field, level*)

Generate a title for a plot.

Parameters field : str

Field plotted.

level : int

Verical level plotted.

Returns title : str

Plot title.

generate_latitudinal_level_title (*field, level*)

Generate a title for a plot.

Parameters field : str

Field plotted.

level : int

Longitudinal level plotted.

Returns title : str

Plot title.

generate_longitudinal_level_title (*field, level*)

Generate a title for a plot.

Parameters field : str

Field plotted.

level : int

Longitudinal level plotted.

Returns title : str

Plot title.

get_basemap ()

get basemap of the plot

plot_basemap (*lat_lines=None, lon_lines=None, resolution='l', area_thresh=10000, auto_range=True, min_lon=-92, max_lon=-86, min_lat=40, max_lat=44, ax=None, **kwargs*)

Plot a basemap.

Parameters lat_lines, lon_lines : array or None

Locations at which to draw latitude and longitude lines. None will use default values which are resonable for maps of North America.

auto_range : bool

True to determine map ranges from the latitude and longitude limits of the grid. False will use the min_lon, max_lon, min_lat, and max_lat parameters for the map range.

min_lat, max_lat, min_lon, max_lon : float

Latitude and longitude ranges for the map projection region in degrees. These parameter are not used if auto_range is True.

resolution : 'c', 'l', 'i', 'h', or 'f'.

Resolution of boundary database to use. See Basemap documentation for details.

area_thresh : int

Basemap area_thresh parameter. See Basemap documentation.

ax : axes or None.

Axis to add the basemap to, if None the current axis is used.

kwargs: Basemap options

Options to be passed to Basemap. If projection is not specified here it uses proj='merc' (mercator).

plot_colorbar (*mappable=None, orientation='horizontal', label=None, cax=None, ax=None, fig=None, field=None, ticks=None, ticklabs=None*)

Plot a colorbar.

Parameters mappable : Image, ContourSet, etc.

Image, ContourSet, etc to which the colorbar applied. If None the last mappable object will be used.

field : str

Field to label colorbar with.

label : str

Colorbar label. None will use a default value from the last field plotted.

orient : str

Colorbar orientation, either 'vertical' [default] or 'horizontal'.

cax : Axis

Axis onto which the colorbar will be drawn. None is also valid.

ax : Axes

Axis onto which the colorbar will be drawn. None is also valid.

fig : Figure

Figure to place colorbar on. None will use the current figure.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

plot_crosshairs (*lon=None, lat=None, line_style='r-', linewidth=2, ax=None*)

Plot crosshairs at a given longitude and latitude.

Parameters lon, lat : float

Longitude and latitude (in degrees) where the crosshairs should be placed. If None the center of the grid is used.

line_style : str

Matplotlib string describing the line style.

linewidth : float

Width of markers in points.

ax : axes or None.

Axis to add the crosshairs to, if None the current axis is used.

plot_grid (*field, level=0, vmin=None, vmax=None, norm=None, cmap=None, mask_outside=False, title=None, title_flag=True, axislabels=(None, None), axislabels_flag=False, colorbar_flag=True, colorbar_label=None, colorbar_orient='vertical', edges=True, ax=None, fig=None, ticks=None, ticklabs=None, **kwargs*)

Plot the grid onto the current basemap.

Additional arguments are passed to Basemaps's pcolormesh function.

Parameters field : str

Field to be plotted.

level : int

Index corresponding to the height level to be plotted.

vmin, vmax : float

Lower and upper range for the colormesh. If either parameter is None, a value will be determined from the field attributes (if available) or the default values of -8, 64 will be used. Parameters are ignored if norm is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside : bool

True to mask data outside of vmin, vmax. False performs no masking.

title : str

Title to label plot with, None to use default title generated from the field and level parameters. Parameter is ignored if title_flag is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

plot_latitude_slice (*field*, *lon=None*, *lat=None*, ***kwargs*)

Plot a slice along a given latitude.

For documentation of additional arguments see [*plot_latitudinal_level\(\)*](#).

Parameters field : str

Field to be plotted.

lon, lat : float

Longitude and latitude (in degrees) specifying the slice. If None the center of the grid is used.

plot_latitudinal_level (*field, y_index, vmin=None, vmax=None, norm=None, cmap=None, mask_outside=False, title=None, title_flag=True, axislabels=(None, None), axislabels_flag=True, colorbar_flag=True, colorbar_label=None, colorbar_orient='vertical', edges=True, ax=None, fig=None, ticks=None, ticklabs=None, **kwargs*)

Plot a slice along a given latitude.

Additional arguments are passed to Basemaps's pcolormesh function.

Parameters **field** : str

Field to be plotted.

y_index : float

Index of the latitudinal level to plot.

vmin, vmax : float

Lower and upper range for the colormesh. If either parameter is None, a value will be determined from the field attributes (if available) or the default values of -8, 64 will be used. Parameters are ignored if norm is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the vmin and vmax parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside : bool

True to mask data outside of vmin, vmax. False performs no masking.

title : str

Title to label plot with, None to use default title generated from the field and lat,lon parameters. Parameter is ignored if title_flag is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

plot_latlon_level (*field, ind_1, ind_2, vmin=None, vmax=None, norm=None, cmap=None, mask_outside=False, title=None, title_flag=True, axislabels=(None, None), axislabels_flag=True, colorbar_flag=True, colorbar_label=None, colorbar_orient='vertical', edges=True, ax=None, fig=None, ticks=None, ticklabs=None, **kwargs*)

Plot a slice along two points given by its lat, lon

Additional arguments are passed to Basemaps's pcolormesh function.

Parameters **field** : str

Field to be plotted.

ind_1, ind_2 : float

x,y indices of the two points crossed by the slice.

vmin, vmax : float

Lower and upper range for the colormesh. If either parameter is None, a value will be determined from the field attributes (if available) or the default values of -8, 64 will be used. Parameters are ignored if norm is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside : bool

True to mask data outside of vmin, vmax. False performs no masking.

title : str

Title to label plot with, None to use default title generated from the field and lat,lon parameters. Parameter is ignored if title_flag is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

plot_latlon_slice (*field*, *coord1*=None, *coord2*=None, ***kwargs*)

Plot a slice along a given longitude.

For documentation of additional arguments see [`plot_longitudinal_level\(\)`](#).

Parameters field : str

Field to be plotted.

coord1, coord2 : tuple of floats

tuple of floats containing the longitude and latitude (in degrees) specifying the two points crossed by the slice. If none two extremes of the grid is used

plot_longitude_slice (*field*, *lon*=None, *lat*=None, ***kwargs*)

Plot a slice along a given longitude.

For documentation of additional arguments see [`plot_longitudinal_level\(\)`](#).

Parameters field : str

Field to be plotted.

lon, lat : float

Longitude and latitude (in degrees) specifying the slice. If None the center of the grid is used.

plot_longitudinal_level (*field, x_index, vmin=None, vmax=None, norm=None, cmap=None, mask_outside=False, title=None, title_flag=True, axislabels=(None, None), axislabels_flag=True, colorbar_flag=True, colorbar_label=None, colorbar_orient='vertical', edges=True, ax=None, fig=None, ticks=None, ticklabs=None, **kwargs*)

Plot a slice along a given longitude.

Additional arguments are passed to Basemaps's pcolormesh function.

Parameters field : str

Field to be plotted.

x_index : float

Index of the longitudinal level to plot.

vmin, vmax : float

Lower and upper range for the colormesh. If either parameter is None, a value will be determined from the field attributes (if available) or the default values of -8, 64 will be used. Parameters are ignored if norm is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside : bool

True to mask data outside of vmin, vmax. False performs no masking.

title : str

Title to label plot with, None to use default title generated from the field and lat,lon parameters. Parameter is ignored if title_flag is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

class `pyart.graph.RadarDisplay` (*radar*, *shift*=(0.0, 0.0))

Bases: `object`

A display object for creating plots from data in a radar object.

Parameters **radar** : Radar

Radar object to use for creating plots.

shift : (float, float)

Shifts in km to offset the calculated x and y locations.

Attributes

plots	(list) List of plots created.
plot_vars	(list) List of fields plotted, order matches plot list.
cbs	(list) List of colorbars created.
origin	(str) 'Origin' or 'Radar'.
shift	((float, float)) Shift in meters.
loc	((float, float)) Latitude and Longitude of radar in degrees.
fields	(dict) Radar fields.
scan_type	(str) Scan type.
ranges	(array) Gate ranges in meters.
azimuths	(array) Azimuth angle in degrees.
elevations	(array) Elevations in degrees.
fixed_angle	(array) Scan angle in degrees.
an- tenna_transition	(array or None) Antenna transition flag (1 in transition, 0 in transition) or None if no antenna transition.

Methods

<code>generate_az_rhi_title(field, azimuth)</code>	Generate a title for a ray plot.
<code>generate_filename(field, sweep[, ext])</code>	Generate a filename for a plot.
<code>generate_ray_title(field, ray)</code>	Generate a title for a ray plot.
<code>generate_title(field, sweep)</code>	Generate a title for a plot.
<code>generate_vpt_title(field)</code>	Generate a title for a VPT plot.
<code>label_xaxis_r([ax])</code>	Label the xaxis with the default label for r units.
<code>label_xaxis_rays([ax])</code>	Label the yaxis with the default label for rays.
<code>label_xaxis_time([ax])</code>	Label the yaxis with the default label for rays.
<code>label_xaxis_x([ax])</code>	Label the xaxis with the default label for x units.
<code>label_yaxis_field(field[, ax])</code>	Label the yaxis with the default label for a field units.
<code>label_yaxis_y([ax])</code>	Label the yaxis with the default label for y units.
<code>label_yaxis_z([ax])</code>	Label the yaxis with the default label for z units.
<code>plot(field[, sweep])</code>	Create a plot appropriate for the radar.
<code>plot_azimuth_to_rhi(field, target_azimuth[, ...])</code>	Plot pseudo-RHI scan by extracting the vertical field associated with the given azimuth.
<code>plot_colorbar([mappable, field, label, ...])</code>	Plot a colorbar.
<code>plot_cross_hair(size[, npts, ax])</code>	Plot a cross-hair on a ppi plot.
<code>plot_grid_lines([ax, col, ls])</code>	Plot grid lines.
<code>plot_label(label, location[, symbol, ...])</code>	Plot a single symbol and label at a given location.
<code>plot_labels(labels, locations[, symbols, ...])</code>	Plot symbols and labels at given locations.
<code>plot_ppi(field[, sweep, mask_tuple, vmin, ...])</code>	Plot a PPI.
<code>plot_range_ring(range_ring_location_km[, ...])</code>	Plot a single range ring.
<code>plot_range_rings(range_rings[, ax, col, ls, lw])</code>	Plot a series of range rings.
<code>plot_ray(field, ray[, format_str, ...])</code>	Plot a single ray.
<code>plot_rhi(field[, sweep, mask_tuple, vmin, ...])</code>	Plot a RHI.
<code>plot_vpt(field[, mask_tuple, vmin, vmax, ...])</code>	Plot a VPT scan.
<code>set_aspect_ratio([aspect_ratio, ax])</code>	Set the aspect ratio for plot area.
<code>set_limits([xlim, ylim, ax])</code>	Set the display limits.

__class__

alias of type

__delattr__

Implement delattr(self, name).

__dict__ = mappingproxy({'_get_azimuth_rhi_data_x_y_z': <function RadarDisplay._get_azimuth_rhi_data_x_y_z>, ...})

__dir__ () → list

default dir() implementation

__eq__

Return self==value.

__format__ ()

default object formatter

__ge__

Return self>=value.

__getattr__

Return getattr(self, name).

__gt__

Return self>value.

__hash__
Return hash(self).

__init__ (*radar*, *shift*=(0.0, 0.0))
Initialize the object.

__le__
Return self<=value.

__lt__
Return self<value.

__module__ = 'pyart.graph.radardisplay'

__ne__
Return self!=value.

__new__ ()
Create and return a new object. See help(type) for accurate signature.

__reduce__ ()
helper for pickle

__reduce_ex__ ()
helper for pickle

__repr__
Return repr(self).

__setattr__
Implement setattr(self, name, value).

__sizeof__ () → int
size of object in memory, in bytes

__str__
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

__get_azimuth_rhi_data_x_y_z (*field*, *target_azimuth*, *edges*, *mask_tuple*, *filter_transitions*, *gatefilter*)
Retrieve and return pseudo-RHI data from a plot function.

__get_colorbar_label (*field*)
Return a colorbar label for a given field.

__get_data (*field*, *sweep*, *mask_tuple*, *filter_transitions*, *gatefilter*)
Retrieve and return data from a plot function.

__get_ray_data (*field*, *ray*, *mask_tuple*, *gatefilter*)
Retrieve and return ray data from a plot function.

__get_vpt_data (*field*, *mask_tuple*, *filter_transitions*, *gatefilter*)
Retrieve and return vpt data from a plot function.

`_get_x_y` (*sweep, edges, filter_transitions*)
 Retrieve and return x and y coordinate in km.

`_get_x_y_z` (*sweep, edges, filter_transitions*)
 Retrieve and return x, y, and z coordinate in km.

`_get_x_z` (*sweep, edges, filter_transitions*)
 Retrieve and return x and z coordinate in km.

`_label_axes_ppi` (*axis_labels, ax*)
 Set the x and y axis labels for a PPI plot.

`_label_axes_ray` (*axis_labels, field, ax*)
 Set the x and y axis labels for a ray plot.

`_label_axes_rhi` (*axis_labels, ax*)
 Set the x and y axis labels for a RHI plot.

`_label_axes_vpt` (*axis_labels, time_axis_flag, ax*)
 Set the x and y axis labels for a PPI plot.

`_set_az_rhi_title` (*field, azimuth, title, ax*)
 Set the figure title for a ray plot using a default title.

`_set_ray_title` (*field, ray, title, ax*)
 Set the figure title for a ray plot using a default title.

`_set_title` (*field, sweep, title, ax*)
 Set the figure title using a default title.

`static _set_vpt_time_axis` (*ax, date_time_form=None, tz=None*)
 Set the x axis as a time formatted axis.

Parameters **ax** : Matplotlib axis instance

Axis to plot. None will use the current axis.

date_time_form : str

Format of the time string for x-axis labels.

tz : str

Time zone info to use when creating axis labels (see datetime).

`_set_vpt_title` (*field, title, ax*)
 Set the figure title using a default title.

`generate_az_rhi_title` (*field, azimuth*)
 Generate a title for a ray plot.

Parameters **field** : str

Field plotted.

azimuth : float

Azimuth plotted.

Returns **title** : str

Plot title.

`generate_filename` (*field, sweep, ext='png'*)
 Generate a filename for a plot.

Generated filename has form: radar_name_field_sweep_time.ext

Parameters **field** : str

Field plotted.

sweep : int

Sweep plotted.

ext : str

Filename extension.

Returns **filename** : str

Filename suitable for saving a plot.

generate_ray_title (*field, ray*)

Generate a title for a ray plot.

Parameters **field** : str

Field plotted.

ray : int

Ray plotted.

Returns **title** : str

Plot title.

generate_title (*field, sweep*)

Generate a title for a plot.

Parameters **field** : str

Field plotted.

sweep : int

Sweep plotted.

Returns **title** : str

Plot title.

generate_vpt_title (*field*)

Generate a title for a VPT plot.

Parameters **field** : str

Field plotted.

Returns **title** : str

Plot title.

label_xaxis_r (*ax=None*)

Label the xaxis with the default label for r units.

static label_xaxis_rays (*ax=None*)

Label the yaxis with the default label for rays.

static label_xaxis_time (*ax=None*)

Label the yaxis with the default label for rays.

label_xaxis_x (*ax=None*)

Label the xaxis with the default label for x units.

label_yaxis_field (*field*, *ax=None*)

Label the yaxis with the default label for a field units.

label_yaxis_y (*ax=None*)

Label the yaxis with the default label for y units.

label_yaxis_z (*ax=None*)

Label the yaxis with the default label for z units.

plot (*field*, *sweep=0*, ***kwargs*)

Create a plot appropriate for the radar.

This function calls the plotting function corresponding to the *scan_type* of the radar. Additional keywords can be passed to customize the plot, see the appropriate plot function for the allowed keywords.

Parameters **field** : str

Field to plot.

sweep : int

Sweep number to plot, not used for VPT scans.

See also:

[*plot_ppi*](#) Plot a PPI scan

[*plot_rhi*](#) Plot a RHI scan

[*plot_vpt*](#) Plot a VPT scan

plot_azimuth_to_rhi (*field*, *target_azimuth*, *mask_tuple=None*, *vmin=None*, *vmax=None*, *norm=None*, *cmap=None*, *mask_outside=False*, *title=None*, *title_flag=True*, *axislabels=(None, None)*, *axislabels_flag=True*, *colorbar_flag=True*, *colorbar_label=None*, *colorbar_orient='vertical'*, *edges=True*, *gatefilter=None*, *reverse_xaxis=None*, *filter_transitions=True*, *ax=None*, *fig=None*, *ticks=None*, *ticklabs=None*, *raster=None*, ***kwargs*)

Plot pseudo-RHI scan by extracting the vertical field associated with the given azimuth.

Additional arguments are passed to Matplotlib's `pcolormesh` function.

Parameters **field** : str

Field to plot.

target_azimuth : integer

Azimuthal angle in degrees where cross section will be taken.

Other Parameters **mask_tuple** : (str, float)

2-Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where $NCP < 0.5$ set mask to `['NCP', 0.5]`. None performs no masking.

vmin : float

Luminance minimum value, None for default value. Parameter is ignored if norm is not None.

vmax : float

Luminance maximum value, None for default value. Parameter is ignored if norm is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

title : str

Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

reverse_xaxis : bool or None

True to reverse the x-axis so the plot reads east to west, False to have east to west. None (the default) will reverse the axis only when all the distances are negative.

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions : bool

True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

raster : bool

False by default. Set to True to render the display as a raster rather than a vector in call to `pcolormesh`. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

plot_colorbar (*mappable=None, field=None, label=None, orient='vertical', cax=None, ax=None, fig=None, ticks=None, ticklabs=None*)

Plot a colorbar.

Parameters **mappable** : Image, ContourSet, etc.

Image, ContourSet, etc to which the colorbar applied. If None the last mappable object will be used.

field : str

Field to label colorbar with.

label : str

Colorbar label. None will use a default value from the last field plotted.

orient : str

Colorbar orientation, either 'vertical' [default] or 'horizontal'.

cax : Axis

Axis onto which the colorbar will be drawn. None is also valid.

ax : Axes

Axis onto which the colorbar will be drawn. None is also valid.

fig : Figure

Figure to place colorbar on. None will use the current figure.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

static plot_cross_hair (*size, npts=100, ax=None*)

Plot a cross-hair on a ppi plot.

Parameters **size** : float

Size of cross-hair in km.

npts: int

Number of points in the cross-hair, higher for better resolution.

ax : Axis

Axis to plot on. None will use the current axis.

static plot_grid_lines (*ax=None, col='k', ls=':'*)

Plot grid lines.

Parameters **ax** : Axis

Axis to plot on. None will use the current axis.

col : str or value

Color to use for grid lines.

ls : str

Linestyle to use for grid lines.

plot_label (*label, location, symbol='r+', text_color='k', ax=None*)

Plot a single symbol and label at a given location.

Transforms of the symbol location in latitude and longitude units to x and y plot units is performed using an azimuthal equidistance map projection centered at the radar.

Parameters **label** : str

Label text to place just above symbol.

location : 2-tuples

Tuple of latitude, longitude (in degrees) at which the symbol will be place. The label is placed just above the symbol.

symbol : str

Matplotlib color+marker strings defining the symbol to place at the given location.

text_color : str

Matplotlib color defining the color of the label text.

ax : Axis

Axis to plot on. None will use the current axis.

plot_labels (*labels, locations, symbols='r+', text_color='k', ax=None*)

Plot symbols and labels at given locations.

Parameters **labels** : list of str

List of labels to place just above symbols.

locations : list of 2-tuples

List of latitude, longitude (in degrees) tuples at which symbols will be place. Labels are placed just above the symbols.

symbols : list of str or str

List of matplotlib color+marker strings defining symbols to place at given locations. If a single string is provided, that symbol will be placed at all locations.

text_color : str

Matplotlib color defining the color of the label text.

ax : Axis

Axis to plot on. None will use the current axis.

plot_ppi (*field*, *sweep*=0, *mask_tuple*=None, *vmin*=None, *vmax*=None, *norm*=None, *cmap*=None, *mask_outside*=False, *title*=None, *title_flag*=True, *axislabels*=(None, None), *axislabels_flag*=True, *colorbar_flag*=True, *colorbar_label*=None, *colorbar_orient*='vertical', *edges*=True, *gatefilter*=None, *filter_transitions*=True, *ax*=None, *fig*=None, *ticks*=None, *ticklabs*=None, *raster*=None, ***kwargs*)

Plot a PPI.

Additional arguments are passed to Matplotlib's `pcolormesh` function.

Parameters **field** : str

Field to plot.

sweep : int, optional

Sweep number to plot.

Other Parameters **mask_tuple** : (str, float)

Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set `mask_tuple` to ['NCP', 0.5]. None performs no masking.

vmin : float

Luminance minimum value, None for default value. Parameter is ignored if `norm` is not None.

vmax : float

Luminance maximum value, None for default value. Parameter is ignored if `norm` is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the `vmax` and `vmin` parameters are ignored. If None, `vmin` and `vmax` are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside : bool

True to mask data outside of `vmin`, `vmax`. False performs no masking.

title : str

Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if `title_flag` is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if `axislabels_flag` is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions : bool

True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

raster : bool

False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

static plot_range_ring (*range_ring_location_km*, *npts=100*, *ax=None*, *col='k'*, *ls='-'*, *lw=2*)

Plot a single range ring.

Parameters *range_ring_location_km* : float

Location of range ring in km.

npts: int

Number of points in the ring, higher for better resolution.

ax : Axis

Axis to plot on. None will use the current axis.

col : str or value

Color to use for range rings.

ls : str

Linestyle to use for range rings.

plot_range_rings (*range_rings*, *ax=None*, *col='k'*, *ls='-'*, *lw=2*)

Plot a series of range rings.

Parameters *range_rings* : list

List of locations in km to draw range rings.

ax : Axis

Axis to plot on. None will use the current axis.

col : str or value

Color to use for range rings.

ls : str

Linestyle to use for range rings.

plot_ray (*field*, *ray*, *format_str='k-'*, *mask_tuple=None*, *ray_min=None*, *ray_max=None*,
mask_outside=False, *title=None*, *title_flag=True*, *axislabels=(None, None)*, *gate-*
filter=None, *axislabels_flag=True*, *ax=None*, *fig=None*)

Plot a single ray.

Parameters *field* : str

Field to plot.

ray : int

Ray number to plot.

Other Parameters *format_str* : str

Format string defining the line style and marker.

mask_tuple : (str, float)

Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

ray_min : float

Minimum ray value, None for default value, ignored if mask_outside is False.

ray_max : float

Maximum ray value, None for default value, ignored if mask_outside is False.

mask_outside : bool

True to mask data outside of vmin, vmax. False performs no masking.

title : str

Title to label plot with, None to use default title generated from the field and ray parameters. Parameter is ignored if title_flag is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if `axislabels_flag` is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

plot_rhi (*field, sweep=0, mask_tuple=None, vmin=None, vmax=None, norm=None, cmap=None, mask_outside=False, title=None, title_flag=True, axislabels=(None, None), axislabels_flag=True, reverse_axis=None, colorbar_flag=True, colorbar_label=None, colorbar_orient='vertical', edges=True, gatefilter=None, filter_transitions=True, ax=None, fig=None, ticks=None, ticklabs=None, raster=False, **kwargs*)

Plot a RHI.

Additional arguments are passed to Matplotlib's `pcolormesh` function.

Parameters field : str

Field to plot.

sweep : int,

Sweep number to plot.

Other Parameters mask_tuple : (str, float)

2-Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where `NCP < 0.5` set mask to `['NCP', 0.5]`. None performs no masking.

vmin : float

Luminance minimum value, None for default value. Parameter is ignored is norm is not None.

vmax : float

Luminance maximum value, None for default value. Parameter is ignored is norm is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the `vmax` and `vmin` parameters are ignored. If None, `vmin` and `vmax` are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

title : str

Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if `title_flag` is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if `axislabels_flag` is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

reverse_xaxis : bool or None

True to reverse the x-axis so the plot reads west to east, False to have east to west. None (the default) will reverse the axis only when all the distances are negative. (i.e) axis will be absolute distance without taking into consideration the orientation

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions : bool

True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the `antenna_transition` attribute of the underlying radar is not present.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

raster : bool

False by default. Set to true to render the display as a raster rather than a vector in call to `pcolormesh`. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

plot_vpt (*field*, *mask_tuple*=None, *vmin*=None, *vmax*=None, *norm*=None, *cmap*=None, *mask_outside*=False, *title*=None, *title_flag*=True, *axislabels*=(None, None), *axislabels_flag*=True, *colorbar_flag*=True, *colorbar_label*=None, *colorbar_orient*='vertical', *edges*=True, *gatefilter*=None, *filter_transitions*=True, *time_axis_flag*=False, *date_time_form*=None, *tz*=None, *ax*=None, *fig*=None, *ticks*=None, *ticklabs*=None, *raster*=None, ***kwargs*)

Plot a VPT scan.

Additional arguments are passed to Matplotlib's `pcolormesh` function.

Parameters **field** : str

Field to plot.

Other Parameters **mask_tuple** : (str, float)

Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set `mask_tuple` to ['NCP', 0.5]. None performs no masking.

vmin : float

Luminance minimum value, None for default value. Parameter is ignored if `norm` is not None.

vmax : float

Luminance maximum value, None for default value. Parameter is ignored if `norm` is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the `vmax` and `vmin` parameters are ignored. If None, `vmin` and `vmax` are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside : bool

True to mask data outside of `vmin`, `vmax`. False performs no masking.

title : str

Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if `title_flag` is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if `axislabels_flag` is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions : bool

True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

time_axis_flag : bool

True to plot the x-axis as time. False uses the index number. Default is False - index-based.

date_time_form : str, optional

Format of the time string for x-axis labels. Parameter is ignored if time_axis_flag is set to False.

tz : str, optional

Time zone info to use when creating axis labels (see datetime). Parameter is ignored if time_axis_flag is set to False.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

raster : bool

False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

static set_aspect_ratio (*aspect_ratio=0.75, ax=None*)

Set the aspect ratio for plot area.

static set_limits (*xlim=None, ylim=None, ax=None*)

Set the display limits.

Parameters xlim : tuple, optional

2-Tuple containing y-axis limits in km. None uses default limits.

ylim : tuple, optional

2-Tuple containing x-axis limits in km. None uses default limits.

ax : Axis

Axis to adjust. None will adjust the current axis.

class `pyart.graph.RadarMapDisplay` (*radar*, *shift*=(0.0, 0.0))

Bases: `pyart.graph.radardisplay.RadarDisplay`

A display object for creating plots on a geographic map from data in a Radar object.

This class is still a work in progress. Some functionality may not work correctly. Please report any problems to the Py-ART GitHub Issue Tracker.

Parameters radar : Radar

Radar object to use for creating plots.

shift : (float, float)

Shifts in km to offset the calculated x and y locations.

Attributes

<code>plots</code>	(list) List of plots created.
<code>plot_vars</code>	(list) List of fields plotted, order matches plot list.
<code>cbs</code>	(list) List of colorbars created.
<code>origin</code>	(str) 'Origin' or 'Radar'.
<code>shift</code>	((float, float)) Shift in meters.
<code>loc</code>	((float, float)) Latitude and Longitude of radar in degrees.
<code>fields</code>	(dict) Radar fields.
<code>scan_type</code>	(str) Scan type.
<code>ranges</code>	(array) Gate ranges in meters.
<code>azimuths</code>	(array) Azimuth angle in degrees.
<code>elevations</code>	(array) Elevations in degrees.
<code>fixed_angle</code>	(array) Scan angle in degrees.
<code>proj</code>	(Proj) Object for performing cartographic transformations specific to the geographic map plotted.
<code>basemap</code>	(Basemap) Last plotted basemap, None when no basemap has been plotted.

Methods

<code>generate_az_rhi_title</code> (field, azimuth)	Generate a title for a ray plot.
<code>generate_filename</code> (field, sweep[, ext])	Generate a filename for a plot.
<code>generate_ray_title</code> (field, ray)	Generate a title for a ray plot.
<code>generate_title</code> (field, sweep)	Generate a title for a plot.
<code>generate_vpt_title</code> (field)	Generate a title for a VPT plot.
<code>label_xaxis_r</code> ([ax])	Label the xaxis with the default label for r units.
<code>label_xaxis_rays</code> ([ax])	Label the yaxis with the default label for rays.
Continued on next page	

Table 9.6 – continued from previous page

<code>label_xaxis_time([ax])</code>	Label the yaxis with the default label for rays.
<code>label_xaxis_x([ax])</code>	Label the xaxis with the default label for x units.
<code>label_yaxis_field(field[, ax])</code>	Label the yaxis with the default label for a field units.
<code>label_yaxis_y([ax])</code>	Label the yaxis with the default label for y units.
<code>label_yaxis_z([ax])</code>	Label the yaxis with the default label for z units.
<code>plot(field[, sweep])</code>	Create a plot appropriate for the radar.
<code>plot_azimuth_to_rhi(field, target_azimuth[, ...])</code>	Plot pseudo-RHI scan by extracting the vertical field associated with the given azimuth.
<code>plot_colorbar([mappable, field, label, ...])</code>	Plot a colorbar.
<code>plot_cross_hair(size[, npts, ax])</code>	Plot a cross-hair on a ppi plot.
<code>plot_grid_lines([ax, col, ls])</code>	Plot grid lines.
<code>plot_label(label, location[, symbol, ...])</code>	Plot a single symbol and label at a given location.
<code>plot_labels(labels, locations[, symbols, ...])</code>	Plot symbols and labels at given locations.
<code>plot_line_geo(line_lons, line_lats[, line_style])</code>	Plot a line segments on the current map given values in lat and lon.
<code>plot_line_xy(line_x, line_y[, line_style])</code>	Plot a line segments on the current map given radar x, y values.
<code>plot_point(lon, lat[, symbol, label_text, ...])</code>	Plot a point on the current map.
<code>plot_ppi(field[, sweep, mask_tuple, vmin, ...])</code>	Plot a PPI.
<code>plot_ppi_map(field[, sweep, mask_tuple, ...])</code>	Plot a PPI volume sweep onto a geographic map.
<code>plot_range_ring(range_ring_location_km[, ...])</code>	Plot a single range ring on the map.
<code>plot_range_rings(range_rings[, ax, col, ls, lw])</code>	Plot a series of range rings.
<code>plot_ray(field, ray[, format_str, ...])</code>	Plot a single ray.
<code>plot_rhi(field[, sweep, mask_tuple, vmin, ...])</code>	Plot a RHI.
<code>plot_vpt(field[, mask_tuple, vmin, vmax, ...])</code>	Plot a VPT scan.
<code>set_aspect_ratio([aspect_ratio, ax])</code>	Set the aspect ratio for plot area.
<code>set_limits([xlim, ylim, ax])</code>	Set the display limits.

__class__

alias of type

__delattr__

Implement delattr(self, name).

__dict__ = mappingproxy({'__init__': <function RadarMapDisplay.__init__>, 'plot_line_xy': <function RadarMapDis**__dir__** () → list

default dir() implementation

__eq__

Return self==value.

__format__ ()

default object formatter

__ge__

Return self>=value.

__getattr__

Return getattr(self, name).

__gt__

Return self>value.

__hash__

Return hash(self).

```

__init__(radar, shift=(0.0, 0.0))
    Initialize the object.

__le__
    Return self<=value.

__lt__
    Return self<value.

__module__ = 'pyart.graph.radarmapdisplay'

__ne__
    Return self!=value.

__new__()
    Create and return a new object. See help(type) for accurate signature.

__reduce__()
    helper for pickle

__reduce_ex__()
    helper for pickle

__repr__
    Return repr(self).

__setattr__
    Implement setattr(self, name, value).

__sizeof__() → int
    size of object in memory, in bytes

__str__
    Return str(self).

__subclasshook__()
    Abstract classes can override this to customize issubclass().

    This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
    list of weak references to the object (if defined)

__check_baseimap__()
    Check that basemap is not None, raise ValueError if it is.

__get_azimuth_rhi_data_x_y_z(field, target_azimuth, edges, mask_tuple, filter_transitions,
                             gatefilter)
    Retrieve and return pseudo-RHI data from a plot function.

__get_colorbar_label(field)
    Return a colorbar label for a given field.

__get_data(field, sweep, mask_tuple, filter_transitions, gatefilter)
    Retrieve and return data from a plot function.

__get_ray_data(field, ray, mask_tuple, gatefilter)
    Retrieve and return ray data from a plot function.

__get_vpt_data(field, mask_tuple, filter_transitions, gatefilter)
    Retrieve and return vpt data from a plot function.

```

`_get_x_y` (*sweep, edges, filter_transitions*)
 Retrieve and return x and y coordinate in km.

`_get_x_y_z` (*sweep, edges, filter_transitions*)
 Retrieve and return x, y, and z coordinate in km.

`_get_x_z` (*sweep, edges, filter_transitions*)
 Retrieve and return x and z coordinate in km.

`_label_axes_ppi` (*axis_labels, ax*)
 Set the x and y axis labels for a PPI plot.

`_label_axes_ray` (*axis_labels, field, ax*)
 Set the x and y axis labels for a ray plot.

`_label_axes_rhi` (*axis_labels, ax*)
 Set the x and y axis labels for a RHI plot.

`_label_axes_vpt` (*axis_labels, time_axis_flag, ax*)
 Set the x and y axis labels for a PPI plot.

`_set_az_rhi_title` (*field, azimuth, title, ax*)
 Set the figure title for a ray plot using a default title.

`_set_ray_title` (*field, ray, title, ax*)
 Set the figure title for a ray plot using a default title.

`_set_title` (*field, sweep, title, ax*)
 Set the figure title using a default title.

`_set_vpt_time_axis` (*ax, date_time_form=None, tz=None*)
 Set the x axis as a time formatted axis.

Parameters **ax** : Matplotlib axis instance

Axis to plot. None will use the current axis.

date_time_form : str

Format of the time string for x-axis labels.

tz : str

Time zone info to use when creating axis labels (see datetime).

`_set_vpt_title` (*field, title, ax*)
 Set the figure title using a default title.

`generate_az_rhi_title` (*field, azimuth*)
 Generate a title for a ray plot.

Parameters **field** : str

Field plotted.

azimuth : float

Azimuth plotted.

Returns **title** : str

Plot title.

`generate_filename` (*field, sweep, ext='png'*)
 Generate a filename for a plot.

Generated filename has form: radar_name_field_sweep_time.ext

Parameters **field** : str

Field plotted.

sweep : int

Sweep plotted.

ext : str

Filename extension.

Returns **filename** : str

Filename suitable for saving a plot.

generate_ray_title (*field, ray*)

Generate a title for a ray plot.

Parameters **field** : str

Field plotted.

ray : int

Ray plotted.

Returns **title** : str

Plot title.

generate_title (*field, sweep*)

Generate a title for a plot.

Parameters **field** : str

Field plotted.

sweep : int

Sweep plotted.

Returns **title** : str

Plot title.

generate_vpt_title (*field*)

Generate a title for a VPT plot.

Parameters **field** : str

Field plotted.

Returns **title** : str

Plot title.

label_xaxis_r (*ax=None*)

Label the xaxis with the default label for r units.

label_xaxis_rays (*ax=None*)

Label the yaxis with the default label for rays.

label_xaxis_time (*ax=None*)

Label the yaxis with the default label for rays.

label_xaxis_x (*ax=None*)

Label the xaxis with the default label for x units.

label_yaxis_field (*field*, *ax=None*)

Label the yaxis with the default label for a field units.

label_yaxis_y (*ax=None*)

Label the yaxis with the default label for y units.

label_yaxis_z (*ax=None*)

Label the yaxis with the default label for z units.

plot (*field*, *sweep=0*, ***kwargs*)

Create a plot appropriate for the radar.

This function calls the plotting function corresponding to the *scan_type* of the radar. Additional keywords can be passed to customize the plot, see the appropriate plot function for the allowed keywords.

Parameters **field** : str

Field to plot.

sweep : int

Sweep number to plot, not used for VPT scans.

See also:

[*plot_ppi*](#) Plot a PPI scan

[*plot_rhi*](#) Plot a RHI scan

[*plot_vpt*](#) Plot a VPT scan

plot_azimuth_to_rhi (*field*, *target_azimuth*, *mask_tuple=None*, *vmin=None*, *vmax=None*, *norm=None*, *cmap=None*, *mask_outside=False*, *title=None*, *title_flag=True*, *axislabels=(None, None)*, *axislabels_flag=True*, *colorbar_flag=True*, *colorbar_label=None*, *colorbar_orient='vertical'*, *edges=True*, *gatefilter=None*, *reverse_xaxis=None*, *filter_transitions=True*, *ax=None*, *fig=None*, *ticks=None*, *ticklabs=None*, *raster=None*, ***kwargs*)

Plot pseudo-RHI scan by extracting the vertical field associated with the given azimuth.

Additional arguments are passed to Matplotlib's `pcolormesh` function.

Parameters **field** : str

Field to plot.

target_azimuth : integer

Azimuthal angle in degrees where cross section will be taken.

Other Parameters **mask_tuple** : (str, float)

2-Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where $NCP < 0.5$ set mask to `['NCP', 0.5]`. None performs no masking.

vmin : float

Luminance minimum value, None for default value. Parameter is ignored if norm is not None.

vmax : float

Luminance maximum value, None for default value. Parameter is ignored if norm is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

title : str

Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

reverse_xaxis : bool or None

True to reverse the x-axis so the plot reads east to west, False to have east to west. None (the default) will reverse the axis only when all the distances are negative.

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions : bool

True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

raster : bool

False by default. Set to True to render the display as a raster rather than a vector in call to `pcolormesh`. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

plot_colorbar (*mappable=None, field=None, label=None, orient='vertical', cax=None, ax=None, fig=None, ticks=None, ticklabs=None*)

Plot a colorbar.

Parameters **mappable** : Image, ContourSet, etc.

Image, ContourSet, etc to which the colorbar applied. If None the last mappable object will be used.

field : str

Field to label colorbar with.

label : str

Colorbar label. None will use a default value from the last field plotted.

orient : str

Colorbar orientation, either 'vertical' [default] or 'horizontal'.

cax : Axis

Axis onto which the colorbar will be drawn. None is also valid.

ax : Axes

Axis onto which the colorbar will be drawn. None is also valid.

fig : Figure

Figure to place colorbar on. None will use the current figure.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

plot_cross_hair (*size, npts=100, ax=None*)

Plot a cross-hair on a ppi plot.

Parameters **size** : float

Size of cross-hair in km.

npts: int

Number of points in the cross-hair, higher for better resolution.

ax : Axis

Axis to plot on. None will use the current axis.

plot_grid_lines (*ax=None, col='k', ls=':'*)

Plot grid lines.

Parameters **ax** : Axis

Axis to plot on. None will use the current axis.

col : str or value

Color to use for grid lines.

ls : str

Linestyle to use for grid lines.

plot_label (*label, location, symbol='r+', text_color='k', ax=None*)

Plot a single symbol and label at a given location.

Transforms of the symbol location in latitude and longitude units to x and y plot units is performed using an azimuthal equidistance map projection centered at the radar.

Parameters **label** : str

Label text to place just above symbol.

location : 2-tuples

Tuple of latitude, longitude (in degrees) at which the symbol will be place. The label is placed just above the symbol.

symbol : str

Matplotlib color+marker strings defining the symbol to place at the given location.

text_color : str

Matplotlib color defining the color of the label text.

ax : Axis

Axis to plot on. None will use the current axis.

plot_labels (*labels, locations, symbols='r+', text_color='k', ax=None*)

Plot symbols and labels at given locations.

Parameters **labels** : list of str

List of labels to place just above symbols.

locations : list of 2-tuples

List of latitude, longitude (in degrees) tuples at which symbols will be place. Labels are placed just above the symbols.

symbols : list of str or str

List of matplotlib color+marker strings defining symbols to place at given locations. If a single string is provided, that symbol will be placed at all locations.

text_color : str

Matplotlib color defining the color of the label text.

ax : Axis

Axis to plot on. None will use the current axis.

plot_line_geo (*line_lons, line_lats, line_style='r-', **kwargs*)

Plot a line segments on the current map given values in lat and lon.

Additional arguments are passed to basemap.plot.

Parameters **line_lons** : array

Longitude of line segment to plot.

line_lats : array

Latitude of line segment to plot.

line_style : str

Matplotlib compatible string which specifies the line style.

plot_line_xy (*line_x, line_y, line_style='r-', **kwargs*)

Plot a line segments on the current map given radar x, y values.

Additional arguments are passed to basemap.plot.

Parameters **line_x** : array

X location of points to plot in meters from the radar.

line_y : array

Y location of points to plot in meters from the radar.

line_style : str, optional

Matplotlib compatible string which specifies the line style.

plot_point (*lon, lat, symbol='ro', label_text=None, label_offset=(None, None), **kwargs*)

Plot a point on the current map.

Additional arguments are passed to basemap.plot.

Parameters **lon** : float

Longitude of point to plot.

lat : float

Latitude of point to plot.

symbol : str

Matplotlib compatible string which specified the symbol of the point.

label_text : str, optional.

Text to label symbol with. If None no label will be added.

label_offset : [float, float]

Offset in lon, lat degrees for the bottom left corner of the label text relative to the point.

A value of None will use 0.01 de

plot_ppi (*field, sweep=0, mask_tuple=None, vmin=None, vmax=None, norm=None, cmap=None, mask_outside=False, title=None, title_flag=True, axislabels=(None, None), axislabels_flag=True, colorbar_flag=True, colorbar_label=None, colorbar_orient='vertical', edges=True, gatefilter=None, filter_transitions=True, ax=None, fig=None, ticks=None, ticklabs=None, raster=None, **kwargs*)

Plot a PPI.

Additional arguments are passed to Matplotlib's pcolormesh function.

Parameters **field** : str

Field to plot.

sweep : int, optional

Sweep number to plot.

Other Parameters **mask_tuple** : (str, float)

Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

vmin : float

Luminance minimum value, None for default value. Parameter is ignored is norm is not None.

vmax : float

Luminance maximum value, None for default value. Parameter is ignored is norm is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside : bool

True to mask data outside of vmin, vmax. False performs no masking.

title : str

Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions : bool

True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

raster : bool

False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

plot_ppi_map (*field*, *sweep*=0, *mask_tuple*=None, *vmin*=None, *vmax*=None, *cmap*=None, *norm*=None, *mask_outside*=False, *title*=None, *title_flag*=True, *colorbar_flag*=True, *colorbar_label*=None, *ax*=None, *fig*=None, *lat_lines*=None, *lon_lines*=None, *projection*='lcc', *area_thresh*=10000, *min_lon*=None, *max_lon*=None, *min_lat*=None, *max_lat*=None, *width*=None, *height*=None, *lon_0*=None, *lat_0*=None, *resolution*='h', *shapefile*=None, *edges*=True, *gatefilter*=None, *basemap*=None, *filter_transitions*=True, *embelish*=True, *ticks*=None, *ticklabs*=None, *raster*=False, ***kwargs*)

Plot a PPI volume sweep onto a geographic map.

Additional arguments are passed to Basemap.

Parameters **field** : str

Field to plot.

sweep : int, optional

Sweep number to plot.

Other Parameters **mask_tuple** : (str, float)

Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

vmin : float

Luminance minimum value, None for default value. Parameter is ignored is norm is not None.

vmax : float

Luminance maximum value, None for default value. Parameter is ignored is norm is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside : bool

True to mask data outside of vmin, vmax. False performs no masking.

title : str

Title to label plot with, None to use default title generated from the field and tilt parameters. Parameter is ignored if title_flag is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

lat_lines, lon_lines : array or None

Locations at which to draw latitude and longitude lines. None will use default values which are resonable for maps of North America.

projection : str

Map projection supported by basemap. The use of cylindrical projections (mill, merc, etc) is not recommended as they exhibit large distortions at high latitudes. Equal area (aea, laea), conformal (lcc, tmerc, stere) or equidistant projection (aeqd, cass) work well even at high latitudes. The cylindrical equidistant projection (cyl) is not supported as coordinate transformations cannot be performed.

area_thresh : float

Coastline or lake with an area smaller than area_thresh in km² will not be plotted.

min_lat, max_lat, min_lon, max_lon : float

Latitude and longitude ranges for the map projection region in degrees.

width, height : float

Width and height of map domain in meters. Only this set of parameters or the previous set of parameters (min_lat, max_lat, min_lon, max_lon) should be specified. If neither set is specified then the map domain will be determined from the extend of the radar gate locations.

lon_0, lat_0 : float

Center of the map domain in degrees. If the default, None is used the latitude and longitude of the radar will be used.

shapefile : str

Filename for a ESRI shapefile as background (untested).

resolution : 'c', 'l', 'i', 'h', or 'f'.

Resolution of boundary database to use. See Basemap documentation for details.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions : bool

True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

embelish: bool

True by default. Set to false to suppress drawing of coastlines etc.. Use for speedup when specifying shapefiles.

basemap: Basemap instance

If None, create basemap instance using other keyword info. If not None, use the user-specified basemap instance.

raster : bool

False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

plot_range_ring (*range_ring_location_km*, *npts*=360, *line_style*='k-', ***kwargs*)

Plot a single range ring on the map.

Additional arguments are passed to basemap.plot.

Parameters range_ring_location_km : float

Location of range ring in km.

npts: int

Number of points in the ring, higher for better resolution.

line_style : str

Matplotlib compatible string which specified the line style of the ring.

plot_range_rings (*range_rings*, *ax=None*, *col='k'*, *ls='-'*, *lw=2*)

Plot a series of range rings.

Parameters range_rings : list

List of locations in km to draw range rings.

ax : Axis

Axis to plot on. None will use the current axis.

col : str or value

Color to use for range rings.

ls : str

Linestyle to use for range rings.

plot_ray (*field*, *ray*, *format_str='k-'*, *mask_tuple=None*, *ray_min=None*, *ray_max=None*,
mask_outside=False, *title=None*, *title_flag=True*, *axislabels=(None, None)*, *gate-
filter=None*, *axislabels_flag=True*, *ax=None*, *fig=None*)

Plot a single ray.

Parameters field : str

Field to plot.

ray : int

Ray number to plot.

Other Parameters format_str : str

Format string defining the line style and marker.

mask_tuple : (str, float)

Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

ray_min : float

Minimum ray value, None for default value, ignored if mask_outside is False.

ray_max : float

Maximum ray value, None for default value, ignored if mask_outside is False.

mask_outside : bool

True to mask data outside of vmin, vmax. False performs no masking.

title : str

Title to label plot with, None to use default title generated from the field and ray parameters. Parameter is ignored if title_flag is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

plot_rhi (*field, sweep=0, mask_tuple=None, vmin=None, vmax=None, norm=None, cmap=None, mask_outside=False, title=None, title_flag=True, axislabels=(None, None), axislabels_flag=True, reverse_xaxis=None, colorbar_flag=True, colorbar_label=None, colorbar_orient='vertical', edges=True, gatefilter=None, filter_transitions=True, ax=None, fig=None, ticks=None, ticklabs=None, raster=False, **kwargs*)

Plot a RHI.

Additional arguments are passed to Matplotlib's pcolormesh function.

Parameters field : str

Field to plot.

sweep : int,

Sweep number to plot.

Other Parameters mask_tuple : (str, float)

2-Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask to ['NCP', 0.5]. None performs no masking.

vmin : float

Luminance minimum value, None for default value. Parameter is ignored is norm is not None.

vmax : float

Luminance maximum value, None for default value. Parameter is ignored is norm is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

title : str

Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

reverse_xaxis : bool or None

True to reverse the x-axis so the plot reads west to east, False to have east to west. None (the default) will reverse the axis only when all the distances are negative. (i.e) axis will be absolute distance without taking into consideration the orientation

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions : bool

True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

raster : bool

False by default. Set to true to render the display as a raster rather than a vector in call to `pcolormesh`. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

plot_vpt (*field*, *mask_tuple*=None, *vmin*=None, *vmax*=None, *norm*=None, *cmap*=None, *mask_outside*=False, *title*=None, *title_flag*=True, *axislabels*=(None, None), *axislabels_flag*=True, *colorbar_flag*=True, *colorbar_label*=None, *colorbar_orient*='vertical', *edges*=True, *gatefilter*=None, *filter_transitions*=True, *time_axis_flag*=False, *date_time_form*=None, *tz*=None, *ax*=None, *fig*=None, *ticks*=None, *ticklabs*=None, *raster*=None, ***kwargs*)

Plot a VPT scan.

Additional arguments are passed to Matplotlib's `pcolormesh` function.

Parameters field : str

Field to plot.

Other Parameters mask_tuple : (str, float)

Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where $NCP < 0.5$ set `mask_tuple` to ['NCP', 0.5]. None performs no masking.

vmin : float

Luminance minimum value, None for default value. Parameter is ignored if `norm` is not None.

vmax : float

Luminance maximum value, None for default value. Parameter is ignored if `norm` is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the `vmax` and `vmin` parameters are ignored. If None, `vmin` and `vmax` are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside : bool

True to mask data outside of `vmin`, `vmax`. False performs no masking.

title : str

Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if `title_flag` is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if `axislabels_flag` is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions : bool

True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

time_axis_flag : bool

True to plot the x-axis as time. False uses the index number. Default is False - index-based.

date_time_form : str, optional

Format of the time string for x-axis labels. Parameter is ignored if time_axis_flag is set to False.

tz : str, optional

Time zone info to use when creating axis labels (see datetime). Parameter is ignored if time_axis_flag is set to False.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

raster : bool

False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

set_aspect_ratio (*aspect_ratio=0.75, ax=None*)

Set the aspect ratio for plot area.

set_limits (*xlim=None, ylim=None, ax=None*)

Set the display limits.

Parameters **xlim** : tuple, optional

2-Tuple containing y-axis limits in km. None uses default limits.

ylim : tuple, optional

2-Tuple containing x-axis limits in km. None uses default limits.

ax : Axis

Axis to adjust. None will adjust the current axis.

class `pyart.graph.RadarMapDisplayCartopy` (*radar, shift=(0.0, 0.0), grid_projection=None*)

Bases: `pyart.graph.radardisplay.RadarDisplay`

A display object for creating plots on a geographic map from data in a Radar object.

This class is still a work in progress. Some functionality may not work correctly. Please report any problems to the Py-ART GitHub Issue Tracker.

Parameters **radar** : Radar

Radar object to use for creating plots.

shift : (float, float)

Shifts in km to offset the calculated x and y locations.

Attributes

plots	(list) List of plots created.
plot_vars	(list) List of fields plotted, order matches plot list.
cbs	(list) List of colorbars created.
origin	(str) 'Origin' or 'Radar'.
shift	((float, float)) Shift in meters.
loc	((float, float)) Latitude and Longitude of radar in degrees.
fields	(dict) Radar fields.
scan_type	(str) Scan type.
ranges	(array) Gate ranges in meters.
azimuths	(array) Azimuth angle in degrees.
elevations	(array) Elevations in degrees.
fixed_angle	(array) Scan angle in degrees.
grid_projection	(cartopy.crs) AzimuthalEquidistant cartopy projection centered on radar. Used to transform points into map projection

Methods

<code>generate_az_rhi_title</code> (field, azimuth)	Generate a title for a ray plot.
<code>generate_filename</code> (field, sweep[, ext])	Generate a filename for a plot.
<code>generate_ray_title</code> (field, ray)	Generate a title for a ray plot.
Continued on next page	

Table 9.7 – continued from previous page

<code>generate_title(field, sweep)</code>	Generate a title for a plot.
<code>generate_vpt_title(field)</code>	Generate a title for a VPT plot.
<code>label_xaxis_r([ax])</code>	Label the xaxis with the default label for r units.
<code>label_xaxis_rays([ax])</code>	Label the yaxis with the default label for rays.
<code>label_xaxis_time([ax])</code>	Label the yaxis with the default label for rays.
<code>label_xaxis_x([ax])</code>	Label the xaxis with the default label for x units.
<code>label_yaxis_field(field[, ax])</code>	Label the yaxis with the default label for a field units.
<code>label_yaxis_y([ax])</code>	Label the yaxis with the default label for y units.
<code>label_yaxis_z([ax])</code>	Label the yaxis with the default label for z units.
<code>plot(field[, sweep])</code>	Create a plot appropriate for the radar.
<code>plot_azimuth_to_rhi(field, target_azimuth[, ...])</code>	Plot pseudo-RHI scan by extracting the vertical field associated with the given azimuth.
<code>plot_colorbar([mappable, field, label, ...])</code>	Plot a colorbar.
<code>plot_cross_hair(size[, npts, ax])</code>	Plot a cross-hair on a ppi plot.
<code>plot_grid_lines([ax, col, ls])</code>	Plot grid lines.
<code>plot_label(label, location[, symbol, ...])</code>	Plot a single symbol and label at a given location.
<code>plot_labels(labels, locations[, symbols, ...])</code>	Plot symbols and labels at given locations.
<code>plot_line_geo(line_lons, line_lats[, line_style])</code>	Plot a line segments on the current map given values in lat and lon.
<code>plot_line_xy(line_x, line_y[, line_style])</code>	Plot a line segments on the current map given radar x, y values.
<code>plot_point(lon, lat[, symbol, label_text, ...])</code>	Plot a point on the current map.
<code>plot_ppi(field[, sweep, mask_tuple, vmin, ...])</code>	Plot a PPI.
<code>plot_ppi_map(field[, sweep, mask_tuple, ...])</code>	Plot a PPI volume sweep onto a geographic map.
<code>plot_range_ring(range_ring_location_km[, ...])</code>	Plot a single range ring on the map.
<code>plot_range_rings(range_rings[, ax, col, ls, lw])</code>	Plot a series of range rings.
<code>plot_ray(field, ray[, format_str, ...])</code>	Plot a single ray.
<code>plot_rhi(field[, sweep, mask_tuple, vmin, ...])</code>	Plot a RHI.
<code>plot_vpt(field[, mask_tuple, vmin, vmax, ...])</code>	Plot a VPT scan.
<code>set_aspect_ratio([aspect_ratio, ax])</code>	Set the aspect ratio for plot area.
<code>set_limits([xlim, ylim, ax])</code>	Set the display limits.

__class__

alias of type

__delattr__

Implement delattr(self, name).

__dict__ = mappingproxy({'__init__': <function RadarMapDisplayCartopy.__init__>, 'plot_line_xy': <function RadarMapDisplayCartopy.plot_line_xy>})**__dir__** () → list

default dir() implementation

__eq__

Return self==value.

__format__ ()

default object formatter

__ge__

Return self>=value.

__getattr__

Return getattr(self, name).

__gt__
Return self>value.

__hash__
Return hash(self).

__init__ (*radar*, *shift*=(0.0, 0.0), *grid_projection*=None)
Initialize the object.

__le__
Return self<=value.

__lt__
Return self<value.

__module__ = 'pyart.graph.radarmapdisplay_cartopy'

__ne__
Return self!=value.

__new__ ()
Create and return a new object. See help(type) for accurate signature.

__reduce__ ()
helper for pickle

__reduce_ex__ ()
helper for pickle

__repr__
Return repr(self).

__setattr__
Implement setattr(self, name, value).

__sizeof__ () → int
size of object in memory, in bytes

__str__
Return str(self).

__subclasshook__ ()
Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__
list of weak references to the object (if defined)

__check_ax ()
Check that a GeoAxes object exists, raise ValueError if not

__get_azimuth_rhi_data_x_y_z (*field*, *target_azimuth*, *edges*, *mask_tuple*, *filter_transitions*, *gatefilter*)
Retrieve and return pseudo-RHI data from a plot function.

__get_colorbar_label (*field*)
Return a colorbar label for a given field.

__get_data (*field*, *sweep*, *mask_tuple*, *filter_transitions*, *gatefilter*)
Retrieve and return data from a plot function.

__get_ray_data (*field, ray, mask_tuple, gatefilter*)
 Retrieve and return ray data from a plot function.

__get_vpt_data (*field, mask_tuple, filter_transitions, gatefilter*)
 Retrieve and return vpt data from a plot function.

__get_x_y (*sweep, edges, filter_transitions*)
 Retrieve and return x and y coordinate in km.

__get_x_y_z (*sweep, edges, filter_transitions*)
 Retrieve and return x, y, and z coordinate in km.

__get_x_z (*sweep, edges, filter_transitions*)
 Retrieve and return x and z coordinate in km.

__label_axes_ppi (*axis_labels, ax*)
 Set the x and y axis labels for a PPI plot.

__label_axes_ray (*axis_labels, field, ax*)
 Set the x and y axis labels for a ray plot.

__label_axes_rhi (*axis_labels, ax*)
 Set the x and y axis labels for a RHI plot.

__label_axes_vpt (*axis_labels, time_axis_flag, ax*)
 Set the x and y axis labels for a PPI plot.

__set_az_rhi_title (*field, azimuth, title, ax*)
 Set the figure title for a ray plot using a default title.

__set_ray_title (*field, ray, title, ax*)
 Set the figure title for a ray plot using a default title.

__set_title (*field, sweep, title, ax*)
 Set the figure title using a default title.

__set_vpt_time_axis (*ax, date_time_form=None, tz=None*)
 Set the x axis as a time formatted axis.

Parameters **ax** : Matplotlib axis instance

Axis to plot. None will use the current axis.

date_time_form : str

Format of the time string for x-axis labels.

tz : str

Time zone info to use when creating axis labels (see datetime).

__set_vpt_title (*field, title, ax*)
 Set the figure title using a default title.

generate_az_rhi_title (*field, azimuth*)
 Generate a title for a ray plot.

Parameters **field** : str

Field plotted.

azimuth : float

Azimuth plotted.

Returns **title** : str

Plot title.

generate_filename (*field*, *sweep*, *ext*='png')

Generate a filename for a plot.

Generated filename has form: radar_name_field_sweep_time.ext

Parameters **field** : str

Field plotted.

sweep : int

Sweep plotted.

ext : str

Filename extension.

Returns **filename** : str

Filename suitable for saving a plot.

generate_ray_title (*field*, *ray*)

Generate a title for a ray plot.

Parameters **field** : str

Field plotted.

ray : int

Ray plotted.

Returns **title** : str

Plot title.

generate_title (*field*, *sweep*)

Generate a title for a plot.

Parameters **field** : str

Field plotted.

sweep : int

Sweep plotted.

Returns **title** : str

Plot title.

generate_vpt_title (*field*)

Generate a title for a VPT plot.

Parameters **field** : str

Field plotted.

Returns **title** : str

Plot title.

label_xaxis_r (*ax*=None)

Label the xaxis with the default label for r units.

label_xaxis_rays (*ax=None*)

Label the yaxis with the default label for rays.

label_xaxis_time (*ax=None*)

Label the yaxis with the default label for rays.

label_xaxis_x (*ax=None*)

Label the xaxis with the default label for x units.

label_yaxis_field (*field, ax=None*)

Label the yaxis with the default label for a field units.

label_yaxis_y (*ax=None*)

Label the yaxis with the default label for y units.

label_yaxis_z (*ax=None*)

Label the yaxis with the default label for z units.

plot (*field, sweep=0, **kwargs*)

Create a plot appropriate for the radar.

This function calls the plotting function corresponding to the `scan_type` of the radar. Additional keywords can be passed to customize the plot, see the appropriate plot function for the allowed keywords.

Parameters **field** : str

Field to plot.

sweep : int

Sweep number to plot, not used for VPT scans.

See also:

[`plot_ppi`](#) Plot a PPI scan

[`plot_rhi`](#) Plot a RHI scan

[`plot_vpt`](#) Plot a VPT scan

plot_azimuth_to_rhi (*field, target_azimuth, mask_tuple=None, vmin=None, vmax=None, norm=None, cmap=None, mask_outside=False, title=None, title_flag=True, axislabels=(None, None), axislabels_flag=True, colorbar_flag=True, colorbar_label=None, colorbar_orient='vertical', edges=True, gatefilter=None, reverse_xaxis=None, filter_transitions=True, ax=None, fig=None, ticks=None, ticklabs=None, raster=None, **kwargs*)

Plot pseudo-RHI scan by extracting the vertical field associated with the given azimuth.

Additional arguments are passed to Matplotlib's `pcolormesh` function.

Parameters **field** : str

Field to plot.

target_azimuth : integer

Azimuthal angle in degrees where cross section will be taken.

Other Parameters **mask_tuple** : (str, float)

2-Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where `NCP < 0.5` set mask to `['NCP', 0.5]`. None performs no masking.

vmin : float

Luminance minimum value, None for default value. Parameter is ignored is norm is not None.

vmax : float

Luminance maximum value, None for default value. Parameter is ignored is norm is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

title : str

Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

reverse_xaxis : bool or None

True to reverse the x-axis so the plot reads east to west, False to have east to west. None (the default) will reverse the axis only when all the distances are negative.

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions : bool

True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

raster : bool

False by default. Set to True to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

plot_colorbar (*mappable=None, field=None, label=None, orient='vertical', cax=None, ax=None, fig=None, ticks=None, ticklabs=None*)

Plot a colorbar.

Parameters **mappable** : Image, ContourSet, etc.

Image, ContourSet, etc to which the colorbar applied. If None the last mappable object will be used.

field : str

Field to label colorbar with.

label : str

Colorbar label. None will use a default value from the last field plotted.

orient : str

Colorbar orientation, either 'vertical' [default] or 'horizontal'.

cax : Axis

Axis onto which the colorbar will be drawn. None is also valid.

ax : Axes

Axis onto which the colorbar will be drawn. None is also valid.

fig : Figure

Figure to place colorbar on. None will use the current figure.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

plot_cross_hair (*size, npts=100, ax=None*)

Plot a cross-hair on a ppi plot.

Parameters **size** : float

Size of cross-hair in km.

npts: int

Number of points in the cross-hair, higher for better resolution.

ax : Axis

Axis to plot on. None will use the current axis.

plot_grid_lines (*ax=None, col='k', ls=':'*)

Plot grid lines.

Parameters **ax** : Axis

Axis to plot on. None will use the current axis.

col : str or value

Color to use for grid lines.

ls : str

Linestyle to use for grid lines.

plot_label (*label, location, symbol='r+', text_color='k', ax=None*)

Plot a single symbol and label at a given location.

Transforms of the symbol location in latitude and longitude units to x and y plot units is performed using an azimuthal equidistance map projection centered at the radar.

Parameters **label** : str

Label text to place just above symbol.

location : 2-tuples

Tuple of latitude, longitude (in degrees) at which the symbol will be place. The label is placed just above the symbol.

symbol : str

Matplotlib color+marker strings defining the symbol to place at the given location.

text_color : str

Matplotlib color defining the color of the label text.

ax : Axis

Axis to plot on. None will use the current axis.

plot_labels (*labels, locations, symbols='r+', text_color='k', ax=None*)

Plot symbols and labels at given locations.

Parameters **labels** : list of str

List of labels to place just above symbols.

locations : list of 2-tuples

List of latitude, longitude (in degrees) tuples at which symbols will be place. Labels are placed just above the symbols.

symbols : list of str or str

List of matplotlib color+marker strings defining symbols to place at given locations. If a single string is provided, that symbol will be placed at all locations.

text_color : str

Matplotlib color defining the color of the label text.

ax : Axis

Axis to plot on. None will use the current axis.

plot_line_geo (*line_lons*, *line_lats*, *line_style*='r-', ***kwargs*)

Plot a line segments on the current map given values in lat and lon.

Additional arguments are passed to ax.plot.

Parameters line_lons : array

Longitude of line segment to plot.

line_lats : array

Latitude of line segment to plot.

line_style : str

Matplotlib compatible string which specifies the line style.

plot_line_xy (*line_x*, *line_y*, *line_style*='r-', ***kwargs*)

Plot a line segments on the current map given radar x, y values.

Additional arguments are passed to ax.plot.

Parameters line_x : array

X location of points to plot in meters from the radar.

line_y : array

Y location of points to plot in meters from the radar.

line_style : str, optional

Matplotlib compatible string which specifies the line style.

plot_point (*lon*, *lat*, *symbol*='ro', *label_text*=None, *label_offset*=(None, None), ***kwargs*)

Plot a point on the current map.

Additional arguments are passed to ax.plot.

Parameters lon : float

Longitude of point to plot.

lat : float

Latitude of point to plot.

symbol : str

Matplotlib compatible string which specified the symbol of the point.

label_text : str, optional.

Text to label symbol with. If None no label will be added.

label_offset : [float, float]

Offset in lon, lat degrees for the bottom left corner of the label text relative to the point.
A value of None will use 0.01.

plot_ppi (*field*, *sweep*=0, *mask_tuple*=None, *vmin*=None, *vmax*=None, *norm*=None, *cmap*=None, *mask_outside*=False, *title*=None, *title_flag*=True, *axislabels*=(None, None), *axislabels_flag*=True, *colorbar_flag*=True, *colorbar_label*=None, *colorbar_orient*='vertical', *edges*=True, *gatefilter*=None, *filter_transitions*=True, *ax*=None, *fig*=None, *ticks*=None, *ticklabs*=None, *raster*=None, ***kwargs*)

Plot a PPI.

Additional arguments are passed to Matplotlib's pcolormesh function.

Parameters **field** : str

Field to plot.

sweep : int, optional

Sweep number to plot.

Other Parameters **mask_tuple** : (str, float)

Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

vmin : float

Luminance minimum value, None for default value. Parameter is ignored if norm is not None.

vmax : float

Luminance maximum value, None for default value. Parameter is ignored if norm is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the vmin and vmax parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside : bool

True to mask data outside of vmin, vmax. False performs no masking.

title : str

Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if title_flag is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions : bool

True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

raster : bool

False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

plot_ppi_map (*field*, *sweep*=0, *mask_tuple*=None, *vmin*=None, *vmax*=None, *cmap*=None, *norm*=None, *mask_outside*=False, *title*=None, *title_flag*=True, *colorbar_flag*=True, *colorbar_label*=None, *ax*=None, *fig*=None, *lat_lines*=None, *lon_lines*=None, *projection*=None, *min_lon*=None, *max_lon*=None, *min_lat*=None, *max_lat*=None, *width*=None, *height*=None, *lon_0*=None, *lat_0*=None, *resolution*='110m', *shapefile*=None, *shapefile_kwargs*=None, *edges*=True, *gatefilter*=None, *filter_transitions*=True, *embelish*=True, *maps_list*=['countries', 'coastlines'], *raster*=False, *ticks*=None, *ticklabs*=None)

Plot a PPI volume sweep onto a geographic map.

Parameters *field* : str

Field to plot.

sweep : int, optional

Sweep number to plot.

Other Parameters *mask_tuple* : (str, float)

Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where $NCP < 0.5$ set `mask_tuple` to `['NCP', 0.5]`. `None` performs no masking.

vmin : float

Luminance minimum value, `None` for default value. Parameter is ignored if `norm` is not `None`.

vmax : float

Luminance maximum value, `None` for default value. Parameter is ignored if `norm` is not `None`.

norm : Normalize or `None`, optional

matplotlib Normalize instance used to scale luminance data. If not `None` the `vmax` and `vmin` parameters are ignored. If `None`, `vmin` and `vmax` are used for luminance scaling.

cmap : str or `None`

Matplotlib colormap name. `None` will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside : bool

True to mask data outside of `vmin`, `vmax`. False performs no masking.

title : str

Title to label plot with, `None` to use default title generated from the field and tilt parameters. Parameter is ignored if `title_flag` is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

colorbar_label : str

Colorbar label, `None` will use a default label generated from the field information.

ax : Cartopy GeoAxes instance

If `None`, create GeoAxes instance using other keyword info. If provided, `ax` must have a Cartopy `crs` projection and projection kwarg below is ignored.

fig : Figure

Figure to add the colorbar to. `None` will use the current figure.

lat_lines, lon_lines : array or `None`

Locations at which to draw latitude and longitude lines. `None` will use default values which are reasonable for maps of North America.

projection : cartopy.crs class

Map projection supported by cartopy. Used for all subsequent calls to the GeoAxes object generated. Defaults to LambertConformal centered on radar.

min_lat, max_lat, min_lon, max_lon : float

Latitude and longitude ranges for the map projection region in degrees.

width, height : float

Width and height of map domain in meters. Only this set of parameters or the previous set of parameters (min_lat, max_lat, min_lon, max_lon) should be specified. If neither set is specified then the map domain will be determined from the extend of the radar gate locations.

shapefile : str

Filename for a shapefile to add to map.

shapefile_kwargs : dict

Key word arguments used to format shapefile. Projection defaults to lat lon (cartopy.crs.PlateCarree())

resolution : '10m', '50m', '110m'.

Resolution of NaturalEarthFeatures to use. See Cartopy documentation for details.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions : bool

True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

embelish: bool

True by default. Set to False to suppress drawing of coastlines etc.. Use for speedup when specifying shapefiles. Note that lat lon labels only work with certain projections.

maps_dict: list of strings

if embelish is true the list of maps to use. default

raster : bool

False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

plot_range_ring (*range_ring_location_km*, *npts*=360, *line_style*='k-', ***kwargs*)

Plot a single range ring on the map.

Additional arguments are passed to ax.plot.

Parameters *range_ring_location_km* : float

Location of range ring in km.

npts: int

Number of points in the ring, higher for better resolution.

line_style : str

Matplotlib compatible string which specified the line style of the ring.

plot_range_rings (*range_rings*, *ax=None*, *col='k'*, *ls='-'*, *lw=2*)

Plot a series of range rings.

Parameters range_rings : list

List of locations in km to draw range rings.

ax : Axis

Axis to plot on. None will use the current axis.

col : str or value

Color to use for range rings.

ls : str

Linestyle to use for range rings.

plot_ray (*field*, *ray*, *format_str='k-'*, *mask_tuple=None*, *ray_min=None*, *ray_max=None*, *mask_outside=False*, *title=None*, *title_flag=True*, *axislabels=(None, None)*, *gatefilter=None*, *axislabels_flag=True*, *ax=None*, *fig=None*)

Plot a single ray.

Parameters field : str

Field to plot.

ray : int

Ray number to plot.

Other Parameters format_str : str

Format string defining the line style and marker.

mask_tuple : (str, float)

Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask_tuple to ['NCP', 0.5]. None performs no masking.

ray_min : float

Minimum ray value, None for default value, ignored if mask_outside is False.

ray_max : float

Maximum ray value, None for default value, ignored if mask_outside is False.

mask_outside : bool

True to mask data outside of vmin, vmax. False performs no masking.

title : str

Title to label plot with, None to use default title generated from the field and ray parameters. Parameter is ignored if title_flag is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if axislabels_flag is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

plot_rhi (*field, sweep=0, mask_tuple=None, vmin=None, vmax=None, norm=None, cmap=None, mask_outside=False, title=None, title_flag=True, axislabels=(None, None), axislabels_flag=True, reverse_xaxis=None, colorbar_flag=True, colorbar_label=None, colorbar_orient='vertical', edges=True, gatefilter=None, filter_transitions=True, ax=None, fig=None, ticks=None, ticklabs=None, raster=False, **kwargs*)
Plot a RHI.

Additional arguments are passed to Matplotlib's pcolormesh function.

Parameters field : str

Field to plot.

sweep : int,

Sweep number to plot.

Other Parameters mask_tuple : (str, float)

2-Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set mask to ['NCP', 0.5]. None performs no masking.

vmin : float

Luminance minimum value, None for default value. Parameter is ignored is norm is not None.

vmax : float

Luminance maximum value, None for default value. Parameter is ignored is norm is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the vmax and vmin parameters are ignored. If None, vmin and vmax are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

title : str

Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if `title_flag` is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if `axislabels_flag` is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

reverse_xaxis : bool or None

True to reverse the x-axis so the plot reads west to east, False to have east to west. None (the default) will reverse the axis only when all the distances are negative. (i.e) axis will be absolute distance without taking into consideration the orientation

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions : bool

True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the `antenna_transition` attribute of the underlying radar is not present.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

raster : bool

False by default. Set to true to render the display as a raster rather than a vector in call to `pcolormesh`. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

plot_vpt (*field*, *mask_tuple*=None, *vmin*=None, *vmax*=None, *norm*=None, *cmap*=None, *mask_outside*=False, *title*=None, *title_flag*=True, *axislabels*=(None, None), *axislabels_flag*=True, *colorbar_flag*=True, *colorbar_label*=None, *colorbar_orient*='vertical', *edges*=True, *gatefilter*=None, *filter_transitions*=True, *time_axis_flag*=False, *date_time_form*=None, *tz*=None, *ax*=None, *fig*=None, *ticks*=None, *ticklabs*=None, *raster*=None, ***kwargs*)

Plot a VPT scan.

Additional arguments are passed to Matplotlib's `pcolormesh` function.

Parameters field : str

Field to plot.

Other Parameters mask_tuple : (str, float)

Tuple containing the field name and value below which to mask field prior to plotting, for example to mask all data where NCP < 0.5 set `mask_tuple` to ['NCP', 0.5]. None performs no masking.

vmin : float

Luminance minimum value, None for default value. Parameter is ignored if `norm` is not None.

vmax : float

Luminance maximum value, None for default value. Parameter is ignored if `norm` is not None.

norm : Normalize or None, optional

matplotlib Normalize instance used to scale luminance data. If not None the `vmax` and `vmin` parameters are ignored. If None, `vmin` and `vmax` are used for luminance scaling.

cmap : str or None

Matplotlib colormap name. None will use the default colormap for the field being plotted as specified by the Py-ART configuration.

mask_outside : bool

True to mask data outside of `vmin`, `vmax`. False performs no masking.

title : str

Title to label plot with, None to use default title generated from the field and sweep parameters. Parameter is ignored if `title_flag` is False.

title_flag : bool

True to add a title to the plot, False does not add a title.

axislabels : (str, str)

2-tuple of x-axis, y-axis labels. None for either label will use the default axis label. Parameter is ignored if `axislabels_flag` is False.

axislabels_flag : bool

True to add label the axes, False does not label the axes.

colorbar_flag : bool

True to add a colorbar with label to the axis. False leaves off the colorbar.

colorbar_label : str

Colorbar label, None will use a default label generated from the field information.

ticks : array

Colorbar custom tick label locations.

ticklabs : array

Colorbar custom tick labels.

colorbar_orient : 'vertical' or 'horizontal'

Colorbar orientation.

edges : bool

True will interpolate and extrapolate the gate edges from the range, azimuth and elevations in the radar, treating these as specifying the center of each gate. False treats these coordinates themselves as the gate edges, resulting in a plot in which the last gate in each ray and the entire last ray are not plotted.

gatefilter : GateFilter

GateFilter instance. None will result in no gatefilter mask being applied to data.

filter_transitions : bool

True to remove rays where the antenna was in transition between sweeps from the plot. False will include these rays in the plot. No rays are filtered when the antenna_transition attribute of the underlying radar is not present.

time_axis_flag : bool

True to plot the x-axis as time. False uses the index number. Default is False - index-based.

date_time_form : str, optional

Format of the time string for x-axis labels. Parameter is ignored if time_axis_flag is set to False.

tz : str, optional

Time zone info to use when creating axis labels (see datetime). Parameter is ignored if time_axis_flag is set to False.

ax : Axis

Axis to plot on. None will use the current axis.

fig : Figure

Figure to add the colorbar to. None will use the current figure.

raster : bool

False by default. Set to true to render the display as a raster rather than a vector in call to pcolormesh. Saves time in plotting high resolution data over large areas. Be sure to set the dpi of the plot for your application if you save it as a vector format (i.e., pdf, eps, svg).

set_aspect_ratio (*aspect_ratio=0.75, ax=None*)

Set the aspect ratio for plot area.

set_limits (*xlim=None, ylim=None, ax=None*)

Set the display limits.

Parameters xlim : tuple, optional

2-Tuple containing y-axis limits in km. None uses default limits.

ylim : tuple, optional

2-Tuple containing x-axis limits in km. None uses default limits.

ax : Axis

Axis to adjust. None will adjust the current axis.

UTILITIES (PYART . UTIL)

Miscellaneous utility functions.

The location and names of these functions within Py-ART may change between versions without deprecation, use with caution.

10.1 Direction statistics

<code>angular_mean(angles)</code>	Compute the mean of a distribution of angles in radians.
<code>angular_std(angles)</code>	Compute the standard deviation of a distribution of angles in radians.
<code>angular_mean_deg(angles)</code>	Compute the mean of a distribution of angles in degrees.
<code>angular_std_deg(angles)</code>	Compute the standard deviation of a distribution of angles in degrees.
<code>interval_mean(dist, interval_min, interval_max)</code>	Compute the mean of a distribution within an interval.
<code>interval_std(dist, interval_min, interval_max)</code>	Compute the standard deviation of a distribution within an interval.
<code>mean_of_two_angles(angles1, angles2)</code>	Compute the element by element mean of two sets of angles.
<code>mean_of_two_angles_deg(angle1, angle2)</code>	Compute the element by element mean of two sets of angles in degrees.

10.2 Miscellaneous functions

<code>cross_section_ppi(radar, target_azimuths[, ...])</code>	Extract cross sections from a PPI volume along one or more azimuth angles.
<code>cross_section_rhi(radar, target_elevations)</code>	Extract cross sections from an RHI volume along one or more elevation angles.
<code>colocated_gates(radar1, radar2[, h_tol, ...])</code>	Flags radar gates of radar1 colocated with radar2
<code>intersection(radar1, radar2[, h_tol, ...])</code>	Flags region of radar1 that is intersecting with radar2 and complies with
<code>estimate_noise_hs74(spectrum[, navg])</code>	Estimate noise parameters of a Doppler spectrum.
<code>is_vpt(radar[, offset])</code>	Determine if a Radar appears to be a vertical pointing scan.
<code>to_vpt(radar[, single_scan])</code>	Convert an existing Radar object to represent a vertical pointing scan.
<code>join_radar(radar1, radar2)</code>	Combine two radar instances into one.

Continued on next page

Table 10.2 – continued from previous page

<code>simulated_vel_from_profile(radar, profile[, ...])</code>	Create simulated radial velocities from a profile of horizontal winds.
<code>texture_along_ray(myradar, var[, wind_size])</code>	Compute field texture along ray using a user specified window size.
<code>rolling_window(a, window)</code>	create a rolling window object for application of functions
<code>angular_texture_2d(image, N, interval)</code>	Compute the angular texture of an image.

`pyart.util.angular_mean` (*angles*)

Compute the mean of a distribution of angles in radians.

Parameters *angles* : array like

Distribution of angles in radians.

Returns *mean* : float

The mean angle of the distribution in radians.

`pyart.util.angular_mean_deg` (*angles*)

Compute the mean of a distribution of angles in degrees.

Parameters *angles* : array like

Distribution of angles in degrees.

Returns *mean* : float

The mean angle of the distribution in degrees.

`pyart.util.angular_std` (*angles*)

Compute the standard deviation of a distribution of angles in radians.

Parameters *angles* : array like

Distribution of angles in radians.

Returns *std* : float

Standard deviation of the distribution.

`pyart.util.angular_std_deg` (*angles*)

Compute the standard deviation of a distribution of angles in degrees.

Parameters *angles* : array like

Distribution of angles in degrees.

Returns *std* : float

Standard deviation of the distribution.

`pyart.util.angular_texture_2d` (*image, N, interval*)

Compute the angular texture of an image. Uses convolutions in order to speed up texture calculation by a factor of ~50 compared to using `ndimage.generic_filter`

Parameters *image* : 2D array of floats

The array containing the velocities in which to calculate texture from.

N : int

This is the window size for calculating texture. The texture will be calculated from an N by N window centered around the gate.

interval : float

The absolute value of the maximum velocity. In conversion to radial coordinates, π will be defined to be interval and $-\pi$ will be $-\text{interval}$. It is recommended that interval be set to the Nyquist velocity.

Returns **std_dev** : float array

Texture of the radial velocity field.

`pyart.util.collocated_gates (radar1, radar2, h_tol=0.0, latlon_tol=0.0, coloc_gates_field=None)`
Flags radar gates of radar1 colocated with radar2

Parameters **radar1** : Radar

radar object that is going to be flagged

radar2 : Radar

radar object

h_tol : float

tolerance in altitude [m]

latlon_tol : float

tolerance in latitude/longitude [deg]

coloc_gates_field : string

Name of the field to retrieve the data

Returns **coloc_dict** : dict

a dictionary containing the colocated positions of radar 1 (ele, azi, rng) and radar 2

coloc_rad1 :

field with the colocated gates of radar1 flagged

`pyart.util.cross_section_ppi (radar, target_azimuths, az_tol=None)`

Extract cross sections from a PPI volume along one or more azimuth angles.

Parameters **radar** : Radar

Radar volume containing PPI sweeps from which azimuthal cross sections will be extracted.

target_azimuth : list

Azimuthal angles in degrees where cross sections will be taken.

az_tol : float

Azimuth angle tolerance in degrees. If none the nearest angle is used. If valid only angles within the tolerance distance are considered.

Returns **radar_rhi** : Radar

Radar volume containing RHI sweeps which contain azimuthal cross sections from the original PPI volume.

`pyart.util.cross_section_rhi (radar, target_elevations, el_tol=None)`

Extract cross sections from an RHI volume along one or more elevation angles.

Parameters **radar** : Radar

Radar volume containing RHI sweeps from which azimuthal cross sections will be extracted.

target_elevations : list

Elevation angles in degrees where cross sections will be taken.

el_tol : float

Elevation angle tolerance in degrees. If none the nearest angle is used. If valid only angles within the tolerance distance are considered.

Returns radar_ppi : Radar

Radar volume containing PPI sweeps which contain azimuthal cross sections from the original RHI volume.

`pyart.util.estimate_noise_hs74(spectrum, navg=1)`

Estimate noise parameters of a Doppler spectrum.

Use the method of estimating the noise level in Doppler spectra outlined by Hildebrand and Sekhon, 1974.

Parameters spectrum : array like

Doppler spectrum in linear units.

navg : int, optional

The number of spectral bins over which a moving average has been taken. Corresponds to the **p** variable from equation 9 of the article. The default value of 1 is appropriate when no moving average has been applied to the spectrum.

Returns mean : float-like

Mean of points in the spectrum identified as noise.

threshold : float-like

Threshold separating noise from signal. The point in the spectrum with this value or below should be considered as noise, above this value signal. It is possible that all points in the spectrum are identified as noise. If a peak is required for moment calculation then the point with this value should be considered as signal.

var : float-like

Variance of the points in the spectrum identified as noise.

nnoise : int

Number of noise points in the spectrum.

References

P. H. Hildebrand and R. S. Sekhon, Objective Determination of the Noise Level in Doppler Spectra. Journal of Applied Meteorology, 1974, 13, 808-811.

`pyart.util.intersection(radar1, radar2, h_tol=0.0, latlon_tol=0.0, vol_d_tol=None, vismin=None, hmin=None, hmax=None, rmin=None, rmax=None, elmin=None, elmax=None, azmin=None, azmax=None, visib_field=None, inter-sec_field=None)`

Flags region of radar1 that is intersecting with radar2 and complies with criteria regarding visibility, altitude, range, elevation angle and azimuth angle

Parameters radar1 : Radar

radar object that is going to be flagged

radar2 : Radar

radar object checked for intersecting region

h_tol : float

tolerance in altitude [m]

latlon_tol : float

latitude and longitude tolerance [decimal deg]

vol_d_tol : float

pulse volume diameter tolerance [m]

vismin : float

minimum visibility [percentage]

hmin, hmax : floats

min and max altitude [m MSL]

rmin, rmax : floats

min and max range from radar [m]

elmin, elmax : floats

min and max elevation angle [deg]

azmin, azmax : floats

min and max azimuth angle [deg]

Returns **intersec_rad1_dict** : dict

the field with the gates of radar1 in the same region as radar2 flagged

`pyart.util.interval_mean` (*dist, interval_min, interval_max*)

Compute the mean of a distribution within an interval.

Return the average of the array elements which are interpreted as being taken from a circular interval with endpoints given by `interval_min` and `interval_max`.

Parameters **dist** : array like

Distribution of values within an interval.

interval_min, interval_max : float

The endpoints of the interval.

Returns **mean** : float

The mean value of the distribution

`pyart.util.interval_std` (*dist, interval_min, interval_max*)

Compute the standard deviation of a distribution within an interval.

Return the standard deviation of the array elements which are interpreted as being taken from a circular interval with endpoints given by `interval_min` and `interval_max`.

Parameters **dist** : array_like

Distribution of values within an interval.

interval_min, interval_max : float

The endpoints of the interval.

Returns `std` : float

The standard deviation of the distribution.

`pyart.util.is_vpt (radar, offset=0.5)`

Determine if a Radar appears to be a vertical pointing scan.

This function only verifies that the object is a vertical pointing scan, use the `to_vpt ()` function to convert the radar to a vpt scan if this function returns True.

Parameters `radar` : Radar

Radar object to determine if

`offset` : float

Maximum offset of the elevation from 90 degrees to still consider to be vertically pointing.

Returns `flag` : bool

True if the radar appear to be verticle pointing, False if not.

`pyart.util.join_radar (radar1, radar2)`

Combine two radar instances into one.

Parameters `radar1` : Radar

Radar object.

`radar2` : Radar

Radar object.

`pyart.util.mean_of_two_angles (angles1, angles2)`

Compute the element by element mean of two sets of angles.

Parameters `angles1` : array

First set of angles in radians.

`angles2` : array

Second set of angles in radians.

Returns `mean` : array

Elements by element angular mean of the two sets of angles in radians.

`pyart.util.mean_of_two_angles_deg (angle1, angle2)`

Compute the element by element mean of two sets of angles in degrees.

Parameters `angle1` : array

First set of angles in degrees.

`angle2` : array

Second set of angles in degrees.

Returns `mean` : array

Elements by element angular mean of the two sets of angles in degrees.

`pyart.util.rolling_window (a, window)`

create a rolling window object for application of functions eg: `result=np.ma.std(array, 11), 1)`

```
pyart.util.simulated_vel_from_profile(radar, profile, interp_kind='linear',
                                     sim_vel_field=None)
```

Create simulated radial velocities from a profile of horizontal winds.

Parameters **radar** : Radar

Radar instance which provides the scanning parameters for the simulated radial velocities.

profile : HorizontalWindProfile

Profile of horizontal winds.

interp_kind : str, optional

Specifies the kind of interpolation used to determine the winds at a given height. Must be one of 'linear', 'nearest', 'zero', 'slinear', 'quadratic', or 'cubic'. See the documentation for the SciPy `scipy.interpolate.interp1d` function for descriptions.

sim_vel_field : str, optional

Name to use for the simulated velocity field metadata. None will use the default field name from the Py-ART configuration file.

Returns **sim_vel** : dict

Dictionary containing a radar field of simulated radial velocities.

```
pyart.util.texture_along_ray(myradar, var, wind_size=7)
```

Compute field texture along ray using a user specified window size.

Parameters **myradar** : radar object

The radar object where the field is

var : str

Name of the field which texture has to be computed

wind_size : int

Optional. Size of the rolling window used

Returns **tex** : radar field

the texture of the specified field

```
pyart.util.to_vpt(radar, single_scan=True)
```

Convert an existing Radar object to represent a vertical pointing scan.

This function does not verify that the Radar object contains a vertical pointing scan. To perform such a check use `is_vpt()`.

Parameters **radar** : Radar

Mislabeled vertical pointing scan Radar object to convert to be properly labeled. This object is converted in place, no copy of the existing data is made.

single_scan : bool, optional

True to convert the volume to a single scan, any azimuth angle data is lost. False will convert the scan to contain the same number of scans as rays, azimuth angles are retained.

TESTING UTILITIES (PYART . TESTING)

Utilities helpful when writing and running unit tests.

11.1 Testing functions

<i>make_empty_ppi_radar</i> (ngates, rays_per_sweep, ...)	Return an Radar object, representing a PPI scan.
<i>make_target_radar</i> ()	Return a PPI radar with a target like reflectivity field.
<i>make_single_ray_radar</i> ()	Return a PPI radar with a single ray taken from a ARM C-SAPR Radar
<i>make_velocity_aliased_radar</i> ([alias])	Return a PPI radar with a target like reflectivity field.
<i>make_empty_grid</i> (grid_shape, grid_limits)	Make an empty grid object without any fields or metadata.
<i>make_target_grid</i> ()	Make a sample Grid with a rectangular target.
<i>make_normal_storm</i> (sigma, mu)	Make a sample Grid with a gaussian storm target.

11.2 Testing classes

<i>InTemporaryDirectory</i> ([suffix, prefix, dir])	Create, return, and change directory to a temporary directory
---	---

```
class pyart.testing.InTemporaryDirectory(suffix='', prefix='tmp', dir=None)
```

```
    Bases: pyart.testing.tmpdirs.TemporaryDirectory
```

```
    Create, return, and change directory to a temporary directory
```

Examples

```
>>> import os
>>> my_cwd = os.getcwd()
>>> with InTemporaryDirectory() as tmpdir:
...     _ = open('test.txt', 'wt').write('some text')
...     assert os.path.isfile('test.txt')
...     assert os.path.isfile(os.path.join(tmpdir, 'test.txt'))
>>> os.path.exists(tmpdir)
False
>>> os.getcwd() == my_cwd
True
```

Methods

cleanup()

__class__alias of `type`**__delattr__**Implement `delattr(self, name)`.**__dict__** = `mappingproxy({'__exit__': <function InTemporaryDirectory.__exit__>, '__doc__': 'Create, return, and ch`**__dir__**() → listdefault `dir()` implementation**__enter__**()**__eq__**Return `self==value`.**__exit__**(*exc, value, tb*)**__format__**()

default object formatter

__ge__Return `self>=value`.**__getattr__**Return `getattr(self, name)`.**__gt__**Return `self>value`.**__hash__**Return `hash(self)`.**__init__**(*suffix='', prefix='tmp', dir=None*)**__le__**Return `self<=value`.**__lt__**Return `self<value`.**__module__** = `'pyart.testing.tmpdirs'`**__ne__**Return `self!=value`.**__new__**()Create and return a new object. See `help(type)` for accurate signature.**__reduce__**()

helper for pickle

__reduce_ex__()

helper for pickle

__repr__Return `repr(self)`.

__setattr__

Implement setattr(self, name, value).

__sizeof__ () → int

size of object in memory, in bytes

__str__

Return str(self).

__subclasshook__ ()

Abstract classes can override this to customize issubclass().

This is invoked early on by abc.ABCMeta.__subclasscheck__(). It should return True, False or NotImplemented. If it returns NotImplemented, the normal algorithm is used. Otherwise, it overrides the normal algorithm (and the outcome is cached).

__weakref__

list of weak references to the object (if defined)

cleanup ()

`pyart.testing.make_empty_grid(grid_shape, grid_limits)`

Make an empty grid object without any fields or metadata.

Parameters `grid_shape` : 3-tuple of floats

Number of points in the grid (z, y, x).

grid_limits : 3-tuple of 2-tuples

Minimum and maximum grid location (inclusive) in meters for the z, y, x coordinates.

Returns `grid` : Grid

Empty Grid object, centered near the ARM SGP site (Oklahoma).

`pyart.testing.make_empty_ppi_radar(ngates, rays_per_sweep, nsweeps)`

Return an Radar object, representing a PPI scan.

Parameters `ngates` : int

Number of gates per ray.

rays_per_sweep : int

Number of rays in each PPI sweep.

nsweeps : int

Number of sweeps.

Returns `radar` : Radar

Radar object with no fields, other parameters are set to default values.

`pyart.testing.make_empty_rhi_radar(ngates, rays_per_sweep, nsweeps)`

Return an Radar object, representing a RHI scan.

Parameters `ngates` : int

Number of gates per ray.

rays_per_sweep : int

Number of rays in each PPI sweep.

nsweeps : int

Number of sweeps.

Returns `radar` : Radar

Radar object with no fields, other parameters are set to default values.

`pyart.testing.make_normal_storm(sigma, mu)`

Make a sample Grid with a gaussian storm target.

`pyart.testing.make_single_ray_radar()`

Return a PPI radar with a single ray taken from a ARM C-SAPR Radar

Radar object returned has 'reflectivity_horizontal', 'norm_coherent_power', 'copol_coeff', 'dp_phase_shift', and 'diff_phase' fields with no metadata but a 'data' key. This radar is used for unit tests in correct modules.

`pyart.testing.make_storm_grid()`

Make a sample Grid with a rectangular storm target.

`pyart.testing.make_target_grid()`

Make a sample Grid with a rectangular target.

`pyart.testing.make_target_radar()`

Return a PPI radar with a target like reflectivity field.

`pyart.testing.make_velocity_aliased_radar(alias=True)`

Return a PPI radar with a target like reflectivity field.

Set alias to False to return a de-aliased radar.

`pyart.testing.make_velocity_aliased_rhi_radar(alias=True)`

Return a RHI radar with a target like reflectivity field.

Set alias to False to return a de-aliased radar.

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

BIBLIOGRAPHY

- [R11] <http://www.ncdc.noaa.gov/>
- [R12] <http://thredds.ucar.edu/thredds/catalog.html>
- [R13] <http://www.unidata.ucar.edu/software/netcdf-java/documentation.htm>
- [R14] <http://thredds.ucar.edu/thredds/catalog.html>
- [R15] <http://www.ncdc.noaa.gov/>
- [R16] http://www.roc.noaa.gov/wsr88d/Level_III/Level3Info.asp
- [R1] Doviak and Zrnic, Doppler Radar and Weather Observations, Second Edition, 1993, p. 21.
- [R2] Snyder, J. P. Map Projections—A Working Manual. U. S. Geological Survey Professional Paper 1395, 1987, pp. 191-202.
- [R3] Snyder, J. P. Map Projections—A Working Manual. U. S. Geological Survey Professional Paper 1395, 1987, pp. 191-202.
- [R7] Miguel Arevallilo Herraiez, David R. Burton, Michael J. Lalor, and Munther A. Gdeisat, “Fast two-dimensional phase-unwrapping algorithm based on sorting by reliability following a noncontinuous path”, Journal Applied Optics, Vol. 41, No. 35 (2002) 7437,
- [R8] Abdul-Rahman, H., Gdeisat, M., Burton, D., & Lalor, M., “Fast three-dimensional phase-unwrapping algorithm based on sorting by reliability following a non-continuous path. In W. Osten, C. Gorecki, & E. L. Novak (Eds.), Optical Metrology (2005) 32–40, International Society for Optics and Photonics.

p

- `pyart.aux_io`, 19
- `pyart.bridge`, 46
- `pyart.core`, 27
- `pyart.correct`, 60
- `pyart.filters`, 47
- `pyart.graph`, 115
- `pyart.io`, 1
- `pyart.map`, 110
- `pyart.retrieve`, 91
- `pyart.testing`, 209
- `pyart.util`, 201

Symbols

- `__class__` (pyart.core.Grid attribute), 31
- `__class__` (pyart.core.HorizontalWindProfile attribute), 34
- `__class__` (pyart.core.Radar attribute), 37
- `__class__` (pyart.correct.GateFilter attribute), 63
- `__class__` (pyart.filters.GateFilter attribute), 51
- `__class__` (pyart.graph.AirborneRadarDisplay attribute), 119
- `__class__` (pyart.graph.GridMapDisplay attribute), 136
- `__class__` (pyart.graph.RadarDisplay attribute), 148
- `__class__` (pyart.graph.RadarMapDisplay attribute), 164
- `__class__` (pyart.graph.RadarMapDisplayCartopy attribute), 183
- `__class__` (pyart.testing.InTemporaryDirectory attribute), 212
- `__delattr__` (pyart.core.Grid attribute), 31
- `__delattr__` (pyart.core.HorizontalWindProfile attribute), 34
- `__delattr__` (pyart.core.Radar attribute), 37
- `__delattr__` (pyart.correct.GateFilter attribute), 63
- `__delattr__` (pyart.filters.GateFilter attribute), 51
- `__delattr__` (pyart.graph.AirborneRadarDisplay attribute), 119
- `__delattr__` (pyart.graph.GridMapDisplay attribute), 136
- `__delattr__` (pyart.graph.RadarDisplay attribute), 148
- `__delattr__` (pyart.graph.RadarMapDisplay attribute), 164
- `__delattr__` (pyart.graph.RadarMapDisplayCartopy attribute), 183
- `__delattr__` (pyart.testing.InTemporaryDirectory attribute), 212
- `__dict__` (pyart.core.Grid attribute), 31
- `__dict__` (pyart.core.HorizontalWindProfile attribute), 34
- `__dict__` (pyart.core.Radar attribute), 37
- `__dict__` (pyart.correct.GateFilter attribute), 64
- `__dict__` (pyart.filters.GateFilter attribute), 51
- `__dict__` (pyart.graph.AirborneRadarDisplay attribute), 119
- `__dict__` (pyart.graph.GridMapDisplay attribute), 136
- `__dict__` (pyart.graph.RadarDisplay attribute), 148
- `__dict__` (pyart.graph.RadarMapDisplay attribute), 164
- `__dict__` (pyart.graph.RadarMapDisplayCartopy attribute), 183
- `__dict__` (pyart.testing.InTemporaryDirectory attribute), 212
- `__dir__()` (pyart.core.Grid method), 31
- `__dir__()` (pyart.core.HorizontalWindProfile method), 34
- `__dir__()` (pyart.core.Radar method), 37
- `__dir__()` (pyart.correct.GateFilter method), 64
- `__dir__()` (pyart.filters.GateFilter method), 51
- `__dir__()` (pyart.graph.AirborneRadarDisplay method), 119
- `__dir__()` (pyart.graph.GridMapDisplay method), 136
- `__dir__()` (pyart.graph.RadarDisplay method), 148
- `__dir__()` (pyart.graph.RadarMapDisplay method), 164
- `__dir__()` (pyart.graph.RadarMapDisplayCartopy method), 183
- `__dir__()` (pyart.testing.InTemporaryDirectory method), 212
- `__enter__()` (pyart.testing.InTemporaryDirectory method), 212
- `__eq__` (pyart.core.Grid attribute), 31
- `__eq__` (pyart.core.HorizontalWindProfile attribute), 34
- `__eq__` (pyart.core.Radar attribute), 37
- `__eq__` (pyart.correct.GateFilter attribute), 64
- `__eq__` (pyart.filters.GateFilter attribute), 51
- `__eq__` (pyart.graph.AirborneRadarDisplay attribute), 119
- `__eq__` (pyart.graph.GridMapDisplay attribute), 136
- `__eq__` (pyart.graph.RadarDisplay attribute), 148
- `__eq__` (pyart.graph.RadarMapDisplay attribute), 164
- `__eq__` (pyart.graph.RadarMapDisplayCartopy attribute), 183
- `__eq__` (pyart.testing.InTemporaryDirectory attribute), 212
- `__exit__()` (pyart.testing.InTemporaryDirectory method), 212
- `__format__()` (pyart.core.Grid method), 31
- `__format__()` (pyart.core.HorizontalWindProfile method), 34
- `__format__()` (pyart.core.Radar method), 37
- `__format__()` (pyart.correct.GateFilter method), 64
- `__format__()` (pyart.filters.GateFilter method), 51

`__format__()` (pyart.graph.AirborneRadarDisplay method), 119

`__format__()` (pyart.graph.GridMapDisplay method), 136

`__format__()` (pyart.graph.RadarDisplay method), 148

`__format__()` (pyart.graph.RadarMapDisplay method), 164

`__format__()` (pyart.graph.RadarMapDisplayCartopy method), 183

`__format__()` (pyart.testing.InTemporaryDirectory method), 212

`__ge__` (pyart.core.Grid attribute), 31

`__ge__` (pyart.core.HorizontalWindProfile attribute), 34

`__ge__` (pyart.core.Radar attribute), 37

`__ge__` (pyart.correct.GateFilter attribute), 64

`__ge__` (pyart.filters.GateFilter attribute), 51

`__ge__` (pyart.graph.AirborneRadarDisplay attribute), 119

`__ge__` (pyart.graph.GridMapDisplay attribute), 136

`__ge__` (pyart.graph.RadarDisplay attribute), 148

`__ge__` (pyart.graph.RadarMapDisplay attribute), 164

`__ge__` (pyart.graph.RadarMapDisplayCartopy attribute), 183

`__ge__` (pyart.testing.InTemporaryDirectory attribute), 212

`__getattr__` (pyart.core.Grid attribute), 31

`__getattr__` (pyart.core.HorizontalWindProfile attribute), 34

`__getattr__` (pyart.core.Radar attribute), 37

`__getattr__` (pyart.correct.GateFilter attribute), 64

`__getattr__` (pyart.filters.GateFilter attribute), 51

`__getattr__` (pyart.graph.AirborneRadarDisplay attribute), 119

`__getattr__` (pyart.graph.GridMapDisplay attribute), 136

`__getattr__` (pyart.graph.RadarDisplay attribute), 148

`__getattr__` (pyart.graph.RadarMapDisplay attribute), 164

`__getattr__` (pyart.graph.RadarMapDisplayCartopy attribute), 183

`__getattr__` (pyart.testing.InTemporaryDirectory attribute), 212

`__getstate__()` (pyart.core.Grid method), 31

`__getstate__()` (pyart.core.Radar method), 37

`__gt__` (pyart.core.Grid attribute), 31

`__gt__` (pyart.core.HorizontalWindProfile attribute), 34

`__gt__` (pyart.core.Radar attribute), 37

`__gt__` (pyart.correct.GateFilter attribute), 64

`__gt__` (pyart.filters.GateFilter attribute), 51

`__gt__` (pyart.graph.AirborneRadarDisplay attribute), 119

`__gt__` (pyart.graph.GridMapDisplay attribute), 136

`__gt__` (pyart.graph.RadarDisplay attribute), 148

`__gt__` (pyart.graph.RadarMapDisplay attribute), 164

`__gt__` (pyart.graph.RadarMapDisplayCartopy attribute), 183

`__gt__` (pyart.testing.InTemporaryDirectory attribute), 212

`__hash__` (pyart.core.Grid attribute), 31

`__hash__` (pyart.core.HorizontalWindProfile attribute), 34

`__hash__` (pyart.core.Radar attribute), 37

`__hash__` (pyart.correct.GateFilter attribute), 64

`__hash__` (pyart.filters.GateFilter attribute), 51

`__hash__` (pyart.graph.AirborneRadarDisplay attribute), 119

`__hash__` (pyart.graph.GridMapDisplay attribute), 136

`__hash__` (pyart.graph.RadarDisplay attribute), 148

`__hash__` (pyart.graph.RadarMapDisplay attribute), 164

`__hash__` (pyart.graph.RadarMapDisplayCartopy attribute), 184

`__hash__` (pyart.testing.InTemporaryDirectory attribute), 212

`__init__()` (pyart.core.Grid method), 31

`__init__()` (pyart.core.HorizontalWindProfile method), 34

`__init__()` (pyart.core.Radar method), 38

`__init__()` (pyart.correct.GateFilter method), 64

`__init__()` (pyart.filters.GateFilter method), 51

`__init__()` (pyart.graph.AirborneRadarDisplay method), 119

`__init__()` (pyart.graph.GridMapDisplay method), 136

`__init__()` (pyart.graph.RadarDisplay method), 149

`__init__()` (pyart.graph.RadarMapDisplay method), 164

`__init__()` (pyart.graph.RadarMapDisplayCartopy method), 184

`__init__()` (pyart.testing.InTemporaryDirectory method), 212

`__le__` (pyart.core.Grid attribute), 31

`__le__` (pyart.core.HorizontalWindProfile attribute), 34

`__le__` (pyart.core.Radar attribute), 38

`__le__` (pyart.correct.GateFilter attribute), 64

`__le__` (pyart.filters.GateFilter attribute), 51

`__le__` (pyart.graph.AirborneRadarDisplay attribute), 119

`__le__` (pyart.graph.GridMapDisplay attribute), 136

`__le__` (pyart.graph.RadarDisplay attribute), 149

`__le__` (pyart.graph.RadarMapDisplay attribute), 165

`__le__` (pyart.graph.RadarMapDisplayCartopy attribute), 184

`__le__` (pyart.testing.InTemporaryDirectory attribute), 212

`__lt__` (pyart.core.Grid attribute), 31

`__lt__` (pyart.core.HorizontalWindProfile attribute), 34

`__lt__` (pyart.core.Radar attribute), 38

`__lt__` (pyart.correct.GateFilter attribute), 64

`__lt__` (pyart.filters.GateFilter attribute), 51

`__lt__` (pyart.graph.AirborneRadarDisplay attribute), 119

`__lt__` (pyart.graph.GridMapDisplay attribute), 136

`__lt__` (pyart.graph.RadarDisplay attribute), 149

__lt__ (pyart.graph.RadarMapDisplay attribute), 165
 __lt__ (pyart.graph.RadarMapDisplayCartopy attribute), 184
 __lt__ (pyart.testing.InTemporaryDirectory attribute), 212
 __module__ (pyart.core.Grid attribute), 31
 __module__ (pyart.core.HorizontalWindProfile attribute), 34
 __module__ (pyart.core.Radar attribute), 38
 __module__ (pyart.correct.GateFilter attribute), 64
 __module__ (pyart.filters.GateFilter attribute), 51
 __module__ (pyart.graph.AirborneRadarDisplay attribute), 119
 __module__ (pyart.graph.GridMapDisplay attribute), 136
 __module__ (pyart.graph.RadarDisplay attribute), 149
 __module__ (pyart.graph.RadarMapDisplay attribute), 165
 __module__ (pyart.graph.RadarMapDisplayCartopy attribute), 184
 __module__ (pyart.testing.InTemporaryDirectory attribute), 212
 __ne__ (pyart.core.Grid attribute), 31
 __ne__ (pyart.core.HorizontalWindProfile attribute), 34
 __ne__ (pyart.core.Radar attribute), 38
 __ne__ (pyart.correct.GateFilter attribute), 64
 __ne__ (pyart.filters.GateFilter attribute), 51
 __ne__ (pyart.graph.AirborneRadarDisplay attribute), 119
 __ne__ (pyart.graph.GridMapDisplay attribute), 136
 __ne__ (pyart.graph.RadarDisplay attribute), 149
 __ne__ (pyart.graph.RadarMapDisplay attribute), 165
 __ne__ (pyart.graph.RadarMapDisplayCartopy attribute), 184
 __ne__ (pyart.testing.InTemporaryDirectory attribute), 212
 __new__() (pyart.core.Grid method), 31
 __new__() (pyart.core.HorizontalWindProfile method), 34
 __new__() (pyart.core.Radar method), 38
 __new__() (pyart.correct.GateFilter method), 64
 __new__() (pyart.filters.GateFilter method), 51
 __new__() (pyart.graph.AirborneRadarDisplay method), 119
 __new__() (pyart.graph.GridMapDisplay method), 136
 __new__() (pyart.graph.RadarDisplay method), 149
 __new__() (pyart.graph.RadarMapDisplay method), 165
 __new__() (pyart.graph.RadarMapDisplayCartopy method), 184
 __new__() (pyart.testing.InTemporaryDirectory method), 212
 __reduce__() (pyart.core.Grid method), 31
 __reduce__() (pyart.core.HorizontalWindProfile method), 34
 __reduce__() (pyart.core.Radar method), 38
 __reduce__() (pyart.correct.GateFilter method), 64
 __reduce__() (pyart.filters.GateFilter method), 51
 __reduce__() (pyart.graph.AirborneRadarDisplay method), 119
 __reduce__() (pyart.graph.GridMapDisplay method), 136
 __reduce__() (pyart.graph.RadarDisplay method), 149
 __reduce__() (pyart.graph.RadarMapDisplay method), 165
 __reduce__() (pyart.graph.RadarMapDisplayCartopy method), 184
 __reduce__() (pyart.testing.InTemporaryDirectory method), 212
 __reduce_ex__() (pyart.core.Grid method), 31
 __reduce_ex__() (pyart.core.HorizontalWindProfile method), 34
 __reduce_ex__() (pyart.core.Radar method), 38
 __reduce_ex__() (pyart.correct.GateFilter method), 64
 __reduce_ex__() (pyart.filters.GateFilter method), 51
 __reduce_ex__() (pyart.graph.AirborneRadarDisplay method), 119
 __reduce_ex__() (pyart.graph.GridMapDisplay method), 136
 __reduce_ex__() (pyart.graph.RadarDisplay method), 149
 __reduce_ex__() (pyart.graph.RadarMapDisplay method), 165
 __reduce_ex__() (pyart.graph.RadarMapDisplayCartopy method), 184
 __reduce_ex__() (pyart.testing.InTemporaryDirectory method), 212
 __repr__ (pyart.core.Grid attribute), 32
 __repr__ (pyart.core.HorizontalWindProfile attribute), 34
 __repr__ (pyart.core.Radar attribute), 38
 __repr__ (pyart.correct.GateFilter attribute), 64
 __repr__ (pyart.filters.GateFilter attribute), 51
 __repr__ (pyart.graph.AirborneRadarDisplay attribute), 119
 __repr__ (pyart.graph.GridMapDisplay attribute), 136
 __repr__ (pyart.graph.RadarDisplay attribute), 149
 __repr__ (pyart.graph.RadarMapDisplay attribute), 165
 __repr__ (pyart.graph.RadarMapDisplayCartopy attribute), 184
 __repr__ (pyart.testing.InTemporaryDirectory attribute), 212
 __setattr__ (pyart.core.Grid attribute), 32
 __setattr__ (pyart.core.HorizontalWindProfile attribute), 35
 __setattr__ (pyart.core.Radar attribute), 38
 __setattr__ (pyart.correct.GateFilter attribute), 64
 __setattr__ (pyart.filters.GateFilter attribute), 51
 __setattr__ (pyart.graph.AirborneRadarDisplay attribute), 119
 __setattr__ (pyart.graph.GridMapDisplay attribute), 137
 __setattr__ (pyart.graph.RadarDisplay attribute), 149

`__setattr__` (pyart.graph.RadarMapDisplay attribute), 165
`__setattr__` (pyart.graph.RadarMapDisplayCartopy attribute), 184
`__setattr__` (pyart.testing.InTemporaryDirectory attribute), 212
`__setstate__` (pyart.core.Grid method), 32
`__setstate__` (pyart.core.Radar method), 38
`__sizeof__` (pyart.core.Grid method), 32
`__sizeof__` (pyart.core.HorizontalWindProfile method), 35
`__sizeof__` (pyart.core.Radar method), 38
`__sizeof__` (pyart.correct.GateFilter method), 64
`__sizeof__` (pyart.filters.GateFilter method), 52
`__sizeof__` (pyart.graph.AirborneRadarDisplay method), 120
`__sizeof__` (pyart.graph.GridMapDisplay method), 137
`__sizeof__` (pyart.graph.RadarDisplay method), 149
`__sizeof__` (pyart.graph.RadarMapDisplay method), 165
`__sizeof__` (pyart.graph.RadarMapDisplayCartopy method), 184
`__sizeof__` (pyart.testing.InTemporaryDirectory method), 213
`__str__` (pyart.core.Grid attribute), 32
`__str__` (pyart.core.HorizontalWindProfile attribute), 35
`__str__` (pyart.core.Radar attribute), 38
`__str__` (pyart.correct.GateFilter attribute), 64
`__str__` (pyart.filters.GateFilter attribute), 52
`__str__` (pyart.graph.AirborneRadarDisplay attribute), 120
`__str__` (pyart.graph.GridMapDisplay attribute), 137
`__str__` (pyart.graph.RadarDisplay attribute), 149
`__str__` (pyart.graph.RadarMapDisplay attribute), 165
`__str__` (pyart.graph.RadarMapDisplayCartopy attribute), 184
`__str__` (pyart.testing.InTemporaryDirectory attribute), 213
`__subclasshook__` (pyart.core.Grid method), 32
`__subclasshook__` (pyart.core.HorizontalWindProfile method), 35
`__subclasshook__` (pyart.core.Radar method), 38
`__subclasshook__` (pyart.correct.GateFilter method), 64
`__subclasshook__` (pyart.filters.GateFilter method), 52
`__subclasshook__` (pyart.graph.AirborneRadarDisplay method), 120
`__subclasshook__` (pyart.graph.GridMapDisplay method), 137
`__subclasshook__` (pyart.graph.RadarDisplay method), 149
`__subclasshook__` (pyart.graph.RadarMapDisplay method), 165
`__subclasshook__` (pyart.graph.RadarMapDisplayCartopy method), 184
`__subclasshook__` (pyart.testing.InTemporaryDirectory method), 213
`__weakref__` (pyart.core.Grid attribute), 32
`__weakref__` (pyart.core.HorizontalWindProfile attribute), 35
`__weakref__` (pyart.core.Radar attribute), 38
`__weakref__` (pyart.correct.GateFilter attribute), 65
`__weakref__` (pyart.filters.GateFilter attribute), 52
`__weakref__` (pyart.graph.AirborneRadarDisplay attribute), 120
`__weakref__` (pyart.graph.GridMapDisplay attribute), 137
`__weakref__` (pyart.graph.RadarDisplay attribute), 149
`__weakref__` (pyart.graph.RadarMapDisplay attribute), 165
`__weakref__` (pyart.graph.RadarMapDisplayCartopy attribute), 184
`__weakref__` (pyart.testing.InTemporaryDirectory attribute), 213
`_check_ax` (pyart.graph.RadarMapDisplayCartopy method), 184
`_check_basemap` (pyart.graph.RadarMapDisplay method), 165
`_check_sweep_in_range` (pyart.core.Radar method), 38
`_dic_info` (pyart.core.Radar method), 38
`_find_and_check_nradar` (pyart.core.Grid method), 32
`_find_nearest_grid_indices` (pyart.graph.GridMapDisplay method), 137
`_get_azimuth_rhi_data_x_y_z` (pyart.graph.AirborneRadarDisplay method), 120
`_get_azimuth_rhi_data_x_y_z` (pyart.graph.RadarDisplay method), 149
`_get_azimuth_rhi_data_x_y_z` (pyart.graph.RadarMapDisplay method), 165
`_get_azimuth_rhi_data_x_y_z` (pyart.graph.RadarMapDisplayCartopy method), 184
`_get_colorbar_label` (pyart.graph.AirborneRadarDisplay method), 120
`_get_colorbar_label` (pyart.graph.RadarDisplay method), 149
`_get_colorbar_label` (pyart.graph.RadarMapDisplay method), 165
`_get_colorbar_label` (pyart.graph.RadarMapDisplayCartopy method), 184
`_get_data` (pyart.graph.AirborneRadarDisplay method), 120
`_get_data` (pyart.graph.RadarDisplay method), 149
`_get_data` (pyart.graph.RadarMapDisplay method), 165
`_get_data` (pyart.graph.RadarMapDisplayCartopy method), 184
`_get_fdata` (pyart.correct.GateFilter method), 65

[_get_fdata\(\) \(pyart.filters.GateFilter method\), 52](#)
[_get_label_x\(\) \(pyart.graph.GridMapDisplay method\), 137](#)
[_get_label_y\(\) \(pyart.graph.GridMapDisplay method\), 137](#)
[_get_label_z\(\) \(pyart.graph.GridMapDisplay method\), 137](#)
[_get_ray_data\(\) \(pyart.graph.AirborneRadarDisplay method\), 120](#)
[_get_ray_data\(\) \(pyart.graph.RadarDisplay method\), 149](#)
[_get_ray_data\(\) \(pyart.graph.RadarMapDisplay method\), 165](#)
[_get_ray_data\(\) \(pyart.graph.RadarMapDisplayCartopy method\), 184](#)
[_get_vpt_data\(\) \(pyart.graph.AirborneRadarDisplay method\), 120](#)
[_get_vpt_data\(\) \(pyart.graph.RadarDisplay method\), 149](#)
[_get_vpt_data\(\) \(pyart.graph.RadarMapDisplay method\), 165](#)
[_get_vpt_data\(\) \(pyart.graph.RadarMapDisplayCartopy method\), 185](#)
[_get_x_y\(\) \(pyart.graph.AirborneRadarDisplay method\), 120](#)
[_get_x_y\(\) \(pyart.graph.RadarDisplay method\), 149](#)
[_get_x_y\(\) \(pyart.graph.RadarMapDisplay method\), 165](#)
[_get_x_y\(\) \(pyart.graph.RadarMapDisplayCartopy method\), 185](#)
[_get_x_y_z\(\) \(pyart.graph.AirborneRadarDisplay method\), 120](#)
[_get_x_y_z\(\) \(pyart.graph.RadarDisplay method\), 150](#)
[_get_x_y_z\(\) \(pyart.graph.RadarMapDisplay method\), 166](#)
[_get_x_y_z\(\) \(pyart.graph.RadarMapDisplayCartopy method\), 185](#)
[_get_x_z\(\) \(pyart.graph.AirborneRadarDisplay method\), 120](#)
[_get_x_z\(\) \(pyart.graph.RadarDisplay method\), 150](#)
[_get_x_z\(\) \(pyart.graph.RadarMapDisplay method\), 166](#)
[_get_x_z\(\) \(pyart.graph.RadarMapDisplayCartopy method\), 185](#)
[_label_axes_grid\(\) \(pyart.graph.GridMapDisplay method\), 137](#)
[_label_axes_latitude\(\) \(pyart.graph.GridMapDisplay method\), 137](#)
[_label_axes_latlon\(\) \(pyart.graph.GridMapDisplay method\), 137](#)
[_label_axes_longitude\(\) \(pyart.graph.GridMapDisplay method\), 137](#)
[_label_axes_ppi\(\) \(pyart.graph.AirborneRadarDisplay method\), 120](#)
[_label_axes_ppi\(\) \(pyart.graph.RadarDisplay method\), 150](#)
[_label_axes_ppi\(\) \(pyart.graph.RadarMapDisplay method\), 166](#)
[_label_axes_ppi\(\) \(pyart.graph.RadarMapDisplayCartopy method\), 185](#)
[_label_axes_ppi\(\) \(pyart.graph.RadarMapDisplayCartopy method\), 185](#)
[_label_axes_ray\(\) \(pyart.graph.AirborneRadarDisplay method\), 120](#)
[_label_axes_ray\(\) \(pyart.graph.RadarDisplay method\), 150](#)
[_label_axes_ray\(\) \(pyart.graph.RadarMapDisplay method\), 166](#)
[_label_axes_ray\(\) \(pyart.graph.RadarMapDisplayCartopy method\), 185](#)
[_label_axes_rhi\(\) \(pyart.graph.AirborneRadarDisplay method\), 120](#)
[_label_axes_rhi\(\) \(pyart.graph.RadarDisplay method\), 150](#)
[_label_axes_rhi\(\) \(pyart.graph.RadarMapDisplay method\), 166](#)
[_label_axes_rhi\(\) \(pyart.graph.RadarMapDisplayCartopy method\), 185](#)
[_label_axes_vpt\(\) \(pyart.graph.AirborneRadarDisplay method\), 120](#)
[_label_axes_vpt\(\) \(pyart.graph.RadarDisplay method\), 150](#)
[_label_axes_vpt\(\) \(pyart.graph.RadarMapDisplay method\), 166](#)
[_label_axes_vpt\(\) \(pyart.graph.RadarMapDisplayCartopy method\), 185](#)
[_make_basemap\(\) \(pyart.graph.GridMapDisplay method\), 137](#)
[_merge\(\) \(pyart.correct.GateFilter method\), 65](#)
[_merge\(\) \(pyart.filters.GateFilter method\), 52](#)
[_parse_location_data\(\) \(pyart.core.HorizontalWindProfile method\), 35](#)
[_set_az_rhi_title\(\) \(pyart.graph.AirborneRadarDisplay method\), 120](#)
[_set_az_rhi_title\(\) \(pyart.graph.RadarDisplay method\), 150](#)
[_set_az_rhi_title\(\) \(pyart.graph.RadarMapDisplay method\), 166](#)
[_set_az_rhi_title\(\) \(pyart.graph.RadarMapDisplayCartopy method\), 185](#)
[_set_ray_title\(\) \(pyart.graph.AirborneRadarDisplay method\), 120](#)
[_set_ray_title\(\) \(pyart.graph.RadarDisplay method\), 150](#)
[_set_ray_title\(\) \(pyart.graph.RadarMapDisplay method\), 166](#)
[_set_ray_title\(\) \(pyart.graph.RadarMapDisplayCartopy method\), 185](#)
[_set_title\(\) \(pyart.graph.AirborneRadarDisplay method\), 120](#)
[_set_title\(\) \(pyart.graph.RadarDisplay method\), 150](#)
[_set_title\(\) \(pyart.graph.RadarMapDisplay method\), 166](#)
[_set_title\(\) \(pyart.graph.RadarMapDisplayCartopy method\), 185](#)

`_set_vpt_time_axis()` (pyart.graph.AirborneRadarDisplay method), 120
`_set_vpt_time_axis()` (pyart.graph.RadarDisplay static method), 150
`_set_vpt_time_axis()` (pyart.graph.RadarMapDisplay method), 166
`_set_vpt_time_axis()` (pyart.graph.RadarMapDisplayCartopy method), 185
`_set_vpt_title()` (pyart.graph.AirborneRadarDisplay method), 121
`_set_vpt_title()` (pyart.graph.RadarDisplay method), 150
`_set_vpt_title()` (pyart.graph.RadarMapDisplay method), 166
`_set_vpt_title()` (pyart.graph.RadarMapDisplayCartopy method), 185

A

`add_field()` (pyart.core.Grid method), 32
`add_field()` (pyart.core.Radar method), 38
`add_field_like()` (pyart.core.Radar method), 39
`AirborneRadarDisplay` (class in pyart.graph), 117
`angular_mean()` (in module pyart.util), 204
`angular_mean_deg()` (in module pyart.util), 204
`angular_std()` (in module pyart.util), 204
`angular_std_deg()` (in module pyart.util), 204
`angular_texture_2d()` (in module pyart.util), 204
`antenna_to_cartesian()` (in module pyart.core), 42
`antenna_vectors_to_cartesian()` (in module pyart.core), 43

C

`calculate_attenuation_philinear()` (in module pyart.correct), 68
`calculate_attenuation_zphi()` (in module pyart.correct), 69
`calculate_snr_from_reflectivity()` (in module pyart.retrieve), 94
`calculate_velocity_texture()` (in module pyart.filters), 55
`cartesian_to_antenna()` (in module pyart.core), 43
`cartesian_to_geographic()` (in module pyart.core), 43
`cartesian_to_geographic_aeqd()` (in module pyart.core), 44
`cartesian_vectors_to_geographic()` (in module pyart.core), 44
`check_field_exists()` (pyart.core.Radar method), 39
`class_based_gate_filter()` (in module pyart.filters), 56
`cleanup()` (pyart.testing.InTemporaryDirectory method), 213
`colocated_gates()` (in module pyart.util), 205
`compute_cdr()` (in module pyart.retrieve), 94
`compute_l()` (in module pyart.retrieve), 94
`compute_noisedBZ()` (in module pyart.retrieve), 95
`compute_signal_power()` (in module pyart.retrieve), 95
`compute_snr()` (in module pyart.retrieve), 96
`copy()` (pyart.correct.GateFilter method), 65
`copy()` (pyart.filters.GateFilter method), 52

`correct_bias()` (in module pyart.correct), 71
`correct_noise_rho_hv()` (in module pyart.correct), 71
`correct_sys_phase()` (in module pyart.correct), 72
`correct_visibility()` (in module pyart.correct), 72
`cross_section_ppi()` (in module pyart.util), 205
`cross_section_rhi()` (in module pyart.util), 205

D

`dealias_fourdd()` (in module pyart.correct), 72
`dealias_region_based()` (in module pyart.correct), 75
`dealias_unwrap_phase()` (in module pyart.correct), 77
`despeckle_field()` (in module pyart.correct), 78
`det_sys_phase_ray()` (in module pyart.correct), 79

E

`est_rain_rate_a()` (in module pyart.retrieve), 96
`est_rain_rate_hydro()` (in module pyart.retrieve), 96
`est_rain_rate_kdp()` (in module pyart.retrieve), 97
`est_rain_rate_z()` (in module pyart.retrieve), 98
`est_rain_rate_za()` (in module pyart.retrieve), 98
`est_rain_rate_zkdp()` (in module pyart.retrieve), 99
`est_rain_rate_zpoly()` (in module pyart.retrieve), 99
`est_rho_hv_rain()` (in module pyart.correct), 79
`est_vertical_windshear()` (in module pyart.retrieve), 100
`est_wind_vel()` (in module pyart.retrieve), 100
`est_zdr_precip()` (in module pyart.correct), 80
`est_zdr_snow()` (in module pyart.correct), 81
`estimate_noise_hs74()` (in module pyart.util), 206
`example_roi_func_constant()` (in module pyart.map), 111
`example_roi_func_dist()` (in module pyart.map), 111
`example_roi_func_dist_beam()` (in module pyart.map), 111
`exclude_above()` (pyart.correct.GateFilter method), 65
`exclude_above()` (pyart.filters.GateFilter method), 52
`exclude_all()` (pyart.correct.GateFilter method), 65
`exclude_all()` (pyart.filters.GateFilter method), 52
`exclude_below()` (pyart.correct.GateFilter method), 65
`exclude_below()` (pyart.filters.GateFilter method), 52
`exclude_equal()` (pyart.correct.GateFilter method), 65
`exclude_equal()` (pyart.filters.GateFilter method), 53
`exclude_gates()` (pyart.correct.GateFilter method), 65
`exclude_gates()` (pyart.filters.GateFilter method), 53
`exclude_inside()` (pyart.correct.GateFilter method), 66
`exclude_inside()` (pyart.filters.GateFilter method), 53
`exclude_invalid()` (pyart.correct.GateFilter method), 66
`exclude_invalid()` (pyart.filters.GateFilter method), 53
`exclude_masked()` (pyart.correct.GateFilter method), 66
`exclude_masked()` (pyart.filters.GateFilter method), 53
`exclude_none()` (pyart.correct.GateFilter method), 66
`exclude_none()` (pyart.filters.GateFilter method), 53
`exclude_not_equal()` (pyart.correct.GateFilter method), 66
`exclude_not_equal()` (pyart.filters.GateFilter method), 53
`exclude_outside()` (pyart.correct.GateFilter method), 66

exclude_outside() (pyart.filters.GateFilter method), 53
 exclude_transition() (pyart.correct.GateFilter method), 66
 exclude_transition() (pyart.filters.GateFilter method), 53
 extract_sweeps() (pyart.core.Radar method), 39

F

fetch_radar_time_profile() (in module pyart.retrieve), 101
 find_objects() (in module pyart.correct), 82
 from_u_and_v() (pyart.core.HorizontalWindProfile class method), 35

G

gate_excluded (pyart.correct.GateFilter attribute), 67
 gate_excluded (pyart.filters.GateFilter attribute), 54
 gate_included (pyart.correct.GateFilter attribute), 67
 gate_included (pyart.filters.GateFilter attribute), 54
 GateFilter (class in pyart.correct), 62
 GateFilter (class in pyart.filters), 49
 generate_az_rhi_title() (pyart.graph.AirborneRadarDisplay method), 121
 generate_az_rhi_title() (pyart.graph.RadarDisplay method), 150
 generate_az_rhi_title() (pyart.graph.RadarMapDisplay method), 166
 generate_az_rhi_title() (pyart.graph.RadarMapDisplayCartopy method), 185
 generate_filename() (pyart.graph.AirborneRadarDisplay method), 121
 generate_filename() (pyart.graph.GridMapDisplay method), 138
 generate_filename() (pyart.graph.RadarDisplay method), 150
 generate_filename() (pyart.graph.RadarMapDisplay method), 166
 generate_filename() (pyart.graph.RadarMapDisplayCartopy method), 186
 generate_grid_title() (pyart.graph.GridMapDisplay method), 138
 generate_latitudinal_level_title() (pyart.graph.GridMapDisplay method), 138
 generate_longitudinal_level_title() (pyart.graph.GridMapDisplay method), 138
 generate_ray_title() (pyart.graph.AirborneRadarDisplay method), 121
 generate_ray_title() (pyart.graph.RadarDisplay method), 151
 generate_ray_title() (pyart.graph.RadarMapDisplay method), 167
 generate_ray_title() (pyart.graph.RadarMapDisplayCartopy method), 186
 generate_title() (pyart.graph.AirborneRadarDisplay method), 121
 generate_title() (pyart.graph.RadarDisplay method), 151
 generate_title() (pyart.graph.RadarMapDisplay method), 167
 generate_title() (pyart.graph.RadarMapDisplayCartopy method), 186
 generate_vpt_title() (pyart.graph.AirborneRadarDisplay method), 122
 generate_vpt_title() (pyart.graph.RadarDisplay method), 151
 generate_vpt_title() (pyart.graph.RadarMapDisplay method), 167
 generate_vpt_title() (pyart.graph.RadarMapDisplayCartopy method), 186
 geographic_to_cartesian() (in module pyart.core), 45
 geographic_to_cartesian_aeqd() (in module pyart.core), 45
 get_azimuth() (pyart.core.Radar method), 39
 get_basemap() (pyart.graph.GridMapDisplay method), 139
 get_coeff_attg() (in module pyart.retrieve), 101
 get_elevation() (pyart.core.Radar method), 40
 get_end() (pyart.core.Radar method), 40
 get_field() (pyart.core.Radar method), 40
 get_freq_band() (in module pyart.retrieve), 101
 get_gate_x_y_z() (pyart.core.Radar method), 40
 get_mask_fzl() (in module pyart.correct), 82
 get_nyquist_vel() (pyart.core.Radar method), 41
 get_point_longitude_latitude() (pyart.core.Grid method), 32
 get_projparams() (pyart.core.Grid method), 33
 get_slice() (pyart.core.Radar method), 41
 get_start() (pyart.core.Radar method), 41
 get_start_end() (pyart.core.Radar method), 41
 get_sun_hits() (in module pyart.correct), 83
 Grid (class in pyart.core), 29
 grid_displacement_pc() (in module pyart.retrieve), 101
 grid_from_radars() (in module pyart.map), 111
 grid_shift() (in module pyart.retrieve), 102
 GridMapDisplay (class in pyart.graph), 135

H

HorizontalWindProfile (class in pyart.core), 33
 hydroclass_semisupervised() (in module pyart.retrieve), 102

I

include_above() (pyart.correct.GateFilter method), 67
 include_above() (pyart.filters.GateFilter method), 54
 include_all() (pyart.correct.GateFilter method), 67
 include_all() (pyart.filters.GateFilter method), 54
 include_below() (pyart.correct.GateFilter method), 67
 include_below() (pyart.filters.GateFilter method), 54
 include_equal() (pyart.correct.GateFilter method), 67
 include_equal() (pyart.filters.GateFilter method), 54
 include_gates() (pyart.correct.GateFilter method), 67

`include_gates()` (pyart.filters.GateFilter method), 54
`include_inside()` (pyart.correct.GateFilter method), 67
`include_inside()` (pyart.filters.GateFilter method), 54
`include_none()` (pyart.correct.GateFilter method), 67
`include_none()` (pyart.filters.GateFilter method), 54
`include_not_equal()` (pyart.correct.GateFilter method), 67
`include_not_equal()` (pyart.filters.GateFilter method), 54
`include_not_masked()` (pyart.correct.GateFilter method), 67
`include_not_masked()` (pyart.filters.GateFilter method), 54
`include_not_transition()` (pyart.correct.GateFilter method), 67
`include_not_transition()` (pyart.filters.GateFilter method), 54
`include_outside()` (pyart.correct.GateFilter method), 68
`include_outside()` (pyart.filters.GateFilter method), 55
`include_valid()` (pyart.correct.GateFilter method), 68
`include_valid()` (pyart.filters.GateFilter method), 55
`info()` (pyart.core.Radar method), 41
`init_gate_altitude()` (pyart.core.Radar method), 41
`init_gate_longitude_latitude()` (pyart.core.Radar method), 41
`init_gate_x_y_z()` (pyart.core.Radar method), 41
`init_point_altitude()` (pyart.core.Grid method), 33
`init_point_longitude_latitude()` (pyart.core.Grid method), 33
`init_point_x_y_z()` (pyart.core.Grid method), 33
`init_rays_per_sweep()` (pyart.core.Radar method), 42
`InTemporaryDirectory` (class in pyart.testing), 211
`intersection()` (in module pyart.util), 206
`interval_mean()` (in module pyart.util), 207
`interval_std()` (in module pyart.util), 207
`is_vpt()` (in module pyart.util), 208
`iso0_based_gate_filter()` (in module pyart.filters), 56
`iter_azimuth()` (pyart.core.Radar method), 42
`iter_elevation()` (pyart.core.Radar method), 42
`iter_end()` (pyart.core.Radar method), 42
`iter_field()` (pyart.core.Radar method), 42
`iter_slice()` (pyart.core.Radar method), 42
`iter_start()` (pyart.core.Radar method), 42
`iter_start_end()` (pyart.core.Radar method), 42

J

`join_radar()` (in module pyart.util), 208

K

`kdp_leastsquare_double_window()` (in module pyart.retrieve), 103
`kdp_leastsquare_single_window()` (in module pyart.retrieve), 104
`kdp_maesaka()` (in module pyart.retrieve), 104
`kdp_schneebeli()` (in module pyart.retrieve), 106
`kdp_vulpiani()` (in module pyart.retrieve), 107

L

`label_xaxis_r()` (pyart.graph.AirborneRadarDisplay method), 122
`label_xaxis_r()` (pyart.graph.RadarDisplay method), 151
`label_xaxis_r()` (pyart.graph.RadarMapDisplay method), 167
`label_xaxis_r()` (pyart.graph.RadarMapDisplayCartopy method), 186
`label_xaxis_rays()` (pyart.graph.AirborneRadarDisplay method), 122
`label_xaxis_rays()` (pyart.graph.RadarDisplay static method), 151
`label_xaxis_rays()` (pyart.graph.RadarMapDisplay method), 167
`label_xaxis_rays()` (pyart.graph.RadarMapDisplayCartopy method), 186
`label_xaxis_time()` (pyart.graph.AirborneRadarDisplay method), 122
`label_xaxis_time()` (pyart.graph.RadarDisplay static method), 151
`label_xaxis_time()` (pyart.graph.RadarMapDisplay method), 167
`label_xaxis_time()` (pyart.graph.RadarMapDisplayCartopy method), 187
`label_xaxis_x()` (pyart.graph.AirborneRadarDisplay method), 122
`label_xaxis_x()` (pyart.graph.RadarDisplay method), 151
`label_xaxis_x()` (pyart.graph.RadarMapDisplay method), 167
`label_xaxis_x()` (pyart.graph.RadarMapDisplayCartopy method), 187
`label_yaxis_field()` (pyart.graph.AirborneRadarDisplay method), 122
`label_yaxis_field()` (pyart.graph.RadarDisplay method), 151
`label_yaxis_field()` (pyart.graph.RadarMapDisplay method), 167
`label_yaxis_field()` (pyart.graph.RadarMapDisplayCartopy method), 187
`label_yaxis_y()` (pyart.graph.AirborneRadarDisplay method), 122
`label_yaxis_y()` (pyart.graph.RadarDisplay method), 152
`label_yaxis_y()` (pyart.graph.RadarMapDisplay method), 168
`label_yaxis_y()` (pyart.graph.RadarMapDisplayCartopy method), 187
`label_yaxis_z()` (pyart.graph.AirborneRadarDisplay method), 122
`label_yaxis_z()` (pyart.graph.RadarDisplay method), 152
`label_yaxis_z()` (pyart.graph.RadarMapDisplay method), 168
`label_yaxis_z()` (pyart.graph.RadarMapDisplayCartopy method), 187

M

make_empty_grid() (in module pyart.testing), 213
 make_empty_ppi_radar() (in module pyart.testing), 213
 make_empty_rhi_radar() (in module pyart.testing), 213
 make_normal_storm() (in module pyart.testing), 214
 make_single_ray_radar() (in module pyart.testing), 214
 make_storm_grid() (in module pyart.testing), 214
 make_target_grid() (in module pyart.testing), 214
 make_target_radar() (in module pyart.testing), 214
 make_time_unit_str() (in module pyart.io), 4
 make_velocity_aliased_radar() (in module pyart.testing), 214
 make_velocity_aliased_rhi_radar() (in module pyart.testing), 214
 map_gates_to_grid() (in module pyart.map), 112
 map_profile_to_gates() (in module pyart.retrieve), 108
 map_to_grid() (in module pyart.map), 113
 mean_of_two_angles() (in module pyart.util), 208
 mean_of_two_angles_deg() (in module pyart.util), 208
 metranet_read_cartesian() (in module pyart.aux_io), 21
 moment_and_texture_based_gate_filter() (in module pyart.filters), 56
 moment_based_gate_filter() (in module pyart.correct), 84
 moment_based_gate_filter() (in module pyart.filters), 58

P

phase_proc_lp() (in module pyart.correct), 85
 plot() (pyart.graph.AirborneRadarDisplay method), 122
 plot() (pyart.graph.RadarDisplay method), 152
 plot() (pyart.graph.RadarMapDisplay method), 168
 plot() (pyart.graph.RadarMapDisplayCartopy method), 187
 plot_azimuth_to_rhi() (pyart.graph.AirborneRadarDisplay method), 122
 plot_azimuth_to_rhi() (pyart.graph.RadarDisplay method), 152
 plot_azimuth_to_rhi() (pyart.graph.RadarMapDisplay method), 168
 plot_azimuth_to_rhi() (pyart.graph.RadarMapDisplayCartopy method), 187
 plot_basemap() (pyart.graph.GridMapDisplay method), 139
 plot_colorbar() (pyart.graph.AirborneRadarDisplay method), 124
 plot_colorbar() (pyart.graph.GridMapDisplay method), 139
 plot_colorbar() (pyart.graph.RadarDisplay method), 154
 plot_colorbar() (pyart.graph.RadarMapDisplay method), 170
 plot_colorbar() (pyart.graph.RadarMapDisplayCartopy method), 189
 plot_cross_hair() (pyart.graph.AirborneRadarDisplay method), 125
 plot_cross_hair() (pyart.graph.RadarDisplay static method), 154
 plot_cross_hair() (pyart.graph.RadarMapDisplay method), 170
 plot_cross_hair() (pyart.graph.RadarMapDisplayCartopy method), 189
 plot_crosshairs() (pyart.graph.GridMapDisplay method), 140
 plot_grid() (pyart.graph.GridMapDisplay method), 140
 plot_grid_lines() (pyart.graph.AirborneRadarDisplay method), 125
 plot_grid_lines() (pyart.graph.RadarDisplay static method), 155
 plot_grid_lines() (pyart.graph.RadarMapDisplay method), 171
 plot_grid_lines() (pyart.graph.RadarMapDisplayCartopy method), 190
 plot_label() (pyart.graph.AirborneRadarDisplay method), 125
 plot_label() (pyart.graph.RadarDisplay method), 155
 plot_label() (pyart.graph.RadarMapDisplay method), 171
 plot_label() (pyart.graph.RadarMapDisplayCartopy method), 190
 plot_labels() (pyart.graph.AirborneRadarDisplay method), 126
 plot_labels() (pyart.graph.RadarDisplay method), 155
 plot_labels() (pyart.graph.RadarMapDisplay method), 171
 plot_labels() (pyart.graph.RadarMapDisplayCartopy method), 190
 plot_latitude_slice() (pyart.graph.GridMapDisplay method), 141
 plot_latitudinal_level() (pyart.graph.GridMapDisplay method), 142
 plot_latlon_level() (pyart.graph.GridMapDisplay method), 143
 plot_latlon_slice() (pyart.graph.GridMapDisplay method), 144
 plot_line_geo() (pyart.graph.RadarMapDisplay method), 171
 plot_line_geo() (pyart.graph.RadarMapDisplayCartopy method), 191
 plot_line_xy() (pyart.graph.RadarMapDisplay method), 172
 plot_line_xy() (pyart.graph.RadarMapDisplayCartopy method), 191
 plot_longitude_slice() (pyart.graph.GridMapDisplay method), 144
 plot_longitudinal_level() (pyart.graph.GridMapDisplay method), 145
 plot_point() (pyart.graph.RadarMapDisplay method), 172
 plot_point() (pyart.graph.RadarMapDisplayCartopy method), 191

plot_ppi() (pyart.graph.AirborneRadarDisplay method), 126
 plot_ppi() (pyart.graph.RadarDisplay method), 155
 plot_ppi() (pyart.graph.RadarMapDisplay method), 172
 plot_ppi() (pyart.graph.RadarMapDisplayCartopy method), 191
 plot_ppi_map() (pyart.graph.RadarMapDisplay method), 174
 plot_ppi_map() (pyart.graph.RadarMapDisplayCartopy method), 193
 plot_range_ring() (pyart.graph.AirborneRadarDisplay method), 128
 plot_range_ring() (pyart.graph.RadarDisplay static method), 157
 plot_range_ring() (pyart.graph.RadarMapDisplay method), 176
 plot_range_ring() (pyart.graph.RadarMapDisplayCartopy method), 195
 plot_range_rings() (pyart.graph.AirborneRadarDisplay method), 128
 plot_range_rings() (pyart.graph.RadarDisplay method), 158
 plot_range_rings() (pyart.graph.RadarMapDisplay method), 177
 plot_range_rings() (pyart.graph.RadarMapDisplayCartopy method), 196
 plot_ray() (pyart.graph.AirborneRadarDisplay method), 128
 plot_ray() (pyart.graph.RadarDisplay method), 158
 plot_ray() (pyart.graph.RadarMapDisplay method), 177
 plot_ray() (pyart.graph.RadarMapDisplayCartopy method), 196
 plot_rhi() (pyart.graph.AirborneRadarDisplay method), 129
 plot_rhi() (pyart.graph.RadarDisplay method), 159
 plot_rhi() (pyart.graph.RadarMapDisplay method), 178
 plot_rhi() (pyart.graph.RadarMapDisplayCartopy method), 197
 plot_sweep_grid() (pyart.graph.AirborneRadarDisplay method), 131
 plot_vpt() (pyart.graph.AirborneRadarDisplay method), 133
 plot_vpt() (pyart.graph.RadarDisplay method), 160
 plot_vpt() (pyart.graph.RadarMapDisplay method), 180
 plot_vpt() (pyart.graph.RadarMapDisplayCartopy method), 199
 prepare_for_read() (in module pyart.io), 4
 projection_proj (pyart.core.Grid attribute), 33
 pyart.aux_io (module), 19
 pyart.bridge (module), 46
 pyart.core (module), 27
 pyart.correct (module), 60
 pyart.filters (module), 47
 pyart.graph (module), 115

pyart.io (module), 1
 pyart.map (module), 110
 pyart.retrieve (module), 91
 pyart.testing (module), 209
 pyart.util (module), 201

R

Radar (class in pyart.core), 35
 RadarDisplay (class in pyart.graph), 146
 RadarMapDisplay (class in pyart.graph), 163
 RadarMapDisplayCartopy (class in pyart.graph), 182
 read() (in module pyart.io), 4
 read_arm_sonde() (in module pyart.io), 5
 read_arm_sonde_vap() (in module pyart.io), 5
 read_cfradial() (in module pyart.io), 5
 read_chl() (in module pyart.io), 6
 read_d3r_gcpep_nc() (in module pyart.aux_io), 21
 read_edge_netcdf() (in module pyart.aux_io), 22
 read_gamic() (in module pyart.aux_io), 22
 read_grid() (in module pyart.io), 7
 read_grid_mdv() (in module pyart.io), 7
 read_kazr() (in module pyart.aux_io), 23
 read_mdv() (in module pyart.io), 8
 read_metrantet() (in module pyart.aux_io), 23
 read_nexrad_archive() (in module pyart.io), 9
 read_nexrad_cdm() (in module pyart.io), 10
 read_nexrad_level3() (in module pyart.io), 11
 read_noxp_iphex_nc() (in module pyart.aux_io), 24
 read_odim_h5() (in module pyart.aux_io), 24
 read_pattern() (in module pyart.aux_io), 25
 read_radix() (in module pyart.aux_io), 25
 read_rainbow_wrl() (in module pyart.aux_io), 25
 read_rsl() (in module pyart.io), 11
 read_sigmet() (in module pyart.io), 12
 read_sinarama_h5() (in module pyart.aux_io), 26
 read_uf() (in module pyart.io), 14
 rolling_window() (in module pyart.util), 208

S

selfconsistency_bias() (in module pyart.correct), 86
 selfconsistency_kdp_phidp() (in module pyart.correct), 87
 set_aspect_ratio() (pyart.graph.AirborneRadarDisplay method), 135
 set_aspect_ratio() (pyart.graph.RadarDisplay static method), 162
 set_aspect_ratio() (pyart.graph.RadarMapDisplay method), 181
 set_aspect_ratio() (pyart.graph.RadarMapDisplayCartopy method), 200
 set_limits() (pyart.graph.AirborneRadarDisplay method), 135
 set_limits() (pyart.graph.RadarDisplay static method), 162

`set_limits()` (`pyart.graph.RadarMapDisplay` method), 182
`set_limits()` (`pyart.graph.RadarMapDisplayCartopy`
method), 201
`simulated_vel_from_profile()` (in module `pyart.util`), 208
`smooth_phidp_double_window()` (in module
`pyart.correct`), 89
`smooth_phidp_single_window()` (in module
`pyart.correct`), 89
`snr_based_gate_filter()` (in module `pyart.filters`), 58
`steiner_conv_strat()` (in module `pyart.retrieve`), 109
`sun_power()` (in module `pyart.correct`), 90
`sun_retrieval()` (in module `pyart.correct`), 91

T

`temp_based_gate_filter()` (in module `pyart.filters`), 59
`texture_along_ray()` (in module `pyart.util`), 209
`to_vpt()` (in module `pyart.util`), 209

U

`u_wind` (`pyart.core.HorizontalWindProfile` attribute), 35

V

`v_wind` (`pyart.core.HorizontalWindProfile` attribute), 35
`visibility_based_gate_filter()` (in module `pyart.filters`), 59

W

`wgs84_to_swissCH1903()` (in module `pyart.core`), 46
`write()` (`pyart.core.Grid` method), 33
`write_cfradial()` (in module `pyart.io`), 14
`write_grid()` (in module `pyart.io`), 15
`write_grid_geotiff()` (in module `pyart.io`), 16
`write_grid_mdv()` (in module `pyart.io`), 17
`write_sinaram_cfradial()` (in module `pyart.aux_io`), 27
`write_uf()` (in module `pyart.io`), 18