10 Inch Smart Tab

MEURON

MST-1050

Slim Chassis depth
Less than 3cm when installed on a wall

27mm

NFC (Near Field Communication)
Support interactive RFID/Mifare/FeliCa

Glass / Surface / Recessed Mount
Mountable on all surfaces

PoE+ (Power over Ethernet)
Single cable; clean installation. IEEE 802.3at standard

LED light bar
Designed with LED light bar on the side of chassis is obvious to realize if there is any meeting room available.

RTSP (Real time streaming protocol)
Support Live content Input through network

Technical Specification

NFC (Near Field Communication)

LED light bar

Micro SD   USB   Ethernet   DC in   USB   Audio Out

Features

Programming API	HTML5 / SMIL / Android SDK
CPU	ARM quad-core 1.6GHz
Memory	2GB DDR3
Storage	8GB eMMC
Video decoder	H.264/MPEG-4/VC-1/MVC
Image codecs	JPEG/PNG (max. 1920x1080)
Orientation display	Landscape
Audio codecs	MP3
NFC module	V
PoE+	V

Display

Size	10.1"
Resolution (Max.)	1280 x 800
Brightness	300 nits
Contrast ratio	1000:1
Touch	V
Viewing angle (H/V)	178/178

IO interface

Ethernet	1 x RJ45 (10M/100M)
USB	2 x USB2.0 type
Analog Stereo out	1 x 3.5mm stereo
Expansion storage	1 x Micro SDHC slot
Speaker	2W x 2

Mechanical&Environment

Dimension (WxDxH) without stand	261.1 x 193.3 x 27mm (10.28" x 7.61" x 1.06")
Weight	710g / 1.56 1bs
Mounting	Glass / Surface / Recessed
Housing	Plastic
Environment	Operating Temp. 0~50°C Storage temperature : -20°C to 60°C Humidity : 10 to 85% (non-condensing)
Power	DC 12V, 1.5A
Certification	CE/FCC/BSMI/NCC/IC/CCC/SRRC/IMDA/BIS/WPC/RoHS
Warranty	1yr

godigitalX

MEURON