

# Assignments

| Operation                              | Comment  | Call                             | Team       |
|--|--|----------------------------------|------------|
| Example                                |  |                                  |            |
| $B := LB$                              | Lower triangular matrix $L$                    | <code>Trmm_llnn ( L, B )</code>  | Robert vdG |
| Symmetric matrix-matrix multiplication |  |                                  |            |
| $C := AB + C$                          | $A$ symmetric, stored in lower-triangular part | <code>Symm_ll ( A, B, C )</code> |            |
| $C := AB + C$                          | $A$ symmetric, stored in upper-triangular part | <code>Symm_lu ( A, B, C )</code> |            |
| $C := BA + C$                          | $A$ symmetric, stored in lower-triangular part | <code>Symm_rl ( A, B, C )</code> |            |
| $C := BA + C$                          | $A$ symmetric, stored in upper-triangular part | <code>Symm_ru ( A, B, C )</code> |            |
| Symmetric rank-k update                |  |                                  |            |
| $C := AA^T + C$                        | $C$ symmetric, stored in lower-triangular part | <code>Syrk_ln ( A, C )</code>    |            |
| $C := AA^T + C$                        | $C$ symmetric, stored in upper-triangular part | <code>Syrk_ut ( A, C )</code>    |            |
| $C := A^T A + C$                       | $C$ symmetric, stored in lower-triangular part | <code>Syrk_ln ( A, C )</code>    |            |
| $C := A^T A + C$                       | $C$ symmetric, stored in upper-triangular part | <code>Syrk_ut ( A, C )</code>    |            |

| Operation                                   | Comment  | Team                       |  |
|---|--|----------------------------|--|
| Symmetric rank-2k update                    |  |                            |  |
| $C := AB^T + BA^T + C$                      | $C$ symmetric, stored in lower-triangular part | Syr2k_ln ( $A, B, C$ )     |  |
| $C := AB^T + BA^T + C$                      | $C$ symmetric, stored in upper-triangular part | Syr2k_un ( $A, B, C$ )     |  |
| $C := A^T B + B^T A + C$                    | $C$ symmetric, stored in lower-triangular part | Syr2k_lt ( $A, B, C$ )     |  |
| $C := A^T B + B^T A + C$                    | $C$ symmetric, stored in upper-triangular part | Syr2k_ut ( $A, B, C$ )     |  |
| Triangular matrix-matrix multiplication     |  |                            |  |
| $B := L^T B$                                | $L$ stored in lower triangle                   | Trmm_l_ltn ( $A, B$ )      |  |
| $B := UB$                                   | $U$ stored in upper triangle                   | Trmm_l_unn ( $A, B$ )      |  |
| $B := U^T B$                                | $U$ stored in upper triangle                   | Trmm_l_utn ( $A, B$ )      |  |
| $B := BL$                                   | $L$ stored in lower triangle                   | Trmm_r_lnn ( $A, B$ )      |  |
| $B := BL^T$                                 | $L$ stored in lower triangle                   | Trmm_r_ltn ( $A, B$ )      |  |
| $B := BU$                                   | $U$ stored in upper triangle                   | Trmm_r_unn ( $A, B$ )      |  |
| $B := BU^T$                                 | $U$ stored in upper triangle                   | Trmm_r_utn ( $A, B$ )      |  |
| Triangular-triangular matrix multiplication |  |                            |  |
| $B := LU$                                   | $L$ lower triangular, $U$ upper triangular     | Trtrmm_l_unn ( $L, U, B$ ) |  |
| $B := UL$                                   | $L$ lower triangular, $U$ upper triangular     | Trtrmm_u_lnn ( $U, L, B$ ) |  |
| $B := U^T L$                                | $L$ lower triangular, $U$ upper triangular     | Trtrmm_u_ltn ( $U, L, B$ ) |  |
| $B := UL^T$                                 | $L$ lower triangular, $U$ upper triangular     | Trtrmm_u_lnt ( $U, L, B$ ) |  |



## **Part I**

# **Triangular Matrix-matrix Multiplication**



Cases

Triangular matrix-matrix multiplication (TRMM) is matrix-matrix multiplication where one of the matrices is square and (lower or upper) triangular.

The full set of triangular matrix-matrix multiplication cases is denoted by TRMM\_□□□□, where the letters in the four boxes denote whether the triangular matrix is on the Left or Right, is Lower or Upper triangular, is Not transposed or Transposed, and has a Nonunit or Unit diagonal:

|      | LL□□        | LU□□        | RL□□       | RU□□       |
|------|-------------|-------------|------------|------------|
| □□N□ | $B = LB$    | $B = UB$    | $B = BL$   | $B = BU$   |
| □□T□ | $B = L^T B$ | $B = U^T B$ | $B = BL^T$ | $B = BU^T$ |





**$B := LB$  — Team: Robert van de Geijn**

## 2.1 Operation

Consider the operation

$$B := LB$$

where  $L$  is a  $m \times m$  lower triangular matrix and  $B$  is a  $m \times n$  matrix. This is a special case of triangular matrix-matrix multiplication, with the Lower triangular matrix on the LEFT, and the triangular matrix is Not transposed. We will refer to this operation as TRMM\_LLNN where the LLNN stands for left lower no-transpose nonunit diagonal. The nonunit diagonal means we will use the entries of the matrix that are stored on the diagonal.

## 2.2 Precondition and postcondition

In the precondition

$$B = \hat{B}$$

$\hat{B}$  denotes the original contents of  $B$ . This allows us to express the state upon completion, the postcondition, as

$$B = L\hat{B}.$$

## 2.3 Partitioned Matrix Expressions and loop invariants

There are two PME's for this operation.

### 2.3.1 PME 1

To derive the second PME, partition

$$L \rightarrow \left( \begin{array}{c|c} L_{TL} & 0 \\ \hline L_{BL} & L_{BR} \end{array} \right), \quad \text{and} \quad B \rightarrow \left( \begin{array}{c} B_T \\ B_B \end{array} \right).$$

Substituting these into the postcondition yields

$$\left( \frac{B_T}{B_B} \right) = \left( \frac{L_{TL} \mid 0}{L_{BL} \mid L_{BR}} \right) \left( \frac{\hat{B}_T}{\hat{B}_B} \right)$$

or, equivalently,

$$\left( \frac{B_T}{B_B} \right) = \left( \frac{L_{TL}\hat{B}_T}{L_{BL}\hat{B}_T + L_{BR}\hat{B}_B} \right)$$

so that, upon completion

$$\frac{B_T = L_{TL}\hat{B}_T}{B_B = L_{BL}\hat{B}_T + L_{BR}\hat{B}_B}$$

From this, we can choose two loop invariants:

**Invariant 1:**  $\left( \frac{B_T = \hat{B}_T}{B_B = L_{BR}\hat{B}_B} \right)$ . (The top part has been left alone and the bottom part has been partially computed).

**Invariant 2:**  $\left( \frac{B_T = \hat{B}_T}{B_B = L_{BL}\hat{B}_T + L_{BR}\hat{B}_B} \right)$ . (The top part has been left alone and the bottom part has been completely computed).

### 2.3.2 PME 2

To derive the second PME, partition

$$B \rightarrow \left( B_L \mid B_R \right)$$

and does not partition  $L$ . Substituting these into the postcondition yields

$$\left( B_L \mid B_R \right) = L \left( \hat{B}_L \mid \hat{B}_R \right)$$

or, equivalently,

$$\left( B_L \mid B_R \right) = \left( L\hat{B}_L \mid L\hat{B}_R \right)$$

so that, upon completion

$$B_L = L\hat{B}_L \mid B_R = L\hat{B}_R$$

From this, we can choose two more loop invariants:

**Invariant 3:**  $\left( B_L = L\hat{B}_L \mid B_R = \hat{B}_R \right)$ . (The left part has been completely finished and the right part has been left untouched).

**Invariant 4:**  $\left( B_L = \hat{B}_L \mid B_R = L\hat{B}_R \right)$ . (The left part has been completely finished and the right part has been left untouched).

### 2.3.3 Notes

How do I decide to partition the matrices in the postcondition?

- Pick a matrix (operand), any matrix.
- If that matrix has
  - a triangular structure (in storage), then you want to either partition it into four quadrants, or not at all. Symmetric matrices and triangular matrices have a triangular structure (in storage).
  - no particular structure, then you partition it vertically (left-right), horizontally (top-bottom), or not at all.
- Next, partition the other matrices similarly, but conformally (meaning the resulting multiplications with the parts are legal).

Take our problem here:  $B := LB$ . Start by partitioning  $L$  into quadrants:

$$L = \left( \begin{array}{c|c} L_{TL} & 0 \\ \hline L_{BL} & L_{BR} \end{array} \right) \hat{B}.$$

Now, the way partitioned matrix multiplication works, this doesn't make sense:

$$B = \underbrace{\left( \begin{array}{c|c} L_{TL} & 0 \\ \hline L_{BL} & L_{BR} \end{array} \right) \hat{B}}_{\left( \begin{array}{c} L_{TL} \times \text{something} + 0 \times \text{something} \\ \hline L_{BL} \times \text{something} + L_{BR} \times \text{something} \end{array} \right)}.$$

So, we need to also partition  $B$  into a top part and a bottom part:

$$\left( \begin{array}{c} B_T \\ B_B \end{array} \right) = \underbrace{\left( \begin{array}{c|c} L_{TL} & 0 \\ \hline L_{BL} & L_{BR} \end{array} \right) \left( \begin{array}{c} \hat{B}_T \\ \hat{B}_B \end{array} \right)}_{\left( \begin{array}{c} L_{TL}B_T + B_B \\ \hline L_{BL}B_T + L_{BR}B_B \end{array} \right)}.$$

Alternatively, what if you don't partition  $L$ ? You have to partition *something* so let's try partitioning  $B$ :

$$\left( \begin{array}{c} B_T \\ B_B \end{array} \right) = L \left( \begin{array}{c} \hat{B}_T \\ \hat{B}_B \end{array} \right)$$

But that doesn't work... Instead

$$\left( B_L \mid B_R \right) = L \left( \hat{B}_L \mid \hat{B}_R \right) = \left( L\hat{B}_L \mid L\hat{B}_R \right)$$

works just fine.



## **Part II**

# **Symmetric Matrix-matrix Multiplication**



Cases

Symmetric matrix-matrix multiplication (SYMM) is matrix-matrix multiplication where one of the matrices is square and symmetric, stored in the lower or upper triangular part of the matrix.

The full set of symmetric matrix-matrix multiplication cases is denoted by SYMM\_□□, where the letters in the two boxes denote whether the symmetric matrix is on the Left or Right, and is stored in the Lower or Upper triangular part of that matrix:

|    | L□            | R□            |                                       |
|----|---------------|---------------|---------------------------------------|
| □L | $C := AB + C$ | $C := BA + C$ | A symmetric, stored in lower triangle |
| □U | $C := AB + C$ | $C := BA + C$ | A symmetric, stored in upper triangle |





# **Part III**

## **Symmetric Rank-k Update**



## Cases

Symmetric rank-k update (SYRK) is matrix-matrix multiplication of a matrix with its transpose, where the matrix  $C$  being updated is symmetric, stored in the lower or upper triangular part of the matrix.

The full set of symmetric rank-k cases is denoted by SYRK\_□□, where the letters in the two boxes denote whether the matrices begin multiplied are Not transposed or Transposed, and whether the matrix being updated is stored in the Lower or Upper triangular part:

|    | N□              | T□               |   |
|----|-----------------|------------------|---|
| □L | $C := AA^T + C$ | $C := A^T A + C$ | $C$ symmetric, stored in lower triangle |
| □U | $C := AA^T + C$ | $C := A^T A + C$ | $C$ symmetric, stored in upper triangle |



# **Part IV**

## **Symmetric Rank-2k Update**



## Cases

Symmetric rank-2k update (SYR2K) is matrix-matrix multiplication of two matrices where both the result and the transpose of that result are added to a symmetric matrix  $C$ , stored in the lower or upper triangular part of the matrix.

The full set of symmetric rank-2k cases is denoted by SYR2K\_□□, where the letters in the two boxes denote whether the matrices begin multiplied are Not transposed or Transposed, and whether the matrix being updated is stored in the Lower or Upper triangular part:

|    | N□                     | T□                       |   |
|----|------------------------|--------------------------|---|
| □L | $C := AB^T + BA^T + C$ | $C := A^T B + B^T A + C$ | $C$ symmetric, stored in lower triangle |
| □U | $C := AB^T BA^T + C$   | $C := A^T B + B^T A + C$ | $C$ symmetric, stored in upper triangle |





## **Part V**

# **Triangular Solve with Multiple Right-hand Sides**



## Cases

Triangular solve with multiple right-hand sides (TRSM) is a matrix-matrix multiplication in disguise: Not only is one of the matrices square and (lower or upper) triangular, but in addition, one multiplies with the inverse of the matrix.

The full set of TRSM cases is denoted by `TRSM_□□□□`, where the letters in the four boxes denote whether the triangular matrix is on the Left or Right, is Lower or Upper triangular, is Not transposed or Transposed, and has a Nonunit or Unit diagonal:

|      | LL□□           | LU□□           | RL□□           | RU□□           |
|------|----------------|----------------|----------------|----------------|
| □□N□ | $B := L^{-1}B$ | $B := U^{-1}B$ | $B := BL^{-1}$ | $B := BU^{-1}$ |
| □□T□ | $B := L^{-T}B$ | $B := U^{-T}B$ | $B := BL^{-T}$ | $B := BU^{-T}$ |

We will only consider the case where we compute with the diagonal.

Where does the name *triangular solve with multiple right-hand sides* come from? If one wants to compute  $B := A^{-1}B$  one can also think of this as solving  $AX = B$ , overwriting the matrix  $A$  with the solution matrix  $X$ . Now, partition  $X$  and  $B$  by columns. Then

$$\underbrace{A \begin{pmatrix} x_0 & x_1 & \cdots & x_{n-1} \end{pmatrix}}_{\begin{pmatrix} Ax_0 & Ax_1 & \cdots & Ax_{n-1} \end{pmatrix}} = \begin{pmatrix} b_0 & b_1 & \cdots & b_{n-1} \end{pmatrix}$$

and hence, for each column  $j$ ,  $Ax_j = b_j$ . This means that one can instead solve with matrix  $A$ , and because  $B$  has many columns, this becomes a *solve with multiple right-hand sides*. If  $A$  is triangular, then it is a *triangular solve with multiple right-hand sides*. Importantly, the inverse of the matrix is never computed.