ECE 6310 - Advanced Electromagnetic Fields: Homework Set #1

Miguel Gomez

1 days - 8 hours - 7 min until deadline!!

$\mathscr{A}\mathscr{B}\mathscr{C}\mathscr{D}\mathscr{E}\mathscr{F}\mathscr{G}\mathscr{H}\mathscr{I}\mathscr{J}\mathscr{K}\mathscr{L}\mathscr{M}\mathscr{N}\mathscr{O}\mathscr{P}\mathscr{Q}\mathscr{R}\mathscr{S}\mathscr{T}\mathscr{U}\mathscr{V}\mathscr{W}\mathscr{X}\mathscr{Y}\mathscr{Z}$

$\mathcal{A}\mathcal{B}\mathcal{C}\mathcal{D}\mathcal{E}\mathcal{F}\mathcal{G}\mathcal{H}\mathcal{I}\mathcal{J}\mathcal{K}\mathcal{L}\mathcal{M}\mathcal{N}\mathcal{O}\mathcal{P}\mathcal{Q}\mathcal{R}\mathcal{S}\mathcal{T}\mathcal{U}\mathcal{V}\mathcal{W}\mathcal{X}\mathcal{Y}\mathcal{Z}$

1 Preliminaries

In this document, we use standard notation for electromagnetic theory. Key equations and concepts are summarized below:

Vector Notation

- $\boldsymbol{\mathscr{E}}$: Electric field intensity
- $\boldsymbol{\mathscr{H}}$: Magnetic field intensity
- $\boldsymbol{\mathscr{D}}$: Electric flux density
- $\boldsymbol{\mathscr{B}}$: Magnetic flux density
- $\boldsymbol{\mathscr{J}}$: Current density
- ρ_v: Volume charge density

Differential Operators

- $\nabla\cdot$: Divergence of a vector field
- $\nabla\times$: Curl of a vector field

- ∇ : Gradient of a scalar field
- ∂_i : Partial derivative with respect to the independent basis element i

Maxwell's Equations

In integral form, Maxwell's equations are given by:

$$\oint_{\partial V} \boldsymbol{\mathscr{E}} \cdot d\boldsymbol{\ell} = -\frac{d}{dt}\int_V \boldsymbol{\mathscr{B}} \cdot d\boldsymbol{\mathcal{S}} \qquad \text{(Faraday's Law of Induction)} \tag{1}$$

$$\oint_{\partial V} \boldsymbol{\mathscr{H}} \cdot d\boldsymbol{\ell} = \int_V \boldsymbol{\mathscr{J}} \cdot d\boldsymbol{\mathcal{S}} + \frac{d}{dt}\int_V \boldsymbol{\mathscr{D}} \cdot d\boldsymbol{\mathcal{S}} \qquad \text{(Ampère's Circuital Law)} \tag{2}$$

$$\oiint_{\partial V} \boldsymbol{\mathscr{D}} \cdot d\boldsymbol{\mathcal{S}} = \int_V \rho_v dV \qquad \text{(Gauss's Law for Electricity)} \tag{3}$$

$$\oiint_{\partial V} \boldsymbol{\mathscr{B}} \cdot d\boldsymbol{\mathcal{S}} = 0 \qquad \text{(Gauss's Law for Magnetism)} \tag{4}$$

Other Relevant Equations

- Continuity Equation: $\nabla \cdot \boldsymbol{\mathscr{J}} + \partial_t \rho_v = 0$
- Relationship between $\boldsymbol{\mathscr{E}}$, $\boldsymbol{\mathscr{D}}$: $\boldsymbol{\mathscr{D}} = \epsilon \boldsymbol{\mathscr{E}}$
- Relationship between $\boldsymbol{\mathscr{H}}$, $\boldsymbol{\mathscr{B}}$: $\boldsymbol{\mathscr{B}} = \mu \boldsymbol{\mathscr{H}}$

Boundary Conditions

Discuss the boundary conditions for $\boldsymbol{\mathscr{E}}$, $\boldsymbol{\mathscr{H}}$, $\boldsymbol{\mathscr{D}}$, and $\boldsymbol{\mathscr{B}}$ at interfaces between different media.

Problem 1.3

The electric flux density inside a cube is given by:

(a) $\vec{D} = \hat{a}_x(3 + x)$

(b) $\vec{D} = \hat{a}_y(4 + y^2)$

Find the total electric charge enclosed inside the cubical volume when the cube is in the first octant with three edges coincident with the x, y, z axes and one corner at the origin. Each side of the cube is 1 m long.
Ok, this one we can do by using the following expressions from the text [1]:

$$\oiint_s \boldsymbol{\mathscr{D}} ds = \iiint_v \mathscr{q}_{ev} dv = \mathscr{Q}_e \tag{5}$$

$$\mathscr{q}_{ev} = \Delta \cdot \boldsymbol{\mathscr{D}} \tag{6}$$

We apply expression 6 then plug into expression 5 to get the total electric charge.

$$\iiint_V \mathscr{q}_{ev} = \iiint_V \Delta \cdot (\hat{a}_x(3 + x))dV = \iiint_V \partial_x(\hat{a}_x(3 + x))dV = \iiint_0^1 1dV = 1$$

$$\iiint_V \mathscr{q}_{ev} = \iiint_V \Delta \cdot (\hat{a}_y(4 + y^2))dV = \iiint_V \partial_y(\hat{a}_y(4 + y^2))dV = \iiint_0^1 2y\ dV$$

$$\iiint_0^1 2y\ dV = \iint_0^1 \int_0^1 2ydy\ ds = \iint_0^1 y^2|_0^1 ds = \iint_0^1 (1 - 0)\ ds = 1$$

Problem 1.4

An infinite planar interface between media, as shown in the figure, is formed by having air (medium #1) on the left of the interface and lossless polystyrene (medium #2) to the right of the interface. An electric surface charge density $\sigma_{es} = 0.2\,\mathrm{C/m^2}$ exists along the entire interface. The static electric flux density inside the polystyrene is given by $\vec{D}_2 = 6\hat{a}_x + 3\hat{a}_z\,\mathrm{C/m^2}$. Determine the corresponding vector:

(a) Electric field intensity inside the polystyrene.
we can find this using the following expression for the Electric field

intensity vector:

$$
\begin{aligned}
\epsilon_{poly} &= 2.56\epsilon_0 \\
\boldsymbol{\mathscr{D}} &= \epsilon\boldsymbol{\mathscr{E}} \\
\boldsymbol{\mathscr{E}} &= \epsilon^{-1}\boldsymbol{\mathscr{D}} = 0.390625\epsilon_0^{-1} \cdot \boldsymbol{\mathscr{D}} = \epsilon_0^{-1}(2.34 \cdot a_x \ + \ 1.17 \cdot a_z)
\end{aligned}
$$

(b) Electric polarization vector inside the polystyrene.
we can find this using the following expression for the polarization vector:

$$\boldsymbol{\mathscr{P}}_e = \epsilon_0\chi_e\boldsymbol{\mathscr{E}}$$

$$\chi_e = \epsilon_r - 1 = 2.56 - 1 = 1.56$$

$$\boldsymbol{\mathscr{P}}_e = 1.56\cancelto{1}{\epsilon_0\epsilon_0^{-1}}(2.34 \cdot a_x \ + \ 1.17 \cdot a_z) = 3.6504 \cdot a_x \ + \ 1.8252 \cdot a_z$$

(c) Electric flux density inside the air medium.
By the continuity of tangential components at the boundary:
$\hat{\mathbf{n}} \times (\boldsymbol{\mathscr{E}}_2 - \boldsymbol{\mathscr{E}}_1) = 0$
we apply the following.

$$
\begin{aligned}
\boldsymbol{\mathscr{E}}_{air} &= \boldsymbol{\mathscr{E}}_{Poly} \\
\boldsymbol{\mathscr{D}}_{air} &= \epsilon_{air}\boldsymbol{\mathscr{E}}_{air} \\
\therefore \boldsymbol{\mathscr{D}}_{air}\epsilon_{air}^{-1} &= \boldsymbol{\mathscr{D}}_{Poly}\epsilon_{Poly}^{-1} \\
\boldsymbol{\mathscr{D}}_{air} &= \frac{\epsilon_{air}}{\epsilon_{Poly}}\boldsymbol{\mathscr{D}}_{Poly} = \frac{\cancel{\epsilon_0} \cdot 1}{\cancel{\epsilon_0} \cdot 2.56} \cdot \boldsymbol{\mathscr{D}}_{Poly} \\
&= \frac{6}{2.56}a_x = 2.34 \cdot a_x
\end{aligned}
$$

The normal components at the boundary are not continuous and therefore we must do more.
The normal is $\hat{a}_z$
$\hat{\mathbf{n}} \cdot (\boldsymbol{\mathscr{D}}_2 - \boldsymbol{\mathscr{D}}_1) = q_{es}$

$$
\begin{aligned}
\hat{a}_z \cdot (\boldsymbol{\mathscr{D}}_2 - \boldsymbol{\mathscr{D}}_1) &= 0.2 \\
\boldsymbol{\mathscr{D}}_{1z} &= \boldsymbol{\mathscr{D}}_{2z} - 0.2 = 3 - .2 = 2.8
\end{aligned}
$$

(d) Electric field intensity inside the air medium.
Again using the expression $\boldsymbol{\mathscr{D}} = \epsilon\boldsymbol{\mathscr{E}}$

$$
\begin{aligned}
\boldsymbol{\mathscr{D}}_{air} &= \epsilon_{air}\boldsymbol{\mathscr{E}}_{air} \\
\boldsymbol{\mathscr{E}}_{air} &= \epsilon_{air}^{-1}\boldsymbol{\mathscr{D}}_{air} \\
&= \epsilon_0^{-1}(2.34 \cdot a_x + 2.8 \cdot a_z)
\end{aligned}
$$

(e) Electric polarization vector inside the air medium.
Again using $\boldsymbol{\mathscr{P}}_e = \epsilon_0\chi_e\boldsymbol{\mathscr{E}}$

$$
\begin{aligned}
\boldsymbol{\mathscr{P}}_{e_{air}} &= \epsilon_0\chi_{e_{air}}\boldsymbol{\mathscr{E}}_{air} \\
&= \chi_{e_{air}}\cancelto{1}{\epsilon_0\epsilon_0^{-1}}(2.34 \cdot a_x + 2.8 \cdot a_z) \\
\chi_{e_{air}} &= \epsilon_{r_{air}} - 1 = 1 - 1 = 0 \\
\therefore \boldsymbol{\mathscr{P}}_{e_{air}} &= \mathbf{0}
\end{aligned}
$$

Leave your answers in terms of ϵ_0, μ_0.

Problem 1.13

The instantaneous magnetic flux density in free space is given by:

$$\boldsymbol{\mathscr{B}} = \hat{a}_x B_x \cos(2y)\sin(\omega t - \pi z) + \hat{a}_y B_y \cos(2x)\cos(\omega t - \pi z)$$

where B_x and B_y are constants. Assuming there are no sources at the observation points x, y, determine the electric displacement current density.
We can obtain the electric displacement current $\mathscr{J}_d$ by using the following expressions:

$$
\begin{aligned}
\nabla \times \boldsymbol{H} &= \boldsymbol{J}_i + \boldsymbol{J}_c + \boldsymbol{J}_d && (7) \\
\boldsymbol{B} &= \mu\boldsymbol{H} && (8) \\
\boldsymbol{J}_d &= \frac{\partial \boldsymbol{D}}{\partial t} && (9)
\end{aligned}
$$

We take $\boldsymbol{J}_i + \boldsymbol{J}_c$ to be 0 since we have no sources at the observation points. Using expression 7 and solving expression 8 for $\boldsymbol{H}$:

$$
\begin{aligned}
\nabla \times \boldsymbol{H} &= \boldsymbol{J}_d \\
\boldsymbol{J}_d &= \nabla \times \mu^{-1} \boldsymbol{B} \\
\boldsymbol{J}_d &= \mu^{-1} \nabla \times \boldsymbol{B} \\
&= \mu^{-1} \left[\hat{a}_x \left(\frac{\partial \boldsymbol{B}_z}{\partial y} - \frac{\partial \boldsymbol{B}_y}{\partial z} \right) - \hat{a}_y \left(\frac{\partial \boldsymbol{B}_z}{\partial x} - \frac{\partial \boldsymbol{B}_x}{\partial z} \right) + \hat{a}_z \left(\frac{\partial \boldsymbol{B}_y}{\partial x} - \frac{\partial \boldsymbol{B}_x}{\partial y} \right) \right] \\
\boldsymbol{B}_z &= 0 \\
&= \mu^{-1} \left[\hat{a}_x \left(0 - \frac{\partial \boldsymbol{B}_y}{\partial z} \right) - \hat{a}_y \left(0 - \frac{\partial \boldsymbol{B}_x}{\partial z} \right) + \hat{a}_z \left(\frac{\partial \boldsymbol{B}_y}{\partial x} - \frac{\partial \boldsymbol{B}_x}{\partial y} \right) \right] \\
&= \mu^{-1} \left[-\hat{a}_x \frac{\partial \boldsymbol{B}_y}{\partial z} + \hat{a}_y \frac{\partial \boldsymbol{B}_x}{\partial z} + \hat{a}_z \left(\frac{\partial \boldsymbol{B}_y}{\partial x} - \frac{\partial \boldsymbol{B}_x}{\partial y} \right) \right] \\
\frac{\partial \boldsymbol{B}_x}{\partial z} &= -\pi B_x \cos(2y) \cos(\omega t - \pi z) \\
\frac{\partial \boldsymbol{B}_y}{\partial z} &= \pi B_y \cos(2x) \sin(\omega t - \pi z) \\
\boldsymbol{\mathscr{B}} &= \hat{a}_x B_x \cos(2y) \sin(\omega t - \pi z) + \hat{a}_y B_y \cos(2x) \cos(\omega t - \pi z)
\end{aligned}
$$

Problem 1.20

The instantaneous electric field inside a conducting rectangular pipe (waveguide) of width a is given by:

$$
\boldsymbol{\mathscr{E}} = \hat{a}_y E_0 \sin\left(\frac{\pi x}{a}\right) \cos(\omega t - \beta_z z)
$$

where β_z is the waveguide's phase constant. Assuming there are no sources within the free-space-filled pipe determine the:

(a) Corresponding instantaneous magnetic field components inside the conducting pipe.

(b) Phase constant β_z.

(c) The height of the waveguide is b.

Problem 2.18

The time-varying electric field inside a lossless dielectric material of polystyrene, of infinite dimensions and with a relative permittivity (dielectric constant) of 2.56, is given by:

$$\vec{\mathscr{E}} = \hat{a}_x 10^{-3} \sin(2\pi \times 10^7 t)\,\mathrm{V/m}$$

Determine the corresponding:

(a) Electric susceptibility of the dielectric material.

(b) Time-harmonic electric flux density vector.

(c) Time-harmonic electric polarization vector.

(d) Time-harmonic displacement current density vector.

(e) Time-harmonic polarization current density vector defined as the partial derivative of the corresponding electric polarization vector.

Leave your answers in terms of ϵ_0, μ_0.

Problem 2.25

Aluminum has a static conductivity of about $\sigma = 3.96 \times 10^7\,\mathrm{S/m}$ and an electron mobility of $\mu_e = 2.2 \times 10^{-3}\,\mathrm{m^2/(V\text{-}s)}$. Assuming that an electric field of $\vec{E} = \hat{a}_x 2\,\mathrm{V/m}$ is applied perpendicularly to the square area of an aluminum wafer with cross-sectional area of about $10\,\mathrm{cm}^2$, find the:

(a) Electron charge density q_{ve}.

(b) Electron drift velocity v_e.

(c) Electric current density J.

(d) Electric current flowing through the square cross section of the wafer.

(e) Electron density N_e.

Leave your answers in terms of ϵ_0, μ_0.

References

[1] Constantine A. Balanis. *advanced engineering electromagnetics*, chapter 1, page 2–3. John Wiley & Sons, 2024.