

## Lab 2

### 练习 1: 理解first-fit 连续物理内存分配算法（思考题）

我将逐段解释 kern/mm/default\_pmm.c 中的代码，归纳每个函数、结构体的作用，最后总结该 C 代码的设计流程及效果。代码解读时将使用原文件的行号以便对代码所处位置进行定位。

- 行 1-61: 文件引入与注释

```
1 // pmm 头文件引入
2 #include <pmm.h>
3 // 链表变量结构头文件引入
4 #include <list.h>
5 // string 型变量头文件引入
6 #include <string.h>
7 // default_pmm 头文件引入
8 #include <default_pmm.h>
9 // 注释部分详细说明了 First-Fit 内存分配算法（FFMA）的基本思想：在空闲链表中找到第一个满足需求的内存块分配出去
10 /* In the first fit algorithm, the allocator keeps a list of free blocks (known as the free
11 list) and,
12 on receiving a request for memory, scans along the list for the first block that is large
13 enough to
14 satisfy the request. If the chosen block is significantly larger than that requested, then
15 it is
16 usually split, and the remainder added to the list as another free block.
17 Please see Page 196~198, Section 8.2 of Yan Wei Min's chinese book "Data Structure -- C
18 programming language"
19 */
20 // LAB2 EXERCISE 1: YOUR CODE
21 // you should rewrite functions: default_init,default_init_memmap,default_alloc_pages,
22 default_free_pages.
23 /*
24 * Details of FFMA
25 * (1) Prepare: In order to implement the First-Fit Mem Alloc (FFMA), we should manage the free
26 mem block use some list.
27 * The struct free_area_t is used for the management of free mem blocks. At first
28 you should
29 * be familiar to the struct list in list.h. struct list is a simple doubly linked
30 list implementation.
31 * You should know how to USE: list_init, list_add(list_add_after),
32 list_add_before, list_del, list_next, list_prev
33 * Another tricky method is to transform a general list struct to a special struct
34 (such as struct page):
35 * you can find some MACRO: le2page (in memlayout.h), (in future labs: le2vma (in
36 vmm.h), le2proc (in proc.h),etc.)
37 * (2) default_init: you can reuse the demo default_init fun to init the free_list and set
38 nr_free to 0.
39 * free_list is used to record the free mem blocks. nr_free is the total number
40 for free mem blocks.
41 * (3) default_init_memmap: CALL GRAPH: kern_init --> pmm_init-->page_init-->init_memmap-->
42 pmm_manager->init_memmap
43 * This fun is used to init a free block (with parameter: addr_base, page_number).
44 * First you should init each page (in memlayout.h) in this free block, include:
45 * p->flags should be set bit PG_property (means this page is valid. In
46 pmm_init fun (in pmm.c),
47 * the bit PG_reserved is setted in p->flags)
48 * if this page is free and is not the first page of free block, p->property
49 should be set to 0.
50 * if this page is free and is the first page of free block, p->property
51 should be set to total num of block.
52 * p->ref should be 0, because now p is free and no reference.
```

```

36 *           We can use p->page_link to link this page to free_list, (such as:
list_add_before(&free_list, &(p->page_link)); )
37 *           Finally, we should sum the number of free mem block: nr_free+=n
38 * (4) default_alloc_pages: search find a first free block (block size >=n) in free list and
reszie the free block, return the addr
39 *           of malloced block.
40 *           (4.1) So you should search freelist like this:
41 *               list_entry_t le = &free_list;
42 *               while((le=list_next(le)) != &free_list) {
43 *                   ....
44 *               (4.1.1) In while loop, get the struct page and check the p->property (record
the num of free block) >=n?
45 *                   struct Page *p = le2page(le, page_link);
46 *                   if(p->property >= n){ ...
47 *               (4.1.2) If we find this p, then it' means we find a free block(block size
>=n), and the first n pages can be malloced.
48 *                   Some flag bits of this page should be setted: PG_reserved =1,
PG_property =0
49 *                   unlink the pages from free_list
50 *                   (4.1.2.1) If (p->property >n), we should re-caluculate number of the the
rest of this free block,
51 *                       (such as: le2page(le,page_link))->property = p->property - n;)
52 *                   (4.1.3) re-caluculate nr_free (number of the the rest of all free block)
53 *                   (4.1.4) return p
54 *                   (4.2) If we can not find a free block (block size >=n), then return NULL
55 * (5) default_free_pages: relink the pages into free list, maybe merge small free blocks into
big free blocks.
56 *           (5.1) according the base addr of withdrew blocks, search free list, find the
correct position
57 *           (from low to high addr), and insert the pages. (may use list_next,
le2page, list_add_before)
58 *           (5.2) reset the fields of pages, such as p->ref, p->flags (PageProperty)
59 *           (5.3) try to merge low addr or high addr blocks. Notice: should change some
pages's p->property correctly.
60 */
61 static free_area_t free_area;
62 // 为两个变量类型设置宏名字
63 // free_list 表示空闲块双向链表的链表头
64 #define free_list (free_area.free_list)
65 // nr_free 表示空闲页数量
66 #define nr_free (free_area.nr_free)

```

- 行 \$62-67\$: 函数 \$default\_init\$, 用于初始化空闲块链表空间和空闲页数量

```

1 static void
2 default_init(void) {
3     list_init(&free_list);
4     nr_free = 0;
5 }

```

• 行 \$68-95\$, 函数 \$default\_init\_memmap\$, 用于初始化一段连续的空闲物理页

```

1 // 标记从 base 开始、长度为 n 的一段页为可分配空闲页块
2 static void
3 default_init_memmap(struct Page *base, size_t n) {
4     // 块长需大于 0
5     assert(n > 0);
6     // 初始化指针 p 指向输入参数 base 的地址
7     struct Page *p = base;
8     // 对每个页结构体重置标志位 flags 与 property, 清空引用计数
9     for (; p != base + n; p++) {
10         assert(PageReserved(p));
11         p->flags = p->property = 0;
12         set_page_ref(p, 0);
13     }

```

```

14 // 对块首页 base 设置 property = n, 代表块长度
15 base->property = n;
16 // 设置 PageProperty 标志
17 SetPageProperty(base);
18 // 空闲页数量加 n
19 nr_free += n;
20 // 将该块插入空闲链表中, 按物理地址从低到高顺序排列
21 if (list_empty(&free_list)) {
22     // list_empty 宏会检查 free_list 的前驱和后继是否都指向自身, 若空闲链表为空, 直接插入
23     list_add(&free_list, &(base->page_link));
24 } else {
25     // 若不为空, 自头结点遍历链表
26     list_entry_t* le = &free_list;
27     while ((le = list_next(le)) != &free_list) {
28         // 找到当前链表节点对应的物理页 page
29         struct Page* page = le2page(le, page_link);
30         // 如果当前要插入的块 base 的地址小于当前节点 page 的地址, 在此节点前插入
31         if (base < page) {
32             list_add_before(le, &(base->page_link));
33             break;
34         } else if (list_next(le) == &free_list) {
35             // 否则在链表末尾插入
36             list_add(le, &(base->page_link));
37         }
38     }
39 }
40 }

```

- 行 \$96-125\$, 函数 \$default\_alloc\_pages\$, 实现 \$First-Fit\$ 分配算法

```

1 static struct Page *
2 default_alloc_pages(size_t n) {
3     // 所需连续空闲页数量需大于 0
4     assert(n > 0);
5     // 所需连续空闲页数量大于空闲页数量, 则找不到合适的空闲块, 返回空
6     if (n > nr_free) {
7         return NULL;
8     }
9     // 自头结点遍历链表
10    struct Page *page = NULL;
11    list_entry_t *le = &free_list;
12    while ((le = list_next(le)) != &free_list) {
13        // 找到当前链表节点对应的物理页 page
14        struct Page *p = le2page(le, page_link);
15        // 若空闲页块大小比所求大, 直接移出链表
16        if (p->property >= n) {
17            page = p;
18            break;
19        }
20    }
21    // 将移除的空闲页删去后, 更新链表中空闲页块信息, 空闲页数量减少 n
22    if (page != NULL) {
23        list_entry_t* prev = list_prev(&(page->page_link));
24        list_del(&(page->page_link));
25        if (page->property > n) {
26            struct Page *p = page + n;
27            p->property = page->property - n;
28            SetPageProperty(p);
29            list_add(prev, &(p->page_link));
30        }
31        nr_free -= n;
32        ClearPageProperty(page);
33    }
34    return page;
35 }

```

- 行 \$126-175\$, 函数 \$default\\_free\\_pages\$, 用于完成空闲页回收与空闲块合并

```
1 static void
2 default_free_pages(struct Page *base, size_t n) {
3     // 以下直至下次注释用于将被释放的页块 base 初始化为空闲页块状态, 分割其为数量为 n 的连续空闲页并插入空闲页
    链表
4     assert(n > 0);
5     struct Page *p = base;
6     for (; p != base + n; p++) {
7         assert(!PageReserved(p) && !PageProperty(p));
8         p->flags = 0;
9         set_page_ref(p, 0);
10    }
11    base->property = n;
12    SetPageProperty(base);
13    nr_free += n;
14
15    if (list_empty(&free_list)) {
16        list_add(&free_list, &(base->page_link));
17    } else {
18        list_entry_t* le = &free_list;
19        while ((le = list_next(le)) != &free_list) {
20            struct Page* page = le2page(le, page_link);
21            if (base < page) {
22                list_add_before(le, &(base->page_link));
23                break;
24            } else if (list_next(le) == &free_list) {
25                list_add(le, &(base->page_link));
26            }
27        }
28    }
29    // 自头节点遍历链表
30    list_entry_t* le = list_prev(&(base->page_link));
31    if (le != &free_list) {
32        p = le2page(le, page_link);
33        // 如果存在前后相邻的页连续, 合并为更大块
34        if (p + p->property == base) {
35            p->property += base->property;
36            ClearPageProperty(base);
37            list_del(&(base->page_link));
38            base = p;
39        }
40    }
41    // 更新 property 并删除被合并节点
42    le = list_next(&(base->page_link));
43    if (le != &free_list) {
44        p = le2page(le, page_link);
45        if (base + base->property == p) {
46            base->property += p->property;
47            ClearPageProperty(p);
48            list_del(&(p->page_link));
49        }
50    }
51 }
```

- 行 \$176-180\$, 函数 \$default\\_nr\\_free\\_pages\$, 用于返回当前空闲页总数

```
1 static size_t
2 default_nr_free_pages(void) {
3     return nr_free;
4 }
```

- 行 \$181-231\$, 函数 \$basic\\_check\$, 用于进行内存分配器的基本功能验证, 不多详述

```

1 static void
2 basic_check(void) {
3     struct Page *p0, *p1, *p2;
4     p0 = p1 = p2 = NULL;
5     assert((p0 = alloc_page()) != NULL);
6     assert((p1 = alloc_page()) != NULL);
7     assert((p2 = alloc_page()) != NULL);
8
9     assert(p0 != p1 && p0 != p2 && p1 != p2);
10    assert(page_ref(p0) == 0 && page_ref(p1) == 0 && page_ref(p2) == 0);
11
12    assert(page2pa(p0) < npage * PGSIZE);
13    assert(page2pa(p1) < npage * PGSIZE);
14    assert(page2pa(p2) < npage * PGSIZE);
15
16    list_entry_t free_list_store = free_list;
17    list_init(&free_list);
18    assert(list_empty(&free_list));
19
20    unsigned int nr_free_store = nr_free;
21    nr_free = 0;
22
23    assert(alloc_page() == NULL);
24
25    free_page(p0);
26    free_page(p1);
27    free_page(p2);
28    assert(nr_free == 3);
29
30    assert((p0 = alloc_page()) != NULL);
31    assert((p1 = alloc_page()) != NULL);
32    assert((p2 = alloc_page()) != NULL);
33
34    assert(alloc_page() == NULL);
35
36    free_page(p0);
37    assert(!list_empty(&free_list));
38
39    struct Page *p;
40    assert((p = alloc_page()) == p0);
41    assert(alloc_page() == NULL);
42
43    assert(nr_free == 0);
44    free_list = free_list_store;
45    nr_free = nr_free_store;
46
47    free_page(p);
48    free_page(p1);
49    free_page(p2);
50 }

```

- 行 232-296\$, 函数 \$default\_check\$, 同样用于进行内存分配器的基本功能验证, 不多详述

```

1 // LAB2: below code is used to check the first fit allocation algorithm (your EXERCISE 1)
2 // NOTICE: You SHOULD NOT CHANGE basic_check, default_check functions!
3 static void
4 default_check(void) {
5     int count = 0, total = 0;
6     list_entry_t *le = &free_list;
7     while ((le = list_next(le)) != &free_list) {
8         struct Page *p = le2page(le, page_link);
9         assert(PageProperty(p));
10        count ++, total += p->property;
11    }
12    assert(total == nr_free_pages());

```

```

13
14     basic_check();
15
16     struct Page *p0 = alloc_pages(5), *p1, *p2;
17     assert(p0 != NULL);
18     assert(!PageProperty(p0));
19
20     list_entry_t free_list_store = free_list;
21     list_init(&free_list);
22     assert(list_empty(&free_list));
23     assert(alloc_page() == NULL);
24
25     unsigned int nr_free_store = nr_free;
26     nr_free = 0;
27
28     free_pages(p0 + 2, 3);
29     assert(alloc_pages(4) == NULL);
30     assert(PageProperty(p0 + 2) && p0[2].property == 3);
31     assert((p1 = alloc_pages(3)) != NULL);
32     assert(alloc_page() == NULL);
33     assert(p0 + 2 == p1);
34
35     p2 = p0 + 1;
36     free_page(p0);
37     free_pages(p1, 3);
38     assert(PageProperty(p0) && p0->property == 1);
39     assert(PageProperty(p1) && p1->property == 3);
40
41     assert((p0 = alloc_page()) == p2 - 1);
42     free_page(p0);
43     assert((p0 = alloc_pages(2)) == p2 + 1);
44
45     free_pages(p0, 2);
46     free_page(p2);
47
48     assert((p0 = alloc_pages(5)) != NULL);
49     assert(alloc_page() == NULL);
50
51     assert(nr_free == 0);
52     nr_free = nr_free_store;
53
54     free_list = free_list_store;
55     free_pages(p0, 5);
56
57     le = &free_list;
58     while ((le = list_next(le)) != &free_list) {
59         struct Page *p = le2page(le, page_link);
60         count --, total -= p->property;
61     }
62     assert(count == 0);
63     assert(total == 0);
64 }

```

- 行 297-306\$, 结构体 \$pmm\_manager\$, 这是物理内存管理模块的“函数指针表”, 系统初始化时通过此结构调用相应函数

```

1  const struct pmm_manager default_pmm_manager = {
2      .name = "default_pmm_manager",
3      .init = default_init,
4      .init_memmap = default_init_memmap,
5      .alloc_pages = default_alloc_pages,
6      .free_pages = default_free_pages,
7      .nr_free_pages = default_nr_free_pages,
8      .check = default_check,
9  };

```

**总结:** 该 \$C\$ 代码用于实现基础的内存分配算法, 添加空闲块时, 按地址从小到大的顺序插入链表; 进行内存分配时, 按从空闲页链表上查找第一个大小大于所需内存的块, 分配; 回收时, 按照地址从小到大的顺序插入链表, 并且合并与之相邻且连续的空闲内存块。

## 练习 2: 实现 Best-Fit 连续物理内存分配算法 (需要编程)

以下是我们在源代码基础上修改实现的 \$Best-Fit\$ 连续物理内存分配算法, 展示如下:

```
1  #include <pmm.h>
2  #include <list.h>
3  #include <string.h>
4  #include <best_fit_pmm.h>
5  #include <stdio.h>
6
7  /* In the first fit algorithm, the allocator keeps a list of free blocks (known as the free
8   list) and,
9   on receiving a request for memory, scans along the list for the first block that is large
10  enough to
11  satisfy the request. If the chosen block is significantly larger than that requested, then
12  it is
13  usually split, and the remainder added to the list as another free block.
14  Please see Page 196~198, Section 8.2 of Yan Wei Min's chinese book "Data Structure -- C
15  programming language"
16  */
17  // LAB2 EXERCISE 1: YOUR CODE
18  // you should rewrite functions: default_init,default_init_memmap,default_alloc_pages,
19  // default_free_pages.
20  /*
21   * Details of FFMA
22   * (1) Prepare: In order to implement the First-Fit Mem Alloc (FFMA), we should manage the
23   free mem block use some list.
24   * The struct free_area_t is used for the management of free mem blocks. At
25   first you should
26   * be familiar to the struct list in list.h. struct list is a simple doubly
27   linked list implementation.
28   * You should know howto USE: list_init, list_add(list_add_after),
29   list_add_before, list_del, list_next, list_prev
30   * Another tricky method is to transform a general list struct to a special
31   struct (such as struct page):
32   * you can find some MACRO: le2page (in memlayout.h), (in future labs: le2vma
33   (in vmm.h), le2proc (in proc.h),etc.)
34   * (2) default_init: you can reuse the demo default_init fun to init the free_list and set
35   nr_free to 0.
36   * free_list is used to record the free mem blocks. nr_free is the total number
37   for free mem blocks.
38   * (3) default_init_memmap: CALL GRAPH: kern_init --> pmm_init-->page_init-->init_memmap-->
39   pmm_manager->init_memmap
40   * This fun is used to init a free block (with parameter: addr_base,
41   page_number).
42   * First you should init each page (in memlayout.h) in this free block, include:
43   * p->flags should be set bit PG_property (means this page is valid. In
44   pmm_init fun (in pmm.c),
45   * the bit PG_reserved is setted in p->flags)
46   * if this page is free and is not the first page of free block, p-
47   >property should be set to 0.
48   * if this page is free and is the first page of free block, p->property
49   should be set to total num of block.
50   * p->ref should be 0, because now p is free and no reference.
51   * We can use p->page_link to link this page to free_list, (such as:
52   list_add_before(&free_list, &(p->page_link)); )
53   * Finally, we should sum the number of free mem block: nr_free+=n
54   * (4) default_alloc_pages: search find a first free block (block size >=n) in free list and
55   reszie the free block, return the addr
56   * of malloced block.
57   * (4.1) So you should search freelist like this:
```

```

38 *          list_entry_t le = &free_list;
39 *          while((le=list_next(le)) != &free_list) {
40 *              ....
41 *              (4.1.1) In while loop, get the struct page and check the p->property
(record the num of free block) >=n?
42 *              struct Page *p = le2page(le, page_link);
43 *              if(p->property >= n){ ...
44 *              (4.1.2) If we find this p, then it' means we find a free block(block size
>=n), and the first n pages can be malloced.
45 *              Some flag bits of this page should be setted: PG_reserved =1,
PG_property =0
46 *              unlink the pages from free_list
47 *              (4.1.2.1) If (p->property >n), we should re-caluculate number of the
the rest of this free block,
48 *              (such as: le2page(le,page_link))->property = p->property - n;)
49 *              (4.1.3) re-caluculate nr_free (number of the the rest of all free block)
50 *              (4.1.4) return p
51 *              (4.2) If we can not find a free block (block size >=n), then return NULL
52 * (5) default_free_pages: relink the pages into free list, maybe merge small free blocks
into big free blocks.
53 * (5.1) according the base addr of withdrew blocks, search free list, find
the correct position
54 * (from low to high addr), and insert the pages. (may use list_next,
le2page, list_add_before)
55 * (5.2) reset the fields of pages, such as p->ref, p->flags (PageProperty)
56 * (5.3) try to merge low addr or high addr blocks. Notice: should change some
pages's p->property correctly.
57 */
58 static free_area_t free_area;
59
60 #define free_list (free_area.free_list)
61 #define nr_free (free_area.nr_free)
62
63 static void
64 best_fit_init(void) {
65     list_init(&free_list);
66     nr_free = 0;
67 }
68
69 static void
70 best_fit_init_memmap(struct Page *base, size_t n) {
71     assert(n > 0);
72     struct Page *p = base;
73     for (; p != base + n; p++) {
74         assert(PageReserved(p));
75         /*LAB2 EXERCISE 2: 2313815_段俊宇_2313485_陈展_2310591_李相儒*/
76         // 清空当前页框的标志和属性信息, 并将页框的引用计数设置为0
77         assert(PageReserved(p));
78         p->flags = p->property = 0;
79         set_page_ref(p, 0);
80     }
81     base->property = n;
82     SetPageProperty(base);
83     nr_free += n;
84     if (list_empty(&free_list)) {
85         list_add(&free_list, &(base->page_link));
86     } else {
87         list_entry_t* le = &free_list;
88         while ((le = list_next(le)) != &free_list) {
89             struct Page* page = le2page(le, page_link);
90             /*LAB2 EXERCISE 2: 2313815_段俊宇_2313485_陈展_2310591_李相儒*/
91             // 编写代码
92             // 1、当base < page时, 找到第一个大于base的页, 将base插入到它前面, 并退出循环
93             // 2、当list_next(le) == &free_list时, 若已经到达链表结尾, 将base插入到链表尾部
94             if(base < page)
95                 {

```



```

96         list_add_before(le, &(base->page_link));
97         break;
98     }
99     else if(list_next(le) == &free_list)
100     {
101         list_add(le, &(base->page_link));
102     }
103 }
104 }
105 }
106
107 static struct Page *
108 best_fit_alloc_pages(size_t n) {
109     assert(n > 0);
110     if (n > nr_free) {
111         return NULL;
112     }
113     struct Page *page = NULL;
114     list_entry_t *le = &free_list;
115     size_t best_size = nr_free + 1;
116     /*LAB2 EXERCISE 2: 2313815_段俊宇_2313485_陈展_2310591_李相儒*/
117     // 下面的代码是first-fit的部分代码, 请修改下面的代码改为best-fit
118     // 遍历空闲链表, 查找满足需求的空闲页框
119     // 如果找到满足需求的页面, 记录该页面以及当前找到的最小连续空闲页框数量
120     // 遍历空闲链表并找到最小但是可以满足n页的块
121     while ((le = list_next(le)) != &free_list) {
122         struct Page *p = le2page(le, page_link);
123         if (p->property >= n && p->property < best_size) {
124             best_size = p->property;
125             page = p;
126         }
127     }
128     // 找到最小的块并分配
129     if (page != NULL) {
130         list_entry_t* prev = list_prev(&(page->page_link));
131         list_del(&(page->page_link));
132         if (page->property > n) {
133             struct Page *p = page + n;
134             p->property = page->property - n;
135             setPageProperty(p);
136             list_add(prev, &(p->page_link));
137         }
138         nr_free -= n;
139         clearPageProperty(page);
140     }
141     return page;
142 }
143
144 static void
145 best_fit_free_pages(struct Page *base, size_t n) {
146     assert(n > 0);
147     struct Page *p = base;
148     for (; p != base + n; p++) {
149         assert(!PageReserved(p) && !PageProperty(p));
150         p->flags = 0;
151         set_page_ref(p, 0);
152     }
153     /*LAB2 EXERCISE 2: 2313815_段俊宇_2313485_陈展_2310591_李相儒*/
154     // 编写代码
155     // 具体来说就是设置当前页块的属性为释放的页块数、并将当前页块标记为已分配状态、最后增加nr_free的值
156     base->property = n;
157     setPageProperty(base);
158     nr_free += n;
159
160     if (list_empty(&free_list)) {
161         list_add(&free_list, &(base->page_link));

```

```

162     } else {
163         list_entry_t* le = &free_list;
164         while ((le = list_next(le)) != &free_list) {
165             struct Page* page = le2page(le, page_link);
166             if (base < page) {
167                 list_add_before(le, &(base->page_link));
168                 break;
169             } else if (list_next(le) == &free_list) {
170                 list_add(le, &(base->page_link));
171             }
172         }
173     }
174
175     list_entry_t* le = list_prev(&(base->page_link));
176     if (le != &free_list) {
177         p = le2page(le, page_link);
178         /*LAB2 EXERCISE 2: 2313815_段俊宇_2313485_陈展_2310591_李相儒*/
179         // 编写代码
180         // 1、判断前面的空闲页块是否与当前页块是连续的，如果是连续的，则将当前页块合并到前面的空闲页块中
181         // 2、首先更新前一个空闲页块的大小，加上当前页块的大小
182         // 3、清除当前页块的属性标记，表示不再是空闲页块
183         // 4、从链表中删除当前页块
184         // 5、将指针指向前一个空闲页块，以便继续检查合并后的连续空闲页块
185         if(p + p->property == base)
186         {
187             p->property += base->property;
188             ClearPageProperty(base);
189             list_del(&(base->page_link));
190             base = p;
191         }
192     }
193
194     le = list_next(&(base->page_link));
195     if (le != &free_list) {
196         p = le2page(le, page_link);
197         if (base + base->property == p) {
198             base->property += p->property;
199             ClearPageProperty(p);
200             list_del(&(p->page_link));
201         }
202     }
203 }
204
205 static size_t
206 best_fit_nr_free_pages(void) {
207     return nr_free;
208 }
209
210 static void
211 basic_check(void) {
212     struct Page *p0, *p1, *p2;
213     p0 = p1 = p2 = NULL;
214     assert((p0 = alloc_page()) != NULL);
215     assert((p1 = alloc_page()) != NULL);
216     assert((p2 = alloc_page()) != NULL);
217
218     assert(p0 != p1 && p0 != p2 && p1 != p2);
219     assert(page_ref(p0) == 0 && page_ref(p1) == 0 && page_ref(p2) == 0);
220
221     assert(page2pa(p0) < npage * PGSIZE);
222     assert(page2pa(p1) < npage * PGSIZE);
223     assert(page2pa(p2) < npage * PGSIZE);
224
225     list_entry_t free_list_store = free_list;
226     list_init(&free_list);
227     assert(list_empty(&free_list));

```

```

228
229     unsigned int nr_free_store = nr_free;
230     nr_free = 0;
231
232     assert(alloc_page() == NULL);
233
234     free_page(p0);
235     free_page(p1);
236     free_page(p2);
237     assert(nr_free == 3);
238
239     assert((p0 = alloc_page()) != NULL);
240     assert((p1 = alloc_page()) != NULL);
241     assert((p2 = alloc_page()) != NULL);
242
243     assert(alloc_page() == NULL);
244
245     free_page(p0);
246     assert(!list_empty(&free_list));
247
248     struct Page *p;
249     assert((p = alloc_page()) == p0);
250     assert(alloc_page() == NULL);
251
252     assert(nr_free == 0);
253     free_list = free_list_store;
254     nr_free = nr_free_store;
255
256     free_page(p);
257     free_page(p1);
258     free_page(p2);
259 }
260
261 // LAB2: below code is used to check the best fit allocation algorithm (your EXERCISE 1)
262 // NOTICE: You SHOULD NOT CHANGE basic_check, default_check functions!
263 static void
264 best_fit_check(void) {
265     int score = 0, sumscore = 6;
266     int count = 0, total = 0;
267     list_entry_t *le = &free_list;
268     while ((le = list_next(le)) != &free_list) {
269         struct Page *p = le2page(le, page_link);
270         assert(PageProperty(p));
271         count ++, total += p->property;
272     }
273     assert(total == nr_free_pages());
274
275     basic_check();
276
277     #ifdef ucore_test
278     score += 1;
279     cprintf("grading: %d / %d points\n", score, sumscore);
280     #endif
281     struct Page *p0 = alloc_pages(5), *p1, *p2;
282     assert(p0 != NULL);
283     assert(!PageProperty(p0));
284
285     #ifdef ucore_test
286     score += 1;
287     cprintf("grading: %d / %d points\n", score, sumscore);
288     #endif
289     list_entry_t free_list_store = free_list;
290     list_init(&free_list);
291     assert(list_empty(&free_list));
292     assert(alloc_page() == NULL);
293

```

```

294     #ifdef ucore_test
295     score += 1;
296     cprintf("grading: %d / %d points\n", score, sumscore);
297     #endif
298     unsigned int nr_free_store = nr_free;
299     nr_free = 0;
300
301     // * - - * -
302     free_pages(p0 + 1, 2);
303     free_pages(p0 + 4, 1);
304     assert(alloc_pages(4) == NULL);
305     assert(PageProperty(p0 + 1) && p0[1].property == 2);
306     // * - - * *
307     assert((p1 = alloc_pages(1)) != NULL);
308     assert(alloc_pages(2) != NULL);        // best fit feature
309     assert(p0 + 4 == p1);
310
311     #ifdef ucore_test
312     score += 1;
313     cprintf("grading: %d / %d points\n", score, sumscore);
314     #endif
315     p2 = p0 + 1;
316     free_pages(p0, 5);
317     assert((p0 = alloc_pages(5)) != NULL);
318     assert(alloc_page() == NULL);
319
320     #ifdef ucore_test
321     score += 1;
322     cprintf("grading: %d / %d points\n", score, sumscore);
323     #endif
324     assert(nr_free == 0);
325     nr_free = nr_free_store;
326
327     free_list = free_list_store;
328     free_pages(p0, 5);
329
330     le = &free_list;
331     while ((le = list_next(le)) != &free_list) {
332         struct Page *p = le2page(le, page_link);
333         count --, total -= p->property;
334     }
335     assert(count == 0);
336     assert(total == 0);
337     #ifdef ucore_test
338     score += 1;
339     cprintf("grading: %d / %d points\n", score, sumscore);
340     #endif
341 }
342
343 const struct pmm_manager best_fit_pmm_manager = {
344     .name = "best_fit_pmm_manager",
345     .init = best_fit_init,
346     .init_memmap = best_fit_init_memmap,
347     .alloc_pages = best_fit_alloc_pages,
348     .free_pages = best_fit_free_pages,
349     .nr_free_pages = best_fit_nr_free_pages,
350     .check = best_fit_check,
351 };

```

[illegible]

kern/mm/default\_pmm.c: 对于代码实现的 \$First-Fit\$ 算法, 我认为有两点可以改进:

- kern/mm/best\_fit\_pmm.c：对于代码实现的 \$Best-Fit\$ 算法，我认为可以对适用块的搜索策略进行优化，例如使用最小堆的方式对空闲块进行排序，这样可以减少分配时间，提升代码性能。