



```
Router0
     Physical Config CLI Attributes
        Press RETURN to get started!
       Enter configuration commands, one per line. End with CNTL/2. Router(config)#int fa0/0 Router(config-if)#ip address 10.3.0.1 255.255.255.0 Router(config-if)#no 8h
        Router(config-if) #
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up
        %LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up
       Router(config=if) #ex
Router(config=if) #ex
Router(config=if) #ex perceived—address 10.3.0.1
Router(config=if) #exp pool Telephony
Router(dhcp-config) #exemurk 10.3.0.0 285.285.285.0
Router(dhcp-config) #exemurk 10.3.0.1
Router(dhcp-config) #exemurk 10.3.0.1
Router(dhcp-config) #ex
Router(chcp-config) #ex
Router(config=if) #ex
R
         Router(config-telephony) super source-address 10.3.0.1 port 2000 Router(config-telephony) such 1 to 10
        % Invalid input detected at '^' marker
        Router(config-telephony) #auto assign 1 to 10
        Router(config-telephony) pephone-dn 1
Router(config-ephone-dn) pellNK-3-UPDOWN: Interface ephone_dsp DN 1.1, changed state to up
number 101
        Router(config-ephone-dn)#
%IPPHONE-6-REGISTER: ephone-1 IP:10.3.0.2 Socket:2 DeviceType:Phone has registered.
        ephone-dn 2
Router(config-ephone-dn)#%LINK-3-UPPOWN: Interface ephone_dsp DN 2.1, changed state to up
       Router(config-ephone-dn) #number 102
Router(config-ephone-dn) #number 102
Router(config-ephone-dn) #ephone-dn 3
Router(config-ephone-dn) #ephone-dn 3
Router(config-ephone-dn) #$LINK-3-UDDOWN: Interface ephone_dsp DN 3.1, changed state to up number 103
Router(config-ephone-dn) #ephone-dn 4
Router(config-ephone-dn) #sLINK-3-UDDOWN: Interface ephone_dsp DN 4.1, changed state to up number 103
Router(config-ephone-dn) #sLINK-3-UDDOWN: Interface ephone_dsp DN 4.1, changed state to up
        nummer 1Us
Router(config-ephone-dn) #ephone-dn 6
Router(config-ephone-dn) #$LINK-3-UPDOWN: Interface ephone_dsp DN 6.1, changed state to up
number 106
Router(config-ephone-dn) #ex
Router(config) #ephone 1
       Router(config) #ephone 1
Router(config) #ephone 2
Router(config-ephone) #mac-address 0009.7C34.3C01
ephone slot is already registered with 0001.970B.BD01
Cannot change HAC address.
Router(config-ephone) #supton 1:1
Dn already assigned.
Router(config-ephone) #ex
Router(config-ephone) #ex
Router(config) #ephone 2
Fata CatterDay #ex
Fata
       Router(config-ephone) #ex
        Router(config) #ephone 2
        Router(config-ephone) #mac-address 000C.CF09.D862
        Router(config-ephone) #type 7960
        Router(config-ephone) #button 1:2
        Router(config-ephone)#ex
        Router(config) #ephone 3
       Router(config-ephone) #mac-address 0006.2A28.7710
        Router(config-ephone) #type CIPC
        Router(config-ephone) #button 1:3
        Router(config-ephone) #ex
        Router(config) #ephone 4
        Router(config-ephone) #mac-address 0008.3BF4.8263
        Router(config-ephone) #button 1:4
        Router(config-ephone)#ex
        Router(config) #ephone 5
        Router(config-ephone) #mac-address 000B.F26C.8749
        Router(config-ephone) #type smart
        % Invalid input detected at '^' marker.
       Router(config-ephone) #type SMART
        % Invalid input detected at '^' marker.
       Router(config-ephone) #type SMAR
        % Invalid input detected at '^' marker.
        Router(config-ephone) #button 1:5
        Router(config-ephone)#ex
        Router(config) #ephone 6
        Router(config-ephone) #mac-address 0001.2F57.2348
        Router(config-ephone) #button 1:6
        Router(config-ephone) #ex
        Router (config) #
```

