

Switch0

Physical Config CLI Attributes

IOS Command Line Interface

```

%LINK-5-CHANGED: Interface FastEthernet0/3, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/3, changed state to up
%LINK-5-CHANGED: Interface FastEthernet0/4, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/4, changed state to up
%LINK-5-CHANGED: Interface FastEthernet0/5, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/5, changed state to up
%LINK-5-CHANGED: Interface FastEthernet0/6, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/6, changed state to up

Switch>en
Switch#config
Configuring from terminal, memory, or network [terminal]? ter
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#vlan 3
Switch(config-vlan)#name buhg
Switch(config-vlan)#unt range fa0/3-6

% Invalid input detected at '^' marker.

Switch(config-vlan)#int range fa0/3-6
Switch(config-if-range)#
Switch#
%SYS-5-CONFIG_I: Configured from console by console

Switch#^Z
Switch#^Z
Switch#^Z
Switch#^Z
  
```

Copy Paste

```

Switch(config)#vlan 3
Switch(config-vlan)#switchport mode access
Switch(config-vlan)^
% Invalid input detected at '^' marker.

Switch(config-vlan)#int range fa0/3-6
Switch(config-if-range)#switchport mode access
Switch(config-if-range)#switchport access vlan 3
Switch(config-if-range)#ex
Switch(config)#ex
Switch#
%SYS-5-CONFIG_I: Configured from console by console
  
```

```
Switch#show vlan
```

VLAN Name	Status	Ports
1 default	active	Fa0/1, Fa0/2, Fa0/7, Fa0/8 Fa0/9, Fa0/10, Fa0/11, Fa0/12 Fa0/13, Fa0/14, Fa0/15, Fa0/16 Fa0/17, Fa0/18, Fa0/19, Fa0/20 Fa0/21, Fa0/22, Fa0/23, Fa0/24 Gig0/1, Gig0/2
3 buhg	active	Fa0/3, Fa0/4, Fa0/5, Fa0/6
1002 fddi-default	active	
1003 token-ring-default	active	
1004 fddinet-default	active	
1005 trnet-default	active	

VLAN	Type	SAID	MTU	Parent	RingNo	BridgeNo	Stp	BrdgMode	Trans1	Trans2
1	enet	100001	1500	-	-	-	-	-	0	0
3	enet	100003	1500	-	-	-	-	-	0	0
1002	fddi	101002	1500	-	-	-	-	-	0	0
1003	tr	101003	1500	-	-	-	-	-	0	0

Enter configuration commands, one per line. End with CNTL/Z.

Switch(config)#vlan 2

Switch(config-vlan)#int programmer

^
% Invalid input detected at '^' marker.

Switch(config-vlan)#name programmer

Switch(config-vlan)#ex

Switch(config)#ex

Switch#

%SYS-5-CONFIG_I: Configured from console by console

show vlan

VLAN Name	Status	Ports
1 default	active	Fa0/7, Fa0/8, Fa0/9, Fa0/10 Fa0/11, Fa0/12, Fa0/13, Fa0/14 Fa0/15, Fa0/16, Fa0/17, Fa0/18 Fa0/19, Fa0/20, Fa0/21, Fa0/22 Fa0/23, Fa0/24, Gig0/1, Gig0/2
2 programmer	active	Fa0/1, Fa0/2, Fa0/3
3 buhg	active	Fa0/4, Fa0/5, Fa0/6
1002 fddi-default	active	
1003 token-ring-default	active	
1004 fddinet-default	active	
1005 trnet-default	active	

VLAN	Type	SAID	MTU	Parent	RingNo	BridgeNo	Stp	BrdgMode	Trans1	Trans2
1	enet	100001	1500	-	-	-	-	-	0	0
2	enet	100002	1500	-	-	-	-	-	0	0
3	enet	100003	1500	-	-	-	-	-	0	0
1002	fddi	101002	1500	-	-	-	-	-	0	0

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/4, changed state to up

```
Switch>en
Switch#conf
Configuring from terminal, memory, or network [terminal]?
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#vlan 2
Switch(config-vlan)#int range fa0/1-2
Switch(config-if-range)#switchport mode access
Switch(config-if-range)#switchport access vlan 2
Switch(config-if-range)#name programmer
```

% Invalid input detected at '^' marker.

```
Switch(config-if-range)#ex
Switch(config)#vlan 2
Switch(config-vlan)#name programmer
Switch(config-vlan)#ex
Switch(config)#vlan 3
Switch(config-vlan)#name buhg
Switch(config-vlan)#int range fa0/3-4
Switch(config-if-range)#switchport mode access
Switch(config-if-range)#switchport access vlan 3
Switch(config-if-range)#ex
Switch(config)#ex
Switch#
%SYS-5-CONFIG_I: Configured from console by console
```


Switch#show vlan

VLAN Name	Status	Ports
1 default	active	Fa0/5, Fa0/6, Fa0/7, Fa0/8 Fa0/9, Fa0/10, Fa0/11, Fa0/12 Fa0/13, Fa0/14, Fa0/15, Fa0/16

Copy

Paste

Top



```

Switch(config-if-range)#name programmer
^
% Invalid input detected at '^' marker.

Switch(config-if-range)#ex
Switch(config)#vlan 2
Switch(config-vlan)#name programmer
Switch(config-vlan)#ex
Switch(config)#vlan 3
Switch(config-vlan)#name buhg
Switch(config-vlan)#int range fa0/3-4
Switch(config-if-range)#switchport mode access
Switch(config-if-range)#switchport access vlan 3
Switch(config-if-range)#ex
Switch(config)#ex
Switch#
%SYS-5-CONFIG_I: Configured from console by console

```

```
Switch#show vlan
```

VLAN	Name	Status	Ports
1	default	active	Fa0/5, Fa0/6, Fa0/7, Fa0/8 Fa0/9, Fa0/10, Fa0/11, Fa0/12 Fa0/13, Fa0/14, Fa0/15, Fa0/16 Fa0/17, Fa0/18, Fa0/19, Fa0/20 Fa0/21, Fa0/22, Fa0/23, Fa0/24 Gig0/1, Gig0/2
2	programmer	active	Fa0/1, Fa0/2
3	buhg	active	Fa0/3, Fa0/4
1002	fddi-default	active	
1003	token-ring-default	active	
1004	fddinet-default	active	
1005	trnet-default	active	

VLAN	Type	SAID	MTU	Parent	RingNo	BridgeNo	Stp	BrdgMode	Trans1	Trans2
1	enet	1000001	1500	-	-	-	-	-	0	0
2	enet	1000002	1500	-	-	-	-	-	0	0
3	enet	1000003	1500	-	-	-	-	-	0	0
1002	fddi	101002	1500	-	-	-	-	-	0	0

--More--

