```
Switch>en
Switch#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
Switch(config)#hostname 1sw
1sw(config)#int vlan 1
1sw(config-if)#no sh

1sw(config-if)#
%LINK-5-CHANGED: Interface Vlan1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to up

1sw(config-if)#ip address 192.168.0.2 255.255.255.0
1sw(config-if)#ex
1sw(config)#
```

```
Switch>en
Switch#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
Switch(config)#hostname 2sw
2sw(config)#int vlan 1
2sw(config-if)#no sh

2sw(config-if)#
%LINK-5-CHANGED: Interface Vlan1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to up

2sw(config-if)#ip address 192.168.0.3 255.255.255.0
2sw(config-if)#ex
2sw(config)#
```

```
1sw(config-if)#
%LINK-5-CHANGED: Interface Vlan1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to up

1sw(config-if)#ip address 192.168.0.2 255.255.255.0
1sw(config-if)#ex
1sw(config)#line vty 0 4
1sw(config-line)#pass 111
1sw(config-line)#en secret 123
% Ambiguous command: "en secret 123"
1sw(config)#enable secret 123
1sw(config)#
```

```
2sw(config-if)#
%LINK-5-CHANGED: Interface Vlan1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to up

2sw(config-if)#ip address 192.168.0.3 255.255.255.0
2sw(config-if)#ex
2sw(config)#line vty 0 4
2sw(config-line)#pass 111
2sw(config-line)#enable secret 123
2sw(config)#
```

```
Cisco Packet Tracer PC Command Line 1.0
C:\>telnet 192.168.0.2
Trying 192.168.0.2 ...Open


User Access Verification

Password:
1sw>en
Password:
1sw#ex

[Connection to 192.168.0.2 closed by foreign host]
C:\>telnet 192.168.0.3
Trying 192.168.0.3 ...Open


User Access Verification

Password:
2sw>en
Password:
2sw#
```