

```

Router(config-if)#exit
Router(config)#interface FastEthernet0/1
Router(config-if)#ip address 100.10.10.1 255.0.0.0
Router(config-if)#no shutdown
Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up

Router(config-if)#exit
Router(config)#interface FastEthernet0/0
Router(config-if)#no shutdown
Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up

Router(config-if)#ex
Router(config)#access-list
Router(config)#access-list
Router(config)#access-list
Router(config)#access-list
Router(config)#access-list
Router(config)#access-list
Router(config)#access-list 1 per
Router(config)#access-list 1 permit 192.168.0.0 0.0.0.255
Router(config)#ip nat inside source list 1 int fa0/1 overload
Router(config)#int fa0/0
Router(config-if)#ip nat inside
Router(config-if)#int fa0/1
Router(config-if)#ip nat outside
Router(config-if)#

```

```

C:\>ping 100.10.10.2

Pinging 100.10.10.2 with 32 bytes of data:
Request timed out.
Reply from 100.10.10.2: bytes=32 time<1ms TTL=254
Reply from 100.10.10.2: bytes=32 time<1ms TTL=254
Reply from 100.10.10.2: bytes=32 time=6ms TTL=254

Ping statistics for 100.10.10.2:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 6ms, Average = 2ms

C:\>ping 100.10.10.2

Pinging 100.10.10.2 with 32 bytes of data:
Reply from 100.10.10.2: bytes=32 time<1ms TTL=254
Reply from 100.10.10.2: bytes=32 time<1ms TTL=254
Reply from 100.10.10.2: bytes=32 time<1ms TTL=254
Reply from 100.10.10.2: bytes=32 time<1ms TTL=254

Ping statistics for 100.10.10.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms
C:\>

```

```

Router#show ip nat translations
Pro Inside global      Inside local      Outside local      Outside global
icmp 100.10.10.1:20     192.168.0.1:20    100.10.10.2:20     100.10.10.2:20

```