

```

Physical Config CLI Attributes
IOS Command Line Interface


R860 processor: part number 0, mask 49
3 FastEthernet/IEEE 802.3 interface(s)
191K bytes of NVRAM
63498K bytes of ATA CompactFlash (Read/Write)
Cisco IOS Software, 1841 Software (C1841-ADVIPSERVICESK9-M), Version 12.4(15)T1, RELEASE
SOFTWARE (fc)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2007 by Cisco Systems, Inc.
Compiled Wed 18-Jul-07 04:52 by pt_team

--- System Configuration Dialog ---

Would you like to enter the initial configuration dialog? [yes/no]:

Press RETURN to get started!

Router>enable
Router#
Router#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#interface FastEthernet0/0
Router(config-if)#ip address 192.168.0.100 255.255.255.0
Router(config-if)#
Router(config-if)#exit
Router(config)#interface FastEthernet0/1
Router(config-if)#ip address 30.30.30.100 255.0.0.0
Router(config-if)#access-list 1 permit any
Router(config)#ip nat inside source list 1 interface fa0/1 overload
Router(config)#int fa0/1
Router(config-if)#ip nat inside
Router(config-if)#ex
Router(config)#int fa0/1
Router(config-if)#ip nat outside
Router(config-if)#
  
```



```

Physical Config Desktop Programming Attributes
Command Prompt


Cisco Packet Tracer PC Command Line 1.0
C:\>ping 30.30.30.1

Pinging 30.30.30.1 with 32 bytes of data:

Request timed out.
Reply from 30.30.30.1: bytes=32 time<1ms TTL=127
Reply from 30.30.30.1: bytes=32 time<1ms TTL=127
Reply from 30.30.30.1: bytes=32 time<1ms TTL=127

Ping statistics for 30.30.30.1:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>
  
```



```

% Invalid input detected at '^' marker.

Router(config-if)#show ip nat translations
^
% Invalid input detected at '^' marker.

Router(config-if)#ex
Router(config)#ex
Router#
%SYS-5-CONFIG_I: Configured from console by console
conf t
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#show ip nat translations
^
% Invalid input detected at '^' marker.

Router(config)#ex
Router#
%SYS-5-CONFIG_I: Configured from console by console
show ip nat translations
Router#show ip nat translations
Router#
Router#
Router#show ip nat translations
Router#
  
```