


FUNCTIONS AS OBJECTS, DICTIONARIES

FUNCTIONS AS OBJECTS

- functions are **first class objects**:
 - have types
 - can be elements of data structures like lists
 - can appear in expressions
 - as part of an assignment statement
 - as an argument to a function!!
 - particularly useful to use functions as arguments when coupled with lists
 - aka **higher order programming**
- 

EXAMPLE

→ function
function as parameter

```
def applyToEach(L, f):  
    """assumes L is a list, f a function  
        mutates L by replacing each element,  
        e, of L by f(e)"""  
    for i in range(len(L)):  
        L[i] = f(L[i])
```

EXAMPLE

```
def applyToEach(L, f):
```

```
    for i in range(len(L)):
```

```
        L[i] = f(L[i])
```



L = [1, -2, 3.4]

```
applyToEach(L, abs)
```

```
applyToEach(L, int)
```

```
applyToEach(L, fact)
```

```
applyToEach(L, fib)
```

EXAMPLE

```
def applyToEach(L, f):
```

```
    for i in range(len(L)):
```

```
        L[i] = f(L[i])
```

L = [1, -2, 3.4]

```
applyToEach(L, abs)
```



[1, 2, 3.4]

```
applyToEach(L, int)
```

```
applyToEach(L, fact)
```

```
applyToEach(L, fib)
```

EXAMPLE

```
def applyToEach(L, f):
```

```
    for i in range(len(L)):
```

```
        L[i] = f(L[i])
```

```
    L = [1, -2, 3.4]
```

```
applyToEach(L, abs)
```

```
[1, 2, 3.4]
```

```
applyToEach(L, int)
```

```
[1, 2, 3]
```



```
applyToEach(L, fact)
```

```
applyToEach(L, fib)
```

EXAMPLE

```
def applyToEach(L, f):  
    for i in range(len(L)):  
        L[i] = f(L[i])
```

L = [1, -2, 3.4]

```
applyToEach(L, abs)
```

[1, 2, 3.4]

```
applyToEach(L, int)
```

[1, 2, 3]

```
applyToEach(L, fact)
```

[1, 2, 6]

```
applyToEach(L, fib)
```



EXAMPLE

```
def applyToEach(L, f):  
    for i in range(len(L)):  
        L[i] = f(L[i])
```

L = [1, -2, 3.4]

```
applyToEach(L, abs)
```

[1, 2, 3.4]

```
applyToEach(L, int)
```

[1, 2, 3]

```
applyToEach(L, fact)
```

[1, 2, 6]

```
applyToEach(L, fib)
```

[1, 2, 13]



LISTS OF FUNCTIONS

→ pass in a list of functions.

```
def applyFuns (L, x) :  
    for f in L:  
        print (f (x))  
→ function name with no params.  
applyFuns ([abs, int, fact, fib], 4)
```

4

4

24

5

GENERALIZATION OF HOPS

- Python provides a general purpose HOP, `map`

■ simple form – a unary function and a collection of suitable arguments

```
map(abs, [1, -2, 3, -4])
```

■ produces an 'iterable', so need to walk down it

```
for elt in map(abs, [1, -2, 3, -4]):  
    print(elt)
```

```
[1, 2, 3, 4]
```

remember
range?

■ general form – an n-ary function and n collections of arguments

```
◦ L1 = [1, 28, 36]  
◦ L2 = [2, 57, 9]
```

```
for elt in map(min, L1, L2):  
    print(elt)
```

```
[1, 28, 9]
```

STRINGS, TUPLES, RANGES, LISTS

■ Common operations

- `seq[i]` → `i`th element of sequence
- `len(seq)` → length of sequence
- `seq1 + seq2` → concatenation of sequences (not range)
- `n*seq` → sequence that repeats `seq` `n` times (not range)
- `seq[start:end]` → slice of sequence
- `e in seq` → `True` if `e` contained in sequence
- `e not in seq` → `True` if `e` contained in sequence
- `for e in seq` → iterates over elements of sequence

PROPERTIES


Type	Type of elements	Examples of literals	Mutable
str	characters	' ', 'a', 'abc'	No
tuple	any type	(), (3,), ('abc' , 4)	No
range	integers	range(10) , range(1,10,2)	No
list	any type	[] , [3] , ['abc' , 4]	Yes

DICTIONARIES

HOW TO STORE STUDENT INFO

- so far, can store using separate lists for every info

```
names = ['Ana', 'John', 'Denise', 'Katy']  
grade = ['B', 'A+', 'A', 'A']  
course = [2.00, 6.0001, 20.002, 9.01]
```



- a **separate list** for each item
- each list must have the **same length**
- info stored across lists at **same index**, each index refers to info for a different person

HOW TO UPDATE/RETRIEVE STUDENT INFO

```
def get_grade(student, name_list, grade_list, course_list):  
    i = name_list.index(student)  
    grade = grade_list[i]  
    course = course_list[i]  
    return (course, grade)
```

- **messy** if have a lot of different info to keep track of
- must maintain **many lists** and pass them as arguments
- must **always index** using integers
- must remember to change multiple lists

A BETTER AND CLEANER WAY – A DICTIONARY

- nice to **index item of interest directly** (not always int)
- nice to use **one data structure**, no separate lists

A list

0	Elem 1
1	Elem 2
2	Elem 3
3	Elem 4
...	...

index

element

A dictionary

Key 1	Val 1
Key 2	Val 2
Key 3	Val 3
Key 4	Val 4
...	...

custom
index by
label

element

A PYTHON DICTIONARY

- store pairs of data
 - key
 - value

'Ana '	'B '
'Denise '	'A '
'John '	'A+ '
'Katy '	'A '

custom
index by
label

element

```
my_dict = {}
```

empty
dictionary

```
grades = {'Ana': 'B', 'John': 'A+', 'Denise': 'A', 'Katy': 'A'}
```

key1 val1 key2 val2 key3 val3 key4 val4

DICTIONARY LOOKUP

- similar to indexing into a list
- **looks up the key**
- **returns the value** associated with the key
- if key isn't found, get an error

'Ana '	'B '
'Denise '	'A '
'John '	'A+ '
'Katy '	'A '

```
grades = {'Ana': 'B', 'John': 'A+', 'Denise': 'A', 'Katy': 'A'}
```

```
grades['John'] → evaluates to 'A+'
```

```
grades['Sylvan'] → gives a KeyError
```

DICTIONARY OPERATIONS

'Ana'	'B'
'Denise'	'A'
'John'	'A+'
'Katy'	'A'
'Sylvan'	'A'

```
grades = {'Ana':'B', 'John':'A+', 'Denise':'A', 'Katy':'A'}
```

- **add** an entry

```
grades['Sylvan'] = 'A'
```

- **test** if key in dictionary

```
'John' in grades    → returns True  
'Daniel' in grades → returns False
```

- **delete** entry

```
del (grades['Ana'])
```

DICTIONARY OPERATIONS

'Ana '	'B '
'Denise '	'A '
'John '	'A+ '
'Katy '	'A '

```
grades = { 'Ana': 'B', 'John': 'A+', 'Denise': 'A', 'Katy': 'A' }
```

- get an **iterable that acts like a tuple of all keys** *no guaranteed order*

```
grades.keys() → returns ['Denise', 'Katy', 'John', 'Ana']
```

- get an **iterable that acts like a tuple of all values** *no guaranteed order*

```
grades.values() → returns ['A', 'A', 'A+', 'B']
```

DICTIONARY KEYS and VALUES

- values
 - any type (**immutable and mutable**)
 - can be **duplicates**
 - dictionary values can be lists, even other dictionaries!
- keys
 - must be **unique**
 - **immutable** type (`int, float, string, tuple, bool`)
 - actually need an object that is **hashable**, but think of as immutable as all immutable types are hashable
 - careful with `float` type as a key
- **no order** to keys or values!

```
d = {4:{1:0}, (1,3):"twelve", 'const':[3.14,2.7,8.44]}
```

List VS dict

- **ordered** sequence of elements
- look up elements by an integer index
- indices have an **order**
- index is an **integer**
- **matches** “keys” to “values”
- look up one item by another item
- **no order** is guaranteed
- key can be any **immutable** type

EXAMPLE: 3 FUNCTIONS TO ANALYZE SONG LYRICS

- 1) create a **frequency dictionary** mapping `str: int`
- 2) find **word that occurs the most** and how many times
 - use a list, in case there is more than one word
 - return a tuple (`list, int`) for (`words_list, highest_freq`)
- 3) find the **words that occur at least X times**
 - let user choose “at least X times”, so allow as parameters
 - return a list of tuples, each tuple is a (`list, int`) containing the list of words ordered by their frequency
 - IDEA: From song dictionary, find most frequent word. Delete most common word. Repeat. It works because you are mutating the song dictionary.

CREATING A DICTIONARY

```
def lyrics_to_frequencies(lyrics):  
    myDict = {}  
    for word in lyrics:  
        if word in myDict:  
            myDict[word] += 1  
        else:  
            myDict[word] = 1  
    return myDict
```

can iterate over list
can iterate over keys
in dictionary
update value
associated with key

USING THE DICTIONARY

```
def most_common_words(freqs):  
    values = freqs.values()  
    best = max(values)  
    words = []  
    for k in freqs:  
        if freqs[k] == best:  
            words.append(k)  
    return (words, best)
```

*this is an iterable, so can
apply built-in function*

*can iterate over keys
in dictionary*

LEVERAGING DICTIONARY PROPERTIES

```
def words_often(freqs, minTimes):  
    result = []  
    done = False  
    while not done:  
        temp = most_common_words(freqs)  
        if temp[1] >= minTimes:  
            result.append(temp)  
            for w in temp[0]:  
                del(freqs[w])  
        else:  
            done = True  
    return result  
  
print(words_often(beatles, 5))
```

*can directly mutate
dictionary; makes it
easier to iterate*


FIBONACCI RECURSIVE CODE

```
def fib(n):  
    if n == 1:  
        return 1  
    elif n == 2:  
        return 2  
    else:  
        return fib(n-1) + fib(n-2)
```

- two base cases
- calls itself twice
- this code is inefficient

INEFFICIENT FIBONACCI

$$\text{fib}(n) = \text{fib}(n-1) + \text{fib}(n-2)$$



- **recalculating** the same values many times!
- could keep **track** of already calculated values

FIBONACCI WITH A DICTIONARY

```
def fib_efficient(n, d):  
    if n in d:  
        return d[n]  
    else:  
        ans = fib_efficient(n-1, d) + fib_efficient(n-2, d)  
        d[n] = ans  
        return ans
```

Method sometimes
called "
memoization"

```
d = {1:1, 2:2} base case.  
print(fib_efficient(6, d))
```

- do a **lookup first** in case already calculated the value
- **modify dictionary** as progress through function calls

GLOBAL VARIABLES

- can be dangerous to use
 - breaks the scoping of variables by function call
 - allows for side effects of changing variable values in ways that affect other computation
- but can be convenient when want to keep track of information inside a function
- example – measuring how often `fib` and `fib_efficient` are called

TRACKING EFFICIENCY

```
def fib(n):  
    global numFibCalls  
    numFibCalls += 1  
    if n == 1:  
        return 1  
    elif n == 2:  
        return 2  
    else:  
        return fib(n-1) + fib(n-2)
```

```
def fibef(n, d):  
    global numFibCalls  
    numFibCalls += 1  
    if n in d:  
        return d[n]  
    else:  
        ans = fibef(n-1, d) + fibef(n-2, d)  
        d[n] = ans  
    return ans
```

accessible from outside scope of function

TRACKING EFFICIENCY

```
numFibCalls = 0

print(fib(12))
print('function calls', numFibCalls)

numFibCalls = 0

d = {1:1, 2:2}
print(fib_efficient(12, d))
print('function calls', numFibCalls)
```