Task Column Descriptions

This document is meant to outline the columns of each task's raw behavioral data. The first section includes a description of all the common columns found within every task's raw behavioral file, while the following sections describe the columns specifically associated with bespoke tasks.

Common Task Columns

Rt: response time, if there is a key press recorded. Otherwise, recorded as -1
Key_press: key code for key press recorded. If none, recorded as -1
Trial_type: type of javascript object
Trial_index: index
Time_elapsed: time elapsed from beginning of experiment in ms. time elapsed is saved at the end of javascript item, so in order to calculate onset time from time_elapsed, you have to subtract timing_post_trial and block_duration from time_elapsed
Subject: subject id
Text: format and content of text on screen if there were any
Block_duration: length of javascript object in ms
Timing_post_trial: length of time after current object in ms
Trial_id: type of item. “fmri_scanner_wait” was the screen during the prep scan. “fmri_trigger_wait” received a sync pulse from the scanner (T, key code = 84). Task began after receiving sync pulses for dummy scans. For onset to match the timing of images saved as a Nifti file, calculate timing starting from “fmri_buffer”.
Stimulus: format and content of stimulus on screen if there were any
Possible_responses: key codes for possible responses
Stim_duration: duration of stimulus showing on screen in ms
Exp_stage: experiment stage, practice or main task (test)
Exp_id: experiment id

ANT Data Columns

Correct: TRUE if response was correct, FALSE if response was incorrect
Correct_response: javascript key code associated with the correct response
Feedback_duration: length of feedback on screen in ms
Flanker_middle_direction: direction of arrow key in middle (critical arrow)
Flanker_type: congruent if flanker arrows are same as arrow in middle, incongruent if flanker arrows are opposite of arrow in middle
Flanker_location: location of flanker stimuli showing on screen

Cue: double if cue was uninformative, spatial if cue was informative of where flanker stimuli will show on screen
Trial_num: trial count of main task

CCTHot

Which_round: round number
Num_click_in_round: count for action taken in trial
Num_cards: total number of cards in deck
Num_loss_cards: total number of loss cards in deck
Gain_amount: how much points you gain for each gain card you flip
Loss_amount: how much points you lose for flipping a loss card
Round_points: how much points you earned for entire round
Clicked_on_loss_card: True if clicked on a loss card at given choice action phase, False if not
Reward: list consisting of 3 randomly chosen rewards taken from the Ruond_points column

Discountfix

Small_amount: amount to be received sooner, fixed at $20
Large_amount: amount to be received later in dollars
Later_delay: amount of days until larger amount is received
Choice: which case participant chose
Bonus: error in code did not provide actual value

DPX

Trial_num: trial count of main task
Correct_response: javascript key code associated with the correct response
Correct: TRUE if response was correct, FALSE if response was incorrect

motorSelectiveStop

Correct: TRUE if response was correct, FALSE if response was incorrect
Correct_response: javascript key code associated with the correct response
Feedback_duration: length of feedback on screen in ms
SS_stimulus: format of stop signal stimulus
SS_delay: stop signal delay in ms
SS_trial_type: stop signal trial type

SS_duration: length of stop signal on screen in ms
Condition: trial condition. Go means no stop signal was shown, ignore means stop signal was shown for non-critical shape, stop means stop signal was shown for critical shape
Stop_response: key code for critical shape response

stopSignal

Correct: TRUE if response was correct, FALSE if response was incorrect
Correct_response: javascript key code associated with the correct response
Feedback_duration: length of feedback on screen in ms
SS_stimulus: format of stop signal stimulus
SS_delay: stop signal delay in ms
SS_trial_type: stop signal trial type
SS_duration: length of stop signal on screen in ms

Stroop

Correct: TRUE if response was correct, FALSE if response was incorrect
Correct_response: javascript key code associated with the correct response
Feedback_duration: length of feedback on screen in ms
Condition: condition type of trial
Stim_color: color of word
Stim_word: word itself
Trial_num: trial count of main task

Survey Medley

Survey: which survey the specific question belongs to. "impulsive_venture": "subset of Impulsiveness-Venturesomeness (Eysenck, Pearson, Easting, & Allsopp, 1985)",
"grit": "Grit Scale (Duckworth et al., 2009)",
"upps": "subset of UPPS+P impulsivity (Lynam, Smith, Whiteside, & Cyders, 2006)",
"brief": "Brief Self-Control Scale (Roth, Isquith, & Gioia, 2005)",
"future_time": "Carstensen Future Time Perspective (Carstensen & Lang, 1996)"
Item_coding: whether question was reverse coded or not
Item_text: survey question text
Options: options given to participant and format
Response: participant’s response

Coded_response: participant's response with reverse and forward coding taken into account. Lower values generally indicate a more negative response, higher values generally indicate a more positive response.

twoByTwo

Cue: which cue was presented to indicate the task
Stim_color: color of stimulus
Stim_number: stimulus shown on screen
Task: which task was to be performed
Task_switch: whether task was switched from previous trial
Cue_switch: whether cue was switched from previous trial
Trial_num: trial count of main task
Correct: TRUE if response was correct, FALSE if response was incorrect
Correct_response: javascript key code associated with the correct response
Feedback_duration: length of feedback on screen in ms

WATT3

Current_position: current state of balls on peg. Each three numbers sequentially represent 3 possible positions on each peg. 0 = empty position / 1,2,3 = label for specific balls
Num_moves: count of number of moves made in trial
Min_moves: minimum number of moves necessary to complete the task. Fixed to 3
Start_state: start state of balls on peg. Each three numbers sequentially represent 3 possible positions on each peg. 0 = empty position / 1,2,3 = label for specific balls.
Goal_state: goal state of balls on peg. Each three numbers sequentially represent 3 possible positions on each peg. 0 = empty position / 1,2,3 = label for specific balls.
Condition: "UA_with_intermediate": "unambiguous trial that requires intermediate moves", "UA_without_intermediate": "unambiguous trial that does not require intermediate moves", "PA_with_intermediate": "partially ambiguous trial that requires intermediate moves", "PA_without_intermediate": "partially ambiguous trial that does not require intermediate moves"
Problem_time: time spent in completing trial in ms
Correct: TRUE if response was correct, FALSE if response was incorrect