

Smooth tensor estimation with unknown permutation


Chanwoo Lee¹ and Miaoyan Wang²

Department of Statistics, University of Wisconsin - Madison

NeurIPS workshop on Quantum Tensor Networks in Machine Learning

¹chanwoo.lee@wisc.edu ²miaoyan.wang@wisc.edu

Main problems: the permuted signal plus noise model



The diagram illustrates the permuted signal plus noise model. It shows three 3D tensors, each with axes labeled 10, 20, 30, and 40. The first tensor, labeled \mathcal{Y} and "Observed tensor", is a noisy cube with a red and blue pattern. The second tensor, labeled Θ and "Signal tensor", is a smooth cube with a red-to-blue gradient. The third tensor, labeled \mathcal{E} and "Noise tensor", is a plain gray cube. The equation is represented as $\mathcal{Y} = \Theta \circ \pi + \mathcal{E}$, where \circ is the element-wise product operator and π is the permutation tensor.

$$\underbrace{\mathcal{Y}}_{\text{Observed tensor}} = \underbrace{\Theta}_{\text{Signal tensor}} \circ \underbrace{\pi}_{\text{Permutation}} + \underbrace{\mathcal{E}}_{\text{Noise tensor}}$$

- Question: How to estimate the permuted signal tensor $\Theta \circ \pi$?

Main problems: the permuted signal plus noise model

$\underbrace{\mathcal{Y}}_{\text{Observed tensor}} = \underbrace{\Theta}_{\text{Signal tensor}} \circ \underbrace{\pi}_{\text{Permutation}} + \underbrace{\mathcal{E}}_{\text{Noise tensor}}$

- Question: How to estimate **the permuted signal tensor** $\Theta \circ \pi$?
- We assume that there exists a **multivariate function** $f: [0, 1]^m \rightarrow \mathbb{R}$ underlying the signal tensor, such that

$$\Theta_{i_1, \dots, i_m} = f\left(\frac{i_1}{d}, \dots, \frac{i_m}{d}\right), \text{ for all } i_1, \dots, i_m \in [d].$$

Our contribution

	Pananjady and Samworth (2020)	Balasubramanian (2021)	Li et al. (2019)	Ours*
model structure	monotonic	Lipschitz	Lipschitz	α -smoothness
minimax lower bound	\checkmark	\times	\times	\checkmark
error rate for order-3 tensors	$d^{-1/3}$	$d^{-6/5}$	d^{-1}	d^{-2}
polynomial algorithm	\checkmark	\times	\checkmark	\checkmark

We list here only the result for infinitely smooth order-3 tensors.


- We develop a general permuted model for an arbitrary smoothness and order of tensors with **optimal rate**.

Our contribution

	Pananjady and Samworth (2020)	Balasubramanian (2021)	Li et al. (2019)	Ours*
model structure	monotonic	Lipschitz	Lipschitz	α -smoothness
minimax lower bound	$\sqrt{}$	\times	\times	$\sqrt{}$
error rate for order-3 tensors	$d^{-1/3}$	$d^{-6/5}$	d^{-1}	d^{-2}
polynomial algorithm	$\sqrt{}$	\times	$\sqrt{}$	$\sqrt{}$


We list here only the result for infinitely smooth order-3 tensors.

- We develop a general permuted model for an arbitrary smoothness and order of tensors with **optimal rate**.




- We discover a **phase transition phenomenon** with respect to the smoothness threshold needed for optimal tensor recovery.
- We provide an efficient **polynomial-time Borda count algorithm** that provably achieves optimal rate.

Block-wise polynomial approximation



Block-wise polynomial approximation



- We propose the **least square estimation**,

$$(\hat{\Theta}^{\text{LSE}}, \hat{\pi}^{\text{LSE}}) = \arg \min_{\Theta \in \mathcal{B}(k, \ell), \pi \in [d] \rightarrow [d]} \|\mathcal{Y} - \Theta \circ \pi\|_F \quad \text{where,}$$

$$\mathcal{B}(k, \ell) = \left\{ \mathcal{B} \in (\mathbb{R}^d)^{\otimes m} : \mathcal{B}(\omega) = \sum_{\Delta \in \mathcal{E}_k} \text{Poly}_{\ell, \Delta}(\omega) \mathbb{1}\{\omega \in \Delta\} \text{ for all } \omega \in [d]^m \right\}.$$

Least-squares estimation error and its optimality

For two tensor Θ_1, Θ_2 , define $\text{MSE}(\Theta_1, \Theta_2) = \frac{1}{d^m} \|\Theta_1 - \Theta_2\|_F^2$.

Least-squares estimation error (L. and Wang 2021)

Suppose that the generating function f is α -Hölder smooth. For optimally chosen polynomial degree ℓ^* and the number of groups k^* ,

$$\text{MSE}(\hat{\Theta}^{\text{LSE}} \circ \hat{\pi}^{\text{LSE}}, \Theta \circ \pi) \lesssim \begin{cases} d^{-\frac{2m\alpha}{m+2\alpha}} & \text{when } \alpha < \frac{m(m-1)}{2}, \\ \frac{\log d}{d^{m-1}} & \text{when } \alpha \geq \frac{m(m-1)}{2}. \end{cases}$$

$$\ell^* = \min(\lceil \alpha \rceil, m(m-1)/2) - 1 \text{ and } k^* = \lceil d^{m/(m+2\min(\alpha, \ell^*+1))} \rceil$$

- The error consists of the **nonparametric error** and **permutation error**.
- The dominating error depends on **the smoothness and order of tensor**.
- We show that the least-square estimation is **minimax rate-optimal**.

Least-squares estimation error and its optimality

For two tensor Θ_1, Θ_2 , define $\text{MSE}(\Theta_1, \Theta_2) = \frac{1}{d^m} \|\Theta_1 - \Theta_2\|_F^2$.

Least-squares estimation error (L. and Wang 2021)

Suppose that the generating function f is α -Hölder smooth. For optimally chosen polynomial degree ℓ^* and the number of groups k^* ,

$$\text{MSE}(\hat{\Theta}^{\text{LSE}} \circ \hat{\pi}^{\text{LSE}}, \Theta \circ \pi) \lesssim \begin{cases} d^{-\frac{2m\alpha}{m+2\alpha}} & \text{when } \alpha < \frac{m(m-1)}{2}, \\ \frac{\log d}{d^{m-1}} & \text{when } \alpha \geq \frac{m(m-1)}{2}. \end{cases}$$

$$\ell^* = \min(\lceil \alpha \rceil, m(m-1)/2) - 1 \text{ and } k^* = \lceil d^{m/(m+2\min(\alpha, \ell^*+1))} \rceil$$

- The error consists of the **nonparametric error** and **permutation error**.
- The dominating error depends on **the smoothness and order of tensor**.
- We show that the least-square estimation is **minimax rate-optimal**.

However, the algorithm for the least square estimation is **computationally intractable**.

Polynomial-time algorithm: Borda count estimation

1. **Sorting stage:** Estimate a permutation $\hat{\pi}^{\text{BC}}$ such that the permuted score function $\tau \circ (\hat{\pi}^{\text{BC}})^{-1}$ is monotonically increasing, where

$$\tau(i) = \frac{1}{d^{m-1}} \sum_{(i_2, \dots, i_m) \in [d]^{m-1}} \mathcal{Y}(i, i_2, \dots, i_m).$$

2. **Polynomial approximation stage:** Estimate the degree- ℓ polynomial block tensor

$$\hat{\Theta}^{\text{BC}} = \arg \min_{\Theta \in \mathcal{B}(k, \ell)} \|\mathcal{Y} \circ (\hat{\pi}^{\text{BC}})^{-1} - \Theta\|_F.$$


Polynomial-time algorithm: Borda count estimation

1. **Sorting stage:** Estimate a permutation $\hat{\pi}^{\text{BC}}$ such that the permuted score function $\tau \circ (\hat{\pi}^{\text{BC}})^{-1}$ is monotonically increasing, where


$$\tau(i) = \frac{1}{d^{m-1}} \sum_{(i_2, \dots, i_m) \in [d]^{m-1}} \mathcal{Y}(i, i_2, \dots, i_m).$$

2. **Polynomial approximation stage:** Estimate the degree- ℓ polynomial block tensor


$$\hat{\Theta}^{\text{BC}} = \arg \min_{\Theta \in \mathcal{B}(k, \ell)} \|\mathcal{Y} \circ (\hat{\pi}^{\text{BC}})^{-1} - \Theta\|_F.$$




Observation



Sorted observation




Polynomial approximation




True signal

Borda count algorithm provably achieves **optimal rate** under **monotonicity assumptions**


Simulation results




Observation




Model 1




Borda Count
(5.4×10^{-4})




Spectral
(3.1×10^{-3})




LSE
(5.3×10^{-3})




Observation




Model 3




Borda Count
(3.6×10^{-4})




Spectral
(6.5×10^{-3})




LSE
(1.1×10^{-3})




Observation




Model 5



Borda Count
(2.5×10^{-3})



Spectral
(7.5×10^{-3})



LSE
(3.6×10^{-3})

Thank you!

References I

- Balasubramanian, K. (2021). Nonparametric modeling of higher-order interactions via hypergraphons. *arXiv preprint arXiv:2105.08678*.
- Li, Y., Shah, D., Song, D., and Yu, C. L. (2019). Nearest neighbors for matrix estimation interpreted as blind regression for latent variable model. *IEEE Transactions on Information Theory*, 66(3):1760–1784.
- Pananjady, A. and Samworth, R. J. (2020). Isotonic regression with unknown permutations: Statistics, computation, and adaptation. *arXiv preprint arXiv:2009.02609*.