

Package ‘ASSIST’

May 5, 2021

Type Package

Title Nonparametric Trace Regression via Sign Series Representation

Version 0.1.0

Author Chanwoo Lee <chanwoo.lee@wisc.edu>, Lexin Li <lexinli@berkeley.edu>, Hao Helen Zhang <hzhang@math.arizona.edu>, Miaoyan Wang <miaoyan.wang@wisc.edu>

Maintainer Chanwoo Lee <chanwoo.lee@wisc.edu>

Description Efficient algorithm for the Aggregation of Structured Sign Series for Trace regression (ASSIST). The algorithm employs the alternating direction method of multipliers (ADMM) to solve the weighted classification problem. The detailed algorithm description can be found in Lee, C., Li, L., Zhang, H., and Wang, M. (2021). Nonparametric Trace Regression via Sign Series Representation. <arXiv:2105.01783>.

URL <https://arxiv.org/abs/2105.01783>

Imports quadprog,
Matrix,
glmnet,
keras

License GPL(>=2)

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

R topics documented:

ADMM	2
ASSIST	3
CNN	5
Lasso	5
Index	6

ADMM

*ADMM algorithm for weighted classification***Description**

Implement an ADMM algorithm to optimize the weighed classification loss.

Usage

```
ADMM(X,ybar,Weight,Covariate=NULL,r,srow,scol,lambda=0,rho.ini=1)
```

Arguments

X	A list of predictor matrices.
ybar	A vector of shifted response variables.
Weight	Classification weight.
Covariate	Additional covariate including intercept. Covariate = NULL does not include covariate.
r	A rank of coefficient matrix to be fitted.
srow	The number of zero rows in coefficient matrix.
scol	The number of zero columns in coefficient matrix.
lambda	Lagrangian multiplier.
rho.ini	Initial step size.

Value

The returned object is a list of components.

intercept - The estimated intercept of the classifier.

P_row - The left-singular vectors of the coefficient matrix.

P_col - The right-singular vectors of the coefficient matrix.

obj - Trajectory of weighted classification loss values over iterations.

iter - The number of iterations.

fitted - A vector of fitted values from estimated classifier.

B - The estimated coefficient matrix of the classifier.

References

Lee, C., Li, L., Zhang, H., and Wang, M. (2021). Nonparametric Trace Regression via Sign Series Representation. *arXiv preprint arXiv:2105.01783*.

Examples

```

### Generate predictor matrices #####
X = list()
for(i in 1:10){
  X[[i]] = matrix(runif(4,-1,1),nrow = 2,ncol = 2)
}

#### Generate coefficient matrix #####
B = runif(2,-1,1)%*%t(runif(2,-1,1))

#### Generate response variables #####
y = NULL
for(i in 1:10){
  y = c(y,sign(sum(X[[i]]*B)+rnorm(1,sd = 0.1)))
}

#### classification with equal weight #####
res = ADMM(X,y,rep(1,10),r = 1,srow = 0,scol = 0)
### Misclassification rate on training data #####
mean(sign(res$fitted)-y)

```

ASSIST

*Aggregation of structured sign series for trace regression (ASSIST)***Description**

Implement ASSIST based on ADMM algorithm.

Usage

```
ASSIST(X,y,X_new=NULL,r,sparse_r,sparse_c,H=10,lambda=0,rho.ini=0.1,min,max)
```

Arguments

X	A list of predictor matrices.
y	A vector of response variables.
X_new	A list of new matrices at which predictions are to made. X_new = NULL is regarded as X_new = X.
r	A rank of sign representable function to be fitted.
sparse_r	The number of zero rows in coefficient matrix.
sparse_c	The number of zero columns in coefficient matrix.
H	Resoution parameter.
lambda	Lagrangian multiplier.
rho.ini	Initial step size.
min	Minimum value of the response variables
max	Maximum value of the response variables.

Value

The returned object is a list of components.

`B_est` - An array of which slices are the estimated coefficient matrix at each level.

`fitted` - The estimated responses at the predictor `Xnew`.

`sign_fitted` - A matrix of which rows are the sign of responses shifted by each level.

References

Lee, C., Li, L., Zhang, H., and Wang, M. (2021). Nonparametric Trace Regression via Sign Series Representation. *arXiv preprint arXiv:2105.01783*.

Examples

```
##### Generate predictor matrices #####
X = list()
for(i in 1:10){
  X[[i]] = matrix(runif(4,-1,1),nrow = 2,ncol = 2)
}

##### Generate coefficient matrix #####
B = runif(2,-1,1)%*%t(runif(2,-1,1))

##### Generate response variables #####
y = NULL;signal = NULL
for(i in 1:10){
  signal = c(signal,sum(X[[i]]*B))
  y = c(y,sum(X[[i]]*B)+rnorm(1,sd = 0.1))
}

##### Run ASSIST #####
res =ASSIST(X,y,r = 1,sparse_r = 0,sparse_c = 0,min = min(y),max = max(y))
mean(abs(res$fitted-signal))

##### Generate new matrices at which predictions are to made #
X_new = list()
for(i in 1:10){
  X_new[[i]] = matrix(runif(4,-1,1),nrow = 2,ncol = 2)
}

##### Generate response variables from X_new #####
y_new = NULL
for(i in 1:10){
  y_new = c(y_new,sum(X_new[[i]]*B))
}

##### Run ASSIST #####
res =ASSIST(X,y,X_new,r = 1,sparse_r = 0,sparse_c = 0,min = min(y),max = max(y))
mean(abs(res$fitted-y_new))
```

CNN

*Convolutional Neural Network (CNN) with two hidden layers***Description**

Implement a CNN with two hidden layers and ReLu activation.

Usage

```
CNN(X,y,X_new,plot.figure = FALSE)
```

Arguments

X	A list of predictor matrices.
y	Binary response variable.
X_new	A list of new matrices at which predictions are to made.
plot.figure	Option for plotting trajectory of accuracy over epochs.

Value

The returned object is a list of components.

prob - The estimated probabilities of the binary response at the predictors Xnew.

class - The estimated binary response at the predictors Xnew.

history - The trajectory of accuracy over epochs.

acc - The classification accuracy on test data.

Lasso

*Logistic probability model via penalized maximum likelihood***Description**

Fit a logistic probability model based on Lasso penalty

Usage

```
Lasso(xvec,y,xnew,lambda)
```

Arguments

xvec	An input matrix. Each row is a vectorized predictor.
y	Binary response variable.
xnew	Matrix of new values at which predictions are to made.
lambda	The regularization penalty.

Value

The returned object is a list of components.

B_est - The estimated coefficient matrix of linear predictor.

prob - The estimated probabilities of the binary response at the predictors xnew.

Index

ADMM, [2](#)
ASSIST, [3](#)

CNN, [5](#)

Lasso, [5](#)