

# Package ‘TensorComplete’

May 18, 2021

**Type** Package  
**Title** Tensor Noise Reduction and Completion Methods  
**Version** 0.1.0  
**Author** Anonymous  
**Maintainer** Anonymous <anonymous@anonymous.com>  
**Imports** pracma, methods, utils, tensorregress, MASS  
**Description** Efficient algorithms for nonparametric tensor completion via sign series. This package provides the nonparametric completion tool for estimating tensor signals from noisy, possibly incomplete observations. The algorithms employ the alternating optimization. The detailed algorithm description can be found in the main paper.  
**License** GPL(>=2)  
**Encoding** UTF-8  
**RoxygenNote** 7.1.1

## R topics documented:

Altopt . . . . .	1
fit_continuous_cp . . . . .	2
fit_nonparaT . . . . .	3
<b>Index</b>	<b>5</b>

---

Altopt	<i>Alternating optimization of the weighted classification loss</i>
--------	---

---

### Description

Optimize the weighted classification loss given a weight tensor, an observed data tensor, and a large margin loss. This function is used as a subroutine in the main function `fit_nonparaT`.

### Usage

```
Altopt(Ybar,W,r,type = c("logistic","hinge"),start = "linear")
```

**Arguments**

Ybar	A given (possibly noisy and incomplete) data tensor.
W	A weight tensor used in the weighted classification loss.
r	A rank to be fitted (CP rank).
type	A large margin loss to be used. Logistic or hinge loss is available.
start	Choice of initialization method. Use random initialization if start = "random"; Use the initialization based on low rank approximation if start = "linear". Linear initialization is default.

**Value**

The returned object is a list of components.

binary\_obj - Trajectory of binary loss values over iterations.

obj - Trajectory of weighted classification loss values over iterations.

iter - The number of iterations.

error - Trajectory of errors over iterations.

fitted - A tensor that optimizes the weighted classification loss.

**Examples**

```
library(tensorregress)
indices = c(2,3,4)
noise = rand_tensor(indices)@data
Theta = array(runif(prod(indices),min=-3,max = 3),indices)

# The signal plus noise model
Y = Theta + noise

# Optimize the weighted classification for given a sign tensor sign(Y) and a weight tensor abs(Y)
result = Altopt(sign(Y),abs(Y),r = 3,type = "hinge",start = "linear")
signTheta = sign(result$fitted)
```

---

fit_continuous_cp	<i>Signal tensor estimation from a noisy and incomplete data tensor based on CP low rank tensor method.</i>
-------------------	---

---

**Description**

Estimate a signal tensor from a noisy and incomplete data tensor using CP low rank tensor method.

**Usage**

```
fit_continuous_cp(data,r)
```

**Arguments**

data	A given (possibly noisy and incomplete) data tensor.
r	A rank to be fitted (CP rank).

**Value**

The returned object is a list of components.

est - An estimated signal tensor based on CP low rank tensor method.

U - A list of factor matrices.

lambda - A vector of tensor singular values.

**Examples**

```
library(tensorregress)
indices = c(2,3,4)
noise = rand_tensor(indices)@data
Theta = array(runif(prod(indices),min=-3,max = 3),indices)

# The signal plus noise model
Y = Theta + noise

# Estimate Theta from CP low rank tensor method
hatTheta = fit_continuous_cp(Y,3)
print(hatTheta$est)
```

---

fit_nonparaT	<i>Main function for nonparametric tensor estimation and completion based on low sign rank model.</i>
--------------	---

---

**Description**

Estimate a signal tensor from a noisy and incomplete data tensor using nonparametric tensor method via sign series.

**Usage**

```
fit_nonparaT(Y,truer,H,Lmin,Lmax,option = 2)
```

**Arguments**

Y	A given (possibly noisy and incomplete) data tensor. The function allows both continuous- and binary-valued tensors. Missing value should be encoded as NA.
truer	Sign rank of the signal tensor.
H	Resolution parameter.
Lmin	Minimum value of the signal tensor (or minimum value of the tensor Y).
Lmax	Maximum value of the signal tensor (or maximum value of the tensor Y).
option	A large margin loss to be used. Use logistic loss if option = 1, hinge loss if option = 2. Hinge loss is default.

**Value**

The returned object is a list of components.

fitted - A series of optimizers that minimize the weighted classification loss at each level.

est - An estimated signal tensor based on nonparametric tensor method via sign series.

**Examples**

```
library(tensorregress)
indices = c(2,2,2)
noise = rand_tensor(indices)@data
Theta = array(runif(prod(indices),min=-2,max = 2),indices)

# The signal plus noise model
Y = Theta + noise

# Estimate Theta from nonparametric completion method via sign series
hatTheta = fit_nonparaT(Y,truer = 2,H = 2,Lmin = -2,Lmax = 2, option =2)
print(hatTheta$est)
```

# Index

Altopt, [1](#)

fit\_continuous\_cp, [2](#)

fit\_nonparaT, [3](#)