

Connection between kernel SMM and SVM

Miaoyan Wang, May 18, 2020

Fact: Let $X \in \mathbb{R}^d$ denote a column vector and $X^* = \begin{bmatrix} 0 & X^T \\ X & 0 \end{bmatrix} \in \mathbb{R}^{(d+1) \times (d+1)}$ be the lifted matrix.

Under general nonlinear kernels, we cannot guarantee the equal decision boundaries between X -trained and X^* -trained SMMs!

Where goes wrong? Fact: Repeated attributes are down-weighted in SVM.

Consider two SVMs, one trained on $X = (x_1, x_2)^T$, and another one trained on $X^* = (x_1, x_2, x_2)^T$. It turns out the decision boundary trained by X and X^* are different.

Reason: The primal problems for these two SVMs are

$$(P1) \quad \min_{\beta_1, \beta_2} \left\{ \beta_1^2 + \beta_2^2 + C \sum_i [y_i(\beta_1 x_1 + \beta_2 x_2)]_+ \right\},$$

and

$$\begin{aligned} (P2) \quad & \min_{\beta_1, \beta_2, \beta_3} \left\{ \beta_1^2 + \beta_2^2 + \beta_3^2 + C' \sum_i [y_i(\beta_1 x_1 + (\beta_2 + \beta_3)x_2)]_+ \right\} \\ & = \min_{\beta_1, \beta_2} \left\{ \beta_1^2 + \frac{1}{2}\beta_2^2 + C' \sum_i [y_i(\beta_1 x_1 + \beta_2 x_2)]_+ \right\}. \end{aligned}$$

The solutions to (P1) and (P2) are usually different unless $\beta_1 = 0$. In particular, the repeated attribute, x_2 , is down-weighted in the cost function (P2).

Back to the kernel SMM problem. Under general nonlinear kernels, the attributes have different occurrences in $h(X^*)$ and $h(X)$. Therefore, the two decision boundaries might be different. Note that the two classifiers agree in the special case of linear kernels, since each attribute repeats precisely twice.

Implication: A weighted SVM

$$\min_{\beta} \beta^T [\text{Cov}(X)]^{-1} \beta + \sum_i [y_i \langle \beta, X \rangle]_+$$

will stabilize the contribution from repeated attributes, thereby maintaining the equivalence between X - and X^* -trained SVMs. In our context of kernel SMM, however, the unequal occurrences of attributes are actually okay. We can interpret the unequal occurrences as a prior knowledge of “importance” in the classifier.

Theorem 0.1 (Compatibility with Kernel SVM). *Let $X \in \mathbb{R}^d$ denote a column vector and $X^* =$*

$\begin{bmatrix} 0 & X^T \\ X & 0 \end{bmatrix} \in \mathbb{R}^{(d+1) \times (d+1)}$ be the symmetrized matrix. Then, under our proposed column-wise kernels, the SMM classifier trained on X^* equals the SVM classifier trained on X .

Remark 1. The decision boundaries generated by two classifiers are the same, but the optimal objective values may not be the same.

Proof. We prove the following stronger result.

(Set-up.) Let $X \in \mathbb{R}^{m \times n}$ be the original matrix feature,

$$X = \begin{bmatrix} | & | & | & | \\ x_1 & x_2 & \vdots & x_n \\ | & | & | & | \end{bmatrix} = \begin{bmatrix} - & y_1^T & - \\ - & y_2^T & - \\ - & \dots & - \\ - & y_m^T & - \end{bmatrix},$$

where x_i and y_j^T denotes the i -th column and j -th row of the matrix X , respectively. Let $X^* \in \mathbb{R}^{(m+n) \times (m+n)}$ be the symmetrized matrix feature. Based on the assumption (of sufficiently valid kernels), the feature mapping h is applied to matrix X^* in a column-wise fashion; that is,

$$X^* = \begin{bmatrix} 0 & X^T \\ X & 0 \end{bmatrix} \Rightarrow h(X^*) = \begin{bmatrix} & & & 0 & & & | & | & | & \\ & & & & & & h(y_1) & \dots & h(y_m) & \\ \dots & \dots & \dots & \dots & \dots & \dots & | & | & | & \\ h(x_1) & \dots & h(x_n) & & & & | & | & | & \\ | & | & | & & & & 0 & & & \end{bmatrix} =: \begin{bmatrix} 0 & A \\ C & 0 \end{bmatrix},$$

where, with a little abuse of notation, we have used $h(x_i)$ and $h(y_i)$ to denote the non-zero coordinates in the image vector $h((0, \dots, 0, x_i))$ and $h((0, \dots, 0, y_j))$, respectively.

(Conclusion.) Assume the set of elements in C contains all elements in A . Then, the classifier trained on X equals to the classifier trained on X^* .

(Proof of the above conclusion.) Because the elements in C contains all elements in A , we rearrange the elements in C into a possibly larger matrix:

$$C = \begin{bmatrix} 0 & A^T \\ D & 0 \end{bmatrix}.$$

Such arrangement is possible by, for example, setting $D = \text{diag}(\{C\}/\{A\})$. (The element arrangement within D is non-important.) To prove the equivalence between X - and X^* -trained classifiers,

it suffices to prove the equivalence between

$$h(X^*) = \begin{bmatrix} 0 & 0 & A \\ 0 & A^T & 0 \\ D & 0 & 0 \end{bmatrix}, \quad \text{and} \quad h(X) = \begin{bmatrix} 0 & A^T \\ D & 0 \end{bmatrix} \quad (\text{c.f. (??) and (??)}).$$

Now we apply the same proof techniques as in 051820_SMMK_modification.pdf. Specifically, consider the primal problems with $h(X^*)$ and $h(X)$. The relevant linear predictors are

$$\langle B^*, h(X^*) \rangle = \left\langle \begin{bmatrix} 0 & 0 & B_3^* \\ 0 & B_2^* & 0 \\ B_1^* & 0 & 0 \end{bmatrix}, \begin{bmatrix} 0 & 0 & A \\ 0 & A^T & 0 \\ D & 0 & 0 \end{bmatrix} \right\rangle, \quad \text{and} \quad \langle B, h(X) \rangle = \left\langle \begin{bmatrix} 0 & B_2 \\ B_1 & 0 \end{bmatrix}, \begin{bmatrix} 0 & A^T \\ D & 0 \end{bmatrix} \right\rangle.$$

The optimizations are

$$\begin{aligned} (P1) \quad & \min_{B_1^*, B_2^*, B_3^*} \|B_1^*\|_F^2 + \|B_2^*\|_F^2 + \|B_3^*\|_F^2 + C \sum_i \xi_i, \\ & \text{s.t. where } \langle B^*, h(X^*) \rangle = \langle B_1^*, D \rangle + \langle B_2^*, A^T \rangle + \langle B_3^{*T}, A \rangle \\ & \quad = \langle B_1^*, D \rangle + \langle B_2^{*T} + B_3^*, A \rangle, \end{aligned}$$

and

$$\begin{aligned} (P2) \quad & \min_{B_1, B_2} \|B_1\|_F^2 + \|B_2\|_F^2 + C \sum_i \xi_i, \\ & \text{s.t. ... where } \langle B, h(X) \rangle = \langle B_1, D \rangle + \langle B_2, A \rangle. \end{aligned}$$

It is easy to see that the optimal solution to (P1) is achieved at $B_2^* = B_3^{*T}$ because

$$\|B_2^*\|_F^2 + \|B_3^*\|_F^2 \geq \frac{1}{2} \|B_2^* + B_3^{*T}\|_F^2.$$

With this choice, the optimizations become

$$(P1) \quad \min_{B_1^*, B_2^*} \|B_1^*\|_F^2 + \frac{1}{2} \|B_2^*\|_F^2 + C \sum_i [y_i (\langle B_1^*, D \rangle + \langle B_2^*, A \rangle)]_+.$$

and

$$(P2) \quad \min_{B_1, B_2} \|B_1\|_F^2 + \|B_2\|_F^2 + C \sum_i [y_i (\langle B_1, D \rangle + \langle B_2, A \rangle)]_+.$$

These two optimizations are different! Repeated features contribute less to (P1) compared to (P2). □