


# COMP26120: Introducing Complexity Analysis (2020/21)

Lucas Cordeiro

[lucas.cordeiro@manchester.ac.uk](mailto:lucas.cordeiro@manchester.ac.uk)



# Introducing Complexity Analysis

- Textbook:
  - *Algorithm Design and Applications*, Goodrich, Michael T. and Roberto Tamassia (Chapter 1)






# Introducing Complexity Analysis

- Textbook:
  - *Algorithm Design and Applications*, Goodrich, Michael T. and Roberto Tamassia (Chapter 1)
  - *Introduction to Algorithms*, Cormen, Leiserson, Rivest, Stein (Chapters 2 and 3)



# Introducing Complexity Analysis

- Textbook:
  - *Algorithm Design and Applications*, Goodrich, Michael T. and Roberto Tamassia (Chapter 1)
  - *Introduction to Algorithms*, Cormen, Leiserson, Rivest, Stein (Chapters 2 and 3)
  - *Computer Organization and Design*, Patterson and Hennessy (Chapter 2)



# Intended Learning Outcomes

- Define **asymptotic notation**, **functions**, and **running times**

# Intended Learning Outcomes

- Define **asymptotic notation**, **functions**, and **running times**
- Analyse the **running time** used by an algorithm via **asymptotic analysis**

# Intended Learning Outcomes

- Define **asymptotic notation**, **functions**, and **running times**
- Analyse the **running time** used by an algorithm via **asymptotic analysis**
- Examine and sketch examples of **asymptotic analysis** using the **insertion sorting algorithm**

# Motivating Example

- What does this code fragment represent?

```
...  
for(i = 0; i < N-1; i++) {  
    for(j = 0; j < N-1; j++) {  
        if (a[j] > a[j+1]) {  
            ● t = a[j];  
            a[j] = a[j+1];  
            a[j+1] = t;  
        }  
    }  
}  
...
```



# Motivating Example

- What does this code fragment represent?

```
...  
for(i = 0; i < N-1; i++) {  
    for(j = 0; j < N-1; j++) {  
        if (a[j] > a[j+1]) {  
            t = a[j];  
            ● a[j] = a[j+1];  
            a[j+1] = t;  
        }  
    }  
}  
...
```

# Motivating Example


- What does this code fragment represent?

```
...  
for(i = 0; i < N-1; i++) {  
    for(j = 0; j < N-1; j++) {  
        if (a[j] > a[j+1]) {  
            t = a[j];  
            a[j] = a[j+1];  
            ● a[j+1] = t;  
        }  
    }  
}  
...
```

# Motivating Example

- What does this code fragment represent?

```
...  
for(i = 0; i < N-1; i++) {  
    for(j = 0; j < N-1; j++) {  
        if (a[j] > a[j+1]) {  
            t = a[j];  
            a[j] = a[j+1];  
            a[j+1] = t;  
        }  
    }  
}  
...
```



# Motivating Example

- What does this code fragment represent?

```
...  
for(i = 0; i < N-1; i++) {  
    for(j = 0; j < N-1; j++) {  
        if (a[j] > a[j+1]) {  
            t = a[j];  
            a[j] = a[j+1];  
            a[j+1] = t;  
        }  
    }  
}  
...
```

- This is bubble sort

# Motivating Example

- What does this code fragment represent? What is its complexity?

```
...  
for(i = 0; i < N-1; i++) {  
    for(j = 0; j < N-1; j++) {  
        if (a[j] > a[j+1]) {  
            t = a[j];  
            a[j] = a[j+1];  
            a[j+1] = t;  
        }  
    }  
}  
...
```

- This is bubble sort

# Motivating Example

- What does this code fragment represent? What is its complexity?

```
...  
for(i = 0; i < N-1; i++) {  
    for(j = 0; j < N-1; j++) {  
        if (a[j] > a[j+1]) {  
            t = a[j];  
            a[j] = a[j+1];  
            a[j+1] = t;  
        }  
    }  
}  
...
```

- This is bubble sort
- There are two loops

# Motivating Example

- What does this code fragment represent? What is its complexity?

```
...  
for(i = 0; i < N-1; i++) {  
    for(j = 0; j < N-1; j++) {  
        if (a[j] > a[j+1]) {  
            t = a[j];  
            a[j] = a[j+1];  
            a[j+1] = t;  
        }  
    }  
}  
...
```

- This is bubble sort
- There are two loops
- Both loops make  $n-1$  iterations so we have  $(n-1)*(n-1)$

# Motivating Example

- What does this code fragment represent? What is its complexity?

```
...  
for(i = 0; i < N-1; i++) {  
    for(j = 0; j < N-1; j++) {  
        if (a[j] > a[j+1]) {  
            t = a[j];  
            a[j] = a[j+1];  
            a[j+1] = t;  
        }  
    }  
}  
...
```

- This is bubble sort
- There are two loops
- Both loops make  $n-1$  iterations so we have  $(n-1)*(n-1)$
- The complexity is  $O(n^2)$



# Motivating Example

- What does this code fragment represent? What is its complexity?

```
...  
for(i = 0; i < N-1; i++) {  
    for(j = 0; j < N-1; j++) {  
        if (a[j] > a[j+1]) {  
            t = a[j];  
            a[j] = a[j+1];  
            a[j+1] = t;  
        }  
    }  
}  
...
```

- This is bubble sort
- There are two loops
- Both loops make  $n-1$  iterations so we have  $(n-1)*(n-1)$
- The complexity is  $O(n^2)$

Perform worst case analysis  
and ignore constants

# Motivating Example

You can download these examples from the  
course website:

[http://syllabus.cs.manchester.ac.uk/ugt/2020/  
COMP26120/](http://syllabus.cs.manchester.ac.uk/ugt/2020/COMP26120/)