




CHALMERS



Active Steering Dolly for Long Combination Vehicles

Design of a Real-Time Control Interface for a steerable Dolly
Master's thesis in Automotive Engineering

SEBASTIAN FRANZ
MICHAEL HOFMANN

Department of Applied Mechanics
CHALMERS UNIVERSITY OF TECHNOLOGY
Göteborg, Sweden 2015

MASTER'S THESIS IN AUTOMOTIVE ENGINEERING

Active Steering Dolly for Long Combination Vehicles

Design of a Real-Time Control Interface for a steerable Dolly

SEBASTIAN FRANZ
MICHAEL HOFMANN

Department of Applied Mechanics
Division of Vehicle Dynamics
CHALMERS UNIVERSITY OF TECHNOLOGY
Göteborg, Sweden 2015

Active Steering Dolly for Long Combination Vehicles
Design of a Real-Time Control Interface for a steerable Dolly
SEBASTIAN FRANZ
MICHAEL HOFMANN

© SEBASTIAN FRANZ, MICHAEL HOFMANN, 2015

Master's thesis 2015:01
ISSN 1652-8557
Department of Applied Mechanics
Division of Vehicle Dynamics
Chalmers University of Technology
SE-412 96 Göteborg
Sweden
Telephone: +46 (0)31-772 1000

Cover:
Some explanation

Chalmers Reproservice
Göteborg, Sweden 2015

Active Steering Dolly for Long Combination Vehicles
Design of a Real-Time Control Interface for a steerable Dolly
Master's thesis in Automotive Engineering
SEBASTIAN FRANZ
MICHAEL HOFMANN
Department of Applied Mechanics
Division of Vehicle Dynamics
Chalmers University of Technology

ABSTRACT

Keywords: Some stuff, More stuff, Stuff

PREFACE

ACKNOWLEDGEMENTS

NOMENCLATURE

CONTENTS

Abstract	i
Preface	iii
Acknowledgements	iii
Nomenclature	v
Contents	vii
1 Introduction	1
1.1 Purpose	1
1.2 Limitations	1
1.3 Structure of this work	1
2 Overview	2
2.1 Ongoing research	2
2.2 Legal Situation	2
2.3 Market overview for existing solutions	2
3 Hardware Setup	3
3.1 Utilized dolly system	3
3.2 Real-Time Environment	3
3.3 Interfaces with Dolly	3
3.4 Measurment Setup	3
4 Processing Time evaluation	4
4.1 Background	4
4.2 Measured input delay	4
4.3 Computational delay	4
5 Steering Model	5
5.1 Overview of the model	5
5.2 Input parameters	5
5.3 Real-Time implementation	5
5.4 Interface with Real-Time environment	5
6 Testing	6
6.1 Overview	6
6.2 Bench-Testing	6
6.2.1 ECU-setup	6
6.2.2 CAN verification	6
6.3 Vehicle testing	6
6.3.1 System calibration	6
6.3.2 Actuator tests	6
6.3.3 Algorithm evaluation	6
6.3.4 Sensor testing	6
6.4 Track testing	6
6.4.1 Testenvironment	6
6.4.2 Testmatrix	6
6.4.3 Test setup	6
6.5 Interface with Real-Time environment	6

7	Discussion	7
7.1	Results from bench testing	7
7.2	Results from in vehicle testing	7
7.3	Results from on-track testing	7
7.4	Comparrison	7
8	Conclusion	8
8.1	Recommendation	8
8.2	Future Work	8
	References	9

1 Introduction

1.1 Purpose

Heavy goods-transport on the road has constantly increased over the last decades. Coupled with the stricter environmental regulations concerning CO₂-emissions and pollution, the call for more economical transport solution has led to the wider introduction of long combination vehicles. Those truck-trailer combinations have a longer history in areas with low population density, mining and transport within factory sites where rail-road transport is not a viable option but large volumes and tonnages are needed. The prospects of saving costs on driver's salaries, reduced fuel consumption and decreased costs suggests the introduction of those combinations in other areas as well.

The driving behaviour of LCVs is in many ways different to that of the standard truck and needs to be researched in great detail to gain an understanding of the vehicle's dynamic properties, that is equally detailed as it is for other vehicles class. This will lead to development of better safety systems and thus reduction in accidents and fatalities involving this emerging mode of transportation.

The major cause for accidents involving LCVs is loss of control in cornering situations.

1.2 Limitations

The actual algorithm to compute the desired angle of the dolly's steerable axles is not in the scope of this thesis. Nevertheless to establish an easier insight into the interfaces' parameters, an overview of the structure and parameters of the underlying computational steering model is needed and shall be presented in chapter XXX.

The hardware- and low-level control-system of the hydraulic actuators is in place already and thus will not be part of this thesis. It is supplied as turn-key software by the manufacturer and readily available on the dolly's electrical control units (ECU). The ECU's software version will be available fully calibrated and parametrized for the dolly at hand and thus provide a reliable working base to build upon.

1.3 Structure of this work

2 Overview

2.1 Ongoing research

2.2 Legal Situation

2.3 Market overview for existing solutions

3 Hardware Setup

3.1 Utilized dolly system

3.2 Real-Time Environment

3.3 Interfaces with Dolly

3.4 Measurment Setup

4 Processing Time evaluation

4.1 Background

4.2 Measured input delay

4.3 Computational delay

5 Steering Model

5.1 Overview of the model

5.2 Input parameters

5.3 Real-Time implementation

5.4 Interface with Real-Time environment

6 Testing

6.1 Overview

6.2 Bench-Testing

6.2.1 ECU-setup

6.2.2 CAN verification

6.3 Vehicle testing

6.3.1 System calibration

6.3.2 Actuator tests

6.3.3 Algorithm evaluation

6.3.4 Sensor testing

6.4 Track testing

6.4.1 Testenvironment

6.4.2 Testmatrix

6.4.3 Test setup

6.5 Interface with Real-Time environment

7 Discussion

7.1 Results from bench testing

7.2 Results from in vehicle testing

7.3 Results from on-track testing

7.4 Comparrison

8 Conclusion

8.1 Recommendation

8.2 Future Work

genital[Pom+08]

References

- [Han+04] K. Hanjalic et al. A robust near-wall elliptic-relaxation eddy-viscosity turbulence model for CFD. *Int. J. Heat Fluid Flow* **25** (2004), 1047–1051.
- [Ise04] A. Iserles. *A First Course in the Numerical Analysis of Differential Equations*. Cambridge University Press, 2004. ISBN: 0-521-55655-4.
- [Mat] *MATLAB manual. Ordinary Differential Equations*. Version 7.8. Mathworks, 2008. URL: <http://www.mathworks.com/access/helpdesk/help/techdoc/ref/ode45.html>.
- [SWS06] P. Steenhof, C. Woudsma, and E. Sparling. Greenhouse gas emissions and the surface transport of freight in Canada. *Transportation Research Part D: Transport and Environment* **11.5** (2006), 369–376. ISSN: 1361-9209. DOI: <http://dx.doi.org/10.1016/j.trd.2006.07.003>. URL: <http://www.sciencedirect.com/science/article/pii/S1361920906000411>.