

Neural Conversational AI


Ondřej Dušek

MLSS^N Summer School

30 June 2022



Charles University
Faculty of Mathematics and Physics
Institute of Formal and Applied Linguistics



unless otherwise stated

Ondřej

- Charles University, Prague
- '16-18 at Heriot-Watt Uni Edinburgh
- working mostly on language generation
- often in/with dialogue systems



This lecture

- relatively vague/high-level (focus on main ideas)
- focusing on what I work with (pretrained language models)
- trying to avoid digressions
- expecting you know NNs, but haven't necessarily worked in NLP
- probably much more applied than other talks here
 - most of you probably know more about ML theory than I do
- slightly improvised (depending on timing, I might skip stuff)

Topics of Today

1. Intro: “Conversational AI” = “Dialogue Systems”
2. Transformer & pretrained language models
3. Neural models for dialogue system components
 - language understanding
 - state tracking
 - dialogue policy
4. End-to-end neural models
5. Evaluation metrics

1. Introduction

What's Conversational AI = Dialogue System?

- Definition: A (*spoken*) dialogue system is a **computer system designed to interact** with users **in (*spoken*) natural language**
 - Wide – covers lots of different cases
 - “smart speakers” / phone OS assistants
 - phone hotline systems (even tone-dial ones)
 - in-car systems
 - assistive technologies: therapy, elderly care, companions
 - entertainment: video game NPCs, chatbots
- DSs are cool:
 - ultimate natural interface: say what you want
 - lots of active research – far from solved
 - already used commercially



Real-life dialogue systems: virtual assistants

- Google, Amazon, Apple & others, Mycroft, Rhasspy: open-source
- Really good microphones
 - and not much else – listen for wake word, processing happens online
- Huge knowledge bases
 - combined with web search
- Lots of domains programmed in, but all by hand
 - integration with a lot of services (calendar, music, shopping, weather, news...)
 - you can add your own (with limitations)
- Can keep some context
- Conversational capabilities limited



<https://www.lifehacker.com.au/2018/02/specs-showdown-google-home-vs-amazon-echo-vs-apple-homepod/>

<https://homealarmreport.com/smart-home/amazon-echo-vs-google-home/>

Dialogue System Types

Task-oriented

- focused on completing a certain task/tasks
 - booking restaurants/flights, finding bus schedules, smart home...
- most actual DS in the wild
 - also our main focus in this course
- (typically) **single/multi domain**
 - talk about 1/more topics


Non-task-oriented

- chitchat – social conversation, entertainment
 - persona, gaming the Turing test
- typically **open-domain** – talk about anything

Comm. Modes: voice / text / multimodal (face, graphics...)

Dialogue Systems Architecture

- traditional DS pipeline:
 - ASR: voice → text
 - **NLU: text → meaning**
 - **DM: meaning → reaction**
 - **NLG: reaction → text**
 - TTS: text → voice
- backend
 - needed for anything better than basic chit-chat
- text-based systems (here):
NLU→DM→NLG



Task-oriented Dialogue Example

(Budzianowski et al., 2018)

<https://aclanthology.org/D18-1547/>

- MultiWOZ: benchmark for task-oriented dialogue in multiple domains
 - hotels, restaurants, attractions, trains, taxi, police, hospital
 - domains are connected (e.g. taxi from hotel to attraction)
 - 10k dialogues, extensive annotation (but noisy!)

- user:** I am looking for a train from Cambridge to London Kings Cross.
state: *{train {departure = cambridge, destination = london kings cross}}*
DB: *{train (70) {...}}*

	[count]	[departure]	[destination]
system:	There are 70	trains departing from Cambridge to London Kings Cross.	What day would you like to travel?
- user:** I would like to leave on Saturday after 18:45.
state: *{train {day = saturday, departure = cambridge, destination = london kings cross, leave at = 18:45}}*
DB: *{train (3) {arrive by = 19:51,21:51,23:51; id = TR0427,TR0925,TR4898; leave at = 19:00,21:00,23:00; ... }}*

	[id]	[leave_at]	[arrive_by]
system:	TR0427	leaves at 19:00	and arrives by 19:51 . Would you like to book this train?
- user:** Yes, I would like to book it for eight people.
system: I have booked it for you. Your reference number is 00000057. Is there anything else I can help you with?


	[reference]
system:	I have booked it for you. Your reference number is 00000057. Is there anything else I can help you with?
- user:** I am also looking for an expensive restaurant in the centre.
belief: *{restaurant {area = centre, price range = expensive} train {...}}*
DB: *{restaurant (33) {area = centre (33); name=Curry Garden, ...; ...}, ...}*

	[count]	[price_range]	[area]
system:	There are 33	expensive restaurants in the centre.	Is there a particular type of food you would like?


2. Transformer & Pretrained Models

Representing Language: Embeddings

- distributed representation
 - each word = a vector of floats**
 - basically an easy conversion of 1-hot \rightarrow numeric
 - a dictionary of trainable features
- part of network parameters – trained
 - pretraining (optional)
 - training for the target task
- the network learns which words are used similarly – for the given task
 - they end up having close embedding values
 - different embeddings for different tasks
- embedding size: ~100s-1000
- vocab size: ~50-100k




<http://blog.kaggle.com/2016/05/18/home-depot-product-search-relevance-winners-interview-1st-place-alex-andreas-nurlan/>



<http://ruder.io/word-embeddings-2017/>

Subwords

- vocabulary is unlimited, embedding matrix isn't
 - + the bigger the embedding matrix, the slower your models
- Special **out-of-vocabulary token** *<unk>*
 - loses information, we don't want it on the output
- **Subwords:** groups of characters that
 - make shorter sequences than using individual characters
 - cover everything
 - 20-50k subwords for 1 language, ~250k subwords multilingual
- **Byte-pair Encoding** (=one way to get subwords)
 - start from individual characters
 - iteratively merge most frequent bigram, until you get desired # of subwords

*fast_
faster_
tall_
taller_*  *fast er_
tall er_
slower_
tall est_*

Encoder-Decoder Networks (Sequence-to-sequence)

- Default RNN paradigm for sequences/structure prediction

- **encoder** RNN: encodes the input token-by-token into **hidden states** h_t

- next step: last hidden state + next token as input

$$h_0 = 0$$
$$h_t = \text{cell}(x_t, h_{t-1})$$



- **decoder** RNN: constructs the output token-by-token **autoregressively**

- initialized by last encoder hidden state
 - output: hidden state & softmax over output vocabulary + argmax
 - next step: last hidden state + last generated token as input

$$s_0 = h_T$$
$$p(y_t | y_1, \dots, y_{t-1}, \mathbf{x}) = \text{softmax}(s_t)$$
$$s_t = \text{cell}(y_{t-1}, s_{t-1})$$

- LSTM/GRU cells=layers over vectors of ~ embedding size

- used for many NLP tasks





<https://lilianweng.github.io/lil-log/2018/06/24/attention-attention.html>

<https://medium.com/syncedreview/a-brief-overview-of-attention-mechanism-13c578ba9129>


Attention

- Encoder-decoder is too crude for complex sequences
 - the whole input is crammed into a fixed-size vector (last hidden state)
- **Attention** = “memory” of **all encoder** hidden states
 - weighted combination, re-weighted for every decoder step
→ can focus on currently important part of input
 - fed into decoder inputs + decoder softmax layer
- **Self-attention** – over **previous decoder steps**
 - increases consistency when generating long sequences



<https://skymind.ai/wiki/attention-mechanism-memory-network>




Seq2seq RNNs with Attention



Transformer

(Waswani et al., 2017)
<https://arxiv.org/abs/1706.03762>


- getting rid of recurrences
 - faster to train, allows bigger nets
 - replace everything with **attention** + **feed-forward** networks
 - \Rightarrow needs more layers
 - \Rightarrow needs to encode positions
- positional encoding
 - adding position-dependent patterns to the input
- attention – simple dot-product
 - scaled by $\frac{1}{\sqrt{\text{\#dms}}}$ (so values don't get too big)
 - **more heads** (attentions in parallel)
 - focus on multiple inputs



Transformer

feed-forward (fully connected) network

- ReLU activations
- tricks for better training



Pretrained Language Models

- Transformer Architecture
 - Encoder-only (= good for classification/token tagging)
 - Decoder-only (= good for generation)
 - Encoder-Decoder (= RNN seq2seq equivalent)
- **Self-supervised pretraining**
 - standard supervised training, but without annotation
 - naturally occurring labels
 - automatic labels ~ fix artificially corrupted data
 - typically simple language tasks (→)
 - used with huge amounts of data – many GBs of text (e.g. CommonCrawl)
 - models not useful for much, but **can be finetuned** for the target task
 - just train further, use data for target task

Pretrained Language Models

(Devlin et al., 2019)

<https://www.aclweb.org/anthology/N19-1423>


<https://github.com/google-research/bert>

(Rogers et al., 2020) <http://arxiv.org/abs/2002.12327>

(Liu et al., 2019) <http://arxiv.org/abs/1907.11692>

- Pretraining Tasks

- Masked word prediction
- Next-word prediction
- Fixing corrupt sentences
- Sentence order prediction



(Lewis et al., 2020) <http://arxiv.org/abs/1910.13461>

(Raffel et al., 2019) <http://arxiv.org/abs/1910.10683>

- Models

- **BERT** encoder only, variants: multilingual, **RoBERTa** (optimized)
- **GPT(-2/-3/-j/-neo)**: decoder only, next-word prediction
- **(m)BART, (m)T5**: encoder-decoder
- **ByT5**: enc-dec, byte-level (instead of subwords)
- a lot of pretrained models released plug-and-play
 - you only need to finetune (and sometimes, not even that)

(Radford et al., 2019) <https://openai.com/blog/better-language-models/>

(Brown et al., 2020) <http://arxiv.org/abs/2005.14165>

(Xue et al., 2022) https://doi.org/10.1162/tacl_a_00461



<https://github.com/huggingface/transformers>

3. Component Models

Natural/Spoken Language understanding (NLU/SLU)

- **Words → meaning:** Extracting the meaning from user utterance
- **dialogue acts** (or other structured semantic representation):
 - act type/**intent** (*inform, request, confirm*)
 - **slot**/attribute (*price, time...*)
 - **value** (*11:34, cheap, city center...*)
 - typically intent classification + slot-value tagging
 - (other, more complex representations – e.g. trees, predicate logic)
- Specific steps:
 - **named entity resolution** (NER)
 - identifying task-relevant names (*London, Saturday*)
 - **coreference resolution**
 - (“*it*” → “*the restaurant*”)

inform(food=Chinese, price=cheap)
request(address)

NLU Challenges

- non-grammaticality *find something cheap for kids should be allowed*
- disfluencies
 - hesitations – pauses, fillers, repetitions *uhm I want something in the west the west part of town*
 - fragments *uhm I'm looking for a cheap*
 - self-repairs (~6%!) *uhm find something uhm something cheap no I mean moderate*
- ASR errors *I'm looking for a for a chip Chinese rest or rant*
- synonymy *Chinese city centre*
I've been wondering if you could find me a restaurant that has Chinese food close to the city centre please
- out-of-domain utterances *oh yeah I've heard about that place my son was there last month*

- You can get far with keywords/regexes (for a limited domain)
- **Intent classification**
 - RNN: last hidden state
 - Transformers, PLMs: typically over 1st input element (start-of-sentence token)
- **Slot value detection**
 - classification (binary: “is slot value *X* present?”)
 - **slot tagging** – classify every token
 - **BIO/IOB** scheme: beginning (+slot) – inside (+slot) – outside
- **Delexicalization**: replacing slot values by placeholders
 - essentially named entity recognition
 - essentially tagging, but typically done by dictionaries

I need a flight from Boston to New York tomorrow
OO OO O B-dept O B-arr I-arr B-date


I'm looking for a Japanese restaurant in Notting Hill.
I'm looking for a <food> restaurant in <area>.

I need to leave after 12:00.
I need to leave after <time>.
(= not necessarily 1:1 with slots)


BERT-based NLU

- combined intent-slot
- slot tagging on top of pretrained BERT
 - standard **IOB approach**
 - feed last BERT layers to **softmax over tags**
 - classify only at 1st subword in case of split words (don't want tag changes mid-word)
- special start token tagged with intent
 - again, softmax on top of last BERT layer
- finetune both tasks at once
 - essentially same task, just having different labels on the 1st token 😊

(Chen et al., 2019)
<http://arxiv.org/abs/1902.10909>



- Pretraining on dialogue tasks can do better (& smaller) than BERT
 - ConveRT: Transformer-based **dual encoder**
 - 2 Transformer encoders: context + response
 - feed forward + cosine similarity on top
 - training objective: **response selection**
 - response that actually happened = 1
 - random response from another dialogue = 0
 - trained on a large dialogue dataset (Reddit)
- can be used as a base to train models for:
 - **slot tagging** (top self-attention layer → CNN → CRF)
 - **intent classification** (top feed-forward → more feed-forward → softmax)
 - Transformer layers are fixed, not fine-tuned
 - works well for little training data (**few-shot**)




(Coope et al., 2020)
<https://www.aclweb.org/anthology/2020.acl-main.11>

(Casanueva et al., 2020)
<https://www.aclweb.org/anthology/2020.nlp4convai-1.5>

TOD-BERT

- pre-finetuning BERT on vast *task-oriented* dialogue data
 - basically combination of 2 previous approaches
- **BERT + user/sys tokens** + train for:
 - masked language modelling
 - response selection (dual encoder style)
 - over [CLS] tokens from whole batch
 - other examples in batch = negative
- result: “better dialogue BERT”
 - can be finetuned for various dialogue tasks
 - intent classification
 - slot tagging
 - good performance even few-shot
 - just 1 or 10 examples per class



(Wu et al., 2020)

<https://www.aclanthology.org/2020.emnlp-main.66>

Dialogue Manager (DM)

- Given NLU input & dialogue so far, responsible for **deciding on next action**
 - keeps track of what has been said in the dialogue
 - keeps track of user profile
 - interacts with backend (database, internet services)
- Dialogue so far = **dialogue history**, modelled by **dialogue state**
 - managed by **dialogue state tracker**
- System actions decided by **dialogue policy**

Dialogue state / State tracking

- Stores (a summary of) dialogue history
 - User requests + information they provided so far
 - Information requested & provided by the system
 - User preferences
- Implementation
 - **handcrafted** – e.g. replace value for slot with last-mentioned
 - good enough in some circumstances
 - **probabilistic (belief state)**
 - keep an estimate of per-slot preferences based on NLU
 - more robust, more complex
 - accumulates probability over time & n-best lists
 - → handles NLU/ASR errors
 - e.g. 3x same low-confidence input = prob. high enough to react

price: cheap
food: Chinese
area: riverside

price: 0.8 cheap
0.1 moderate
0.1 <null>
food: 0.7 Chinese
0.3 Vietnamese
area: 0.5 riverside
0.3 <null>
0.2 city center

Basic State/Belief Trackers

a) Always trust the NLU

for **null** value:

$p = \text{prev} \cdot p(\text{👉}) \sim \text{user didn't mention this slot}$

non-null value v :

$p = \text{prev} \cdot p(\text{👉}) + p(v)$

\sim didn't mention = carry from previous

\sim did mention = add new NLU probability

- basically rule-based (but good if NLU is good)


b) “NLU” over whole dialogue

- typically classification (“is slot value v present?”)
 - option: limit to some candidates (from NLU/delexicalization), rank them
- may not need NLU, may be better, but slower

BERT & Span Selection a.k.a. Span Tagging (~question answering/reading comprehension)

- BERT over previous system & current user utterance
- from 1st token's representation, get a **decision**: *none*/*dontcare*/*span*
 - per-slot (BERT is shared, but the final decision is slot-specific)
- span = need to find a concrete value as a span somewhere in the text
 - **predict start & end token** of the span using 2 softmaxes over tokens
- rule-based update:
 - if *none* is predicted, keep previous value
 - essentially similar to NLU & update rule

(Chao & Lane, 2019)
<http://arxiv.org/abs/1907.03040>



Break


Action Selection / Policy

- **Deciding what to do next**

- **action** based on the current belief state
- following a **policy** (strategy) towards an end **goal** (e.g. book a flight)
- controlling the coherence & flow of the dialogue
- actions: linguistic & non-linguistic (backend access)
- actions represented by system dialogue acts

- DM/policy should:

- manage uncertainty from belief state ← *Did you say Indian or Italian?*
- recognize & follow dialogue structure ← follow convention, don't be repetitive
- plan actions ahead towards the goal ← e.g. ask for all information you require




(from Milica Gašić's slides)

confirm(food=Chinese)

*inform(name=Golden Dragon,
food=Chinese, price=cheap)*

Action Selection Approaches

- Finite-state machines
 - simplest possible
 - dialogue state is machine state
- Frame-based/flowcharts (e.g. VoiceXML)
 - slot-filling + providing information – basic agenda
 - rule-based in essence
- Rule-based
 - any kind of rules (e.g. Python code)
- **Statistical**
 - typically trained with **reinforcement learning**




```
229 elif fact['we_did_not_understand']:
230     # NLG("Sorry, I did not understand")
231     res_da = DialogueAct("notunderstood")
232     res_da.extend(self.get_limited_context())
233     dialogue_state["ludait"].reset()
234
235 elif fact['user_wants_help']:
236     # NLG("Pomoc.")
237     res_da = DialogueAct("help()")
238     dialogue_state["ludait"].reset()
239
240 elif fact['user_thanked']:
241     # NLG("Díky.")
242     res_da = DialogueAct('inform(context)')
243     dialogue_state["ludait"].reset()
244
245 elif fact['user_wants_restart']:
246     # NLG("Dobře, začneme znovu.")
```

Why Reinforcement Learning

- **Action selection ~ classification** → use supervised learning?
 - set of possible actions is known
 - belief state should provide all necessary features
- Yes, but...
 - You'd **need** sufficiently large **human-human data** – hard to get
 - human-machine would just mimic the original system
 - Dialogue is ambiguous & complex
 - there's **no single correct next action**– multiple options may be equally good
 - but datasets will only have one next action
 - **some paths will be unexplored** in data, but you may encounter them
 - DSs won't behave the same as people
 - ASR errors, limited NLU, limited environment model/actions
 - **DSs should behave differently** – make the best of what they have
 - supervised classification **doesn't plan ahead**
 - RL optimizes for the whole dialogue, not just the immediate action

Reinforcement learning: Definition

- MDP formalism: agent in an environment, **state-action-reward**



- RL = finding a **policy that maximizes long-term reward**

- unlike supervised learning, we don't know if an action is good
- immediate reward might be low while long-term reward high

return =
accumulated
long-term reward

$$R_t = \sum_{t=0}^T \gamma^t r_{t+1}$$

$\gamma \in [0,1]$ = **discount factor**
(immediate vs. future reward trade-off)

- state transition is stochastic \rightarrow maximize **expected return**

$$\mathbb{E}[R_t | \pi, s_0]$$

\leftarrow expected R_t if we start from state s_0 and follow policy π

Policy Gradients

- Train a **network to represent the policy** $\pi(a|s, \theta)$ – θ are parameters
- To optimize, we need a **performance metric**: $J(\theta) = V^{\pi_\theta}(s_0)$
 - expected return in starting state when following π_θ
 - we want to directly optimize this using gradient ascent
- **Policy Gradient Theorem**:
 - expresses $\nabla J(\theta)$ in terms of $\nabla \pi(a|s, \theta)$

$$\nabla J(\theta) \propto \underbrace{\sum_s \mu(s)}_{\mu(s) \text{ is state probability under } \pi - \text{this is the same as expected value } E_\pi} \sum_a Q^\pi(s, a) \nabla \pi(a|s, \theta) = E_\pi \left[\sum_a \underbrace{Q^\pi(s, a)}_{Q^\pi(s, a) = \text{“Q-function”} - \text{value of taking action } a \text{ in state } s, \text{ then following policy } \pi} \nabla \pi(a|s, \theta) \right]$$

$\mu(s)$ is state probability under π – this is the same as expected value E_π

$Q^\pi(s, a)$ = “Q-function”

– value of taking action a in state s , then following policy π

REINFORCE: Monte Carlo Policy Gradients

- direct search for policy parameters by stochastic gradient ascent
 - looking to maximize performance $J(\boldsymbol{\theta}) = V^{\pi_{\boldsymbol{\theta}}}(s_0)$
- choose learning rate α , initialize $\boldsymbol{\theta}$ arbitrarily
- loop forever:
 - generate an episode $s_0, a_0, r_1, \dots, s_{T-1}, a_{T-1}, r_T$, following $\pi(\cdot | \cdot, \boldsymbol{\theta})$
 - for each $t = 0, 1 \dots T$: $\boldsymbol{\theta} \leftarrow \boldsymbol{\theta} + \alpha \gamma^t R_t \nabla \ln \pi(a_t | s_t, \boldsymbol{\theta})$

this will guarantee
the right state
distribution/frequency $\mu(s)$

returns $R_t = \sum_{i=t}^{T-1} \gamma^{i-t} r_{i+1}$

variant – **advantage** instead of returns:
discounting a **baseline**
 $b(s)$ (predicted by any model)
 $A_t = R_t - b(s_t)$ instead of R_t
gives better performance

this is stochastic $\nabla J(\boldsymbol{\theta})$:

- from policy gradient theorem
- using single action sample a_t
- expressing Q^{π} as R_t (under E_{π})
- using $\nabla \ln x = \frac{\nabla x}{x}$

Rewards in RL

- Typical setup – **handcrafted rewards**:
 - every turn: -1 (encourage fast dialogues)
 - successful dialogue: + 20
 - unsuccessful: - 10 (~center around 0)
- Problems:
 - domain knowledge needed to detect dialogue success
 - **need simulated and/or paid users** (known goal)
 - simulated = essentially another dialogue system
 - paid users = costly + often fail to follow pre-set goals
 - needs a lot of dialogues to train (1000s) → simulated users, supervised pretraining
- Solutions:
 - trained rewards
 - provided by a network, can be turn-level
 - corpus-based RL (supervised/RL hybrid)
 - follow dataset, just assign rewards like RL (→)

Natural Language Generation (NLG) / Response Generation

- Representing system dialogue act in natural language (text)
 - reverse NLU
- How to express things might depend on context
 - Goals: fluency, naturalness, avoid repetition (...)
- Traditional approach: **templates**
 - Fill in (=lexicalize) values into predefined templates (sentence skeletons)
 - Works well for limited domains


inform(name=Golden Dragon, food=Chinese, price=cheap)
+
<name> is a <price>-ly priced restaurant serving <food> food
=
Golden Dragon is a cheaply priced restaurant serving Chinese food.

- Statistical approach: **seq2seq**/pretrained language models
 - input: system dialogue act, output: sentence (operation similar to →)

4. End-to-end models

End-to-End Systems

- experimental, research state-of-the-art
 - but not ready for practical deployment
- the whole system (NLU/DM/NLG) is a single neural network
 - joint training (“end-to-end”)
 - more elegant
 - potentially easily retrainable
- typically still needs annotation
 - same as individual modules
 - can be less predictable
- connecting the database is a problem
 - typically this step is done separately




(Wen et al., 2017)

<https://www.aclweb.org/anthology/E17-1042/>

End-to-end vs. separate components


- Traditional architecture – separate components:

- more flexible (replace one, keep the rest)
- error accumulation
- improved components don't mean improved system
- possibly joint optimization by RL
- more explainable



- End-to-end:

- joint supervised optimization, RL still works
- still needs DA-level annotation
- typically needs a lot of data
- less control of outputs: hallucination, dull/repetitive



Seqquicity: Two-stage Copy Net

(Lei et al., 2018) <https://www.aclweb.org/anthology/P18-1133>

- fully **RNN/seq2seq**-based, not much structure
 - still explicit dialogue state
 - DB is external (as in most systems)
- operation:

1) encode


- previous dialogue state
- prev. system response
- current user input

2) decode new dialogue state first

- attend over whole encoder

3) decode system output (delexicalized)

- attend over state only
+ use DB output (one-hot vector added to each generator input)
 - DB: 0/1/more results – vector of length 3
- **delexicalized** decoding: use placeholders (replaced based on full DB result)




End-to-end Dialogue with GPT-2

(Peng et al., 2021)
(Hosseini-Asl et al., 2020)
(Ham et al., 2020)
(Yang et al., 2021)

<http://arxiv.org/abs/2005.05298>
<http://arxiv.org/abs/2005.00796>
<https://www.aclweb.org/anthology/2020.acl-main.54>
<http://arxiv.org/abs/2012.03539>

- Multiple recent DSs are based on GPT-2 (SOLOIST, UBAR, SimpleTOD, NeuralPipeline)
 - decoder-only PLM
- Similar to Sequicity, everything recast as sequence generation
 - dialogue context, belief state, database outputs represented as sequences
 - GPT-2 **prompting**: force-decode some input (ignore softmaxes, feed your tokens)
 - allows attention over it, conditions following text
 - essentially works like an encoder
- Multi-step operation:
 - 1) prompt with context & decode belief state
 - 2) query DB (external)
 - 3) prompt with DB output & decode response



AuGPT: Our take on this approach

(Kulhánek et al., 2021)
<http://arxiv.org/abs/2102.05126>

- Same idea as ↑, multiple improvements

- Operation:

- 1) context → belief state

- prompt w. context & user utterance
- greedy decoding of state
- text-like belief state representation

- 2) belief state → DB


- text-like DB results

- 3) DB → response





- top-p sampling (diversity)
- delexicalized (slot placeholders)

- Training:

- belief/response prediction + consistency (Y/N)



- **Additional training task** – generating & classifying at the same time
 - additional classification layer on top of last decoder step logits
 - incurs additional loss, added to generation loss
- Aim: **robustness** – detecting problems
 - **½ data artificially corrupted** – state or target response don't fit context
 - prev. work: corrupted state sampled randomly
 - **AuGPT**: corrupted state sampled from the **same domain** – **harder!**

context	state	response	consistent?
i want a cheap italian restaurant	{ price range = cheap , food = Italian }	ok which area ?	
i want a cheap Italian restaurant	{ price range = cheap , food = Italian }	thanks, goodbye !	 bad response
i want a cheap italian restaurant	{ destination = Cambridge , leave at = 19:00 }	ok which area ?	 bad state
i want a cheap italian restaurant	{ area = north , food = Chinese }	ok which area ?	 bad state (same domain)



new in AuGPT

- **Data augmentation** via backtranslation (en \rightarrow xx \rightarrow en)
 - MT between English and 40 languages from the ELITR project (<https://elitr.eu/>)
 - we chose 10 best languages
 - user inputs chosen at random from **original & 10 backtranslated texts**
- **Data cleaning**
 - checking consistency of user goal with database
 - ~30% MultiWOZ data discarded
- **Unlikelihood loss** for output diversity
 - repeated tokens are penalized
- **Sampling** for output diversity

MinTL: Diff dialogue states

(Lin et al., 2020)
<https://aclanthology.org/2020.emnlp-main.273/>

- 2-step decoding, same as \uparrow
 - based on T5 or BART here
 - explicit 2 decoders (for state, for response)
- “Levenshtein states”
 - don’t decode full state each time
 - **just decode a diff** (“Levenshtein distance from previous”)
 - better consistency over dialogue



DB queried based on updated state
response decoder starting token = # of DB results


Training end-to-end systems: RL?

- Supervised
 - sometimes components still trained separately
 - e.g. hard knowledge base lookup
 - sometimes all in one
 - can't learn from users
 - problems with train-test mismatch
- RL
 - can learn from users, can learn all-in-one
 - doesn't work great if done on word-level
 - RL doesn't care about fluency/naturalness
 - either avoid word-level, or mix with supervised

<https://www.independent.co.uk/life-style/gadgets-and-tech/news/facebook-artificial-intelligence-ai-chatbot-new-language-research-openai-google-a7869706.html>


```
Alice : book=(count:3 value:1) hat=(count:2 value:1) ball=(count:1 value:5)
Bob   : book=(count:3 value:0) hat=(count:2 value:0) ball=(count:1 value:10)
-----
Bob   : i can i i everything else . . . . .
Alice : balls have zero to me to me to me to me to me to me to me to me to
Bob   : you i everything else . . . . .
Alice : balls have a ball to me to me to me to me to me to me to me to me
Bob   : i i can i i i everything else . . . . .
Alice : balls have a ball to me to me to me to me to me to me to me to me
Bob   : i . . . . .
Alice : balls have zero to me to me to me to me to me to me to me to me to
Bob   : you i i i i i everything else . . . . .
Alice : balls have 0 to me to me to me to me to me to me to me to me to
Bob   : you i i i everything else . . . . .
Alice : balls have zero to me to me to me to me to me to me to me to me to
```

<https://towardsdatascience.com/the-truth-behind-facebook-ai-inventing-a-new-language-37c5d680e5a7>




Facebook abandoned an experiment after two artificially intelligent programs appeared to be chatting to each other in a strange language only they understood.

- Making system actions latent, learning them implicitly
- **Discrete latent space** here (M k -way variables)
 - using Gumbel-Softmax trick for backpropagation
 - trained using Full ELBO (KL divergence vs. a prior network) or “Lite ELBO” (KL divergence vs. uniform)
- RL over latent actions, not words
 - avoids producing disfluent language
 - **corpus-based RL**
 - generate outputs, but use original contexts from a dialogue from training data
 - success & RL updates based on generated responses
- ignores DB & state tracking
 - takes gold annotation from data (assumes external model for this)



- Similar to (\uparrow), but tries word-level RL
 - corpus-level RL
 - RNN architecture
 - dialogue state not tracked
- hierarchical RL:
 - **top level:** latent actions, like LARL
 - latent actions Gaussian here
 - standard reward based on success
 - **bottom level:** words
 - reward based on fluency
 - language model probability
 - both rewards weighted (word level much lower)
 - levels updated asynchronously



5. Evaluation

- Task: take real dialogue history from corpus + **generate 1 response**
 - repeat over whole dialogue, collect responses
- Metrics:
 - **Inform rate** – last offered entity matches user constraints
 - **Success rate** – \uparrow + system provided all requested information about it
 - **Joint goal accuracy** – % turns where all user constraints are captured correctly
 - **BLEU** – n-gram precision (matching sub-phrases of 1-4 words against reference)
- Problems:
 - really artificial setting, but easiest to use (just need test data)
 - Inf/Succ/JGA: matching the provided entities (more ways to do it)
 - BLEU: tokenization, measuring over delexicalized text

Simulator Evaluation

- **User Simulator** – works as a user, tries to follow goals
- **Dialogue-level** – good over 1 turn \neq good over whole dialogue
 - especially for end-to-end systems, errors may accumulate over time
 - simulator is the only automatic way to assess this
- Main metric: **Success rate**: was the simulated user's goal reached?
 - i.e. did the system give a correct entity & all information
 - technically same as corpus-based, but now over real dialogues
- Problems:
 - the simulator needs to be built for a given domain
 - it's essentially another dialogue system (👤 x 🤖)
 - simulator behavior will bias the evaluation

Human Evaluation

Metrics (objective – measuring):

- **Task success** (boolean): did the user get what they wanted?
 - (paid) testers with known goal → check if they found what they were supposed to
 - [warning] sometimes people go off script
 - basic check: did we provide any information at all?
- **Duration**: number of turns (fewer is better)

Metrics (subjective – questionnaires):

- **Success rate**: Did you get all the information you wanted?
 - typically different from objective measures!
- **Future use**: Would you use the system again?
- Component-specific questions

System	# calls	Subjective Success Rate	Objective Success Rate
HDC	627	82.30% (± 2.99)	62.36% (± 3.81)
NBC	573	84.47% (± 2.97)	63.53% (± 3.95)
NAC	588	89.63% (± 2.46)	66.84% (± 3.79)
NABC	566	90.28% (± 2.44)	65.55% (± 3.91)

(Jurčiček et al., 2012)

<https://doi.org/10.1016/j.csl.2011.09.004>

Final Remarks

Further Research Areas

- Multi/open domains
 - reusability, domain transfer
 - training from little data
 - using less annotation
 - connecting task-oriented systems and chatbots
- Context dependency
 - understand/reply in context (grounding, speaker alignment)
- Incrementality
 - don't wait for the whole sentence to start processing
- Evaluation
 - neural-net-based metrics

Multimodal/Visual Dialogue



- adding other modalities
- specific components
 - parallel to NLU
 - vision – image classification networks
 - face identification/tracking
 - parallel to NLG
 - mimics/gesture generation
 - gaze
 - image retrieval
- vision – typically CNN
 - often off-the-shelf stuff
- specific classifiers/rules



C: A dog with goggles is in a motorcycle side car.
Q: Is motorcycle moving or still?
A: It's parked
Q: What kind of dog is it?
A: Looks like beautiful pit bull mix

Q: What color is it?

<http://demo.visualdialog.org/>



The screenshot displays a multi-panel interface. On the left, a 'Console' window shows a log of system messages. In the center, a 'Situation Map' visualizes the spatial relationships between agents (agent-1, agent-2) and objects (table, system) in a 3D environment. On the right, a video feed shows a person wearing a VR headset. Below these, a timeline of events is visible. At the bottom, a chat window shows a conversation between a 'SHOPPER' and an 'AGENT'.

SHOPPER: Hello
AGENT: Hi, please tell me what i can help you with today?
SHOPPER: show me few of your top large sized rubber type upper material clogs that is mostly light pink in colored that i would like .
AGENT: Of course. Just wait a few seconds while i browse through my catalog
AGENT: Sorry i dont have any in pink but would you like to see some in

And what is your name?
My name is Raveesh



other color

SHOPPER: Please show me something similar to the 1st image but in a different upper material

AGENT: The similar looking ones are



SHOPPER: I like the 4th result . Show me something like it but in material as in the 1st image from what you had previously shown me in clogs

<https://youtu.be/5fhjuGu3d0I?t=137>

<https://vimeo.com/248025147>

(Agarwal et al., 2018)

<http://aclweb.org/anthology/W18-6514>

Thanks

Contact me:

MLSS^N Slack
in person till tomorrow
odusek@ufal.mff.cuni.cz

**I'm looking for a postdoc
& will be looking for PhD students
(know someone?)**

<http://ufal.cz/ng-nlg/postdoc>

Get the slides here:

<http://ufal.cz/ondrej-dusek/bibliography> (under “Talks”)

References/Inspiration/Further:

Apart from materials referred directly, these slides are based on slides and syllabi by:

- Pierre Lison (Oslo University): <https://www.uio.no/studier/emner/matnat/ifi/INF5820/h14/timeplan/index.html>
- Oliver Lemon & Verena Rieser (Heriot-Watt University): <https://sites.google.com/site/olemon/conversational-agents>
- Filip Jurčiček (Charles University): <https://ufal.mff.cuni.cz/~jurcicek/NPFL099-SDS-2014LS/>
- Milica Gašić (University of Cambridge): <http://mi.eng.cam.ac.uk/~mg436/teaching.html>
- David DeVault & David Traum (Uni. of Southern California): <http://projects.ict.usc.edu/nld/cs599s13/schedule.php>
- Luděk Bártek (Masaryk University Brno): <https://is.muni.cz/el/1433/jaro2018/PA156/um/>
- Gina-Anne Levow (University of Washington): <https://courses.washington.edu/ling575/>

Recommended Reading

Best:

- Jurafsky & Martin: Speech & Language processing. 3rd ed. draft 2021, Chap. 24 (+23, 25, 26) (<https://web.stanford.edu/~jurafsky/slp3/>) – relatively brief intro, good for rest of NLP too!
- McTear: Conversational AI. Morgan & Claypool 2021. (<https://doi.org/10.2200/S01060ED1V01Y202010HLT048>) – a bit more advanced & focused, pretty new
- Gao et al.: Neural Approaches to Conversational AI, 2019 (<http://arxiv.org/abs/1809.08267>) – more advanced, slightly outdated
- Sutton & Barto: Reinforcement Learning: An Introduction, 2018 (freely online) – specifically on RL, pretty advanced
- recent papers from the field (linked on individual slides)

Also good (but more outdated):

- McTear et al.: The Conversational Interface: Talking to Smart Devices. Springer 2016.
- Jokinen & McTear: Spoken dialogue systems. Morgan & Claypool 2010.
- Lemon & Pietquin: Data-Driven Methods for Adaptive Spoken Dialogue Systems. Springer 2012.
- Rieser & Lemon: Reinforcement learning for adaptive dialogue systems. Springer 2011.