Automated protein design to disrupt disease-relevant protein-protein interactions

Michael Uckelmann
Hubrecht Institute, Uppsalalaan 8, 3584 CT Utrecht, The Netherlands

Abstract

Integrating the reasoning capabilities of large language models with deterministic tools for protein structure analysis and protein design can facilitate reliable automated protein binder design. Furthermore, providing the language model with access to a curated scientific literature database can in principle serve detailed niche knowledge to the model that is not readily available from the trained weights. Here we present a framework based on LLM agent skills with access to protein design software, that is backed by a literature backbone consisting of thousands of scientific papers digested into key findings stored in a vector database for semantic search. The framework allows fully automated design campaigns from a one-sentence natural language prompt provided by the user. Example campaigns show that binders designed against disease-relevant protein-protein interactions can be generated with good in silico success rates from a fully automated pipeline.

Introduction

Large language models (LLMs) have rapidly improved over the past years, to the extent that they are now routinely used for knowledge-based scientific work involving information retrieval, analysis and reasoning over the analyzed information[1–3]. Providing models with access to deterministic computational tools is a particularly powerful approach to combine the models reasoning capabilities with reliable computations. Some limitations remain: training knowledge is bounded by the data available at the training cutoff date, training knowledge embedded in the parameters of general purpose models is necessarily very broad and recall of accurate detailed information (e.g. affinities between two proteins) from training knowledge alone is often not possible, models occasionally “hallucinate” and provenance of information is not always assigned accurately. Especially in the scientific domain accurate reasoning over specialist knowledge is key, small details can matter substantially and assigning provenance is important for credibility. Providing LLM agents with access to databases holding domain-specific scientific knowledge can ground the models responses in established fact and giving access to code-based programmatical tools can help make routine tasks reproducible and analyze data deterministically where advantageous. Recent attempts at building specialized LLM frameworks for the scientific domain show that combining deterministic code, accurate databases and reasoning capabilities of LLMs can significantly improve the model’s performance at scientific tasks[1–3].

In parallel to the advances in LLMs, accuracy and speed of diffusion models for protein structure prediction and protein structure generation (protein design) improved significantly as well[4–13]. These models now enable generation of protein binders for a given target protein that have a relatively high experimental success rate. Frameworks such as Bindcraft[11], ProteinHunter[12] or NISE[14] consolidated multi-step design tasks using multiple design tools into reproducible pipelines. The recently released chaperone framework attempts to integrate multiple design tools with lightweight abstraction layers to improve interoperability and enable use by LLM agents[15].

Here we explore if a structured framework, that provides LLMs access to a curated literature database and deterministic coding tools for protein structure analysis, enables reliable end-to-end automation of protein design tasks starting from natural language prompts.

Results

The Little Protein Tiger (LPT) is a framework for automated design of protein-protein interaction inhibitors with fixed orchestration of LLM stages. Each LLM stage has access to a set of tools written in python code (Table 1) and runs a bounded agentic loop within a narrowly defined task. The pipeline intentionally limits LLM freedom and urges use of code-based tools wherever possible with the aim of making the output more reliable and controlling token usage. The LLM stages currently support API calls to Anthropics Claude models, OpenAI models and Google's Gemini models, as well as querying local models via Ollama. The complete pipeline runs through different phases that take a user's prompt, read the design intent, select an appropriate target protein, analyze the biology surrounding the target, select a structure, analyze it and run a protein design campaign to design mini-proteins or macrocyclic peptides meant to inhibit the targeted protein-protein interaction (Fig.1). The different LLM stages of the pipeline all have a distinct system prompt (”skill”, Supplemental Information 1) that defines their task and sets out stages to achieve it. Along with the system prompt, either the user input or a structured handoff in JSON format from the previous stage is passed to the LLM. The target selection phase consists of two LLM stages, “pathway” and “literature”. Prompts to the target selection phase can be broad (e.g. “Design immune checkpoint inhibitors.”, Supplemental Information 2). The pathway-expert skill is tasked to understand the design intent and select an appropriate target. It has access to a custom-built literature database and tools to query the database. The second LLM stage, uses the molecular-biology-expert skill as system prompt, provides a more thorough analysis of the chosen target, the surrounding molecular pathways and currently available inhibitors. It suggests specific target sites based on literature and a PDB structure to design against. It is encouraged to make frequent calls to the literature database. The pipeline then moves to the structure analysis phase. The complex-structure-analysis LLM skill is tasked to pick a PDB structure, run a comprehensive protein structure analysis and determine the most suitable amino acid residues to be targeted (hotspot residues). The target decision along with the structure file and the chosen hotspot residues are then relayed to the design phase. The design stage needs GPU access (local workstation by default) and runs diffusion models for protein design and protein structure prediction for quality control and scoring. It starts with a small scale pilot and calibration runs to size the production run scale. It then executes the production run at the determined scale, analyzes results, ranks designs and provides a final summary of the campaign. In the following, the different modules of the pipeline and the literature database are discussed in detail.

A literature database as a knowledge backbone

The pathway and literature stage have access to a curated scientific literature database that serves as the knowledge backbone of the pipeline. The LLMs are asked to use this database as a source of information during reasoning. The aim is to provide the models with access to accurate information and assign provenance to the findings. The database is constructed by user-defined keyword queries to NCBI PMC, Europe PMC and Semantic Scholar.




Figure 1: *Flow chart illustrating the different stages of the pipeline. An end-to-end run is orchestrated by a pipeline runner and moves through all five stages automatically. Stages are resumable. The literature database is built independently and can be expanded.*

Search results are indexed and stored in a SQLite database. For papers published in journals matching a user-defined journal tier list, the PDFs are downloaded, if available, with XML as a fallback option.
To make paper content accessible and searchable for the later LLM stages, each paper is curated into a fingerprint using an LLM curator. The curation prompt (Supplemental Information 3) is used as the system prompt in the LLM call and the paper contents are processed with PyMuPDF. Only text and figure captions are considered, figures themselves are not processed. The LLM is tasked to understand the key findings from the paper and extract supportive quantitative and qualitative evidence for each key finding. It is asked to analyze the molecular pathway context, assess negative and/or contradictory results, extract method details, PDB structure identifiers and the proteins studied, determine which proteins interact according to the paper and find affinities, if measured. Finally, the curation skill writes a context hook summarizing the main findings of the paper (Supplemental information 4 for three example fingerprints[16–18]). The curation skill is tasked to emit the fingerprints in a structured json format with strict formatting guidelines. Guidelines are enforced via a Pydantic evaluation-correction loop during the curation call. From all interacting protein pairs that have been identified across all papers in the literature database, an interaction graph is built. Proteins are the graph nodes. The edges carry mention counts of the interaction with supporting DOIs and affinity information; all reported kd and ki values for the pair with citation (DOI), location in the source and experimental context. The skills can further export a subgraph where correlations across the DepMap CRISPR gene effect dataset[19] get added to the edges (Fig.2A). The fingerprints are encoded into vectors using PubmedBERT embeddings[20] and stored in a LanceDB vector database. LLM skills can access the fingerprints via tools that query the vector database. The database is also directly accessible via the conversational corpus-explorer skill

To assess if, and how, access to the literature database improves LLM responses we ran several ablation tests. We prompted the pathway expert, using Gemini Flash 3.7 as the model, with 7 different prompts in three different arms. The first arm used the standard pathway skill with access to all regular tools and the literature database. The second arm used a “wildcard” skill. This skill encourages the LLM to reason over information contained in the literature database and from DepMap correlations, as well as promoting more tool usage. In particular, the skill is encouraged to query the interaction graph and reason along edges (Fig.2A). The third arm resembles a straight LLM API call without any tool usage, the system prompt was an adapted pathway expert system prompt where all tool-use phases were replaced by one phase stating "no tools, work from your own knowledge" (full prompts and replies in Appendix I). Three replicates of the seven prompts were run for each setting to assess internal variability. Two different LLMs, claude-sonnet-5 and gpt-5.6-terra, were then tasked to judge the outputs according to a grading rubric. Each criterion was scored with a grade of 1-5 (1= poor or wrong, 5= excellent,specific and correct, Appendix I). We do not pose a verdict on the quality of the chosen targets and it should be noted that the judging models themselves might be steered by their training knowledge.




Figure 2. Ablation studies and different skills test the impact of the literature database. An illustration *of the interaction graph that the LLMs can query via toolset C. Rendering of information contained in the interaction graph built from the literature database. Nodes are proteins, edges indicate interaction and carry affinity information and number of times this interaction is mentioned in*

the database. The illustrated graph only shows a limited number of nodes, edge thickness corresponds to number of mentions of the interaction, color hue corresponds to DepMap Pearson correlation of the pair across the DepMap CRISPR gene effect dataset. The graph only considers protein pairs included in the database. ***B*** *Response scores for the standard pathway expert skill and the wildcard expert skill as judged by Claude Sonnet 5.0 and OpenAI terra. Scores are shown relative to a run where the LLM did not have access to any tools (no-tools arm). Seven different prompts were given, three replicates per prompt, for a total of 21 responses for each arm. Each point is averaged over a prompt's repeats and then over all seven prompts. Bar indicates 95% bootstrap interval (3000 iterations, reports were resampled with replacement within each prompt and arm)* ***C*** *Comparison of tool calls between the standard pathway expert skill and the wildcard skill. Mean calls per run and total runs where the respective tool was called are shown.*

On target rational, calibration, prior art and usefulness the responses score similarly (Fig.2B), skills with access to tools score marginally better than the no-tools arm. Traceability is the one category where corpus access leads to substantial improvements. This is expected, models in the arm without corpus access are asked to cite only if certain, but still shows that access to a database can improve provenance assignment. There is substantial overlap in the targets chosen between the different trials (Table 2), which may suggest that suitable targets for these prompts can be picked straight from training knowledge or that training knowledge dominates decision making. The wildcard skill chose the most varied targets, reflecting its instructions. The extensive tool-calling of the wildcard skill (Fig.2C) indicates that the skill accesses information contained in the database frequently. If this information improves target choice remains untested and we expect that a more comprehensive database would be necessary to take full advantage of the possibilities afforded by the tools.

To test if the LLM can retrieve detailed information from the literature database that is not immediately accessible through training knowledge, we ran closed-book and open-book exams using the corpus-explorer skill (Box 1), with Gemini 3.7 Flash as the model. We chose 48 questions where the accurate answer is contained in the literature database fingerprints, including questions about specific affinities between proteins, specific residues involved in protein-protein interactions and about recent findings. In the open book case the expert skill had access to the LPT literature tools and database, in the closed book case not. The models were allowed to answer with “unknown” if they did not know the answer to a question. In the open book case the model answered correctly 41 times and answered “unknown” 7 times. In the closed book case the model never answered correctly, answered "unknown" 47 times and answered wrong once.
The complete exam with all questions and answers is provided in Appendix II. The test was necessarily biased towards information that was contained in the database and some questions were leading. Nonetheless, it shows that inclusion of a carefully curated literature database allows the LLM stages to find information not readily accessible from training knowledge.

To summarize, the literature database contains accurate information from scientific publications digested into fingerprints and organized for LLM-friendly access in a vector database. Information can be retrieved accurately by the different LLM skills and the skills make use of the database during their reasoning stages.

Box 1: Example questions and answers of the open/closed book test

"What dissociation constant (Kd) has been reported for the interaction between scFv6 and TcdB? Context: SPR analysis and cryo-EM structure determination of combinatorially assembled scFvs. Give one value with units."

*Answer: 72 nM. This value is reported from surface plasmon resonance (SPR) measurements of the *de novo* designed scFv6 binding to the Frizzled-binding epitope of *Clostridium difficile* toxin B (TcdB) in a study detailing antibody design using RFdiffusion (DOI: 10.1038/s41586-025-09721-5).*

A 2026 study examined ARX and PTPRD. Context: CRISPRi screen across 44 TFs. What did it report?

Answer: PTPRD is a convergent downstream effector gene regulated by ARX (and other transcription factors) that is enriched for neuropsychiatric disorder (schizophrenia/SCZ and major depressive disorder/MDD) risk genes ($P < 0.05$).
This comes from a 2026 single-cell CRISPRi (Perturb-seq) screen evaluating 44 transcription factors in human radial glia during cortical neurogenesis (DOI: 10.1038/s41586-025-09997-7). Convergent downstream effectors like PTPRD showed significant enrichment for neuropsychiatric disease-associated gene sets by Fisher's exact test.

End-to-end orchestration of protein inhibitor design from a single prompt

The whole pipeline is best illustrated by following one specific example throughout all the stages. The examples shown here are taken from an actual run that proceeded end-to-end (Supplemental Information 5 for all generated stage reports). In this example case, the only input was one prompt:

Prompt: "Design novel inhibitors for pain receptors that are promising drug targets."

In the first stage of the pipeline, this prompt is passed via an API call to the chosen LLM (gemini-3.7-flash in this case) along with the pathway-expert skill (Supplemental Information 1) as system prompt. The model is tasked to understand the disease context, pathways implicated in the disease, the disease mechanism and pathway dysregulation. It has access to all tools that interact with the literature database (Table 1). In the specific example, it categorizes the disease context as *"Chronic and inflammatory nociceptive pain"*, identifies key receptor-driven pathways involved and possible target nodes. The skill assessed the different target nodes for suitability and recommended to disrupt CALCRL-RAMP1 interaction. The decision was based on validated efficacy in pain and neurovascular

inflammation, a solvent-exposed extracellular domain and a high-quality experimental structure of the complex (Supplemental Information 5). Claims are supported by accurate citations from the literature database throughout[21–32]. It provides a structured handoff with the target choice, structure suggestion and alternative targets to the next phase.
In between the first two stages the pipeline runs a deterministic step that is meant to improve structure choice. It collects alternative structures from the PDB that contain both chains to be disrupted, then compares them against the original suggestion of the pathway-expert skill. It triggers a switch if a better alternative is found. In the example case the presence of three G-proteins and a nanobody in the original choice triggered a switch to a smaller, higher resolution crystal structure.

Stage two accepts the handover and runs the molecular-biology-expert skill. This skill is tasked with a more detailed analysis of the chosen target and the surrounding biology, specifically drawing from information contained in the literature database, with access to all literature tools. It is further asked to analyze known inhibitors and prior art, identify suitable target sites, including key residues, and provide a feasibility assessment. In our specific example, it analyzed the RAMP1-CALCRL heterodimer role in CGRP-dependent pain signaling, highlighted known small molecule, antibody and small peptide inhibitors and identified key residues in the heterodimer interface that should be targeted. It accurately cites supporting evidence drawn from the literature database throughout[23,24,26,28–30]. The structured handoff for the next stage includes the PDB accession code of the selected structure and the suggested residues that should be targeted.

Stage three then runs an analysis of the protein structure to determine the final target site and hotspot residues that get passed to the diffusion models. A code-based tool is run before the LLM stage to prepare the structure. The tool downloads the structure file (if not on disk) and checks the chain identities. It generates a chain table that includes entity description and protein residue counts for each chain, computes buried surface area (BSA) and estimates H-bonds for every chain pair that involves the target protein. This information then gets combined with handoff from the previous stage into a prompt for the subsequent LLM stage.

The combined prompt gets passed to the structure analysis LLM stage, with the complex-structure-analysis skill as the system prompt. The skill runs through an agentic loop, calling different tools to analyse the given complex structure. In a first phase the tool calls return an analysis of the interaction interface including residue- and interface-level BSA, H-bonds between interface residues, per-chain interface residues with per-residue information: residue type, hydrophobicity, contacts and an estimated binding contribution $\boldsymbol{\varepsilon}$. The model then groups residues into clusters based on shared contacts (about 10 residues per cluster).
Phase two calls a tool that analyzes the clusters and returns hydrophobic fraction, spatial spread of the residues and a suitability rating. The model then chooses the most suitable target patch (tight clustering, hydrophobic anchors, disrupts target interface) and runs a literature cross-check against the literature database to assess what, if anything, is known about the chosen hotspot residues. Finally the skill generates residue hotspot lists in the appropriate format for RFD3[4] and boltzgen[6]. In the example case, the skill determined two suitable target regions and chose region 1, a 10-residue patch with high aromatic density that spans the core heterodimerization surface on RAMP1 (Fig. 3A).

The chosen hotspots are then passed to the actual design phase. Hotspot and chain information are translated into the appropriate input format for the chosen design backend, RFD3 in the example case. All GPU-bound stages in the example case were run on a local workstation with a NVIDIA RTX Pro 4500 Blackwell GPU. LPT also supports staging of cluster runs and computing via Modal. Every design phase runs a 5-step program: (1) Diffusion with RFD3[4]; (2) A prefilter stage that removes designs with clashes, chain breaks or those with little secondary structure; (3) Sequence re-design with solubleMPNN[33]; (4) Refolding with RoseTTAFold3[34]; (5) Scoring of the refolds. This sequence is repeated at different scales: pilot, calibration and production. The pilot runs at 100 designs to determine timing and prefilter pass rate. Calibration runs at a scale of 580 backbones, 4 sequences for each prefilter survivor, to determine hit rate for successful designs. Criteria for a successful design are: iPTM > 0.7, no clashes, dock RMSD ≤ 5 Å, fold RMSD ≤ 2 Å, binder pLDDT ≥ 0.75, interface PAE ≤ 15 Å, hotspot engagement ≥ 0.75. Based on the calibration, the production run scale is set to reach 50 successful designs. In the example case the hit rate was particularly high, which triggered an automatic raise of the iPTM target to >0.85.
The example production run produced 1396 refolded designs. The designs considered successful according to the criteria described above are then scored. The surviving designs are ranked with a combination of a composite z-score, iPTM and iPSAE (Supplemental Information 6). An optional Rosetta[35,36] stage can add Rosetta interface energy (ddG), Rosetta contact molecular surface and a penalty for buried unsatisfied polar residues. Top scoring designs from two end-to-end runs show good hotspot engagement, cover the targeted site and have promising in silico scores (Fig.3). The second end-to-end campaign started with the prompt “Design immune checkpoint inhibitors.". In this campaign the model chose to design binders against PD-L1 to disrupt interaction with PD-1 (Figure 3B, Supplemental information 2). The in silico success rates for designs to pass all hard gates and iPTM ≥ 0.7 was 17.9% for the RAMP1 campaign and 9.6% for the PD-L1 campaign. Costs for the campaigns were $0.33 and $0.42 in LLM API credits and ~11 h and ~34 GPU hours on the local workstation, respectively.

Alternative entry points

Next to end-to-end runs starting from one natural language prompt, the pipeline also supports alternative entry points. If the user knows which target to design against, they can provide the gene name as a query and enter the pipeline via the flag “--workflow binder”. The LLM stages for target selection and literature analysis are skipped in this case and the pipeline moves immediately to picking a structure and analyzing it. The user can also provide a structure file directly, in which case the pipeline starts with analyzing this structure. GPU stages remain the same across all entry points. The LLM skills can be run in isolation as well, via the CLI with a user-defined query. The literature database can be queried directly via a conversational LLM loop.




Figure 3: Binders generated from a single natural language prompt pass in silico filters. ***A*** *Results of the pain receptor prompt end-to-end run. The two leftmost structures show the complex to be disrupted (PDB 3N7S[37]) and the model-chosen hotspot (gold). The four structures on the right show the highest ranking designs.* ***B*** *As in* ***A*** *but starting from the immune checkpoint prompt, the chosen target is a PD-L1/PD-1 complex (PDB 4ZQK[38]).*

Discussion and limitations

The presented framework illustrates how integrating LLM reasoning with custom tools for protein design, backed by a literature database, can successfully drive an automated protein design campaign to disrupt disease-relevant protein-protein interactions. Multiple recent efforts have proposed LLM-based workflows to automate and accelerate scientific discovery[1,2,15,39] and the recently released protein design model RFD4-Proteina[40] was built with agentic workflows in mind. Anthropic has shown that Claude, with unlimited token usage and a GPU budget of $10000, can design binders against multiple different disease-relevant targets[41]. Our own end-to-end campaigns cost $0.33 and $0.42 in LLM API credits and ~11 h and ~34 GPU hours using the local workstation (pain receptor prompt and immune checkpoint campaign, respectively). We have not evaluated the experimental success rate for our pipeline and can only provide in silico metrics as a proxy for success, but the published success rates for RFDiffusion with similar in silico filters appears to be high[4,5]. Somewhat surprisingly, we noticed that safety refusals were triggered when we attempted to use our pipeline with Claude Sonnet to design against three of the targets that Anthropic used in their campaign[41], suggesting the published approach was not readily reproducible with the publicly available models when we tested.

The literature knowledge backbone of our pipeline is limited by the database size and we would expect the model's target picks to improve/become more varied with access to a larger database. The example campaigns were run with a database size of ~14000 papers, the released database is smaller because it is limited to papers with licences that allow redistribution of derivatives. Though we can't comprehensively assess if the presence of the database leads to better target choices, it does enable access to detailed quantitative information that is not readily accessible from training knowledge and can supply novel information from after the training cutoff date. It also enables accurate tracking of sources and assigning provenance to claims.

Our pipeline is not reliant on any one LLM provider, other models than the ones used can be integrated with minimal effort. Similarly, the diffusion and refolding backends can be swapped with little effort, especially if standardized communication frameworks between design software and LLM agents, like the recently developed "chaperone"[15], become the norm. Automated protein design frameworks like the one we presented, combined with lab automation, have the potential to significantly accelerate hypothesis generation, testing and lead generation in the early stages of drug discovery.

Table 1. Tools available to the pipeline skills

	Tool	What it does	Data source	Pathway / wildcard	Literature	Structure / interface	Target intel
A	search_corpus	Semantic search over curated papers; returns fingerprints	vector index of fingerprints	●	●	●	●
	get_fingerprint	Full fingerprint of one paper (findings, methods, entities)	fingerprint JSON	●	●	●	●
B	get_interactions_for	All partners of a protein reported in the corpus	literature graph	●	●	●	●
	find_quantitative_evidence	Every measured Kd / Ki for a pair, tightest first	fingerprint findings	●	●	●	●
C	shortest_interaction_path	Shortest paths between two proteins, with evidence	literature graph	●	●	·	·
	interaction_hubs	Highest-degree proteins, filtered by mentions	literature graph	●	●	·	·
	export_subgraph	Neighbourhood around seeds as Cytoscape JSON	literature graph + DepMap	●	●	·	·
	novelty_signal	Prior-art score from four corpus counts (1 = unstudied)	fingerprints + graph	●	●	·	·
	get_genetic_codependency	CRISPR co-essentiality r between two genes	DepMap Chronos	●	●	·	·
	find_cocorrelated_genes	Top co-essential and anti-correlated genes	DepMap Chronos	●	●	·	·
	cluster_for_protein	Co-functional cluster containing a protein	clusters (Louvain)	●	●	·	·
	cluster_members	Members, hub and edges of one cluster	clusters (Louvain)	●	●	·	·
	find_clusters_by_keyword	Clusters whose members match a substring	clusters (Louvain)	●	●	·	·
D	find_pdb_structures	PDB entries the corpus links to a protein	fingerprints + RCSB metadata	●	·	·	●
	search_rcsb_pdb	Full-text RCSB search; fallback when corpus has none	RCSB PDB	●	·	·	●
E	resolve_protein_identifier	Gene symbol or alias to human UniProt	bundled ID tables (offline)	·	·	·	●
	find_complex_structures	PDB entries with this UniProt plus another protein	RCSB PDB	·	·	·	●
F	tool_analyze_interface	Buried area, contacts, H-bonds between two chains	structure file	●	●	●	●
	tool_get_residue_contacts	All contacts of one residue with a partner chain	structure file	●	●	●	●
	tool_check_mutation_clash	Clash estimate for a point mutation (C-beta)	structure file	●	●	●	●
	tool_get_sequence_map	Chain sequence with auth / label numbering maps	structure file	●	●	●	●
	tool_score_surface_patch	Spread, hydrophobicity, charge of a residue set	structure file	●	●	●	●
G	tool_find_glue_pockets	Paired pockets flanking an interface (glue mode)	structure file	·	·	●	●

Table 2. Target picks in the ablation studies

Prompt	Rep	Standard pathway	Wildcard v2	No tools
ALT histone chaperones	1	HIRA / ASF1A	ASF1A / HIRA	ASF1A / HIST1H3A
	2	UBN1 / Histone H3.3	UBN1 / Histone H3.3	ASF1A / HIRA
	3	UBN1 / H3.3	HIRA / ASF1A	ASF1A / Histone H3
Epigenetic modifiers	1	EZH2 / EED	Menin / KMT2A	WDR5 / MLL1
	2	EZH2 / EED	EZH2 / SUZ12	WDR5 / KMT2A
	3	EZH2 / EED	MEN1 / PSIP1	EED / EZH2
KRAS, lung adenocarcinoma	1	KRAS / RAF1	SHOC2 / KRAS	KRAS / RAF1
	2	KRAS / RAF1	SHOC2 / KRAS	KRAS / RAF1
	3	KRAS / RAF1	SHOC2 / KRAS	KRAS / RAF1
MASH / MASLD	1	PD-L1 / TGFBR2	*no pick*	TGFB1 / TGFBR2
	2	TAZ / TEAD4	TGFBR2 / 5HCS_TGFBR2_1	TGFB1 / TGFBR2
	3	TAZ / TEAD4	TAZ / TEAD	TGFB1 / TGFBR2
RA cytokine signalling	1	E2F-1 / BRD4	MALT1 / BCL10	IL6 / IL6R
	2	BRD4 / E2F1	MALT1 / BCL10	IL6 / IL6R
	3	TNF / TNFRSF1A	SOCS1 / JAK1	IL6 / IL6R
cGAS-STING	1	STING / TBK1	STING / TBK1	STING1 / TBK1
	2	STING / TBK1	SPSB3 / cGAS	TBK1 / STING1
	3	STING1 / TBK1	STING / TBK1	STING1 / TBK1
Hsp70/Hsp90, tau	1	STUB1 / MAPT	HSPA1A / BAG3	AHSA1 / HSP90AA1
	2	CHIP / tauC3	STUB1 / MAPT	FKBP5 / HSP90AA1
	3	STUB1 / MAPT	STUB1 / MAPT	AHSA1 / HSP90AA1

Code and data availability
The code is available at https://github.com/MichaUckelmann/little-protein-tiger, alongside data from the example campaigns.

Acknowledgements
I want to thank Anastassis Perrakis, members of the Perrakis group and Xiaohu Guo for input and useful discussions in the early stages of the project and Danny Sahtoe and members of the Sahtoe group for input and discussions during the later stages.

Methods

Building and expanding the literature database

The literature database is built by searching NCBI PMC, Europe PMC and Semantic Scholar with user-defined keywords. The search results get indexed and stored with metadata in a SQLite database. Papers get assigned a priority score (score = min(1.0, 0.55 * journal_tier + 0.3 * pub_type + 0.15 * recency + 0.08 * citation_boost)). Journal tier is defined by a journal tier list that can be edited by the user. For papers published in journals that are mentioned in the journal tier list, PDF download is attempted from the AWS PMC open access bucket, with XML download as a fallback option. Downloaded papers can then be curated via an LLM skill (Supplemental Information 3), via the curate_papers.py function. By default Google's gemini-3.1-flash-lite is used as the curation model. The PDF text is extracted with PyMuPDF, figures are not considered, and processed according to the stages outlined in the curation prompt. The requested output is a structured JSON fingerprint with pre-defined fields populated that include the papers key findings with associated evidence, quantitative data, protein-protein interactions measured, PDB codes, a list of protein pairs that interact according to the evidence and negative results. The fingerprint includes a context hook that summarizes the main findings in a short paragraph. Fingerprints are validated by Pydantic during the LLM curation phase and sent back to the model with a Pydantic error if correction is necessary. At the end of a curation run the interaction graph is rebuilt with the new protein interaction information. Fingerprints (excluding numerical fields) are embedded using the PubMedBERT[20] language model into 768-dimensional L2 normalized vectors and stored in a LanceDB. The LLM stages can semantically search the vector database.

Execution of LLM stages

Each LLM stage runs a provider-agnostic agentic loop (Google, Anthropic or OpenAI API). The stage's skill definition (Supplemental Information 1) gets passed as the system prompt, the stage input (either handoff from a previous stage or direct user input) gets passed as the user prompt. Alongside system and user prompt, the model gets access to stage-specific tools to search and retrieve information from the literature database, for graph queries and for protein structure analysis (Table 1). If the model decides to call a tool, this tool gets executed locally and the returns are appended to the conversation. Multiple tool calls are possible (maximum 30 on default). When the model responds without a tool call, this is considered the final response and the stage ends. The final report ends in a structured handoff block. The full report gets saved to disk as a markdown file, the handoff block is parsed for deterministic checks and as input for downstream stages. If safety classifiers are triggered, the run ends with a note.

Tools for LLMs to access to literature database

The LLM stages have access to the information contained in the literature database through various tools, which are described in brief in the following:

Search_corpus. Runs a semantic search over the fingerprint embeddings that are stored in the vector database. It returns the top-k papers by cosine similarity with their DOI, study category and key findings.
Get_fingerprint. Retrieves the whole fingerprint for a given paper.
Get_interaction_for. For a given protein, returns all interacting proteins reported in the literature database, alongside mention counts, supporting DOI, k_i and k_d values
Find_quantitative_evidence. For a given protein pair, returns every measured affinity contained in the literature database
Shortest_interaction_path. Queries the interaction graph built from reported interactions between proteins, based on the literature database. It takes two proteins as input, determines the shortest path between them along the graph, then returns the nodes and edges along that path
Get_genetic_codependency. If DepMap data is available, returns the Pearson correlation of essentiality between two genes.
Find_cocorrelated_genes. Given an input gene, finds all genes co-correlated in the DepMap CRISPR gene effect dataset[19] with a minimum |r| of 0.2 with data in at least 100 cell lines. Returns the top 25 co-correlated genes. The model can override the default parameters.
find_pdb_structure. Finds PDB accession codes for target proteins in the literature database.
Search_rcsb_pdb. Allows directly searching the RCSB PBD if no PDB accession is found in the literature database

Tools for LLMs to access to analyze protein structures

The LLM agent of the structure stage has access to deterministic tools for protein structure analysis implemented with BioPython and Gemmi. These tools, if called by the LLM, execute locally on the downloaded mmCIF or PDB file. The tools return numerical output to the agent. A brief description of the key tools follows.

Tool_analyze_interface. The main tool for interface analysis. Skills are asked to only call it once per complex structure. Given a structure of a protein complex of proteins A and B, it returns the following metrics:
Buried surface area (BSA): BSA is computed by determining the solvent accessible surface area (SASA) for the complex and for the target chains in isolation. SASA is determined by the Shrake-Rupley algorithm[42], rolling a 1.4 A probe over the surface with BioPython default van der Waals radii per atom, 100 test points per atom are summed to residue level. BSA for individual residues is then calculated as SASA of that residue on isolated chains minus the SASA of that residue in the complex structure. Interface BSA is the sum of residue BSA of both chains across the interface.
Interface residues and contacts: Residues belong to an interface if any of the residue's heavy atoms lie within 4.5 A of a heavy atom on the other chain. Residue-residue contacts

are identified using a k-d tree search (SciPy KDTree implementation with default parameters). For each interface residue pair the minimum atom-atom distance and an interaction type is reported. The interaction type is determined based on the residue identities. The possible interaction types are hydrogen bonds, electrostatic attractive or repulsive, hydrophobic, aromatic, polar and van der Waals.
Hydrogen bonds: H-bonds are estimated by distance between two candidate residues N, O or S heavy atoms and rough geometry check. To be considered as forming a h-bond the heavy atoms need to be ≤ 3.2 A and the angle D-A-X needs to be at least 90 degrees (D= donor, A = acceptor, X = the closest heavy atom covalently bonded to the acceptor). This is an estimate of best candidates for hydrogen bonds rather than a rigorous test.
Per-residue ΔΔG estimate $\boldsymbol{\varepsilon}$: For each residue a heuristic ΔΔG, denoted as $\boldsymbol{\varepsilon}$, is estimated using the following terms: -0.028 kcal/mol per Angstrom of buried surface area (only for hydrophobic and aromatic residues), -1.0 kcal/mol per H-bond and -0.5 kcal/mol per attractive electrostatic interaction. Residues below -2.0 are considered good hotspot candidates.
pLDDT: For input from structure predictions the pLDDT is read from the B-factor column and low-confidence parts are flagged.
Tool-_score_surface_patch: Scores a given set of residues for its suitability as a target patch. The spatial spread of the residues is calculated based on C-alpha coordinates. Hydrophobicity for the patch is reported as the mean Kyle-Doolittle value for the given patch. Each residue is assigned a class (aromatic, hydrophobic, charged, polar, other). The hydrophobic fraction is reported as the share of aromatic and hydrophobic residues over all residues of the patch. The suitability ranking is based on fixed cutoffs: “Excellent”: hydrophobic fraction ≥ 0.5, spread ≤ 10 Å and patch size at least 3 residues; “Good”: hydrophobic fraction ≥ 0.3, spread ≤ 15 Å; “marginal”: hydrophobic fraction ≥ 0.2. Everything else is returned as “poor”.

End-to-end pipeline run

An end-to-end run of the whole pipeline is initiated by running a python script:
run_pipeline.py --workflow ppi --query “<*user prompt*>” --project <project name>

After the CLI validates the input, the pipeline runner (pipeline_runner.py) starts up. The default settings are:
Provider: Gemini (gemini-3.8-flash currently, gemini-3.7-flash for most examples presented in the paper),
Pathway mode: standard (“wildcard” optional),
Design engine: foundry (RFD3, solubleMPNN, RF3)
Modality: mini-protein
Agentic loop limit: 30 tool turns
Per-call input ceiling: 150k tokens
The pipeline runner then executes a set of pre-defined phases in sequence (Fig.1), starting with target selection, followed by structure analysis and finishing with GPU-based design phases. The LLM stages all have a fixed token budget (150k tokens by default) and a fixed API budget can be set as well (estimated from the API cost table in the config, make sure it is accurate). By default, each LLM stage is limited to 30 turns of tool-calling. If a safety classifier is triggered, stages stop. The pipeline is resumable from completed stages, if LLM

stages get interrupted within the stage, due to token limits, cost caps or turn limits, they need to be restarted from the beginning.
Communications between stages are handled via structured JSON handoffs, which serve as input to the next stage, alongside the system prompt of the respective stage.

GPU-bound stages

The GPU stages for examples shown in this preprint were run on a local Nvidia RTX Pro 4500 Blackwell with 32 GB memory. The pipeline also supports Modal integration (Modal account necessary) and cluster staging.
The design stage defaults to RFD3 -> solubleMPNN -> RF3. Under default settings, RFD3 runs with diffusion_batch_size: 4, inference_sampler.step_scale=3, gamma_0=0.2, infer_ori_strategy: hotspots, is_non_loopy: true and dialect: 2; MPNN defaults are temperature 0.1, n_seq 4; RF3 runs with template: target, diffusion_batch_size: 1 and Seed 0. The GPU-bound design stage starts with a pilot at a default scale of 100 designs to test the input specifications. If successful, it proceeds to a calibration stage that generates 570 designs, then 4 sequences with solubleMPNN and RF3 refolds. Calibration is used to time the run and measure hit rate. Hits are defined as designs that clear all hard gates:

- Dock RMSD at most 5.0 Å.
- Epitope recall at least 0.5.
- Hotspot engagement at least 0.75.
- Fold RMSD at most 2.0 Å.
- Binder pLDDT at least 0.75.
- iPTM at least 0.5.
- Interface PAE at most 15.
- Minimum contact at least 1.8 Å (no clash).

And additionally clear a success metric, that is by default set to iPTM > 0.7. Additionally, the design aim is set to deliver 50 hits in the production stage and this aim must fit into the budget. The default budget is 5 campaign days (120 GPU hours).
Based on hit rate and timing the calibration stage returns a verdict:
SCALE_UP: At least 5 hits and pessimistic cost fits budget -> Production is sized to the full 50 design goal
SCALE_UP_PARTIAL: at least 5 hits, pessimistic cost exceeds budget by at maximum 1.5-fold -> campaign proceeds at reduced aim if at least 1/10 of the initial aim can be achieved within budget
ITERATE: Fewer than 5 hits or the budget buys less than 1/10 of the initial aim -> pipeline stops and prints options with estimated time and costs.
STOP: no hits

If the pipeline proceeds and the pessimistic timing estimate is under 48 hours, the campaign runs on the local GPU, otherwise a cluster run is staged (if staging is setup).
Final scoring is done based on hard gates and a composite z-score scoring the surviving designs relative to all survivors of the given campaign. Details in Supplemental information 6.

References

1. Zhang, H. G., Eckmann, P., Miao, J., Mahon, A. B. & Zou, J. The Virtual Biotech: A multi-agent AI framework for therapeutic discovery and development. *Science* **394**, eaeg6779 (2026).
2. Ghareeb, A. E. *et al.* A multi-agent system for automating scientific discovery. *Nature* **655**, 497–505 (2026).
3. Gottweis, J. *et al.* Accelerating scientific discovery with Co-Scientist. *Nature* **655**, 487–496 (2026).
4. Butcher, J. *et al.* Atomic functional site scaffolding in biopolymers with RFdiffusion3. *Science* **0**, eaeh2982 (2026).
5. Watson, J. L. *et al.* De novo design of protein structure and function with RFdiffusion. *Nature* **620**, 1089–1100 (2023).
6. Stark, H. *et al.* BoltzGen: Toward Universal Binder Design. 2025.11.20.689494 Preprint at https://doi.org/10.1101/2025.11.20.689494 (2026).
7. Passaro, S. *et al.* Boltz-2: Towards Accurate and Efficient Binding Affinity Prediction. 2025.06.14.659707 Preprint at https://doi.org/10.1101/2025.06.14.659707 (2025).
8. Abramson, J. *et al.* Accurate structure prediction of biomolecular interactions with AlphaFold 3. *Nature* **630**, 493–500 (2024).
9. Krishna, R. *et al.* Generalized biomolecular modeling and design with RoseTTAFold All-Atom. *Science* **384**, eadl2528 (2024).
10. Didi, K. *et al.* Latent generative search unlocks de novo design of untapped biomolecular interactions at scale. 2026.09.12.751118 Preprint at https://doi.org/10.64898/2026.09.12.751118 (2026).

11. Pacesa, M. *et al.* One-shot design of functional protein binders with BindCraft. *Nature* **646**, 483–492 (2025).
12. Cho, Y., Rangel, G., Bhardwaj, G. & Ovchinnikov, S. Protein Hunter: exploiting structure hallucination within diffusion for protein design. 2025.10.10.681530 Preprint at https://doi.org/10.1101/2025.10.10.681530 (2025).
13. Dauparas, J. *et al.* Atomic context-conditioned protein sequence design using LigandMPNN. *Nat Methods* **22**, 717–723 (2025).
14. Fry, B., Slaw, K. & Polizzi, N. F. Zero-shot design of drug-binding proteins via neural iterative selection−expansion. *Nature* **656**, 237–249 (2026).
15. Butcher, J. *et al.* Reliable and Efficient Agentic Protein Design with Toolset Harnessing. 2026.10.19.759896 Preprint at https://doi.org/10.64898/2026.10.19.759896 (2026).
16. Lövestam, S. *et al.* Disease-specific tau filaments assemble via polymorphic intermediates. *Nature* **625**, 119–125 (2024).
17. Ning, B. *et al.* USP26 functions as a negative regulator of cellular reprogramming by stabilising PRC1 complex components. *Nat Commun* **8**, 349 (2017).
18. Santiago-Frangos, A., Jeliazkov, J. R., Gray, J. J. & Woodson, S. A. Acidic C-terminal domains autoregulate the RNA chaperone Hfq. *eLife* **6**, e27049 (2017).
19. DepMap 24Q2 Public. Figshare+ https://doi.org/10.25452/figshare.plus.25880521.v1 (2024).
20. papers/pubmedbert-embeddings/pubmedbert-embeddings.pdf at master · neuml/papers. *GitHub* https://github.com/neuml/papers/blob/master/pubmedbert-embeddings/pubmedbert-embeddings.pdf.
21. Minett, M. S. *et al.* Pain without nociceptors? Nav1.7-independent pain mechanisms. *Cell Rep* **6**, 301–312 (2014).
22. Koui, Y., Song, S., Dong, X. & Mukouyama, Y.-S. Local keratinocyte-nociceptor interactions enhance obesity-mediated painful small fiber neuropathy via NGF-TrkA-PI3K signaling axis. *iScience* **28**, 112047 (2025).

23. Booe, J. M. *et al.* Structural Basis for Receptor Activity-Modifying Protein-Dependent Selective Peptide Recognition by a G Protein-Coupled Receptor. *Molecular Cell* **58**, 1040–1052 (2015).
24. Zirimwabagabo, J.-O. *et al.* Discovery of a First-In-Class Small Molecule Antagonist against the Adrenomedullin-2 Receptor: Structure-Activity Relationships and Optimization. *J Med Chem* **64**, 3299–3319 (2021).
25. Liu, A. *et al.* Light-Inducible Activation of TrkA for Probing Chronic Pain in Mice. *ACS Chem Biol* **19**, 1626–1637 (2024).
26. J Gingell, J. *et al.* An allosteric role for receptor activity-modifying proteins in defining GPCR pharmacology. *Cell Discov* **2**, 16012 (2016).
27. Minett, M. S. *et al.* Endogenous opioids contribute to insensitivity to pain in humans and mice lacking sodium channel Nav1.7. *Nat Commun* **6**, 8967 (2015).
28. Liang, Y.-L. *et al.* Cryo-EM structure of the active, Gs-protein complexed, human CGRP receptor. *Nature* **561**, 492–497 (2018).
29. Pinho-Ribeiro, F. A. *et al.* Bacteria hijack a meningeal neuroimmune axis to facilitate brain invasion. *Nature* **615**, 472–481 (2023).
30. Watkins, H. A. *et al.* Receptor Activity-modifying Proteins 2 and 3 Generate Adrenomedullin Receptor Subtypes with Distinct Molecular Properties. *Journal of Biological Chemistry* **291**, 11657–11675 (2016).
31. Gorokhova, S. *et al.* Uncoupling of Molecular Maturation from Peripheral Target Innervation in Nociceptors Expressing a Chimeric TrkA/TrkC Receptor. *PLOS Genetics* **10**, e1004081 (2014).
32. Tavares-Ferreira, D. *et al.* Spatial transcriptomics of dorsal root ganglia identifies molecular signatures of human nociceptors. *Sci Transl Med* **14**, eabj8186 (2022).
33. Goverde, C. A. *et al.* Computational design of soluble and functional membrane protein analogues. *Nature* **631**, 449–458 (2024).
34. Accelerating Biomolecular Modeling with AtomWorks and RF3 | bioRxiv. https://www.biorxiv.org/content/10.1101/2025.08.14.670328v2.

35. Chaudhury, S., Lyskov, S. & Gray, J. J. PyRosetta: a script-based interface for implementing molecular modeling algorithms using Rosetta. *Bioinformatics* **26**, 689–691 (2010).
36. Leaver-Fay, A. *et al.* ROSETTA3: an object-oriented software suite for the simulation and design of macromolecules. *Methods Enzymol* **487**, 545–574 (2011).
37. ter Haar, E. *et al.* Crystal structure of the ectodomain complex of the CGRP receptor, a class-B GPCR, reveals the site of drug antagonism. *Structure* **18**, 1083–1093 (2010).
38. Zak, K. M. *et al.* Structure of the Complex of Human Programmed Death 1, PD-1, and Its Ligand PD-L1. *Structure* **23**, 2341–2348 (2015).
39. Shao, Q. *et al.* MutexaGPT: an intuition-to-design translator for physics-based enzyme engineering. *Nat Comput Sci* **6**, 1133–1146 (2026).
40. RFD4-Proteina.pdf. https://rfd4-proteina.org/assets/paper/RFD4-Proteina.pdf.
41. claude_protein_binder_design.pdf. https://www-cdn.anthropic.com/30bf50e22a01388bb29bf077ee3f244531594b7a.pdf.
42. Shrake, A. & Rupley, J. A. Environment and exposure to solvent of protein atoms. Lysozyme and insulin. *Journal of Molecular Biology* **79**, 351–371 (1973).

Supplemental Information 1 - Skill definitions of the LPT pipeline

binder-optimizer

`binder-optimizer` `2558 words`

> **Frontmatter description.** Invoke ONLY when the user explicitly asks for it by name or clearly requests this specific workflow; do not trigger it from a general question, which you can answer better from your own knowledge than from this narrow corpus. Analyses a predicted binder-target complex (local CIF/PDB from AF3/RFDiffusion/Boltz), maps the binding interface atomically, proposes 4 single-point mutations on the binder to improve affinity, validates steric clashes, and outputs 4 mutated sequences for experimental testing. Optionally cross-validates against molecular-biology-expert or ppi-analysis reports. Requires structure-tools MCP server. Trigger on: "optimize binder", "improve binding affinity", "suggest mutations", "mutate binder", "affinity maturation", "binder optimization", or any request to improve a designed binder given a local structure file. Do NOT invoke for target selection (use pathway-expert) or first-pass interface analysis without an improvement task (use complex-structure-analysis).

Binder Optimizer

Proposes 4 independent single-point binder mutations for experimental validation. Binders will be tested experimentally — no AlphaFold JSON submission needed. Combined multi-mutation candidates belong in round 2, after singles are ranked experimentally — combining before knowing which ones work produces uninterpretable results.

Output: `## BINDER OPTIMIZATION REPORT` + machine-readable `### MUTATION OUTPUT` JSON block.

Phase 1: Parse Input

From the user message identify: - `file_path` — local CIF or PDB of the predicted complex - `binder_chain` / `target_chain` — chain IDs (**confirm with user if not given** — for RFDiffusion outputs the designed chain is commonly A, target B, reversing convention) - `structure_source` — AF3 / Boltz / RFDiffusion / other (determines pLDDT validity) - `context_reports` — optional mol-bio-expert or ppi-analysis report

Phase 2: Interface Analysis

2a — Interface map

One tool call returns the full contact map:

```
mcp__structure-tools__tool_analyze_interface
  file_path = "<path>"
  chain_a   = "<binder_chain>"
  chain_b   = "<target_chain>"
  cutoff    = 4.5
```

From the result, extract: - `interface.bsa_total_A2`, `interface.n_hbonds`, `interface.hbonds[]` - `chain_a_interface_residues[]` — each entry has: `residue`, `resnum`, `one_letter`, `type`, `hydrophobicity`, `contacts[]`, `n_contacts`, `gap_flag` - Each contact in `contacts[]` has: `target_res`, `target_resnum`, `min_dist_A`, `interaction` - `plddt_at_interface` — `{resnum: plddt_score}`; valid for AF3/Boltz only - `low_confidence_residues` — pre-flagged list (pLDDT < 70)

For pLDDT: if `structure_source` is RFDiffusion or other non-AF output, B-factors are placeholders — note "pLDDT not applicable" in the report and ignore confidence flags.

The `contacts[]` field on each binder residue is the proximity map. Build the PROXIMITY MAP table directly from this data — no additional tool calls needed.

If a specific binder residue needs deeper inspection (e.g. to confirm an H-bond candidate before reasoning), call:

```
mcp__structure-tools__tool_get_residue_contacts
  file_path     = "<path>"
  chain         = "<binder_chain>"
  resnum        = <auth_seq_id>
  partner_chain = "<target_chain>"
  cutoff        = 4.5
```

2b — Target surface patch characterisation

Collect the `target_resnum` values from all contacts in `chain_a_interface_residues[]` (de-duplicate). Call:

```
mcp__structure-tools__tool_score_surface_patch
  file_path    = "<path>"
```

```
chain        = "<target_chain>"
residue_list = [<de-duplicated target interface resnums>]
```

Returns: `mean_hydrophobicity`, `hydrophobic_fraction`, `spatial_spread_A`, `residue_type_breakdown`, `suitability_rating` (Excellent/Good/Marginal/Poor), `rationale`.

Extract and record: - **Patch hydrophobic fraction** — drives the hole-filling strategy in Phase 3 - **Suitability rating** — a Marginal/Poor patch means stacking more hydrophobics on the binder is unlikely to help; electrostatic optimisation becomes the priority - **Spatial spread (Å)** — large spread = diffuse interface; small spread = compact pocket

2c — Shape complementarity proxy

True Sc (Lawrence-Colman) requires molecular-dot-surface computation not available here. Use the following proxies from Phase 2a data:

PROXY	HOW TO COMPUTE	INTERPRETATION
Void count	Count residues where `gap_flag: true`	Each void is a potential fill site
Mean contact distance	Average `min_dist_A` across all contacts	< 3.8 Å = tight packing; > 4.2 Å = loose
Close-contact fraction	Fraction of contacts with `min_dist_A` ≤ 3.8 Å	< 0.4 = poor complementarity
Exposed polars	Polar binder residue with vdw-only contacts and no H-bond entry	Desolvation penalty without reward

Report a qualitative Sc proxy rating: - **Good** — void count ≤ 2, mean dist < 3.9 Å, close-contact fraction ≥ 0.5 - **Moderate** — 3–5 voids or mean dist 3.9–4.1 Å - **Poor** — > 5 voids or mean dist > 4.1 Å or close-contact fraction < 0.3

Phase 2.5: Alanine Scan Classification

No tool calls. Derive from Phase 2a data. For every residue in `chain_a_interface_residues[]`, classify it into one of three tiers:

TIER	CRITERIA	IMPLICATION
Hotspot	n_contacts ≥ 3, OR appears in `hbonds[]` as donor/acceptor, OR `interaction: electrostatic` or `aromatic`	Alanine substitution predicted to significantly impair binding — do NOT mutate
Neutral	n_contacts 1–2, `interaction: vdw_contact` only, no H-bond, not a gap	Alanine substitution predicted neutral — may be optimisable
Target	`gap_flag: true`, OR polar residue with vdw-only contacts and no H-bond partner	Alanine scan would be neutral-to-slightly-negative — prime for optimisation

How to apply in Phase 3: Hotspot residues are excluded from mutation proposals. Neutral and Target residues feed the rule engine. Targets are prioritised.

Output the ALANINE SCAN TABLE (see Phase 7) directly from this classification — do not fabricate ΔΔG numbers; use "Hotspot", "Neutral", or "Target" as the predicted effect.

Phase 3: Mutation Candidate Reasoning

No tool calls. Reason over the proximity map and Phase 2.5 classification. Generate 8–12 candidates. **Only propose mutations for Neutral or Target residues.**

Pre-filter (before any rule): Skip PRO, GLY in turns/loops — already excluded by hard constraints. Skip any Hotspot residue from Phase 2.5.

Rule 1 — Charge complement (highest priority): uncharged/weakly polar binder near charged target → mutate to opposite charge (target ARG/LYS → D/E on binder; target ASP/GLU → R/K on binder, prefer R for longer reach).

Rule 2 — H-bond formation: binder residue has `interaction: h_bond_candidate` but no `h_bond` entry in the H-bond list → mutate to S, T, N, Q, Y, or H.

Rule 3a — Hydrophobic gap fill (void): `gap_flag: true` and target contacts are hydrophobic → bulkier hydrophobic (A→L/I/F, V→L/I). Avoid W directly — large sidechain, check clash first.

Rule 3b — Pocket fill (no gap, tight contact): binder residue is small (A/V/G), target contacts are hydrophobic, `min_dist_A` ≤ 3.8 Å for all contacts, no gap_flag. Indicates a tight hydrophobic pocket that a slightly larger residue could pack into more fully. Prefer A→V, V→L, A→I — one methylene step at a time. Patch hydrophobic fraction from Phase 2b ≥ 0.4 is a supporting condition; skip if < 0.3.

Rule 4 — Desolvation: `interaction: vdw_contact` or `h_bond_candidate`, binder residue is polar, target contacts are hydrophobic, no H-bond present → mutate to non-polar (S/T→A/V; N/Q→L/I).

Rule 5 — Repulsion removal: `interaction: electrostatic_repulsive` → mutate binder to neutral or opposite charge.

Rule 6 — Second-shell support: Look for binder residues that are NOT in the interface (absent from `chain_a_interface_residues[]`) but neighbour an interface residue whose sidechain is floppy or solvent-exposed. If the interface residue is a Hotspot, locking it in the correct rotamer via a second-shell contact can contribute significantly to binding. Flag candidates where a second-shell residue could form a new intra-binder H-bond or hydrophobic contact to pre-organise the hotspot sidechain. These are lower-confidence (no direct structural data) — mark as Rule 6 and note "second-shell, requires AF3 confirmation."

Hard constraints (apply before generating any candidate): - Never PRO (destroys backbone H-bond donor, disrupts backbone conformation) - Never mutate GLY in turns/loops (Gly φ/ψ are inaccessible to any other residue) - Binder chain only — never mutate the target - Exactly 4 single-point mutations in final output; no combined submissions in round 1 - No CYS unless disulfide is clearly supported (oxidising environment, proximal Cys)

For each candidate record: `resnum` (auth_seq_id), WT one-letter, proposed one-letter, shorthand `<WT><resnum><New>` (e.g. `A265E`), one-sentence rationale, rule number.

Phase 4: Red Flag Filter

No tool calls. Apply before clash validation — discard or downgrade candidates that fail. Record the flag in the MUTATION CANDIDATES table.

Flag A — Buried polar (desolvation penalty): The proposed new residue is polar (S, T, N, Q, H) AND none of the target contacts in `contacts[]` are capable of forming an H-bond (all interactions are `vdw_contact` or `hydrophobic`). Without a partner, burying a polar residue costs ~1–2 kcal/mol. **Discard unless Rule 2 intent.**

Flag B — Aggregation patch: The proposed mutation introduces a large hydrophobic (W, F, L, I) AND the binder residue is on a solvent-exposed face (few contacts, low n_contacts). A new exposed hydrophobic can drive self-aggregation. **Downgrade; note in report.**

Flag C — Steric over-reach (Rule 3b heuristic fail): Pocket-fill candidate (Rule 3b) where all contacts already have `min_dist_A` ≤ 3.5 Å — space is already occupied. Bulking up here guarantees a hard clash. **Discard; do not send to Phase 5.**

Flag D — Removes a hotspot-proximal backbone donor: The WT residue is the only non-Gly residue providing a backbone NH toward the target (visible in `hbonds[]` as backbone H-bond). Even a conservative substitution changes the sidechain environment. **Retain but flag; note AF3 repack required.**

Candidates with Flag A or C are removed from the pool before Phase 5. Flags B and D are retained with a note. If the pool drops below 6 after flagging, go back to Phase 3 and generate additional candidates from lower-priority rules.

Phase 5: Steric Clash Validation

For the top 6–8 candidates (after red-flag filter) call one tool per candidate:

```
mcp__structure-tools__tool_check_mutation_clash
  file_path     = "<path>"
  chain         = "<binder_chain>"
  resnum        = <auth_seq_id>
  new_aa        = "<1-letter or 3-letter code>"
  partner_chain = "<target_chain>"
```

Returns: `clash` (none / minor / major), `hard_clashes`, `soft_clashes`, `sidechain_reach_proposed_A`.

RESULT	ACTION
`none`	Pass — retain
`minor`	Retain with note: "minor clash, may resolve by AF3 repacking"
`major`	Discard

The tool uses a Cβ-heuristic (sidechain reach radius, not a rotamer library). It is a pre-filter, not a definitive verdict — AF3 re-prediction resolves ambiguous minor cases. Prune to the best 4–6 passing candidates for Phase 6.

Phase 6: Context Integration

Skip if no context reports provided.

From molecular-biology-expert (`INTERFACE INSIGHTS FROM LITERATURE`): - Upgrade if the contacted target residue is a confirmed hotspot (alanine scan > 5× loss) - Downgrade if the target residue is "tolerant of mutation" (< 2× effect)

From ppi-analysis report (`MODEL-READY HOTSPOTS` or `HOTSPOT REGIONS`): - Upgrade if the contacted target residue appears in the hotspot table - This provides structural corroboration that the contact is energetically real

---

Phase 7: Final Selection and Sequence Construction

Select top 4

Rank by: rule priority (1 > 2 > 3a/3b > 4 > 5 > 6) → red-flag status (no flag > Flag B/D

> discarded) → clash result (none > minor) → context support (hotspot confirmed > structural > none) → pLDDT at position (≥ 70 preferred).

Do not recommend two mutations at the same position. Prefer candidates targeting **different interface regions** — spatial independence makes round-2 combining cleaner.

Get binder sequence

```
mcp__structure-tools__tool_get_sequence_map
  file_path = "<path>"
  chain     = "<binder_chain>"
```

Returns `sequence` (1-letter uppercase string) and `auth_to_string_idx` mapping. Use `auth_to_string_idx[resnum]` to find the exact 0-based position in the sequence string — do not use the residue number directly.

Apply each mutation independently to the binder sequence to produce 4 mutated sequences.

Emit MUTATION OUTPUT block

After selecting the 4 mutations, output a machine-readable JSON block exactly as shown:

````
### MUTATION OUTPUT
```json
[
  {"mutation": "A265E", "mutated_sequence": "<full binder sequence with A265E applied>"},
  {"mutation": "V271L", "mutated_sequence": "<full binder sequence with V271L applied>"},
  {"mutation": "T290N", "mutated_sequence": "<full binder sequence with T290N applied>"},
  {"mutation": "K312R", "mutated_sequence": "<full binder sequence with K312R applied>"}
]
````

````
Each `mutated_sequence` must be the complete binder sequence (same length as WT except
for the single substitution). The block must appear verbatim so it can be parsed
programmatically.

**Round 2**: after experimental results are in, re-invoke binder-optimizer on the
uploaded CIF of the best-performing mutant to propose a double mutant.

---

## Phase 8: Output Report

Populate all sections from tool outputs. Do not fabricate distances, BSA values, or
interaction types. Write "Not determined" where tool data is absent.
````

BINDER OPTIMIZATION REPORT

INPUT SUMMARY

- Structure:
- Binder chain: (res) —
- Target chain: (, res)
- Task:
- Structure source:
- pLDDT:
- Context reports:
````

INTERFACE OVERVIEW

- BSA: Å²
- H-bonds:
- Interface residues: binder, target
- Binder residues by type: Hydrophobic: [...] Aromatic: [...] Charged: [...] Polar: [...]
- Low-confidence binder residues (pLDDT < 70):
- Target patch: suitability , hydrophobic fraction , spatial spread Å
- Shape complementarity (proxy): — voids: , mean contact dist: Å, close-contact fraction:

ALANINE SCAN TABLE

BINDER RESIDUE	N_CONTACTS	H-BOND?	DOMINANT INTERACTION	TIER	IMPLICATION
		Yes/No		Hotspot/Neutral/Target	Leave alone / Monitor / Optimise

PROXIMITY MAP

BINDER RESIDUE	TARGET CONTACTS (4.5 Å)	INTERACTION	GAP FLAG
	(Å,), ...		Yes/No

MUTATION CANDIDATES (pre-validation)

RANK	MUTATION	RULE	RATIONALE	RED FLAG
1		R1		None/A/B/C/D

CLASH VALIDATION

MUTATION	CLASH	HARD	SOFT	SIDECHAIN REACH (Å)	STATUS
	none/minor/major				Pass/Discard

CONTEXT INTEGRATION

(Omit if no context reports provided) - Upgrades: - Downgrades / eliminations:

RECOMMENDED MUTATIONS

#	MUTATION	RATIONALE	CLASH	RED FLAG	PLDDT	CONTEXT
1	...	...	none	None	<val	N/A>
2–4	...					

Caveats: Round 2: after experimental affinity results, upload the best mutant CIF and re-invoke.

MUTATION OUTPUT

```
[full MUTATION OUTPUT JSON array — see Phase 6]
```

```

## Handoff Contract

- **Standalone**: user provides file path + chain IDs + task
- **From orchestrator**: write report to `&lt;run_folder&gt;/05_binder_optimization.md`
- **To wet lab**: `RECOMMENDED MUTATIONS` table + `MUTATION OUTPUT` sequences
- **To round 2**: re-invoke on uploaded CIF of best experimentally-validated mutant

## Common Pitfalls

- **Chain identity in RFDiffusion outputs**: the designed chain is commonly chain A, target chain B — the reverse of convention. Always confirm before Phase 2.
- **auth_to_string_idx, not resnum**: `tool_get_sequence_map` returns the exact string index map. Use `auth_to_string_idx[resnum]` — do not use the residue number directly as a string index; chains may start above 1 or contain numbering gaps.
- **useStructureTemplate suppresses mutant geometry**: if you ever submit to AF3 in round 2, always use `useStructureTemplate: false` — the WT template would correct the mutation back toward WT geometry.
- **No combined mutants in round 1**: if a combined mutant underperforms you cannot identify the culprit without the singles. Singles first, always.
```

- **pLDDT < 70 is a caveat, not a veto**: uncertain geometry ≠ wrong position. The mutation may stabilise the interface. Flag it and let AF3 decide.
- **Pro/Gly constraints are absolute**: filter these in Phase 3 before reasoning — do not pass them to Phase 5 clash checking.
- **Clash tool is a heuristic**: `tool_check_mutation_clash` uses Cβ reach radius, not a rotamer library. Minor results are pre-filters; AF3 resolves the final geometry.
- **Alanine scan is contact-based, not energetic**: the Phase 2.5 classification uses structural proxies (n_contacts, H-bonds, interaction type). Do not state ΔΔG numbers — say "Hotspot", "Neutral", or "Target" only.
- **tool_score_surface_patch scores the target patch, not the binder**: use it to characterise what the binder is docking onto, not the binder itself. A Marginal/Poor target patch means the binding site is inherently difficult — temper expectations accordingly.
- **Sc proxy is not Lawrence-Colman Sc**: gap_flag + contact distance is a heuristic. Report it as "proxy" — do not equate to published Sc values.

SUPPLEMENTARY INFORMATION · LPT EXPERT SKILL

binder-target-intel

`binder-target-intel` `1257 words`

> **Frontmatter description.** Choose the structure, chain pair and interface to design a binder against, given a named protein target and a design intent. Receives a pre-computed table of candidate interfaces (PDB entries containing the target plus a partner, ranked by buried surface area, H-bonds and hydrophobicity) and decides which one carries the biology the user asked to disrupt or stabilise. Invoke ONLY as stage 0 of the binder workflow, when the target is already named and no literature discovery is wanted (e.g. "design binders against KRAS", "design binders to <TARGET> to disrupt downstream interactions"). Do NOT invoke for disease-first questions (use pathway-expert) or novelty triage (wildcard-expert).

Binder target intelligence

You pick **what to design against**. A downstream pipeline will trim the target, build an RFD3 specification and spend GPU-days on it, so a wrong interface here is not recoverable later — it produces a technically successful campaign against the wrong biology.

What you are given

The query contains a **candidate interface table**, already computed:

COLUMN	MEANING
PDB / method / res Å	the entry and how it was solved
target chain + len	the chain carrying the target's UniProt accession
partner chain + len	the other protein in the interface
BSA Å²	buried surface area, both sides, biological assembly 1
iface res	interface residues on the target side
H-bonds	across the interface
φ frac	fraction of interface residues that are hydrophobic or aromatic

Everything in it is measured, not predicted. Crystal-packing contacts under 500 Å² are already removed. Entries are biological assembly 1, so the chain pairs are the ones that exist in solution.

Do not re-derive these numbers. Your value is judgement about biology, not recomputation.

Membrane proteins

If the query says the target is membrane-bound, **design against the extracellular side** unless it explicitly asks for the intracellular one. The query carries the UniProt topology when there is any; respect it.

Never pick an interface that sits in a transmembrane helix. In an isolated structure a TM helix is an exposed hydrophobic slab, so it attracts binders that score well on every contact metric and cannot work in a cell, where that surface is buried in lipid. The trim removes TM residues automatically, but choosing that interface in the first place wastes the round.

The decision

Pick ONE PRIMARY (structure, target chain, partner chain) and justify it. The question is almost never "which interface is biggest" — it is **which interface, if blocked, produces the effect the user asked for**.

Work through:

1. **Is the partner a physiological effector, or a reagent?** Candidate tables for well-studied targets are full of DARPins, Affimers, Fabs, nanobodies and designed mini-binders. They form large, high-quality interfaces and tell you nothing about signalling. They are *sometimes* the right answer — they mark a demonstrably druggable epitope — but say so explicitly if you pick one.
2. **Does blocking it interrupt the pathway the user named?** For "disrupt downstream interactions", prefer the interface the target uses to *recruit or activate its effector* (e.g. KRAS→RAF1 RBD) over one that merely involves the target.
3. **Is the target chain tractable?** Prefer a chain within the residue budget given in the query, at good resolution, with a compact contiguous interface. A large multi-domain chain will be trimmed; note the domain you care about.
4. **Is the epitope bindable?** A high φ fraction and a decent H-bond count suggest a real hydrophobic patch to design against. Very low φ with few H-bonds is often a flat, polar, electrostatics-driven interface — much harder for a de novo binder.
5. **Design intent.** `disrupt` = compete for the partner's site (the default for "disrupt downstream interactions"). `stabilize` = a molecular-glue-style interface. `inhibit_active_site` = an enzyme's catalytic pocket, not a PPI.

If the table has nothing usable — no physiological partner, every target chain a fragment, every interface tiny — say so and emit `go_recommendation: NO_GO` with the reason. That is a useful answer; inventing a target is not.

More than one good site

Targets often have several defensible epitopes: a different effector interface, a distinct face of the same partner, a validated allosteric pocket. If two or three are genuinely competitive, **list them all** in `sites_json`. The pipeline can run a small design trial per site and compare measured success rates, which settles the question far better than reasoning does.

List a second site only when you would actually be uncertain between them — not to hedge. Each extra site costs a full trial campaign. One clearly-best site should produce a single entry.

Tools

You normally need **none**. The table already answers the structural questions. Use tools only to break a genuine tie, and at most two or three calls:

- `search_corpus` — what the literature says about a specific interface's role. The single most useful call: it distinguishes a signalling interface from a structural one.
- `tool_analyze_interface` — re-measure one entry in detail if the table is ambiguous between two chain pairs.
- `tool_score_surface_patch` — rate the designability of a specific patch.
- `find_complex_structures` / `search_rcsb_pdb` — only if the table is empty or you suspect the right complex is missing.

Never guess a PDB id. Every id you emit must come from the table or from a tool result.

Modality

Report `mini_protein` unless you are told otherwise.

- `mini_protein` (70–86 residues) — the default, and what the design backend actually builds. Suits flat or extended interfaces, which is most PPIs.
- `cyclic_peptide` (12–15 residues) — suits small, well-defined pockets, but it is an **opt-in** modality the operator selects at kickoff with `--modality cyclic_peptide`. Cyclic peptides need specialised synthesis, cost substantially more, and have a thinner experimental track record. The default design engine (RFD3/foundry) cannot build them at all.

If the epitope is a compact pocket and you think a cyclic peptide would suit it better, say so in `interface_rationale` as a suggestion for the operator — but still report `modality: mini_protein`. You are not choosing the modality; the operator already has.

Output

A short report — what you picked, what you rejected and why — then exactly this block. Downstream stages parse it; every key must be present.

```
### PIPELINE HANDOFF
- target_gene: <symbol>
- target_uniprot: <accession>
- pdb_id: <4-character id from the table>
- assembly: ba1
- target_chain: <auth chain id>
- partner_chain: <auth chain id>
- partner_name: <what the partner is>
- target_entity_description: <as in the table>
- target_chain_length: <int>
- interface_bsa_A2: <int>
- signalling_interface: yes | no
- downstream_effect: <one clause: what blocking this interface does>
- interface_rationale: <one sentence: why this interface over the others>
- design_intent: disrupt | stabilize | inhibit_active_site
- modality: mini_protein          # unless the operator opted into cyclic_peptide
- binder_length_min: <int>
- binder_length_max: <int>
- keep_domain_hint: <chain><start>-<end>, or NONE
- sites_json: [{"site_id": "raf1_rbd", "pdb_id": "6VJJ", "target_chain": "A", "partner_chain": "B",
"partner_name": "RAF1 RBD", "rationale": "..."}]
- alternatives_json: [{"pdb_id": "...", "target_chain": "...", "partner_chain": "...", "why_not": "..."}]
- membrane_side: extracellular | cytoplasmic | not_applicable
- go_recommendation: GO | CONDITIONAL_GO | NO_GO
- go_rationale: <one sentence>
```

```
- structure_query: <the question the structure stage should answer, naming the
  proteins and the intent — NEVER chain letters, which it assigns itself>
```

Rules for the handoff

- `pdb_id` must be `NOT_FOUND` if you could not choose one; never invent it.
- `target_chain` / `partner_chain` are the **auth** chain ids from the table.
- `binder_length_min` / `max` follow the modality (12/15 or 70/86) unless the query's constraints say otherwise.
- `keep_domain_hint` names the region worth keeping when the target is trimmed — the domain carrying the interface. `NONE` if the chain is already compact.
- `structure_query` is handed to a structure-analysis stage that assigns chains itself from the mmCIF. Name the proteins and the intent; do not name chains.
- `sites_json` must ALWAYS contain at least the primary site, as its first entry, with the same `pdb_id` / `target_chain` / `partner_chain` as the fields above. `site_id` is a short slug, unique within the list, used as a directory name.
- `membrane_side` is `not_applicable` for a soluble protein.

chimerax-visualization

`chimerax-visualization` `925 words`

> **Frontmatter description.** Invoke ONLY when the user explicitly asks for it by name or clearly requests this specific workflow; do not trigger it from a general question, which you can answer better from your own knowledge than from this narrow corpus. Generates a ready-to-run ChimeraX (.cxc) script that loads a PPI structure, renders the target chain as the focal object (colored cartoon + semi-transparent surface with hotspot patches highlighted), and washes out the binder/partner chain with low-opacity cartoon and surface. Reads all inputs from a prior complex-structure-analysis or binder-optimizer report passed via --context. No MCP tools required — output is a .cxc script block to save and run. Trigger on: "visualize interface", "chimerax script", "highlight hotspots", "render the structure", "make a figure", or any request to visualise a PPI complex after an analysis report has been produced.

ChimeraX Interface Visualization

Generates a commented `.cxc` script for ChimeraX that produces a publication-quality view of a PPI interface. The target protein is the visual focus; the binder is rendered as a translucent ghost. Hotspot residues stand out with opaque surface patches and sphere representation.

No tool calls are made. All inputs are extracted from the context report.

Phase 1: Extract Inputs from Context Report

From the prior complex-structure-analysis or binder-optimizer report, extract:

FIELD	SOURCE IN REPORT
`file_path`	COMPLEX OVERVIEW → Structure
`target_chain`	COMPLEX OVERVIEW → Target chain
`partner_chain`	COMPLEX OVERVIEW → Partner chain
`hotspot_residues`	HOTSPOT REGIONS → Residues (auth_seq_id list) — primary patch only
`interface_residues`	TARGET CHAIN INTERFACE RESIDUES + all hotspot regions (union)
`hbond_pairs`	H-BONDS AT INTERFACE table — donor and acceptor residue numbers
`label_residues`	Top 4–6 hotspot residues with highest BSA (most important to label)
`complex_name`	Infer from protein names in report (used in script header comment)
`structure_source`	COMPLEX OVERVIEW → Structure source

If any field is missing, use a safe fallback: - Missing `interface_residues`: use `hotspot_residues` only - Missing `hbond_pairs`: omit the `hbonds` command - Missing `label_residues`: label the top 3 hotspot residues

Phase 2: Select Color Scheme

Apply this palette consistently:

ELEMENT	COLOR	HEX	NOTES
Target chain (cartoon)	Steel blue	`#2E86C1`	Main chain color
Target interface surface	Steel blue, 50% transparent	`#2E86C1`	Broad interface region
Hotspot patch (surface)	Amber	`#E67E22`	Primary hotspot, 20% transparent
Hotspot patch (atoms)	Amber	`#E67E22`	Sphere style, same residues
H-bonds	Gold	`#F4D03F`	
Binder chain (cartoon)	Light gray	`#BDBDBD`	70% transparent
Binder surface	Light gray	`#D5D8DC`	85% transparent
Background	White	—	
Labels	Dark slate	`#2C3E50`	

If the user requests a different palette, substitute consistently across all elements.

Phase 3: Generate the Script

Produce a fully commented `.cxc` script. Follow the block structure below exactly. Fill in all residue lists as comma-separated integers with no spaces (e.g. `52,56,98,103`).

```
# ============================================================
# ChimeraX Visualization — <complex_name>
# Structure: <file_path>
# Target chain: <target_chain> | Partner chain: <partner_chain>
# Generated by little_protein_tiger chimerax-visualization
# ============================================================

# --- Setup ---
open <file_path>
windowsize 1400 1000
set bgColor white
lighting soft

# --- Base representation ---
hide atoms
cartoon #1
color #1 #AAAAAA

# --- Target chain: <target_chain> ---
color #1/<target_chain> #2E86C1
transparency #1/<target_chain> 0 cartoons

# Molecular surface on full target interface region
surface #1/<target_chain>
color #1/<target_chain> #2E86C1 target s
transparency #1/<target_chain> 50 surfaces

# Hotspot patch: opaque surface + sphere atoms
color #1/<target_chain>:<hotspot_residues> #E67E22
color #1/<target_chain>:<hotspot_residues> #E67E22 target s
transparency #1/<target_chain>:<hotspot_residues> 20 surfaces
show #1/<target_chain>:<hotspot_residues> atoms
style #1/<target_chain>:<hotspot_residues> sphere

# --- Partner / binder chain: <partner_chain> (ghost) ---
color #1/<partner_chain> #BDBDBD
transparency #1/<partner_chain> 40 cartoons
surface #1/<partner_chain>
color #1/<partner_chain> #D5D8DC target s
transparency #1/<partner_chain> 55 surfaces

# --- H-bonds at interface ---
# (omit this block if no hbond data was in the report)
hbonds #1 restrict both reveal true color #F4D03F showDist false

# --- Labels on key hotspot residues ---
label #1/<target_chain>:<label_residues> residues text "{0.label_name}{0.label_number}" color #2C3E50 height 0.6


# --- Focus view on hotspot ---
view #1/<target_chain>:<hotspot_residues> pad 0.7
turn y 15

# --- Save image ---
# Adjust path as needed; supersample 3 gives 3× resolution for publication
save <output_dir>/<complex_name>_interface.png width 2560 height 1440 supersample 3
```

Phase 4: Output

Write the output as two blocks:

Block 1 — Script instructions

```
## CHIMERAX VISUALIZATION SCRIPT

**Structure**: <file_path>
**Complex**: <complex_name>
```

```
**Target chain**: <target_chain> | **Partner chain**: <partner_chain>
**Hotspot residues highlighted**: <hotspot_residues>

Save the script below as `<complex_name>_viz.cxc` and run:
```

chimerax <complex_name>_viz.cxc

```
Or open ChimeraX and use **File → Open** to run the `.cxc` file.
```

Block 2 — The complete `.cxc` script in a fenced code block

Label the fence: ```` ```chimerax ````

Common Pitfalls

- **Residue spec syntax**: ChimeraX uses `#model/chain:resnum` — no spaces around `/` or `:`. Comma-separated resnums with no spaces: `#1/A:52,56,98` not `#1/A:52, 56, 98`.
- **auth_seq_id vs label_seq_id**: use **auth_seq_id** values from the report for all ChimeraX residue specs — these match the PDB author numbering in the file.
- **surface before color**: `surface #1/A` must be called before `color #1/A surface ...` and `transparency #1/A ... surfaces`. Surface creation and coloring are separate commands.
- **transparency target keywords**: use `cartoons` (plural) and `surfaces` (plural) as the target argument: `transparency #1/B 70 cartoons`, `transparency #1/B 85 surfaces`. Using singular forms (`cartoon`, `surface`) is a common error and will fail silently.
- **hbonds with no cross-chain contacts**: if `restrict both` returns no bonds, the command silently succeeds with nothing shown — this is fine, not an error.
- **`style sphere` vs `style ball`**: `sphere` renders atoms at full Van der Waals radius (bulky, very visible). Use `ball` for a subtler look. For hotspot emphasis, `sphere` is usually preferred.
- **turn y 15**: adds a slight rotation after `view` to reveal interface depth. Adjust or remove if the default orientation already shows the interface clearly.
- **save path**: use an absolute path or a path relative to where ChimeraX is launched. The `supersample 3` flag renders at 3× then downsamples — required for publication quality.

complex-expert

`complex-expert` `2160 words`

> **Frontmatter description.** Characterise a predicted or known protein complex from a set of gene/protein names. Searches the curated literature corpus to determine pathway involvement, disease relevance, and therapeutic targeting potential. Operates in two modes: Summary mode (default — brief biology blurb, ~4–6 tool calls) for rapid triage of many complexes, and Full pipeline mode (deep follow-up — ends with a complex-structure-analysis handoff) for high-value hits. Invoke ONLY when the user explicitly asks for analysis starting from a set of proteins or a predicted complex (e.g. "what do we know about the ARFRP1/JTB/SYS1/ARL1 complex?", "characterise this complex", "what pathway is this in?"). Do NOT invoke for disease-first questions (use pathway-expert) or when a PDB ID is the starting point (use complex-structure-analysis directly). Requires: literature-db MCP server.

Protein Complex Expert

This skill reasons from a set of proteins outward to pathway biology, disease context, and therapeutic opportunity. It is the inverse of pathway-expert: instead of starting from a disease and finding a target, it starts from a (possibly novel) complex and determines what biology it participates in.

The key novelty signal: **complexes with little or no corpus coverage may represent new biology**. Low coverage is not a failure — it is a flag to investigate further and enrich the database.

Pre-flight: Determine Mode

Before running any queries, determine the operating mode from user intent:

Summary mode (default) — user wants rapid triage: - "what do we know about X?" - "give me a brief summary of this complex" - "screen this list of complexes" - No request for structure or design

Full pipeline mode — user wants deep characterisation: - "give me the full analysis" - "I want to take this to the design stage" - "run the complete pipeline starting from this complex" - User explicitly mentions ChimeraX, structural analysis, or design inputs

If unclear, run Summary mode and offer Full pipeline at the end.

Phase 1: Literature Search

Run 3–4 `search_corpus` calls. Vary query angle to triangulate coverage.

Query 1 — Direct complex / pairwise interaction (top_k=6): Search for the proteins as a group and pairwise. For a complex [A, B, C, D], run:

```
search_corpus
  query="<A> <B> <C> complex interaction"
  top_k=6
```

Then for the most likely functional pair (first two, or anchor + suspected partner):

```
search_corpus
  query="<A> <B> protein interaction binding"
  top_k=5
```

Query 2 — Pathway / functional context (top_k=6): Without knowing the pathway, use broad functional terms. Rotate through candidates:

```
search_corpus
  query="<A> <B> signaling trafficking membrane transport"
  top_k=6
```

Query 3 — Disease / therapeutic relevance (top_k=5):

```
search_corpus
  query="<A> cancer oncogene tumor suppressor disease"
  top_k=5
```

Query 4 — Pathway biology filter (top_k=5):

```
search_corpus
  query="<A> <B> pathway mechanism dysregulation"
```

```
  study_category="pathway_biology"
  top_k=5
```

Deduplicate results by DOI. Retain highest score per paper.

Coverage Assessment (do this immediately after queries)

Classify corpus coverage: - **Good** — ≥3 papers with score ≥ 0.35, at least one directly mentions both proteins - **Sparse** — 1–2 papers with score ≥ 0.35, or no paper mentions the complex as a unit - **None** — all scores < 0.25 or fewer than 2 results total

For **None** or **Sparse** coverage: this is a novelty signal. Note it prominently in the output and generate fetch keywords (see Phase 3). Do NOT treat low coverage as an error — it may indicate unstudied biology.

Phase 2: Fingerprint Retrieval

Retrieve full fingerprints for the top 3–5 unique papers from Phase 1. Prioritise: 1. Papers where both (or multiple) complex members appear in `protein_pair` or `entities.proteins` 2. Papers with `study_category = "pathway_biology"` (richer target_node data) 3. Papers with `key_findings` containing direct binding or functional data

From each fingerprint, extract: - **Pathway involvement** — from `pathway_context.pathways`, `pathway_context.pathway_logic`, or inferred from `situational_context_hook` - **Disease associations** — from `pathway_context.disease_associations` or `key_findings` - **Functional role of each protein** — from `pathway_context.target_nodes` or `entities` - **Any reported interactions** — from `protein_pair`, `key_findings`, or `methodology` - **Genetic dependency evidence** — CRISPR/RNAi essentiality data if present - **Prior therapeutic targeting** — from `pathway_context.target_nodes[].prior_therapeutic_targeting` - **Suggested PDB structures** — from `pathway_context.target_nodes[].suggested_pdb_structures`

Phase 2.5: Pathway/Disease Term-Expansion Search

This phase runs **only for Sparse coverage** — it is skipped in two cases: - **Good coverage** (≥8 papers, score ≥0.35) — the core biology is likely covered; proceed to Phase 3. - **None coverage** (all scores < 0.25 or <2 results) — no fingerprints to expand from; proceed to Phase 3 and generate fetch keywords instead.

What to extract from Phase 2 fingerprints

The user already provided the gene symbols, so re-querying with them adds nothing. Instead, extract **new vocabulary** that the fingerprints reveal but the Phase 1 queries did not use:

SOURCE FIELD	WHAT TO EXTRACT
`pathway_context.pathways`	Pathway names not used in Phase 1 queries (e.g. "ARF GTPase cycle", "Golgi trafficking")
`pathway_context.disease_associations[].disease`	Cancer types or disease contexts not in Phase 1 queries
`situational_context_hook`	Biological process terms (e.g. "vesicle budding", "lipid transfer", "membrane tethering")
`pathway_context.upstream_regulators` / `downstream_effectors`	Interacting partners outside the original complex set

Identify the **2–3 most specific new terms**. Prefer pathway names and biological process terms over disease terms, as these are more likely to find mechanistic papers in the corpus.

Expansion queries (at most 2)

Expansion Query A — Pathway/process context (top_k=6):

```
search_corpus
  query="<pathway_name OR biological_process_term> <anchor_protein> mechanism"
  top_k=6
```

Expansion Query B — Disease context (top_k=5, only if a disease term was identified AND no disease-relevant paper was found in Phase 1):

```
search_corpus
  query="<disease_term> <pathway_name OR anchor_protein> cancer dependency"
  top_k=5
```

Deduplicate against all DOIs already collected from Phase 1. For any new papers with score ≥ 0.25, call `get_fingerprint` and merge their extracted fields into the working set before Phase 3.

Record for output: how many new unique papers the expansion round added and which terms triggered them (reported in the CORPUS SOURCES section of the final output).

Phase 3: Knowledge Gap Assessment

Before generating output, assess what is NOT known:

1. **Is this a characterised complex?** — If all members appear together in ≥2 papers, it is known. If only individual proteins appear, it may be a newly predicted assembly.
2. **Is the pathway known?** — If pathway context could be inferred from any fingerprint, state it. If not, flag as "pathway not established in corpus."
3. **Generate fetch keywords** — Always produce a set of suggested NCBI keywords for database expansion, even when coverage is Good. Use this template: `"<GeneA>[Title/Abstract] AND <GeneB>[Title/Abstract] AND interaction[Title/Abstract]" "<GeneA>[Title/Abstract] AND <GeneB>[Title/Abstract] AND complex[Title/Abstract]" "<GeneA>[Title/Abstract] AND cancer[Title/Abstract]"` Where GeneA/GeneB are the most informative pair (anchor protein + suspected partner).

Phase 4a: Summary Mode Output

Produce a `## COMPLEX SUMMARY` block. Keep it concise — this is for triage.

```
## COMPLEX SUMMARY

### COMPLEX: <ProteinA / ProteinB / ProteinC / ...>

**Known / predicted**: <Known complex (characterised in corpus) | Predicted assembly (limited corpus coverage — possible new biology)>

**Corpus coverage**: <Good / Sparse / None> (<N> relevant papers found, best score: <X>; expansion round: <ran / skipped — why>; <+N new papers> if ran)

**Pathway involvement**:
<1–2 sentences: which pathway(s), what role, cite DOI if from corpus. If not found: "Pathway not established in corpus — likely unstudied or novel context.">

**Disease relevance**:
<1–2 sentences: cancer types, mutation data, genetic dependency if any. "Not found in corpus" if absent.>

**Targeting potential**:
<1 sentence assessment: any prior therapeutic attempts? PDB available? Interface accessible?>

**Novelty signal**: <High / Medium / Low>
<High = sparse/no coverage AND predicted assembly AND no therapeutic history — strong candidate for new biology>
<Medium = some coverage but pathway unclear or complex not characterised as a unit>
<Low = well-characterised complex with known pathway and disease role>

**Suggested fetch keywords** (run before deeper analysis):
- "<keyword 1>"
- "<keyword 2>"
- "<keyword 3>"

**Recommended next step**: <one of:>
- "Proceed to full pipeline (structure + design)" — for high novelty + disease relevance
- "Expand database first, then re-run" — for high novelty but no structural data available
- "Run pathway-expert for [disease context]" — when disease is known but pathway unclear
- "Archive — low therapeutic relevance" — for well-known non-oncogenic complexes
```

After the summary, offer:

> "Want me to run the full pipeline for this complex (literature deep-dive + structural analysis)?"

Phase 4b: Full Pipeline Mode Output

Produce the full `## COMPLEX CHARACTERISATION REPORT`, then hand off to downstream skills.

```
## COMPLEX CHARACTERISATION REPORT

### COMPLEX IDENTITY
```

```
- Members: <ProteinA (gene) / ProteinB (gene) / ...>
- Status: <Known complex | Predicted assembly | Novel — not characterised in corpus>
- Corpus coverage: <Good / Sparse / None> (<N> papers, best score: <X>)

### PATHWAY BIOLOGY
- Pathway(s): <from corpus, or "Not established">
- Pathway position: <upstream regulator / effector / scaffold / adaptor / other>
- Pathway logic: <ON/OFF logic if known, or "Not found in corpus">
- Upstream regulators: <from pathway_context or inferred>
- Downstream effectors: <from pathway_context or inferred>

### DISEASE ASSOCIATIONS
- Relevant disease(s): <cancer types, mechanisms — cite DOI + source_span>
- Mutation/dysregulation: <specific mutations or expression changes, or "Not found">
- Genetic dependency: <CRISPR/RNAi essentiality evidence, or "Not found in corpus">

### THERAPEUTIC HISTORY
- Prior targeting attempts: <modality, target protein, outcome — or "None found in corpus">
- Known structures: <PDB IDs from suggested_pdb_structures, or "None mentioned in corpus">
- Interface accessibility: <extracellular / intracellular / unknown>

### NOVELTY ASSESSMENT
- Novel biology signal: <High / Medium / Low>
  Reasoning: <why this complex may or may not represent new biology>
- Recommended interface to target: <ProteinA–ProteinB interface, or "unclear — structural analysis needed">

### CORPUS SOURCES
| # | Title (truncated) | DOI | Score | Source round | Key finding |
|---|-------------------|-----|-------|--------------|-------------|
| 1 | ...               | ... | ...   | Phase 1 / Expansion | ...   |

- Expansion round: <ran / skipped — reason>
- Expansion terms used: <pathway names, process terms, disease terms>
- New papers added by expansion: <N>

### FETCH KEYWORDS FOR DATABASE EXPANSION
Run: `python scripts/fetch_papers.py --keywords "<keyword>"`
- "<keyword 1>"
- "<keyword 2>"
- "<keyword 3>"
- "<keyword 4>"
```

Handoff to downstream skills

After the COMPLEX CHARACTERISATION REPORT, determine the handoff:

If a known PDB ID was found in corpus:

> "Proceeding to structural analysis. Invoking complex-structure-analysis with PDB [ID], target interface: [ProteinA / ProteinB]." Then invoke **complex-structure-analysis** with that PDB ID and the recommended interface pair.

If no PDB ID found but complex has therapeutic potential:

> "No PDB structure found in corpus. Before structural analysis, the database should be expanded using the fetch keywords above. Once curated, run AlphaFold structure analysis: invoke complex-structure-analysis with the local .cif file path." Provide the local AlphaFold path if the user has specified it.

If novelty signal is High:

> "This complex shows a high novelty signal — sparse corpus coverage suggests it may represent unstudied biology. Recommend: (1) expand database with fetch keywords, (2) re-run this skill, (3) if confirmed, proceed to full structural analysis using the AlphaFold prediction."

AlphaFold Local File Handling

If the user provides a local AlphaFold file path (e.g. `/data/alphafold/complex_001.cif`), include it in the chimerax handoff:

> "For ChimeraX structural analysis with the local AlphaFold prediction, use: `run_command 'open /data/alphafold/complex_001.cif'` rather than `open_structure` (which is for RCSB IDs only)."

The complex-structure-analysis skill will handle the rest once the structure is open.

Novelty Signal Calibration

High novelty (prioritise for full pipeline): - Predicted assembly (not previously co-purified or co-crystallised) - ≤1 paper mentioning any member in a complex context - No therapeutic history - At least one member is disease-associated individually (suggests the complex context may be the missing piece)

Medium novelty: - Some members are well-studied but not in this combination - Pathway is known but complex role is unclear - 2–4 papers mention the proteins but not as a functional unit

Low novelty: - Well-characterised complex (≥5 papers, complex named, structure available) - Pathway, disease role, and therapeutic history all established

Common Pitfalls

- **Do not conflate individual protein function with complex function.** A protein may have a known role in isolation, but the complex it forms may have a different or emergent function. Report individual and complex-level evidence separately.
- **Sparse corpus ≠ unimportant.** Flag low coverage as novelty signal, not as a dead end.
- **Do not guess PDB IDs.** Only report structures explicitly mentioned in retrieved fingerprints or that you are certain exist (well-known structures like 6NB6 for the complex of interest). If uncertain, say "None found in corpus — check RCSB manually."
- **Citations: DOI only, no author/journal/year.** Every cited claim must come from a retrieved fingerprint. Write the DOI string (e.g. `10.7554/eLife.77415`) — never author names, journal titles, or years. If you know a fact from training knowledge but have no corpus DOI, state the fact without a citation rather than inventing one.
- **Keep Summary mode summaries short.** The whole point is rapid triage — one paragraph per section maximum.
- **Always generate fetch keywords**, even for well-covered complexes. The corpus is never complete and new structures / mutagenesis data may be missing.
- **In Phase 2.5, do not re-query with the original gene symbols** — those were already used in Phase 1. The point is to expand into pathway/process vocabulary revealed by the fingerprints. Querying "ARFRP1 ARL1 interaction" again after Phase 1 already did that is wasted calls.
- **Phase 2.5 is not useful for None-coverage complexes.** If no fingerprints were retrieved, there is nothing to extract expansion terms from. Go straight to fetch keywords and database expansion instead.

SUPPLEMENTARY INFORMATION · LPT EXPERT SKILL

complex-structure-analysis

`complex-structure-analysis` `7598 words` `+ chimerax-ppi-commands.md`

> **Frontmatter description.** Invoke ONLY when the user explicitly asks for it by name or clearly requests this specific workflow; do not trigger it from a general question, which you can answer better from your own knowledge than from this narrow corpus. Analyse protein-protein interaction interfaces to identify surface hotspots for disruption OR stabilization by de novo cyclic peptides and mini-proteins. In disrupt mode: identifies single-chain interface hotspots. In stabilize (molecular glue) mode: identifies periinterface patches on BOTH chains for a bridging binder design. Computes BSA, SASA, H-bonds, pairwise contacts, and periinterface geometry using the structure-tools MCP server (no ChimeraX required). Accepts local CIF/PDB files or RCSB PDB IDs (download first). Trigger on: "interaction interface", "contact residues", "buried surface", "hydrophobic patch", "hotspot", "disrupt interaction", "stabilize interaction", "molecular glue", "PPI stabilizer", "PPI analysis", "design a binder", "cyclic peptide target", "mini-protein target", or when a multi-chain structure is provided and the user asks which surface to target. Also trigger for known complexes (a named two-protein complex). Requires structure-tools MCP.

PPI Interface Analysis for Peptide / Mini-Protein Design

Systematic interface analysis using the `structure-tools` MCP server. All geometric quantities (BSA, SASA, contacts, H-bonds) are computed directly from atomic coordinates — not inferred from residue names. Reasoning is applied on top of reliable numerical outputs.

Three operating modes, selected by the `design_intent` field in the PIPELINE HANDOFF from pathway-expert (and confirmed by mol-bio-expert): - **`disrupt` mode** (default): identify single-chain interface hotspots; binder competes with the partner chain to break the interaction. **Two-chain input.** - **`stabilize` mode (molecular glue)**: identify periinterface patches on *both* chains flanking the interface; binder bridges across and reinforces the complex. **Two-chain input.** - **`inhibit_active_site` mode**: single-protein target — interpret broadly. Covers (a) enzyme catalytic sites, (b) allosteric pockets, (c) any substrate-binding cleft on a non-catalytic protein, including DNA-binding clefts (e.g. blocking cGAS from sensing cytosolic dsDNA), RNA-binding pockets, lipid-binding sites, and metabolite-binding pockets. The mode name is historical — the analysis is the same for any single-chain binding-pocket target. Hotspots come primarily from the literature-stage handoff (`target_site_hint.priority_residues`), with structural confirmation of pocket geometry per residue. **Single-chain input.**

When the mol-bio-expert handoff includes a `target_site_hint` JSON object with `priority_residues`, treat those as the authoritative starting set in **any** mode — they are the residues literature already implicated. The job of this skill is to confirm geometry, not to re-derive residue importance from scratch.

Output: `## PPI ANALYSIS REPORT` with MODEL-READY HOTSPOT formats for BoltzGen and RFD3.

CITATION POLICY — READ FIRST

This report has NO access to the literature corpus. All geometric facts come from tool results. All reference facts must come from Step 3 web search results.

Rules — enforced throughout this entire report:

1. **No author names, journal names, or years** — ever. These are unverifiable in this context and will be hallucinated from training knowledge. The sentence `"Smith et al. 2023 showed..."` or `"Nature 2024"` or `"Ratti et al."` is **always wrong** unless the text was returned verbatim by a web search tool call.
2. **DOI-only citation format.** The only permitted citation is a DOI string, e.g. `10.7554/eLife.77415`. Write this only if a web search tool returned it explicitly. Never construct or guess a DOI from memory.
3. **Biological facts without a DOI: state the fact without any citation.** If you know a residue is a disease hotspot from training knowledge, you may state that biological fact — but omit any reference entirely. A fact with no citation is correct. A fact with a fabricated citation is a data integrity error.
4. **`Literature evidence: not found`** is the correct and acceptable value when Step 3 returned nothing. Do not fill this field from training knowledge.
5. **Do not add report sections not present in the template below.** Sections like `### BIOLOGICAL CONTEXT`, `### CLINICAL SIGNIFICANCE`, or similar are not in this skill's report format and must not be added — they are a vector for hallucinated references. All biological context belongs in the designated fields within the template sections.
6. **Structure source classification** comes from the file path or the user's description only — never from a paper attribution. Write `experimental (cryo-EM)`, `experimental (X-ray)`, `af3_boltz`, or `rfdiffusion`. Never add `"; Author et al. Year / Journal"` — you do not have the publication metadata.

Pre-flight: Obtain a Local Structure File

Before calling any tools, identify the **structure source** from the user's message: - `experimental` — X-ray crystallography, cryo-EM, NMR, or any RCSB PDB ID not explicitly described as a prediction. **This is the default if not stated.** - `af3_boltz` — explicitly described as AlphaFold3, Boltz, or another confidence-scored prediction model - `rfdiffusion` — RFDiffusion or other diffusion-based design output (B-factors are placeholders, not confidence)

The B-factor column in experimental structures contains crystallographic B-factors, not pLDDT. **Never interpret B-factors as confidence scores unless the user explicitly states this is an AF3/Boltz output.**

Local file (CIF or PDB): use the path directly.

RCSB PDB ID: check `data/structures/<ID>.cif` first — structures cited in the literature corpus are pre-downloaded there by `scripts/download_pdb_structures.py`. If not present, download on the fly:

```
! curl -o data/structures/<ID>.cif https://files.rcsb.org/download/<ID>.cif
```

(PDB format if needed: replace `.cif` with `.pdb`)

Phase 0: Detect Design Mode + Parse Literature Hint

Before any tool calls, read the `design_intent` from the PIPELINE HANDOFF (passed in the query from the orchestrator). Set the operating mode for this entire run:

- `design_intent: disrupt` → **DISRUPT mode** — proceed with standard Phase 1–3 below.
- `design_intent: stabilize` → **STABILIZE mode** — follow the STABILIZE branches in Phases 1–3; skip Phase 2 (surface patch scoring) and use `tool_find_glue_pockets` instead.
- `design_intent: inhibit_active_site` → **INHIBIT_ACTIVE_SITE mode** — single-chain input. Skip Phase 1 (no two-chain interface to analyse) and Phase 2 (no patch scoring); go straight to Phase 1B (per-residue context) using the literature-supplied priority residues.
- Not present → default to **DISRUPT mode**.

Membrane proteins: hotspots go on ONE face, never in the bilayer

If the target is a membrane protein — any GPCR, any receptor tyrosine kinase, any single-pass or multi-pass receptor — the only residues a designed binder can engage are those exposed to solvent on one side of the membrane. A transmembrane helix in an isolated structure looks like an ideal hydrophobic patch and scores well on every contact metric here; in a cell that surface is buried in lipid and a binder against it cannot work.

Concretely, when picking hotspots on such a target:

- Keep to ONE face, and let the INTERFACE YOU WERE ASKED ABOUT decide which. For a cell-surface receptor the extracellular side is usually the one that carries the effect — the extracellular domain (class B/C GPCRs), the N-terminus, the extracellular loops — and it is the right default when the upstream stage did not pin a face. But the cytoplasmic face is a legitimate choice when that is where the complex being disrupted actually sits (an effector-recruitment surface, or any protein in an intracellular-organelle membrane, where "extracellular" names no real surface at all). The downstream trim follows your residues to whichever face they are on; it does not assume the outer one. Say in COMPLEX OVERVIEW which face you picked and why, so the operator can see the delivery question a cytoplasmic epitope raises rather than discover it later.
- Never select a residue in a transmembrane span, and never select an epitope that straddles both faces — no single binder can engage that, and a straddling set leaves the trim no face to restrict to.
- The orthosteric pocket of a class A GPCR sits INSIDE the helical bundle. For lipid ligands (cannabinoid, S1P, LPA, prostaglandin) it is also reached laterally from within the membrane. It is a small-molecule site, not a mini-protein site: if `priority_residues` point there, say so in the report and emit NO_GO rather than returning transmembrane hotspots.

This is checked deterministically downstream — UniProt topology is mapped into author numbering and a hotspot annotated transmembrane halts the run — so returning them costs the campaign a stage and the user real money. A run on the CB1 receptor returned seven hotspots of which five were transmembrane; that target was never viable and the report should have said so.

Record the mode explicitly: write `<!-- MODE: DISRUPT -->`, `<!-- MODE: STABILIZE -->`, or `<!-- MODE: INHIBIT_ACTIVE_SITE -->` at the top of your scratchpad so it stays visible throughout the analysis.

Also parse `target_site_hint` (if present in the query). It looks like:

```
target_site_hint: {"mode":"ppi_interface","target_protein":"GENE_B","priority_residues":
["L24","W57","K61"],"notes":"…"}
```

The `priority_residues` list comes from the mol-bio-expert literature pass and should be the authoritative starting set for hotspot selection — confirm their geometry but do not silently drop residues from this list. If the list is empty, fall back to purely geometry-driven hotspot selection.

Collapse the biological assembly — BEFORE the first tool call. The orchestrator injects a chain table (entity description + residue count for every chain) into the query. Read it first and group the chains by `(entity description, residue count)`. Chains sharing both are **copies of the same molecule**, and a biological assembly of an oligomer repeats the *same* interface once per copy — analysing a second copy returns the same numbers at full token cost. Two chains with the same description but *different* residue counts are different constructs (a truncation, a tagged variant), **not** copies; keep those apart.

- Pick **one representative pair** — one target-chain copy and the partner-chain copy it contacts — and analyse only that pair.
- **Never call a structure tool on a redundant copy.** Hotspots declared on the representative chain hold for every copy of it.
- State the collapse in one line, in the `Assembly` field of COMPLEX OVERVIEW: name the groups and the pair you kept.

Worked example — 5GRS assembly 1 has twelve chains: A,B,C,D (375 res, SCAP), I,J,K,L (62 res, SREBP), E,F,G,H (187–191 res). That is a 4:4 tetramer of one interface repeated four times, visible entirely from the chain table without a single tool call. Collapse it to `A/I` and write: *"Assembly: 4:4 tetramer — A/B/C/D (SCAP, 375 aa) and I/J/K/L (SREBP, 62 aa) are the same interface repeated; analysed A/I as the representative pair."*

Confirm the structure is actually your target — BEFORE any geometry pass. The corpus stores paper-level `entities.proteins` and `paper_metadata.pdb_accessions` as two independent lists. A paper that mentions protein X and deposits a PDB of paralog Y will resolve "find PDBs for X" → Y's PDB. The orchestrator runs a deterministic substring check and surfaces the result in the query as **"Orchestrator PDB identity check: PASS | MISMATCH"** with the expected target and actual structure metadata. You are the judge — orchestrator check is strict and produces false positives on canonical-name variants.

Adjudication rules (apply before any geometry call):

- **PASS** verdict → proceed. The expected name appears in title / entity descriptions.
- **MISMATCH but same protein under canonical RCSB long form** → proceed, note the synonymy in your report. Examples:
- Expected `GAPDH` vs entity `"Glyceraldehyde-3-phosphate dehydrogenase"` → same, proceed.
- Expected `ACTB` vs entity `"Actin, cytoplasmic 1"` → same, proceed.
- Expected `EGFR` vs entity `"Epidermal growth factor receptor"` → same, proceed.
- Expected `ENPP1` vs entity `"Ectonucleotide pyrophosphatase/phosphodiesterase family member 1"` → same, proceed.
- **MISMATCH = different paralogs / family members** → **NO_GO**. Emit a stub PIPELINE HANDOFF naming both the expected target and the actual entity. Examples:
- Expected `ENPP1` vs entity `"... family member 2"` → ENPP2, NO_GO.
- Expected `ACTB` vs entity `"Actin, cytoplasmic 2"` → ACTG1, NO_GO (different actin paralog — they differ by four residues).
- Expected `ACTB` vs entity for ACTG1 → NO_GO.
- Expected `GENE_A / GENE_B` vs a complex of GENE_A's paralog → NO_GO.
- **MISMATCH = different species / orthologs but same gene** (e.g. mouse vs human ENPP1) → **proceed.** An ortholog is often the only structure that exists for a complex, and a site conserved between it and the human protein is a legitimate design target — being non-human is not by itself a NO_GO. What you must do is *say so*: name the source organism in COMPLEX OVERVIEW and fill the ORTHOLOG NOTE section (Phase 4), because the residue numbers you emit are that organism's, not human. Recommend a human PDB instead only when you can name one that covers the same interface.
- **Partial match** (e.g. one of a PPI pair matches, the other is missing) → proceed only if you can name a substitute or argue the missing partner is not needed for the design. Otherwise NO_GO.

Be conservative — only proceed when you can name the equivalence in plain English. If you can't articulate why the actual entity name maps to the expected name, treat it as a paralog mismatch and NO_GO.

On tool failures and UNVERIFIED label_seq_ids. If `tool_get_sequence_map` or another structure tool returns an error (e.g. a transient MCP dependency issue), you may write `**UNVERIFIED**` in the `label_seq_id` column of MODEL-READY HOTSPOTS and the orchestrator will resolve those tokens post-hoc via gemmi before passing the report to downstream stages. **Do not invent workaround scripts in your report** — the auth_seq_id + the literal `UNVERIFIED` token is enough; the orchestrator handles the rest. The orchestrator also runs a residue-name sanity check (e.g. confirming that `THR238` is actually a threonine at auth_seq_id 238 in the structure) and logs a warning if there's a mismatch — useful for catching mouse↔human numbering offsets that look correct on paper.

Respect the target size policy. The orchestrator injects per-chain residue counts plus the configured `max_target_residues` (default 500) and `target_residues_warn` (default 250) into your query. Before committing to a target chain assignment: - If the chosen target chain ≤ `target_residues_warn`: proceed normally. - If between warn and max: proceed but **note in the report** that the binder pass rate may drop and flag this for the user. - If above `max_target_residues`: **do not proceed with the full analysis**. Instead, produce a short report recommending one of: 1. Cropping to a binding domain — name the residue range if literature or the mmCIF header suggests one. 2. Selecting a different PDB or chain — name an alternative if you can. 3. Re-running the pathway stage with a constraint to avoid this target. Emit a stub PIPELINE HANDOFF with `go_recommendation: NO_GO` and `go_rationale` naming the size violation. The downstream design stage will not run.

Phase 1: Interface Analysis

Call once — this returns everything needed for hotspot reasoning:

```
mcp__structure-tools__tool_analyze_interface
  file_path = "<absolute_path>"
  chain_a   = "<target_chain>"
  chain_b   = "<partner_chain>"
  cutoff    = 4.5
```

If chain assignments are unclear, check model info from the file and confirm with user before proceeding — swapping target and partner changes the entire analysis.

[STABILIZE mode only] — after `tool_analyze_interface` completes, also call `tool_find_glue_pockets`:

```
mcp__structure-tools__tool_find_glue_pockets
  file_path            = "<absolute_path>"
  chain_a              = "<chain_a>"
  chain_b              = "<chain_b>"
  periinterface_radius = 10.0
  max_bridge_span      = 20.0
  min_periface_sasa    = 5.0
  top_n                = 3
```

From the glue pockets result, extract and note: - `glue_pockets[]` — ranked list of cross-chain patch pairs; each entry has: - `rank`, `combined_rating`, `centroid_separation_A`, `bridgeable`, `design_note` - `chain_a_patch.residues[]` — residue nums + SASA on chain A - `chain_b_patch.residues[]` — residue nums + SASA on chain B - `interface_summary.n_interface_residues_a` / `.n_interface_residues_b` and `.interface_resnums_a` / `.interface_resnums_b` — the interface this pocket flanks. `interface_summary` carries **no BSA**; take BSA from `interface.bsa_total_A2` in the `tool_analyze_interface` result instead. - Top-1 pocket `centroid_separation_A` → note modality SUITABILITY (the operator chooses): - ≤ 12 Å: bicyclic or large cyclic peptide - 13–20 Å: mini-protein recommended (needs structural scaffold to bridge) - > 20 Å (`bridgeable: false`): very long span — note as challenging, flag for user

From the `tool_analyze_interface` result, extract and note: - `interface.bsa_total_A2` — total BSA; use to note modality SUITABILITY (the operator chooses): - < 500 Å²: crystal packing, likely not biological - 500–1000 Å²: small — cyclic peptide - 1000–2000 Å²: typical PPI — cyclic peptide or mini-protein - > 2000 Å²: large — mini-protein recommended - `interface.n_hbonds` and `interface.hbonds[]` — H-bond list with donor/acceptor/distance - `chain_a_interface_residues[]` — per-residue: type, hydrophobicity, contacts, n_contacts, gap_flag, BSA, ddg_estimate_kcal_mol - `chain_b_interface_residues[]` — same schema as chain_a; both chains now receive full ΔΔG scoring - `chain_a_categories`, `chain_b_categories` — pre-computed hydrophobic/aromatic/charged/polar breakdown - `interface.bsa_per_residue[]` — BSA contribution per residue (key for hotspot ranking) - `plddt_at_interface` — B-factor column values. Interpret as pLDDT **only** if `structure_source` is `af3_boltz`. For `experimental` structures these are crystallographic B-factors — do not flag, threshold, or reason over them as confidence scores. For `rfdiffusion` they are placeholders — ignore entirely. - `low_confidence_residues` — pre-flagged list; relevant only for `af3_boltz` sources.

Validate chain assignment: receptor groove vs. ligand surface

[DISRUPT mode — do this before Phase 2]

Before ranking hotspots, confirm that chain_a is the *design target* — the chain whose surface the designed binder will engage. In a helix-on-groove interaction one chain provides a concave hydrophobic receptor groove (the better design target) and the other contributes a single helix or short loop.

Compare the two chains using the tool result:

SIGNAL	RECEPTOR GROOVE (→ SHOULD BE CHAIN_A)	LIGAND HELIX/LOOP
`n_contacts`	More interface residues (6–12+)	Fewer (3–7)

SIGNAL	RECEPTOR GROOVE (→ SHOULD BE CHAIN_A)	LIGAND HELIX/LOOP
BSA distribution	Many residues with moderate BSA (50–150 Å²)	Few residues with concentrated BSA
Per-residue ΔΔG	Moderate (−1 to −3 kcal/mol), spread broadly	Concentrated hotspots (−3 to −6 kcal/mol) at 2–5 positions
Secondary structure	Groove/sheet/loop surface	Often a single α-helix

If chain_b matches the receptor groove profile (more contacts, distributed BSA, broadly spread ΔΔG), the chains are assigned backwards for design purposes. **Do not re-call the tool** — reinterpret the result you already have. Both chains receive full ΔΔG scoring and per-residue BSA in a single call, so the swap is a relabelling, not a new calculation: read `chain_b_interface_residues[]` and the chain B half of `bsa_per_residue` wherever the rest of this skill says chain_a, and set `target_chain` in the PIPELINE HANDOFF to the groove chain. A second `tool_analyze_interface` call returns the same numbers with the headings exchanged, for ~25,000 tokens — on a large interface that alone can end the run. Say in the report which chain you treated as the design target and that the tool was called with the chains the other way round.

Reading chain identity

The orchestrator's chain table in the query already lists every chain with its entity description and residue count — that is the answer, and it costs nothing. Read chain identity off it. Do **not** call `tool_get_sequence_map` to recover information the table states: it is the most token-expensive tool in this surface (~30,000 tokens for a 375-residue chain), and walking a 12-chain assembly with it exhausts the context budget before any analysis happens. For designed binders, the shorter chain is usually the binder.

Only if the query carries **no** chain table, probe with:

```
mcp__structure-tools__tool_get_sequence_map
  file_path = "<path>"
  chain     = "<chain letter>"
```

and probe **at most two chains** — the `length` field and residue list are enough to tell a target from a binder. Never walk the alphabet.

Phase 1B: Single-protein pocket analysis

[INHIBIT_ACTIVE_SITE mode only] — skip if in DISRUPT or STABILIZE mode.

The input is a single-chain pocket-bearing protein — could be an enzyme, an innate-immunity DNA sensor, an RNA-binding protein, a lipid-binding protein, or any single chain whose binding cleft is the design target. There is no partner chain to analyse. The hotspot set is sourced from `target_site_hint.priority_residues` (literature-derived catalytic / substrate-binding / DNA-binding / allosteric pocket residues from the mol-bio stage) and confirmed by single-residue geometric context.

For each residue in `priority_residues`, gather geometric context:

```
mcp__structure-tools__tool_get_residue_contacts
  file_path = "<absolute_path>"
  chain     = "<target_chain>"
  residue   = <auth_seq_id>
  cutoff    = 4.5
```

Record per residue: - `residue` (three-letter name) and `resnum` (the auth_seq_id) — canonical identifier - `n_contacts` and `gap_flag` — a residue with `gap_flag: true` (< 2 contacts) is weakly engaged; note it for the user but keep it in the hotspot list - `contacts[]` — neighbouring residues within the cutoff; these are the pocket walls. Use them to confirm the residue is part of a coherent pocket (≥ 3 close contacts) rather than an isolated surface residue.

This tool returns **no per-residue SASA** — there is no `sasa_A2` field in the result. Do not report one, and do not infer solvent accessibility from the residue name; use the contact count as the burial proxy instead.

If the literature `priority_residues` list is empty (the mol-bio stage couldn't find specific residues), report this as a degraded run: the structure expert cannot de-novo identify a binding pocket without either (a) literature guidance or (b) a co-crystal structure with a bound ligand. Recommend the user re-run literature search with more targeted queries.

Score and rank for output: use a simple composite to pick the top 4–6 residues for MODEL-READY HOTSPOTS: - `len(contacts) ≥ 4` → in a coherent pocket - `gap_flag: false` → engaged rather than an isolated surface position - High residue-type score for designability (HYS, ASP, GLU, ARG, LYS, TYR, TRP, PHE preferred over GLY, ALA, SER, etc.)

For INHIBIT_ACTIVE_SITE mode, the MODEL-READY HOTSPOTS section is the same format as DISRUPT mode but uses the target chain only (no partner_chain — the binder will be the second chain in boltzgen's design).

Phase 2: Hotspot Identification

[DISRUPT mode] — follow all steps below.

[STABILIZE mode] — `tool_find_glue_pockets` already returned scored periinterface patches from Phase 1. **Skip Steps 1–2 entirely.** Go directly to Step 3 (literature cross-reference), then proceed to Phase 3 using the glue pocket output.

Step 1 — Rank residues by ΔΔG estimate

[DISRUPT mode only]

`tool_analyze_interface` now returns `ddg_estimate_kcal_mol` on every residue in `chain_a_interface_residues`. Use this as the **primary ranking criterion** — it is a physically-grounded empirical estimate of the free-energy contribution of each residue to binding affinity, combining three terms:

TERM	COEFFICIENT	APPLIED WHEN
Hydrophobic burial	−0.028 kcal/mol per Å² BSA	Residue is hydrophobic or aromatic
H-bond to partner	−1.0 kcal/mol per H-bond	Residue is donor or acceptor
Salt bridge to partner	−0.5 kcal/mol per contact	Both residues are charged, attractive

Interpretation: - `ddg_estimate_kcal_mol` < −2.0 → **strong hotspot candidate** (see `ddg_hotspot_threshold_kcal_mol`) - −2.0 to −1.0 → moderate contributor - > −1.0 → minor contributor; deprioritise unless spatially central

The field `interface.top_hotspots_by_ddg` lists the five strongest candidates across both chains. By this point chain_a is the confirmed design target (validated in Phase 1), so focus on the chain_a entries. Chain_b entries are useful context (they show which partner residues anchor the interaction) but are not design targets in DISRUPT mode.

Use `bsa_A2` from `interface.bsa_per_residue` as a **co-equal criterion alongside ΔΔG**: when two residues have similar ΔΔG, prefer the one with larger BSA. High total chain_a BSA distributed across many residues — even when individual per-residue ΔΔG values are moderate — is a strong indicator that you are targeting a druggable groove surface.

Identify clusters: residues within ~8 Å Cα-Cα of each other (use contact data — residues that share contacts with the same partner residues are spatially proximate).

Step 2 — Score candidate patches

[DISRUPT mode only]

For each cluster of 3–6 candidate hotspot residues, call:

```
mcp__structure-tools__tool_score_surface_patch
  file_path    = "<path>"
  chain        = "<target_chain>"
  residue_list = [<resnum1>, <resnum2>, ...]
```

Returns: hydrophobic fraction, mean KD score, spatial spread (Cα RMSD), and a qualitative rating (Excellent / Good / Marginal / Poor). Use this to evaluate patch **geometry and druggability** — it is complementary to the ΔΔG ranking, not a replacement for it.

Good patch characteristics for peptide/mini-protein: - Hydrophobic fraction ≥ 0.4 - Spatial spread ≤ 12 Å (compact, not dispersed) - Mean KD score > 1.0

Step 2b — Cap the set at 12 residues

A region may declare at most 12 hotspot residues. Fewer is normal and fine; 6–10 is the usual useful range.

This is a limit on what the generative model can actually be asked for, not a limit on what the interface contains. RFdiffusion3 is given the hotspot set as a constraint, and on a 12-residue set only about half its backbones end up contacting all twelve — asking for more does not make a binder cover more, it just makes the constraint less meaningful and the downstream engagement gate less informative.

If more than 12 residues qualify, **choose, and say why in the report**. Rank by, in order:

1. **Clustered, not scattered.** Prefer residues that fall in one compact patch — re-run `tool_score_surface_patch` on the candidate subsets and keep the one with the smaller spatial spread. A spread over ~12 Å means you are describing two sites, not one; if both are real, emit them as two independent regions rather than one 12-residue set spanning both.
2. **Hydrophobic anchor first.** Keep the residues driving the hydrophobic core of the patch (ILE/LEU/VAL/PHE/TYR/TRP/MET, and the `bsa_A2` that goes with them). A patch of charged/polar residues gives a binder little to grip.
3. **Strongest ΔΔG and BSA.** Within the surviving cluster, keep the largest |`ddg_estimate_kcal_mol`| and the largest `bsa_A2`.

4. **Literature-validated positions**, where Step 3 found mutagenesis for them — a residue with a measured alanine-scanning cost outranks an equal one without.

Drop residues that are pocket-facing, backbone-only contacts (GLY, or contacted only via CA/CB), or at the rim with `bsa_A2` under ~10 Å² — they contribute little and spend a slot. State the number considered and the number kept, e.g. *"18 interface residues qualified; kept the 11 forming the compact hydrophobic patch, dropped 7 rim/polar positions."* - Prefer patches where multiple residues have `ddg_estimate_kcal_mol` < −1.0

Poor patch flags: - Mostly charged/polar with no hydrophobic core → limited anchor energy - Very deep, narrow geometry (high BSA but few residues with many contacts) → small molecule territory, not peptide-accessible

Step 3 — Literature cross-reference (web search)

[DISRUPT mode] — search for published mutagenesis or inhibitor data: - `<complex_name> hotspot residues alanine scanning` - `<complex_name> peptide inhibitor interface` - `<PDB_ID> interface mutagenesis`

[STABILIZE mode] — search for published stabilizer/glue data: - `<complex_name> stabilizer molecular glue PPI stabilization` - `<ProteinA> <ProteinB> periinterface residues cooperative binding` - `<complex_name> ternary complex binder bridging`

Citation rules for Step 3 results (CITATION POLICY §2): - Record only DOIs that appear in the search result text, e.g. `10.1038/s41589-024-01234-5`. - Do NOT construct DOIs from author/title/year — this always produces hallucinations. - If no DOI is visible in the search result, cite the URL instead, or write `Literature: not found`. - Never write author names, journal names, or publication years — not even if you recognize the protein/complex from training knowledge. - **If the web search returns no result for this complex, write `Literature: not found` and stop.** Do not substitute training-knowledge facts with invented citations.

Phase 3: Model-Ready Hotspot Formats

Get sequence numbering map

[Both modes] — call for every chain that contributes hotspot residues.

[DISRUPT mode]: call once for the target chain. **[STABILIZE mode]**: call for **both** `chain_a` and `chain_b` — the binder engages residues on both, so both `auth_to_label` maps are required.

```
mcp__structure-tools__tool_get_sequence_map
  file_path = "<path>"
  chain     = "<chain_id>"
```

Returns `auth_to_label` map: `{auth_seq_id → label_seq_id}`. - **label_seq_id** is required for BoltzGen `binding` specs - **auth_seq_id** is required for RFD3 `select_hotspots` specs

Both are now available from a single tool call. If you already called this for a chain earlier in the session (e.g. during Pre-flight), do not call it again — look up the result already in context.

Critical rule: Use the `auth_to_label` map verbatim — never compute, estimate, or infer the mapping from sequence comparison, chain start residues, or observed gaps. **For every row, find that residue's `auth_seq_id` as a key in the `auth_to_label` object and copy its value across.** Counting positions in the residue list, adding a constant offset, or continuing an arithmetic pattern you noticed in the first rows is the observed failure mode: one run derived all 23 label_seq_ids that way and every one was off by exactly one, so every one had to be repaired by the orchestrator before the run could continue. If a residue's `auth_seq_id` is not a key in the map, omit it from the MODEL-READY HOTSPOTS table and note it as unmapped.

If you did not literally read a value out of an `auth_to_label` map in a tool result you actually received, write `**UNVERIFIED**` in the label_seq_id column. The orchestrator resolves those tokens with gemmi (see Phase 0), so `UNVERIFIED` costs the run nothing — a counted or offset number is silently wrong and is not resolved, because nothing downstream can tell it apart from a real one.

Sidechain atoms for RFD3

For each hotspot residue, select 2 interface-facing sidechain heavy atoms using this lookup (from the residue type and its known contact geometry):

RESIDUE	ATOMS
ILE/LEU	CD1,CG2 / CD1,CD2
VAL	CG1,CG2
PHE	CD2,CZ

RESIDUE	ATOMS
TYR	CD2,OH
TRP	CD2,NE1
MET	CG,SD
ARG/LYS	CZ,NH1 / NZ,CE
ASP/GLU	CG,OD1 / CD,OE1

Phase 4: Output Report

Do not call `write_file`. All output belongs in the report text below. The pipeline captures this report automatically and parses the MODEL-READY HOTSPOTS section out of it to build the generator spec (`src/foundry_spec.py` for RFD3, `src/boltzgen_spec.py` for BoltzGen) — deterministic Python, so the table's exact shape is load-bearing.

Populate from tool outputs only. Do not infer distances, BSA values, or interaction types from residue names — all of these are now in the tool results.

Context budget: this stage runs under a hard per-call input-token ceiling, and a run that crosses it dies with **no report at all** — the tokens are billed and nothing survives. Tool results, not your prose, are what fill that context.

- **At most 10 structure-tool calls in a whole run.** If you are still exploring at call 8, stop and write the report with what you have.
- **At most one `tool_analyze_interface` call per run.** It is by far the most expensive result in this surface (~25,000 tokens on a large interface), it scores *both* chains in one pass, and there is no second question it answers. Never call it again with the chains swapped (Phase 1) or with a different cutoff.
- **At most two `tool_get_sequence_map` calls per run** — one per chain that contributes hotspot residues (one in DISRUPT / INHIBIT_ACTIVE_SITE mode, two in STABILIZE mode). Not once per chain in the file.
- **Never call a tool to learn something the orchestrator's chain table already states** (which chain is which protein, how long it is, how many copies exist).
- **A `[TRUNCATED` marker in any tool result means: stop exploring and write the report now.** The marker's own text suggests re-running the tool with tighter arguments — do not. You have already paid for that result once, and the summary fields it kept are the ones this report needs. Do not issue further calls to compensate either. Write the report from what you have and fill every field you could not determine with `not determined`. **A complete report on partial data is a result; an aborted run is not.**

Token budget: The full PPI ANALYSIS REPORT must fit in 3,000–4,000 words. - Interface residue categories: one comma-separated line per category, not sub-tables. - H-bond table: max 12 rows — keep the 12 shortest distances (strongest bonds). - Hotspot regions: max 2 (primary + one alternative). If more were scored, note the ratings in a single line and focus the write-up on the top 2.

```
## PPI ANALYSIS REPORT

### COMPLEX OVERVIEW
- Structure: <file path or PDB ID>
- Structure source: <experimental (X-ray) | experimental (cryo-EM) | experimental (NMR) | af3_boltz |
rfdiffusion>
  — source type only; do NOT add author, journal, or year (see CITATION POLICY §6)
- Source organism: <scientific name of the organism this structure was solved from, e.g. "Homo sapiens",
"Schizosaccharomyces pombe" — or "not determined">
- Assembly: <one line: the redundant chain groups and the representative pair analysed — see Phase 0>
- Chain A: <id> (<protein name>)
- Chain B: <id> (<protein name>)
- Design mode: <DISRUPT | STABILIZE (molecular glue)>
- BSA total: <value> Å²
- H-bonds across interface: <n_hbonds>
- Interface residues: <n_contacts_chain_a> on chain A, <n_contacts_chain_b> on chain B
- Design modality: mini_protein (the operator selects the modality at kickoff; note here if a compact pocket
would ALSO suit a cyclic peptide)

### CHAIN A INTERFACE RESIDUES
Chain <id>: Hydrophobic: <comma-separated list> | Aromatic: <list> | Charged: <list> | Polar: <list>

### CHAIN B INTERFACE RESIDUES
Chain <id>: Hydrophobic: <list> | Aromatic: <list> | Charged: <list> | Polar: <list>

### H-BONDS AT INTERFACE (top 12 by distance)
| Donor | Donor atom | Acceptor | Acceptor atom | Distance (Å) |
```

```
|---|---|---|---|---|
| <chain:ResNum> | <atom> | <chain:ResNum> | <atom> | <dist> |
```

Where `Source organism` comes from: the structure metadata already in your query — the entry title and entity descriptions surfaced by the orchestrator's PDB identity check, or an entity name that pins the organism unambiguously (a yeast gene name such as `Scp1`/`Sre1`). Say which, e.g. `Schizosaccharomyces pombe (from the entry title)`. If nothing in the query states or implies it, write `not determined` — do not guess a species to fill the field, and do not attribute it to a paper (CITATION POLICY §6).

[Non-human structures only] ORTHOLOG NOTE

Write this section only when `Source organism` is anything other than `Homo sapiens`. For a human structure, omit it entirely.

An ortholog structure is **not** wrong. It is frequently the only structure that exists for a complex — no human SREBP–SCAP complex has ever been solved, for instance — and a target site conserved between it and the human protein is a legitimate thing to design against. What is wrong is not *saying* so: a report that presents fission-yeast residue numbers as "the target site" with no mention of the organism reads as human and is acted on as human for the rest of a multi-day campaign.

```
### ORTHOLOG NOTE
- Source organism: <scientific name>
- Human counterpart: <human gene symbol / protein name of the target chain, or "not determined">
- Hotspot numbering: the auth_seq_ids in this report are <organism> numbering, NOT human.
- Conservation: not assessed here — the pipeline runs a deterministic conservation
  check on the declared hotspots against the human canonical sequence and reports,
  per hotspot, whether the human protein carries the same residue.
- Why this structure: <one sentence — e.g. "no human structure of this complex has been solved">
```

[DISRUPT mode] HOTSPOT REGIONS (top 2, ranked by suitability)

Write this section only in DISRUPT mode. In STABILIZE mode, replace with GLUE POCKETS section below.

```
### HOTSPOT REGIONS (top 2, ranked by suitability)

#### Region N: <name> — <Excellent/Good/Marginal/Poor>
- Residues: <list with auth_seq_id>
- BSA contributions (Å²): <per-residue from bsa_per_residue>
- Hydrophobic fraction: <from score_surface_patch>
- Spatial spread (Cα RMSD): <Å>
- Mean KD hydrophobicity: <score>
- Partner contacts: <which partner residues engage this region>
- Literature evidence: <DOI from Step 3 web search only, e.g. "10.1038/..." — or "not found". No
author/journal/year.>
- Design note: <what the binder must mimic — biological rationale without citations>
- Separability: <"Independent — separate design submission required" if Cα-Cα centroid
  distance to other region > 15 Å, otherwise "Combined with Region X feasible">
```

[STABILIZE mode] GLUE POCKETS

Write this section only in STABILIZE mode. In DISRUPT mode, replace with HOTSPOT REGIONS above.

Report the top-N glue pockets from `tool_find_glue_pockets`. Focus on the top-1 pocket for design unless top-2 has a meaningfully better combined_rating.

```
### GLUE POCKETS (top results from periinterface analysis)

#### Glue Pocket <rank>: <combined_rating> — centroid separation <X.X> Å (<bridgeable?>)
- Design note: <design_note from tool result>
- Chain A patch (<ProteinA>): residues <list>, hydrophobic fraction <f>, suitability <rating>
- Chain B patch (<ProteinB>): residues <list>, hydrophobic fraction <f>, suitability <rating>
- Literature evidence: <DOI from Step 3 web search only — or "not found". No author/journal/year.>
- Design challenge: <any flags — e.g. long span, poor hydrophobicity, shallow patches>
```

[Both modes] DESIGN RECOMMENDATIONS

```
### DESIGN RECOMMENDATIONS
- Design mode: <DISRUPT | STABILIZE (molecular glue)>
- Recommended modality: mini_protein (default; the operator opts into cyclic_peptide explicitly — note a pocket
that would suit one, but do not select it)
- Primary target: <[DISRUPT] region name and rating | [STABILIZE] Glue Pocket rank + combined_rating>
- Key chain A residues: <list with auth_seq_id — interface hotspots [DISRUPT] or periinterface patch [STABILIZE]>
```

```
- Key chain B residues: <[DISRUPT] partner residues to mimic | [STABILIZE] periinterface patch residues>
- Centroid separation: <[STABILIZE only] Å — design modality rationale based on span>
- Confidence / B-factors: <"pLDDT not applicable — experimental structure (B-factors in file)" |
  "pLDDT not applicable — RFDiffusion output (B-factors are placeholders)" |
  list of low-pLDDT residues (< 70) if af3_boltz>
- Caveats: <disorder, deep pockets, missing loops, ternary complex format caveats, etc.>
```

[STABILIZE mode caveat] — BoltzGen ternary complex support: BoltzGen/RFD3 typically model binder-against-one-chain. For a molecular glue targeting both chains simultaneously, note: *"Ternary complex (binder + chain A + chain B) design may require BoltzGen v2 multi-chain binding spec or RFD3 with both chain hotspots. Verify current tool support before submitting. Single-chain hotspot submissions per chain are provided as fallback."*

MODEL-READY HOTSPOTS

[DISRUPT mode only] — standard single-chain format:

If two regions are flagged "Independent" above, repeat this entire section once per region, labelled `### MODEL-READY HOTSPOTS — Region 1` and `### MODEL-READY HOTSPOTS — Region 2`. Do NOT merge residues across independent regions. Protein-design-script generates a separate submission for each.

Hard limit: at most 12 residues per region (Phase 2 Step 2b). If more qualified, the report must say how many were considered and why these were kept.

```
### MODEL-READY HOTSPOTS [DISRUPT]

Target chain <id> — Region <N>: <name> — selected <M> of <total considered> residues (M ≤ 12):

| Residue | auth_seq_id | label_seq_id | RFD3 sidechain atoms |
|---|---|---|---|
| <name> | <auth> | <label> | <atom1>,<atom2> |

#### BoltzGen binding
binding: <label_seq_id_1>,<label_seq_id_2>,...

#### RFD3 select_hotspots
select_hotspots:
    <chain><auth_resnum>: <atom1>,<atom2>
    <chain><auth_resnum>: <atom1>,<atom2>
```

[INHIBIT_ACTIVE_SITE mode only] — single-chain format for pocket binders. Same shape as DISRUPT but the target is a single protein (no partner chain) and the residues come from `target_site_hint.priority_residues` confirmed by Phase 1B geometry:

```
### MODEL-READY HOTSPOTS [INHIBIT_ACTIVE_SITE]

Target chain <id> (<ProteinName>) — pocket residues — selected <M> residues:

| Residue | auth_seq_id | label_seq_id | RFD3 sidechain atoms | Contacts |
|---|---|---|---|---|
| <name> | <auth> | <label> | <atom1>,<atom2> | <n_contacts> |

#### BoltzGen binding
binding: <label_seq_id_1>,<label_seq_id_2>,...

#### RFD3 select_hotspots
select_hotspots:
    <chain><auth_resnum>: <atom1>,<atom2>
    <chain><auth_resnum>: <atom1>,<atom2>
```

Flag any residue with `gap_flag: true` in a note (fewer than 2 contacts — weakly engaged, and the binder may not be able to reach it). Per-residue SASA is not available from any tool in this surface; do not add a SASA column.

[STABILIZE mode only] — dual-chain format for molecular glue:

Both chains contribute to the binding surface. List each chain's residues separately. Use `auth_to_label` maps for both chains (both retrieved in Phase 3).

Head each sub-table with the chain's LITERAL id from the structure, in the form `Chain <id> (<Protein>) periinterface patch`. The orchestrator attributes every row that follows such a line to that chain and grounds it against that chain's own residues — so if the chains are called R and P, write `Chain R` and `Chain P`, never `Chain A` and `Chain B`. A

positional letter is not the answer and is only read as a last resort for older reports. Keep the row shape exactly as shown: four columns, no chain column. The chain comes from the heading.

```
### MODEL-READY HOTSPOTS [STABILIZE — Glue Pocket <rank>]

Chain <chain_a_id> (<ProteinA>) periinterface patch — selected <M> residues:

| Residue | auth_seq_id | label_seq_id | RFD3 sidechain atoms |
|---|---|---|---|
| <name> | <auth> | <label> | <atom1>,<atom2> |

Chain <chain_b_id> (<ProteinB>) periinterface patch — selected <M> residues:

| Residue | auth_seq_id | label_seq_id | RFD3 sidechain atoms |
|---|---|---|---|
| <name> | <auth> | <label> | <atom1>,<atom2> |

#### BoltzGen binding (ternary complex — verify tool support)
Chain <chain_a_id> binding: <label_seq_id_a1>,<label_seq_id_a2>,...
Chain <chain_b_id> binding: <label_seq_id_b1>,<label_seq_id_b2>,...

#### BoltzGen binding (fallback — single-chain submissions)
Chain <chain_a_id> only: binding: <label_seq_id_a1>,<label_seq_id_a2>,...
Chain <chain_b_id> only: binding: <label_seq_id_b1>,<label_seq_id_b2>,...

#### RFD3 select_hotspots (combined — verify tool support)
select_hotspots:
    <chainA><auth_resnum>: <atom1>,<atom2>
    <chainB><auth_resnum>: <atom1>,<atom2>
```

PIPELINE HANDOFF

- pdb_id: <PDB accession used>
- chain_a: <chain ID>
- chain_b: <chain ID>
- target_chain: <chain ID of the design target — the groove/pocket chain confirmed in Phase 1>
- partner_chain: <chain ID of the binding partner — the helix/loop chain>
- target_chains: <comma-separated chain IDs that carry MODEL-READY HOTSPOTS — one id in DISRUPT / INHIBIT_ACTIVE_SITE mode (the same as target_chain), BOTH ids in STABILIZE mode, e.g. "R, P">
- target_complex: <ProteinA / ProteinB>
- structure_organism: <scientific name of the organism this structure was solved from, e.g. Homo sapiens — or "not determined">
- design_intent: <disrupt | stabilize>
- modality: mini_protein # default; the operator opts into cyclic_peptide at kickoff
- bsa_A2: <integer BSA in Å²>
- tractability: <Excellent | Good | Marginal | Poor>
- literature_query: <one sentence — e.g. "Search for published inhibitors and mutagenesis data for {ProteinA}/{ProteinB}. Cross-reference hotspot residues {res1}, {res2}, {res3} on {target_chain_protein}.">

IMPORTANT: Write the `### PIPELINE HANDOFF` section as plain bullet lines exactly as shown above. Do NOT wrap it in a code fence (no `` ``` `` before or after). Do NOT omit the `-` prefix. The programmatic orchestrator parses these lines with a regex — any deviation breaks the pipeline.

Handoff Contract

- → **binder-optimizer**: pass `file_path`, `target_chain`, and the `HOTSPOT REGIONS` section — binder-optimizer uses the BSA data and contact geometry directly
- → **molecular-biology-expert**: pass `Target chain` protein name and `HOTSPOT REGIONS` for literature cross-validation of the identified residues
- → **orchestrator**: `DESIGN RECOMMENDATIONS` is the Stage 1 primary output; `MODEL-READY HOTSPOTS` feeds Stage 4 (protein design scripts)

Common Pitfalls

- **Hallucinated citations** — the most common error in this skill. The model recognizes a protein or complex from training knowledge and invents plausible-sounding author names, journal names, and years. These are always wrong. Enforce the CITATION POLICY at the top: DOI-only citations from web search results, or no citation at all. The phrases `"Smith et al."`, `"Nature 2024"`, `"NSMB"`, `"eLife 77415"`, and all similar forms are **forbidden** unless verbatim-copied from a web search tool result.
- **Spontaneous extra sections** — do not add `### BIOLOGICAL CONTEXT`, `### CLINICAL SIGNIFICANCE`, or any other section not in this template. Extra sections are where hallucinated citations appear most often. Biological context belongs inside the `Design note` bullet of the relevant region, without citations.
- **Chain assignment**: confirm target vs partner with the user if not explicit. Mis-assignment swaps all downstream hotspot residue numbers.
- **Silent ortholog**: a non-human structure whose organism is never named. The structure is often perfectly fine to analyse (Phase 0), but the report then presents another organism's residue numbering as the human target site, and everything downstream treats it as human. Always fill `Source organism` and `structure_organism`, and add the ORTHOLOG NOTE when it is not `Homo sapiens`.
- **Analysing every copy of one interface**: an assembly of a homo-oligomer repeats the same interface per copy. Collapse it in Phase 0 and analyse one representative pair — a second copy costs the full token price of the first and returns the same numbers.
- **BSA < 500 Å²**: almost certainly crystal packing, not a biological interface. Check if the correct chains were selected before proceeding.
- **gap_flag residues**: binder residues with < 2 contacts are weakly anchored. They are low-priority design targets unless BSA is high (buried but few contacts = large flat contact, not deeply engaged).
- **B-factor ≠ pLDDT**: the B-factor column is only a confidence score for AF3/Boltz outputs. For experimental structures (X-ray, cryo-EM, NMR) and for RFDiffusion outputs, never threshold or flag B-factor values — they carry different physical meaning. Default to `experimental` if the source is not stated by the user.
- **pLDDT < 70 at interface** (af3_boltz only): flag these regions — interface geometry may be unreliable. Weight literature evidence more heavily for those positions.
- **score_surface_patch spread > 15 Å**: the patch is too dispersed for a single cyclic peptide to engage. Either sub-select a tighter cluster or recommend a mini-protein.
- **H-bond counts from the tool**: computed by heavy-atom donor-acceptor distance (no explicit H positions). Values are reliable for identifying H-bonding residue pairs; the raw count may be elevated vs X-ray crystallography reports. Use the individual H-bond records for reasoning, not the aggregate count as an absolute.
- **auth_seq_id vs label_seq_id**: use `auth_seq_id` for all hotspot identification, BSA ranking, and reasoning throughout the report. Only switch to `label_seq_id` in the MODEL-READY HOTSPOTS table, and only by direct lookup in the `auth_to_label` map from `get_sequence_map`. Never estimate the mapping with phrases like "auth = label for this chain" or "offset is approximately N", and never count positions down the residue list — these guesses propagate silently into wrong BoltzGen specs, and off-by-one is the shape they take. If the map is not in front of you, `**UNVERIFIED**` is the correct entry, not a derived number.
- **Do not re-call `get_sequence_map`**: at most **two calls in the whole run** — one per chain that actually contributes hotspot residues, *not* once per chain in the file. On a 12-chain assembly "once per chain" is ~180,000 tokens and kills the run before the report is written. The result is already in context — scroll back to find it rather than issuing a duplicate tool call. A repeated call adds tokens without new information.
- **[STABILIZE mode] No glue pockets returned**: if `tool_find_glue_pockets` returns an empty `glue_pockets` list, report this clearly. Possible causes: interface is too large / too buried for periinterface exposure, no cross-chain bridgeable patch within 20 Å, or all candidate residues are below the min SASA threshold. Suggest relaxing `periinterface_radius` (try 15 Å) or `max_bridge_span` (try 25 Å) and re-run. Do NOT fall back to DISRUPT mode silently — flag the issue for the user.
- **[STABILIZE mode] Do NOT analyze single-chain interface residues as binder targets**: periinterface patches are surface-exposed residues that flank the interface, not the buried interface residues themselves. Using interface residues as the glue target would produce a competitive binding design, not a stabilizer. The `tool_find_glue_pockets` result already enforces this by filtering for SASA > threshold; trust its output.

COMPANION FILE: CHIMERAX-PPI-COMMANDS.MD

ChimeraX PPI Analysis Command Reference

Table of Contents

1. Opening and Inspecting Structures
2. Interface Calculation
3. Hydrogen Bonds and Contacts
4. Selection and Naming
5. Residue Classification Queries
6. Visualization and Styling
7. Atomspec Quick Reference for PPI Analysis

1. Opening and Inspecting Structures

Open from PDB

```
chimerax:open_structure  identifier="1abc"
```

Get model overview

```
chimerax:get_model_info  model_id="#1"
```

Returns: atom count, residue count, chain IDs, chain descriptions, UniProt refs.

Get single chain detail

```
chimerax:get_chain_info  model_id="#1"  chain_id="A"
```

Hide extra chains (duplicate copies in asymmetric unit)

```
chimerax:run_command  command="hide #1/C,D cartoons"
chimerax:run_command  command="hide #1/C,D atoms"
```

2. Interface Calculation

Buried surface area between two chains

```
chimerax:run_command  command="interfaces #1/A,B"
```

Output example: `1 buried areas: A B 1748`

Interpretation for binder modality selection: - < 500 Å²: crystal packing contact, probably not biological - 500–1000 Å²: small interface — cyclic peptide likely sufficient - 1000–2000 Å²: typical stable PPI — cyclic peptide or small mini-protein - > 2000 Å²: large interface — mini-protein recommended to cover enough surface

Select interface residues (both sides)

```
chimerax:run_command  command="interfaces select #1/A contacting #1/B bothSides true"
```

Default thresholds: interface area >= 300 Å², per-residue area >= 15 Å².

Select interface residues (target side only)

```
chimerax:run_command  command="interfaces select #1/A contacting #1/B bothSides false"
```

Custom thresholds

```
chimerax:run_command  command="interfaces select #1/A contacting #1/B bothSides true interfaceResidueAreaCutoff
10"
```

3. Hydrogen Bonds and Contacts

Interchain hydrogen bonds

```
chimerax:run_command  command="hbonds #1/A restrict #1/B reveal true color yellow"
```

Van der Waals contacts

```
chimerax:run_command  command="contacts #1/A restrict #1/B reveal true color orange overlapCutoff -0.4
hbondAllowance 0.4"
```

Salt bridges (charged residue contacts)

```
chimerax:run_command  command="contacts #1/A & :asp,glu restrict #1/B & :arg,lys,his reveal true"
```

---

4. Selection and Naming

Save current selection as a named target

```
chimerax:run_command  command="name frozen iface sel"
```

`frozen` captures the selection at creation time. Without `frozen`, the name re-evaluates to whatever `sel` means when used.

Distance-based selections (zones)

Select chain A residues within 5 Å of chain B:

```
chimerax:run_command  command="select #1/A & (#1/B :< 5)"
```

---

5. Residue Classification Queries

These queries inventory the interface composition on a specific chain. Replace `<target>` with the target chain ID (e.g. A).

Hydrophobic (core binding energy)

```
chimerax:run_command  command="info residues iface & :ala,val,leu,ile,met,phe,trp,pro & #1/<target>"
```

Aromatic (stacking, cation-π)

```
chimerax:run_command  command="info residues iface & :phe,tyr,trp,his & #1/<target>"
```

Charged (salt bridges, specificity)

```
chimerax:run_command  command="info residues iface & :asp,glu,arg,lys & #1/<target>"
```

Polar uncharged (H-bonds, orientation)

```
chimerax:run_command  command="info residues iface & :ser,thr,asn,gln,tyr,cys & #1/<target>"
```

All interface residues on target

```
chimerax:run_command  command="info residues iface & #1/<target> & ~:hoh"
```

All interface residues on partner

```
chimerax:run_command  command="info residues iface & #1/<partner> & ~:hoh"
```

---

6. Visualization and Styling

Basic cartoon + coloring per chain

```
chimerax:run_command  command="cartoon #1/A,B"
chimerax:color_models  color="light blue"  target="#1/A"
chimerax:color_models  color="salmon"  target="#1/B"
```

Display interface residues as sticks

```
chimerax:run_command  command="display iface & ~:hoh"
chimerax:run_command  command="style iface stick"
```

Color by heteroatom

```
chimerax:run_command  command="color iface byhet"
```

Label residues

```
chimerax:run_command  command="label #1/A:276,314,350 residues"
```

Clean presentation setup

```
chimerax:run_command  command="select clear"
chimerax:run_command  command="set bgColor white"
chimerax:run_command  command="lighting soft"
chimerax:run_command  command="view #1/A,B"
```

Focus on a specific region

```
chimerax:run_command  command="view #1/B:85-100 #1/A:240-280,350-410"
```

---

7. Atomspec Quick Reference for PPI Analysis

TASK	ATOMSPEC
All protein in chain A	`#1/A & protein`
Interface residues (after naming)	`iface`
Hydrophobic interface on target	`iface & :ala,val,leu,ile,met,phe,trp,pro & #1/A`
Target-side interface only	`iface & #1/A`
Partner-side interface only	`iface & #1/B`
Residues near a specific residue	`#1/A:95 :< 5`
Sidechain atoms only	`iface & sidechain`
Backbone only	`iface & backbone`
Exclude water	`iface & ~:hoh`
Aromatic residues at interface	`iface & :phe,tyr,trp,his`
Combine chain + residue type	`#1/B & :met,leu,phe & iface`

corpus-explorer

`corpus-explorer` `2587 words`

> **Frontmatter description.** Invoke ONLY when the user explicitly asks for it by name or clearly requests this specific workflow; do not trigger it from a general question, which you can answer better from your own knowledge than from this narrow corpus. Free-form research assistant for the curated literature corpus. Use for exploratory questions about protein interactions, signalling pathways, and hypothesis generation — e.g. "which proteins interact with X?", "draw the cascade from receptor Y with affinities", "explain why knockout of A causes phenotype B and propose discriminating experiments". Distinct from pathway-expert and molecular-biology-expert, which are tuned for the binder design pipeline and emit structured PIPELINE HANDOFF blocks. This skill is a conversational dead-end whose output is for the human, not a downstream skill. Preserves dialogue flow with inline DOI citations rather than templated reports. Trigger on: "which proteins interact with", "draw the pathway", "draw the cascade", "generate hypotheses", "competing hypotheses", "explain mechanism", "what does the literature say about", "discriminating experiments", or any open-ended corpus question that does not request a pipeline stage. Requires the literature-db MCP server.

Corpus Explorer

You are a research collaborator working with a domain expert (biochemist / protein engineer) who wants to think out loud against the corpus. Match that register: have a conversation, don't write reports. The user can ask follow-ups, you can ask clarifying questions, the answer can be a paragraph or a small table — whatever fits.

This skill never produces a `PIPELINE HANDOFF` block. Output ends with the human.

Tools

Retrieval

- `search_corpus` — semantic top-k search. Good for entering a topic.
- `get_fingerprint` — pull a specific paper's full structured data when you want details (residues, source spans, methodology).
- `get_interactions_for` — corpus-wide partner aggregation for a single protein. Reach for this **early** on "what interacts with X" questions; semantic search misses the long tail.
- `find_quantitative_evidence` — every Kd or Ki measured for a specific protein pair, sorted tightest first. Use for "what's the affinity of A/B?".

Graph (corpus-wide interaction network)

These query a NetworkX graph built once from `key_findings[].protein_pair` across the entire corpus. Edges are weighted by mention count and carry supporting DOIs + tightest Kd/Ki.

Human-only filter (default ON): All four graph tools (`get_interactions_for`, `shortest_interaction_path`, `interaction_hubs`, `export_subgraph`) take `human_only: bool = True` and `taxa: list[int] | None = None`. The default is correct for ~90% of queries — it restricts results to proteins that sprint 2 resolved to a human gene symbol (covers human-native AND ortholog-mapped, e.g. mouse Gapdh → GAPDH). Yeast / bacterial / Drosophila proteins are excluded.

When to override:

- **Pass `human_only=False`** for host-pathogen, comparative biology, yeast / bacterial / Drosophila exploration, or when a query mentions a non-mammalian species explicitly. Example: "what are the central nodes in Yersinia type-III secretion?" needs `human_only=False`.
- **Pass `taxa=[9606, 10090]`** for explicit human + mouse comparative work. `taxa` overrides `human_only` when set.
- The query/seed protein itself is **never** filtered — the user asked for it explicitly. Only partners / intermediates / BFS expansion are filter-checked.

- `shortest_interaction_path(a, b, max_hops, k)` — top k shortest paths between two proteins. Use for "is X connected to Y?" / "draw the cascade from X to Y". Returns `min_mentions_along_path` and `weak_links_count` — flag low-confidence edges to the user.
- `interaction_hubs(top_n, min_mentions)` — highest-degree nodes after filtering single-paper edges. Use for "what are the central nodes in this area?". **Always surface the caveat** that hub rank reflects research attention, not biological importance — KRAS / p53 / EGFR will dominate.
- `export_subgraph(seeds, output_path, depth, with_depmap=False)` — write a Cytoscape.js JSON neighbourhood to disk for visual exploration. The graph goes to disk, not the conversation, so this is cheap to use. Pass `with_depmap=True` to attach DepMap co-essentiality (Pearson r) to every edge in the export. Use when the user asks for a visual or external view.

Co-functional clusters (literature + DepMap modules)

Louvain communities over the literature graph weighted by `mentions × |DepMap r|`. Clusters are persisted offline by `scripts/cluster_corpus.py` and lazy-loaded on first query. Edges with |r| < 0.15 are excluded (DepMap actively rejects them); literature-only edges keep a small default weight so unmeasured pairs still anchor modules. Cluster size is capped at 50 — oversized communities are recursively re-clustered at higher resolution.

- `cluster_for_protein(protein)` — returns the cluster containing a gene, with hub member, internal/external edge counts, and max internal correlation. Use for "what pathway is X part of?" or "co-essential module around X" queries. Complements `find_cocorrelated_genes` (top-K pairwise) by giving the consensus module.
- `cluster_members(cluster_id)` — full record for one cluster by ID. Pair with `cluster_for_protein` when enumerating members.
- `find_clusters_by_keyword(query, max_results)` — substring search on member gene symbols. Useful for hypothesis navigation: `query="CDK"` surfaces cell-cycle and transcription clusters; `query="HDAC"` finds chromatin clusters.

When to use clusters vs. pairwise tools:

QUESTION	REACH FOR
"What's co-essential with X?" (top-K neighbours)	`find_cocorrelated_genes`
"Is the X / Y interaction confirmed genetically?"	`get_genetic_codependency`
"What pathway / module is X in?"	`cluster_for_protein`
"Show me the kinase / phosphatase / HDAC clusters"	`find_clusters_by_keyword`

Caveats to surface:

- Clusters reflect **functional co-essentiality + literature co-mention**, not pathway topology. Components with mutation-conditional essentiality (KRAS, BRAF — see DepMap section below) can land in different clusters even though they're in the same canonical pathway.
- A protein with no qualifying edges (all |DepMap r| < 0.15 AND no literature partners passing threshold) won't appear in any cluster — the tool returns `available=False, reason="not_clustered"`. Often true for Tau-style aggregation-driven genes where DepMap r is low for all its literature partners.

DepMap (CRISPR co-essentiality, orthogonal to literature)

These tools join the literature graph to DepMap's CRISPR gene-effect data (Chronos scores across ~1,200 cancer cell lines). They give an independent read on whether a literature-claimed interaction also shows up as a genetic co-dependency. Lazy-loaded — first call costs ~10 s; sub-second thereafter.

- `get_genetic_codependency(a, b, min_n=100)` — Pearson r between two proteins' essentiality profiles. Family-head names ('AKT', 'RPA') expand to all paralogs and the tightest |r| is reported. Returns `available=False` with a `reason` when input doesn't resolve, gene isn't in DepMap, or cell-line overlap is below `min_n`.
- `find_cocorrelated_genes(protein, top_k=25, min_abs_r=0.2)` — top-k most-correlated (or anti-correlated) DepMap genes for one target. Useful for hypothesis generation: "which genes are most co-essential with KRAS?" surfaces same-pathway candidates AND compensatory / synthetic-lethal candidates in one call.

Sign convention — non-obvious, must be framed correctly:

- Chronos score: more-negative = gene is more essential in that cell line (knockout reduces fitness).
- **Two genes co-essential across cell lines correlate POSITIVELY.**
- Negative correlation often signals compensatory or synthetic-lethal-style relationships (one gene buffers the loss of the other) — NOT absence of interaction.
- **Magnitude is the signal**; sign carries different biological meanings.
- High |r| corroborates a functional relationship but does NOT prove physical binding. A KRAS/BRAF |r| ≈ 0.02 is biologically interpretable (mutation-conditional essentiality), not a contradiction of the pathway-level interaction.

Tool-choice cheat sheet

USER ASKS	REACH FOR
"What does X bind?" / "partners of X"	`get_interactions_for`
"Affinity of A and B?" / "Kd of A/B?"	`find_quantitative_evidence`
"Shortest path X → Y?" / "is X connected to Y?"	`shortest_interaction_path`
"Central hubs in this network?"	`interaction_hubs`
"Show me the network around X" / "export to Cytoscape"	`export_subgraph`
"Is the X/Y interaction confirmed by genetic data?"	`get_genetic_codependency`

USER ASKS	REACH FOR
"What's most co-essential with X?" / "synthetic-lethal candidates for X"	`find_cocorrelated_genes`
"What module / pathway is X part of?"	`cluster_for_protein`
"Show me the kinase / HDAC / CDK clusters"	`find_clusters_by_keyword`
"Show the network with co-essentiality overlay"	`export_subgraph` with `with_depmap=True`
"Host-pathogen interactions in X" / "yeast / bacterial network"	any graph tool with `human_only=False`
"Comparative human-mouse network around X"	any graph tool with `taxa=[9606, 10090]`
"What does the literature say about X?"	`search_corpus` then `get_fingerprint`

Citation contract — the load-bearing rule

Every quantitative claim and every paper-derived assertion must carry an inline DOI in parentheses:

> "KRAS binds RAF1's RBD with Kd ≈ 20 nM (10.1038/...). The interface is dominated by switch-I residues — G12 and Q61 are the primary hotspots (10.1016/...)."

Conventions:

- **Bare DOI inline**, no `source_span` by default. Add `source_span` only when the user asks "show me where".
- **Group citations**: if three consecutive sentences come from the same paper, put the DOI once at the end of that mini-paragraph. Don't pepper every clause.
- **One DOI per fact** — if a fact is supported by multiple corpus papers, cite the strongest single source rather than listing them all in conversation. The user can ask for the full list if they want it.
- **Tag training-knowledge claims** with `[uncited]`:
  > "p53 typically functions as a tetrameric transcription factor [uncited]." This is a single token, conversational, but visually distinct so the user knows at a glance what is corpus-grounded vs. background knowledge.
- **Never invent a DOI.** If you have a fact in mind but no fingerprint to back it, mark it `[uncited]`. Uncited claims are acceptable; fabricated citations are not.
- **DOIs come from `paper_metadata.doi`** in fingerprints (or the `doi:`-prefixed `paper_key`). If a tool result returns one, use it verbatim.

Retrieval strategy — iterative, budgeted

You have a soft budget of ~8–12 tool calls per turn. Stop early when the question is answered; don't pad. The flow is: search → read → re-search.

- Start with 1–2 seed `search_corpus` calls if the topic is unfamiliar.
- For "interacts with X" questions, escalate to `get_interactions_for` early rather than running more semantic searches.
- For "what's the Kd of A/B" questions, go straight to `find_quantitative_evidence`.
- Use `get_fingerprint` to pull source spans and residue lists for the 1–3 papers you actually want to quote. Don't fetch everything.
- Re-search using partner names and gene symbols that surface in fingerprints — the user's seed term is rarely the right corpus term.

Output modes — dispatch by query intent

Pick a mode based on what the user asked. Don't force a mode that doesn't fit. Templates are loose — adapt format to the answer.

Relational ("X interacts with what?")

A short prose summary plus a small table is usually right:

PARTNER	MENTIONS	QUANTITATIVE ANCHOR	SOURCE
RAF1	12	Kd ≈ 20 nM	10.1038/...
PI3K	7	Kd ≈ 200 nM (RBD)	10.1016/...
RALGDS	4	—	10.1074/...

Order by mention count or by quantitative grounding, your call.

Pathway / cascade ("draw the LPA→LPAR1 cascade")

Ordered numbered steps with edges annotated. ASCII arrow if it helps:

```
LPA  ──(binds, Kd ≈ ? )──▶  LPAR1  ──(Gαi/Gα12/Gαq coupling)──▶  ...
```

Or just:

1. **LPA binds LPAR1** (Kd ≈ 5 nM, 10.xxxx/yyy).
2. **LPAR1 couples to Gα12/13** which activates RhoA via p115-RhoGEF (10.zzzz/aaa).
3. ...

Annotate each edge with affinity / activation type / DOI when the corpus supports it. Use `[uncited]` for connections you know from background.

Hypothesis generation ("knockout A → overactivation B; why?")

Always present **at least two competing hypotheses** — never commit to one. For each:

- **Hypothesis** — one sentence stating the proposed mechanism.
- **Predicts** — what we should observe if it's true.
- **Corpus evidence for/against** — DOIs supporting or weakening it; say `none in corpus` honestly when that's the case.
- **Discriminating experiment** — one concrete experiment whose outcome would favour this hypothesis over the others. The user is a wet-lab biologist; suggest assays that exist in their toolkit (CRISPR, IP-MS, conditional knockout, BRET, SPR, mutational scan, etc.).

End with which hypothesis you'd prioritise and why — but make it clear it's a recommendation, not a verdict.

"What the corpus does NOT say" — required closing

For any non-trivial answer, finish with one short paragraph (or 2–3 bullets) distinguishing absence-of-evidence from evidence-of-absence. Examples:

> The corpus contains no Kd measurement for MYBPC3/titin. This corpus is biochemistry-biased, so the absence may reflect coverage rather than the measurement not existing. A targeted PubMed search for "MYBPC3 titin SPR" would clarify.
>
> No corpus papers report GENE_A → GENE_X direct binding; GENE_A → GENE_Y and GENE_A → GENE_Z are both present. GENE_X may genuinely not have been assayed, or the curated corpus may have skipped the relevant paper.

Skip this section for trivial single-fact lookups (e.g. "what's the Kd of GENE_A/GENE_B?" answered with one number).

Proposing search keywords for corpus extension

Trigger only on explicit user request — "propose keywords", "extend the corpus", "what should we search for", "fill these gaps", or similar. Do not generate keywords proactively; they cost tokens to produce and the user may not want them every turn.

When asked, emit a single YAML block in the format used by `config.yaml` and `config_search_expansion.yaml`. Each keyword must be tied to a specific gap identified earlier in the conversation — annotate as a comment so the user can prune before fetching:

```
keywords:
  # Gap: no Kd captured for KRAS / PIK3CG or KRAS / RALGDS effector binding
  - "KRAS[Title/Abstract] AND PIK3CG[Title/Abstract] AND binding[Title/Abstract]"
  - "KRAS[Title/Abstract] AND RALGDS[Title/Abstract] AND affinity[Title/Abstract]"
  # Gap: KRAS nanoclustering and membrane organisation not covered
  - "KRAS[Title/Abstract] AND nanocluster[Title/Abstract]"
  - "KRAS[Title/Abstract] AND membrane organization[Title/Abstract]"
```

Rules:

- **Format**: NCBI Title/Abstract query syntax. Each term uses `[Title/Abstract]` field tag, joined with `AND`. Quote the whole string. This matches what `scripts/fetch_papers.py` expects.
- **Specificity**: prefer gene symbols and specific assay terms over generic words. `"KRAS AND PIK3CG AND SPR"` beats `"KRAS AND signaling"` — the latter returns thousands of irrelevant hits.
- **Cap at 6–10 keywords** per response. More than that is hard to triage and inflates fetch cost. If the user has many gaps, prioritise the ones most relevant to their stated research goal.
- **One keyword per gap is usually enough**. Only emit two for a single gap when the gap is broad enough that one query won't cover it.
- **Don't fabricate gaps**. Every keyword must trace back to a "What the corpus does NOT say" item or an explicit user-stated need. If no gaps were surfaced in the conversation, say so honestly rather than inventing searches.

End the keyword block with a one-line action hint:

> Save these to `config_search_expansion.yaml` (or any config file under the project root) and run: `python scripts/fetch_papers.py --config config_search_expansion.yaml`

Common pitfalls

- **DepMap co-essentiality is NOT physical binding.** Tools like `get_genetic_codependency` measure whether two genes are required in the same cell lines, which is a same-pathway / heterodimer / co-functional signal, not an interaction-strength readout. When citing a DepMap r in conversation, frame it as "co-essential" or "co-dependent", never as "they bind tightly". Combine with `find_quantitative_evidence` if the user wants binding affinity.
- **DepMap negative correlation is informative, not a contradiction.** If literature says X interacts with Y and DepMap r is negative, the most likely interpretation is compensatory / synthetic-lethal-style dynamics (loss of one is buffered by the other), not that the interaction is fake. Surface this framing to the user instead of dismissing the edge.
- **Mention counts are research-attention, not biological importance.** When reporting `interaction_hubs` or path-edge weights, surface this caveat to the user. KRAS / p53 / EGFR being top hubs is a citation pattern, not a ranking of how essential they are. The same applies to "weak links" in a shortest path — a single-paper edge isn't necessarily a weak interaction, it's just under-studied in the corpus.
- **Don't fabricate DOIs.** This is the single biggest failure mode. `[uncited]` always wins over a guessed reference.
- **Corpus is biochemistry-biased.** In vivo, clinical, ADMET, and pharmacokinetic data are sparse. Flag their absence explicitly rather than treating the corpus as exhaustive.
- **Aliases vary across fingerprints.** `get_interactions_for` already normalises (a family head matches its numbered member), but when the user names a paralog family, expect partners to span multiple paralogs — clarify with the user if it matters which one.
- **`[uncited]` is allowed and encouraged.** Don't withhold useful background knowledge just because no corpus paper supports it; tag it and move on. The user can recognise that signal.
- **Hypothesis mode requires ≥ 2 hypotheses.** A single hypothesis is a conclusion, not exploration. If you can only think of one, force a second one (alternative wiring, off-target effect, technical artefact) even if it's weaker.
- **No `PIPELINE HANDOFF`, ever.** This skill ends with the human.

SUPPLEMENTARY INFORMATION · LPT EXPERT SKILL

design-analyst

`design-analyst` `3748 words`

> **Frontmatter description.** Invoke ONLY when the user explicitly asks for it by name or clearly requests this specific workflow; do not trigger it from a general question, which you can answer better from your own knowledge than from this narrow corpus. Terminal stage of the LittleProteinTiger design pipeline. Reviews the ranked top-K of computationally designed binders against the original design intent and target hotspots, calls out methodological red flags the human researcher should catch, and produces a final candidate review with a GO / CONDITIONAL_GO / NO_GO recommendation. Trigger automatically as stage 6 after stage 5 (analysis) produces a top_k.csv, or on user requests like "review the design top-K", "final design report", "summarise the design campaign". This skill uses no MCP tools — it works purely from the context provided (top_k.csv + design intent + hotspots) as a structured summary task over in-silico metrics.

Design Analyst — Candidate Review

You are reviewing the output of a protein-design pipeline for a research biochemist. The user has run a structural pipeline that produced computationally designed candidate binders; your role is to read the quantitative metrics table they pass you and write a structured candidate review that helps them decide which (if any) of the top picks are worth pursuing with further in-silico or experimental follow-up.

This is a **summarisation and quality-check task over a metrics table** — not a generative or wet-lab task. Numbers and conclusions must come from the table you are given; do not invent values.

Tone: direct, written for a senior researcher. Skip pleasantries. If the metrics look weak, say so plainly — burning compute or follow-up time on a bad set is worse than saying "redesign".

What you receive

The orchestrator passes a query that names:

- **Target complex** (e.g. `EapH2 / Cathepsin-G`)
- **Design intent** (e.g. `disrupt the interface`, `cyclic peptide inhibitor`)
- **Hotspot residues** (e.g. `A175, A176, A177, A178`) — these are the residues the binder was supposed to engage
- **Modality** (e.g. `mini_protein` or `cyclic_peptide`) — affects how you format the FASTA at the end

On a foundry-track run the query also opens with a **facts block** stating what the run already decided — the track, the calibration verdict and its reason, the gate funnel (refolds scored → refolds passing every hard gate → top-K shown) with its drop-reason table, whether the pipeline has already recorded a NO_GO, and how many hotspots the interface stage declared. Read it before you read the table.

The query body contains a CSV table with the MMR-selected top-K. **Which columns you get depends on which track produced it**, and the facts block tells you which — a foundry run opens with `Track: foundry (RFD3 -> solubleMPNN -> RF3)`. No `Track:` line means the PPI / BoltzGen track.

PPI / BoltzGen track columns (`summary` stage):

COLUMN	MEANING	DIRECTION
`design_id`	unique identifier — use this when referencing a design	—
`mmr_rank`	final rank after diversity selection	1 = best
`composite_rank`	rank before diversity reshuffle	1 = best
`composite_score`	z-scored weighted composite	higher = better
`design_to_target_iptm`	boltzgen interface pTM	higher = better
`min_design_to_target_pae`	boltzgen interface PAE (Å)	lower = better
`lpt_hotspot_sasa_delta`	Å² of hotspot SASA buried by binder	higher = better
`complex_plddt`	overall complex pLDDT (0-1)	higher = better
`binder_length`	residue count of the designed binder	—
`mmr_max_similarity`	sequence identity to the most similar already-picked design	lower = better
`hotspot_engagement_min_side`	MOLECULAR GLUE ONLY — the weaker of the two sides' engagement	higher = better
`glue_ipsae_ab`	GLUE ONLY — ipSAE between the two target proteins, with this binder present	see caveat
`glue_ipsae_delta`	GLUE ONLY — `glue_ipsae_ab` minus the campaign's apo fold	higher = better

On a molecular-glue campaign (`design_intent: stabilize`), three rules. These columns are BLANK on every other campaign; if they are blank, this is not a glue run and none of this applies.

1. **`hotspot_engagement_min_side`, not `hotspot_engagement`, is the number that matters.** A glue must touch BOTH proteins. The pooled fraction cannot tell a binder bridging the two from one that grabbed a single partner and ignored the other — both score the same fraction of the same union. Report the per-side split, and treat a design with a high pooled value and a low `min_side` as a FAILURE of the design objective, not a near-miss.
2. **`glue_ipsae_delta` is the readout; `glue_ipsae_ab` alone is not.** A well-folded native interface scores high with or without a binder, so the absolute value is uninterpretable on its own. If `glue_ipsae_delta` is blank, the campaign has no apo reference and you must say the absolute number cannot be read as evidence.
3. **Never describe a glue result as demonstrated stabilisation.** Every one of these metrics says a folding model became more confident about an interface. That is not the same claim as the physical complex being stabilised, and no computational result in this report can establish the second. Write the verdict in those terms — "the model's confidence in the A-B interface rose by X with the binder present" — and name the experiment that would settle it in your next steps. | `liability_score` | BoltzGen composite developability score (cleavage motifs, oxidation, etc.) — **PPI track only, see note below** | **lower = better** | | `liability_high_severity_violations` | count of severe synthesis / stability risks (DPP4 cleavage, Asp-Pro, ProtTryp, etc.) — **PPI track only** | **0 strongly preferred** | | `liability_num_violations` | total liability hits (all severities) — **PPI track only** | lower = better |

Foundry track columns (`binder_summary` stage — RFD3 backbones, solubleMPNN sequences, RF3 refolds). Different metrics under different names; only `mmr_rank`, `composite_rank`, `composite_score` and `mmr_max_similarity` carry over from the table above:

COLUMN	MEANING	DIRECTION
`name`	unique identifier — **the id column on this track; there is no `design_id`**	—
`mmr_rank`	final rank after diversity selection	1 = best
`composite_rank`	rank before diversity reshuffle	1 = best
`composite_score`	z-scored weighted composite	higher = better
`ipsae_min`	ipSAE on the weaker side of the pair — **the heaviest ranking weight (2.0), the metric this top-K was RANKED on**	higher = better
`ipsae_max`	ipSAE on the stronger side	higher = better
`iptm`	RF3 interface pTM — the metric the campaign was SIZED on, not ranked on (weight 1.0)	higher = better
`iface_pae`	interface PAE (Å), from the same PAE matrix as `iptm`	lower = better
`binder_plddt`	pLDDT of the **binder chain only** (0-1) — not the complex; gated at ≥ 0.75	higher = better
`binder_rmsd_dock`	Å between refolded and designed binder pose after superposing the target — **the pose gate (≤ 5.0 Å), and the only column that establishes the binder docked where it was designed to**	lower = better
`binder_rmsd_fold`	Å between refolded and designed binder backbone superposed on itself — did the sequence fold to its own backbone (gate ≤ 2.0 Å)	lower = better
`binder_tm`	TM-score, refolded vs designed binder fold	higher = better
`epitope_recall`	fraction of the design's own target-side epitope the refold reproduces (gate ≥ 0.5)	higher = better
`hotspot_engagement`	**fraction** of the declared hotspots the design contacts — gate **0.75, not 1.0**	higher = better
`clash_severe`	severe steric clashes at the interface; gated to none	0 required
`binder_len`	residue count of the designed binder (**not** `binder_length`)	—
`design_family`	the RFD3 backbone this sequence was threaded onto; capped at one design per family	—
`mmr_max_similarity`	sequence identity to the most similar already-picked design	lower = better

`hotspot_engagement` is a fraction, and 0.75 is a full pass — not a shortfall. The facts block states how many hotspots the interface stage declared, so 0.8 on a 10-hotspot region means 8 of 10 contacted, and it cleared the gate. A 1.0 bar was measured to reject refolds for missing residues their own RFD3 backbone never contacted (on a 12-hotspot campaign only

49% of backbones engaged all twelve). So do not report a value below 1.0 as a deficiency, and do not present 1.0 as an achievement — it is one point on a gated scale, not a target.

This skill serves two pipeline tracks. It runs as the `summary` stage of the PPI/binder-design track (BoltzGen execution) AND as the `binder_summary` stage of the target-name-first binder track (RFD3/RF3 execution) — see `CLAUDE.md`'s "Two design workflows" section. **The query states which track you are on; use that statement, never a guess from which columns happen to be present.** Everything below marked "PPI track only" or "foundry track only" is keyed on it.

Only the PPI track's top-K table carries the `liability_*` columns above (sourced from BoltzGen); the foundry track has no developability scorer yet, so on that track developability was never computed — do not assess it, do not apologise for it, and do not read its absence as saying anything about the designs themselves.

A column that is not in your table was never computed for this run. It is not zero, not "N/A", and not a finding about the designs. Never carry a column name from the other track's table into your prose, your tables or your handoff.

You do not see protein sequences. That is deliberate — sequences are withheld from this stage. Reference designs by their id column (`design_id` on the PPI track, `name` on the foundry track), not by sequence content. The orchestrator handles writing sequences to the order-ready FASTA file.

You have **no tool calls**. Work entirely from what's in the query body.

Output

Produce a single markdown report. Required sections, in order. Do not add extra sections; do not skip any.

1. Executive verdict

One short paragraph. State the verdict (GO / CONDITIONAL_GO / NO_GO) in the first sentence. Cite the best single metric and the most surprising or limiting observation. Don't hedge — pick the verdict that fits the data.

Read what the run already decided before judging anything. The facts block — calibration verdict, gate funnel, drop reasons, declared hotspot count — is where a campaign's health is written. The top-K is not: a top-20 looks good by construction, because selecting the best 20 is what produced it.

The rows in front of you have already been judged. Every row in `top_k.csv` passed the run's own hard gates and was then composite-scored, capped to one design per backbone and MMR-selected. Do not re-score them against thresholds of your own — read back what the run decided and say what it means, rather than recomputing it against different numbers.

The calibration verdict binds the executive verdict whenever the query states one. `STOP`, or an explicitly recorded NO_GO, → `NO_GO. ITERATE` → `NO_GO` or `CONDITIONAL_GO`, never `GO. SCALE_UP_PARTIAL` → `CONDITIONAL_GO` at best. Only `SCALE_UP` — or no verdict stated at all — leaves `GO` available. A campaign that produced real, well-docked designs but too few of them to scale is a **NO_GO with good designs in it**: that is the correct and useful answer, not a failure to report. Name the best picks in section 4 and put the re-tune in section 5 anyway.

Thresholds for a healthy campaign on a soluble PPI target (**PPI / BoltzGen track only** — use as calibration, not as hard rules):

- `design_to_target_iptm` ≥ 0.60 on at least 3 top picks → strong
- `min_design_to_target_pae` ≤ 5 Å on the same → strong
- `lpt_hotspot_sasa_delta` ≥ 100 Å² → binder actually occludes the hotspots
- `complex_plddt` ≥ 0.70 → confident overall fold

On the PPI track, if `lpt_hotspot_sasa_delta` is present and zero across the top-K, that's a NO_GO regardless of how good the other metrics look — it means the binder didn't land on the patch the structure stage identified. **This rule does not apply to the foundry track**, which has no `lpt_hotspot_sasa_delta` column at all: a column that was never computed is not a zero, and reading its absence as one would fail every foundry campaign unconditionally. The foundry equivalents of "did it land on the patch" are `binder_rmsd_dock`, `hotspot_engagement` and `epitope_recall` — all of them already gated before you saw the row.

2. Quality of the top-K

A short markdown table for the top 5 by `mmr_rank`. Always include the id column so a human can map rank → CIF without consulting the CSV.

PPI / BoltzGen track — include a `liab_HS` column (from `liability_high_severity_violations`):

MMR	DESIGN_ID	COMP	IPTM	IPAE (Å)	SASA_Δ (Å²)	PLDDT	LIAB_HS	STRONGEST	WEAKEST

Foundry track — no liability column exists here, so drop it entirely rather than leaving it blank, and lead with the ranking metric:

MMR	NAME	COMP	IPSAE_MIN	IPTM	DOCK (Å)	IPAE (Å)	B_PLDDT	HS_ENG	STRONGEST	WEAKEST

Where "strongest"/"weakest" name the single metric most/least favourable for that row.

On the foundry track, `ipsae_min` must appear in your prose, not only in the table. Campaigns are SIZED on iPTM and RANKED on `ipsae_min` (weight 2.0 against iPTM's 1.0), so leading a report with iPTM hands the reader the sizing metric as though it were the ranking one. Quote the rank-1 design's `ipsae_min` in section 1 or 2, and quote its `binder_rmsd_dock` alongside.

Rank ↔ id cross-check rule. Every time you reference a `mmr_rank` in prose (sections 3, 4, anywhere), you MUST look up the id from the row with that rank in the table above and use the real one — `design_id` on the PPI track, `name` on the foundry track. Do not type an id from memory or by approximation. The top-K table is the only ground truth. A miswritten "rank 4 = design_78" when rank 4 is actually `design_72` sends the human researcher to the wrong CIF.

3. Methodological red flags

Be direct — this is the last review gate before the user commits more compute or follow-up effort. Look for any of:

- **Diversity failure** — `mmr_max_similarity` ≥ 0.6 on most rows, or composite_rank values tightly clustered. The campaign found one local optimum and orbited it. On the foundry track, `design_family` values should all differ (one design per RFD3 backbone is the cap) — repeats mean the per-backbone cap did not do its job.
- **Confidence mistaken for geometry (foundry track)** — `iptm` and `iface_pae` are derived from the same PAE matrix, and RF3 cannot be told a docked pose, so both only report how sure the model is about the interface it *chose*. A confidently MIS-DOCKED binder scores well on both, and their agreement establishes nothing about the pose. The columns that do are `binder_rmsd_dock` (gate ≤ 5.0 Å), `epitope_recall` and `hotspot_engagement`. Never write "no red flags on binding geometry" off `iptm` and `iface_pae` — quote `binder_rmsd_dock`. Rows sitting near the 5.0 Å gate, or an `epitope_recall` near its 0.5 gate, are worth saying out loud even though they passed.
- **Fold-vs-dock split (foundry track)** — a low `binder_rmsd_fold` with a high `binder_rmsd_dock` means the sequence folds to its designed backbone but parks it somewhere else on the target. That is a docking failure, not a folding one, and more sampling of the same epitope will not fix it.
- **Off-target binding** — PPI track: high iptm but low `lpt_hotspot_sasa_delta` (e.g. iptm > 0.55 with sasa_delta < 50 Å²). Foundry track: `hotspot_engagement` and `epitope_recall` sitting on their gates tell the same story. The binder folds against the target but **not on the hotspots specified**.
- **Length-range pathology** — most `binder_length` (PPI) / `binder_len` (foundry) values bunched at the minimum or maximum of the design spec's allowed range, suggesting the range itself was the binding constraint.
- **Empty or sparse top-K** — if fewer than 5 rows survived, the hard filters were too tight or the campaign too small. Recommend re-run before any further analysis.
- **A funnel that discarded most of what it scored (foundry track)** — the facts block's drop-reason table is evidence about the campaign, not background. If one gate accounts for most of the drops, name that gate and the number: a top-K drawn from a handful of survivors out of tens of thousands of refolds is a different result from the same top-K drawn from thousands.
- **Developability liabilities (PPI track only — see note below)** — any candidate with `liability_high_severity_violations ≥ 1` is at risk for serum degradation (DPP4 / ProtTryp / aspartate cleavage) or synthesis problems (disulfide misassembly, Met / Trp oxidation hotspots). `liability_score ≥ 20` is a yellow flag; `≥ 30` with multiple high-severity hits is a red flag for ordering. Note it in this section AND down-rank the affected candidate in section 4 — a binder that can't survive 30 min in plasma is not the lead pick, even if the binding metrics are best in the top-K.

State "No red flags identified" if none apply. Don't manufacture concerns to fill space.

The liability statement is keyed on the stated track, not on which columns you can see. On the **PPI / BoltzGen track**, section 3 MUST contain at least one sentence on the liability picture of the top-5: how many rows have `liability_high_severity_violations ≥ 1`, what the worst violation is, and whether the rank-1 pick is clean or flagged. Writing "No red flags identified" without a liability sentence is incomplete there — liability is a separate developability axis from binding metrics and cannot be silently waived. On the **foundry track** that scorer does not exist, so omit the liability statement entirely: no liability heading, no "not computed" line, no note calling the absence an omission, and never let the subject reach `go_rationale`. It is a property of the track, not a finding about the campaign.

Multi-region runs. If the orchestrator's run-input section mentions a `multi_region_skipped.txt` file or a list of unexecuted design YAMLs, surface it here as a red flag of its own ("Region 2 generated by stage 3 but not executed by stage 4 — design space is half-sampled. The human should run Region 2 manually before treating these picks as the final answer"). Do not silently ignore.

4. Recommended designs

Pick **between 0 and 5** design ids from the top-K (`design_id` on the PPI track, `name` on the foundry track) to recommend to the user as the priorities for downstream work. Format as a short bulleted list, each line:

- `<id>` — one short sentence on why this one (e.g. "best composite_score with tight iPAE and high hotspot occlusion"; on the foundry track, "best ipsae_min in the set at 0.61, docked 0.9 Å from its designed pose").

Selection rule: prefer designs that combine good binding metrics (composite_score, iPTM, iPAE, hotspot SASA) with, **when liability columns are present in the data (PPI track)**, low `liability_score` and zero high-severity violations. A design with the best composite_score but `liability_high_severity_violations ≥ 2` should NOT be the rank-1 pick in that case — call this out explicitly and recommend a clean-liability alternative as the lead, with the high-binding-but-risky design as a secondary option for re-engineering or comparison. On the **foundry track** there are no liability columns: rank on what the composite ranked on — `ipsae_min` first (heaviest weight), then `binder_rmsd_dock` and `binder_plddt`, with `iptm` / `iface_pae` as confirmation rather than as the lead.

If the campaign genuinely produced no candidates worth pursuing, output the literal line `_None — see Recommended next steps for re-run guidance._` and skip to section 5. Do **not** list designs purely to fill space.

The orchestrator writes a deterministic FASTA of the whole top-K, not just your picks, in parallel (`06_top_k.fasta` on the PPI track, `top_k.fasta` in the scoring directory on the foundry track) — that's where sequences for ordering live.

5. Recommended next steps

2–3 short bullets — pick the branch that matches the verdict in section 1:

- **GO branch** (campaign healthy): concrete in-silico follow-ups for the recommended designs from section 4 — e.g. "predict expression feasibility for {ids}", "re-rank with iPAE weight bumped to 2.0 to prioritise interface accuracy".
- **NO_GO / CONDITIONAL_GO branch** (campaign weak): concrete re-run instructions. Reference the funnel stats from section 3. Examples:
- "Re-run with hotspots expanded to include adjacent residues X, Y."
- "Production batch was {N} designs — bump to {2×N} and re-rank."
- "Tighten iptm_min to 0.65 and relax hotspot_sasa_delta_min to 50." (PPI track knobs; on the foundry track the equivalents live under `design.binder_ranking` — e.g. "most drops were on `binder_rmsd_dock_max`, so the epitope is the problem, not the sampling: re-run against the alternate site" or "escalate the trial to 1000 backbones so the yield estimate closes".)

No platitudes. Every action should map to a config knob or a clear methodological change.

6. Artifact pointers

Brief, path-only:

- `top_k.csv` — the table you reviewed
- `ranked.csv` — full ranked survivor list (not just top-K)
- `filter_stats.txt` — funnel + drop reasons from stage 5
- `<run_dir>/04_execution_outputs/intermediate_designs/` — per-design CIFs

(The orchestrator passes you the actual paths in the query — quote them verbatim. On the foundry track no paths are passed and the layout differs: name the artifacts by filename only — `top_k.csv`, `ranked.csv`, `top_k.fasta` under the campaign's scoring directory — and do not invent absolute paths.)

PIPELINE HANDOFF

This is the **terminal** stage — nothing downstream consumes the handoff, but the orchestrator parses it to record the final verdict on the run. Emit at the end of your response, exact format, no code fence:

PIPELINE HANDOFF

- go_recommendation: GO
- go_rationale: <one short sentence>
- target_complex: <as given>
- top_k_count: <integer>
- best_iptm: <float, 3 decimals>
- best_ipae: <float, 2 decimals>

Then the id and the track's own headline metrics, from the top-K row with `mmr_rank=1`. On the **PPI / BoltzGen track** add exactly:

- best_hotspot_sasa_delta: <float, 1 decimal>
- best_design_id: <design_id from the top_k.csv row with mmr_rank=1>

On the **foundry track** add exactly these instead:

- best_ipsae_min: <float, 3 decimals>
- best_dock_rmsd: <float, 2 decimals>
- best_name: <name from the top_k.csv row with mmr_rank=1>

`best_iptm` / `best_ipae` come from `design_to_target_iptm` / `min_design_to_target_pae` on the PPI track, and from `iptm` / `iface_pae` on the foundry track.

Never emit a placeholder. Do not write `N/A`, `none`, `-`, an empty value, or a zero for a metric that was not computed on this track. A field whose column does not exist in your table is simply not emitted — omitting the line is the correct answer, and a fabricated `0.0` is worse than useless because downstream it reads as a measured value. `go_rationale` is parsed and shown to the user: one sentence about the designs, never a remark about which columns you did or did not receive.

`go_recommendation` must be one of `GO | CONDITIONAL_GO | NO_GO`. Use the verdict you stated in section 1 — which, when the query stated a calibration verdict or an already-recorded NO_GO, is bounded by it.

molecular-biology-expert

`molecular-biology-expert` `4165 words`

> **Frontmatter description.** Invoke ONLY when the user explicitly asks for it by name or clearly requests this specific workflow; do not trigger it from a general question, which you can answer better from your own knowledge than from this narrow corpus. Query the curated scientific literature database to assess the biology, prior art, feasibility, and design challenges for a candidate binder target — either a protein-protein interaction (PPI; default) or a single-protein active-site / allosteric-pocket target when the pathway-expert handoff specifies design_intent=inhibit_active_site. Runs BEFORE complex-structure-analysis in the pipeline: emits literature-derived residue hints (target_site_hint) that the structure-analysis stage uses to focus its geometry pass. Also uses corpus graph and DepMap tools when the target is a cancer / disease pathway node. Trigger on: "what does the literature say about", "prior art for", "known inhibitors of", "has anyone targeted", "biology of [target]", "feasibility of targeting", "target feasibility", "molecular biology analysis", or as stage 1 of the pathway → mol-bio → structure → design pipeline. Requires the literature-db MCP server (search_corpus, get_fingerprint, graph tools).

Molecular Biology Expert: Target Feasibility Analysis

This skill queries the curated biochemistry literature database to characterize a candidate binder target. It works for both PPI targets (the default — characterise both partners, the interface, and prior PPI-disruptor or stabilizer art) and single-protein direct-inhibition targets (active site or allosteric pocket, characterise the pocket residues and prior peptide/macrocycle inhibitor art).

The output is a structured report covering biological context, inhibitor prior art, literature-derived candidate residues, and a design feasibility assessment. Crucially, the report emits a `target_site_hint` field in the PIPELINE HANDOFF — this is consumed by the next stage (complex-structure-analysis) to focus its geometry pass on the residues literature has already implicated.

Prerequisites

Verify that `search_corpus`, `get_fingerprint`, and the graph tools (`cluster_for_protein`, `get_genetic_codependency`, `find_cocorrelated_genes`, `shortest_interaction_path`) are available — literature-db MCP server must be connected.

You run **before** complex-structure-analysis in the pipeline. There is no structure report yet to cross-reference against. Your job is to give the structure expert the best literature-derived starting point.

Phase 1: Identify the Target

Extract the following from the user's request or the pathway-expert handoff:

- **For PPI targets** (most common):
- **ProteinA** and **ProteinB** — the two proteins forming the complex
- **Target protein** — the protein whose surface the binder will engage
- **For direct-inhibition targets** (pathway-expert handoff sets `design_intent=inhibit_active_site`):
- **Target protein** — the single enzyme / pocket-bearing protein
- **Site type** — active site / allosteric pocket / cryptic pocket
- **Organism** — human unless specified otherwise
- **Disease context** — cancer, viral, inflammatory, etc. (if known)
- **design_intent** from pathway-expert handoff: `disrupt`, `stabilize`, or `inhibit_active_site`

If the target is ambiguous (e.g., "KRAS" without specifying which effector), ask the user to clarify before proceeding.

Common name normalisation: Use canonical protein names in queries. Examples: - GAPDH / G3PDH / hGAPDH → "GAPDH" - ACTB / ACTG1 → "actin" (search broadly, then filter to the specific paralog if needed) - p53 / TP53 / tumor protein p53 → "p53"

Phase 2: Multi-Query Corpus Search

A single query is insufficient. Run **3–5 targeted `search_corpus` calls** covering different aspects of the target. Collect all results and deduplicate by DOI.

Required queries (always run)

Adapt the query wording to the design_intent:

Query 1 — Target biology:

```
# PPI target:
search_corpus  query="<ProteinA> <ProteinB> interaction mechanism binding"  top_k=8
# Direct-inhibition target:
search_corpus  query="<ProteinName> active site catalytic mechanism structure"  top_k=8
```

Query 2 — Inhibitor prior art:

```
# PPI target:
search_corpus  query="<ProteinA> <ProteinB> inhibitor peptide Ki Kd affinity"  top_k=8
# Direct-inhibition target:
search_corpus  query="<ProteinName> macrocyclic peptide inhibitor Ki IC50 active site"  top_k=8
```

Query 3 — Key residues:

```
# PPI target:
search_corpus  query="<ProteinA> <ProteinB> mutagenesis alanine scanning hotspot residues ΔΔG"  top_k=5
# Direct-inhibition target:
search_corpus  query="<ProteinName> catalytic residues active site mutation activity"  top_k=5
```

Conditional queries (run if applicable)

Query 4 — Disease / in vivo relevance (if disease context is known):

```
search_corpus  query="<target> <cancer/tumor/signaling> in vivo cellular"  top_k=5
```

Deduplication

After all searches, collect unique papers by DOI (`paper_key` field). If the same paper appears across multiple searches, keep only its highest relevance score. Note how many total unique papers were found and how many came from each query.

Phase 3: Retrieve Full Fingerprints

For the **top 5–8 unique papers** (ranked by score), retrieve complete fingerprints:

```
get_fingerprint  identifier=<doi>
```

Use the `paper_key` value from search results directly (e.g., `doi:10.1021/...`). Strip the `doi:` prefix if the tool needs a bare DOI.

Prioritisation

When choosing which papers to fetch in full, prioritise: 1. Score > 0.35 (high semantic relevance) 2. `study_type`: `experimental_in_vitro` or `experimental_structural` over `review` or `computational` 3. Non-null `affinities_kd_Molar` or `inhibitory_constant_Ki` (quantitative data) 4. Papers with `key_amino_acid_residues` populated — these residue lists are exactly what feeds the `target_site_hint` handoff to the structure stage.

Always fetch the top 3 papers by score regardless of study type.

What to extract from each fingerprint

From `paper_metadata`: - `title`, `doi`, `study_type`, `situational_context_hook`

From `key_findings[]` (for each finding): - `claim`, `evidence_value`, `affinities_kd_Molar`, `inhibitory_constant_Ki`, `key_amino_acid_residues`, `protein_pair`, `experimental_context`, `confidence_score`, `source_span`

From `contradictions_and_negative_results[]`: - `finding`, `conflicts_with_prior_work`, `reasoning`

From `entities`: - `chemicals` (inhibitors, reagents), `proteins`

From `methodology`: - `experimental_methods_used`, `instruments_used`

Phase 4: Pathway / DepMap context (when applicable)

This phase runs only when the target is a human protein in a disease context (cancer, immune, metabolic, etc.). For viral / structural / academic-mechanism targets, skip and proceed to Phase 5.

The graph tools answer questions that semantic search can't:

- **`cluster_for_protein(<target>)`** — what co-functional module does this protein sit in? Hub gene, internal/external edge counts, max internal DepMap correlation. Use this to surface unsuspected functional partners the user might want to consider as alternative targets or co-targets.

- `get_genetic_codependency(<target>, <partner>)` — for PPI targets, this is the Pearson correlation between the two genes' DepMap dependency scores. |r| ≥ 0.3 is meaningful (the genes co-essential across cell lines), |r| ≥ 0.5 is strong corroboration that the PPI is biologically load-bearing. **A high-confidence PPI without DepMap codependency is a yellow flag** — the interaction may not be functionally important in the cell lines DepMap covers.
- `find_cocorrelated_genes(<target>, top_k=10)` — top co-essential partners. Use this to discover unsuspected functional partners not surfaced by literature.
- `shortest_interaction_path(<target>, <disease-gene>)` — connects the target to a known disease driver. Surface to the user when the path is short (≤ 2 hops); it justifies why the target matters in the disease context.

Run **at most 2–3 graph tool calls** here — they are not free and the literature queries above are already substantial. Pick the ones that materially change the tractability verdict.

For inhibit_active_site targets, the graph tools are less central (enzymes often have weak DepMap signal because of redundancy), but `cluster_for_protein` is still useful to surface paralog risk.

Phase 5: Synthesise and Generate Report

Analyse across all retrieved fingerprints + graph results. Do not fabricate information — if a section cannot be filled from the corpus, write "Not found in corpus." and note whether the absence is informative (e.g., no prior inhibitors = novel target) or simply a corpus coverage gap.

Citation policy: All cited claims must come from retrieved fingerprints. - Citation format: DOI string only (e.g. `10.7554/eLife.25068`) + source_span. The `Source:` field in the KNOWN INHIBITORS table and the `Source (DOI, span)` column in the TARGET-SITE INSIGHTS table must use this format. - No author names, journal names, or years. Write the DOI, not "Smith et al. 2023 Nature" or "eLife 2024". - If a fact is known from training knowledge but no corpus DOI exists for it, state the fact without any citation. Do not invent or guess a reference. - DepMap and graph tool results are not literature citations — cite them as e.g. "(DepMap codependency r=0.42)" without a DOI.

The job of this report is to give the downstream structure-analysis stage the best literature-derived starting point. Collect every key residue mentioned in the corpus with mutagenesis or structural evidence — these go into the `target_site_hint` field in PIPELINE HANDOFF (the structure expert uses them to focus its geometry pass).

Use `source_span` values from fingerprints to cite provenance (e.g., "Page 3, Para 1" of DOI 10.7554/eLife.25068).

On a membrane protein, only propose residues a binder can reach

`priority_residues` is treated as AUTHORITATIVE by the structure stage — it is told to confirm your residues geometrically, not to re-derive which ones matter. So a residue you propose inside the membrane becomes a residue the pipeline tries to design against, and the run is refused several stages later.

A designed binder is a folded protein in solution. On any membrane protein — GPCR, receptor kinase, ion channel, single-pass receptor — it can only engage surface exposed on ONE face of the bilayer. Which face is a judgement about where the therapeutic effect lives, not a fixed answer:

- **Prefer the extracellular / lumenal face** where the effect lives there, which for a cell-surface receptor it usually does: extracellular domains (class B/C GPCR ECDs, receptor ectodomains), N-termini, extracellular loops, and the ligand-binding surfaces of secreted-factor / receptor pairs. This face needs no delivery argument — the binder and the site are in the same compartment.
- **The cytoplasmic face is allowed when that is where the mechanism is**, and a cytoplasmic epitope is NOT refused: the pipeline reads the face off your residues and trims to it. Many real mechanisms live there — a receptor's kinase or effector-recruitment surface, or an intracellular-organelle membrane protein, where "extracellular" names no real surface at all. What you owe in exchange is the delivery requirement, **stated**: a protein binder reaching the cytosol needs a route (fusion to a delivery module, intracellular expression, a degrader/glue format), and a target whose effect requires one cannot be scored `tractability: Excellent` without naming it. Naming the burden is the requirement; pretending it is absent is the error.
- **Never propose**: any transmembrane residue, or the orthosteric pocket of a class A GPCR — the last is inside the helical bundle and, for lipid ligands, is reached laterally from within the membrane. Neither is on any face; a TM surface is buried in lipid in a cell, whichever side you approach from.
- **Never mix faces** in one hint. An epitope split across the membrane is not a site one binder can engage — and it is the one case the pipeline cannot resolve for you, since a straddling set gives it no face to trim to.

Literature reports the residues that matter *mechanistically*, which for a receptor routinely includes pocket-lining transmembrane residues. Those are correct biology and the wrong design target: filter them out, and say in the report that you did. If the only

residues the corpus gives you are intramembrane, that is a genuine finding — set `tractability: Poor` and explain, rather than passing them on.

Worked example from a real run, on a class B GPCR / accessory-protein pair: the useful half of the hint named three residues on the accessory protein's extracellular domain — the epitope an approved antibody engages. The SAME hint also carried three residues on the receptor that are transmembrane by UniProt annotation, and that half cost the run a stage. One hint, both kinds; check each residue's topology rather than the hint as a whole.

Report Format

Use the exact section headers below — they are parsed by the downstream design agent and the orchestrator skill.

Token budget: The full MOLECULAR BIOLOGY REPORT must fit in 2,500–3,500 words. - Limit each inhibitor entry to 5 bullet lines. - If more than 4 inhibitor classes are found, group minor variants under the closest class rather than adding new `####` blocks. - Omit sub-sections that have no content — do not write empty placeholders. - Literature sources table: max 8 rows.
```

## MOLECULAR BIOLOGY REPORT

### COMPLEX OVERVIEW

- Target complex:
- Indication organism:
- Cited structures: — \ — \>", e.g. "5GRS — Schizosaccharomyces pombe — ortholog of human SCAP/SREBF1". Do NOT fold these into the organism field above: the indication is routinely human while every available structure is not, and collapsing the two is how a yeast crystal passes as a human interface.>
- Disease context:
- Biological role:
- Drug target validation:
- Papers analysed: from

### KNOWN INHIBITORS AND PRIOR ART

> If no inhibitors are found: "No inhibitors found in corpus — novel target or corpus gap."

For each inhibitor class (max 4 classes; group variants; max 5 bullets each):

- Modality:
- Best affinity:
- Source:
- Key residues engaged:
- Limitations:

### TARGET-SITE INSIGHTS FROM LITERATURE

#### Confirmed key residues (mutagenesis / structural data)

For PPIs: interface residues with ΔΔG or alanine-scan effect on binding. For inhibit_active_site: catalytic residues + pocket-lining residues from inhibitor co-crystal structures.

| RESIDUE | PROTEIN | ROLE / EFFECT | METHOD | SOURCE (DOI, SPAN) |
|---|---|---|---|---|
| ... | ... | ... | ... | ... |

#### Residues tolerant of mutation

#### Pathway / DepMap context

- Co-functional cluster: - Genetic codependency: - Notable co-essential genes: - Disease-driver connectivity:

### FEASIBILITY ASSESSMENT

- Target tractability / informativeness:
- **Excellent**: structural interface clear in a named PDB with both partners, whose source organism is stated; literature names at least 2 interface residues; modality precedent in the literature (peptide / mini-protein / antibody-fragment for ANY member of the same family is sufficient), **OR** a clearly stated falsifiable hypothesis from the pathway stage where disrupting the interaction predicts a specific biological readout. Quantitative anchors (Kd / Ki / ΔΔG) reported when present but NOT required.

  **When the only structure of the interface is an ortholog**, this tier is still reachable — an ortholog crystal is frequently the only structure that exists (no human SCAP/SREBP complex has ever been solved), and designing against a conserved site on one is legitimate. It is reachable only when the report (a) names the structure's source organism in COMPLEX OVERVIEW, (b) states which human protein it stands in for, and (c) commits to the conservation question **for the residues it is actually proposing**: which of them do you expect to be identical in the human protein, and on what
```

basis. "Convincing homology" is not an answer to (c) — a β-propeller fold can be conserved end to end while the specific epitope on its face is not. Without (c) the ceiling is **Good** (the interface is real; the site is not yet shown to transfer), and where those residues are the only thing making the target attractive and nothing can be said about their conservation, **Marginal**. - **Good**: structural interface clear AND at least one mutagenesis or interface-residue claim in the corpus, OR a modality precedent on a paralog, OR a coherent mechanistic prediction with a named readout. - **Marginal**: structural interface clear but no residue-level data, no modality precedent, AND no clear falsifiable prediction. - **Poor**: structural interface unresolved (partner absent from PDB and no homologue available); cannot be designed against until structure work is done.

Absence of ΔΔG or Kd in the corpus is NOT grounds for downgrading. Novel or hypothesis-tier targets typically lack these values. If the structural rationale is sound AND the pathway stage articulated a falsifiable hypothesis (a `predicted_consequence` + `falsifying_readout` in the upstream handoff), GO stands. Quantitative anchors are HIGHLIGHTED when present (always cite the DOI + value), but they are reportable evidence, never gates.

When the upstream pathway-stage choice carries `predicted_consequence` / `falsifying_readout` fields (wildcard mode emits these), restate them at the TOP of this FEASIBILITY ASSESSMENT section so the design stages downstream see the testable claim, not just the target name.

Ortholog structures and the downstream conservation check. When the cited structure is an ortholog, the pipeline runs a deterministic per-residue check that maps every hotspot through SIFTS onto the human canonical sequence and reports which ones the human protein actually carries; too few conserved and it halts the run. Two consequences here. First, the conservation claim belongs in `go_rationale` — name the residues you expect to transfer, because that is the claim being tested. Second, an ortholog crystal is the fallback, not the default: where a **human** structure of the same interface exists prefer it, and where none does, note that a human **AlphaFold** model of the target chain can be fetched and used instead once the epitope has been restated in human numbering. Neither is a reason to reject the ortholog — only to say what was chosen and why. Measured on SCAP/SREBF1: the fission-yeast "RK patch" (R617/K635/R640/K643/K659/K685), which reads as a thoroughly characterised epitope, has **none** of those six residues conserved in human SCAP.

- Corpus confidence:
- Design challenges:
- Negative results:
- Missing data gaps:

DESIGN RECOMMENDATIONS

- Suggested modality: — reasoning in one sentence
- Residues to prioritise:
- Residues to avoid:
- Epitope to mimic:
- Affinity target — use the FIRST rule that applies, and state in one sentence which rule fired: 1. **Corpus has measured Kd or Ki** (use `find_quantitative_evidence`) → aim for one half-log tighter than the tightest cited value. E.g. corpus has 31 nM SPR → "aim for ≤ 10 nM Kd (one half-log tighter than the 31 nM cyclic probe in DOI X)". 2. **VALIDATED or BIOLOGICALLY_JUSTIFIED tier** (from pathway-expert handoff) → "aim for ≤ 30 nM Kd, peptide-binding heuristic for druggable PPIs". 3. **HYPOTHESIS / CROSS_INDICATION_TRANSFER / SYNTHETIC_LETHALITY / PATHWAY_INFERRED without quant anchor** → "aim for ≤ 100 nM Kd, peptide-binding heuristic for novel targets — refine after first design round".
- Key risk:

LITERATURE SOURCES (max 8 rows)

#	TITLE (TRUNCATED TO 60 CHARS)	DOI	STUDY TYPE	SCORE	KEY FINDING
1	...	...	...	...	...

PIPELINE HANDOFF

- target_complex:
- design_intent:
- structure_organism:
- ortholog_of_human:
- tractability:
- go_recommendation:
- go_rationale:
- modality: mini_protein # default; the operator opts into cyclic_peptide at kickoff
- target_site_hint:
- design_query:

IMPORTANT: Write the `### PIPELINE HANDOFF` section as plain bullet lines exactly as shown above. Do NOT wrap it in a code fence (no ``` before or after). Do NOT omit the `-` prefix. The programmatic orchestrator parses these lines with a regex — any deviation breaks the pipeline.

Rules for `### PIPELINE HANDOFF`: - `go_recommendation` must be exactly one of: `GO`, `CONDITIONAL_GO`, or `NO_GO`. Use the tractability rubric: Excellent/Good → GO; Marginal → CONDITIONAL_GO (still produces designs, with the key risk surfaced); Poor → NO_GO. Note: missing ΔΔG / Kd values are not a downgrade trigger — see the Tractability rubric in FEASIBILITY ASSESSMENT. An ortholog structure is never itself a NO_GO; but when `ortholog_of_human` is not NONE and the report makes no per-residue conservation claim about the priority residues, tractability is Good at best and `go_recommendation` is capped at `CONDITIONAL_GO`, with that uncertainty as the `go_rationale`. - `go_rationale` is a single sentence — the programmatic orchestrator displays this directly to the user. - `design_query` is the verbatim query string carried forward to the design stages; include PDB ID, top 3–5 hotspot residues, and suggested affinity target. Do NOT include chain letters — chain assignment is handled by the structure-analysis stage downstream. - `target_site_hint` is a single-line JSON object with these keys (use straight double-quotes, no trailing commas): - `mode`: `"ppi_interface"` (for disrupt / stabilize) or `"single_protein_pocket"` (for inhibit_active_site) - `target_protein`: the

protein whose surface the binder engages - `priority_residues`: array of residue identifiers from the corpus (numbers and/or one-letter+number, e.g. `["F69", "L91", "R89"]` or `["245", "247", "250"]`); leave empty `[]` if literature gave no specific residues - `notes`: short string explaining the source of the residues AND the numbering convention used. If the literature numbers are from a paralog, from another species' ortholog, or from a full-length canonical sequence while the PDB structure may be a truncated construct or a different family member, say so. Examples: `"alanine scan ΔΔG > 2 kcal/mol from doi:..., <partner> numbering"`, `"<target> canonical numbering — mapping to PDB target chain must be confirmed by structure stage"`, `"catalytic triad from inhibitor co-crystal doi:..."`.

Example (placeholder names — substitute your own): `- target_site_hint: {"mode":"ppi_interface","target_protein":"GENE_B","priority_residues":["L24","W57","K61"],"notes":"Alanine scan ΔΔG > 1.5 kcal/mol from doi:...; GENE_A numbering"}`

Residue-numbering guardrail. Do NOT claim that residue numbers from one paralog map directly onto another paralog, or onto a specific PDB entry, without structural verification. Close paralogs share high sequence identity but have offset numbering when crystallised as truncated constructs; literature numbers are corpus-side identifiers, not PDB auth_seq_ids. State the numbering convention in `target_site_hint.notes`; do NOT assert PDB-residue equivalence in the report body. The structure stage downstream owns the literature→PDB residue mapping (by contact geometry against the actual mmCIF) and will surface the equivalent auth_seq_ids in its MODEL-READY HOTSPOTS block.

The same rule applies **across species, and harder**. If `target_site_hint.priority_residues` were read off an ortholog structure — or off a paper whose mutagenesis was done on the ortholog — they are ortholog numbering on an ortholog sequence, and `notes` must say so explicitly: organism, source structure, and that the human equivalents are not established. Example: `"S. pombe Scp1 numbering from PDB 4YHC/5GRS, doi:10.1038/cr.2015.32; human SCAP equivalents not established"`. These numbers flow toward an RFD3 hotspot spec, where an unlabelled ortholog residue id becomes a design constraint on a site never checked against the human protein. Do not restate them as human numbering, and do not assert a human equivalent you have not derived — the pipeline derives it (SIFTS plus a global ortholog↔human alignment) and reports the human position for each hotspot.

Handoff Notes

The `INTERFACE INSIGHTS FROM LITERATURE` and `DESIGN RECOMMENDATIONS` sections are formatted for downstream consumption by: - **the design stages** (`src/foundry_spec.py` / `src/boltzgen_spec.py`, via `complex-structure-analysis`'s hotspot table) — use the residues to prioritise, the suggested modality and the affinity target to parameterise the RFD3 contig or BoltzGen YAML. Deterministic Python, not a skill. - **Orchestrator skill** (planned) — uses tractability rating and key risk to make go/no-go recommendations before committing compute

The `LITERATURE SOURCES` table enables traceability: any claim in the report can be traced to a DOI and then to a `source_span` within the full fingerprint.

Common Pitfalls

- **Run all queries before synthesising.** A single search misses complementary papers. The biology query and the inhibitor query often return different papers.
- **Deduplicate before fetching fingerprints.** Papers appear in multiple search results; fetch each DOI only once.
- **Do not fabricate.** If a section cannot be filled from retrieved fingerprints, write "Not found in corpus." Do not infer or hallucinate binding affinities, residue names, or inhibitor structures.
- **Score threshold.** If all search results score < 0.25, the corpus likely does not contain directly relevant papers. State this explicitly and note that the analysis is limited.
- **`get_fingerprint` identifier.** Use the `paper_key` value from search results (e.g. `doi:10.7554/eLife.25068`). If the tool requires a bare DOI, strip the `doi:` prefix.
- **Residue name normalisation.** When cross-referencing structure-tools hotspots against fingerprint `key_amino_acid_residues`, treat "Phe69", "F69", "PHE 69", and "h<GENE> Arg273" as equivalent. Match on residue number + one-letter or three-letter amino acid code.
- **Corpus bias.** The corpus is focused on biochemistry and biophysics. In vivo validation, clinical data, and ADMET properties are rarely in the corpus — flag their absence rather than treating it as evidence of absence.

orchestrator

`orchestrator` `2404 words`

> **Frontmatter description.** Invoke ONLY when the user explicitly asks for it by name or clearly requests this specific workflow; do not trigger it from a general question, which you can answer better from your own knowledge than from this narrow corpus. Sequence the protein-protein interaction target-assessment pipeline across three expert skills: target selection (pathway-expert OR complex-expert, conditional), structural analysis (complex-structure-analysis) and literature analysis (molecular-biology-expert). Synthesises a go/no-go campaign recommendation before committing to design compute; generating the design inputs themselves is the CLI pipeline's job, not this skill's. Trigger on: "run the full pipeline", "design campaign for [target]", "orchestrate", "start the design workflow", "full analysis of [target]", "go from structure to design", or when a PDB ID is provided and the user asks to run the complete workflow. Also trigger when a disease or cancer type is provided without a specific PPI target (Stage 0 = pathway-expert), or when a set of proteins / predicted complex is the starting point (Stage 0 = complex-expert). Requires: structure-tools MCP server (for Stage 1) and literature-db MCP server (for Stage 0 and 2).

Design Campaign Orchestrator

This skill coordinates the expert skills in sequence, manages their handoffs, and synthesises a go/no-go recommendation before generating design inputs. It does not perform analysis itself — it directs, extracts key signals, and decides when to proceed.

Pipeline Overview

```
Stage 0: Target Selection (conditional) →  pathway-expert  [disease → target]
                                    OR  →  complex-expert  [proteins → target]
Stage 1: Structural Analysis            →  complex-structure-analysis
Stage 2: Literature Analysis            →  molecular-biology-expert
Stage 3: Go/No-Go Synthesis             →  CAMPAIGN RECOMMENDATION (this skill)
```

The pipeline **ends at the recommendation**. Design inputs are built deterministically by `scripts/run_pipeline.py` (`src/foundry_spec.py` / `src/boltzgen_spec.py`) from the structure stage's hotspots — no skill writes a generator spec any more.

Prerequisites

Before starting, verify tool availability: - **structure-tools MCP tools** (`tool_analyze_interface`, `tool_get_residue_contacts`, etc.) — required for Stage 1. If not connected: halt and tell the user to start the structure-tools MCP server before proceeding (`python scripts/launch_structure_tools.py`). - **literature-db MCP tools** (`search_corpus`, `get_fingerprint`) — required for Stage 0 and Stage 2. If not connected: note this, offer to run Stage 1 only, and skip Stages 0 and 2 if the user agrees. - **Filesystem MCP tool** — required for saving outputs to LittleProteinTiger. If not connected: warn the user; continue the pipeline but note that outputs will not be saved.

LittleProteinTiger Output Management

LittleProteinTiger is the name of this design framework. All pipeline outputs are saved to a dedicated run folder under `outputs/`.

At the very start of the pipeline, before Stage 0:

1. Determine `{ProteinA}` and `{ProteinB}` from the user's request (or use the disease/complex name if Stage 0 is needed — update after Stage 0 resolves the target).
2. Set the run folder path: `outputs/{ProteinA}_{ProteinB}_{YYYY-MM-DD}/` Use today's date in `YYYY-MM-DD` format.
3. Create the folder using the filesystem tool (`create_directory`).
4. Announce the path to the user:

   > "Run folder: `outputs/{ProteinA}_{ProteinB}_{YYYY-MM-DD}/`"

After each stage, write the expert's full report to the run folder:

STAGE	FILE
Stage 0A (pathway-expert)	`00_target_selection.md`
Stage 0B (complex-expert)	`00_complex_analysis.md`
Stage 1 (structure-tools)	`01_structural_analysis.md`
Stage 2 (mol-bio expert)	`02_literature_report.md`

STAGE	FILE
Stage 3 (campaign recommendation)	`03_campaign_recommendation.md`

Use `filesystem:write_file` with the full path and the complete report content (copy verbatim from the conversation — do not summarise or truncate).

Stage 0: Target Selection (Conditional)

Stage 0 has two variants depending on the starting point. Choose the right one:

Skip conditions — proceed directly to Stage 1: - User provides a PDB ID (e.g. "PDB 1ABC") - User provides a protein pair (e.g. "KRAS/RAF1", "PD-1/PD-L1") - A PPI target has already been agreed upon earlier in the conversation - User provides a path to a pre-existing pathway expert or complex expert report (see below)

Stage 0A: Disease → Target (pathway-expert)

Trigger: User provides only a disease or cancer type without a specific PPI target. (e.g. "PDAC", "NSCLC", "which node in <pathway> is most tractable?")

Invoke the **pathway-expert** skill with the disease context and any pathway hint from the user.

Wait for the full `## PATHWAY BIOLOGY REPORT` to be produced. Then extract: - **Recommended PPI** — the ProteinA / ProteinB complex from `RECOMMENDED PPI TARGET` - **Suggested PDB ID(s)** — for Stage 1 input - **Redundancy risks** — carry forward to the Stage 3 CAMPAIGN RECOMMENDATION

If the pathway-expert reports no corpus coverage (all scores < 0.20 and fallback used): - State this to the user - Ask whether to (a) proceed with a manually specified PPI or (b) pause to run the fetch/curate pipeline with the suggested keywords first - Do not proceed to Stage 1 without a confirmed PPI target

---

Stage 0B: Proteins → Target (complex-expert)

Trigger: User provides a set of protein/gene names or a predicted complex without specifying which interface to target or which PDB to use. (e.g. "run the full pipeline for ARFRP1/JTB/SYS1/ARL1", "design a binder for this complex")

Invoke the **complex-expert** skill in **Full pipeline mode** with the protein list.

Wait for the full `## COMPLEX CHARACTERISATION REPORT` to be produced. Then extract: - **Recommended interface** — the ProteinA–ProteinB pair to target from `NOVELTY ASSESSMENT` - **PDB ID or local AlphaFold path** — from `THERAPEUTIC HISTORY` or provided by the user - **Novelty signal** — carry forward to Stage 3 CAMPAIGN RECOMMENDATION - **Fetch keywords** — if coverage was Sparse or None, flag for the user before proceeding

If the complex-expert finds no PDB and no local AlphaFold file: - Report this to the user - Do not proceed to Stage 1 without a structure - Suggest: run the fetch keywords first, then re-run; or provide the AlphaFold file path

Local AlphaFold file handling at Stage 1: If Stage 0B identified a local AlphaFold file (user-provided path), pass it to the complex-structure-analysis skill explicitly:

> "Use `run_command 'open /path/to/file.cif'` instead of `open_structure` for this structure."

Pre-existing Stage 0 report

If the user provides a file path to a prior pathway-expert or complex-expert output (e.g. `"the pathway expert output is at results/00_pathway.md"`), read the file using the filesystem MCP tool and treat its contents as the Stage 0 output.

- For a pathway-expert report: extract `RECOMMENDED PPI TARGET`, `REDUNDANCY AND RESISTANCE RISKS`
- For a complex-expert report: extract `NOVELTY ASSESSMENT → Recommended interface`, `THERAPEUTIC HISTORY → Known structures`, and novelty signal

Do not re-run the skill.

Present a one-paragraph summary and confirm the target with the user:

> "Stage 0 complete. Recommended target: [complex / interface]. Suggested PDB: [ID or 'AlphaFold local file']. Proceed to structural analysis?"

Save Stage 0 output: Write the full pathway-expert or complex-expert report to `{run_folder}\00_target_selection.md` (Stage 0A) or `{run_folder}\00_complex_analysis.md` (Stage 0B). If the run folder name used a placeholder (disease name), rename it now that the target proteins are known.

Stage 1: Structural Analysis

Invoke the **complex-structure-analysis** skill with the target PDB ID (or local AlphaFold file path) and complex name. The skill uses the structure-tools MCP server — no ChimeraX required. If Stage 0B produced a local AlphaFold path, pass the file path directly. If the user has not specified which protein is the target chain, let the complex-structure-analysis skill ask — do not anticipate this yourself.

Wait for the full `## PPI ANALYSIS REPORT` to be produced. Then extract:

- **Complex name** — e.g. "GENE_A / GENE_B"
- **Target chain** — chain ID and protein name
- **Buried surface area (BSA)** — in Å²
- **Structural tractability rating** — Excellent / Good / Marginal / Poor (from the `HOTSPOT REGIONS` section)
- **Design modality recommendation** — cyclic peptide / mini-protein / either
- **MODEL-READY HOTSPOTS** — the full table (residue, auth_seq_id, label_seq_id, sidechain atoms)

Present a one-paragraph summary covering BSA, tractability, modality recommendation, and the top hotspot residues. Then ask:

> "Stage 1 complete. Proceed to literature analysis?"

Save Stage 1 output: Write the full `## PPI ANALYSIS REPORT` to `{run_folder}\01_structural_analysis.md`.

Stage 2: Literature Analysis

Invoke the **molecular-biology-expert** skill. When doing so, provide it with the following context from the Stage 1 report:

- Complex name (e.g. "GENE_A / GENE_B")
- Target protein name (e.g. "GENE_B")
- Hotspot residues (e.g. "Leu24, Trp57, Lys61 on GENE_B")
- PDB ID

This context enables the literature skill to run targeted residue-level searches and cross-reference its findings against the structural hotspots.

Wait for the full `## MOLECULAR BIOLOGY REPORT` to be produced. Then extract:

- **Literature tractability rating** — Excellent / Good / Marginal / Poor
- **Corpus confidence** — High / Medium / Low
- **Best prior art affinity** — modality, Kd/Ki, DOI (if any found)
- **Literature-validated hotspot residues** — from `INTERFACE INSIGHTS FROM LITERATURE`
- **Key risk** — from `FEASIBILITY ASSESSMENT`
- **Suggested modality** — from `DESIGN RECOMMENDATIONS`

Present a one-paragraph summary covering tractability, any prior art found, and key risks.

Save Stage 2 output: Write the full `## MOLECULAR BIOLOGY REPORT` to `{run_folder}\02_literature_report.md`.

Stage 3: Go/No-Go Synthesis

This is the orchestrator's primary contribution. Before generating any design inputs, synthesise signals from both reports and produce a `CAMPAIGN RECOMMENDATION`.

Cross-reference hotspots

Compare the structure-tools MODEL-READY HOTSPOTS against the literature `INTERFACE INSIGHTS FROM LITERATURE` validated residues. Normalise naming conventions when comparing (e.g. "Arg273" = "R273" = "ARG273" = "h<GENE> Arg273" — match on residue number + amino acid identity).

Classify each hotspot residue as: - **Cross-validated** — confirmed by both structure-tools interface analysis AND published mutagenesis/structural data in the literature corpus - **Structurally predicted only** — in the structure-tools hotspot list but not found in literature corpus (novel, or corpus coverage gap) - **Literature-validated only** — in the corpus as a validated residue but not in the structure-tools hotspot list (may be outside the primary pocket, or from a different structure)

Go/No-Go rubric

Important: Absence of prior art is NOT a blocker. Peptide and protein binder therapeutics are still rare, so most targets will have no published binders. If prior art exists it is a meaningful confidence boost; if it does not, the pipeline proceeds on

structural and biological grounds.

SIGNAL	WEIGHT
Structural tractability rating	High
Literature tractability rating	High
Cross-validated hotspot count	High
Interface size vs modality fit	Medium
Key risk severity	Medium
Prior art (existence is a plus, absence is neutral)	Low–Medium

GO — Both ratings Excellent or Good; at least 1 cross-validated hotspot; no disqualifying structural blocker. Prior art with ≤ 500 nM affinity = note as confidence boost. Recommend proceeding to a design campaign.

CONDITIONAL GO — One rating Marginal; hotspots partially or not cross-validated; OR key risks identified (e.g. isoform redundancy, intracellular access) but not disqualifying. Recommend proceeding with caveats explicitly listed.

NO-GO — Either rating Poor AND structural rating Marginal/Poor; zero cross-validated hotspots; OR a severe structural blocker: fully disordered target on both sides of the complex, interface BSA < 300 Å², or no druggable surface identified by structure-tools. Absence of prior art alone is NEVER a NO-GO reason.

For NO-GO: explain the specific blocker, suggest alternatives (different interface region, different target protein, different approach), and do not recommend a design campaign.

CAMPAIGN RECOMMENDATION output format

```
## CAMPAIGN RECOMMENDATION

### TARGET SUMMARY
- Complex: <ProteinA / ProteinB>
- Target chain: <chain ID> (<protein name>)
- Interface: <BSA> Å² — <modality recommendation from structure-tools>
- Structural tractability: <Excellent / Good / Marginal / Poor>
- Literature tractability: <Excellent / Good / Marginal / Poor>
- Corpus confidence: <High / Medium / Low> (<N> relevant papers found)
- Pathway redundancy risks: <from Stage 0 pathway-expert, or "Stage 0 not run">
- Novelty signal: <High / Medium / Low / N/A — from Stage 0 complex-expert, or "Stage 0 not run">
- Structure source: <RCSB PDB [ID] | AlphaFold local file | AlphaFold DB>

### CROSS-VALIDATED HOTSPOTS

Confirmed by BOTH structural analysis and literature:
| Residue | Structure-tools evidence | Literature evidence (DOI) | Confidence |
|---------|--------------------|--------------------------|------------|
| ...     | interface contact, hydrophobic core | alanine scan ΔΔG=X kcal/mol | High/Med |

Note: `Literature evidence (DOI)` must be copied verbatim from the Stage 2
molecular-biology-expert INTERFACE INSIGHTS table — do not supply DOIs from training
knowledge. If Stage 2 found no corpus evidence for a residue, write "structural only".

Structurally predicted only (no literature confirmation):
- <list — note: may be valid, just not yet studied>

Literature-validated only (not in primary structure-tools hotspot list):
- <list — consider expanding the hotspot selection if structurally accessible>

### PRIOR ART SUMMARY
- Best reported binder: <modality, affinity, assay, DOI — or "None found in corpus">
  (If none found: this is expected for most PPI targets; proceed on structural grounds)
- Design affinity target: <suggested Kd, e.g. "aim for ≤ 100 nM — best prior art
  is 18 nM SPR (10.7554/eLife.25068)" or "no prior art; target sub-μM as first milestone">
- Key residues to engage: <cross-validated list, in priority order>

### RECOMMENDATION: <GO / CONDITIONAL GO / NO-GO>
Reasoning: <2–3 sentences integrating structural and literature signals>
Caveats: <bulleted list — only if CONDITIONAL GO>
Blocker: <specific reason — only if NO-GO>
Next step: <"Proceed to generate design inputs" / "Address [X] before proceeding">
```

Save Stage 3 output: Write the full `## CAMPAIGN RECOMMENDATION` block to `{run_folder}\03_campaign_recommendation.md`. Include a header line with the target name, date, and pipeline decision (GO

/ CONDITIONAL GO / NO-GO).

Handing off to a design campaign

This skill does NOT generate design inputs, and there is no skill left that does: the generator spec (an RFD3 contig JSON or a BoltzGen YAML) is built deterministically by the CLI pipeline from the structure stage's own `MODEL-READY HOTSPOTS`, because every field in it is a mechanical fact about one structure file.

So after presenting the CAMPAIGN RECOMMENDATION, for GO or CONDITIONAL GO, stop and hand the user the command instead of building anything:

> "To run the campaign on this target: `python scripts/run_pipeline.py --workflow structure --structure <local .cif/.pdb> --project <slug>` (use `--pdb <ACCESSION>` instead of `--structure` for an RCSB entry — `--structure` takes a local FILE, and the two are not interchangeable) (or `--workflow binder --target <GENE>` to let the pipeline pick the structure). It re-reads the interface, trims the target, sizes the campaign from a measured calibration run, and pauses at the calibration verdict."

Then close with a brief summary:

> "Assessment complete for [complex]. Recommendation: [GO / CONDITIONAL GO / NO-GO]. Cross-validated hotspots: [list]. Suggested modality: [modality]. Prior art benchmark: [affinity or 'none']."

Pitfalls

- **Never skip Stage 3.** Even if the user says "just proceed to design," present the CAMPAIGN RECOMMENDATION first. A brief go/no-go takes seconds and prevents wasted compute on a NO-GO target.
- **Keep stage summaries concise.** The full PPI ANALYSIS REPORT and MOLECULAR BIOLOGY REPORT are already in the conversation — do not repeat them. One paragraph per stage.
- **structure-tools missing at Stage 1 = hard stop.** Structural analysis is the foundation; the pipeline cannot proceed without it. Tell the user to run `python scripts/launch_structure_tools.py` and add it to their MCP config.
- **literature-db missing at Stage 2 = soft stop.** Offer to run structural-only mode: skip Stage 2, produce a limited CAMPAIGN RECOMMENDATION based on structural signals only, and flag the missing literature context explicitly.
- **Residue naming normalisation.** When cross-referencing hotspots, treat "Phe69", "R273", "ARG273", and "h<GENE> Arg273" as equivalent.

pathway-expert

`pathway-expert` `5475 words`

Frontmatter description. Invoke ONLY when the user explicitly asks for it by name or clearly requests this specific workflow; do not trigger it from a general question, which you can answer better from your own knowledge than from this narrow corpus. Query the curated literature database to characterise pathway biology for a disease context, identify dysregulated nodes, and recommend the highest-priority druggable opportunity for therapeutic intervention. Default mode is to recommend a PPI target (the design pipeline is optimised for that); however, when literature evidence for PPI disruption is weak AND there is explicit precedent for direct active-site or allosteric-pocket inhibition (e.g. characterised macrocyclic peptide inhibitors of an enzyme), the skill may pivot to recommend a single-protein target with a catalytic / pocket binding mode. Use as the first step when the user provides a disease or cancer subtype without a specific target in mind. Output feeds directly into molecular-biology-expert (provides complex name + disease context) and complex-structure-analysis (provides PDB ID + binding mode). Requires literature-db MCP server. Trigger on: "which target in", "pathway analysis for", "what to target in", "disease mechanism", "<pathway> pathway in", "what's dysregulated in", "target selection for", "which node should we target", or any question pairing a pathway name with a disease or cancer subtype without specifying a PDB or protein pair.

Pathway Biology Expert

This skill queries the curated literature corpus to characterise signalling pathway biology in a disease context, assess candidate target nodes, and recommend the optimal target for the downstream design pipeline. It does not perform structural or biochemistry analysis — that is the job of complex-structure-analysis and molecular-biology-expert.

Default target type is a PPI (protein-protein interaction) — the binder design pipeline is most mature for that case. **Pivot to a direct-inhibition recommendation** (enzyme active site, allosteric pocket) only when (a) PPI evidence for the node is genuinely weak AND (b) literature provides explicit precedent for direct-inhibition modality (e.g. characterised peptide/macrocycle inhibitors of the catalytic site). The pivot path is documented as a fourth tier; PPI candidates always rank first when supported.

The output is a structured `## PATHWAY BIOLOGY REPORT` containing the recommended target (PPI or direct-inhibition) and PDB ID(s) ready to pass downstream.

Phase 1: Extract Context from User Input

Identify: - `disease_or_cancer` — e.g. "PDAC", "NSCLC", "HCC", "AML", "Alzheimer's", "rheumatoid arthritis", "idiopathic pulmonary fibrosis" - `pathway_hint` — optional; a pathway name supplied by the caller. Use it only if given; never invent one, and never carry an example from this prompt into a report. - `constraint` — optional; e.g. "focus on extracellular PPIs", "cyclic peptide accessible" - `disease_category` — classify the disease into one of the categories below and resolve the three query term variables used in Phase 2. If the disease spans multiple categories, pick the most specific match; default to `other` if none fits.

DISEASE_CATEGORY	<DISEASE_MECHANISM_TERM>	<DYSREGULATION_TERM>	<PROTECTIVE_REGULATOR_TERM>
oncology	cancer mechanism	oncogenic	tumor suppressor
neurodegeneration	neurodegeneration mechanism	pathological aggregation	neuroprotective regulator
autoimmune	autoimmune inflammation mechanism	pro-inflammatory	immunosuppressive regulator
metabolic	metabolic disease mechanism	pathological activation	metabolic regulator
infectious	infection pathogenesis mechanism	pathogenic	host defense regulator
cardiovascular	cardiovascular disease mechanism	pathological remodeling	cardioprotective regulator
fibrosis	fibrosis mechanism	pro-fibrotic	anti-fibrotic regulator
other	disease mechanism	pathological	disease-suppressing regulator

If disease is ambiguous (e.g. "lung disease" without subtype), proceed with the broad term — do not block on ambiguity.

Phase 2: Multi-Query Corpus Search

Run 3–4 `search_corpus` calls with `study_category="pathway_biology"`. Vary the query angle to capture different aspects of the evidence:

Substitute `<disease_mechanism_term>`, `<dysregulation_term>`, and `<protective_regulator_term>` with the values resolved from the `disease_category` mapping in Phase 1 before issuing any query.

Important on `top_k` sizing. The corpus has thousands of fingerprints. With `top_k=5-8` you're sampling ~0.1% — a strong topical hit can easily fall outside the window if a few off-topic papers happen to rank above it. Use **`top_k=20` on the first 1-2 broad queries** to get a real sense of coverage, then narrow down with smaller `top_k` for the follow-up queries. 20 is the ceiling — `search_corpus` clamps anything larger, so asking for 30 silently gets you 20. A pathway being "thin in the corpus" should be established by *more* search than usual, not less. Do not declare a corpus gap until you have run at least three queries with combined unique paper count ≥ 30 AND surveyed the graph tools (next section).

Query 1 — Disease-pathway mechanism (top_k=20):

```
search_corpus
  query="<pathway_hint OR disease> signaling dysregulation <disease_mechanism_term>"
  study_category="pathway_biology"
  top_k=20
```

Query 2 — Genetic dependency / essentiality (top_k=6):

```
search_corpus
  query="<disease> CRISPR screen genetic dependency essentiality <pathway_hint>"
  study_category="pathway_biology"
  top_k=6
```

Query 3 — Target node identification (top_k=6):

```
search_corpus
  query="<pathway_hint> effector transcription factor <dysregulation_term> <disease>"
  study_category="pathway_biology"
  top_k=6
```

Query 4 — Upstream regulators (optional, run if pathway_hint is known, top_k=5):

```
search_corpus
  query="<pathway_hint> upstream regulator mutation inactivation <protective_regulator_term> <disease>"
  study_category="pathway_biology"
  top_k=5
```

Deduplicate by DOI across all queries. Retain the highest score per paper.

Corpus gap fallback

If all `study_category="pathway_biology"` results have scores < 0.20 or return empty, re-run the same queries **without** the `study_category` filter. Many existing biochemistry papers have incidental pathway context in their situational_context_hook.

Always state the fallback explicitly in the report — see CORPUS COVERAGE section.

Graph tools — use before declaring the corpus thin

For any disease pathway involving well-known central nodes (a canonical growth, innate-immune, cytokine or developmental signalling axis) the corpus is almost certainly **not** the limiting signal — but `search_corpus` with small `top_k` can miss it. Before concluding that the corpus is sparse on the pathway, run at least one of:

- `cluster_for_protein(<central_node>)` — what co-functional module is the proposed target in? Reveals unsuspected co-essential partners (DepMap) and the cluster's hub.
- `interaction_hubs(top_n=10, min_mentions=2)` — corpus-wide highest-degree nodes (with the "research-attention bias" caveat). Catches central nodes semantic search may have missed.
- `find_cocorrelated_genes(<central_node>, top_k=10)` — DepMap-confirmed functional partners.
- `shortest_interaction_path(<central_node>, <disease_driver>)` — if you have a candidate disease driver, this confirms or refutes pathway connectivity.

Use them sparingly (2-3 calls max for a normal run) but use at least one before writing "no candidates from the corpus".

Phase 3: Retrieve Full Fingerprints

Call `get_fingerprint` for the top 5–8 unique papers from Phase 2. Prioritise papers where the search result indicates a non-null `pathway_context` (check if the `study_category` field in the result is "pathway_biology").

From each fingerprint, extract: - `pathway_context.pathways` — which pathways are covered - `pathway_context.disease_associations` — disease, mechanism, mutation_frequency, source_span - `pathway_context.target_nodes` — protein, pathway_position, dysregulation, genetic_dependency_evidence, prior_therapeutic_targeting, suggested_pdb_structures, source_span - `pathway_context.pathway_logic` — ON/OFF logic summary - `pathway_context.redundancy_risks` - `pathway_context.upstream_regulators`, `downstream_effectors` - `key_findings` — incidental biochemistry findings that may be relevant - `paper_metadata` — title, doi, study_type

Phase 3.5: Term-Expansion Search (Query Expansion Round)

After retrieving fingerprints, extract corpus-specific terms that did **not** appear in any of the Phase 2 query strings. These are high-value expansion candidates:

SOURCE FIELD	WHAT TO EXTRACT
`pathway_context.target_nodes[].protein`	Gene symbols of newly surfaced target proteins
`pathway_context.upstream_regulators`	Regulator gene/protein names not in original query
`pathway_context.downstream_effectors`	Effector gene/protein names not in original query
`pathway_context.disease_associations[].mutation_frequency`	Specific mutation types (formatted "<GENE> loss", "<GENE> amplification", "<GENE> fusion")

Always run Phase 3.5. The only exception is when Phase 2 returned ≥ 12 unique papers with scores ≥ 0.40 — in that case the corpus is saturated and expansion yields diminishing returns. In all other situations, run it.

Otherwise, identify the **2–3 most specific new terms** (prefer gene symbols over pathway names, which were likely already queried). Run at most **2 follow-up searches**:

Expansion Query A — Specific node in disease context (top_k=6):

```
search_corpus
  query="<new_gene_symbol_1> [<new_gene_symbol_2>] <disease> mechanism dependency"
  study_category="pathway_biology"
  top_k=6
```

Expansion Query B — Node interaction / complex (top_k=5, only if a second distinct gene symbol was identified):

```
search_corpus
  query="<new_gene_symbol_1> <new_gene_symbol_2> interaction complex <disease>"
  top_k=5
```

Deduplicate expansion results against all DOIs already collected from Phase 2. For any **new** papers (DOIs not seen before) with score ≥ 0.25, call `get_fingerprint` and merge their extracted fields into the working set before Phase 4.

State in the CORPUS COVERAGE section how many new unique papers the expansion round added and which expansion terms triggered them.

Phase 3.6: Corpus-Wide PDB Lookup

After completing Phases 3 and 3.5, call `find_pdb_structures` **once** with every candidate target protein identified across all phases:

```
find_pdb_structures
  proteins=["<ProteinA>", "<ProteinB>", "<ProteinC>", ...]
```

Include all proteins from `target_nodes`, `upstream_regulators`, and any PPI candidates you intend to include in the TARGET OPPORTUNITY LANDSCAPE — typically 4–8 gene symbols.

This scans the **entire** fingerprint corpus, including papers not retrieved in Phase 2–3, and returns PDB accessions from two sources: `suggested_pdb_structures` in pathway fingerprints and `pdb_accessions` from any paper mentioning the protein.

The result is keyed **per protein** (`by_protein`), and each entry carries `title`, `method`, `resolution_A`, `protein_chain_count`, `entities[]` (with `description`, `organism_taxid`, `organism_name`) and a `query_named_in_metadata` flag. Read all of them — an accession alone tells you nothing about what the structure contains.

When multiple structures are returned for a protein, select the best one using these criteria **in priority order**:

1. **The entry belongs to this node** — a PDB id may only be attached to the node whose **own** protein key returned it in `by_protein`. Corpus `pdb_accessions` include structures a paper merely *cites*, so an id returned under one protein is frequently about something else: read `title` before accepting it, and prefer entries flagged `query_named_in_metadata: true` (they are listed first). If the title describes a different molecule or a different study, discard the entry. If a protein's key returned nothing, that node has **no** suggested structure — never borrow one from another node's list to fill the gap.
2. **Complex present** — `protein_chain_count ≥ 2` and the `entities[].description` fields mention both the target protein AND its binding partner. A co-complex is far more useful than a monomer for interface-based design.
3. **Source organism** — read `entities[].organism_taxid` / `organism_name` for every entry you consider. Prefer a **human** structure (`organism_taxid = 9606`) whenever one exists for the same interface. An **ortholog** structure (any other organism) is a legitimate choice when no human structure of the complex has been solved — that is often the case — but it must be *chosen knowingly and stated*, not picked up by accident: name the organism in the report and flag the entry as an ortholog so the downstream conservation check runs against the human protein. See "Stating the organism" below.
4. **Method quality** — prefer `X-RAY DIFFRACTION` > `ELECTRON MICROSCOPY` > `NMR` (NMR structures lack resolution values and are generally not suitable for interface design).
5. **Resolution** — for X-ray structures, lower `resolution_A` is better; prefer < 2.5 Å when available. For cryo-EM, prefer < 4.0 Å; a coarser map is usable only when nothing better exists for that interface, and say so.

If `metadata_available` is `false` in the tool response (cache not yet populated), use the PDB IDs as-is and note in the report that resolution/method/organism data is unavailable — an unstated organism is itself a finding, not a blank to leave silent.

Stating the organism. Every PDB id you cite anywhere in the report — node assessment, landscape, PRIMARY RECOMMENDATION — must carry its source organism, in the form `<PDB ID> (<organism>)`, adding `— ortholog` when it is not human. Where the recommended structure is an ortholog, say in one clause why no human structure was used (none solved / none in corpus) and which human protein it stands in for. The downstream stages run a deterministic conservation check on an ortholog epitope and can halt the run on it, so an unlabelled ortholog costs a campaign; a labelled one costs nothing.

- Add any newly discovered PDB IDs to the relevant node before writing the report.
- Use the selected ID verbatim in `Suggested PDB ID(s)` fields and in the `### PIPELINE HANDOFF` `pdb_id` line.
- If `total_found` is 0, call `search_rcsb_pdb` with the 2–3 primary target proteins as a fallback. Apply the same selection criteria to the RCSB results. If a suitable structure is found, use its PDB ID in the handoff. If no suitable structure is found from either source, write `NOT_FOUND`.

Phase 4: Synthesise and Output Report

4a — Inferred PPI reasoning (run before writing the report)

For every dysregulated node where `prior_therapeutic_targeting` is null or "None found in corpus", explicitly reason through the following before writing the report:

1. **Interaction necessity**: Does this protein's known pathway role require it to physically engage a specific partner to exert its disease-relevant activity? Use `pathway_logic`, `upstream_regulators`, `downstream_effectors`, and `key_findings` as evidence sources.
2. **Therapeutic mechanism — disrupt, stabilize, or inhibit_active_site?** Determine which design intent applies to this node: - `disrupt` — breaking a protein-protein interaction attenuates the disease-relevant output (e.g. loss of complex formation → loss of oncogenic signalling, loss of transcriptional co-activation, failure to relay a pathological signal). **Default for PPI candidates.** - `stabilize` — the disease mechanism is that a normally protective or autoinhibitory interaction is *lost* or *weakened*; reinforcing it restores the healthy state (e.g. restoring an autoinhibitory complex, re-engaging a sequestered OFF-state, protecting a tumour suppressor complex from degradation). - `inhibit_active_site` — for a single protein where direct occlusion of a **binding cleft** (any kind, not just enzyme active sites) is the established therapeutic mode. The mode name is historical — interpret broadly: it covers (a) enzyme catalytic sites, (b) allosteric pockets, (c) substrate-binding clefts on non-enzymes including **DNA-binding clefts** (e.g. blocking a cytosolic DNA sensor), RNA-binding clefts, lipid-binding pockets, and metabolite-binding sites. The pipeline mechanic is identical in every case: a designed peptide / macrocycle / mini-protein occupies the cleft and competes with the natural ligand.

   Only use when (a) the corpus shows explicit precedent for peptide / macrocycle / mini-protein modulators of this cleft AND (b) no high-quality PPI option exists for the same node. For enzyme active sites specifically, do not pivot just because the protein is "an enzyme" — small molecules dominate catalytic-site inhibition and the binder pipeline only adds value when the pocket is poorly druggable by small molecules. For DNA / RNA / substrate-binding clefts the binder pipeline is more competitive (large, flat, polar surfaces are harder for small molecules), so the bar for choosing this mode is lower. Record one `design_intent` per node. Default to `disrupt` if ambiguous between disrupt and stabilize. Default to `disrupt`

(PPI) over `inhibit_active_site` when both are plausible. 3. **Interaction knowability**: Is the specific binding partner named or strongly implied in the corpus (e.g. a co-activator, scaffold, receptor partner)? Do not infer a generic "this protein must bind something" — name the partner. For `inhibit_active_site` candidates this condition is **replaced by**: is the pocket / active site well-characterised in the corpus (catalytic residues named, or pocket-binding residues from prior inhibitor structures)?

If conditions 1+2+3 are met for a PPI candidate, label it **[PATHWAY INFERRED]**. If genetic dependency is also confirmed, label it **[BIOLOGICALLY JUSTIFIED]**. If prior therapeutic targeting is documented in the corpus, label it **[VALIDATED]**. If the candidate is an `inhibit_active_site` pivot, label it **[DIRECT INHIBITION]** — this tier ranks **below** all PPI tiers regardless of the strength of the active-site evidence, because the pipeline is PPI-optimised. A node may carry only one label.

Produce the full `## PATHWAY BIOLOGY REPORT` using **only information retrieved from the corpus**. Do not hallucinate pathway details. If a section cannot be filled from retrieved fingerprints, omit the line entirely — do not write "Not found in corpus" placeholders for empty fields.

Citation policy: Every cited claim must come from a retrieved fingerprint. - Citation format: `DOI + source_span` (e.g. `10.7554/eLife.77415, Page 3 Para 2`). - No author names, journal names, or years — ever. Write the DOI only. - If you know a biological fact from training knowledge but have no corpus DOI for it, state the fact without any citation — do not invent a reference. - A fact with no citation is acceptable. A fact with a fabricated citation is not.

Token budget: The full PATHWAY BIOLOGY REPORT must fit in 3,000–4,500 words. Write bullet points, not prose paragraphs. Each section should be a tight list.

Report Format

```

## PATHWAY BIOLOGY REPORT

### DISEASE CONTEXT

- Disease / indication:
- Pathway(s) implicated:
- Primary disease mechanism:
- Frequency of pathway dysregulation:

### PATHWAY MAP

- Upstream regulators:
- Core cascade:
- Key effectors / transcription factors:

### DYSREGULATED NODES ASSESSMENT

For each candidate target node — max 4 nodes total, 6 bullet lines per node:

- Pathway position:
- Dysregulation:
- Genetic dependency:
- Prior therapeutic strategies:
- Suggested PDB structures: <ID> (<organism>) and `— ortholog` when not human; ONLY ids returned by a tool under THIS protein's own key; omit if absent>
- Inferred PPI opportunity:

### TARGET OPPORTUNITY LANDSCAPE

Present 2–3 PPI candidates, each assigned an evidence tier from Phase 4a. List highest tier first. Within the same tier, rank by PDB availability.

For each candidate:

[]

- **Evidence basis**: <1–2 sentences citing the specific corpus evidence — genetic dependency result, pathway logic, prior drug program, or inferred interaction necessity>
- **What makes it attractive**:
- **Key uncertainty**:
- **Suggested PDB ID(s)**:
```

Tier definitions for the header labels (PPI candidates ranked above direct-inhibition): - [VALIDATED] — PPI; prior therapeutic targeting documented in corpus - [BIOLOGICALLY JUSTIFIED] — PPI; genetic dependency confirmed; interaction necessity supported by pathway evidence; no therapeutic precedent in corpus - [PATHWAY INFERRED] — PPI; no genetic dependency data; but named interaction is required for disease-relevant pathway output per corpus logic - [DIRECT INHIBITION] — Single-protein target where the designed binder occludes a binding cleft on one chain. Covers enzyme active sites, allosteric pockets, AND substrate-binding clefts on non-catalytic proteins (DNA-binding clefts on innate immunity sensors, RNA-binding sites, lipid-binding pockets, etc.). Use when there is characterised peptide/macrocycle/mini-protein precedent in corpus AND no high-quality PPI option for this node. Always ranked below the three PPI tiers regardless of evidence strength.

PRIMARY RECOMMENDATION

State which candidate from the TARGET OPPORTUNITY LANDSCAPE is recommended for the downstream pipeline, and why (1–2 sentences balancing evidence strength, structural tractability, and novelty value). If the user has provided a constraint (e.g. "focus on unexplored targets"), weight accordingly.

- **Target complex**:
- **Evidence tier**: <[VALIDATED] / [BIOLOGICALLY JUSTIFIED] / [PATHWAY INFERRED]>
- **Suggested PDB ID(s)**:
- **Structure organism**: <organism> (ortholog of human <GENE>). If an ortholog, add one clause on why no human structure was used and which site is expected to be conserved>
- **Proposed next step**: Run complex-structure-analysis on PDB (only if PDB confirmed from corpus; otherwise await user input)

Selection criteria (apply in order, but surface all tiers in the landscape regardless): 1. PPI tier rank — [VALIDATED] > [BIOLOGICALLY JUSTIFIED] > [PATHWAY INFERRED] > [DIRECT INHIBITION] 2. Genetic dependency confirmed (CRISPR essential in disease-relevant lines) — strongest evidence 3. Pathway position as a convergence node (multiple upstream alterations feed into it) 4. Prior therapeutic targeting attempts — validates the interface / pocket is engageable 5. Inferred interaction necessity — named partner, corpus-supported pathway logic, predictable consequence of disruption (see Phase 4a) 6. Known PDB structure available — required for the downstream structure-analysis step 7. For PPIs: accessible interface (prefer surface-exposed). For DIRECT INHIBITION: pocket characterised in corpus + peptide / macrocycle inhibitor precedent. 8. **Target chain size** — design + prediction scale with residue count. Strong preference for chains ≤ 250 residues; hard limit at 500. If a candidate's binding-relevant chain or domain exceeds 500 residues, prefer either (a) a PDB of a smaller domain construct of the same target, (b) a different target in the same pathway, or (c) note the cropping recommendation explicitly so the downstream structure stage can act on it. Surfacing a giant target without flagging the size is a pipeline-time failure mode.

If no recommendation can be made from corpus data alone, state this explicitly and suggest the user run `python scripts/fetch_papers.py` with specific pathway keywords.

REDUNDANCY AND RESISTANCE RISKS

-

CORPUS COVERAGE

- Papers analysed: from
- Fallback used:
- Expansion round:
- Critical gaps:
- Keywords to add (if gaps are critical): `python scripts/fetch_papers.py --keywords "<keyword>"`

PATHWAY SOURCES

#	TITLE (TRUNCATED TO 60 CHARS)	DOI	KEY NODE
1	...	...	...

PIPELINE HANDOFF

- pdb_id:
- structure_organism:
- target_complex:
- design_intent:
- structure_query:
- choices_json:

IMPORTANT: Write the `### PIPELINE HANDOFF` section as plain bullet lines exactly as shown above. Do NOT wrap it in a code fence (no `` before or after). Do NOT omit the `-` prefix. The programmatic orchestrator parses these lines with a

regex — any deviation breaks the pipeline.

Rules for `### PIPELINE HANDOFF`: - `pdb_id` must come from `paper_metadata.pdb_accessions`, `pathway_context.target_nodes[].suggested_pdb_structures` in retrieved fingerprints, **or the `find_pdb_structures` tool result from Phase 3.6**. Write `NOT_FOUND` if nothing found — never guess. - `structure_organism` must be read off the chosen entry's `entities[].organism_name`, not recalled — it is the field the downstream stages use to decide whether to run the ortholog conservation check, and a wrong or omitted organism is how an ortholog reaches design unexamined. - `structure_query` is the verbatim query string passed to complex-structure-analysis by the programmatic orchestrator; make it self-contained (include the local file path `data/structures/{pdb_id}.cif`). - `choices_json` must be a single-line JSON array listing every candidate from TARGET OPPORTUNITY LANDSCAPE in the same order. Each element has exactly these keys: - `tier`: one of `"VALIDATED"`, `"BIOLOGICALLY_JUSTIFIED"`, `"PATHWAY_INFERRED"`, or `"DIRECT_INHIBITION"` - `complex`: the protein pair name exactly as written in the `####` header (formatted `"GENE_A / GENE_B"`). For DIRECT_INHIBITION candidates, the single-protein label (formatted `"GENE_A (active site)"`) - `pdb_ids`: array of PDB accession strings from corpus only — empty array `[]` if none found - `evidence_basis`: one sentence summary of the evidence (no newlines, no quotes inside the string) - `key_uncertainty`: one sentence summary of the key uncertainty (no newlines, no quotes inside the string) - `design_intent`: `"disrupt"`, `"stabilize"`, or `"inhibit_active_site"` from Phase 4a reasoning for this candidate

Example (must be on ONE line, no line breaks inside). The gene names below are DELIBERATE PLACEHOLDERS, not candidates — this example shows the SHAPE of the field and nothing about which target to pick. Substitute the proteins your own analysis arrived at; if `GENE_A` ever appears in a report it means an example was copied instead of answered. `- choices_json: [{"tier":"VALIDATED","complex":"GENE_A / GENE_B","pdb_ids": ["1ABC","2DEF"],"evidence_basis":"One sentence from the corpus, citing the strongest evidence for this pair.","key_uncertainty":"One sentence naming what would falsify it.","design_intent":"disrupt"}, {"tier":"BIOLOGICALLY_JUSTIFIED","complex":"GENE_C / GENE_D","pdb_ids":[],"evidence_basis":"One sentence; e.g. a genetic dependency with no structure in corpus.","key_uncertainty":"No structural data in corpus.","design_intent":"disrupt"}]`

Use straight double-quotes only. No trailing commas. Escape any double-quote inside a string value as `\"`.

Handoff Contract

The `PRIMARY RECOMMENDATION` (within TARGET OPPORTUNITY LANDSCAPE) is the primary handoff to downstream skills:

- → **complex-structure-analysis**: use `Suggested PDB ID(s)` and `Target complex` from PRIMARY RECOMMENDATION
- → **molecular-biology-expert**: use `Target complex` as the protein pair to query
- → **orchestrator**: use the full report for Stage 0 summary; extract complex + PDB from PRIMARY RECOMMENDATION

The `TARGET OPPORTUNITY LANDSCAPE` is for human review only — the orchestrator and downstream skills consume only the `PRIMARY RECOMMENDATION` block.

If the pathway-expert is invoked from within the orchestrator (Stage 0), the orchestrator extracts the `PRIMARY RECOMMENDATION` block and passes it to Stage 1 automatically.

Common Pitfalls

- If corpus has zero pathway_biology papers, the `study_category` filter will return nothing — always fall back to unfiltered search and report the gap transparently.
- **Never guess PDB accession codes.** Only report PDB IDs that appear verbatim in `pathway_context.target_nodes[].suggested_pdb_structures` or `paper_metadata.pdb_accessions` of retrieved fingerprints. Do not supply codes from your training knowledge — LLM recall of 4-character accession codes is unreliable (e.g. confusing 4B7F with 4U6V). If no PDB is present in any fingerprint for the recommended complex, write `"Not found in corpus"` and provide the user with RCSB search terms to look it up manually.
- **Never move a PDB id between nodes.** An id is only evidence for the protein whose own `by_protein` key returned it. Two real failures from one run: an id listed under a caspase node turned out to be a de novo binder-design entry that had matched a three-letter gene symbol as a substring of an unrelated word; and a second id was copied under three separate nodes, one of whose keys had returned nothing at all. Both are avoided by reading `title` and staying inside the key.

Membrane receptors: which site a designed binder can actually reach

A binder is a folded protein in solution. It can only engage surface that is solvent-exposed on ONE face of the membrane. This rules out large parts of a GPCR, and the constraint is chemical, not a limitation of the pipeline — so choose the site accordingly rather than proposing one that will be refused. WHICH face is a judgement about where the therapeutic effect lives; only the lipid-buried surface itself is ruled out on both.

Reachable, and clinically validated — prefer these where the effect lives here, which for a cell-surface receptor it usually does:

- **Class B ECDs.** These use a two-domain mechanism: the peptide hormone's C-terminus binds a genuine extracellular domain, its N-terminus then inserts into the helical bundle. The ECD contact is a real protein-protein interface and is fully extracellular. Approved antibodies and trial agents exist against class B ECDs, so the modality is validated — identify the specific receptor from the corpus, not from this list.
- **Class C Venus flytrap** (mGluR, CaSR, GABA-B) — the orthosteric site is entirely extracellular and large.
- **Class F CRD** (Frizzled, SMO).
- **N-terminus and extracellular loops of PEPTIDE-binding class A receptors** (chemokine receptors, angiotensin, opioid peptide receptors). The ligand has a large extracellular footprint, and antibodies against these surfaces work (mogamulizumab/CCR4, leronlimab/CCR5).
- **Receptor / accessory-protein interfaces**, where the interface itself sits outside the membrane.

Reachable, but only with a delivery route you must name:

- **Cytoplasmic domains and intracellular faces.** Harder to reach, not impossible, and NOT refused by this pipeline — it reads the membrane face off the residues you propose and trims to that face, so a coherently cytoplasmic epitope is designed against normally. Many mechanisms only exist there: a receptor's effector-recruitment or kinase surface, and any protein in an intracellular-organelle membrane, where "extracellular" names no real surface at all. Propose one when that is where the effect is — and say in the same breath what gets the binder into the cytosol (fusion to a delivery module, intracellular expression, a degrader/glue format). A target needing intracellular delivery cannot carry `tractability: Excellent` with the route unstated; the delivery burden belongs in `go_rationale` where a reader can weigh it. Understating it is the error — choosing the target is not.

Not reachable — do not propose these:

- **The orthosteric pocket of a receptor whose ligand is a lipid or a lipophilic small molecule** (cannabinoid, S1P, LPA, prostaglandin, free fatty acid). These pockets are inside the helical bundle and there is strong structural evidence that the ligand enters LATERALLY, from within the bilayer, through gaps between transmembrane helices — S1P1 is capped by its own N-terminal helix, and CB1 has lipid-facing portals. Nothing arriving from solution can occupy that site.
- **Deep aminergic pockets** (adrenergic, muscarinic, dopaminergic). Reached from the extracellular side, but far too enclosed for a 70-86 residue mini-protein; these are small-molecule sites.
- **Any transmembrane surface at all.** In an isolated structure a TM helix looks like an attractive hydrophobic patch; in a cell it is buried in lipid.

A practical test before proposing a membrane target: *is this site solvent-exposed on one face, or is it inside the bundle?* If it is inside the bundle, no designed mini-protein reaches it from either side. "Would an antibody work here?" is the sharper version of that test for the OUTER face only — an antibody's own inability to reach the cytosol says nothing about a site's geometry, and a cytoplasmic domain that fails the antibody test can still be a real target for a delivered binder.

The pipeline enforces this deterministically further down — UniProt topology is mapped into author numbering and the trim drops the transmembrane span and the opposite face, and a hotspot annotated transmembrane fails the run outright. So a receptor whose only druggable site is intramembrane is not a target for this pipeline: say so and pick another node rather than spending stages on it.

When the best target has no experimental structure, an AlphaFold model is a legal answer. Emit `pdb_id: AF-<UniProt accession>` (e.g. the accession you resolved for that protein) and the pipeline fetches the predicted model. Two conditions, both hard:

1. **Only with `design_intent: inhibit_active_site`.** An AlphaFold model is a single chain, so there is no partner in it to disrupt or stabilise. A run that pairs `AF-` with `disrupt` or `stabilize` is refused before any spend.
2. **Only when no experimental co-complex exists.** An experimental structure of the real complex always wins; check with `search_rcsb_pdb` first and say in the report that you looked.

This matters most for the case that used to dead-end: a well-evidenced target with no PDB entry. Recommending a *downstream* complex instead is a real option, but it answers a different question than the user asked — if you do that, say so in one clause in PRIMARY RECOMMENDATION and keep the original target in the landscape at its own tier.

- **Never report a PDB id without its source organism.** Whether the entry is human or an ortholog changes what the downstream stages have to verify, and the organism is in the tool payload — there is no reason to leave it out or to guess it.
- Redundancy risks are easy to miss — always check `pathway_context.redundancy_risks` across ALL retrieved fingerprints, not just the top-scoring one.
- **PPI is the strong default**: a [DIRECT INHIBITION] candidate is only correct when the corpus provides explicit evidence for peptide / macrocycle / mini-protein active-site inhibitors of *this specific pocket* AND no [VALIDATED] / [BIOLOGICALLY

JUSTIFIED] / [PATHWAY INFERRED] PPI candidate exists for the node. If both a PPI and a direct-inhibition path are plausible, recommend the PPI in PRIMARY RECOMMENDATION and include the direct-inhibition entry in the landscape as a lower-tier alternative.

- In Phase 3.5, do not re-query with terms already present in any Phase 2 query string — this yields near-duplicate results and wastes calls. Only use genuinely new gene symbols or mutation terms surfaced by the fingerprints.
- Do not run more than 2 expansion queries. If Phase 3.5 surfaces a large number of new terms, pick the 2–3 most specific (gene symbols > pathway names > disease terms) and stop. More expansion rounds have sharply diminishing returns on a focused corpus.
- **[PATHWAY INFERRED] guardrail**: an inferred PPI target must name a *specific* binding partner supported by the corpus (e.g. co-activator, scaffold, receptor subunit). Do not assign this tier to vague statements like "this protein must interact with a partner" or "complex formation is implied" — name the partner or write "Insufficient evidence."
- **Do not conflate tiers**: the absence of a drug program ([VALIDATED] missing) does not itself make a target [BIOLOGICALLY JUSTIFIED] — that tier requires confirmed genetic dependency. Pathway inference alone is [PATHWAY INFERRED], regardless of how compelling the biology looks.
- **Disease agnosticism**: avoid disease-specific framing (e.g. "tumour suppressor", "oncogenic"). Use neutral language: "pathway suppressor", "disease-relevant activity", "pathological signalling output", "dysregulated node". The pipeline applies to any indication, not only cancer.

wildcard-expert

`wildcard-expert` `6962 words`

Frontmatter description. Invoke ONLY when the user explicitly asks for it by name or clearly requests this specific workflow; do not trigger it from a general question, which you can answer better from your own knowledge than from this narrow corpus. Query the curated literature database to identify non-obvious, potentially novel PPI targets for a disease context. Uses a training-knowledge bridge plus graph-driven novelty triage (interaction_hubs, shortest_interaction_path, novelty_signal) to generate hypotheses, then validates each strictly against the corpus. Complements pathway-expert: use when the user explicitly wants creative or out-of-the-box suggestions, or when standard pathway analysis has already been run and the user wants a parallel speculative analysis for comparison. Output format is identical to pathway-expert and feeds directly into complex-structure-analysis and molecular-biology-expert. Works across disease-driven contexts (cancer indications, autoimmune, metabolic) AND basic-biology contexts (signalling pathway exploration, protein-complex assembly, organelle / compartment biology) — the "novelty" mandate does not assume a disease anchor. Tools: search_corpus, get_fingerprint, find_pdb_structures, search_rcsb_pdb, interaction_hubs, shortest_interaction_path, novelty_signal, get_interactions_for, find_quantitative_evidence, export_subgraph, get_genetic_codependency, find_cocorrelated_genes, cluster_for_protein. Trigger on: "wildcard", "novel target", "creative suggestions", "out-of-the-box", "unexpected PPI", "re-run wildcard", or any explicit request to explore non-obvious targets.

Wildcard Pathway Expert

This skill generates creative, non-obvious PPI target hypotheses by combining a training-knowledge bridge (Phase 3) with strict corpus re-anchoring (Phase 4). It is the speculative counterpart to pathway-expert — every candidate in the final report that makes a factual claim must cite corpus evidence, but the search strategy itself is driven by parametric reasoning rather than only the terms the corpus returns.

The output is a structured `## PATHWAY BIOLOGY REPORT` with the same format and `### PIPELINE HANDOFF` block as pathway-expert, so it slots directly into the downstream pipeline.

Phase 1: Extract Context from User Input

Identify: - `biological_context` — the system being explored. May be a disease ("PDAC", "NSCLC", "HCC", "AML", "ALS", "type-2 diabetes", "IPF"), a pathway in normal physiology ("unfolded protein response", "DNA replication initiation", "hematopoietic stem-cell quiescence"), or a process ("ciliogenesis", "macroautophagy initiation", "spindle assembly checkpoint"). The novelty mandate applies equally to both — many tractable PPIs in basic biology have no disease anchor yet. - `pathway_hint` — optional; a pathway name supplied by the caller. Use it only if given; never invent one, and never carry an example from this prompt into a report. - `mode` — derived: `disease_anchored` if a disease/indication was named, `basic_biology` if only a pathway/process was named. This determines whether downstream queries include disease-essentiality terms or focus on biochemistry / co-essentiality / structural biology. - `constraint` — optional; e.g. "avoid previously targeted nodes", "extracellular only", "phase-separating proteins only"

If the context is ambiguous proceed with the broad term — do not block on ambiguity.

Phase 2: Abbreviated Direct Corpus Search

Run **2 queries** (not 4 — save context budget for the creative phases). Use `study_category="pathway_biology"` with unfiltered fallback if scores < 0.20.

Query 1 — Pathway mechanism (top_k=20):

```
search_corpus
  query="<pathway_hint OR biological_context> signaling molecular mechanism regulation"
  study_category="pathway_biology"
  top_k=20
```

Notes: do NOT include "dysregulation" or "cancer" / "disease" keywords unless `mode = disease_anchored`. In `basic_biology` mode "regulation" / "activation" / "complex formation" give more relevant hits.

Query 2 — Genetic dependency / essentiality (top_k=10):

For `mode = disease_anchored`:

```
search_corpus
  query="<biological_context> CRISPR screen genetic dependency essentiality <pathway_hint>"
  study_category="pathway_biology"
  top_k=10
```

For `mode = basic_biology`:

```
search_corpus
  query="<pathway_hint> essential genes CRISPR screen co-essentiality"
  study_category="pathway_biology"
  top_k=10
```

DepMap-style essentiality data is informative regardless of disease anchor — the goal is to find proteins whose loss-of-function phenocopies the pathway state of interest.

Query 3 — Biochemistry / interface (mode-conditional, optional, top_k=8):

In `basic_biology` mode (or when the disease anchor is weak), add a third query to surface structural / mechanistic literature that pure disease-essentiality searches miss:

```
search_corpus
  query="<pathway_hint> protein-protein interaction interface structure biochemistry"
  top_k=8
```

Deduplicate by DOI. Retrieve `get_fingerprint` for the top 12–16 unique papers from Phase 2. From each fingerprint, explicitly extract and record:

- `pathway_context.pathways` — which pathways are covered
- `pathway_context.disease_associations` — disease, mechanism, mutation_frequency, source_span
- `pathway_context.target_nodes` — protein, pathway_position, dysregulation, genetic_dependency_evidence, prior_therapeutic_targeting, **suggested_pdb_structures**, source_span
- `pathway_context.pathway_logic` — ON/OFF logic summary
- `pathway_context.redundancy_risks`
- `pathway_context.upstream_regulators`, `downstream_effectors`
- `paper_metadata.pdb_accessions` — PDB IDs associated with this paper
- `key_findings` — incidental biochemistry findings that may be relevant

Record every PDB accession found in `suggested_pdb_structures` or `paper_metadata.pdb_accessions` at this stage. These are Phase-2 PDB IDs — carry them forward explicitly; they must appear in the report even if Phase 4.6 returns no additional hits for those proteins.

These fingerprints form the baseline evidence set and seed the term list for Phase 3.

Corpus gap fallback

If both queries return scores < 0.20 or empty, re-run without `study_category`. Always state the fallback in the CORPUS COVERAGE section.

Phase 2.5: Graph-Driven Novelty Triage *(MANDATORY)*

Before Phase 3's creative reasoning, anchor your search in the corpus interaction graph and the novelty signal. This phase produces a "hub residuals" table — well-connected nodes the literature has NOT yet saturated — and seeds the hypothesis space for Phase 3 with proteins your training-knowledge bridge alone would miss.

Required calls (do not skip):

Call 1 — Establish prior-art hubs (always):

```
interaction_hubs
  top_n=20
  min_mentions=3
```

Record the top 5 protein names as **HIGH PRIOR ART nodes** — these are the proteins everyone is already chasing. Candidates that match this list need extraordinary justification for inclusion as novel hypotheses.

Call 2 — Score every emerging candidate:

For each candidate protein already surfaced in Phase 2 (proteins from `pathway_context.target_nodes[].protein`, plus the canonical driver if known from `disease_or_cancer`), call:

```
novelty_signal
  protein=<GENE_SYMBOL>
```

Record `novelty_score` ∈ [0, 1] and `counts.mentions` per candidate.

Call 3 — Connectivity to the anchor node (for each non-anchor candidate):

Identify an `anchor_node` for connectivity queries: - `disease_anchored` mode → the canonical driver gene of the disease, as established by the Phase-2 fingerprints and your own knowledge. Derive it; do not import one. (Where a disease is NAMED for its driver lesion, that lesion is usually the anchor.) - `basic_biology` mode → the most-mentioned hub node in the Phase-2 fingerprints that participates in the pathway of interest (e.g. ATG1 / ULK1 for autophagy initiation, PERK for the UPR).

For each non-anchor candidate, call:

```
shortest_interaction_path
  protein_a=<anchor_node>
  protein_b=<candidate>
  max_hops=4
  k=1
```

Record whether a path exists and the `min_mentions_along_path`. A path of length ≤ 3 with `min_mentions_along_path ≥ 2` is **mechanistically connected**. A missing path or a 1-mention weak link is **disconnected** (still worth considering for UNCHARTED tier but flag the gap explicitly).

Call 4 — DepMap co-essentiality vs. top-3 hubs *(MANDATORY for each candidate)*:

DepMap co-essentiality is the closest thing to ground-truth functional co-dependency we have — it reflects loss-of-function phenocopying across ~1,200 cell lines, independent of literature attention. A high-r pair is strong evidence of functional coupling even if no paper has explicitly connected the two genes.

Use three reference hubs, not one. Literature attention crowns one canonical driver per pathway, but functional coupling does not respect that framing — a candidate uncoupled from the named anchor may still be strongly coupled to a hub the corpus underweights. Take the top-3 hub nodes from Call 1 (`interaction_hubs`); in `disease_anchored` mode, substitute the disease driver for one of them so it is always tested. Call `get_genetic_codependency` for each candidate against each of the three hubs (3 calls per candidate, runnable in parallel):

```
get_genetic_codependency
  gene_a=<hub_i>
  gene_b=<candidate>
```

Record `pearson_r` and `n_cell_lines` for each of the three pairings, take the **maximum r** across the three hubs as the candidate's `depmap_max_r_to_hubs`, and **remember which hub gave that maximum** (the candidate's strongest hub-codep partner). Interpretation applies to `max_r`: - `max_r ≥ 0.4` and `n ≥ 200`: **co-essential to at least one hub** — a strong functional signal even when the literature path is absent. - `0.2 ≤ max_r < 0.4`: **weakly co-essential** — supports but does not establish functional coupling. - `max_r < 0.2` or `n < 100` for all three: **uncoupled from the hub set** by DepMap criteria.

Call 5 — Co-essential partners of the anchor *(MANDATORY once)*:

Surface unexpected co-essential partners of the anchor that did NOT appear in Phase-2 fingerprints — these are the highest-yield hypothesis seeds because they combine functional ground truth with literature absence:

```
find_cocorrelated_genes
  gene=<anchor_node>
  top_n=15
  min_r=0.3
```

Cross-reference the returned gene symbols against (a) Phase-2 proteins, (b) Phase-2 fingerprints' `target_nodes`, (c) the `interaction_hubs` top-20. Any gene that appears here with `r ≥ 0.35` but is missing from ALL three above is a **DepMap residual** — flag prominently for Phase 3.

Call 6 — Cluster context (optional, per top candidate):

For each candidate scoring CONNECTED-NOVEL / PERIPHERY-NOVEL / UNCHARTED, optionally call:

```
cluster_for_protein
  protein=<candidate>
```

Note the cluster's `hub`, top members, and whether the cluster contains the anchor. Co-cluster membership without direct literature path is itself a hypothesis seed.

Call 7 — Candidate-edge DepMap sweep *(MANDATORY for the top-2 candidates by classification rank)*:

Calls 4 and 5 view the codep landscape from the anchor's vantage point — "is this candidate coupled to a hub I already care about?" Call 7 inverts that: it surveys the candidate's OWN functional neighborhood. This catches the highest-value wildcard finding — "the novel pick is strongly codependent with a cancer-relevant protein the corpus has not yet linked to it" — which Calls 4–5 will miss whenever the candidate sits in a separate module from the anchor.

Rank the candidates by classification (DEPMAP-COUPLED > PERIPHERY-NOVEL > UNCHARTED > CONNECTED-NOVEL > MID-NOVEL > SATURATED). For the top 2, run both of the following (they batch into parallel tool calls):

(a) **Global DepMap residuals for the candidate** — top-k codependent genes regardless of corpus presence:

```
find_cocorrelated_genes
  gene=<candidate>
  top_n=10
  min_r=0.3
```

(b) **Corpus-graph neighbors of the candidate** — what the literature says it interacts with:

```
get_interactions_for
  protein=<candidate>
  top_n=10
```

Cross-reference the two result sets and categorise each surfaced partner: - **Graph-confirmed codep partners** — present in BOTH (a) and (b). The literature already names the interaction AND DepMap validates functional coupling. Strongest single signal you can produce; cite both sources. - **Codep residual for the candidate** — present in (a) but NOT (b). Pure functional connection the literature has not caught. Cross-reference against the Call 1 `interaction_hubs` top-20: a candidate strongly codependent (r ≥ 0.4) with a corpus hub it is not edge-connected to is the **highest-yield wildcard finding** (functional coupling to a literature-attended driver, without literature recognition of the link). Flag prominently. - **Corpus-only partner** — present in (b) but NOT (a) with r ≥ 0.3. Literature-claimed interaction without independent DepMap support. Discount when assessing functional importance.

Record the top 3 codep partners per candidate (highest `pearson_r` with `n ≥ 200`) as the candidate's `depmap_neighborhood`. Each entry: `{partner, r, n_cell_lines, in_corpus_graph: bool, in_hub_top20: bool}`. This feeds the CANDIDATE NODE ASSESSMENT line and the `choices_json` handoff, and should inform PRIMARY RECOMMENDATION rationale ("the pick is functionally coupled to <hub> at r=0.55 — an unrecognised axis").

Synthesise: hub residuals table

Combine all six calls into a single table that drives Phase 3 hypothesis generation. The DepMap r is your strongest non-literature signal — surface it as its own column, and surface the top codep partner (from Call 4's hub sweep) so the reviewer can see WHERE the coupling is:

PROTEIN	HUB RANK	NOVELTY_SCORE	PATH TO ANCHOR (HOPS, MIN_MENTIONS)	DEPMAP MAX_R VS HUBS (PARTNER)	TOP CODEP NEIGHBOUR (CALL 7, IF RUN)	CLUSTER	CLASSIFICATION
...	...	...	...	...	...	...	...

Classification rules (assign one per candidate; first matching rule wins):

CLASS	RULE
SATURATED	hub rank in top-20 AND novelty_score < 0.4

CLASS	RULE
CONNECTED-NOVEL	hub rank in top-20 AND novelty_score ≥ 0.6
PERIPHERY-NOVEL	not a hub AND novelty_score ≥ 0.6 AND literature path to anchor exists
DEPMAP-COUPLED	not a hub AND novelty_score ≥ 0.5 AND (max_r vs hubs ≥ 0.4 OR Call-7 top neighbour r ≥ 0.4) — functional coupling without literature recognition; this is the highest-yield wildcard class. The DepMap signal may come from any of the 3 hubs (Call 4) or from the candidate-edge sweep (Call 7); record which
UNCHARTED	novelty_score ≥ 0.8 AND no literature path AND max_r < 0.2 (or n too small to call)
MID-NOVEL	otherwise (0.4 ≤ novelty_score < 0.6, or borderline cases)

`CONNECTED-NOVEL`, `PERIPHERY-NOVEL`, `DEPMAP-COUPLED`, and `UNCHARTED` are the **interesting** classifications. `SATURATED` candidates are pathway-expert's job, not yours; the wildcard mandate is novelty.

Carry `novelty_score`, `classification`, the max_r-to-hubs (with partner), and the Call-7 `depmap_neighborhood` (for the top 2 candidates) per candidate forward into Phase 5 tier assignment and into the `choices_json` handoff.

Phase 3: Hypothesis Generation — Corpus + Graph First, Training Knowledge as Gap-Filler

Generate **3–5 novel PPI hypotheses**. The goal is hypotheses the corpus + graph have already *implied* but no individual paper has *stated* — these are the highest-value outputs of this skill. Training knowledge is allowed only as a last resort to fill specific mechanism / residue gaps after the corpus and graph have done their work.

Step order (do all three; do them in this order):

Step 3a — Mine Phase 2.5 graph patterns (PRIMARY hypothesis source)

Look at the hub-residuals table for these patterns: - **DEPMAP-COUPLED candidates**: a `DEPMAP-COUPLED` row is a hypothesis on a plate — high co-essentiality (DepMap r ≥ 0.4) but no direct literature path means "these two genes phenocopy each other across hundreds of cell lines but nobody has connected them in writing yet". Lift this candidate verbatim as a hypothesis; the mechanism rationale is the DepMap r value. - **CONNECTED-NOVEL with long path**: a candidate with novelty_score ≥ 0.6 and a 3-hop path to the anchor through low-mention edges. The intermediate hop proteins are themselves hypothesis seeds (often more interesting than the endpoint). - **Cluster residuals**: a `cluster_for_protein` result containing a member the disease-driver literature never mentions but the cluster hub does. - **`find_cocorrelated_genes` flagged residuals**: genes that came back with r ≥ 0.35 against the anchor but appeared in zero Phase-2 fingerprints. The Phase-2.5 call already flagged these — promote them to full hypotheses here.

Step 3b — Mine non-obvious connections in Phase 2 fingerprints

Look across the Phase-2 fingerprint set for: - **Single-paper bridges**: two proteins co-mentioned in exactly one fingerprint with `key_findings.protein_pair` — the corpus has *seen* this pair once but no one has built a programme around it. - **Asymmetric pathway membership**: a protein appearing in `pathway_context.target_nodes` but with `prior_therapeutic_targeting=null` in every fingerprint that mentions it. - **Effector / regulator mismatches**: an `upstream_regulator` in one fingerprint that doesn't appear in any other fingerprint's pathway map — suggests an incompletely described axis.

Step 3c — Training knowledge ONLY to fill gaps

Use parametric knowledge to ANNOTATE the corpus/graph-derived hypotheses above — add mechanism, propose specific interface residues from family structural biology, suggest a tractable assay. Do NOT introduce entirely new proteins via training knowledge.

HARD RULE: if your hypothesis introduces a protein that did NOT appear in ANY Phase-2 fingerprint, ANY Phase-2.5 graph output, OR the DepMap correlated set, you are reasoning from training knowledge alone — drop the hypothesis unless Phase 4 re-anchors it. The pipeline's value-add over "ask Claude directly" is the corpus + graph; hypotheses untethered to those forfeit that value-add.

Hypothesis archetypes to consider

These are LENSES for interpreting the Step 3a/3b signals, not free-form brainstorming prompts:

- **Co-essential dark partner** (DepMap-driven): two genes are co-essential across cell lines but no paper has co-cited them in this context. Most-likely interpretation: shared complex, shared substrate, or parallel-pathway redundancy.
- **Cross-context transfer**: a PPI well-characterised in a different biological context (different disease, different tissue, different developmental stage) that should generalise here. Requires explicit reasoning about WHY the transfer works.
- **Paralog vulnerability**: a less-studied paralog whose interaction with a shared scaffold becomes load-bearing when the canonical paralog is lost or suppressed.
- **Upstream rewiring**: an adaptor / co-chaperone whose interaction with a known node has been described in biochemistry but not yet as a target in this context.
- **Phase-separation / condensate residency**: a protein known to localise to a relevant condensate / membrane-less compartment but never characterised as a PPI target there.

Disease-anchored archetypes (use only when `mode = disease_anchored`): - **Synthetic lethality**: a PPI that becomes essential only because of a co-occurring alteration present in the disease. - **Cross-indication transfer**: a PPI well-characterised in a related disease that may be relevant despite sparse direct evidence in the target indication.

Write each hypothesis in this block (internal reasoning — shown before the report):

```
## WILDCARD HYPOTHESIS GENERATION
[Generated from Phase 2.5 graph patterns + Phase 2 corpus connections; training
knowledge used only for annotation. Citations to corpus/DepMap data are
```

```
permitted here; bare training-knowledge claims are not.]

HYPOTHESIS 1: <ProteinA / ProteinB>
  Source signal: <Step 3a graph pattern / Step 3b corpus connection / DepMap r value>
  Mechanism: <why this PPI matters in the biological context — 1–2 sentences>
  Novelty: <what makes this non-obvious — 1 sentence>
  Why corpus might support it: <indirect evidence path — what to search for in Phase 4>
  Search terms: ["<term1>", "<term2>", "<term3>"]

HYPOTHESIS 2: <ProteinA / ProteinB>
  ...
```

Hard rules for Phase 3: - Do not repeat any PPI already surfaced by Phase 2 fingerprints as a known pathway node. - Do not include a hypothesis unless you can name *both* proteins specifically. - Every hypothesis must cite at least ONE Phase-2.5 graph signal or Phase-2 corpus connection in its `Source signal` line. Bare training knowledge is not a valid Source signal. - Do not include a hypothesis that introduces a protein absent from all Phase-2 / Phase-2.5 outputs UNLESS the Phase 4 search succeeds in finding corpus evidence for it.

Phase 4: Hypothesis-Driven Corpus Search

Convert each hypothesis into targeted corpus queries and run them. Cap at **5 queries total** across all hypothesis + cross-pathway searches below.

For each hypothesis (run at most 3 hypothesis queries):

```
search_corpus
  query="<ProteinA> <ProteinB> <mechanism_keyword from hypothesis> <biological_context>"
  top_k=5
```

Drop `<biological_context>` from the query if the hypothesis is a basic-biology PPI without a strong disease anchor — including a weak disease term often suppresses good biochemistry hits.

Co-dependency / cross-pathway query (always run, top_k=6):

For `mode = disease_anchored`:

```
search_corpus
  query="<biological_context> synthetic lethality co-dependency pathway compensation"
  top_k=6
```

For `mode = basic_biology`:

```
search_corpus
  query="<pathway_hint> functional redundancy compensation parallel pathway"
  top_k=6
```

Adjacent-context transfer query (run if pathway_hint is known, top_k=5):

```
search_corpus
  query="<pathway_hint OR anchor_node> <adjacent_context> mechanism interaction"
```

Use the closest well-characterised context neighbour you identified in Phase 3: - Disease mode: another tumour type or indication driven by the same pathway lesion as the one in context. - Basic-biology mode: a different tissue / cell type / developmental stage where the same pathway has been better characterised (e.g. UPR in plasma cells if the context is UPR in pancreatic β-cells).

Deduplicate all Phase 4 results against Phase 2 DOIs. For each **new** paper with score ≥ 0.20, call `get_fingerprint` and merge into the working evidence set.

Map each new paper back to the hypothesis that generated its search query. A hypothesis that produces ≥ 1 paper with score ≥ 0.30 is **corpus-supported**; one with only weak hits (0.20–0.29) is **weakly supported**; one with nothing found is **corpus-absent** (still included in the report with that label).

Phase 4.5: Term-Expansion Search

After completing Phase 2 and Phase 4, extract corpus-specific terms that did not appear in any previous query string. Same logic as pathway-expert Phase 3.5:

SOURCE FIELD	WHAT TO EXTRACT
`pathway_context.target_nodes[].protein`	Gene symbols of newly surfaced proteins
`pathway_context.upstream_regulators`	Regulator names not in original query
`pathway_context.downstream_effectors`	Effector names not in original query

Skip Phase 4.5 only if Phase 2 + Phase 4 combined returned ≥ 14 unique papers with scores ≥ 0.35. Otherwise always run it.

Run at most **1 follow-up search** (not 2 as in pathway-expert — Phase 4 has already done the creative expansion):

```
search_corpus
  query="<new_gene_symbol_1> [<new_gene_symbol_2>] <biological_context> mechanism dependency"
  study_category="pathway_biology"
  top_k=5
```

In `basic_biology` mode replace `<biological_context>` with the pathway / process keyword.

Deduplicate; call `get_fingerprint` for new papers with score ≥ 0.25.

State in CORPUS COVERAGE how many papers this added.

Phase 4.6: Corpus-Wide PDB Lookup

After completing Phases 2–4.5, call `find_pdb_structures` **once** with every candidate target protein across all phases:

```
find_pdb_structures
  proteins=["<ProteinA>", "<ProteinB>", ...]
```

Build the protein list in this order: 1. **Proteins from Phase 2 fingerprints** (`target_nodes`, `upstream_regulators`, `downstream_effectors`) — list these first 2. **Hypothesis PPI partners** from Phase 3 that are new (not already in list above) 3. **Any other PPI candidates** you intend to include in the landscape

Typically 4–10 gene symbols total.

This scans the **entire** fingerprint corpus, including papers not retrieved in Phases 2–4, and returns PDB accessions from two sources: `suggested_pdb_structures` in pathway fingerprints and `pdb_accessions` from any paper mentioning the protein.

When multiple structures are returned for a protein, select the best one using these criteria **in priority order**:

1. **Complex present** — `protein_chain_count ≥ 2` with both target protein AND binding partner in the `entities[].description` fields
2. **Method quality** — prefer `X-RAY DIFFRACTION` > `ELECTRON MICROSCOPY` > `NMR`
3. **Resolution** — for X-ray, prefer < 2.5 Å; for cryo-EM, prefer < 4.0 Å
4. **Human organism** — prefer `entities[].organism_taxid = 9606`

If `metadata_available` is `false`, use PDB IDs as-is and note it in the report.

- **Add any newly discovered PDB IDs to the relevant node before writing the report.** This includes results for Phase 2 proteins as well as hypothesis proteins.
- **Use the selected ID verbatim** in `Suggested PDB ID(s)` fields and in the `### PIPELINE HANDOFF` `pdb_id` line.
- If `total_found` is 0, call `search_rcsb_pdb` with the 2–3 primary target proteins (Phase 2 proteins first) as a fallback. Apply the same selection criteria. If a suitable structure is found, use its PDB ID in the handoff. If no suitable structure found from either source, write `NOT_FOUND`.

Membrane receptors: which site a designed binder can actually reach

A binder is a folded protein in solution. It can only engage surface that is solvent-exposed on ONE face of the membrane. This rules out large parts of a GPCR, and the constraint is chemical, not a limitation of the pipeline — so choose the site accordingly rather than proposing one that will be refused. WHICH face is a judgement about where the therapeutic effect lives; only the lipid-buried surface itself is ruled out on both.

Reachable, and clinically validated — prefer these where the effect lives here, which for a cell-surface receptor it usually does:

- **Class B ECDs.** These use a two-domain mechanism: the peptide hormone's C-terminus binds a genuine extracellular domain, its N-terminus then inserts into the helical bundle. The ECD contact is a real protein-protein interface and is fully extracellular. Approved antibodies and trial agents exist against class B ECDs, so the modality is validated — identify the specific receptor from the corpus, not from this list.
- **Class C Venus flytrap** (mGluR, CaSR, GABA-B) — the orthosteric site is entirely extracellular and large.
- **Class F CRD** (Frizzled, SMO).
- **N-terminus and extracellular loops of PEPTIDE-binding class A receptors** (chemokine receptors, angiotensin, opioid peptide receptors). The ligand has a large extracellular footprint, and antibodies against these surfaces work (mogamulizumab/CCR4, leronlimab/CCR5).
- **Receptor / accessory-protein interfaces**, where the interface itself sits outside the membrane.

Reachable, but only with a delivery route you must name:

- **Cytoplasmic domains and intracellular faces.** Harder to reach, not impossible, and NOT refused by this pipeline — it reads the membrane face off the residues you propose and trims to that face, so a coherently cytoplasmic epitope is designed against normally. Many mechanisms only exist there: a receptor's effector-recruitment or kinase surface, and any protein in an intracellular-organelle membrane, where "extracellular" names no real surface at all. Propose one when that is where the effect is — and say in the same breath what gets the binder into the cytosol (fusion to a delivery module, intracellular expression, a degrader/glue format). A target needing intracellular delivery cannot carry `tractability: Excellent` with the route unstated; the delivery burden belongs in `go_rationale` where a reader can weigh it. Understating it is the error — choosing the target is not.

Not reachable — do not propose these:

- **The orthosteric pocket of a receptor whose ligand is a lipid or a lipophilic small molecule** (cannabinoid, S1P, LPA, prostaglandin, free fatty acid). These pockets are inside the helical bundle and there is strong structural evidence that the ligand enters LATERALLY, from within the bilayer, through gaps between transmembrane helices — S1P1 is capped by its own N-terminal helix, and CB1 has lipid-facing portals. Nothing arriving from solution can occupy that site.
- **Deep aminergic pockets** (adrenergic, muscarinic, dopaminergic). Reached from the extracellular side, but far too enclosed for a 70-86 residue mini-protein; these are small-molecule sites.
- **Any transmembrane surface at all.** In an isolated structure a TM helix looks like an attractive hydrophobic patch; in a cell it is buried in lipid.

A practical test before proposing a membrane target: *is this site solvent-exposed on one face, or is it inside the bundle?* If it is inside the bundle, no designed mini-protein reaches it from either side. "Would an antibody work here?" is the sharper version of that test for the OUTER face only — an antibody's own inability to reach the cytosol says nothing about a site's geometry, and a cytoplasmic domain that fails the antibody test can still be a real target for a delivered binder.

The pipeline enforces this deterministically further down — UniProt topology is mapped into author numbering and the trim drops the transmembrane span and the opposite face, and a hotspot annotated transmembrane fails the run outright. So a receptor whose only druggable

site is intramembrane is not a target for this pipeline: say so and pick another node rather than spending stages on it.

When the best target has no experimental structure, an AlphaFold model is a legal answer. Emit `pdb_id: AF-<UniProt accession>` (e.g. the accession you resolved for that protein) and the pipeline fetches the predicted model. Two conditions, both hard:

1. **Only with `design_intent: inhibit_active_site`.** An AlphaFold model is a single chain, so there is no partner in it to disrupt or stabilise. A run that pairs `AF-` with `disrupt` or `stabilize` is refused before any spend.
2. **Only when no experimental co-complex exists.** An experimental structure of the real complex always wins; check with `search_rcsb_pdb` first and say in the report that you looked.

This matters most for the case that used to dead-end: a well-evidenced target with no PDB entry. Recommending a *downstream* complex instead is a real option, but it answers a different question than the user asked — if you do that, say so in one clause in PRIMARY RECOMMENDATION and keep the original target in the landscape at its own tier.

Phase 5: Inferred PPI Reasoning

For every candidate node, run the same four-condition reasoning check as pathway-expert Phase 4a (interaction necessity, therapeutic mechanism, consequence of disruption or stabilization, interaction knowability).

The mechanism-of-action step (covers both therapeutic intent AND probe experiments — the same `design_intent` field serves both): - `disrupt` — breaking the interaction attenuates the pathway-relevant output. In disease mode this is "loss of oncogenic signalling" or "loss of pathological signal relay"; in basic-biology mode it's "loss of the predicted regulatory step" — useful as a probe to demonstrate that the predicted regulatory step is in fact load-bearing. - `stabilize` — a normally protective or autoinhibitory interaction is weakened (by mutation, expression loss, or experimental challenge) and reinforcing it restores the unperturbed state. Examples: restoring an autoinhibitory complex, re-engaging a sequestered OFF-state, protecting a tumour-suppressor complex from degradation, or clamping an autoinhibited kinase in its OFF conformation as a probe of pathway function.

Record one `design_intent` per node. Default to `disrupt` if ambiguous.

For **hypothesis-tier candidates**: replace the four-condition check with: 1. Name the two proteins specifically. 2. State the corpus support level (corpus-supported / weakly supported / corpus-absent). 3. Give the mechanism rationale in 1–2 sentences from Phase 3. 4. Identify any indirect corpus evidence (e.g. "Phase 4 search found a paper on ProteinA in an adjacent indication suggesting the interaction exists").

Tier assignment for Phase 5 — use the **first tier from this list that applies**:

TIER	CONDITION
`[VALIDATED]`	Prior therapeutic targeting documented in corpus
`[BIOLOGICALLY_JUSTIFIED]`	Genetic dependency confirmed; interaction necessity corpus-supported
`[PATHWAY_INFERRED]`	No genetic dependency; named interaction required per corpus pathway logic
`[SYNTHETIC_LETHALITY]`	Corpus supports a co-dependency; PPI exploitable given a co-occurring alteration present in the disease
`[CROSS_INDICATION_TRANSFER]`	Strong corpus evidence in adjacent indication; transferability argued with explicit reasoning
`[HYPOTHESIS]`	Generated in Phase 3; corpus support is weak or absent; included for creative value

A candidate may carry only one tier — use the highest supported. HYPOTHESIS is the lowest tier and must be used when no stronger corpus evidence was found.

Phase 6: Synthesise and Output Report

WILDCARD HYPOTHESIS GENERATION block

Write the Phase 3 block **above** the main report, clearly labeled as training knowledge. This is informational — it shows the creative reasoning. It is **not** part of the parseable pipeline output.

PATHWAY BIOLOGY REPORT

Produce the full report using **only information retrieved from the corpus** (plus the clearly-labeled hypothesis block above). Do not hallucinate pathway details. Omit lines that cannot be filled — do not write placeholder text.

Citation policy: Every cited claim in the PATHWAY BIOLOGY REPORT must come from a retrieved fingerprint. The WILDCARD HYPOTHESIS GENERATION block above is the only place where training knowledge is acceptable without a citation. - Citation format: `DOI + source_span` (e.g. `10.7554/eLife.77415, Page 3 Para 2`). - No author names, journal names, or years — ever. Write the DOI only. - If you know a biological fact from training knowledge but have no corpus DOI for it, state the fact without any citation — do not invent a reference. - A fact with no citation is acceptable. A fact with a fabricated citation is not.

Token budget: 3,500–5,000 words for the combined output (hypothesis block + PATHWAY BIOLOGY REPORT).

Report Format

All sections identical to pathway-expert **except**:

1. The `#### [<TIER>]` header in TARGET OPPORTUNITY LANDSCAPE uses the expanded tier set (including SYNTHETIC_LETHALITY, CROSS_INDICATION_TRANSFER, HYPOTHESIS).
2. Every candidate in TARGET OPPORTUNITY LANDSCAPE has these additional bullets: - `**Novelty rationale**` — why this target/PPI is non-obvious (1 sentence) - `**Novelty signal**` — `novelty_score=<value>, classification=<class>` - `**Hypothesis**` — the mechanistic claim being tested (1 sentence) - `**Predicted consequence**` — biological outcome if hypothesis is true and the interaction is disrupted (1 sentence, named readout) - `**Falsifying readout**` — assay + threshold that decides (1 sentence)

3. HYPOTHESIS-tier entries have an additional bullet: `- **Corpus support**: <what was found, or "Nothing found in corpus">`
4. The CORPUS COVERAGE section has additional lines: - `- Wildcard hypotheses generated: <N> total; <N> corpus-supported; <N> weakly supported; <N> corpus-absent; <N> graph/DepMap-derived (Step 3a)` - `- Hub residuals table: <N candidates>; counts per class (SATURATED / CONNECTED-NOVEL / PERIPHERY-NOVEL / DEPMAP-COUPLED / UNCHARTED / MID-NOVEL)` - `- DepMap signals used: <N> get_genetic_codependency calls (Call 4 multi-hub + Call 7 sweep); <N> find_cocorrelated_genes calls (Call 5 anchor + Call 7 per candidate); <N> cluster_for_protein calls; <N> get_interactions_for calls (Call 7 candidate-edge sweep)` - `- Call 7 candidate-edge sweep ran on: <candidate_1>, <candidate_2> — strongest neighbourhood finding: <partner (r=<value>); "none above r=0.4" if no hit>`

```

## PATHWAY BIOLOGY REPORT

### BIOLOGICAL CONTEXT

- Mode:
- Disease / indication:
- Pathway(s) / process(es):
- Primary mechanism of interest:
- Frequency / prevalence:

### PATHWAY MAP

- Upstream regulators:
- Core cascade:
- Key effectors / downstream nodes:

### CANDIDATE NODE ASSESSMENT

For each candidate target node — max 5 nodes total (wildcard allows one extra), 6–7 bullet lines per node:

- Pathway position:
- State / dysregulation:
- Genetic dependency:
- DepMap codep vs. top-3 hubs: with \ (n=\); or "uncoupled (max_r=\)"; or "not run">
- DepMap neighborhood (Call 7, top candidates only): <" (r=, in_corpus_graph=, in_hub_top20=); (...); (...)"; or omit if Call 7 not run for this candidate>
- Prior therapeutic / probe targeting:
- Suggested PDB structures:
- Inferred PPI opportunity:
- Novelty note:

### TARGET OPPORTUNITY LANDSCAPE

Present 3–4 PPI candidates (wildcard allows one extra vs. pathway-expert). List highest tier first. Within the same tier, rank by: corpus support strength, then PDB availability.

For each candidate:

[]

- **Evidence basis**: <1–2 sentences citing specific corpus evidence, or Phase 3 reasoning for HYPOTHESIS>
- **What makes it attractive**:
- **Key uncertainty**:
- **Novelty rationale**:
- **Novelty signal**: novelty_score=, classification=, DepMap max_r vs hubs= with , neighbourhood top=) or "—" if Call 7 not run>
- **Hypothesis**:
- **Predicted consequence**: transcript reduction >= 50% at 24h in cells">
- **Falsifying readout**: at 24h post-treatment; >=50% reduction = consistent with hypothesis; <=20% = falsifies">
- **Corpus support**:
- **Suggested PDB ID(s)**:

Tier definitions: - [VALIDATED] — Prior therapeutic targeting documented in corpus - [BIOLOGICALLY_JUSTIFIED] — Genetic dependency confirmed + interaction necessity corpus-supported - [PATHWAY_INFERRED] — No genetic dependency; named interaction required per corpus pathway logic - [SYNTHETIC_LETHALITY] — Co-dependency supported by corpus; requires co-occurring alteration - [CROSS_INDICATION_TRANSFER]— Strong corpus evidence in adjacent indication; transferability argued - [HYPOTHESIS] — Phase 3 origin; weak or no corpus support; speculative

### PRIMARY RECOMMENDATION

State which candidate is recommended for the downstream pipeline. Wildcard mode INVERTS pathway-expert's preference: novelty is the value-add of this skill, so high-prior-art targets are deliberately deprioritised. Apply this rule **in order** — first match wins:

1. **Novelty-first rule.** If a `HYPOTHESIS`, `CROSS_INDICATION_TRANSFER`, or `SYNTHETIC_LETHALITY` candidate satisfies **all three** of: (a) a PDB ID exists in the corpus or via `find_pdb_structures` / `search_rcsb_pdb`, (b) the structural interface is interpretable (the partner protein or a
```

homologous interface is present in the PDB entry), (c) at least one corpus fingerprint mentions the candidate (or a paralog) in a disease context, recommend that candidate. This is the wildcard mandate.

2. **Fallback.** If no candidate satisfies rule 1, recommend the highest-tier remaining candidate (VALIDATED > BIOLOGICALLY_JUSTIFIED > PATHWAY_INFERRED) and state explicitly that the wildcard run found no tractable novel candidate.
3. **Rationale must cite `novelty_score` AND the strongest DepMap neighbourhood signal (when Call 7 ran on the pick).** State both in one sentence — e.g. "novelty_score=0.72 — PERIPHERY-NOVEL, mechanistically connected to via (3-hop path, min mentions = 4); DepMap-coupled to at r=0.58 (n=1208) — an interaction the corpus has not yet recognised but DepMap validates functionally." When the Call-7 sweep produced no partner with r ≥ 0.4, state that explicitly rather than omitting the line.

Tie-break under rule 1: higher `novelty_score` wins.

Anti-pattern guard. A high-prior-art VALIDATED candidate with `novelty_score < 0.3` should NOT be recommended by this skill unless rule 1 is unsatisfiable — those targets belong to pathway-expert. If the wildcard run keeps picking the same VALIDATED targets pathway-expert would pick, the skill has failed at its job.

- **Target complex**:
- **Evidence tier**:
- **Novelty**: novelty_score= ()
- **Suggested PDB ID(s)**:
- **Proposed next step**: Run complex-structure-analysis on PDB (only if PDB confirmed from corpus; otherwise await user input)

REDUNDANCY AND RESISTANCE RISKS

-

CORPUS COVERAGE

- Papers analysed: from
- Fallback used:
- Expansion round:
- Wildcard hypotheses generated: total; corpus-supported; weakly supported; corpus-absent
- Critical gaps:
- Keywords to add (if gaps are critical): `python scripts/fetch_papers.py --keywords "<keyword>"`

PATHWAY SOURCES

#	TITLE (TRUNCATED TO 60 CHARS)	DOI	KEY NODE
1	...	...	...

PIPELINE HANDOFF

- pdb_id:
- target_complex:
- design_intent:
- structure_query:
- choices_json:

IMPORTANT: Write the `### PIPELINE HANDOFF` section as plain bullet lines exactly as shown above. Do NOT wrap it in a code fence (no ``` before or after). Do NOT omit the `-` prefix. The programmatic orchestrator parses these lines with a regex — any deviation breaks the pipeline.

Rules for `### PIPELINE HANDOFF`: - `pdb_id` must come from `paper_metadata.pdb_accessions`, `pathway_context.target_nodes[].suggested_pdb_structures`, **or the `find_pdb_structures` tool result from Phase 4.6**. Write `NOT_FOUND` if nothing found — never guess. - `structure_query` is the verbatim query string passed to complex-structure-analysis; make it self-contained. - `choices_json` lists every candidate from TARGET OPPORTUNITY LANDSCAPE in order. Each element: - `tier`: one of `"VALIDATED"`, `"BIOLOGICALLY_JUSTIFIED"`, `"PATHWAY_INFERRED"`, `"SYNTHETIC_LETHALITY"`, `"CROSS_INDICATION_TRANSFER"`, or `"HYPOTHESIS"` - `complex`: protein pair name exactly as in the `####` header - `pdb_ids`: array of PDB accession strings from corpus only — empty array `[]` if none - `evidence_basis`: one sentence summary (no newlines, no quotes inside) - `key_uncertainty`: one sentence summary (no newlines, no quotes inside) - `design_intent`: `"disrupt"` or `"stabilize"` from Phase 5 reasoning for this candidate - `novelty_score`: float in `[0.0, 1.0]` from `novelty_signal` for the candidate's primary protein - `classification`: one of `"SATURATED"`, `"CONNECTED-NOVEL"`, `"PERIPHERY-NOVEL"`, `"DEPMAP-COUPLED"`, `"UNCHARTED"`, `"MID-NOVEL"` - `depmap_r_to_anchor`: float (Pearson r vs the Phase-2.5 anchor / primary hub) or `null` if not applicable / not computed — kept for backward compatibility with existing consumers; mirror `depmap_max_r_to_hubs` here if no single anchor is meaningful - `depmap_max_r_to_hubs`: object `{r: float, hub: str, n_cell_lines: int}` or `null` — best Pearson r from the Call-4 top-3-hub sweep, with the hub that produced it - `depmap_neighborhood`: array of up to 3 objects `{partner: str, r: float, n_cell_lines: int, in_corpus_graph: bool, in_hub_top20: bool}` from Call 7 — only populated for the top-2 candidates that received the sweep; empty array `[]` otherwise - `predicted_consequence`: one sentence — what disruption should produce biologically; name the readout - `falsifying_readout`: one sentence — the assay + threshold that falsifies the hypothesis

`predicted_consequence` and `falsifying_readout` are REQUIRED for wildcard mode (picking a non-VALIDATED candidate without articulating the testable claim defeats the skill's purpose). They are the JSON-extracted forms of the `Hypothesis` / `Predicted consequence` / `Falsifying readout` bullets in the TARGET OPPORTUNITY LANDSCAPE block.

Example (must be on ONE line): `- choices_json: [{"tier":"PERIPHERY_NOVEL","complex":"GENE_A / GENE_B","pdb_ids":[],"evidence_basis":"Training knowledge plus Phase-4 hit: one sentence on why this pair is plausible and what the corpus does or does not have.","key_uncertainty":"One sentence naming the untested`

`step.","design_intent":"stabilize","novelty_score":0.71,"classification":"PERIPHERY-NOVEL","depmap_r_to_anchor":0.33,"depmap_max_r_to_hubs":{"r":0.41,"hub":"GENE_B","n_cell_lines":1208},"depmap_neighborhood":[{"partner":"GENE_B","r":0.41,"n_cell_lines":1208,"in_corpus_graph":true,"in_hub_top20":true},{"partner":"GENE_C","r":0.36,"n_cell_lines":1208,"in_corpus_graph":true,"in_hub_top20":true},{"partner":"GENE_D","r":0.32,"n_cell_lines":1208,"in_corpus_graph":false,"in_hub_top20":false}],"predicted_consequence":"One sentence with a quantitative molecular readout.","falsifying_readout":"One assay plus the threshold that decides; state what falsifies."}]`

Handoff Contract

Identical to pathway-expert: - → **complex-structure-analysis**: use `Suggested PDB ID(s)` and `Target complex` from PRIMARY RECOMMENDATION - → **molecular-biology-expert**: use `Target complex` as the protein pair to query - → **orchestrator**: use the full report for Stage 0 summary; extract complex + PDB from PRIMARY RECOMMENDATION

The `TARGET OPPORTUNITY LANDSCAPE` is for human review — the orchestrator and downstream skills consume only the `PRIMARY RECOMMENDATION` block.

Common Pitfalls

- **Training knowledge ≠ corpus citation.** Every factual claim in the report body (outside the clearly-labeled WILDCARD HYPOTHESIS GENERATION block) must cite a DOI and source_span from a retrieved fingerprint. The hypothesis block is the only place where training knowledge is acceptable without citation.
- **Never guess PDB accession codes.** Same rule as pathway-expert — only report PDB IDs verbatim from fingerprint fields or `find_pdb_structures` tool result.
- **HYPOTHESIS tier is not a failure.** It is a feature — the value of wildcard mode is surfacing targets that the corpus does not yet validate but that have a reasoned mechanistic basis. Always include them.
- **Don't inflate tiers.** Weak indirect corpus support (one paper tangentially mentioning a protein) is NOT enough for CROSS_INDICATION_TRANSFER or SYNTHETIC_LETHALITY. Those tiers require the corpus to explicitly describe the mechanism in a related context. Genuine ambiguity defaults to HYPOTHESIS.
- **Primary recommendation may be a standard tier.** If Phase 2 returns strong VALIDATED or BIOLOGICALLY_JUSTIFIED evidence, recommend that — novelty for its own sake is not the goal. The wildcard hypotheses augment the landscape; they do not replace well-supported candidates.
- **[PATHWAY INFERRED] guardrail from pathway-expert still applies.** Name a specific binding partner supported by the corpus — do not assign this tier to vague "must interact with something" statements.
- **Do not run more than 5 Phase 4 queries total.** If Phase 3 generates 5 hypotheses, pick the 3 most specific for individual hypothesis queries, then run the 2 standard cross-pathway/adjacent-indication queries. Do not scale queries linearly with hypotheses.

Supplemental Information 2 - Full run report for prompt: Design immune checkpoint inhibitors.

SUPPLEMENTARY INFORMATION · STAGE REPORTS

Stage reports of one end-to-end run

Project `immune_check` · workflow `ppi`

> **Request, verbatim:** Design immune checkpoint inhibitors.

Each pipeline stage writes one markdown report. The pages that follow reproduce those files in full, in stage order, as they were written to disk during the run; only typography has been added. Every report ends with a machine-readable `PIPELINE HANDOFF` block, which is what the next stage parses. Stages 0, 1, 2 and 28 are written by a language model; the others are written by code from measured values.

Stages

#	STAGE	KIND	PRODUCED BY
0	**Pathway**	LLM	pathway-expert `gemini-3.8-flash`, $0.21
1	**Literature**	LLM	molecular-biology-expert `gemini-3.8-flash`, $0.12
2	**Structure**	LLM	complex-structure-analysis `gemini-3.8-flash`, $0.07
20	**Target intel (bridged)**	code	composed in code from stages 0 to 2; no LLM call
22	**Trim**	code	structure_trim.py
23	**Binder spec**	code	foundry_spec.py
24	**Pilot**	code	foundry_runner.py (RFD3, solubleMPNN, RF3)
25	**Calibration gate**	code	campaign_calibration.py
26	**Production**	code	foundry_runner.py (RFD3, solubleMPNN, RF3)
27	**Scoring**	code	binder_metrics.py, binder_ranking.py
28	**Summary**	LLM	design-analyst `gemini-3.8-flash`, $0.02

Stage 21 (interface) is a byte-identical copy of stage 2, written by the bridge so the binder track can start from it; it is not repeated here.

0 Pathway

LLM stage pathway-expert · gemini-3.8-flash · $0.21 · `00_pathway.md`

PATHWAY BIOLOGY REPORT

DISEASE CONTEXT

- Disease / indication: Cancer Immunotherapy (Solid Tumors, Metastatic Melanoma, Non-Small Cell Lung Cancer)
- Pathway(s) implicated: PD-1/PD-L1 immune checkpoint, CTLA-4/CD80/CD86 immune checkpoint, IFN-γ signaling, T cell exhaustion cascade
- Primary disease mechanism: Tumor-infiltrating lymphocytes chronically exposed to tumor antigens upregulate inhibitory checkpoint receptors (PD-1, CTLA-4), which engage ligands (PD-L1, CD80/CD86) in the tumor microenvironment to trigger SHP-2/SHP-1 phosphatase recruitment, dephosphorylate TCR/CD28 signaling complexes, and enforce peripheral T cell exhaustion and adaptive immune resistance (10.1126/science.aar4060, Section: PD-1 as a non-redundant immune checkpoint, Para 1; 10.1016/j.cell.2018.09.035, Section: Targeting a Tumor-Induced Immune Escape Mechanism, Para 1).
- Frequency of pathway dysregulation: PD-L1 upregulation is observed across multiple solid tumors via adaptive IFN-γ induction or constitutive 9p24.1 (PDJ amplicon) gene amplification in Hodgkin's lymphoma (10.1126/science.aar4060, Section: Clinical effects of PD-1/PD-L1 blockade therapy, Para 3); loss-of-function IFN-γ pathway variants (JAK1/2, IFNGR1) occur in 14.7% of resistant NSCLC cohorts (10.1016/j.cell.2019.07.019, Context).

PATHWAY MAP

- Upstream regulators: Chronic TCR stimulation (induces PD-1 and NFAT/TOX activation), tumor-derived/TME IFN-γ (drives transcriptional upregulation of PD-L1/B7-H1 via JAK1/2-STAT1), and CD28 co-stimulation (antagonized competitively by CTLA-4).
- Core cascade: Receptor-ligand engagement (PD-1/PD-L1 or CTLA-4/CD80) at the immunological synapse recruits SHP-2/SHP-1 tyrosine phosphatases via intracellular immunoreceptor tyrosine-based switch motifs (ITSM), directly dephosphorylating CD28 and TCR-associated CD3ζ chains to extinguish downstream PI3K/AKT and MAPK activation.
- Key effectors / transcription factors: TOX (central exhaustion-enforcing nuclear factor driven by calcineurin/NFAT), PRDM1 (Blimp-1, co-regulates inhibitory receptor expression), and TCF-1 (repressed in terminally exhausted T cells).

DYSREGULATED NODES ASSESSMENT

PDCD1 (PD-1 / CD279)

- Pathway position: Effector / upstream co-inhibitory cell-surface receptor on tumor-infiltrating T cells.
- Dysregulation: Sustained cell-surface upregulation and retention on exhausted tumor-infiltrating lymphocytes driven by chronic antigen exposure, core fucosylation via FUT8, and defective FBXO38-mediated proteasomal degradation (10.1038/s41422-020-0343-4, Page 2 Para 2; 10.1126/science.aar4060, Section: PD-1 as a non-redundant immune checkpoint, Para 1).
- Genetic dependency: Core fucosylation via FUT8 is required for PD-1 surface stability; ablation reduces surface PD-1 and elevates T cell killing (10.1038/s41422-020-0343-4, Page 2 Para 2); knockout of negative regulators restores T cell activation and tumor clearance (10.1016/cell.2018.10.024, Key Findings).
- Prior therapeutic strategies: Clinically approved monoclonal antibodies (nivolumab, pembrolizumab), macrocyclic peptide inhibitors (PD-i3), and engineered small proteins.
- Suggested PDB structures: 4Z18 (Homo sapiens), 2M2D (Homo sapiens), 3BIK (Mus musculus — ortholog).
- Inferred PPI opportunity: Physical interaction with CD274 (PD-L1) is obligate for ITSM phosphorylation and SHP-2 recruitment; competitive disruption of the PD-1/PD-L1 interface directly prevents phosphatase engagement and restores cytolytic T cell function.

CD274 (PD-L1 / B7-H1)

- Pathway position: Immunosuppressive cell-surface ligand on tumor cells, antigen-presenting cells, and tumor-derived exosomes.
- Dysregulation: Dramatically overexpressed on tumor membranes in response to microenvironmental IFN-γ or oncogenic signaling, stabilized against lysosomal degradation by CMTM6 association (10.1038/s41422-020-0343-4, Page 3 Para 2; 10.1016/j.cell.2018.09.035, Section: Targeting a Tumor-Induced Immune Escape Mechanism, Para 1).
- Genetic dependency: Depletion of exosomal PD-L1 secretion via Rab27a or nSMase2 ablation blocks tumor growth and induces systemic anti-tumor immune memory in syngeneic models (10.1016/j.cell.2019.02.016, Key Findings).

- Prior therapeutic strategies: Clinically approved monoclonal antibodies (atezolizumab, durvalumab, avelumab), high-affinity macrocyclic peptides (pAC65, IC50 = 1.80 nM; p104, Kd = 380 nM), and small-molecule dimerizers (BMS-1166, P39).
- Suggested PDB structures: 4Z18 (Homo sapiens), 8ALX (Homo sapiens), 7OUN (Homo sapiens), 7XYQ (Homo sapiens), 3BIK (Mus musculus — ortholog).
- Inferred PPI opportunity: Soluble or surface-displayed binders occluding the front β-sheet face of the PD-L1 IgV domain prevent engagement of both PD-1 (Kd = 8.2 μM) and CD80 (Kd = 18.8 μM), relieving dual immunosuppressive checkpoints in the tumor bed.

CTLA4 (CTLA-4 / CD152)

- Pathway position: Upstream negative regulatory cell-surface receptor primarily operating during initial T cell priming in secondary lymphoid tissues and on regulatory T (Treg) cells.
- Dysregulation: Translocates to the cell surface upon T cell activation where it outcompetes CD28 for B7 co-stimulatory ligands, dampening initial T cell activation cascades (10.1126/science.aar4060, Section: CTLA-4 as a non-redundant immune checkpoint and clinical activity, Para 1).
- Genetic dependency: CTLA-4 deletion in mice results in fatal lymphoproliferative infiltration, validating its non-redundant gatekeeper role in controlling immune homeostasis (10.1126/science.aar4060, Section: CTLA-4 as a non-redundant immune checkpoint and clinical activity, Para 1).
- Prior therapeutic strategies: Clinically approved monoclonal antibodies (ipilimumab, tremelimumab).
- Suggested PDB structures: 1I8L (Homo sapiens), 1YJD (Homo sapiens), 3OSK (Homo sapiens), 1NPU (Mus musculus — ortholog).
- Inferred PPI opportunity: Physical binding to CD80 (B7-1) with Kd = 120 nM via a rigid-body binding mechanism; steric inhibition of this interaction frees CD80 to bind CD28, restoring co-stimulatory signaling and priming naive T cells.

PTPN2 (T-cell protein tyrosine phosphatase / TC-PTP)

- Pathway position: Intracellular non-receptor protein tyrosine phosphatase acting as an upstream negative regulator of IFN-γ signaling and antigen presentation.
- Dysregulation: Overexpression in tumor cells attenuates IFN-γ-mediated STAT1 phosphorylation and dampens MHC-I surface presentation, driving primary resistance to immune checkpoint blockade (10.1038/nature23270, Section: Loss of, Para 1).
- Genetic dependency: In vivo CRISPR screening identified Ptpn2 loss as significantly sensitizing tumors to anti-PD-1 therapy, enhancing p-STAT1 and increasing MHC-I expression (10.1038/nature23270, Section: Loss of, Para 1, $P < 0.01$).
- Prior therapeutic strategies: Small-molecule non-competitive allosteric phosphatase inhibitors (10.1038/s41573-022-00618-w, Context).
- Inferred PPI opportunity: Insufficient evidence for direct PPI disruption; PTPN2 operates as an intracellular catalytic enzyme targeting phosphotyrosine residues on JAK1 and STAT1.

TARGET OPPORTUNITY LANDSCAPE

[VALIDATED] PDCD1 / CD274 (PD-1 / PD-L1)

- **Evidence basis**: Verified non-redundant clinical checkpoint whose blockade restores exhausted T-cell anti-tumor immunity with 40% objective response rate in solid tumors (10.1016/j.cell.2018.09.035, Section: The Normalization Cancer Immunotherapy Has Come of Age, Para 1); native human interface affinity measured by SPR at Kd = 8.2 μM (10.1074/jbc.M112.448126, Page 6 Para 2).
- **What makes it attractive**: The interaction interface resides entirely on the extracellular IgV domains (~120 residues each, optimal for binder design), presenting a solvent-accessible flat β-sheet epitope that can be directly occluded by designed mini-proteins or macrocyclic peptides to restore T cell receptor activity without requiring cell entry.
- **Key uncertainty**: Resistance emerging through tumor-intrinsic loss of antigen presentation machinery (B2M loss) or IFN-γ signaling pathway mutations (JAK1/2 loss), which bypass PD-1/PD-L1 blockade.
- **Suggested PDB ID(s)**: 4Z18 (Homo sapiens), 3BIK (Mus musculus — ortholog).

[VALIDATED] CTLA4 / CD80 (CTLA-4 / B7-1)

- **Evidence basis**: Landmark checkpoint target demonstrating synergistic survival enhancement (58% 3-year survival in combination vs 52% monotherapy; 10.1126/science.aar4060, Section: Combination CTLA-4 and PD-1 blockade therapy, Para 1); biophysically characterized rigid-body interface with Kd = 120 nM measured by ITC (10.1074/jbc.M110.182394, Page 9 Para 1).

- **What makes it attractive**: Extracellular IgV interaction domain (~125 residues) with established rigid-body geometry, allowing high-affinity competitive displacement to rescue CD28 co-stimulation during dendritic cell presentation.
- **Key uncertainty**: Systemic toxicities and expansion of immunosuppressive regulatory T cells upon CTLA-4 blockade due to disruption of the homeostatic CD80/CD86 clearance rheostat (10.1016/j.cell.2021.05.027, Context).
- **Suggested PDB ID(s)**: 1I8L (Homo sapiens), 1YJD (Homo sapiens), 1NPU (Mus musculus — ortholog).

[DIRECT INHIBITION] CD274 (PD-L1 binding cleft)

- **Evidence basis**: Characterized high-resolution binding pocket on the PD-L1 front β-sheet interface successfully targeted by macrocyclic peptides such as pAC65 (IC50 = 1.80 nM; 10.1186/s12943-023-01853-4, Page 2 Para 3) and p104 (Kd = 380 nM; 10.3390/molecules26164848, Key Findings).
- **What makes it attractive**: Direct occlusion of the PD-L1 binding surface by a single engineered binder simultaneously dissociates pre-formed PD-1/PD-L1 complexes and PD-L1/CD80 interactions at picomolar-to-nanomolar potencies, bypassing antibody production complexity.
- **Key uncertainty**: Non-antibody modalities face shorter systemic half-lives in vivo and require optimization of pharmacokinetic stability to match IgG exposure profiles.
- **Suggested PDB ID(s)**: 8ALX (Homo sapiens), 7OUN (Homo sapiens).

PRIMARY RECOMMENDATION

The PDCD1 / CD274 (PD-1 / PD-L1) complex is recommended as the primary target for binder design. It combines the highest level of clinical and genetic validation in oncology with a well-characterized, surface-exposed extracellular PPI interface solved at 2.45 Å resolution (PDB 4Z18) in the native human complex, where both interacting chains are compact IgV domains (~120 amino acids) ideally proportioned for computational binder generation.

- **Target complex**: PDCD1 / CD274
- **Evidence tier**: [VALIDATED]
- **Suggested PDB ID(s)**: 4Z18 (Homo sapiens)
- **Structure organism**: Homo sapiens
- **Proposed next step**: Run complex-structure-analysis on PDB 4Z18

REDUNDANCY AND RESISTANCE RISKS

- Compensatory checkpoint upregulation: Persistent chronic tumor antigen exposure triggers secondary inhibitory receptors including TIM-3, LAG-3, and TIGIT, co-regulated via PRDM1 and c-MAF transcription factor modules (10.1038/s41586-018-0206-z, Page 4 Para 1).
- Alternative ligand compensation: PD-L2 retains high binding affinity for PD-1 (Kd = 2.3 μM) and can sustain inhibitory signaling when CD274 (PD-L1) alone is targeted (10.1074/jbc.M112.448126, Page 6 Para 2).
- IFN-γ pathway loss: Acquired or intrinsic loss-of-function mutations in JAK1/2 or B2M prevent tumor antigen presentation and eliminate sensitivity to PD-1/PD-L1 pathway inhibition (10.1126/science.aar4060, Section: Mechanisms of response and resistance to single agent PD-1 therapy, Para 6).

CORPUS COVERAGE

- Papers analysed: 10 fingerprints from 37 search hits
- Fallback used: No — direct pathway_biology and targeted biochemistry queries returned comprehensive coverage
- Expansion round: Yes — expanded on CD274, CTLA4, CD80, and pAC65 macrocyclic inhibitor data, adding 4 structural and biophysical fingerprints
- Critical gaps: None for core PD-1/PD-L1 or CTLA-4 interfaces; high-resolution structures and SPR/ITC constants are well represented in the corpus.

PATHWAY SOURCES

#	TITLE (TRUNCATED TO 60 CHARS)	DOI	KEY NODE
1	Cancer immunotherapy using checkpoint blockade	10.1126/science.aar4060	PD-1 / CTLA-4
2	Immune checkpoint signaling and cancer immunotherapy	10.1038/s41422-020-0343-4	PD-1 / PD-L1
3	A Paradigm Shift in Cancer Immunotherapy: From Enhancement...	10.1016/j.cell.2018.09.035	PD-1 / B7-H1
4	Structure and interactions of the human programmed cell...	10.1074/jbc.M112.448126	PD-1 / PD-L1
5	Structural and biological characterization of pAC65, a macro...	10.1186/s12943-023-01853-4	PD-L1
6	Rigid-body ligand recognition drives cytotoxic T-lymphocyte...	10.1074/jbc.M110.182394	CTLA-4 / B7-1
7	In vivo CRISPR screening identifies Ptpn2 as a cancer...	10.1038/nature23270	PTPN2
8	Induction and transcriptional regulation of the co-inhibitor...	10.1038/s41586-018-0206-z	PRDM1 / MAF

#	TITLE (TRUNCATED TO 60 CHARS)	DOI	KEY NODE
9	TOX is a critical regulator of tumour-specific T cell...	10.1038/s41586-019-1324-y	TOX
10	Human and mouse PD-L1: similar molecular structure, but...	10.1016/j.isci.2020.101960	PD-L1

PIPELINE HANDOFF

- pdb_id: 4Z18
- structure_organism: Homo sapiens
- target_complex: PDCD1 / CD274
- design_intent: disrupt
- structure_query: Analyze PDB 4Z18 (Homo sapiens) at data/structures/4Z18.cif. Target complex: PDCD1 / CD274. Identify hotspot residues for binder design.
- choices_json: [{"tier":"VALIDATED","complex":"PDCD1 / CD274","pdb_ids":["4Z18"],"evidence_basis":"Clinically validated non-redundant immune checkpoint whose blockade reverses T-cell exhaustion, with native human interface affinity Kd = 8.2 uM measured by SPR.","key_uncertainty":"Primary and acquired resistance driven by tumor-intrinsic loss of antigen presentation (B2M) or IFN-gamma pathway signaling (JAK1/2).","design_intent":"disrupt"},{"tier":"VALIDATED","complex":"CTLA4 / CD80","pdb_ids":["1I8L","1YJD"],"evidence_basis":"Non-redundant immune checkpoint regulating initial T-cell activation, with rigid-body human complex affinity Kd = 120 nM measured by ITC.","key_uncertainty":"Dose-limiting immune-related adverse toxicities and proliferation of suppressive Treg populations upon systemic blockade.","design_intent":"disrupt"},{"tier":"DIRECT_INHIBITION","complex":"CD274 (active site)","pdb_ids":["8ALX"],"evidence_basis":"High-resolution crystallographic precedent demonstrating potent macrocyclic peptide occlusion of the PD-L1 front beta-sheet interface with IC50 = 1.8 nM.","key_uncertainty":"Short pharmacokinetic half-life of non-antibody peptide scaffolds requiring chemical or formulation stabilization in vivo.","design_intent":"inhibit_active_site"}]

MODEL PROVENANCE

- skill: `pathway-expert`
- written by: **gemini:gemini-3.8-flash** — the model the operator selected. LPT never substitutes a model on its own; a stage a safety classifier declines ends the run.

CITATION VERIFICATION

- Citations checked: 16
- Verified in corpus: 15
- **NOT IN CORPUS (1):** 10.1016/cell.2018.10.024

STRUCTURE SUBSTITUTION (deterministic, post-stage)

This report recommends **4Z18**. The pipeline designed against **4ZQK** instead.

- **Why:** 4Z18 does not contain both PDCD1 and CD274
- **Decided by:** `_select_designable_structure`, between the pathway and literature stages — structure choice has to be settled before the structure stage analyses anything, because its hotspots then refer to those coordinates.
- **Both entries contain the requested proteins.** The switch only fires on a measurable defect in the chosen one: partner absent, target chain a fusion construct, or materially more scaffolding at no better resolution.
- **To keep the original:** re-run with `--pdb 4Z18`.

The reasoning above is the pathway stage's own, on the evidence it had, and is left unedited.

1 Literature

LLM stage molecular-biology-expert · gemini-3.8-flash · $0.12 · `01_literature.md`

MOLECULAR BIOLOGY REPORT

COMPLEX OVERVIEW

- Target complex: PDCD1 / CD274
- Indication organism: Homo sapiens
- Cited structures:
- 4ZQK — Homo sapiens — human PD-1 / PD-L1 co-crystal complex (designated pipeline design structure)
- 4Z18 — Homo sapiens — human PD-1 / PD-L1 complex (pathway report reference structure)
- 8ALX — Homo sapiens — human PD-L1 in complex with macrocyclic peptide pAC65
- 5JDR — Homo sapiens — human PD-L1 in complex with single-domain nanobody KN035
- 5WT9 — Homo sapiens — human PD-1 in complex with nivolumab Fab
- 2M2D — Homo sapiens — human PD-1 solution NMR structure
- Disease context: oncology (Cancer Immunotherapy / Solid Tumors)
- Biological role: Engagement of cell-surface PDCD1 (PD-1) on tumor-infiltrating T lymphocytes by CD274 (PD-L1) recruits SHP-2 phosphatase to dephosphorylate TCR/CD28 signaling intermediates, extinguishing cytolytic activity and enforcing adaptive immune exhaustion.
- Drug target validation: Monoclonal antibodies and non-antibody competitive inhibitors displacing the PD-1/PD-L1 interface rescue T-cell activation and induce robust anti-tumor immunity across preclinical models and human clinical indications (10.1186/s12943-023-01853-4, Page 4, Para 3; 10.1038/celldisc.2017.4, Page 2, Para 2).
- Papers analysed: 7 full fingerprints from 26 total search hits

KNOWN INHIBITORS AND PRIOR ART

KN035 (Envafolimab)

- Modality: protein domain (single-domain VHH nanobody)
- Best affinity: Kd = 3.0 nM by bio-layer interferometry (IC50 = 5.25 nM by competitive ELISA)
- Source: 10.1038/celldisc.2017.4, Page 2, Para 2
- Key residues engaged: PD-L1 Ile54, Tyr56, Arg113
- Limitations: Strict species selectivity with zero cross-reactivity toward mouse PD-L1 due to an Arg113 to Cys113 sequence divergence.

pAC65

- Modality: cyclic peptide (macrocycle)
- Best affinity: IC50 = 1.80 nM for complex dissociation by HTRF (EC50 = 0.58 nM in cellular activation assays)
- Source: 10.1186/s12943-023-01853-4, Page 2, Para 3
- Key residues engaged: PD-L1 Tyr56, Gln66, Arg113, Met115, Ser117, Ala121, Tyr123, Arg125
- Limitations: Inactive against murine PD-L1; requires peptide cyclization and unnatural amino acid incorporation to ensure metabolic stability.

Nivolumab

- Modality: antibody (human IgG4 monoclonal antibody)
- Best affinity: Kd = 1.45 nM by SPR
- Source: 10.1038/ncomms14369, Page 4, Para 1
- Key residues engaged: PD-1 Leu25, Ser27, Pro28, Asp29, Arg30 (N-terminal loop L25-P34)
- Limitations: High molecular mass (~150 kDa), prolonged in vivo half-life limiting dosing flexibility, and complete dependence on receptor N-terminal loop integrity.

Terphenyl Compound 8j / 8g

- Modality: small molecule (rigidified terphenyl homodimerizer)
- Best affinity: Ki = 0.82 nM (IC50 < 1.0 nM) by HTRF

- Source: 10.1021/acs.jmedchem.1c00957, Page 5, Para 1
- Key residues engaged: PD-L1 Tyr56, Met115, Ala121, Asp122
- Limitations: Acts via ligand-induced target homodimerization rather than direct stoichiometric surface occlusion; inactive on murine PD-L1.

TARGET-SITE INSIGHTS FROM LITERATURE

Confirmed key residues (mutagenesis / structural data)

RESIDUE	PROTEIN	ROLE / EFFECT	METHOD	SOURCE (DOI, SPAN)
Tyr56	CD274 (PD-L1)	Y56A mutation reduces binding affinity by 4400-fold; principal aromatic anchor on CC'FG sheet	BLI mutagenesis	10.1038/celldisc.2017.4, Page 3, Para 2
Arg113	CD274 (PD-L1)	R113A mutation reduces binding affinity by 178-fold; critical basic peripheral anchor	BLI mutagenesis	10.1038/celldisc.2017.4, Page 3, Para 2
Tyr123	CD274 (PD-L1)	Conserved aromatic anchor; acts as wedge into PD-1 cleft; Y123A/G completely abolishes docking	MD / Structural	10.7554/eLife.22889, Page 9, Para 1
Met115	CD274 (PD-L1)	Central hydrophobic cleft lining; human/mouse divergence site driving species selectivity	X-ray / NMR	10.1016/j.isci.2020.101960, Page 7, Para 1
Arg125	CD274 (PD-L1)	Basic pocket residue providing ionic steering and polar contacts across multiple modalities	X-ray / Analysis	10.1021/acs.jmedchem.6c00674, Page 5, Para 1
Ala121 / Asp122	CD274 (PD-L1)	Conserved ADY motif engaging PD-1 flexible loops; coordinates small-molecule cores	MD / X-ray	10.7554/eLife.22889, Page 11, Para 1
Ile114	PDCD1 (PD-1)	I114A mutation completely abrogates binding to PD-L1 and PD-L2	Site-directed mutagenesis	10.1074/jbc.M112.448126, Page 6, Para 1
Ile106	PDCD1 (PD-1)	I106A mutation reduces PD-L1/L2 binding by 70–80%	Site-directed mutagenesis	10.1074/jbc.M112.448126, Page 6, Para 1
Asn66 / Tyr68	PDCD1 (PD-1)	Hydrophilic latch; acts as conformational switch opened by ligand ADY triggers	MD simulation	10.7554/eLife.22889, Page 11, Para 1
Leu25-Pro34	PDCD1 (PD-1)	N-terminal loop; truncation completely abolishes nivolumab recognition	X-ray / SPR	10.1038/ncomms14369, Page 4, Para 1

Membrane topology filter: CD274 is a single-pass type I transmembrane protein. All prioritized residues (Tyr56, Arg113, Met115, Ala121, Asp122, Tyr123, Arg125) are located strictly on the solvent-accessible extracellular face within the front CC'FG beta-sheet of the IgV domain. Transmembrane domain residues (such as the cholesterol-binding CRAC motifs F257/F259/R260/R262) have been deliberately excluded as physically inaccessible to a folded soluble protein binder.

Residues tolerant of mutation

- PDCD1 Asn49, Asn58, Asn74, Asn116: Individual Asn-to-Ala substitutions show wild-type binding affinity (Kd 1.45 to 3.48 nM), demonstrating that N-glycosylation sites across the IgV domain are completely dispensable for interface recognition (SPR / FACS; 10.1038/ncomms14369, Page 3, Para 2).

Pathway / DepMap context

- Co-functional cluster: PDCD1 belongs to co-functional cluster ID 98 (size 3, hub BTNL2, members BTNL2, IL17A, PDCD1). CD274 is unclustered due to absence of cell-autonomous fitness defects in in vitro monocultures.
- Genetic codependency: PDCD1 / CD274: r = -0.0158 (DepMap Chronos CRISPR across 1,208 cell lines). The near-zero correlation is expected: PD-1 is expressed on cytotoxic T lymphocytes, while PD-L1 is expressed on tumor cells and antigen-presenting cells. In standard in vitro cancer cell line screens lacking functional immune effector co-culture, cell-autonomous dependency does not co-vary.

FEASIBILITY ASSESSMENT

- Target tractability / informativeness: Excellent. The human PD-1/PD-L1 interface is structurally resolved at high resolution in PDB 4ZQK (and reference PDB 4Z18). Abundant biophysical literature establishes both the native equilibrium affinity (Kd = 8.2 uM; 10.1074/jbc.M112.448126, Page 6, Para 2) and high-affinity competitive disruption across modalities (nanobody KN035 Kd = 3.0 nM, 10.1038/celldisc.2017.4; macrocycle pAC65 IC50 = 1.80 nM, 10.1186/s12943-023-01853-4). Quantitative alanine scanning identifies steep energetic hotspots (Tyr56 > 4400-fold affinity loss, Arg113 > 178-fold loss), providing clear anchor points for computational design.

- Corpus confidence: High (7 full fingerprints analysed from 26 search hits).
- Design challenges:
- The CC'FG interface on CD274 is a flat, solvent-exposed beta-sheet lacking deep hydrophobic cavities, requiring precise shape complementarity and aromatic pairing.
- Sub-nanomolar affinity is necessary to outcompete native receptor re-engagement in the high-density immunological synapse despite the weak native micromolar affinity (Kd = 8.2 uM).
- Human/mouse sequence divergence at Arg113 and Met115 limits direct translation to standard syngeneic immunocompetent mouse models without humanized knock-in strains (10.1016/j.isci.2020.101960).
- Negative results:
- Durvalumab and small-molecule BMS-1166 fail to bind mouse PD-L1 due to steric hindrance from Ile115, yielding false negatives in non-humanized syngeneic tumor models (10.1016/j.isci.2020.101960, Page 7, Para 1).
- Single-point mutations Y123A and Y123G on PD-L1 fail to form productive encounter complexes in docking simulations, demonstrating that aromatic occupancy at this locus is an obligate requirement (10.7554/eLife.22889).
- Structural surveys confirm the absence of validated allosteric sites distal from the CC'FG face capable of disrupting PD-1 engagement (10.1021/acs.jmedchem.6c00674).
- Missing data gaps: Literature focuses primarily on monoclonal antibodies, macrocyclic peptides, and small molecules; direct structural precedents for de novo designed mini-protein scaffolds (<80 amino acids) targeting this exact epitope are limited.

DESIGN RECOMMENDATIONS

- Suggested modality: mini_protein — a rigid de novo mini-protein (~50–70 residues) provides sufficient surface area (~700–900 A^2) to completely occlude the flat CC'FG beta-sheet while avoiding the delivery barriers of intracellular targets and the manufacturing liabilities of full antibodies.
- Residues to prioritise: CD274 Tyr56, Arg113, Met115, Ala121, Asp122, Tyr123, Arg125.
- Residues to avoid: PD-1 glycosylation positions Asn49, Asn58, Asn74, Asn116 (dispensable for binding).
- Epitope to mimic: The preorganized CC'FG beta-sheet binding mode demonstrated by nanobody KN035 (10.1038/celldisc.2017.4) and cyclic peptide pAC65 (10.1186/s12943-023-01853-4).
- Affinity target: Aim for Kd <= 1.0 nM (one half-log tighter than the 3.0 nM Kd of nanobody KN035 from 10.1038/celldisc.2017.4 and matching the 1.8 nM IC50 of macrocycle pAC65 from 10.1186/s12943-023-01853-4; Rule 1 applied).
- Key risk: Insufficient shape complementarity against the relatively flat CC'FG beta-sheet surface could result in sub-optimal affinity or non-specific hydrophobic sticking if aromatic packing against Tyr56 and Tyr123 is not precisely balanced by polar interactions with Arg113 and Arg125.

LITERATURE SOURCES (max 8 rows)

#	TITLE (TRUNCATED TO 60 CHARS)	DOI	STUDY TYPE	SCORE	KEY FINDING
1	Structure and interactions of the human programmed cell...	10.1074/jbc.M112.448126	experimental_in_vitro	0.740	Human PD-1 binds PD-L1 with Kd = 8.2 uM by SPR at 37 °C
2	Structural basis of a novel PD-L1 nanobody for immune...	10.1038/celldisc.2017.4	experimental_structural	0.668	KN035 binds PD-L1 with Kd = 3.0 nM; Y56A causes 4400-fold drop
3	One Face, Three Solutions: Structural Convergence in PD-L1...	10.1021/acs.jmedchem.6c00674	experimental_structural	0.635	Inhibitors converge on CC'FG sheet anchored by Y56/Y123/R113
4	Structural and biological characterization of pAC65, a macro...	10.1186/s12943-023-01853-4	experimental_in_vitro	0.642	Macrocycle pAC65 dissociates PD-1/PD-L1 with IC50 = 1.80 nM
5	Probing protein flexibility reveals a mechanism for selective...	10.7554/eLife.22889	computational	0.650	PD-L1 Y123 acts as wedge inducing opening of PD-1 N66 switch
6	An unexpected N-terminal loop in PD-1 dominates binding by...	10.1038/ncomms14369	experimental_structural	0.655	Nivolumab binds PD-1 N-loop with Kd = 1.45 nM independent of glycans
7	Human and mouse PD-L1: similar molecular structure, but...	10.1016/j.isci.2020.101960	experimental_in_vitro	0.583	BMS-1166 and peptide-57 fail on mouse PD-L1 due to Ile115 clash

PIPELINE HANDOFF

- target_complex: PDCD1 / CD274
- design_intent: disrupt
- structure_organism: Homo sapiens
- ortholog_of_human: NONE
- tractability: Excellent
- go_recommendation: GO

- go_rationale: High-resolution human complex PDB 4ZQK features well-validated extracellular CC'FG hotspots (Y56, R113, Y123) with proven low-nanomolar competitive disruption precedent.
- modality: mini_protein
- target_site_hint: {"mode":"ppi_interface","target_protein":"CD274","priority_residues":["Y56","R113","M115","A121","D122","Y123","R125"],"notes":"Literature-validated CC'FG beta-sheet extracellular hotspots from doi:10.1038/celldisc.2017.4, doi:10.1021/acs.jmedchem.6c00674, and doi:10.1186/s12943-023-01853-4; CD274 canonical extracellular IgV numbering"}
- design_query: Generate mini_protein design inputs for PDCD1 / CD274, PDB 4ZQK. Priority hotspots: Y56, R113, M115, Y123, R125. Affinity target: Kd <= 1.0 nM. Disrupt extracellular checkpoint interface.

MODEL PROVENANCE

- skill: `molecular-biology-expert`
- written by: **gemini:gemini-3.8-flash** — the model the operator selected. LPT never substitutes a model on its own; a stage a safety classifier declines ends the run.

CITATION VERIFICATION

- Citations checked: 8
- Verified in corpus: 8
- All cited DOIs verified against fingerprint store.

2 Structure

LLM stage complex-structure-analysis · gemini-3.8-flash · $0.07 · `02_structure.md`

PPI ANALYSIS REPORT

COMPLEX OVERVIEW

- Structure: /home/m.uckelmann_cbs-niob.local/code/little-protein-tiger/data/structures/4ZQK_ba1.cif (PDB 4ZQK)
- Structure source: experimental (X-ray)
- Source organism: Homo sapiens
- Assembly: 1:1 heterodimer — Chain A (Programmed cell death 1 ligand 1 / CD274 / PD-L1, 115 aa) and Chain B (Programmed cell death protein 1 / PDCD1 / PD-1, 106 aa); single interface analysed. Target identity confirmed: entity descriptions are canonical full names matching expected genes CD274 and PDCD1.
- Chain A: A (Programmed cell death 1 ligand 1 / CD274) — target chain (115 residues; ≤ 250 threshold satisfied)
- Chain B: B (Programmed cell death protein 1 / PDCD1) — partner chain (106 residues)
- Design mode: DISRUPT
- BSA total: 1566.5 Å²
- H-bonds across interface: 16
- Interface residues: 19 on chain A, 23 on chain B
- Design modality: mini_protein (a cyclic peptide would also suit the compact core hydrophobic sub-pocket around Tyr123 and Ala121)

CHAIN A INTERFACE RESIDUES

Chain A: Hydrophobic: VAL23, ILE54, VAL76, MET115, GLY119, GLY120, ALA121 | Aromatic: PHE19, TYR56, TYR123 | Charged: ASP26, GLU58, ARG113, ASP122, LYS124, ARG125 | Polar: GLN66, SER117

CHAIN B INTERFACE RESIDUES

Chain B: Hydrophobic: VAL64, LEU122, GLY124, ILE126, LEU128, PRO130, ALA132, ILE134 | Aromatic: TYR68 | Charged: ASP77, LYS78, GLU84, LYS131, GLU136 | Polar: ASN66, SER73, ASN74, GLN75, THR76, SER127, GLN133

H-BONDS AT INTERFACE (top 12 by distance)

DONOR	DONOR ATOM	ACCEPTOR	ACCEPTOR ATOM	DISTANCE (Å)
A:ASP122	OD1	B:TYR68	OH	2.56
A:ARG125	O	B:GLN75	NE2	2.61
B:GLU136	OE1	A:ARG113	NH2	2.65
A:ALA121	O	B:LYS78	NZ	2.68
A:TYR123	OH	B:GLU136	OE2	2.70
A:ARG125	N	B:GLN75	OE1	2.73
A:ALA121	O	B:ASN66	ND2	2.85
A:GLN66	OE1	B:ALA132	N	2.91
A:TYR56	OH	B:HOH202	O	2.91
A:LYS124	NZ	B:THR76	O	2.91
A:PHE19	O	B:LYS78	NZ	2.92
A:ALA121	O	B:HOH203	O	2.93

HOTSPOT REGIONS (top 2, ranked by suitability)

Region 1: CC'FG Front-Face Sheet Hotspot — Excellent

- Residues: ILE54, TYR56, GLN66, ARG113, MET115, ALA121, ASP122, TYR123, LYS124, ARG125 (selected 10 of 18 interface residues; dropped 8 peripheral/rim residues PHE19, VAL23, ASP26, GLU58, VAL76, SER117, GLY119, GLY120)
- BSA contributions (Å²): ILE54 (41.1), TYR56 (52.3), GLN66 (52.4), ARG113 (59.0), MET115 (48.5), ALA121 (72.5), ASP122 (35.1), TYR123 (126.0), LYS124 (43.7), ARG125 (51.7)
- Hydrophobic fraction: 0.50 (50% hydrophobic/aromatic)
- Spatial spread (Cα RMSD): 6.8 Å

- Mean KD hydrophobicity: -1.43
- Partner contacts: Engages PDCD1 residues ASN66, TYR68, GLN75, THR76, ASP77, LYS78, ILE126, LEU128, PRO130, LYS131, ALA132, ILE134, GLU136
- Literature evidence: 10.7554/eLife.22889
- Design note: This region comprises the central binding surface on the front CC'FG beta-sheet of CD274. Tyr123 and Ala121 are the dominant energetic anchors (calculated ΔΔG of -5.53 and -5.03 kcal/mol, respectively), burying extensive surface area against PDCD1 hydrophobic core residues (Ile134, Ala132, Leu128, Ile126) and participating in critical hydrogen bonding networks. Surrounding basic and acidic residues (Arg113, Asp122, Lys124, Arg125) provide electrostatic complementarity to Glu136, Tyr68, and Gln75. A designed competitive binder must occupy the hydrophobic pocket anchored by Tyr123/Ala121/Met115/Tyr56 and engage the flanking salt-bridge network.
- Separability: Independent — forms the primary cohesive interaction surface.

DESIGN RECOMMENDATIONS

- Design mode: DISRUPT
- Recommended modality: mini_protein (mini-protein offers optimal scaffold coverage across the 10-residue 6.8 Å RMSD sheet face; a cyclic peptide targeting the Tyr123/Ala121/Met115 pocket is also viable)
- Primary target: Region 1 (CC'FG Front-Face Sheet Hotspot) — Excellent
- Key chain A residues: ILE54, TYR56, GLN66, ARG113, MET115, ALA121, ASP122, TYR123, LYS124, ARG125
- Key chain B residues: TYR68, GLN75, THR76, LYS78, ILE126, LEU128, ALA132, ILE134, GLU136
- Confidence / B-factors: pLDDT not applicable — experimental structure (B-factors in file)
- Caveats: None; the target interface is a rigid, well-ordered extracellular IgV beta-sheet domain with high crystallographic resolution and consistent sidechain density.

MODEL-READY HOTSPOTS [DISRUPT]

Target chain A — Region 1: CC'FG Front-Face Sheet Hotspot — selected 10 of 18 residues:

RESIDUE	AUTH_SEQ_ID	LABEL_SEQ_ID	RFD3 SIDECHAIN ATOMS
ILE	54	37	CD1,CG2
TYR	56	39	CD2,OH
GLN	66	49	CD,OE1
ARG	113	96	CZ,NH1
MET	115	98	CG,SD
ALA	121	104	CB,CA
ASP	122	105	CG,OD1
TYR	123	106	CD2,OH
LYS	124	107	NZ,CE
ARG	125	108	CZ,NH1

BoltzGen binding

binding: 37,39,49,96,98,104,105,106,107,108

RFD3 select_hotspots

select_hotspots: A54: CD1,CG2 A56: CD2,OH A66: CD,OE1 A113: CZ,NH1 A115: CG,SD A121: CB,CA A122: CG,OD1 A123: CD2,OH A124: NZ,CE A125: CZ,NH1

PIPELINE HANDOFF

- pdb_id: 4ZQK
- chain_a: A
- chain_b: B
- target_chain: A
- partner_chain: B
- target_chains: A
- target_complex: CD274 / PDCD1
- structure_organism: Homo sapiens

- design_intent: disrupt
- modality: mini_protein
- bsa_A2: 1566
- tractability: Excellent
- literature_query: Search for published inhibitors and mutagenesis data for CD274/PDCD1. Cross-reference hotspot residues Y56, A121, Y123 on CD274.

MODEL PROVENANCE

- skill: `complex-structure-analysis`
- written by: **gemini:gemini-3.8-flash** — the model the operator selected. LPT never substitutes a model on its own; a stage a safety classifier declines ends the run.

CITATION VERIFICATION

- Citations checked: 1
- Verified in corpus: 1
- All cited DOIs verified against fingerprint store.

20 Target intel (bridged)

deterministic composed in code from stages 0 to 2; no LLM call · `binder/20_target_intel.md`

Target intelligence (bridged from PPI literature)

Structure substituted: the pathway stage recommended 4Z18; this campaign was designed against 4ZQK instead — 4Z18 does not contain both PDCD1 and CD274. Re-run with `--pdb 4Z18` to keep the original.

Bridged from the PPI track's pathway/literature/structure stages for CD274 / PDCD1 — see 00_pathway.md / 01_literature.md / 02_structure.md for the full reasoning. This file exists only so the binder track's stage machine has a target_intel artifact to resume from; no LLM call was made to produce it.

PIPELINE HANDOFF

- pdb_id: 4ZQK
- target_gene: CD274
- target_uniprot: Q9NZQ7
- partner_name: PDCD1
- target_chain: A
- partner_chain: B
- design_intent: disrupt
- modality: mini_protein
- binder_length_min: 70
- binder_length_max: 86
- interface_rationale: High-resolution human complex PDB 4ZQK features well-validated extracellular CC'FG hotspots (Y56, R113, Y123) with proven low-nanomolar competitive disruption precedent.
- go_recommendation: GO

22 Trim

deterministic structure_trim.py · `binder/22_trim.md`

Target trimming

- Method: **cath**
- Topology: the modelled construct is entirely extracellular (115 residues) — no restriction needed
- Residues: 115 -> 115 in 1 segment(s) [(18, 132)]
- Interface area of the kept residues retained: 100.0%
- Newly exposed hydrophobic surface away from the epitope: none — the cut opened no hydrophobic surface
- Hotspots kept: 10/10

PIPELINE HANDOFF

- trimmed_structure: /home/m.uckelmann_cbs-niob.local/code/little-protein-tiger/projects/immune_check/runs/round-1/binder/trim/trimmed.cif
- trim_map: /home/m.uckelmann_cbs-niob.local/code/little-protein-tiger/projects/immune_check/runs/round-1/binder/trim/trim_map.json
- contig: 70-86,/0,A18-132
- n_segments: 1
- n_residues: 115

23 Binder spec

deterministic foundry_spec.py · `binder/23_binder_spec.md`

RFD3 design specification

Contig `70-86,/0,A18-132` with 9 atom-level hotspot(s): A113, A115, A121, A122, A123, A124, A54, A56, A66.

Hotspots repaired against the structure. The interface report named atoms or residues the modelled structure does not contain (typically a disordered side-chain tip). The campaign is designed against the repaired set above, not the table in `21_interface.md`: A125: dropped (none of CZ,NH1 modelled; residue has C,CA,CB,CD,CG,N,O).

PIPELINE HANDOFF

- spec_path: /home/m.uckelmann_cbs-niob.local/code/little-protein-tiger/projects/immune_check/runs/round-1/binder/spec/cd274_binder_001.json
- design_name: cd274_binder_001

24 Pilot

deterministic foundry_runner.py (RFD3, solubleMPNN, RF3) · `binder/24_pilot.md`

Pilot campaign

stage done RFD3 100/100 (100.0%) prefilter 64 MPNN 256 RF3 256/256 (100.0%) free disk 86 GB job pid 932947 · orphaned · 0.83 h elapsed

PIPELINE HANDOFF

- campaign_dir: /home/m.uckelmann_cbs-niob.local/code/little-protein-tiger/projects/immune_check/runs/round-1/binder/campaign/pilot
- n_rfd3: 100
- n_filtered: 64
- n_mpnn: 256
- n_rf3: 256
- prefilter_rate: 0.64
- free_gb: 85.8

25 Calibration gate

deterministic campaign_calibration.py · `binder/25_calibration.md`

Campaign calibration

Goal: **50 designs** meeting all hard gates AND iptm > 0.85. Bar raised from the requested iptm > 0.7 to iptm > 0.85 — this trial supports it within budget.

Sample: 1,628 refolds from 407 RFD3 backbones (4 sequences each, prefilter kept 70%).

Hit rate

UNIT	HITS	N	RATE	95% INTERVAL
backbone	14	407	3.44%	2.06% – 5.69%
refold	152	1,628	9.34%	8.02% – 10.85%

Backbones are the sizing unit: `n_batches` controls backbones, and the 4 sequences sharing one are correlated, not independent trials.

Required scale

```
point estimate             ~ 2,071 designs / 5,814 refolds  ->  18 GPU-h, 6 GB
Wilson 95% lower bound     ~ 3,459 designs / 9,709 refolds  ->  30 GPU-h, 9 GB
```

Yield at softer bars

```
survivors (all hard gates)       319  (19.59% of refolds)
iptm > 0.5                       319  (19.59% of refolds)
iptm > 0.6                       240  (14.74% of refolds)
iptm > 0.65                      197  (12.10% of refolds)
iptm > 0.7                       152  ( 9.34% of refolds)
iptm > 0.75                      104  ( 6.39% of refolds)
iptm > 0.8                        70  ( 4.30% of refolds)
iptm > 0.85                       17  ( 1.04% of refolds)
```

```
best iptm, any refold:  0.8865
best iptm, a survivor:  0.8865
strictest bar this sample can size a campaign at: iptm > 0.85
```

Gate attribution

```
input:     1,628
survivors: 319

dropped by first failing criterion:
```

binder_rmsd_dock <= 5 735 iptm >= 0.5 497 no clash 56 binder_rmsd_fold <= 2 18 binder_plddt >= 0.75 3

```


passing each criterion alone:
```

binder_rmsd_dock <= 5 893 (54.9%) epitope_recall >= 0.5 1,509 (92.7%) hotspot_engagement >= 0.75 1,526 (93.7%) binder_rmsd_fold <= 2 1,529 (93.9%) binder_plddt >= 0.75 1,603 (98.5%) iptm >= 0.5 433 (26.6%) iface_pae <= 15 627 (38.5%) no clash 1,364 (83.8%)

Verdict: SCALE_UP

14/407 backbones produced an excellent design (3.44%, 95% CI 2.06%-5.69%). Even at the pessimistic bound the run costs ~30 GPU-h / 9 GB, inside the 120 h / 120 GB budget. This target is unusually good — the trial supports sizing at iptm > 0.85 (requested was 0.7) within budget, so the bar was raised rather than sizing to the loosest workable target.

Where to run it

```
local  (1 GPU)              ~29.8 h
cluster (8 GPUs, parallel)   ~3.7 h (rough — different refold backend/hardware)
```

Decision: local. Fits the 48 h local budget — running on this workstation's GPU.

26 Production

deterministic foundry_runner.py (RFD3, solubleMPNN, RF3) · `binder/26_production.md`

Production campaign

stage done RFD3 3,456/3,456 (100.0%) prefilter 2,217 MPNN 8,868 RF3 8,868/8,868 (100.0%) free disk 93 GB job pid 1057017 · done · 28.25 h elapsed

PIPELINE HANDOFF

- campaign_dir: /home/m.uckelmann_cbs-niob.local/code/little-protein-tiger/projects/immune_check/runs/round-1/binder/campaign/production
- n_rfd3: 3456
- n_filtered: 2217
- n_mpnn: 8868
- n_rf3: 8868
- prefilter_rate: 0.6415
- free_gb: 93.2

27 Scoring

deterministic binder_metrics.py, binder_ranking.py · `binder/27_scoring.md`

Design scoring and ranking

Scored **8,868** refolds from the production campaign.

```
input:     8,868
survivors: 1,798

dropped by first failing criterion:
```

binder_rmsd_dock <= 5 4,161 iptm >= 0.5 2,597 no clash 239 binder_rmsd_fold <= 2 62 binder_plddt >= 0.75 11

```

passing each criterion alone:
```

binder_rmsd_dock <= 5 4,707 (53.1%) epitope_recall >= 0.5 8,185 (92.3%) hotspot_engagement >= 0.75 8,258 (93.1%) binder_rmsd_fold <= 2 8,470 (95.5%) binder_plddt >= 0.75 8,751 (98.7%) iptm >= 0.5 2,301 (25.9%) iface_pae <= 15 3,417 (38.5%) no clash 7,362 (83.0%)

```

```

1,798 survivors across 847 distinct backbones; top 20 selected.

Rosetta interface metrics computed for 300 of 1,798 gated designs (0 failed). They enter the composite only here — never the gate.

PIPELINE HANDOFF

- scores_csv: /home/m.uckelmann_cbs-niob.local/code/little-protein-tiger/projects/immune_check/runs/round-1/binder/scoring/refold_scores.csv
- top_k_csv: /home/m.uckelmann_cbs-niob.local/code/little-protein-tiger/projects/immune_check/runs/round-1/binder/scoring/top_k.csv
- n_scored: 8868
- n_survivors: 1798

28 Summary

LLM stage design-analyst · gemini-3.8-flash · $0.02 · `binder/28_summary.md`

1. Executive verdict

GO. This campaign yielded an exceptionally strong candidate pool against the CD274 PDCD1 interface, highlighted by rank-1 candidate `cd274_binder_001_cd274_binder_001_325_model_3_b0_d1` exhibiting an `ipsae_min` of 0.737, an `iptm` of 0.890, and a sub-angstrom `binder_rmsd_dock` of 0.97 Å. Across the top picks, interface metrics consistently clear stringent thresholds (iPTM > 0.84, interface PAE <= 5.0 Å, hotspot engagement 1.0 across all 10 declared residues), though non-zero severe clash counts in several top-ranked designs require prioritizing clash-free variants for follow-up.

2. Quality of the top-K

Top 5 designs by `mmr_rank`:

MMR	NAME	COMP	IPSAE_MIN	IPTM	DOCK (Å)	IPAE (Å)	B_PLDDT	HS_ENG	STRONGEST	WEAKEST
1	cd274_binder_001_cd274_binder_001_325_model_3_b0_d1	18.80	0.737	0.890	0.97	3.69	0.818	1.00	binder_tm (0.984)	clash_severe (1)
2	cd274_binder_001_cd274_binder_001_624_model_0_b0_d2	17.64	0.794	0.906	0.73	3.37	0.815	1.00	ipsae_min (0.794)	mmr_rank (4th comp)
3	cd274_binder_001_cd274_binder_001_222_model_0_b0_d0	18.31	0.633	0.854	1.04	5.00	0.840	1.00	b_plddt (0.840)	clash_severe (2)
4	cd274_binder_001_cd274_binder_001_673_model_3_b0_d3	14.64	0.635	0.870	0.87	4.36	0.799	1.00	dock (0.87 Å)	ipsae_min (0.635)
5	cd274_binder_001_cd274_binder_001_570_model_0_b0_d3	18.21	0.586	0.847	1.37	4.94	0.826	1.00	epitope_recall (1.00)	fold rmsd (1.15 Å)

3. Methodological red flags

- **Steric clashes escaping upstream filtering**: Although the hard gate is formally set to zero severe clashes, several entries in the top-K retain severe interface clashes (e.g. rank 1 `cd274_binder_001_cd274_binder_001_325_model_3_b0_d1` has 1 severe clash; rank 3 `cd274_binder_001_cd274_binder_001_222_model_0_b0_d0` has 2; rank 12 has 3). While often resolvable by side-chain relaxation, candidates with `clash_severe = 0` represent much safer structural solutions.
- **Docking geometry is rigorously confirmed**: Crucially, high confidence is supported by actual pose recovery: every top-5 design has `binder_rmsd_dock` between 0.73 Å and 1.37 Å (well within the 5.0 Å threshold), confirming that RF3 places the binders directly on target. Epitope recall (>= 0.93) and hotspot engagement (1.0 across all top designs) confirm full coverage of the 10 declared interface residues without off-target drift.
- **Diversity**: Sequence similarity remains low (`mmr_max_similarity` <= 0.46 across the top-20), and all designs originate from distinct `design_family` backbones, indicating robust sampling across multiple distinct structural topologies rather than convergence to a single local minimum.
- **Length distribution**: Binder lengths span 70 to 86 residues across the 20 designs, showing natural variation without artificial bunching at extreme limits.

4. Recommended designs

- `cd274_binder_001_cd274_binder_001_624_model_0_b0_d2` (mmr 2) — Lead candidate: zero severe clashes, highest `ipsae_min` among the top picks (0.794), exceptional docking fidelity (0.73 Å dock RMSD), tight interface PAE (3.37 Å), and iPTM of 0.906.
- `cd274_binder_001_cd274_binder_001_739_model_0_b0_d3` (mmr 9) — Secondary lead: zero severe clashes, outstanding `ipsae_min` of 0.758, iPTM of 0.897, interface PAE of 3.45 Å, and perfect 1.00 epitope recall and hotspot engagement.
- `cd274_binder_001_cd274_binder_001_131_model_0_b0_d3` (mmr 16) — Zero severe clashes, high `ipsae_min` of 0.759, iPTM of 0.902, low fold RMSD (0.37 Å), and tight interface PAE (3.51 Å) in a compact 74-residue scaffold.
- `cd274_binder_001_cd274_binder_001_325_model_3_b0_d1` (mmr 1) — Highest composite score overall with `ipsae_min` of 0.737 and dock RMSD of 0.97 Å; recommended for side-chain repacking / relaxation to resolve its single minor severe clash.
- `cd274_binder_001_cd274_binder_001_673_model_3_b0_d3` (mmr 4) — Zero severe clashes, dock RMSD of 0.87 Å, fold RMSD of 0.55 Å, and iPTM of 0.870 across an 85-residue helical bundle.

5. Recommended next steps

- Run Rosetta FastRelax or all-atom MD minimization on the top picks (specifically `cd274_binder_001_cd274_binder_001_624_model_0_b0_d2` and

`cd274_binder_001_cd274_binder_001_325_model_3_b0_d1`) to confirm interfacial side-chain packing and relieve the isolated clash in rank 1.
- Perform orthogonal cross-validation via AlphaFold3 or ESMFold complex prediction to ensure binder refolding and pose stability are not RF3-specific artifacts.
- Proceed with gene synthesis and expression profiling for the top 3-5 clash-free designs from `top_k.fasta`.

6. Artifact pointers

- `top_k.csv`
- `ranked.csv`
- `top_k.fasta`

PIPELINE HANDOFF

- go_recommendation: GO
- go_rationale: Exceptional target campaign with multiple sub-angstrom docked binders achieving ipsae_min up to 0.794 and iPTM > 0.88 across diverse backbones.
- target_complex: CD274 (PDCD1 interface, disrupt mode)
- top_k_count: 20
- best_iptm: 0.890
- best_ipae: 3.69
- best_ipsae_min: 0.737
- best_dock_rmsd: 0.97
- best_name: cd274_binder_001_cd274_binder_001_325_model_3_b0_d1

MODEL PROVENANCE

- skill: `design-analyst`
- written by: **gemini:gemini-3.8-flash** — the model the operator selected. LPT never substitutes a model on its own; a stage a safety classifier declines ends the run.

Supplemental Information 3 - Literature curation prompt

SUPPLEMENTARY INFORMATION · LPT CURATION PROMPT

Literature curation prompt

`curation_prompt.md` `schema v2.0` `1560 words`

> System prompt given to the curation model for every paper. Output is validated against `extraction_schema.json`; rendered verbatim from the repository file.

ROLE

You are a Senior Scientific Curator specializing in protein biochemistry and biophysics for drug target discovery. Your task is to ingest the full text of a scientific paper and produce a machine-readable "Fingerprint" stored in a metadata-enriched database.

RELEVANCE GATE

Before extracting, assess whether the paper has meaningful connection to the target domain (protein-protein interactions, binding/affinity measurements, structural data, inhibitor/drug characterisation, molecular pathway mechanisms, mutagenesis/mutational analysis, functional genomics such as CRISPR screens, siRNA, proteomics, host-pathogen protein interactions, or vascular/cardiovascular cell biology).

- If the paper IS relevant (contains any of the above): proceed with full extraction.
- If the paper is entirely off-topic (e.g. pure clinical epidemiology with no molecular data, pharmacokinetics with no protein interaction data, or unrelated organisms/diseases with no transferable mechanistic insight): output only `{"relevant": false}` and stop. Do NOT return this for papers that merely lack affinity measurements — mechanistic, genetic, or structural protein interaction data alone is sufficient. Bias strongly toward extraction.

OBJECTIVE

Deconstruct the provided paper into a **concise** structured JSON object. The fingerprint is a navigation aid — it tells future agents where relevant information lives, not a substitute for the paper itself. Prioritise the most important findings only. If a value is not explicitly stated, return null. Do not infer.

EXTRACTION REQUIREMENTS

1. **Factual Provenance**: Every extracted claim must be accompanied by a `source_span`. - For PDFs: use format `"Page N, Para M"` (e.g., `"Page 4, Para 2"`). - For XML/structured text: use format `"Section: [section heading], Para M"` (e.g., `"Section: Results, Para 3"`).
2. **Contextual Hook**: Write a 100–150 word `situational_context_hook` summarising the study's specific experimental environment, target proteins, and key quantitative finding. Example: "In vitro SPR measurements show KRAS binding affinity to RAF RBD domain is reduced from 200 nM to 900 nM for the RBD R59A mutation."
3. **PDB Accessions**: Extract every PDB accession code explicitly mentioned in the paper — deposited structures, reference structures, and any codes in methods, data availability, or figure legends. PDB codes are exactly 4 characters (digit + 3 alphanumeric, e.g. 7AHL, 4U6V, 2OI0). Store in `paper_metadata.pdb_accessions`. Use empty list `[]` if none are mentioned. Do NOT infer or guess PDB codes — only include codes that appear verbatim in the paper text.
4. **Negative Results**: Explicitly capture what did *not* work or where the hypothesis failed in `contradictions_and_negative_results`.
5. **Entity Mapping**: Identify all key chemical, biological, and mathematical entities.
6. **Protein-Protein Interactions**: Map domains and amino acid residues critical for binding. Report affinity measures if available. Populate `protein_pair` and `experimental_context` for each relevant finding. Structural data: X-ray crystallography and cryo-EM structures of protein complexes are evidence of interaction, map amino acid residues and domains in interfaces.

`protein_pair` contains exactly two PROTEIN NAMES — gene symbols or canonical protein labels (e.g. `"GENE_A"`, `"GENE_B"`, `"human GENE_A (residues 94-312)"`). Never put amino-acid residues, mutations, domain identifiers, or small molecules in this field — those belong in `key_amino_acid_residues` or `entities.chemicals` instead. Every `key_findings` entry must use the same two proteins in `protein_pair`, even if the finding discusses a specific residue-residue contact between them.

- ✅ Correct: `"protein_pair": ["GENE_A", "GENE_B"]`, with `"key_amino_acid_residues": ["GENE_A Phe19", "GENE_B Leu54"]`
- ❌ Wrong: `"protein_pair": ["GENE_A Phe19", "GENE_B Leu54"]` (these are residues, not proteins)

- ❌ Wrong: `"protein_pair": ["GENE_A-TAD", "GENE_A"]` (a domain is not a separate protein)

UNIT CONVERSION RULES

- `affinities_kd_Molar` and `inhibitory_constant_Ki` MUST be expressed as Molar floats.
- 5 nM → 5e-9
- 2.3 µM → 2.3e-6
- 100 pM → 1e-10
- If units are ambiguous or not stated, set to null.
- `protein_origin_organism` MUST be a list of **NCBI Taxonomy integer IDs**, never organism names. The validator rejects a name outright.
- Homo sapiens → 9606
- Mus musculus → 10090
- Saccharomyces cerevisiae (S288C) → 559292
- Escherichia coli K-12 → 83333
- Drosophila melanogaster → 7227
- Xenopus laevis → 8355
- If you do not know the taxid for an organism, use `[]` rather than guessing a number or writing the name.

CONFIDENCE SCORE RUBRIC

Assign `confidence_score` (0.0–1.0) per finding: - **0.9–1.0**: Directly measured with controls and biological/technical replicates - **0.7–0.89**: Measured but limited controls or single replicate - **0.5–0.69**: Inferred from indirect assay or proxy measurement - **< 0.5**: Computational prediction or purely qualitative observation

STUDY TYPE CLASSIFICATION

Use the following closed enum for `study_type`: - `experimental_in_vitro` — cell-free or cell-based experiments - `experimental_in_vivo` — animal or organism-level experiments - `experimental_structural` — X-ray crystallography, cryo-EM, NMR, etc. - `computational` — molecular dynamics, docking, bioinformatics - `review` — literature review or meta-analysis - `case_study` — single patient or clinical case

STUDY CATEGORY CLASSIFICATION

Set `study_category` using the following closed enum. This is **orthogonal** to `study_type` — it describes the scientific domain, not the methodology. A cell-based CRISPR screen is `study_type=experimental_in_vitro` AND `study_category=pathway_biology`.

- `biochemistry` — binding assays, inhibitor characterisation, affinity measurements (Kd/Ki), mutagenesis mapping binding energy; the focus is molecular interaction at the protein or chemical level
- `pathway_biology` — signalling cascade mechanisms, disease-specific pathway dysregulation, genetic dependency (CRISPR essentiality, siRNA screens), oncogenic mechanisms, upstream/downstream node relationships
- `structural_biology` — primarily structural determination (X-ray, cryo-EM, NMR) with minimal functional or binding data; structure is the end goal
- `enzymology` — catalytic mechanism, kinetics (kcat, Km, kcat/Km), active-site chemistry, substrate specificity; the focus is how an enzyme turns substrate over, not what it binds
- `biocatalysis` — enzymes engineered or applied for synthesis, directed evolution campaigns, process/industrial biocatalysis
- `computational_chemistry` — QM/MM, free-energy calculations, docking or MD as the primary result rather than a supporting method
- `host_pathogen` — protein-level interactions between a pathogen (bacterial, viral, fungal) and host proteins; includes virulence factor mechanisms, immune evasion, effector-host protein binding, and antimicrobial resistance mechanisms at the molecular level
- `clinical` — patient cohort data, clinical outcomes, biomarker studies, epidemiology
- `review` — literature review, meta-analysis, or perspective with no original experimental data

When in doubt between `biochemistry` and `pathway_biology`: if the paper measures binding affinities or inhibitor potency, choose `biochemistry`. If the paper characterises how a protein drives disease through a signalling cascade, choose `pathway_biology`. When in doubt between `host_pathogen` and `biochemistry`: if the interacting proteins are from different organisms (pathogen + host), choose `host_pathogen`.

PATHWAY CONTEXT EXTRACTION

Only populate `pathway_context` when `study_category == "pathway_biology"`. For all other categories, set `pathway_context: null`.

When extracting pathway context, apply the same factual provenance rules — `source_span` is required for every `disease_associations` and `target_nodes` entry. Do not infer; only extract what is explicitly stated.

- `pathways`: list the named signalling pathways covered (e.g., ["mTOR", "NF-kB", "unfolded protein response"])
- `disease_associations`: for each disease discussed, extract:
- `disease`: disease or cancer subtype name
- `mechanism`: the mechanistic link (e.g., "<upstream> loss → <kinase> inactivation → <effector> nuclear accumulation")
- `mutation_frequency`: if stated (e.g., "~50% of <indication> cases"); null if not stated
- `genetic_evidence_type`: type of evidence (patient sequencing / TCGA analysis / CRISPR screen / animal model / cell line); null if unclear
- `source_span`: provenance
- `target_nodes`: for each protein discussed as a pathway node or therapeutic target:
- `protein`: gene symbol (e.g., "GENE_A", "GENE_B", "GENE_C")
- `pathway_position`: one of [upstream_regulator, kinase, effector, transcription_factor, adaptor, ligand, receptor]
- `dysregulation`: how it is dysregulated in disease (e.g., "hyperactivated via nuclear translocation in NF2-null tumours")
- `genetic_dependency_evidence`: CRISPR essentiality scores, siRNA knockdown phenotype, or null
- `prior_therapeutic_targeting`: known inhibitor classes or peptidomimetic strategies, or null
- `suggested_pdb_structures`: any PDB IDs mentioned in the paper for this protein; empty list if none
- `source_span`: provenance
- `pathway_logic`: compact ON/OFF logic of the cascade (max 50 words); null if not described
- `redundancy_risks`: compensatory proteins that could rescue loss of a given node (e.g., ["<paralog> compensates for <node> loss"])
- `upstream_regulators`: gene symbols of upstream suppressors or activators (e.g., ["NF2", "MST1", "MST2", "LATS1", "LATS2"])
- `downstream_effectors`: gene symbols of downstream targets (e.g., ["CDKN1A", "BBC3", "MDM2"])

For `key_findings` in `pathway_biology` papers: capture genetic dependency evidence and disease association claims. `affinities_kd_Molar` and `inhibitory_constant_Ki` are not expected and should be null. `protein_pair` should capture the regulatory relationship (e.g., ["GENE_A", "GENE_B"], upstream first). `confidence_score` rubric applies normally.

LENGTH LIMITS — strictly enforced

- `situational_context_hook`: 100–150 words
- `key_findings`: maximum **5** entries — pick the most quantitatively significant
- `claim`: maximum 40 words each
- `experimental_context`: maximum 15 words each
- `contradictions_and_negative_results`: maximum **3** entries
- `entities.chemicals`, `entities.proteins`, `entities.equations`: maximum **10** items each
- `methodology.experimental_methods_used`, `controls`, `instruments_used`: maximum **8** items each
- `pathway_context.disease_associations`: maximum **5** entries
- `pathway_context.target_nodes`: maximum **8** entries
- `pathway_context.pathway_logic`: maximum **50** words
- `pathway_context.upstream_regulators`, `downstream_effectors`, `redundancy_risks`: maximum **10** items each

OUTPUT FORMAT

Strict JSON only. No prose. No preamble. No markdown code fences. Output must conform exactly to the schema below.

SCHEMA

```
{
  "schema_version": "2.0",
  "relevant": true,
  "study_category": "enum[biochemistry, pathway_biology, structural_biology, enzymology, biocatalysis,
computational_chemistry, host_pathogen, clinical, review]",
  "pathway_context": null,
```

```
  "curation_metadata": {
    "model": "string",
    "curated_at": "ISO-8601 datetime",
    "input_tokens": "integer",
    "output_tokens": "integer"
  },
  "paper_metadata": {
    "title": "string",
    "doi": "string or null",
    "study_type": "enum[experimental_in_vitro, experimental_in_vivo, experimental_structural, computational,
review, case_study]",
    "situational_context_hook": "string (100-150 words)",
    "pdb_accessions": ["string"]
  },
  "methodology": {
    "experimental_methods_used": ["string"],
    "protein_origin_organism": ["integer"],
    "controls": ["string"],
    "instruments_used": ["string"]
  },
  "key_findings": [
    {
      "claim": "string",
      "evidence_value": "string or number",
      "quantitative_or_qualitative": "string",
      "protein_pair": ["string", "string"],
      "experimental_context": "string",
      "affinities_kd_Molar": "float or null",
      "inhibitory_constant_Ki": "float or null",
      "key_amino_acid_residues": ["string"],
      "confidence_score": "float (0.0-1.0)",
      "is_statistically_significant": "boolean",
      "source_span": "string"
    }
  ],
  "contradictions_and_negative_results": [
    {
      "finding": "string",
      "conflicts_with_prior_work": "boolean",
      "reasoning": "string"
    }
  ],
  "entities": {
    "chemicals": ["string"],
    "proteins": ["string"],
    "equations": ["string"]
  }
}
```

Supplemental Information 4 - Example Fingerprints

EXAMPLE A · PATHWAY_BIOLOGY · LPT FINGERPRINT · SCHEMA 2.0

USP26 functions as a negative regulator of cellular reprogramming by stabilising PRC1 complex components

DOI 10.1038/s41467-017-00301-4 pathway_biology experimental_in_vitro PMC5571198

SITUATIONAL CONTEXT HOOK

In mouse embryonic fibroblasts (MEFs) undergoing Oct4-Sox2-Klf4-cMyc (OSKM)-mediated cellular reprogramming and embryonic stem cells (ESCs) undergoing differentiation, the deubiquitinase USP26 acts as a potent negative regulator of pluripotency. Co-immunoprecipitation assays in HEK293T cells and differentiating ESCs demonstrate that USP26 physically interacts with canonical PRC1.2 complex components, specifically CBX4 and CBX6, in a RING1A-independent manner. USP26 enzymatic activity removes K48-linked polyubiquitin chains from CBX4 and CBX6, protecting them from 26S proteasomal degradation, whereas catalytic mutant USP26-C304S fails to deubiquitinate them. Accumulated CBX4 and CBX6 recruit PRC1 complexes to pluripotency gene promoters, promoting H2AK119 monoubiquitination and transcriptional repression of Sox2 and Nanog. Knockdown of Usp26 increases alkaline phosphatase-positive iPSC colony generation fourfold (~400 vs ~100 colonies) and upregulates Sox2 and Nanog expression.

KEY FINDINGS (5)

shRNA knockdown of Usp26 in MEFs enhances reprogramming efficiency fourfold, yielding approximately 400 AP+ iPSC colonies.

protein_pair	USP26 ↔ NANOG
evidence	~400 AP+ colonies vs ~100 in control shRNA (quantitative)
context	Dox-induced OSKM MEF reprogramming at day 12
confidence	0.95 · significant: True
source_span	Page 3, Para 1

USP26 physically binds to PRC1.2 components CBX4 and CBX6 independently of the presence of RING1A.

protein_pair	USP26 ↔ CBX4
evidence	Co-IP in WT and RING1A KO 293T cells (qualitative)
context	Anti-FLAG IP in transfected 293T cells
confidence	0.95 · significant: False
source_span	Page 5, Para 1

USP26 deubiquitinase activity specifically removes K48-linked polyubiquitination from CBX4 and CBX6 via active-site Cys304.

protein_pair	USP26 ↔ CBX6
evidence	Loss of K48 deubiquitination in C304S and Δ295-312 mutants (qualitative)
context	In vitro deubiquitination and IP in 293T cells
residues	Cys304
confidence	0.95 · significant: False
source_span	Page 5, Para 1

Accumulated CBX4 and CBX6 bind to Sox2, Nanog, and Cbx7 promoters to repress their transcription.

protein_pair	CBX4 ↔ SOX2
evidence	Significant decrease in luciferase reporter promoter activity (quantitative)
context	Dual luciferase reporter assay in 293T cells
confidence	0.9 · significant: True
source_span	Page 5, Para 1

Individual knockdown of Cbx4 or Cbx6 promotes MEF reprogramming and reactivates Sox2 and Nanog gene expression.

protein_pair	CBX6 ↔ NANOG
evidence	Significant increase in AP+ colonies and Sox2/Nanog mRNA (quantitative)
context	OSKM MEF reprogramming at day 12
confidence	0.9 · significant: True
source_span	Page 6, Para 1

PATHWAY CONTEXT

Pathways: PRC1 Polycomb Repressive Pathway; Somatic Cell Reprogramming; Pluripotency and ESC Differentiation Signaling

Pathway logic: USP26 deubiquitinates and stabilizes CBX4/CBX6, assembling repressive PRC1.2 complexes on Sox2 and Nanog promoters to mediate H2AK119 monoubiquitination and suppress pluripotency.

TARGET NODE	POSITION	DYSREGULATION	DEPENDENCY EVIDENCE	SPAN
USP26	upstream_regulator	Expressed highly in MEFs and differentiated ESCs to repress pluripotency gene activation	shRNA knockdown enhances iPSC reprogramming efficiency 4-fold	Page 3, Para 1
CBX4	effector	Stabilized by USP26 deubiquitination to repress pluripotency genes via PRC1.2	shRNA knockdown enhances AP+ iPSC colony formation and upregulates Sox2/Nanog	Page 6, Para 1
CBX6	effector	Stabilized post-translationally by USP26 to repress Sox2, Nanog, and Cbx7 expression	shRNA knockdown increases reprogramming efficiency and Sox2/Nanog levels	Page 6, Para 1
SOX2	transcription_factor	Repressed through promoter H2AK119 ubiquitination mediated by stabilized CBX4/CBX6-PRC1.2	Upregulated upon Usp26, Cbx4, or Cbx6 shRNA knockdown during reprogramming	Page 5, Para 1
NANOG	transcription_factor	Repressed during differentiation via USP26-promoted PRC1.2 promoter recruitment	Markedly upregulated upon depletion of Usp26, Cbx4, or Cbx6	Page 5, Para 1

Upstream regulators

- CBX7

Downstream effectors

- SOX2
- NANOG
- CBX7

Redundancy risks

- CBX4 and CBX6 act redundantly downstream of USP26 to mediate pluripotency gene repression

CONTRADICTIONS AND NEGATIVE RESULTS (3)

FINDING	CONFLICTS WITH	REASONING
USP26 does not interact with PRC1 components RING1B, RYBP, PCGF1, BMI1, KDM2B, or PHC1, nor with PRC2 components EZH1, EED, or EZH2.	False	USP26 selectively associates with canonical PRC1.2 complex members rather than broad Polycomb complexes.
USP26 catalytic inactive mutant (C304S) and deletion mutant (Δ295-312) fail to remove K48-linked polyubiquitination from CBX4 or CBX6.	False	Catalytic deubiquitinase activity and the conserved active domain are strictly required for substrate stabilization.
Combined knockdown of Usp26 with Cbx4 or Cbx6 does not produce synergistic increases in AP+ iPSC colony counts over Usp26 knockdown alone.	False	CBX4 and CBX6 operate epistatically within the same linear regulatory pathway downstream of USP26.

METHODOLOGY

Methods

- shRNA screen
- CRISPR-Cas9 knockout
- Co-immunoprecipitation
- Western blotting
- ChIP-qPCR
- RT-qPCR

Controls

- Control shRNA
- Empty vector (EV)
- Normal rabbit/mouse IgG
- USP26 catalytic mutant C304S
- USP26 deletion mutant Δ295-312

- Luciferase reporter assay
- In vitro deubiquitination assay

Instruments

- StepOne Real-Time PCR System
- Olympus 1X71S1F fluorescence microscope
- Misonix ultrasonic liquid processor

Source organisms (NCBI taxon)

`10090, 9606`

PDB accessions (0)

ENTITIES

Proteins

USP26, CBX4, CBX6, CBX7, RING1A, PCGF2, SOX2, NANOG, POU5F1, DPPA4

Chemicals

Doxycycline, Retinoic acid, MG132, Lactacystin, Puromycin, Polybrene, CHIR99021, PD0325901

NORMALISED IDENTIFIERS (SIDECAR; 10 RESOLVED, 0 UNRESOLVED, 0 FILTERED)

RAW NAME	GENE	UNIPROT	TIER
USP26	USP26	Q9BXU7	exact_gene
NANOG	NANOG	Q9H9S0	exact_gene
CBX4	CBX4	O00257	exact_gene
CBX6	CBX6	O95503	exact_gene
SOX2	SOX2	P48431	exact_gene
CBX7	CBX7	O95931	exact_gene
RING1A	RING1	Q06587	uniprot_synonym
PCGF2	PCGF2	P35227	exact_gene
POU5F1	POU5F1	Q01860	exact_gene
DPPA4	DPPA4	Q7L190	exact_gene

Curated by `gemini-3.7-flash` on 2026-08-26 (23892 input / 3077 output tokens). Source: Nature Communications 2017, licence CC BY. Fields are rendered verbatim from the stored JSON; layout is added for display. `source_span` values are model-reported locators and are not machine-verified.

Acidic C-terminal domains autoregulate the RNA chaperone Hfq

DOI 10.7554/eLife.27049 biochemistry experimental_in_vitro PMC5606850

SITUATIONAL CONTEXT HOOK

In Escherichia coli, the RNA chaperone Hfq contains an intrinsically disordered C-terminal domain (CTD) that regulates RNA binding and duplex release. Using Rosetta de novo computational modeling and in vitro fluorescence anisotropy binding assays, the acidic tip of the E. coli Hfq CTD was shown to bind specifically to basic arginine- and lysine-rich rim patches on the core Sm domain (Hfq65) with a Kd of 2.9 µM in low-salt buffer and 22 µM in high-salt buffer. This intramolecular interaction acts as a nucleic acid mimic that competitively displaces non-specific RNA and dsRNA from the rim, recycling the chaperone and preventing non-specific DNA aggregation.

KEY FINDINGS (5)

The acidic CTD peptide specifically binds the Hfq core (Hfq65) with micromolar affinity.

protein_pair	Hfq ↔ Hfq
evidence	2.9e-6 (quantitative)
context	Fluorescence anisotropy of FITC-labeled CTD peptide binding to Hfq65 in low salt buffer
Kd	2.90e-06 M
residues	Arg16, Arg17, Arg19, Lys47, Asp97, Glu99, Glu100, Glu102
confidence	0.95 · significant: True
source_span	Page 4, Para 1

Ionic strength reduces binding affinity between the acidic CTD peptide and Hfq65 core.

protein_pair	Hfq ↔ Hfq
evidence	2.2e-5 (quantitative)
context	Fluorescence anisotropy of FITC-labeled CTD peptide binding to Hfq65 in higher salt buffer
Kd	2.20e-05 M
confidence	0.9 · significant: True
source_span	Page 4, Para 1

E. coli Hfq65 binds a heterologous Bacillus subtilis CTD peptide with lower affinity.

protein_pair	Hfq ↔ Hfq
evidence	8.7e-6 (quantitative)
context	Fluorescence anisotropy titration of BsCTD-FITC peptide with E. coli Hfq65
Kd	8.70e-06 M
residues	Lys3, Arg16, Arg17, Arg19
confidence	0.85 · significant: True
source_span	Page 10, Para 2

Full-length Hfq102 exhibits lower binding affinity for dsRNA product than core Hfq65.

protein_pair	Hfq ↔ Hfq
evidence	1.17e-7 (quantitative)
context	Fluorescence anisotropy equilibrium binding to D16-FAM•R16 dsRNA complex at 30°C
Kd	1.17e-07 M
confidence	0.95 · significant: True
source_span	Page 9, Para 1

Hfq-sCTD with shortened linker exhibits the weakest affinity for annealed dsRNA product.

protein_pair	Hfq ↔ Hfq
evidence	1.81e-7 (quantitative)
context	Fluorescence anisotropy equilibrium binding to D16-FAM•R16 dsRNA complex
Kd	1.81e-07 M
confidence	0.95 · significant: True
source_span	Page 9, Para 1

CONTRADICTIONS AND NEGATIVE RESULTS (3)

FINDING	CONFLICTS WITH	REASONING
The mutated basic/polar CTD peptide (RSNKTN) was completely unable to bind Hfq65 core.	False	Acidic residues D97, E99, E100, and E102 at the CTD tip are strictly required for electrostatic binding to basic core rim residues.
Hfq distal face residue Lys31 is not contacted by the CTD.	False	Despite high solvent accessibility, Lys31 does not interact with the CTD, consistent with CTD selectively regulating the rim and proximal faces rather than distal face RNA binding.
The Hfq CTD does not directly bind DNA.	True	Previous reports suggested the CTD binds DNA, but rim mutant R16A abolished insoluble DNA aggregation with Hfq65, demonstrating dsDNA binds the core basic rim patch while the CTD modulates access.

METHODOLOGY

Methods

- Fluorescence anisotropy
- Stopped-flow fluorescence spectroscopy
- Electrophoretic mobility shift assay (EMSA)
- Rosetta FloppyTail de novo modeling
- Multiple sequence alignment and phylogenetic clustering
- Agarose gel electrophoresis DNA binding assay

Controls

- Hfq65 truncation mutant lacking CTD
- Hfq-sCTD shortened linker mutant
- RSNKTN mutant CTD peptide lacking acidic residues
- Non-Hfq RNA annealing controls

Instruments

- Horiba Fluorolog-3
- Typhoon 9410

Source organisms (NCBI taxon)

`562, 287, 1423, 1280, 286`

PDB accessions (5)

`1HK9 1U1S 4NL2 3HSB 1KQ1`

ENTITIES

Proteins

Hfq

Chemicals

FITC, TCEP, Cy3-maleimide, SYBR Gold

Equations y = (Ka * x) / (1 + Ka * x); y = minY + (maxY - minY) / (1 + (x / IC50)^n); C = 1 / ((Vtail - Vcore) * NA); ddG = -RT * ln(Kd_MUT / Kd)

Curated by `gemini-3.7-flash` on 2026-08-25 (35566 input / 2151 output tokens). Source: eLife 2017, licence CC BY. Fields are rendered verbatim from the stored JSON; layout is added for display. `source_span` values are model-reported locators and are not machine-verified.

Disease-specific tau filaments assemble via polymorphic intermediates

DOI 10.1038/s41586-023-06788-w structural_biology experimental_structural PMC10764278

SITUATIONAL CONTEXT HOOK

This study investigates the in vitro assembly mechanism of recombinant human tau (residues 297–391) into filaments associated with Alzheimer’s disease (PHFs) and chronic traumatic encephalopathy (CTE). Using time-resolved cryo-EM, the authors identified a common, transient 'First Intermediate Amyloid' (FIA) filament, which forms as a shared intermediate at 120 minutes across different reaction conditions. The FIA core comprises residues 302–316, forming a hydrophobic interface that precedes the formation of disease-specific filament structures. The study demonstrates that subsequent maturation into diverse, polymorphic J-shaped and C-shaped protofilaments is influenced by reaction conditions (magnesium vs. sodium chloride), providing structural insights into primary and secondary nucleation processes in amyloid assembly. These findings challenge the requirement of non-filamentous oligomers as the primary drivers of amyloid formation in these models.

KEY FINDINGS (4)

Formation of a shared First Intermediate Amyloid (FIA) during the early stages of in vitro assembly of tau(297-391) in both PHF and CTE reaction conditions.

protein_pair	Tau ↔ Tau
evidence	120 min (qualitative)
context	Time-resolved cryo-EM analysis of tau assembly in vitro.
residues	302, 316
confidence	1.0 · significant: True
source_span	Page 3, Para 2

The ordered core of the FIA consists of residues 302–316, where Val306 and Ile308 form a tightly packed hydrophobic interface.

protein_pair	Tau ↔ Tau
evidence	1.7 to 3.8 Å resolution (quantitative)
context	Atomic modelling based on cryo-EM density map.
residues	306, 308, 310
confidence	1.0 · significant: True
source_span	Page 3, Para 3

Tau monomeric backbone displays a propensity to adopt extended conformations in residues 305–314 and 336–345, which are regions found in later β-strand structures.

evidence	null (qualitative)
context	Solution-state NMR of monomeric tau(297-391).
residues	305, 314, 336, 345
confidence	0.9 · significant: True
source_span	Page 2, Para 1

Tau assembly involves maturation from J-shaped protofilaments to C-shaped protofilaments, mediated by rearrangements of 332PGGG335 and 364PGGG367 motifs.

evidence	null (qualitative)
context	Structural analysis of polymorphic intermediates across time points.
residues	332, 335, 364, 367
confidence	0.95 · significant: True
source_span	Page 4, Para 1

CONTRADICTIONS AND NEGATIVE RESULTS (2)

FINDING	CONFLICTS WITH	REASONING
Thioflavin T fluorescence does not detect the FIA or many other early intermediate amyloid species.	False	Standard fluorescence-based monitoring is suboptimal for identifying early nucleated species in this system.
Structures of filaments from early assembly reactions often lack helical twist and are uninterpretable by standard reconstruction methods.	False	Transient, non-helical or heterogenous species at specific time points (e.g., 140-160 min in PHF reaction) prevent structure solution.

METHODOLOGY

Methods

- Time-resolved cryo-electron microscopy
- Solution-state NMR
- Analytical ultracentrifugation
- Thioflavin T fluorescence
- SDS-PAGE
- Helical reconstruction
- Atomic modelling

Controls

- Buffer-only reactions
- Time-zero sample collection
- Replicate reactions for reproducibility
- Internal FSC validation

Instruments

- Thermo Fisher Krios G2
- Thermo Fisher Krios G4
- Falcon-4 camera
- Selectris X energy filter
- Bruker Avance III spectrometers
- Optima XL-I analytical ultracentrifuge
- Fluostar Omega

Source organisms (NCBI taxon)

`9606`

PDB accessions (45)

`8PPO 8Q27 8Q2J 8Q2K 8Q2L 8Q7F 8Q7L 8Q7M 8Q7P 8Q7T 8Q88 8Q8C 8Q8D 8Q8E 8Q8F 8Q8L 8Q8M 8Q8R 8Q8S 8Q8U 8Q8V 8Q8W 8Q8X 8Q8Y …`

ENTITIES

Proteins

tau, amyloid-β, α-synuclein, TDP-43

Chemicals

magnesium chloride, sodium chloride, thioflavin T, ammonium sulfate, IPTG

NORMALISED IDENTIFIERS (SIDECAR; 5 RESOLVED, 0 UNRESOLVED, 0 FILTERED)

RAW NAME	GENE	UNIPROT	TIER
Tau	MAPT	P10636	hgnc_alias
tau	MAPT	P10636	hgnc_alias
amyloid-β	APP	P05067	curated_alias
α-synuclein	SNCA	P37840	curated_alias
TDP-43	TARDBP	Q13148	hgnc_alias

Curated by `gemini-3.1-flash-lite-preview` on 2026-04-06 (29593 input / 2139 output tokens). Source: Nature 2024, licence CC BY. Fields are rendered verbatim from the stored JSON; layout is added for display. `source_span` values are model-reported locators and are not machine-verified.

Supplemental Information 5 - Full run report for prompt: design novel inhibitors for pain receptors that are promising drug targets

Stage reports of one end-to-end run

Project `pain_receptors_rc1` · workflow `ppi`

> **Request, verbatim:** design novel inhibitors for pain receptors that are promising drug targets

Each pipeline stage writes one markdown report. The pages that follow reproduce those files in full, in stage order, as they were written to disk during the run; only typography has been added. Every report ends with a machine-readable `PIPELINE HANDOFF` block, which is what the next stage parses. Stages 0, 1, 2 and 28 are written by a language model; the others are written by code from measured values.

Stages

#	STAGE	KIND	PRODUCED BY
0	**Pathway**	LLM	pathway-expert `gemini-3.7-flash`, $0.13
1	**Literature**	LLM	molecular-biology-expert `gemini-3.7-flash`, $0.09
2	**Structure**	LLM	complex-structure-analysis `gemini-3.7-flash`, $0.09
20	**Target intel (bridged)**	code	composed in code from stages 0 to 2; no LLM call
22	**Trim**	code	structure_trim.py
23	**Binder spec**	code	foundry_spec.py
24	**Pilot**	code	foundry_runner.py (RFD3, solubleMPNN, RF3)
25	**Calibration gate**	code	campaign_calibration.py
26	**Production**	code	foundry_runner.py (RFD3, solubleMPNN, RF3)
27	**Scoring**	code	binder_metrics.py, binder_ranking.py
28	**Summary**	LLM	design-analyst `gemini-3.7-flash`, $0.02

Stage 21 (interface) is a byte-identical copy of stage 2, written by the bridge so the binder track can start from it; it is not repeated here.

0 Pathway

LLM stage pathway-expert · gemini-3.7-flash · $0.13 · `00_pathway.md`

PATHWAY BIOLOGY REPORT

DISEASE CONTEXT

- Disease / indication: Chronic and inflammatory nociceptive pain (including neurogenic inflammation and neuropathic hypersensitivity)
- Pathway(s) implicated: CGRP-CALCRL/RAMP1 signaling, NGF-TrkA-MAPK/PI3K pathway, Nav1.7 (SCN9A) voltage-gated sodium channel signaling
- Primary disease mechanism: Peripheral nociceptor activation triggers sustained release of neuropeptides (CGRP, Substance P) and neurotrophin signaling (NGF/TrkA), driving peripheral and central pain sensitization (10.1038/s41586-023-05753-x, Section: CGRP suppresses meningeal host defences, Para 1; 10.1371/journal.pgen.1004081, Section: Discussion, Para 4).
- Frequency of pathway dysregulation: Broadly co-expressed in ~60–70% of human DRG sensory nociceptors (10.1126/scitranslmed.abj8186).

PATHWAY MAP

- Upstream regulators: Pathogen toxins / tissue injury triggers, high insulin / neuroinflammatory stimuli, Nerve Growth Factor (NGF)
- Core cascade: Ligand engagement (CGRP or NGF) at cell-surface receptor complexes (CALCRL/RAMP1 or NTRK1 homodimer) drives PKA, MAPK/ERK, and PI3K signaling cascades, lowering activation thresholds of ion channels (TRPV1, Nav1.7, Nav1.8) and maintaining sustained nociceptive signaling.
- Key effectors / transcription factors: CREM, JDP2, TRPV1, SCN9A (Nav1.7)

DYSREGULATED NODES ASSESSMENT

CALCRL (Calcitonin receptor-like receptor)

- Pathway position: Class B GPCR receptor
- Dysregulation: Forms a functional heterodimeric complex with RAMP1 on sensory nociceptors and meningeal/immune cells, mediating neurogenic pain and neurovascular inflammation upon CGRP binding (10.1038/s41586-023-05753-x, Section: CGRP suppresses meningeal host defences, Para 1).
- Prior therapeutic strategies: Small molecule antagonists (olcegepant / BIBN4096) and monoclonal antibodies (erenumab).
- Suggested PDB structures: 6E3Y (Homo sapiens)
- Inferred PPI opportunity: Disrupts the extracellular domain (ECD) interaction between CALCRL and RAMP1 or blocks the extracellular CGRP binding cleft, terminating downstream pro-nociceptive PKA signaling.

RAMP1 (Receptor activity-modifying protein 1)

- Pathway position: Single-transmembrane accessory adaptor protein
- Dysregulation: Required for trafficking and presenting CALCRL as a high-affinity CGRP receptor; loss of RAMP1 attenuates neuroinflammatory signaling (10.1038/s41586-023-05753-x, Section: CGRP suppresses meningeal host defences, Para 1).
- Genetic dependency: Lyz2ΔRamp1 conditional knockout mice demonstrate marked attenuation of CGRP-mediated suppression and inflammation (10.1038/s41586-023-05753-x, Section: CGRP suppresses meningeal host defences, Para 3).
- Prior therapeutic strategies: Antagonist BIBN4096 and receptor-targeted biologics.
- Suggested PDB structures: 6E3Y (Homo sapiens)
- Inferred PPI opportunity: Direct disruption of the extracellular RAMP1-CALCRL heterodimer interface or CGRP neuropeptide engagement site.

NTRK1 (TrkA / High affinity nerve growth factor receptor)

- Pathway position: Receptor tyrosine kinase
- Dysregulation: Activated by elevated local NGF levels, driving retrograde MAPK/ERK and PI3K signaling to sensitize nociceptive terminals and upregulate TRPV1 (10.1021/acschembio.4c00300, Section: INTRODUCTION, Para 2; 10.1016/j.isci.2025.112047, Section: Introduction, Para 2).
- Genetic dependency: TrkAC knock-in and conditional optogenetic mouse models demonstrate decoupling of survival from peripheral nociceptive innervation and inflammatory pain hypersensitivity (10.1371/journal.pgen.1004081, Section: Replacing

TrkA with TrkAC supports survival of nociceptive neurons, Para 1).
- Prior therapeutic strategies: Anti-NGF neutralizing antibodies and Trk kinase inhibitors (10.1371/journal.pgen.1004081; 10.1016/j.isci.2025.112047).
- Suggested PDB structures: 1WWA (Homo sapiens)
- Inferred PPI opportunity: Disruption of the extracellular domain interaction between NGF and NTRK1 prevents receptor dimerization, autophosphorylation, and downstream nociceptive sensitization.

SCN9A (Nav1.7 voltage-gated sodium channel alpha subunit)

- Pathway position: Upstream voltage-gated channel / electrical transducer
- Dysregulation: Essential for setting neuronal firing thresholds; loss-of-function causes congenital insensitivity to pain (CIP), whereas hyperactivation leads to extreme pain disorders (10.1016/celrep.2013.12.033; 10.1038/ncomms9967).
- Genetic dependency: Nav1.7 knockout in adult mice reverses established mechanical allodynia in neuropathic pain models (10.1016/j.celrep.2013.12.033, Section: Deleting Nav1.7 in Adult Mice Reverses Neuropathic Pain, Para 1).
- Prior therapeutic strategies: Voltage-sensor and pore-blocking small molecules and peptide toxins (5O0U).
- Suggested PDB structures: Not found in corpus (transmembrane pore architecture poorly suited for soluble de novo protein binder interfaces).
- Inferred PPI opportunity: Insufficient evidence for accessible non-transmembrane extracellular PPI interfaces.

TARGET OPPORTUNITY LANDSCAPE

[VALIDATED] CALCRL / RAMP1

- **Evidence basis**: Heterodimerization of the Class B GPCR CALCRL with RAMP1 forms the canonical CGRP receptor; genetic ablation of Ramp1 and pharmacological antagonism via BIBN4096 demonstrate robust suppression of downstream inflammatory and pain signaling cascades (10.1038/s41586-023-05753-x, Section: CGRP suppresses meningeal host defences, Para 1).
- **What makes it attractive**: The extracellular domain (ECD) presents a well-defined, fully solvent-exposed protein-protein interface that is clinically validated for therapeutic protein binders (e.g., erenumab).
- **Key uncertainty**: RAMP paralog cross-reactivity (RAMP2 and RAMP3 form adrenomedullin receptors with CALCRL) requires selective interface engagement.
- **Suggested PDB ID(s)**: 6E3Y (Homo sapiens)

[VALIDATED] NTRK1 / NGF

- **Evidence basis**: Extracellular binding of NGF to NTRK1 (TrkA) drives nociceptor terminal sensitization via PI3K and MAPK pathways; antibody-mediated neutralization of NGF or genetic replacement of the TrkA signaling domain abolishes chemical and mechanical inflammatory pain behaviors (10.1371/journal.pgen.1004081; 10.1016/j.isci.2025.112047, Section: Inhibition of nerve growth factor-tropomyosin receptor kinase A-phosphoinositide-3-kinase signaling suppresses sensory hypersensitivity in the skin of diet-induced obesity mice, Para 1).
- **What makes it attractive**: High-affinity extracellular protein-protein interaction readily accessible to engineered mini-proteins and biologics without membrane permeability constraints.
- **Key uncertainty**: Systemic TrkA/NGF pathway blockade can induce joint-related adverse events (e.g., rapidly progressive osteoarthritis) observed in anti-NGF antibody clinical trials.
- **Suggested PDB ID(s)**: 1WWA (Homo sapiens)

[BIOLOGICALLY JUSTIFIED] SCN9A (Nav1.7)

- **Evidence basis**: Conditional knockout in sensory and sympathetic neurons reverses neuropathic allodynia; human genetic validation confirms its non-redundant role in pain transduction (10.1016/j.celrep.2013.12.033; 10.1038/ncomms9967).
- **What makes it attractive**: Central gatekeeper of action potential generation in peripheral nociceptors.
- **Key uncertainty**: Target site is located within intramembrane pore loops and voltage-sensor domains, which are inaccessible to soluble designed protein binders in solution.
- **Suggested PDB ID(s)**: Not found in corpus

PRIMARY RECOMMENDATION

CALCRL / RAMP1 (the CGRP receptor heterodimer complex) is the primary recommendation for binder design. It features a fully solvent-exposed extracellular domain (ECD) interface that avoids the membrane-burial pitfalls of channel targets like Nav1.7 and

TRPV1, has validated clinical efficacy in pain and neurovascular inflammation, and is resolved at high resolution in a human cryo-EM structure (PDB 6E3Y).

- **Target complex**: CALCRL / RAMP1
- **Evidence tier**: [VALIDATED]
- **Suggested PDB ID(s)**: 6E3Y (Homo sapiens)
- **Structure organism**: Homo sapiens
- **Proposed next step**: Run complex-structure-analysis on PDB 6E3Y

REDUNDANCY AND RESISTANCE RISKS

- Functional compensation by other sensory channel subtypes (e.g., Nav1.8, TRPA1, TRPM8) in distinct pain modalities (10.1016/j.celrep.2013.12.033).
- Differential expression across male and female sensory nociceptors where CGRP/CALCA transcripts display sex-biased abundance (10.1126/scitranslmed.abj8186).
- Endogenous opioid transcriptional upregulation observed upon prolonged sodium channel or sensory pathway blockade (10.1038/ncomms9967).

CORPUS COVERAGE

- Papers analysed: 8 fingerprints from 20 search hits
- Fallback used: No
- Expansion round: Yes — terms used: CALCRL, RAMP1, NTRK1, NGF; added 3 new fingerprints
- Critical gaps: High-resolution human co-complex structures of full-length ion channel extracellular loops remain limited compared to Class B GPCR ECDs.

PATHWAY SOURCES

#	TITLE (TRUNCATED TO 60 CHARS)	DOI	KEY NODE
1	Nociceptors control bacterial meningitis	10.1038/s41586-023-05753-x	CALCRL / RAMP1
2	Uncoupling of NGF-dependent survival and axon growth in nocic	10.1371/journal.pgen.1004081	NTRK1
3	Opto-iTrkA Enables Light-Inducible and Reversible Mechanical	10.1021/acschembio.4c00300	NTRK1 / TrkA
4	Diet-induced obesity leads to painful small fiber neuropathy	10.1016/j.isci.2025.112047	NTRK1 / NGF
5	Peripheral Nerve Injury and Cancer-Induced Bone Pain Rely on	10.1016/j.celrep.2013.12.033	Nav1.7 / Nav1.8
6	A spatial transcriptomic map of the human dorsal root gangli	10.1126/scitranslmed.abj8186	CALCA / TRPV1
7	Endogenous opioids contribute to insensitivity to pain in hu	10.1038/ncomms9967	Nav1.7

PIPELINE HANDOFF

- pdb_id: 6E3Y
- structure_organism: Homo sapiens
- target_complex: CALCRL / RAMP1
- design_intent: disrupt
- structure_query: Analyze PDB 6E3Y (Homo sapiens) at data/structures/6E3Y.cif. Target complex: CALCRL / RAMP1. Identify hotspot residues for binder design.
- choices_json: [{"tier":"VALIDATED","complex":"CALCRL / RAMP1","pdb_ids":["6E3Y"],"evidence_basis":"Heterodimerization of CALCRL with RAMP1 forms the functional CGRP receptor mediating neurogenic pain and inflammation.","key_uncertainty":"Selectivity over other RAMP family members (RAMP2/RAMP3).","design_intent":"disrupt"},{"tier":"VALIDATED","complex":"NTRK1 / NGF","pdb_ids":["1WWA"],"evidence_basis":"NGF-TrkA extracellular signaling drives peripheral sensitization and inflammatory pain in vivo.","key_uncertainty":"Systemic side effects associated with joint health upon long-term neurotrophin blockade.","design_intent":"disrupt"},{"tier":"BIOLOGICALLY_JUSTIFIED","complex":"SCN9A (Nav1.7)","pdb_ids":[],"evidence_basis":"Genetic loss of SCN9A confers congenital insensitivity to pain in humans and reverses neuropathic pain in mice.","key_uncertainty":"Intramembrane channel pore topology is largely inaccessible to soluble de novo protein binders.","design_intent":"disrupt"}]

MODEL PROVENANCE

- skill: `pathway-expert`
- written by: **gemini:gemini-3.7-flash** — the model the operator selected. LPT never substitutes a model on its own; a stage a safety classifier declines ends the run.

CITATION VERIFICATION

- Citations checked: 8
- Verified in corpus: 7
- **NOT IN CORPUS (1):** 10.1016/celrep.2013.12.033

STRUCTURE SUBSTITUTION (deterministic, post-stage)

This report recommends **6E3Y**. The pipeline designed against **3N7S** instead.

- **Why:** 6E3Y carries 4 scaffolding chain(s) (nanobody / G protein / fusion partner) against 0 in 3N7S, at no worse resolution (2.1 A vs 3.3 A)
- **Decided by:** `_select_designable_structure`, between the pathway and literature stages — structure choice has to be settled before the structure stage analyses anything, because its hotspots then refer to those coordinates.
- **Both entries contain the requested proteins.** The switch only fires on a measurable defect in the chosen one: partner absent, target chain a fusion construct, or materially more scaffolding at no better resolution.
- **To keep the original:** re-run with `--pdb 6E3Y`.

The reasoning above is the pathway stage's own, on the evidence it had, and is left unedited.

1 Literature

LLM stage molecular-biology-expert · gemini-3.7-flash · $0.09 · `01_literature.md`

MOLECULAR BIOLOGY REPORT

COMPLEX OVERVIEW

- Target complex: CALCRL / RAMP1
- Indication organism: Homo sapiens
- Cited structures:
- 3N7S — Homo sapiens — human CALCRL / RAMP1 extracellular domain (ECD) heterodimer (primary design structure)
- 4RWF — Homo sapiens — human CALCRL / RAMP1 ECD heterodimer complexed with CGRP peptide
- 6E3Y — Homo sapiens — full-length human active CGRP receptor heterodimer complexed with Gs heterotrimer
- Disease context: Chronic and inflammatory nociceptive pain / neurogenic inflammation
- Biological role: CALCRL (a Class B GPCR) obligatorily heterodimerizes with the single-pass transmembrane accessory protein RAMP1 to form the high-affinity CGRP receptor, transducing sensory neuropeptide signaling into intracellular cAMP/PKA activation in peripheral nociceptors and meningeal immune cells.
- Drug target validation: Genetic ablation of RAMP1 in myeloid cells (Lyz2ΔRamp1) and pharmacological antagonism by small-molecule antagonists (BIBN4096 / olcegepant) or antibodies significantly attenuate neurogenic inflammation, bacterial meningeal invasion, and pain hypersensitivity in vivo (10.1038/s41586-023-05753-x, Section: CGRP suppresses meningeal host defences, Para 1–3).
- Papers analysed: 5 full fingerprints from 21 total search hits

KNOWN INHIBITORS AND PRIOR ART

Small-Molecule CGRP Receptor Antagonists (Gepants: Olcegepant, Telcagepant, Rimegepant, Ubrogepant)

- Modality: Small-molecule non-peptide antagonists
- Best affinity: Subnanomolar to low nanomolar affinity (e.g., olcegepant Ki ~ 0.2–1 nM; compound (R)-25 analogues pIC50 = 9.2 in TR-FRET cAMP assays)
- Source: 10.1021/acs.jmedchem.0c02191, Section: Design and SAR, Para 6; 10.1038/s41586-023-05753-x, Section: CGRP suppresses meningeal host defences, Para 1
- Key residues engaged: Extracellular binding cleft formed at the CALCRL:RAMP1 interface; exploits RAMP1 Trp74 (W74) and adjacent pocket-lining residues
- Limitations: Oral bioavailability challenges in early generation (olcegepant required IV infusion); high synthetic complexity; small-molecule selectivity vs RAMP2/RAMP3

Monoclonal Antibodies (Erenumab, Galcanezumab, Fremanezumab, Eptinezumab)

- Modality: Monoclonal antibody (mAb) / antibody fragments
- Best affinity: Picomolar to low nanomolar Kd (< 1 nM)
- Source: 10.1021/acs.jmedchem.0c02191, Section: Introduction, Para 1
- Key residues engaged: Erenumab specifically engages the extracellular domain (ECD) epitope of the CALCRL/RAMP1 complex (specifically RAMP1 ECD loops F83/W84/P85)
- Limitations: High molecular weight (>150 kDa), inability to cross the blood-nerve / blood-brain barrier efficiently, parenteral delivery requirement

CGRP Peptide-Derived Antagonists and Mimetics (CGRP8-37 and C-terminal Fragments)

- Modality: Truncated linear and constrained peptide mimetics
- Best affinity: Low-to-mid nanomolar Kd (~10–100 nM)
- Source: 10.1016/j.molcel.2015.04.018, Section: Structures of the CGRPmut-Bound CLR:RAMP1 and AM-Bound CLR:RAMP2 ECD Heterodimers, Para 2
- Key residues engaged: CGRP C-terminal turn residues (Phe37) docking into the RAMP1-augmented CALCRL ECD pocket near RAMP1 F83, W84, and P85
- Limitations: Susceptible to proteolytic degradation, short in vivo circulating half-life

TARGET-SITE INSIGHTS FROM LITERATURE

Confirmed key residues (mutagenesis / structural data)

The functional CGRP-binding pocket is a composite epitope formed by the extracellular domain (ECD) of CALCRL and the extracellular domain of RAMP1. *Note on membrane protein topology filter:* Only solvent-exposed extracellular domain (ECD) residues accessible to a soluble de novo binder in solution are selected. Mechanistically important transmembrane residues (such as CALCRL TM domain residues W254, Y255, and H295) are located within the lipid bilayer and are explicitly excluded from the binder design target site.

RESIDUE	PROTEIN	ROLE / EFFECT	METHOD	SOURCE (DOI, SPAN)
W84	RAMP1	Anchors CGRP peptide C-terminal turn; critical for composite ECD pocket formation	X-ray crystallography (1.8–2.5 Å)	10.1016/j.molcel.2015.04.018, Section: Structures of the CGRPmut-Bound CLR:RAMP1, Para 2
F83	RAMP1	Direct contact with CGRP C-terminus; essential for CGRP receptor ECD complex presentation	Cryo-EM (3.3 Å) & X-ray	10.1038/s41586-018-0535-y, Page 5, Para 1; 10.1016/j.molcel.2015.04.018
P85	RAMP1	Defines the C-terminal CGRP anchoring loop on the extracellular surface of RAMP1	Cryo-EM (3.3 Å) & structural analysis	10.1038/s41586-018-0535-y, Page 5, Para 1
W74	RAMP1	Defines RAMP1 selectivity over RAMP3 (Glu74); major hydrophobic contact for antagonists	Molecular docking / SAR mutagenesis	10.1021/acs.jmedchem.0c02191, Section: Design and SAR, Para 6

Pathway / DepMap context

- Co-functional cluster: RAMP1 belongs to Cluster 6 (size: 27 members; hub: ROCK1; top co-members: RAC1, RHOA, PAK1, CDC42, GNA13), reflecting G-protein coupled receptor cytoskeletal and migration signaling.
- Genetic codependency: CALCRL / RAMP1 Chronos CRISPR essentiality correlation r = 0.018 (DepMap, n = 1208 cell lines). The near-zero DepMap correlation is characteristic of tissue-specific, non-cell-autonomous neurosensory GPCR pathways that do not govern pan-cancer proliferative fitness in transformed monocultures.

FEASIBILITY ASSESSMENT

- Target tractability / informativeness: Excellent
- Human extracellular domain heterodimer structure is solved at high resolution (PDB 3N7S, 2.1 Å; PDB 4RWF, 1.8 Å; and active full-length cryo-EM PDB 6E3Y, 3.3 Å).
- Multiple literature-validated extracellular interface hotspots are confirmed (RAMP1 F83, W84, P85, W74).
- Robust modality precedent exists spanning small molecules (gepants), peptide antagonists (CGRP8-37), and approved therapeutic antibodies (erenumab).
- Corpus confidence: High (5 full fingerprints analyzed, consistent structural and biochemical findings across multiple peer-reviewed studies).
- Design challenges:
- **Paralog selectivity**: RAMP1 shares sequence homology with RAMP2 and RAMP3, which pair with CALCRL to form adrenomedullin receptors (AM1 and AM2). The designed binder must exploit RAMP1-specific ECD residues (notably Trp74 and Phe83/Trp84) to avoid off-target adrenomedullin receptor blockade.
- **Membrane exclusion**: The binder must target the solvent-exposed extracellular domain (ECD) heterodimer interface (PDB 3N7S) without attempting to engage intramembrane helices.
- Missing data gaps: High-resolution structures of de novo engineered mini-proteins in complex with the CALCRL/RAMP1 ECD are not yet available; design relies on mimicking the binding modes of endogenous CGRP C-terminus and clinical antibody erenumab.

DESIGN RECOMMENDATIONS

- Suggested modality: mini_protein — offers high thermal stability, shape complementarity to the composite ECD cleft, and potential for potent, selective disruption of the CALCRL/RAMP1 interaction without requiring large immunoglobulin frameworks.
- Residues to prioritise: RAMP1 F83, W84, P85, and W74 (extracellular domain composite interface).
- Residues to avoid: Intramembrane and juxtamembrane residues (e.g., CALCRL W254, Y255, H295), which cannot be engaged by a soluble binder in aqueous solution.
- Epitope to mimic: The C-terminal turn of CGRP (Phe37 capping turn) and the extracellular cleft engaged by erenumab and gepant small-molecule antagonists.
- Affinity target: Aim for <= 30 nM Kd, peptide-binding heuristic for druggable PPIs (Rule 2: VALIDATED tier from pathway analysis).
- Key risk: Achieving strict selectivity for RAMP1 over RAMP2/RAMP3 while burying sufficient extracellular surface area on the CALCRL:RAMP1 heterodimer interface.

LITERATURE SOURCES (max 8 rows)

#	TITLE (TRUNCATED TO 60 CHARS)	DOI	STUDY TYPE	SCORE	KEY FINDING
1	Structural Basis of Peptide Selectivity and Receptor Activat	10.1016/j.molcel.2015.04.018	experimental_structural	0.704	Resolves CLR:RAMP1 ECD complex and turn-like CGRP C-terminal binding mode involving RAMP1 W84.
2	Allosteric modulation of the calcitonin receptor by receptor	10.1038/celldisc.2016.12	experimental_in_vitro	0.663	RAMP1 allosterically reconfigures Class B GPCR ECD peptide binding pockets.
3	Cryo-EM structure of the active, Gs-protein complexed, human	10.1038/s41586-018-0535-y	experimental_structural	0.646	Full-length 3.3 Å structure showing RAMP1 F83-P85 ECD engagement with CGRP C-terminus.
4	Adrenomedullin Receptor-RAMP Interactions Modulate the Confor	10.1074/jbc.M115.688218	experimental_in_vitro	0.588	RAMP-specific interactions alter CLR binding pocket topography and volume.
5	Nociceptors control bacterial meningitis	10.1038/s41586-023-05753-x	experimental_in_vivo	0.560	Genetic and pharmacological blockade of CALCRL/RAMP1 suppresses inflammatory injury.
6	Development of First-in-Class Small Molecule Antagonists for	10.1021/acs.jmedchem.0c02191	experimental_in_vitro	0.509	Explores RAMP1 vs RAMP3 pocket differences (Trp74 vs Glu74) for selective antagonism.

PIPELINE HANDOFF

- target_complex: CALCRL / RAMP1
- design_intent: disrupt
- structure_organism: Homo sapiens
- ortholog_of_human: NONE
- tractability: Excellent
- go_recommendation: GO
- go_rationale: The extracellular domain heterodimer interface of human CALCRL/RAMP1 is solved at high resolution in PDB 3N7S with well-validated extracellular hotspots (RAMP1 F83, W84, P85, W74) and established clinical modality precedent.
- modality: mini_protein
- target_site_hint: {"mode":"ppi_interface","target_protein":"RAMP1","priority_residues":["F83","W84","P85","W74"],"notes":"Extracellular domain (ECD) residues forming the composite CGRP binding cleft; canonical human RAMP1 numbering in PDB 3N7S/4RWF; intramembrane residues explicitly excluded"}
- design_query: Generate mini_protein design inputs for CALCRL / RAMP1, PDB 3N7S. Priority hotspots: RAMP1 F83, W84, P85, W74. Affinity target: <= 30 nM Kd. Focus on the extracellular domain composite interface.

MODEL PROVENANCE

- skill: `molecular-biology-expert`
- written by: **gemini:gemini-3.7-flash** — the model the operator selected. LPT never substitutes a model on its own; a stage a safety classifier declines ends the run.

CITATION VERIFICATION

- Citations checked: 6
- Verified in corpus: 6
- All cited DOIs verified against fingerprint store.

2 Structure

LLM stage complex-structure-analysis · gemini-3.7-flash · $0.09 · `02_structure.md`

PPI ANALYSIS REPORT

COMPLEX OVERVIEW

- Structure: /home/m.uckelmann_cbs-niob.local/code/little-protein-tiger/data/structures/3N7S_ba1.cif (PDB 3N7S)
- Structure source: experimental (X-ray)
- Source organism: Homo sapiens
- Assembly: 1:1 heterodimer — Chain D (RAMP1 ECD, 84 aa) and Chain A (CALCRL / CLR ECD, 94 aa) complexed with antagonist olcegepant (Chain E); analysed D/A as the representative interface.
- Chain A: A (Calcitonin gene-related peptide type 1 receptor / CALCRL ECD)
- Chain B: D (Receptor activity-modifying protein 1 / RAMP1 ECD)
- Design mode: DISRUPT
- BSA total: 2385.4 Å²
- H-bonds across interface: 17
- Interface residues: 21 on chain A, 25 on chain D (excluding solvent/ligand)
- Design modality: mini_protein (the operator selects the modality at kickoff; the compact, deep aromatic groove on RAMP1 would also suit a cyclic peptide)

CHAIN A INTERFACE RESIDUES

Chain A: Hydrophobic: MET42, ILE52, MET53, GLY71 | Aromatic: TYR46, TYR49, TRP69 | Charged: ARG38, GLU47, LYS51, ASP70, ARG119 | Polar: ASN39, THR43, GLN45, GLN50, GLN54, THR68, SER117, ASN118, THR120

CHAIN B INTERFACE RESIDUES

Chain D: Hydrophobic: ILE63, ALA70, PRO85, VAL89, LEU94, GLY98, PRO105, ILE106, GLY108 | Aromatic: TRP59, TYR66, TRP74, PHE83, TRP84, PHE93, HIS97, PHE101 | Charged: ARG67, GLU68, ASP71, ASP90, ARG102 | Polar: ASN86, CYS104, SER107

H-BONDS AT INTERFACE (top 12 by distance)

DONOR	DONOR ATOM	ACCEPTOR	ACCEPTOR ATOM	DISTANCE (Å)
D:ASP90	OD1	A:TYR49	OH	2.61
D:ASP90	OD2	A:THR68	OG1	2.64
D:HIS97	ND1	A:GLN50	OE1	2.76
D:ASP71	OD2	A:3N6:1	N1	2.87
D:GLY108	N	A:GLU47	OE1	2.93
D:TRP59	NE1	A:THR43	OG1	3.01
D:PRO105	O	A:GLN50	NE2	3.05
D:PHE101	O	A:GLN50	NE2	3.12
D:ARG67	O	A:HOH202	O	3.04
D:ASP90	OD1	A:HOH220	O	2.86
D:HOH200	O	A:TYR46	OH	2.86
D:HOH201	O	A:TYR46	OH	2.96

HOTSPOT REGIONS (top 2, ranked by suitability)

Region 1: CGRP Binding Cleft & ECD Core Patch — Excellent

- Residues: TRP74, PHE83, TRP84, PRO85, ASP90, PHE93, LEU94, HIS97, PHE101, ILE106
- BSA contributions (Å²): TRP74: 77.8, PHE83: 84.4, TRP84: 76.9, PRO85: 43.5, ASP90: 70.3, PHE93: 25.4, LEU94: 64.8, HIS97: 75.1, PHE101: 21.6, ILE106: 100.0
- Hydrophobic fraction: 0.90
- Spatial spread (Cα RMSD): 9.85 Å
- Mean KD hydrophobicity: 0.66

- Partner contacts: CALCRL residues TYR46, GLU47, TYR49, GLN50, ILE52, MET53, GLN54, THR68, TRP69, GLY71, SER117, ASN118, ARG119
- Literature evidence: 10.1016/j.molcel.2015.04.018, 10.1038/s41586-018-0535-y, 10.1021/acs.jmedchem.0c02191
- Design note: Forms the primary composite CGRP binding cleft and core heterodimerization surface on RAMP1 ECD. Trp74, Phe83, Trp84, and Pro85 provide high aromatic density for peptide ligand docking and antagonist engagement, while Asp90, His97, and Ile106 anchor deep polar and hydrophobic contacts with CALCRL helix loops.
- Separability: Primary target region.

Region 2: N-terminal Interhelical Extension — Good

- Residues: TRP59, ILE63, TYR66, ARG67, ALA70, ASP71
- BSA contributions (Å²): TRP59: 62.3, ILE63: 36.2, TYR66: 51.6, ARG67: 72.0, ALA70: 28.8, ASP71: 38.6
- Hydrophobic fraction: 0.67
- Spatial spread (Cα RMSD): 8.42 Å
- Mean KD hydrophobicity: -0.87
- Partner contacts: CALCRL residues ARG38, ASN39, MET42, THR43, GLN45, TYR46
- Literature evidence: 10.1016/j.molcel.2015.04.018
- Design note: Secondary interhelical contact zone flanking the N-terminal alpha-helical segment of RAMP1 ECD that interacts with the N-terminal cap of the CALCRL ECD.
- Separability: Combined with Region 1 feasible (contiguous surface along the ECD interface).

DESIGN RECOMMENDATIONS

- Design mode: DISRUPT
- Recommended modality: mini_protein (default; the compact, aromatic-rich Region 1 cleft on RAMP1 ECD is also highly suitable for a cyclic peptide)
- Primary target: Region 1 (CGRP Binding Cleft & ECD Core Patch, Excellent)
- Key chain A residues: TYR46, GLU47, TYR49, GLN50, MET53 (CALCRL contacts)
- Key chain B residues: TRP74, PHE83, TRP84, PRO85, ASP90, LEU94, HIS97, PHE101, ILE106 (RAMP1 target hotspots)
- Confidence / B-factors: pLDDT not applicable — experimental structure (B-factors in file)
- Caveats: PDB 3N7S contains the small-molecule antagonist olcegepant (BIBN4096BS, Chain E) bound at the interface between CALCRL and RAMP1; binder design targeting RAMP1 Region 1 directly mimics the steric blockage achieved by small-molecule CGRP antagonists.

MODEL-READY HOTSPOTS [DISRUPT]

Target chain D — Region 1: CGRP Binding Cleft & ECD Core Patch — selected 10 of 16 interface residues:

RESIDUE	AUTH_SEQ_ID	LABEL_SEQ_ID	RFD3 SIDECHAIN ATOMS
TRP	74	53	CD2,NE1
PHE	83	62	CD2,CZ
TRP	84	63	CD2,NE1
PRO	85	64	CG,CD
ASP	90	69	CG,OD1
PHE	93	72	CD2,CZ
LEU	94	73	CD1,CD2
HIS	97	76	ND1,NE2
PHE	101	80	CD2,CZ
ILE	106	85	CD1,CG2

BoltzGen binding

binding: 53,62,63,64,69,72,73,76,80,85

RFD3 select_hotspots

select_hotspots: D74: CD2,NE1 D83: CD2,CZ D84: CD2,NE1 D85: CG,CD D90: CG,OD1 D93: CD2,CZ D94: CD1,CD2 D97: ND1,NE2 D101: CD2,CZ D106: CD1,CG2

PIPELINE HANDOFF

- pdb_id: 3N7S
- chain_a: A
- chain_b: D
- target_chain: D
- partner_chain: A
- target_complex: CALCRL / RAMP1
- structure_organism: Homo sapiens
- design_intent: disrupt
- modality: mini_protein
- bsa_A2: 2385
- tractability: Excellent
- literature_query: Search for published peptide antagonists and mutagenesis data for CALCRL/RAMP1. Cross-reference hotspot residues W74, F83, W84, P85, D90, H97, I106 on RAMP1.

MODEL PROVENANCE

- skill: `complex-structure-analysis`
- written by: **gemini:gemini-3.7-flash** — the model the operator selected. LPT never substitutes a model on its own; a stage a safety classifier declines ends the run.

CITATION VERIFICATION

- Citations checked: 3
- Verified in corpus: 3
- All cited DOIs verified against fingerprint store.

20 Target intel (bridged)

deterministic composed in code from stages 0 to 2; no LLM call · `binder/20_target_intel.md`

Target intelligence (bridged from PPI literature)

Structure substituted: the pathway stage recommended 6E3Y; this campaign was designed against 3N7S instead — 6E3Y carries 4 scaffolding chain(s) (nanobody / G protein / fusion partner) against 0 in 3N7S, at no worse resolution (2.1 A vs 3.3 A). Re-run with `--pdb 6E3Y` to keep the original.

Bridged from the PPI track's pathway/literature/structure stages for CALCRL / RAMP1 — see 00_pathway.md / 01_literature.md / 02_structure.md for the full reasoning. This file exists only so foundry's own stage machine has a target_intel artifact to resume from; no LLM call was made to produce it.

PIPELINE HANDOFF

- pdb_id: 3N7S
- target_gene: RAMP1
- target_uniprot: O60894
- partner_name: CALCRL
- target_chain: D
- partner_chain: A
- design_intent: disrupt
- modality: mini_protein
- binder_length_min: 70
- binder_length_max: 86
- interface_rationale: The extracellular domain heterodimer interface of human CALCRL/RAMP1 is solved at high resolution in PDB 3N7S with well-validated extracellular hotspots (RAMP1 F83, W84, P85, W74) and established clinical modality precedent.
- go_recommendation: GO

22 Trim

deterministic structure_trim.py · `binder/22_trim.md`

Target trimming

- Method: **geometric**
- Topology: the modelled construct is entirely extracellular (92 residues) — no restriction needed
- Residues: 84 -> 84 in 1 segment(s) [(27, 110)]
- Interface area of the kept residues retained: 100.0%
- Hotspots kept: 10/10

PIPELINE HANDOFF

- trimmed_structure: /home/m.uckelmann_cbs-niob.local/code/little-protein-tiger/projects/pain_receptors_rc1/runs/round-1/binder/trim/trimmed.cif
- trim_map: /home/m.uckelmann_cbs-niob.local/code/little-protein-tiger/projects/pain_receptors_rc1/runs/round-1/binder/trim/trim_map.json
- contig: 70-86,/0,D27-110
- n_segments: 1
- n_residues: 84

23 Binder spec

deterministic foundry_spec.py · `binder/23_binder_spec.md`

RFD3 design specification

Contig `70-86,/0,D27-110` with 10 atom-level hotspot(s): D101, D106, D74, D83, D84, D85, D90, D93, D94, D97.

PIPELINE HANDOFF

- spec_path: /home/m.uckelmann_cbs-niob.local/code/little-protein-tiger/projects/pain_receptors_rc1/runs/round-1/binder/spec/ramp1_binder_001.json
- design_name: ramp1_binder_001

24 Pilot

deterministic foundry_runner.py (RFD3, solubleMPNN, RF3) · `binder/24_pilot.md`

Pilot campaign

stage done RFD3 100/100 (100.0%) prefilter 88 MPNN 352 RF3 352/352 (100.0%) free disk 129 GB job pid 3444268 · running · 0.93 h elapsed

PIPELINE HANDOFF

- campaign_dir: /home/m.uckelmann_cbs-niob.local/code/little-protein-tiger/projects/pain_receptors_rc1/runs/round-1/binder/campaign/pilot
- n_rfd3: 100
- n_filtered: 88
- n_mpnn: 352
- n_rf3: 352
- prefilter_rate: 0.88
- free_gb: 128.7

25 Calibration gate

deterministic campaign_calibration.py · `binder/25_calibration.md`

Campaign calibration

Goal: **50 designs** meeting all hard gates AND iptm > 0.85. Bar raised from the requested iptm > 0.7 to iptm > 0.85 — this trial supports it within budget.

Sample: 2,152 refolds from 538 RFD3 backbones (4 sequences each, prefilter kept 93%).

Hit rate

UNIT	HITS	N	RATE	95% INTERVAL
backbone	88	538	16.36%	13.47% – 19.72%
refold	438	2,152	20.35%	18.71% – 22.11%

Backbones are the sizing unit: `n_batches` controls backbones, and the 4 sequences sharing one are correlated, not independent trials.

Required scale

```
point estimate             ~ 330 designs / 1,223 refolds  ->  3 GPU-h, 1 GB
Wilson 95% lower bound     ~ 400 designs / 1,485 refolds  ->  4 GPU-h, 1 GB
```

Yield at softer bars

```
survivors (all hard gates)       622  (28.90% of refolds)
iptm > 0.5                       622  (28.90% of refolds)
iptm > 0.6                       545  (25.33% of refolds)
iptm > 0.65                      484  (22.49% of refolds)
iptm > 0.7                       438  (20.35% of refolds)
iptm > 0.75                      361  (16.78% of refolds)
iptm > 0.8                       270  (12.55% of refolds)
iptm > 0.85                      143  ( 6.64% of refolds)
```

```
best iptm, any refold:  0.9338
best iptm, a survivor:  0.9338
strictest bar this sample can size a campaign at: iptm > 0.85
```

Gate attribution

```
input:     2,152
survivors: 622

dropped by first failing criterion:
```

no clash 571 iptm >= 0.5 497 binder_rmsd_dock <= 5 432 binder_rmsd_fold <= 2 28 hotspot_engagement >= 0.75 2

```


passing each criterion alone:
```

binder_rmsd_dock <= 5 1,720 (79.9%) epitope_recall >= 0.5 2,111 (98.1%) hotspot_engagement >= 0.75 2,127 (98.8%) binder_rmsd_fold <= 2 2,048 (95.2%) binder_plddt >= 0.75 2,141 (99.5%) iptm >= 0.5 1,227 (57.0%) iface_pae <= 15 1,585 (73.7%) no clash 1,057 (49.1%)

Verdict: SCALE_UP

88/538 backbones produced an excellent design (16.36%, 95% CI 13.47%-19.72%). Even at the pessimistic bound the run costs ~4 GPU-h / 1 GB, inside the 120 h / 120 GB budget. This target is unusually good — the trial supports sizing at iptm > 0.85 (requested was 0.7) within budget, so the bar was raised rather than sizing to the loosest workable target.

Where to run it

```
local  (1 GPU)              ~4.0 h
cluster (8 GPUs, parallel)   ~0.5 h (rough — different refold backend/hardware)
```

Decision: local. Fits the 48 h local budget — running on this workstation's GPU.

26 Production

deterministic foundry_runner.py (RFD3, solubleMPNN, RF3) · `binder/26_production.md`

Production campaign

stage done RFD3 400/400 (100.0%) prefilter 349 MPNN 1,396 RF3 1,396/1,396 (100.0%) free disk 126 GB job pid 3623604 · done · 3.73 h elapsed

PIPELINE HANDOFF

- campaign_dir: /home/m.uckelmann_cbs-niob.local/code/little-protein-tiger/projects/pain_receptors_rc1/runs/round-1/binder/campaign/production
- n_rfd3: 400
- n_filtered: 349
- n_mpnn: 1396
- n_rf3: 1396
- prefilter_rate: 0.8725
- free_gb: 126.0

27 Scoring

deterministic binder_metrics.py, binder_ranking.py · `binder/27_scoring.md`

Design scoring and ranking

Scored **1,396** refolds from the production campaign.

```
input:     1,396
survivors: 351

dropped by first failing criterion:
```

no clash 423 binder_rmsd_dock <= 5 316 iptm >= 0.5 295 binder_rmsd_fold <= 2 11

```

passing each criterion alone:
```

binder_rmsd_dock <= 5 1,080 (77.4%) epitope_recall >= 0.5 1,362 (97.6%) hotspot_engagement >= 0.75 1,384 (99.1%) binder_rmsd_fold <= 2 1,334 (95.6%) binder_plddt >= 0.75 1,392 (99.7%) iptm >= 0.5 803 (57.5%) iface_pae <= 15 1,010 (72.3%) no clash 639 (45.8%)

```

```

351 survivors across 195 distinct backbones; top 20 selected.

Rosetta interface metrics computed for 299 of 351 gated designs (1 failed). They enter the composite only here — never the gate.

PIPELINE HANDOFF

- scores_csv: /home/m.uckelmann_cbs-niob.local/code/little-protein-tiger/projects/pain_receptors_rc1/runs/round-1/binder/scoring/refold_scores.csv
- top_k_csv: /home/m.uckelmann_cbs-niob.local/code/little-protein-tiger/projects/pain_receptors_rc1/runs/round-1/binder/scoring/top_k.csv
- n_scored: 1396
- n_survivors: 351

28 Summary

LLM stage design-analyst · gemini-3.7-flash · $0.02 · `binder/28_summary.md`

1. Executive verdict

GO. This RAMP1 binder campaign shows exceptional computational convergence, with rank-1 design `ramp1_binder_001_ramp1_binder_001_9_model_0_b0_d1` achieving an ipsae_min of 0.755, an iPTM of 0.894, and an interface PAE of 3.20 Å while docking within 0.915 Å of its designed backbone pose. Across the entire top-K, 100% of the 10 declared CALCRL-interface hotspots are engaged, binder pLDDT values consistently exceed 0.83, and docking RMSDs remain sub-2.0 Å. The trial's high success rate (16.36% yield of top-tier refolds) justifies advancing the leading candidates directly to in-silico validation and biophysical characterisation.

2. Quality of the top-K

MMR	NAME	COMP	IPSAE_MIN	IPTM	DOCK (Å)	IPAE (Å)	B_PLDDT	HS_ENG	STRONGEST	WEAKEST
1	`ramp1_binder_001_ramp1_binder_001_9_model_0_b0_d1`	15.029	0.755	0.894	0.915	3.20	0.834	1.0	composite_score (15.03)	binder_plddt (0.834)
2	`ramp1_binder_001_ramp1_binder_001_32_model_3_b0_d3`	12.768	0.778	0.913	0.750	2.92	0.840	1.0	iptm (0.913) / iface_pae (2.92 Å)	length (71 aa)
3	`ramp1_binder_001_ramp1_binder_001_11_model_3_b0_d1`	13.687	0.674	0.905	1.152	3.11	0.854	1.0	binder_plddt (0.854)	ipsae_min (0.674)
4	`ramp1_binder_001_ramp1_binder_001_34_model_2_b0_d2`	14.189	0.677	0.880	0.842	3.24	0.848	1.0	fold/dock alignment (0.416/0.842 Å)	ipsae_min (0.677)
5	`ramp1_binder_001_ramp1_binder_001_56_model_3_b0_d2`	10.735	0.668	0.872	0.566	3.53	0.847	1.0	dock RMSD (0.566 Å)	composite_rank (14)

3. Methodological red flags

No red flags identified.

- **Pose fidelity & geometry**: All top-5 candidates refold within 1.2 Å RMSD_dock of their generative design pose (sub-0.6 Å for ranks 5 and 7), confirming that high iPTM and low interface PAE reflect precise targeting rather than off-target docking artifacts.
- **Epitope & hotspot recall**: Hotspot engagement is 1.0 (10/10 declared target residues contacted) across all top-20 designs, with epitope recall >= 0.96 in the top 5.
- **Diversity**: Backbone families are unique across the top-K with pairwise sequence identity consistently low (`mmr_max_similarity` <= 0.36 across the top 5), avoiding local minimum traps. Lengths range naturally between 71 and 86 residues.

4. Recommended designs

- `ramp1_binder_001_ramp1_binder_001_9_model_0_b0_d1` — Rank 1 lead; highest composite score (15.03) with high ranking weight metric (ipsae_min = 0.755), 0.915 Å dock RMSD, and 100% hotspot engagement.
- `ramp1_binder_001_ramp1_binder_001_32_model_3_b0_d3` — Rank 2 pick; strongest interface metrics in the set (iptm = 0.913, iface_pae = 2.92 Å, ipsae_min = 0.778) paired with tight 0.750 Å dock RMSD.
- `ramp1_binder_001_ramp1_binder_001_34_model_2_b0_d2` — Rank 4 pick; exceptionally clean folding and docking agreement (0.416 Å fold RMSD, 0.842 Å dock RMSD, 1.0 epitope recall) and second-highest raw composite score.
- `ramp1_binder_001_ramp1_binder_001_20_model_2_b0_d1` — Rank 8 pick; highest raw interface strength metric across the entire campaign (ipsae_min = 0.792, iptm = 0.900) with solid binder confidence (pLDDT = 0.849).

5. Recommended next steps

- Run MD relaxation or AlphaFold3/ESMFold orthogonal validation on the top 4 candidates (`ramp1_binder_001_ramp1_binder_001_9_model_0_b0_d1`, `ramp1_binder_001_ramp1_binder_001_32_model_3_b0_d3`, `ramp1_binder_001_ramp1_binder_001_34_model_2_b0_d2`, `ramp1_binder_001_ramp1_binder_001_20_model_2_b0_d1`) to verify interface stability without the co-receptor CALCRL.
- Assess monomeric solubility and surface hydrophobicity profiles in-silico prior to ordering synthetic genes for expression and SPR/BLI binding assays against the RAMP1 extracellular domain.

6. Artifact pointers

- `top_k.csv`
- `ranked.csv`

- `top_k.fasta`

PIPELINE HANDOFF

- go_recommendation: GO
- go_rationale: Excellent convergence with sub-angstrom dock RMSDs, 100% hotspot engagement, and high interface SAE across diverse backbone families.
- target_complex: RAMP1 (CALCRL interface)
- top_k_count: 20
- best_iptm: 0.894
- best_ipae: 3.20
- best_ipsae_min: 0.755
- best_dock_rmsd: 0.91
- best_name: ramp1_binder_001_ramp1_binder_001_9_model_0_b0_d1

MODEL PROVENANCE

- skill: `design-analyst`
- written by: **gemini:gemini-3.7-flash** — the model the operator selected. LPT never substitutes a model on its own; a stage a safety classifier declines ends the run.

Supplemental Information 6 - How designs are scored and ranked

SUPPLEMENTARY INFORMATION · DESIGN RANKING

How designs are scored and ranked

Worked on the pain-receptor run (RAMP1, 3N7S; project `pain_receptors_rc1`). 1,396 refolds, 351 passed the gates, 195 backbones.

1 Gates, then a composite score

A refold must pass every hard gate. Survivors are then scored; the gates are never part of the score.

GATE (AS RUN)	THRESHOLD
Clash	no heavy-atom pair closer than 2.2 Å (clash_severe = 0)
ipTM	≥ 0.5
Binder dock RMSD	≤ 5 Å
Binder fold RMSD	≤ 2 Å
Binder pLDDT	≥ 0.75
Mean interface PAE	≤ 15 Å
Epitope recall	≥ 0.5
Hotspot engagement	≥ 0.75

2 The composite

$$z_m(i) = (x_m(i) - \mathrm{mean}_S\, x_m) / \mathrm{sd}_S\, x_m$$
$$\mathrm{composite}(i) = \Sigma_m\, w_m \cdot z_m(i)$$

S is the set of gate survivors (351 here). $x_m(i)$ is the metric's value for design i, with its sign reversed for the “lower is better” metrics, so a larger z is always better. A metric with no spread contributes 0; a missing value is replaced by the column mean. Scores are relative to this campaign and are not comparable across campaigns.

TERM	COLUMN	BETTER	USED IN	WEIGHT, RUN	WEIGHT, NOW
ipSAE (min)	`ipsae_min`	higher	first, final	**2**	2
Binder dock RMSD (refold vs design)	`binder_rmsd_dock`	lower	first, final	**1.5**	1.5
Binder pLDDT	`binder_plddt`	higher	first, final	**1.5**	1.5
ipTM	`iptm`	higher	first, final	**1**	1
Mean interface PAE	`iface_pae`	lower	first, final	**1**	1
Epitope recall	`epitope_recall`	higher	first, final	**1**	1
Hotspot engagement	`hotspot_engagement`	higher	first, final	**0.5**	0.5
Patch enrichment (binder on trim-exposed surface)	`patch_enrichment`	lower	first, final	**absent**	0.5
Rosetta interface energy (ddg)	`rosetta_ddg`	lower	final only	**1.5**	1.5
Rosetta contact molecular surface	`rosetta_cms`	higher	final only	**1**	1
Rosetta buried unsatisfied polars	`rosetta_vbuns`	lower	final only	**0.5**	1

The first composite uses the seven confidence and geometry terms. The 300 survivors with the highest first composite are relaxed and scored with PyRosetta (299 completed); the final composite adds the three Rosetta terms and is recomputed over all survivors, with the column mean used for the 52 that have no Rosetta result (51 below the cap, 1 failed). Weights are hand-set. ipSAE carries the most weight because it is high-precision but low-recall as a hard gate.

3 One design per backbone, then a diverse top-K

$$\mathrm{MMR}(i) = \lambda \cdot \tilde{s}(i) - (1 - \lambda) \cdot \max_{j \in \text{picked}} \mathrm{id}(i, j), \quad \lambda = 0.5$$

$$\tilde{s}(i) = (\,\text{composite}(i) - \min\,) / (\,\max - \min\,), \quad \text{candidate dropped if } \max_j \mathrm{id}(i, j) \geq 0.7$$

Only the best-scoring refold of each backbone is kept (195 candidates here). The top design is picked first; each further pick maximises MMR(i) among candidates with sequence identity below 0.7 to everything already picked, until 20 designs are chosen. id is the sequence-matching ratio of the two binder sequences. The order in the top-K table (`mmr_rank`) is this pick order, which is why it need not follow the composite exactly.

4 Worked example: the two best designs

z-scores are the values written to `top_k.csv`; the weights are those of the run. The sum reproduces the stored composite score; this was checked for all 20 top designs.

Rank 1: `9_model_0_b0_d1`

TERM	Z	WEIGHT	WEIGHT × Z
ipSAE (min)	+1.51	2	+3.02
Binder dock RMSD (refold vs design)	+0.74	1.5	+1.10
Binder pLDDT	+0.66	1.5	+0.99
ipTM	+1.18	1	+1.18
Mean interface PAE	+1.19	1	+1.19
Epitope recall	+0.61	1	+0.61
Hotspot engagement	+0.14	0.5	+0.07
Rosetta interface energy (ddg)	+2.65	1.5	+3.98
Rosetta contact molecular surface	+2.66	1	+2.66
Rosetta buried unsatisfied polars	+0.46	0.5	+0.23
Composite score			**15.029**

Rank 2: `32_model_3_b0_d3`

TERM	Z	WEIGHT	WEIGHT × Z
ipSAE (min)	+1.62	2	+3.24
Binder dock RMSD (refold vs design)	+0.95	1.5	+1.42
Binder pLDDT	+1.14	1.5	+1.71
ipTM	+1.35	1	+1.35
Mean interface PAE	+1.32	1	+1.32
Epitope recall	+0.46	1	+0.46
Hotspot engagement	+0.14	0.5	+0.07
Rosetta interface energy (ddg)	+1.29	1.5	+1.94
Rosetta contact molecular surface	+1.56	1	+1.56
Rosetta buried unsatisfied polars	-0.60	0.5	-0.30
Composite score			**12.768**

5 Differences between this run and the current defaults

This run was scored before four later changes, so re-ranking its refolds with today's code would give a somewhat different order.

- **Per-metric clipping.** Today each z is clipped to ±2; this run's scores are unclipped (largest |z| among the top 20 was 2.75).
- **Patch-enrichment term** (weight 0.5) did not exist; it is zero for a trim that cuts nothing, as here.
- **Rosetta buried-unsatisfied-polar weight** was 0.5 and is now 1.
- **Clash gate** was a count of severe overlaps; it is now a minimum heavy-atom distance of 1.8 Å.