MANUSCRIPT

LPT: Orchestrating bounded agentic loops for automated protein binder design


Fixed orchestration of LLM stages, each running a bounded agentic loop with its own system prompt and tool access, backed by a curated literature database. One natural-language prompt in; ranked, in silico validated binder designs out.

Michael Uckelmann
Hubrecht Institute, Utrecht, The Netherlands

Little Protein Tiger (LPT) · github.com/MichaUckelmann/little-protein-tiger

FIGURE 3 / STRUCTURE ANALYSIS

“Design novel inhibitors for pain receptors that are promising drug targets.”




FROM PROMPT TO HOTSPOTS

Starting from the prompt alone, the pipeline selected CALCRL–RAMP1 (PDB 3N7S). The structure-analysis tool returns the interface analysis: interface residues, H-bonds and an estimated binding contribution ε per residue. The model then groups residues into clusters and chooses Region 1, a 10-residue patch spanning the core heterodimerisation surface of RAMP1, and forwards it to the design phase as hotspots.

FIGURE 4A / END-TO-END RUN 1

“Design de novo inhibitors for pain receptors that are promising drug targets.”




The pipeline chose to disrupt CALCRL–RAMP1 (PDB 3N7S). Hotspots in gold; two highly ranked designs in pink, with ipTM, minimum ipSAE and composite score.

17.9%	$0.33	~11 h
OF REFOLDS PASS ALL GATES, IPTM ≥ 0.7	LLM API COST	GPU TIME, LOCAL WORKSTATION

FIGURE 4B / END-TO-END RUN 2

“Design immune checkpoint inhibitors.”



The pipeline chose to disrupt PD-1/PD-L1 (PDB 4ZQK) and designed binders to PD-L1. Hotspots in gold; two highly ranked designs in pink, with ipTM, minimum ipSAE and composite score.


9.6%
OF REFOLDS PASS ALL GATES, IPTM ≥ 0.7

$0.42
LLM API COST

~34 h
GPU TIME, LOCAL WORKSTATION

FIGURE 4C / END-TO-END RUN 3

“...checkpoint inhibitors that are not targeting PD1 or PD-L1 but could synergize with them.”



The pipeline chose to disrupt the TIGIT–PVR (CD155) interaction (PDB 3UDW). Hotspots in gold; two highly ranked designs in pink, with ipTM, minimum ipSAE and composite score.


10%
OF REFOLDS PASS ALL GATES, IPTM ≥ 0.7

$0.39
LLM API COST

~20 h
GPU TIME, LOCAL WORKSTATION

FIGURE 2A / LITERATURE DATABASE

~14,000 papers, digested and linked into an interaction graph.



Nodes are proteins; edges carry affinity information and the number of papers mentioning the interaction (edge width). Edge colour marks the DepMap CRISPR gene-effect correlation of the pair. The graph shown is a small subgraph.

CLOSED-BOOK AGAINST OPEN-BOOK EXAM

48 questions answerable from the database. With database access: 41 correct, 7 “unknown”. Without: 0 correct, 47 “unknown”, 1 wrong. The exam was biased towards database content and some questions were leading.

LITERATURE LAYER

Each paper is digested into a structured fingerprint.

Key findings with evidence, source span and confidence; proteins and structures; pathway context. Example (abridged):

USP26 functions as a negative regulator of cellular reprogramming by stabilising PRC1 complex components

DOI 10.1038/s41467-017-00301-4 · pathway_biology · experimental_in_vitro · schema 2.0

CONTEXT HOOK

In mouse embryonic fibroblasts undergoing OSKM-mediated reprogramming, the deubiquitinase USP26 physically interacts with CBX4 and CBX6, removes K48-linked polyubiquitin and protects them from proteasomal degradation. Knockdown of Usp26 increases AP+ iPSC colony generation fourfold.

KEY FINDING 1 OF 5

claim	shRNA knockdown of Usp26 enhances reprogramming efficiency fourfold
protein_pair	USP26 ↔ NANOG
evidence	~400 AP+ colonies vs ~100 in control shRNA (quantitative)
context	Dox-induced OSKM MEF reprogramming, day 12
confidence	0.95
source_span	Page 3, Para 1

KEY FINDING 3 OF 5

protein_pair	USP26 ↔ CBX6
residues	Cys304
evidence	Loss of K48 deubiquitination in C304S and Δ295–312 mutants (qualitative)
source_span	Page 5, Para 1

Fingerprints are embedded (PubMedBERT) for semantic search and aggregated into the interaction graph. Three complete examples: Supplemental Information 4.

SCOPE AND AVAILABILITY

In silico results, at low cost.

	CALCRL / RAMP1	PD-1 / PD-L1	PVR / TIGIT
Pass all gates, ipTM ≥ 0.7	17.9%	9.6%	10%
LLM API cost	$0.33	$0.42	$0.39
GPU time (local)	~11 h	~34 h	~20 h

The top 20 designs of each campaign were refolded with Boltz-2 and Protenix-v2; the majority pass all gates in all folding models.

LIMITATIONS STATED IN THE MANUSCRIPT

Experimental success rates have not been evaluated; in silico metrics are a proxy. The database (~14,000 papers in the example runs) limits target choice, and the released database is smaller because of licensing.

AVAILABILITY

Manuscript with Supplemental Information 1–6, appendices, code, skills and corpus tooling:

`github.com/MichaUckelmann/little-protein-tiger`