Barrier Detector

Generated by Doxygen 1.8.11

# **Contents**

1	Mair	n Page		1
2	Nam	espace	e Index	3
	2.1	Names	space List	3
3	Clas	s Index	<b>«</b>	5
	3.1	Class I	List	5
4	File	Index		7
	4.1	File Lis	st	7
5	Nam	espace	e Documentation	9
	5.1	cva Na	amespace Reference	9
	5.2	cva::ba	arrier Namespace Reference	9
		5.2.1	Enumeration Type Documentation	9
			5.2.1.1 ObjectLabel	9
		5.2.2	Function Documentation	10
			5.2.2.1 version()	10

iv CONTENTS

6	Clas	ss Docu	mentation		11
	6.1	cva::ba	arrier::Barri	erDetector Class Reference	11
		6.1.1	Member	Enumeration Documentation	11
			6.1.1.1	anonymous enum	11
		6.1.2	Construc	tor & Destructor Documentation	12
			6.1.2.1	~BarrierDetector()=default	12
		6.1.3	Member	Function Documentation	12
			6.1.3.1	createCpu()	12
			6.1.3.2	createGpu(const ac::Precision &precision=ac::Precision::FP32)	12
			6.1.3.3	detect(const ac::ConstImageView ℑ)=0	12
	6.2	cva::ba	arrier::Dete	ctedObject Class Reference	12
		6.2.1	Detailed	Description	13
		6.2.2	Construc	tor & Destructor Documentation	13
			6.2.2.1	~DetectedObject()=default	13
		6.2.3	Member	Function Documentation	13
			6.2.3.1	boundingBox()=0	13
			6.2.3.2	confidence()=0	13
			6.2.3.3	label()=0	13
7	File	Docum	entation		15
	7.1	barrier	hpp File R	eference	15
		7.1.1	Macro De	efinition Documentation	16
			7.1.1.1	CVA_BARRIER_EXPORT	16
	7.2	examp	ole.dox File	Reference	16
	7.3	mainpa	age.dox Fil	e Reference	16
8	Exa	mple Do	ocumentat	ion Control of the Co	17
	8.1	main.c	pp		17

# **Main Page**

#### Note

This library will load data files located in the directory located at ../share/cva/Barrier  $\leftarrow$  Detector/assets relative to it. For correct operation, if the library is copied outside of the installation directory, the assets directory must be copied alongside it.

2 Main Page

# Namespace Index

## 2.1 Namespace List

Here is a list of all namespaces with brief descriptions:

cva	 			 					 								 				9
cva::barrier	 			 					 								 				9

4 Namespace Index

# **Class Index**

### 3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

cva::barrier::BarrierDetector	 11
cva::barrier::DetectedObject	
Class which represents detected object	 12

6 Class Index

# File Index

4 4		
41		iet
<b>9.</b> I	-	J.O.

Here is a list of all files with brief descriptions:							
barrier.hpp	15						

8 File Index

# **Namespace Documentation**

### 5.1 cva Namespace Reference

#### **Namespaces**

barrier

### 5.2 cva::barrier Namespace Reference

#### Classes

- class BarrierDetector
- · class DetectedObject

Class which represents detected object.

#### **Enumerations**

• enum ObjectLabel { ObjectLabel::BACKGROUND, ObjectLabel::VEHICLE, ObjectLabel::PLATE } An identifier of the category to which an object belongs.

### **Functions**

• CVA\_AC\_SHARED\_LIBRARY\_IMPORT ac::Version version ()

Returns the version number of the library.

### 5.2.1 Enumeration Type Documentation

**5.2.1.1 enum cva::barrier::ObjectLabel** [strong]

An identifier of the category to which an object belongs.

#### Enumerator

BACKGROUND VEHICLE PLATE

### **5.2.2 Function Documentation**

5.2.2.1 CVA\_AC\_SHARED\_LIBRARY\_IMPORT ac::Version cva::barrier::version ( )

Returns the version number of the library.

## **Class Documentation**

#### 6.1 cva::barrier::BarrierDetector Class Reference

```
#include <barrier.hpp>
```

#### **Public Types**

enum { MAX\_IMAGE\_WIDTH = 4096, MAX\_IMAGE\_HEIGHT = 4096 }

#### **Public Member Functions**

- virtual ~BarrierDetector ()=default
   Virtual destructor.
- virtual std::vector < std::unique\_ptr < DetectedObject > > detect (const ac::ConstImageView &image)=0
   Detects objects in the image, returns vector of detected objects image image where objects should be detected.

#### **Static Public Member Functions**

- static CVA\_AC\_SHARED\_LIBRARY\_IMPORT std::unique\_ptr< BarrierDetector > createCpu ()

  Returns a pointer to a new object implementing ObjectDetectorCommon that uses the CPU for computations.

  parameters parameters of IE detector.
- static CVA\_AC\_SHARED\_LIBRARY\_IMPORT std::unique\_ptr< BarrierDetector > createGpu (const ac::← Precision &precision=ac::Precision::FP32)

Returns a pointer to a new object implementing ObjectDetectorCommon that uses the GPU for computations. parameters parameters of IE detector.

#### 6.1.1 Member Enumeration Documentation

#### 6.1.1.1 anonymous enum

#### Enumerator

**MAX\_IMAGE\_WIDTH** The maximal supported image width. **MAX\_IMAGE\_HEIGHT** The maximal supported image height.

12 Class Documentation

#### 6.1.2 Constructor & Destructor Documentation

```
6.1.2.1 virtual cva::barrier::BarrierDetector::~BarrierDetector() [virtual], [default]
```

Virtual destructor.

#### 6.1.3 Member Function Documentation

Returns a pointer to a new object implementing ObjectDetectorCommon that uses the CPU for computations. parameters parameters of IE detector.

#### **Examples:**

main.cpp.

```
6.1.3.2 static CVA_AC_SHARED_LIBRARY_IMPORT std::unique_ptr<BarrierDetector> cva::barrier::←

BarrierDetector::createGpu ( const ac::Precision & precision = ac::Precision::FP32 )

[static]
```

Returns a pointer to a new object implementing ObjectDetectorCommon that uses the GPU for computations. parameters parameters of IE detector.

#### Examples:

main.cpp.

```
6.1.3.3 virtual std::vector<std::unique_ptr<DetectedObject> > cva::barrier::BarrierDetector::detect ( const ac::ConstlmageView & image ) [pure virtual]
```

Detects objects in the image, returns vector of detected objects image image where objects should be detected.

The documentation for this class was generated from the following file:

· barrier.hpp

#### 6.2 cva::barrier::DetectedObject Class Reference

Class which represents detected object.

```
#include <barrier.hpp>
```

#### **Public Member Functions**

```
    virtual float confidence ()=0
    returns confidence of detected object in the range [0, 1]
```

• virtual ac::Rectangle < float > boundingBox ()=0

returns bounding box of detected object

• virtual ObjectLabel label ()=0

return label of detected object

virtual ~DetectedObject ()=default

virtual destructor

#### 6.2.1 Detailed Description

Class which represents detected object.

#### 6.2.2 Constructor & Destructor Documentation

```
\textbf{6.2.2.1} \quad \textbf{virtual cva::barrier::DetectedObject::} \sim \textbf{DetectedObject()} \quad [\texttt{virtual}], [\texttt{default}]
```

virtual destructor

#### 6.2.3 Member Function Documentation

```
6.2.3.1 virtual ac::Rectangle<float> cva::barrier::DetectedObject::boundingBox( ) [pure virtual]
```

returns bounding box of detected object

```
6.2.3.2 virtual float cva::barrier::DetectedObject::confidence() [pure virtual]
```

returns confidence of detected object in the range [0, 1]

**6.2.3.3 virtual ObjectLabel cva::barrier::DetectedObject::label()** [pure virtual]

return label of detected object

The documentation for this class was generated from the following file:

· barrier.hpp

14 Class Documentation

## **File Documentation**

### 7.1 barrier.hpp File Reference

```
#include <memory>
#include <string>
#include <vector>
#include <cva/ac/api.hpp>
#include <cva/ac/geometry.hpp>
#include <cva/ac/image_view.hpp>
#include <cva/ac/precision.hpp>
```

#### Classes

- class cva::barrier::DetectedObject
   Class which represents detected object.
- · class cva::barrier::BarrierDetector

#### **Namespaces**

- cva
- cva::barrier

#### **Macros**

• #define CVA\_BARRIER\_EXPORT CVA\_AC\_SHARED\_LIBRARY\_IMPORT

#### **Enumerations**

• enum cva::barrier::ObjectLabel { cva::barrier::ObjectLabel::BACKGROUND, cva::barrier::ObjectLabel::VE← HICLE, cva::barrier::ObjectLabel::PLATE }

An identifier of the category to which an object belongs.

16 File Documentation

### **Functions**

• CVA\_AC\_SHARED\_LIBRARY\_IMPORT ac::Version cva::barrier::version ()

Returns the version number of the library.

- 7.1.1 Macro Definition Documentation
- 7.1.1.1 #define CVA\_BARRIER\_EXPORT CVA\_AC\_SHARED\_LIBRARY\_IMPORT
- 7.2 example.dox File Reference
- 7.3 mainpage.dox File Reference

## **Example Documentation**

### 8.1 main.cpp

```
Copyright 2018 Intel Corporation.
    This software and the related documents are Intel copyrighted materials,
    and your use of them is governed by the express license under which they
    were provided to you (Intel Simplified Software License (Version April 2018))
    Unless the License provides otherwise, you may not use, modify,
    copy, publish, distribute, disclose or transmit this software or
    the related documents without Intel's prior written permission.
    This software and the related documents are provided as is, with no
    express or implied warranties, other than those that are expressly
   stated in the License.
#include <cstdlib>
#include <iostream>
#include <numeric>
#include <iomanip>
#include <cmath>
#include <opencv2/core/core.hpp>
#include <opencv2/highgui/highgui.hpp>
#include <opencv2/imgproc.hpp>
#include <cva/ac/ocv/image_view.hpp>
#include <cva/barrier/barrier.hpp?</pre>
int main(int argc, char *argv[])
    // Parse the command line arguments using OpenCV.
    cv::CommandLineParser parser(argc, argv,
        "{ @image | | image path}"
       "{ help h |
    if (parser.has("help"))
        parser.printMessage();
        return EXIT_SUCCESS;
    auto impl = parser.get<cv::String>("impl");
if (impl != "cpu" && impl != "gpu")
        std::cerr << argv[0] << ": --impl must be either \"cpu\" or \"gpu\".\n";
        return EXIT_FAILURE;
   auto prec = parser.get<cv::String>("prec");
if (prec != "FP32" && prec != "FP16")
        std::cerr << argv[0] << ": --prec must be either \"FP32\" or \"FP16\".\n";
        return EXIT_FAILURE;
```

```
}
auto precision = prec == "FP32" ? cva::ac::Precision::FP32 : cva::ac::Precision::FP16;
if (!parser.check())
    parser.printErrors();
    return EXIT_FAILURE;
auto image_path = parser.get<cv::String>("@image");
cv::Mat image = cv::imread(image_path);
if (image.empty())
    std::cerr << "failed to read image: " << image_path << std::endl;</pre>
    return EXIT_FAILURE;
auto detector = impl == "cpu" ? cva::barrier::BarrierDetector::createCpu
 () : cva::barrier::BarrierDetector::createGpu(precision);
auto objects = detector->detect(cva::ac::cov::toImageView(cva::ac::ImageFormat::BGR_8, image));
struct LabelProperties {
    const char *description;
cv::Scalar color;
} const label_properties[] =
    {"background", {0, 255, 0}},
{"vehicle", {0, 255, 255}},
{"plate", {255, 0, 0}},
};
std::cout << "Objects: " << objects.size() << std::endl;</pre>
for (std::size_t i = 0; i < objects.size(); ++i)</pre>
    auto label = (int)objects[i]->label();
    auto class_description = label_properties[label].description;
    auto confidence = objects[i]->confidence();
    auto bobx = objects[i]->boundingBox();
std::cout << i << ": " << confidence << " " << label << " " << class_description << " " " << bbox.startX() << " " << bbox.endX() << " " << bbox.endY()
              << std::endl:
}
auto show = parser.get<bool>("show");
if (show)
    for (std::size_t i = 0; i < objects.size(); ++i){</pre>
        auto confidence = objects[i]->confidence();
        if (confidence < 0.5f) continue;</pre>
        auto bbox = cv::Rect(objects[i]->boundingBox().startX(),
                               objects[i]->boundingBox().startY(),
        cv::rectangle(image, bbox, color, 5, 8, 0);
    cv::imwrite("result.jpeg", image);
return EXIT_SUCCESS;
```