

Comprehensive Evaluation of Agent-Based Modeling Approaches in Maritime Safety and Rescue Operations

Introduction and the Paradigmatic Shift in Maritime Risk Assessment

The global maritime transport sector carries approximately eighty percent of international trade, yet its operational safety record remains persistently undermined by the profound impact of human error. According to the International Maritime Organization (IMO) and extensive empirical safety studies, human factors are the primary cause in seventy to ninety-six percent of all maritime casualties.¹ This vulnerability is exponentially compounded during adverse weather conditions, particularly when vessels navigate beyond the coastal radio horizon, entering communication shadows where traditional shore-based forecasts degrade into Gaussian noise.¹ For decades, the foundational baseline for preventing these casualties has been the International Regulations for Preventing Collisions at Sea (COLREGs), which provide a deterministic, geometric collision-avoidance framework.¹ However, the implicit assumption underlying COLREGs—that navigational crews possess accurate, timely, and omniscient situational awareness—frequently collapses under the compounding pressures of imperfect information flow, circadian fatigue, and deteriorating environmental visibility.¹

To bridge the analytical gap between deterministic regulatory frameworks and the chaotic realities of real-world navigation, the academic and industrial communities have increasingly turned toward Agent-Based Modeling (ABM). Unlike traditional macroscopic risk assessments that calculate static probabilities over broad geographic areas, ABM provides a high-resolution, micro-level simulation environment. Within this architecture, autonomous entities—such as individual vessels, coastal broadcast stations, and dispatched rescue assets—interact continuously with localized environmental constraints, adapting their behavior based on imperfect information, bounded rationality, and dynamically evolving physical hazards.⁴

The primary analysis presented herein delivers an exhaustive, critical evaluation of a specific multi-agent simulation study designed to mitigate maritime information latency. The proposed model, detailed in the primary project manuscript, constructs a decentralised ship-to-ship weather mesh network grounded in epidemic broadcast theory, aiming to bridge coastal radio shadows and dynamically alter vessel behavior through a quantified preparedness score.¹ This evaluation will meticulously contrast the proposed model with its supplementary technical brief, while critically benchmarking the simulation's architectural choices—specifically its routing mechanisms, Key Performance Indicators (KPIs), structural survivability models, and Search and Rescue (SAR) logistics—against industry-standard methodologies. Particular emphasis is placed on integrating the highly cited frameworks pioneered by the Technical University of Denmark (DTU), Delft University of Technology (TU Delft), and prominent

Scandinavian risk analysts. Furthermore, the analysis will dissect the computational viability of the simulation's Python-based infrastructure, contrasting it with the superior scalability of modern, memory-safe paradigms such as the Rust-based krABMaga engine.⁶

Comparative Documentation Analysis: Proposed Weather Mesh versus Truncated Technical Brief

A rigorous structural and thematic comparison between the primary uploaded manuscript detailing the decentralised weather mesh network and the supplementary deep research brief reveals profound discrepancies in document integrity, analytical depth, and architectural scope.¹

The primary manuscript presents a fully realized, closed-loop simulation methodology designed to test three falsifiable hypotheses regarding the efficacy of hop-limited gossip protocols in reducing maritime fatalities.¹ It meticulously details a one hundred by one hundred nautical mile continuous space built upon an island-archipelago geometry, utilizing a discrete macro-tick time resolution of fifteen minutes.¹ The document extensively outlines the

behavioral algorithms, including a preparedness score (P_{prep}) that synthesizes forecast accuracy and circadian fatigue, a deterministic physical collision detection system, and a defined rescue pipeline with specific asset speeds and weather penalties.¹ Furthermore, the study outlines four distinct adversarial scenarios, strict statistical falsification criteria utilizing the Mann-Whitney U test and Cliff's Delta, and an eleven-step macro-tick execution sequence.¹ Conversely, an analysis of the supplementary deep research brief reveals severe truncation that renders it ineffective as a standalone architectural blueprint.¹ The introductory instructions of the brief explicitly reference numbered model components extending from section four through section thirteen, promising a comprehensive breakdown of the simulation engine.¹ However, the document terminates abruptly mid-sentence within Section 6.3, titled "AR(1) background with advection." The final visible line of the text cuts off at the phrase "...scenario unpredictability...".¹ Consequently, the brief entirely omits critical technical sections. It lacks the explanations for the physics engine, the inter-agent communication mechanics underlying the mesh network, the collision detection thresholds, the human factor algorithms, and the entirety of the Search and Rescue operational logistics.¹

Feature Category	Primary Simulation Manuscript	Truncated Research Brief
Document Integrity	Complete; contains abstract, full execution pipeline, and appendices.	Severely incomplete; terminates abruptly mid-sentence at Section 6.3.

Architectural Scope	Details communication protocols, behavioural models, and physics logic.	Limited entirely to introductory framework and early weather generation processes.
Communication Logic	Specifies a two-hop limit extending data reach by 30 nm beyond shore horizons.	Completely absent due to document truncation.
Behavioral Algorithms	Details the P_{prep} score, circadian fatigue, and evacuation logits.	Completely absent due to document truncation.
Rescue Logistics	Co-models helicopter (80 kn) and patrol vessel (25 kn) mobilization.	Completely absent due to document truncation.

Because the supplementary brief fails to provide the necessary technical scaffolding beyond the initial weather generation algorithms, the subsequent evaluation of the simulation's efficacy, limitations, and potential improvements must be drawn entirely from the architecture detailed within the primary manuscript.¹

Trajectory Generation and Navigation Mechanics: Manual Waypoints versus Empirical AIS Routing

A fundamental limitation of the proposed weather mesh simulation lies in its approach to vessel trajectory generation and collision avoidance mechanics. The model employs a manual waypoint routing system, wherein users define navigable areas via an HTML and graphical user interface (GUI) lane-builder.¹ This system creates ordered waypoint polylines, encompassing three west-east corridors and two north-south channels.¹ Vessels traverse these predetermined shipping lanes as exact sequences with a per-tick distance budget derived from a baseline speed drawn from a uniform distribution between ten and twenty knots,

mathematically defined as $v \sim U(10, 20)$.¹

While this manual, deterministic approach ensures that vessels remain within safe navigable boundaries, it introduces an idealized, rigid track-keeping behavior that fails to capture the stochastic realities of maritime navigation. When vessels approach a headland or a complex geometric intersection and the algorithm cannot find a safe sub-step, the target index simply advances and the vessel holds its position for the entire fifteen-minute macro-tick.¹ The simulation actively ignores active collision avoidance; the hazard-gated speed reduction mechanism—where maximum environmental hazard reduces a vessel's speed to thirty percent

of its nominal velocity—acts as the sole implicit braking mechanism.¹ This geometric fallback halts vessels rather than initiating the fluid, dynamic evasive routing required by COLREGs, thereby oversimplifying the complex encounter geometries inherent in dense coastal traffic.¹

The Paradigm Shift to AIS-Driven Routing and Artificial Force Fields

Contemporary maritime simulation standards, predominantly championed by leading Dutch institutions such as Delft University of Technology (TU Delft) and the Maritime Research Institute Netherlands (MARIN), have moved decisively away from manual waypoint selection.⁸ These institutions employ empirical, data-driven trajectory modeling utilizing Automatic Identification System (AIS) data.³ AIS transponders broadcast a vessel's position, course, speed, and dimensional characteristics at intervals as brief as a few seconds, generating billions of real-world ship position data points.¹⁰ By recasting former data-driven approaches, researchers can extract meaningful trajectory segments, allowing simulations to accurately mirror the statistical distributions of real-world shipping corridors rather than relying on idealized HTML-drawn polylines.¹⁰

Rather than forcing simulated vessels along pre-computed, rigid polylines, researchers at TU Delft—most notably Fangliang Xiao, Han Ligteringen, and Coen van Gulijk—have pioneered the "Artificial Force Field" model for multi-agent nautical traffic.¹³ In this highly sophisticated framework, autonomous ships perceive their local circumstances and react to artificial potentials, moving through their environment under the influence of forces of various origins.¹³ The Artificial Force Field mechanism functions similarly to the movement of charged particles within an electrical field according to the rules of electromagnetism.¹³ The vessel's destination acts as an attractive force, continuously drawing the agent forward. Simultaneously, navigational hazards, shallow banks, bridge piers, and encountering vessels generate repulsive forces.¹³ The magnitudes and directional vectors of these artificial forces are not arbitrarily chosen; they are stochastically calibrated using extensive historical AIS data, embedding the actual collision avoidance practices of human operators directly into the agents' behavioral logic.¹³

This integration allows the simulation to naturally replicate COLREGs-compliant behaviors without relying on rigid geometric halts. For instance, overtaking and head-on encounters inherently resolve themselves through the dynamic balancing of these force vectors, reflecting the "early, large, wide, clear" avoidance requirements mandated by maritime law.³ Furthermore, advanced AIS data mining utilizing combination factor analysis and K-means clustering has allowed researchers to categorize distinct ship driving styles, such as Conservative Close-Distance Avoidance (CCDA).³ Injecting these empirical driving styles into the multi-agent system provides a variance in maneuvering behavior that perfectly reflects the common practices for different dimensions of ships.³

Trajectory Feature	Proposed Mesh Simulation	TU Delft Artificial Force Field Model
--------------------	--------------------------	---------------------------------------

Route Generation	Manual HTML/GUI waypoint polylines.	Data-driven extraction from historical AIS sequence patterns.
Navigational Mechanism	Ordered track-keeping with discrete distance budgets.	Attractive and repulsive force vectors dictating continuous motion.
Collision Avoidance	Implicit braking via weather hazard speed reduction; geometric halting.	Dynamic spatial deviation calibrated by empirical AIS maneuvering styles (e.g., CCDA).
COLREGs Compliance	Absent; explicitly excluded to isolate information quality variables.	Naturally emergent through the interaction of repulsive vessel encounter forces.

If the proposed decentralised weather mesh model intends to accurately measure the reduction of ship-to-ship collisions, it must abandon the manual HTML waypoint system. Integrating an AIS-calibrated Artificial Force Field would elevate the simulation from a static track-keeping exercise to a dynamic, real-time collision avoidance testbed, allowing the

preparedness score (P_{prep}) to dynamically alter the sensitivity of the repulsive force fields rather than merely gating linear speed reductions.¹

Baselines, Key Performance Indicators, and the IWRAP Standard

The experimental design of the proposed weather mesh study evaluates three distinct conditions: Baseline A, representing classical navigation following COLREGs with zero weather intelligence and no preparedness modifier; Baseline B, a shore-only condition relying on noisy coastal station broadcasts subjected to distance and interference degradation; and the Proposed System, which integrates the full decentralised hop-limited gossip protocol and confidence-weighted forecast fusion.¹ The simulation's performance is quantified using six Key Performance Indicators (KPIs): fatal events per one thousand ship-hours, collisions per one thousand ship-hours, survival ratio, average time-to-arrival (TTA) of rescue assets, evacuation activation rate, and mean preparedness score across the fleet.¹

While these selected KPIs are internally consistent for validating the study's specific, isolated hypotheses via the Mann-Whitney U test, they represent a micro-level departure from globally recognized, macro-level maritime risk assessment frameworks.¹ To validate the practical, real-world utility of the weather mesh network, the simulation's outputs must be translatable into industry-standard risk metrics. The paramount standard for evaluating waterway collision

risk is the IALA Waterway Risk Assessment Program (IWRAP Mk II), developed extensively by Peter Friis-Hansen and Marie Lützen at the Technical University of Denmark (DTU).¹⁷

The IWRAP Methodology: Geometric and Causation Probabilities

The IWRAP methodology operates on a probabilistic foundation that fundamentally differs from the raw collision counting mechanism employed in the proposed ABM.¹ IWRAP calculates the expected frequency of collisions by differentiating between the geometric probability of an encounter and the causation probability of human or mechanical failure.¹⁷ The foundational mathematical expression utilized in IWRAP is defined as:

$$N_c = N_a \cdot P_c$$

where N_c represents the actual predicted number of collisions, N_a constitutes the potential number of geometric collision candidates (derived from the lateral distribution of AIS traffic operating blindly on a specified route), and P_c is the causation probability, representing the likelihood that a navigator fails to execute the necessary evasive actions.²

In traditional IWRAP modeling, the causation probability P_c is derived from historical accident statistics and varies based on the encounter geometry. For example, the typical causation factor for a head-on collision in well-regulated traffic is mathematically established as

$P_{head-on} = 0.5 \cdot 10^{-4}$, while bend and crossing collisions possess a causation factor of

$P_{crossing} = 1.3 \cdot 10^{-4}$.¹⁷ The proposed ABM's KPI of "collisions per one thousand ship-hours" provides a localized, time-bound metric useful for internal agent-based validation, but it lacks the spatial context required by maritime regulators who assess risk based on the expected annual frequency of collisions for a specific port infrastructure or fairway (where the acceptable risk threshold is typically less than one collision per year).¹

To bridge the analytical gap between this experimental ABM and maritime regulatory standards, the weather mesh simulation should be programmed to output a synthetic AIS log of its own agents' movements. This synthetic traffic data could then be fed directly into the

IWRAP Mk II software suite.² By comparing the N_c generated by the Baseline A traffic against the N_c generated by the Proposed System traffic, researchers could provide port authorities with a standardized, globally recognized metric proving the exact reduction in annual collision frequencies facilitated by the mesh network.

Human Factors, Preparedness Metrics, and Structural Survivability

A significant innovation within the proposed ABM simulation is its highly sophisticated, dynamic human-factor coupling mechanism. The model abandons the traditional assumption that

human error is a static variable, instead calculating a dynamic error probability (P_{err}) every macro-tick.¹ This calculation integrates the accumulated hours a crew has been awake, modifiers based on crew archetype (Green, Standard, or Veteran), and a circadian phase modeled as a negated cosine wave that reaches its severe performance nadir at 03:00 UTC.¹

This resulting error probability directly dictates the vessel's preparedness score (P_{prep}), which subsequently gates all tactical decisions, including course alteration, speed reduction, and early evacuation triggers.¹

Bayesian Belief Networks and Dynamic Vigilance

This dynamic, per-tick calculation of human performance provides a high-resolution, micro-simulated alternative to the macro-level human reliability analyses traditionally employed in Scandinavian literature. Within the DTU frameworks, human factors are traditionally evaluated using Bayesian Belief Networks (BBN) and Fault Tree Analysis (FTA).²² Foundational research by Peter Friis-Hansen and Preben Terndrup Pedersen demonstrates that human failure accounts

for approximately seventy-five percent of the overall causation probability (P_c) in maritime accidents.²

Within these complex BBNs, specific interconnected nodes—such as "Situation Assessment," "Danger Detection," "Incapacitation," and "Asleep"—dictate the ultimate probability of an officer failing to act.²² DTU's statistical analyses reveal a counter-intuitive phenomenon: the "Asleep" node often dominates the fault tree, accounting for up to sixty percent of the causation probability, challenging the assumption that high vigilance is guaranteed in confined navigational areas.²²

The proposed ABM aligns remarkably well with this insight by allowing the preparedness score to dynamically penalize vessels based on the residual forecast error (E_{wx}) derived from the confidence-weighted weather fusion equation.¹ By bridging the critical gap between weather information asymmetry and cognitive readiness, the proposed model successfully provides a quantifiable, mathematical causal link from data latency to fatal outcomes, advancing the science of human factor modeling beyond static fault trees.¹

Structural Damage and the SIMCOL Model

However, while the cognitive modeling within the proposed ABM is highly advanced, its structural survivability mechanics are rudimentary. The simulation relies on a rigid stability threshold of three discrete damage points—reached by three collision or grounding events—after which the vessel immediately transitions directly to the SUNK state, incrementing the fatality counter.¹ This integer-based health pool represents a severe oversimplification of maritime physics.

Extensive PhD research conducted by Marie Lützen at DTU and the University of Southern Denmark (SDU) established complex internal mechanics models to determine actual structural survivability following a hull breach.²⁴ Lützen's SIMCOL (Simplified Collision Model) utilizes a

time domain simultaneous solution of external vessel dynamics and internal deformation mechanics to accurately predict collision damage.²⁵ By calculating the reacting forces from side and bulkhead structures and measuring the absorbed energy using the Minorsky correlation, SIMCOL establishes a robust damage probability density function.²⁵

Furthermore, this internal mechanics calculation determines the S_i factor, a regulatory survivability metric dependent on the specific location and severity of the flooding.²⁶ A survivability factor of one denotes that the vessel will survive the flooding of the specific damage case, while lower fractions indicate imminent foundering.²⁶ Future iterations of the proposed weather mesh model must replace its simplistic three-point damage counter with a probabilistic damage function based on the exact impact velocity, vessel displacement, and encounter angle, perfectly aligning the agent-based physics engine with Lützen's and Pedersen's established crashworthiness models.¹

Search and Rescue (SAR) Operational Logistics: Deterministic Models versus Dynamic Arctic Operations

The Search and Rescue (SAR) component of the proposed simulation operates on a highly deterministic and idealized pipeline. Upon the probabilistic success of a vessel's SOS transmission reaching a coastal station, the model triggers the dispatch of a rescue asset, drawing either a helicopter operating at eighty knots or a patrol vessel at twenty-five knots.¹ These assets undergo a uniform, unvarying mobilisation delay of exactly two macro-ticks (thirty minutes) before navigating directly to the exact coordinates of the distress signal.¹ During transit, the assets suffer a linear, deterministic weather-dependent speed penalty calculated as $v_{eff} = v \cdot \max(0.40, 1 - 0.35W)$, where W is the normalized environmental hazard scalar.¹ Upon the rescue asset arriving within a 0.2 nm radius of the distress coordinates, surviving crew members immediately transition to the RESCUED state.¹

The MASSIM Framework and Search Optimization

This rigid SAR architecture ignores the vast logistical and environmental complexities inherent in real-world maritime rescue operations. Highly cited literature from researchers Bhakti Stephan Onggo and Mumtaz Karatas highlights that accurate SAR modeling requires the implementation of sophisticated search pattern algorithms and target behavioral matrices.⁵ Their MASSIM (MAritime Search SIMulation) framework evaluates the performance of searchers attempting to detect moving or drifting targets under varying degrees of visibility and cooperation.⁵

In the proposed weather mesh model, the distress position is treated as an absolute, static known variable, completely eliminating the primary "search" phase of Search and Rescue.¹ In reality, maritime evacuations involve deployed liferafts that drift dynamically, continuously influenced by wind vectors, sea state severity, and subsurface ocean currents.³⁰ The MASSIM

framework categorizes targets into cooperative entities (such as victims in a standard SAR operation) and evading targets, requiring the simulation to implement complex search patterns—such as the expanding square, sector search, or parallel sweep—to achieve detection.²⁹ The proposed ABM's assumption of omniscient routing artificially inflates the survival ratio KPI, as it negates the extensive time lost to searching vast areas of ocean for drifting rafts.¹

Arctic Environments and the Barents Sea Model

Further analytical depth is required when simulating SAR operations in severe environmental conditions, as evidenced by the extensive agent-based modeling research conducted by Behrooz Ashrafi at UiT The Arctic University of Norway.³³ Ashrafi's modeling of SAR operations in the Barents Sea and the broader Arctic offshore environment highlights that extreme weather does not simply reduce a rescue vessel's speed by a clean, linear mathematical fraction; rather, it introduces complex "no-go" conditions, mechanical unreliability, and non-linear survivability degradation.³³

In Ashrafi's framework, performing SAR operations involves navigating low temperatures, high waves, heavy snow showers, sea ice, and dense fog, all of which are compounded by the phenomenon of sea spray icing, which physically degrades the stability of both the distressed vessel and the responding patrol craft.³⁶

SAR Modeling Feature	Proposed Mesh Model	Advanced Industry Standard (MASSIM / Ashrafi)
Search Mechanics	Non-existent; direct deterministic routing to a static, known distress coordinate.	Implements complex IAMSAR search patterns (e.g., expanding square) for target detection.
Target Dynamics	Evacuees and liferafts remain static at the exact location of the incident.	Targets drift dynamically, modeled via hydrodynamic forces and ocean currents.
Weather Penalties	Linear deterministic speed reduction formula based on a generalized hazard scalar.	Monte Carlo-driven severity levels with expert-mapped non-linear "no-go" thresholds.
Asset Endurance	Infinite operational capacity and zero environmental	Explicitly models fuel limitations, mechanical

	attrition or fuel loss.	failure rates, and icing constraints.
--	-------------------------	---------------------------------------

Ashrafi's methodology utilizes Monte Carlo simulations driven by historical meteorological data to define distinct weather severity levels.³³ This model employs an expert-judgement mapping function, denoted as $g_i(\cdot)$, to quantify the exact impacts of these severity levels on the performance of rescue agents, explicitly conditioning the rescue time on the calendar month to capture the extreme variance between summer and winter operations (where December to February yields the longest rescue delays).³³ If the proposed weather mesh model is to be utilized for high-stakes operational planning or policy formulation, it must adopt the probabilistic search algorithms of MASSIM and the realistic environmental degradation matrices of Ashrafi's Barents Sea model, rather than assuming guaranteed target location and unimpeded transit.¹

Computational Architecture: The Mesa (Python) Bottleneck versus krABMaga (Rust) Scalability

A foundational architectural constraint dictating the scope of the proposed study is its reliance on the Python-based Mesa framework.¹ The authors explicitly note that the Tier-2 weather process and the spatial grid resolution (limited to 50×50 cells) were deliberately calibrated to remain "light enough for interactive simulation on a laptop".¹ This configuration currently supports a maximum fleet density of up to one hundred concurrent vessels over a thirty-day run horizon, rendering macro-ticks at fifteen-minute intervals.¹

The Inherent Bottlenecks of Python and Mesa

Mesa is an open-source, modular framework built upon Python 3+, highly regarded for its accessibility, ease of use, and rich community ecosystem that provides extensions for data analysis and browser-based visualization.⁷ However, Python's underlying software architecture fundamentally limits the vertical and horizontal scalability required for high-density, discrete-event multi-agent simulations.⁷ Python utilizes a Global Interpreter Lock (GIL), a mutex that protects access to Python objects, preventing multiple threads from executing Python bytecodes at once.⁷ This severely restricts true parallel execution. Furthermore, Python's reliance on automatic memory management via a garbage collector introduces unpredictable, latency-inducing overhead pauses during long-horizon Monte Carlo runs.⁷ For a simulation calculating continuous geometric collision overlap, two-hop packet suppression arrays, dynamic weather matrix generation, and behavioral logits across thousands of discrete entities simultaneously, Mesa rapidly approaches a hard computational ceiling.¹ This bottleneck restricts the simulation to artificially small geographical areas and low agent counts, preventing the analysis of massive, basin-wide shipping networks.⁴¹

The Scalability Paradigm of krABMaga

Recent performance benchmarks and comprehensive architectural reviews published in the *Journal of Artificial Societies and Social Simulation* (JASSS) demonstrate that the simulation industry is rapidly pivoting toward compiled, memory-safe programming languages for complex ABM execution.⁷ The **krABMaga** framework, written entirely in the Rust programming language, represents the current state-of-the-art for fast, reliable, discrete-event multi-agent simulation engines.⁷

Developed to merge efficiency and safeness, krABMaga embraces and re-engineers the core architectural concepts of the highly regarded Java-based MASON simulation library, adapting them to exploit Rust's unique memory paradigms.⁴⁴ The engine utilizes "Safe Rust" specifications, enforcing strict ownership, borrowing, and lifetime rules at compile-time.⁷ This implementation entirely eliminates the memory leaks, stack overflows, and data races that frequently crash C++ engines or stall Python interpreters during extensive parallelized model calibrations.⁷

Furthermore, krABMaga abandons traditional object-oriented overhead by structuring its core module around the Entity Component System (ECS) pattern, leveraging the Bevy game engine.⁷ This architecture ensures highly optimized memory contiguity and exceptional cache performance, drastically reducing the time required to iterate over massive agent populations.⁷ For visualization, rather than relying on slow HTML DOM manipulation, krABMaga utilizes WebAssembly (WASM) and WebGL integration, allowing compiled, high-performance simulations to run directly within a web browser without sacrificing native execution speeds.⁷

Architectural Feature	Mesa (Python) Framework	krABMaga (Rust) Framework
Execution Efficiency	Low to Medium; severely bottlenecked by the Python interpreter and GIL.	Very High; compiled directly to optimized machine code.
Memory Management	Handled via Garbage Collection; prone to overhead pauses in large runs.	Handled at compile-time via Rust's ownership model; zero-cost memory safety.
Architectural Design	Object-Oriented Programming (OOP) with modular Python extensions.	Re-engineered MASON concepts utilizing the Bevy Entity Component System (ECS).

Scalability Ceiling	Practical limit of $\sim 10^3$ agents before significant execution slowdown.	Benchmark tested reliably up to 128,000 agents in highly complex spatial grids.
Parallelization	Difficult; requires complex multiprocessing libraries and high overhead.	Native support via multi-threading libraries (Rayon) and Message Passing Interface (MPI).

Exhaustive scalability tests evaluating models such as Flockers, Wolf-Sheep-Grass, and Schelling segregation reveal that krABMaga vastly outperforms Python's Mesa, Julia's Agents.jl, NetLogo, and Java-based MASON across multiple metrics.⁴⁵ In high-workload capacity benchmarks, krABMaga maintains rapid execution speeds while simulating up to 128,000 concurrent agents.⁴⁵ Additionally, krABMaga natively features mechanisms for model exploration and Bayesian optimization across parallel, distributed, and cloud execution environments (such as AWS EC2 virtual clusters), a capability completely absent from the standard Mesa deployment.⁶

The transition from Mesa to krABMaga would profoundly alter the scientific potential of the proposed weather mesh study. Freed from the computational limits of Python, researchers

could expand the 100×100 nm synthetic archipelago into a geographically accurate representation of the entire Baltic Sea or English Channel.¹ The vessel count could scale from one hundred to tens of thousands, allowing the hop-limited gossip protocol to be rigorously stress-tested in highly dense shipping bottlenecks where packet collision and radio interference are most acute. Furthermore, krABMaga's native support for Bayesian optimization could automate the calibration of the myriad hyperparameters governing the evacuation logits (e.g., $b_0, \alpha, \beta, \gamma$), eliminating the need for manual sensitivity sweeps.¹

Strategic Recommendations for Future Model Trajectories

The proposed decentralized weather mesh network simulation presents a highly innovative, causally linked approach to resolving maritime information latency and mitigating human error.¹ However, to bridge the substantial gap between this abstract academic proof-of-concept and a robust, regulatory-grade risk analysis tool, several fundamental architectural and theoretical enhancements must be integrated into the engine.

1. **Transition to Data-Driven AIS Routing and Artificial Force Fields:** The manual HTML waypoint lane-builder restricts the simulation to an idealized, geometric track-keeping exercise.¹ The model must integrate historical AIS data streams to generate authentic, stochastic traffic distributions.³ By adopting the TU Delft Artificial Force Field

methodology pioneered by Xiao, vessels will naturally deviate from their routes in response to attractive destination forces and repulsive environmental hazards.¹³ This integration will result in a significantly more accurate, emergent representation of maritime near-misses and COLREGs-compliant collision avoidance behaviors.³

2. **Implementation of Probabilistic Damage and Survivability Functions:** The current simulation's reliance on an arbitrary three-strike stability threshold for hull integrity is overly deterministic and ignores collision physics.¹ The model must integrate the crashworthiness and damage probability density functions established by Marie Lützen and Peter Friis-Hansen.²⁵ By utilizing the SIMCOL methodology to calculate the survivability factor based on impact geometry and absorbed kinetic energy, the simulation will accurately link collision severity directly to structural survivability and evacuation necessity.²⁵ S_i
3. **Modernization of Search and Rescue Logistics for Extreme Environments:** The deterministic, omniscient dispatch of rescue assets to static coordinates severely inflates the validity of the survival metrics.¹ The simulation must adopt the principles of the MASSIM framework, simulating hydrodynamic target drift and applying recognized IAMSAR search patterns to locate evading or drifting liferafts.⁵ Furthermore, incorporating Behrooz Ashrafi's expert-mapped weather severity matrices and Monte Carlo meteorological scripting will accurately reflect the operational limitations, mechanical failure rates, and "no-go" thresholds of helicopters operating in extreme maritime environments like the Barents Sea.³³
4. **Framework Migration for Massive Computational Scalability:** To simulate basin-wide traffic dynamics and prevent critical computational bottlenecks, the core engine must be migrated from Python's Mesa framework to Rust's krABMaga.¹ This architectural shift to Safe Rust and the Bevy ECS will unlock memory-safe, concurrent execution, allowing the model to process hundreds of thousands of active agents simultaneously.⁷ This scalability is essential for facilitating the high-resolution, distributed Monte Carlo experiments required to generate unassailable statistical confidence intervals.
5. **Alignment with IALA and IWRAP Reporting Standards:** While the proprietary KPIs utilized in the study effectively isolate the utility of the mesh network within the sandbox, they isolate the research from maritime regulatory bodies.¹ By programming the simulation to output its agent data into a synthetic AIS format, the results can be directly ingested by the IWRAP Mk II software.² This will generate recognized geometric and causation probabilities ($N_c = N_a \cdot P_c$), conclusively proving whether the weather mesh network practically lowers the expected annual collision frequency of a defined waterway to acceptable international regulatory thresholds.²

Concluding Synthesis

The exhaustive evaluation of the decentralized weather mesh networking simulation reveals a highly promising, sophisticated agent-based approach to mitigating human error through

real-time, peer-to-peer hazard communication.¹ By formally linking communication latency, circadian fatigue, and tactical evacuation readiness through the dynamic preparedness score (

P_{prep}), the proposed model successfully advances the academic discourse beyond the static fault-tree analyses traditionally employed in maritime risk assessment, moving firmly into the realm of dynamic, behavioral micro-simulation.¹

However, critical systemic limitations constrain its current operational validity and real-world applicability. The reliance on manual waypoint routing, deterministic collision physics, idealized and omniscient rescue logistics, and the severe computational bottlenecks inherent in the Python Mesa framework artificially simplify the chaotic maritime domain.¹ As evidenced by the severely truncated nature of the supplementary research brief, a comprehensive, defensible simulation must encompass the full spectrum of physical, computational, and operational realities.¹

To evolve from a theoretical academic sandbox into a robust, regulatory-grade maritime risk assessment tool, the simulation must assimilate the methodologies pioneered by leading European maritime institutes. By integrating AIS-driven Artificial Force Fields for dynamic trajectory resolution¹⁴, applying DTU's advanced probabilistic survivability models to replace rigid damage counters²⁴, adopting rigorous MASSIM search algorithms calibrated for extreme Arctic weather⁵, and migrating the entire engine to the highly scalable, memory-safe krABMaga architecture⁷, the model can fully capture the stochastic, complex nature of maritime navigation. Implementing these advanced architectures will ultimately provide maritime regulators, port authorities, and industry stakeholders with an unprecedented, high-fidelity instrument for evaluating the life-saving potential of decentralized communication networks across the global maritime domain.

Cytowane prace

1. report.pdf
2. Models for Estimating the Potential Number of Ship Collisions | The Journal of Navigation | Cambridge Core, otwierano: czerwca 15, 2026, <https://www.cambridge.org/core/journals/journal-of-navigation/article/models-for-estimating-the-potential-number-of-ship-collisions/CB525470B2DC2519C13A7924068588B0>
3. Influence of external conditions and vessel encounters on vessel behavior in ports and waterways using Automatic Identification System data | Request PDF - ResearchGate, otwierano: czerwca 15, 2026, https://www.researchgate.net/publication/312456872_Influence_of_external_conditions_and_vessel_encounters_on_vessel_behavior_in_ports_and_waterways_using_Automatic_Identification_System_data
4. An Agent-Based Ship Firefighting Model - MDPI, otwierano: czerwca 15, 2026, <https://www.mdpi.com/2077-1312/9/8/902>
5. AGENT-BASED MODEL OF MARITIME SEARCH OPERATIONS: A VALIDATION USING TEST-DRIVEN SIMULATION MODELLING, otwierano: czerwca 15, 2026,

- <http://simulation.su/uploads/files/default/2015-bhakti-mumtaz.pdf>
6. krABMaga: A modern developing art for reliable and efficient Agent-based Model (ABM) simulation with the Rust language - GitHub, otwierano: czerwca 15, 2026, <https://github.com/krABMaga/krABMaga>
 7. Reliable and Efficient Agent-Based Modeling and Simulation - JASSS, otwierano: czerwca 15, 2026, <https://www.jasss.org/27/2/4.html>
 8. Traffic studies | MARIN, otwierano: czerwca 15, 2026, <https://www.marin.nl/en/markets/authorities-and-regulators/traffic-studies>
 9. Ports & Waterways Nautical Traffic Lab (PWNT Lab) - TU Delft, otwierano: czerwca 15, 2026, <https://www.tudelft.nl/en/ceg/about-faculty/departments/hydraulic-engineering/sections/rivers-and-ports/research/ports-waterways-nautical-traffic-lab>
 10. Every ship counts on maritime traffic map - Delta - TU Delft, otwierano: czerwca 15, 2026, <https://delta.tudelft.nl/en/article/every-ship-counts-maritime-traffic-map>
 11. WAY: Estimation of Vessel Destination in Worldwide AIS Trajectory - arXiv, otwierano: czerwca 15, 2026, <https://arxiv.org/html/2512.13190v1>
 12. A Quasi-Intelligent Maritime Route Extraction from AIS Data - MDPI, otwierano: czerwca 15, 2026, <https://www.mdpi.com/1424-8220/22/22/8639>
 13. Nautical traffic simulation with multi-agent system - University of Huddersfield Repository, otwierano: czerwca 15, 2026, https://eprints.hud.ac.uk/id/eprint/23345/1/Xiao_Gulijk_Nautical_traffic_simulation_with_multi-agent_system.pdf
 14. Nautical traffic simulation with multi-agent system for safety - ResearchGate, otwierano: czerwca 15, 2026, https://www.researchgate.net/publication/269332267_Nautical_traffic_simulation_with_multi-agent_system_for_safety
 15. Review of Probabilistic Risk Assessment Models for Ship Collisions with Structures, otwierano: czerwca 15, 2026, https://www.researchgate.net/publication/359602497_Review_of_Probabilistic_Risk_Assessment_Models_for_Ship_Collisions_with_Structures
 16. Delft University of Technology Document Version Final published version Licence CC BY-NC-SA Citation (APA) van Koningsveld, M., - TU Delft Research Portal, otwierano: czerwca 15, 2026, https://research.tudelft.nl/files/147632683/43_Book_Manuscript_398_1_10_20230209.pdf
 17. Probabilistic Collision and Grounding Analysis - IWRAP - IALA, otwierano: czerwca 15, 2026, https://www.iala.int/wiki/iwrap/index.php/Probabilistic_Collision_and_Grounding_Analysis
 18. Introduction - IWRAP - IALA, otwierano: czerwca 15, 2026, <https://www.iala.int/wiki/iwrap/index.php/Introduction>
 19. iwrap mk ii working document basic modelling principles for prediction of collision and grounding frequency - IALA, otwierano: czerwca 15, 2026, https://www.iala.int/wiki/iwrap/images/2/2b/IWRAP_Theory.pdf

20. Interpretation of causation factors in IWRAP - IALA, otwierano: czerwca 15, 2026, https://www.iala.int/wiki/iwrap/index.php/Interpretation_of_causation_factors_in_IWRAP
21. Ship Collision Risk Assessment at Water Area of Container Terminal due to Marine Traffic in the Surabaya West Access Channel, otwierano: czerwca 15, 2026, <https://www.clausiuspress.com/conferences/AEASR/MASTIC%202018/045PID.pdf>
22. Causation Probability Modelling - IWRAP - IALA, otwierano: czerwca 15, 2026, https://www.iala.int/wiki/iwrap/index.php/Causation_Probability_Modelling
23. Influences of variables on ship collision probability in a Bayesian belief network model, otwierano: czerwca 15, 2026, https://www.researchgate.net/publication/235444275_Influences_of_variables_on_ship_collision_probability_in_a_Bayesian_belief_network_model
24. (PDF) Ship collision damage - ResearchGate, otwierano: czerwca 15, 2026, https://www.researchgate.net/publication/264374677_Ship_collision_damage
25. SIMPLIFIED SHIP COLLISION MODEL - VTechWorks, otwierano: czerwca 15, 2026, <https://vtechworks.lib.vt.edu/server/api/core/bitstreams/051399cf-0baa-4a8e-9a87-bd395a8c2c4d/content>
26. PROBABILISTIC DAMAGE STABILITY: Knowledge and Understanding - DergiPark, otwierano: czerwca 15, 2026, <https://dergipark.org.tr/en/download/article-file/1044676>
27. (PDF) Structural Design and Response in Collision and Grounding - ResearchGate, otwierano: czerwca 15, 2026, https://www.researchgate.net/publication/252788157_Structural_Design_and_Response_in_Collision_and_Grounding
28. test-driven simulation modelling: a case study using agent-based - Lancaster EPrints, otwierano: czerwca 15, 2026, https://eprints.lancs.ac.uk/id/eprint/78979/1/TDSM_MASSIM_article_accepted.pdf
29. Multi-agent optimization of the intermodal terminal main parameters by using AnyLogic simulation platform_ Case study on the Nin, otwierano: czerwca 15, 2026, <https://www.anylogic.com/upload/iblock/283/283c854fe14c85dbaf5282dd6cab868f.pdf>
30. Unmanned Vehicle Collaboration Research Environment for Maritime Search and Rescue - ICAS - International Council of the Aeronautical Sciences, otwierano: czerwca 15, 2026, https://www.icas.org/icas_archive/ICAS2016/data/papers/2016_0728_paper.pdf
31. Optimizing Heterogeneous Maritime Search Teams using an Agent-based Model and Nonlinear Optimization Methods - Semantic Scholar, otwierano: czerwca 15, 2026, <https://pdfs.semanticscholar.org/b228/51c62395e28a4fbaed9cb6da572e426d3414.pdf>
32. Search Problem Classification (From Karatas (2012)). - ResearchGate, otwierano: czerwca 15, 2026, https://www.researchgate.net/figure/Search-Problem-Classification-From-Karatas-2012_fig1_302480623

33. Behrooz Ashrafi - Norwegian Research Information Repository, otwierano: czerwca 15, 2026, <https://nva.sikt.no/research-profile/1180305>
34. Agent-based modelling and analysis of search and rescue (SAR) operations in the Barents Sea, otwierano: czerwca 15, 2026, <https://rpsonline.com.sg/proceedings/esrel2023/pdf/P580.pdf>
35. A Network-based Simulation Model for Helicopter Rescue Time Estimation in the Canadian Arctic, otwierano: czerwca 15, 2026, <https://ojs.iscram.org/index.php/Proceedings/article/download/150/133/1256>
36. An agent-based modelling framework for performance assessment of search and rescue operations in the Barents Sea - Kyung Hee University, otwierano: czerwca 15, 2026, <https://khu.elsevierpure.com/en/publications/an-agent-based-modelling-framework-for-performance-assessment-of-/>
37. Sushmit Dhar - Norwegian Research Information Repository, otwierano: czerwca 15, 2026, <https://nva.sikt.no/research-profile/1316239>
38. Naseri, Masoud - UiT The Arctic University of Norway, otwierano: czerwca 15, 2026, <https://en.uit.no/go/target/317510>
39. Crowd: A Social Network Simulation Framework - arXiv, otwierano: czerwca 15, 2026, <https://arxiv.org/html/2412.10781v1>
40. Agent-Based Models and Simulations Tools - Encyclopedia.pub, otwierano: czerwca 15, 2026, <https://encyclopedia.pub/entry/40674>
41. The impact of ECS logic on parallel performance in agent-based model simulations - CEUR-WS.org, otwierano: czerwca 15, 2026, <https://ceur-ws.org/Vol-4124/paper43.pdf>
42. Reliable and Efficient Agent-Based Modeling and Simulation - JASSS, otwierano: czerwca 15, 2026, <https://www.jasss.org/27/2/4/4.pdf>
43. krABMaga, otwierano: czerwca 15, 2026, <https://krabmaga.github.io/>
44. Experimenting with Agent-Based Model Simulation Tools - MDPI, otwierano: czerwca 15, 2026, <https://www.mdpi.com/2076-3417/13/1/13>
45. Comparison of agent-based modeling software - Grokipedia, otwierano: czerwca 15, 2026, https://grokipedia.com/page/Comparison_of_agent-based_modeling_software
46. JuliaDynamics/ABMFrameworksComparison: Benchmarks and comparisons of leading ABM frameworks - GitHub, otwierano: czerwca 15, 2026, <https://github.com/JuliaDynamics/ABMFrameworksComparison>
47. GitHub - isislab-unisa/ABM_Comparison: Code used for the performance comparison for the article "Experimenting with Agent-based Model Simulation Tools", otwierano: czerwca 15, 2026, https://github.com/isislab-unisa/ABM_Comparison