

# Version Control with Git

(index.html)

## Creating a Repository

### ✦ Learning Objectives

- Create a local Git repository.

Once Git is configured, we can start using it. Let's create a directory for our work and then move into that directory:

```
$ mkdir planets
$ cd planets
```

Then we tell Git to make `planets` a [repository](#) ([reference.html#repository](#))—a place where Git can store versions of our files:

```
$ git init
```

If we use `ls` to show the directory's contents, it appears that nothing has changed:

```
$ ls
```

But if we add the `-a` flag to show everything, we can see that Git has created a hidden directory within `planets` called `.git`:

```
$ ls -a
```

```
.  .. .git
```

Git stores information about the project in this special sub-directory. If we ever delete it, we will lose the project's history.

We can check that everything is set up correctly by asking Git to tell us the status of our project:

```
$ git status
```

```
# On branch master
#
# Initial commit
#
nothing to commit (create/copy files and use "git add" to track)
```

## Places to Create Git Repositories

Dracula starts a new project, `moons`, related to his `planets` project. Despite Wolfman's concerns, he enters the following sequence of commands to create one Git repository inside another:

```
cd                # return to home directory
mkdir planets    # make a new directory planets
cd planets       # go into planets
git init         # make the planets directory a Git repository
mkdir moons      # make a sub-directory planets/moons
cd moons         # go into planets/moons
git init         # make the moons sub-directory a Git repository
```

Why is it a bad idea to do this? How can Dracula “undo” his last `git init`?

---

Software Carpentry (<http://software-carpentry.org>)

Source (<https://github.com/swcarpentry/git-novice>)

Contact (<mailto:admin@software-carpentry.org>)

License ([LICENSE.html](#))