

Rally Connect Input CSV Maker Mapping Guide

V1.52

Last mapping update: September 2, 2026 - V1.52

This readable guide summarizes source priority, output-field transforms, warning behavior, and the current output schema. The field `rightsDRMrequired` is excluded from output files, Validator schema checks, and Show Mappings.

Workflow Priority

Priority	Source	What It Does
1	WhatsOn and row-producing sources	Creates output rows and maps direct fields/aliases first.
2	Connector knowledge base	Applies strict cross-reference fields such as source media, SKUs, and MediaGenix IDs.
3	Avails	Supplies VOD dates and selected identifiers on strict matches.
4	CVP Metadata	Enriches matched records with descriptions, people, genres, ratings, keywords, dates, and GUIDs when enabled.
5	Metadata Smart Sheet	Optional final override for the approved metadata fields only.
6	Publish selection	Fills selected endpoint fields with the selected publish type.
7	Final defaults/normalization	Applies final genre, rating, language, and date cleanup rules.

Important Output Rules

`assetVodStartDate` and `assetVodEndDate` are sourced from Avails only.

`assetNameSDVI` maps directly from the WhatsOn external reference with no exceptions.

`premiereDate` is always normalized to YYYY-MM-DD; unparseable values are blanked so warnings can drive correction.

`titleKeywords` uses semicolon separators, such as Drama; Family; Ranch.

If `genreMain` finishes as Animation, it is overwritten with For Kids.

If `ratingCSA`, `ratingMPA`, and `ratingTV` are all blank after enrichment, `ratingTV` defaults to tv-pg.

At startup, endpoint fields are set for all endpoints except Truth; users can change that before building.

`rightsDRMrequired` is not an output field.

Warning Rules

Warnings cover required blanks, final metadata gaps, invalid country codes, missing SKU identifiers, Avails parent SKU conflicts, blank `episodeAirOrder` on episode rows, and `descriptionShort`/`descriptionSeason`/`descriptionSeries` values over 150 characters.

Field Mapping Reference

The table below is grouped by output field. The downloadable spreadsheet contains the same data in a sortable field-by-field format.

assetNameSDVI

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: assetNameSDVI, asset name sdvi, asset name, sdvi asset, external reference, internal asset name, title internal alias, episode title internal alias, series title internal alias Transform: WhatsOn External reference maps directly with no exceptions. If no direct value exists, a fallback asset code may be generated from title/series text plus S###E## and truncated to 64 characters.
4	Connector knowledge base	Behavior: Fills blank connector-supported fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: WhatsOn External reference maps directly with no exceptions. If no direct value exists, a fallback asset code may be generated from title/series text plus S###E## and truncated to 64 characters.

Grandfathered

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: Grandfathered, grandfathered, is grandfathered Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
5	Default value	Behavior: Applied when no source filled the field. Details: True Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

SourceMedia

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: SourceMedia, source media, source path, source, s3 path, s3 feature path, media path, feature path, source url Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	Behavior: Overrides connector cross-reference fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

endpoint_Amazon

Priority	Source	Behavior / Details / Transform
6	Home screen publish selection	Behavior: Final pass fills selected endpoint fields with the selected publish kind. Unselected endpoints stay blank. At startup, All except Truth is selected. Details: Full Delivery, Full package replacement, Full Delete, Metadata Update. Default selected endpoints: all except Truth. Transform: Selected endpoints get the publish type selected on the home screen. At startup, all endpoint fields except endpoint_Truth are selected. Unselected endpoints stay blank.

endpoint_Roku

Priority	Source	Behavior / Details / Transform
6	Home screen publish selection	Behavior: Final pass fills selected endpoint fields with the selected publish kind. Unselected endpoints stay blank. At startup, All except Truth is selected. Details: Full Delivery, Full package replacement, Full Delete, Metadata Update. Default selected endpoints: all except Truth. Transform: Selected endpoints get the publish type selected on the home screen. At startup, all endpoint fields except endpoint_Truth are selected. Unselected endpoints stay blank.

endpoint_Frndly

Priority	Source	Behavior / Details / Transform
6	Home screen publish selection	Behavior: Final pass fills selected endpoint fields with the selected publish kind. Unselected endpoints stay blank. At startup, All except Truth is selected. Details: Full Delivery, Full package replacement, Full Delete, Metadata Update. Default selected endpoints: all except Truth. Transform: Selected endpoints get the publish type selected on the home screen. At startup, all endpoint fields except endpoint_Truth are selected. Unselected endpoints stay blank.

endpoint_YouTube

Priority	Source	Behavior / Details / Transform
6	Home screen publish selection	Behavior: Final pass fills selected endpoint fields with the selected publish kind. Unselected endpoints stay blank. At startup, All except Truth is selected. Details: Full Delivery, Full package replacement, Full Delete, Metadata Update. Default selected endpoints: all except Truth. Transform: Selected endpoints get the publish type selected on the home screen. At startup, all endpoint fields except endpoint_Truth are selected. Unselected endpoints stay blank.

endpoint_Truth

Priority	Source	Behavior / Details / Transform
6	Home screen publish selection	Behavior: Final pass fills selected endpoint fields with the selected publish kind. Unselected endpoints stay blank. At startup, All except Truth is selected. Details: Full Delivery, Full package replacement, Full Delete, Metadata Update. Default selected endpoints: all except Truth. Transform: Selected endpoints get the publish type selected on the home screen. At startup, all endpoint fields except endpoint_Truth are selected. Unselected endpoints stay blank.

assetVodStartDate

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: assetVodStartDate, asset vod start date, tvod start date, start, start date, window start, rights start, license start Transform: Uses Avails only. Common date formats are normalized to YYYY-MM-DD when recognized.
2	Avails input	Behavior: Direct Avails match overrides VOD dates. Parent series and season rows roll up earliest matched episode dates. Details: ExternalReference, NewSku, CVP SKU, GUID, TMS, MediaGenix IDs, exact title, or WhatsOn VOD ID SKU/VOD ID SKU CVP to Avails ALID when Connector did not match Transform: Uses Avails only. Common date formats are normalized to YYYY-MM-DD when recognized.

assetVodEndDate

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: assetVodEndDate, asset vod end date, tvod end date, end, end date, window end, fixed end date, rights end, license end Transform: Uses Avails only. Common date formats are normalized to YYYY-MM-DD when recognized.
2	Avails input	Behavior: Direct Avails match overrides VOD dates. Parent series and season rows roll up earliest matched episode dates. Details: ExternalReference, NewSku, CVP SKU, GUID, TMS, MediaGenix IDs, exact title, or WhatsOn VOD ID SKU/VOD ID SKU CVP to Avails ALID when Connector did not match Transform: Uses Avails only. Common date formats are normalized to YYYY-MM-DD when recognized.

contentType

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: contentType, content type, work type, worktype, asset type, type Transform: Normalizes film/feature/program to movie, episode variants to episode, parent series to series, and WhatsOn Series rows with season data to season.
4	Connector knowledge base	Behavior: Fills blank connector-supported fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: Normalizes film/feature/program to movie, episode variants to episode, parent series to series, and WhatsOn Series rows with season data to season.

titleVod

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: titleVod, title vod, title, whats on title, program title, movie title, episode title display unlimited, episode title internal alias, episode title Transform: Uses direct title mapping for movies, episodes, and parent series rows. Season rows can be formed from the parent series title plus ' Season ' plus the season number when creating season placeholders.
4	Connector knowledge base	Behavior: Fills blank connector-supported fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: Uses direct title mapping for movies, episodes, and parent series rows. Season rows can be formed from the parent series title plus ' Season ' plus the season number when creating season placeholders.

titleSeries

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: titleSeries, title series, series title, series name, parent series, series title display unlimited, series title internal alias Transform: Uses the parent series title. Parent series rows also keep titleVod populated with the same series title.

titleEpisode

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: titleEpisode, title episode, episode title, episode name, episode title display, episode title display unlimited, episode title internal alias Transform: For episode rows, copies titleVod into titleEpisode when titleEpisode is blank.

seasonNumber

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: seasonNumber, season number, season, seasonnumber Transform: Converts numeric-looking values to an integer; season placeholder rows use the related season number.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Converts numeric-looking values to an integer; season placeholder rows use the related season number.
4	Connector knowledge base	Behavior: Fills blank connector-supported fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: Converts numeric-looking values to an integer; season placeholder rows use the related season number.

episodeAirOrder

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: episodeAirOrder, episode air order, episode number, episode #, episode, distribution number, episodenummer Transform: Converts numeric-looking values to a normalized episode order; blank episode values warn.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Converts numeric-looking values to a normalized episode order; blank episode values warn.

IdGUID

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: IdGUID, id guid, guid, global id, uuid, mpx guid Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Fills blank values only. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	Behavior: Fills blank connector-supported fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

idSku

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: idSku, id sku, vod id sku, newsku, new sku Transform: Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.
2	Avails input	Behavior: Fills blank SKU fields after WhatsOn and before CVP. Details: NewSku, New SKU Transform: Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.
3	CVP Metadata knowledge base	Behavior: Fills blank values only. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.
4	Connector knowledge base	Behavior: Fills blank connector-supported fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: New SKU. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.

idSku_CVP

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: idSku_CVP, id sku cvp, vod id sku cvp, cvp sku, content id Transform: CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.
2	Avails input	Behavior: Fills blank SKU fields after WhatsOn and before CVP. Details: ContentID, EpisodeContentID, Episode ContentID, CVP_SKU, CVP SKU Transform: CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.
3	CVP Metadata knowledge base	Behavior: Fills blank values only. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.
4	Connector knowledge base	Behavior: Fills blank connector-supported fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.

vodSeriesId (SKU)

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: vodSeriesId (SKU), series newsku, series new sku, parentseriesmediaid Transform: Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.
2	Avails input	Behavior: Fills blank SKU fields after WhatsOn and before CVP. Details: Series NewSku, Series New SKU, ParentSeriesMediaID, SeriesAltID, Series Alt ID Transform: Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.
3	CVP Metadata knowledge base	Behavior: Fills blank values only. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.

vodSeriesId (SKU)_CVP

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: vodSeriesId (SKU)_CVP, vod series id cvp, series cvp sku, series content id, cvp series id Transform: CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.
2	Avails input	Behavior: Fills blank SKU fields after WhatsOn and before CVP. Details: vodSeriesId (SKU)_CVP, Series ContentID, Series CVP_SKU, Series CVP SKU, CVP Series ID, SeriesAltID, Series Alt ID Transform: CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.
3	CVP Metadata knowledge base	Behavior: Fills blank values only. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.
4	Connector knowledge base	Behavior: Overrides connector cross-reference fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.

vodSeasonId (SKU)

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: vodSeasonId (SKU), season newsku, season new sku Transform: Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.
2	Avails input	Behavior: Fills blank SKU fields after WhatsOn and before CVP. Details: Season NewSku, Season New SKU, SeasonAltID, Season Alt ID Transform: Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.
3	CVP Metadata knowledge base	Behavior: Fills blank values only. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.

vodSeasonId (SKU)_CVP

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: vodSeasonId (SKU)_CVP, vod season id cvp, season cvp sku, season content id, cvp season id Transform: CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.
2	Avails input	Behavior: Fills blank SKU fields after WhatsOn and before CVP. Details: vodSeasonId (SKU)_CVP, Season ContentID, Season CVP_SKU, Season CVP SKU, CVP Season ID, SeasonAltID, Season Alt ID Transform: CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.
3	CVP Metadata knowledge base	Behavior: Fills blank values only. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.
4	Connector knowledge base	Behavior: Overrides connector cross-reference fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.

idTMS

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: idTMS, id tms, tms id, tmsnumber, tms number Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
2	Avails input	Behavior: Overrides with tab-specific Avails retailer IDs. Season rows stay blank. Details: Movies!RetailerID1, TV!RetailerEpisodeID1, TV!RetailerSeriesID Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	Behavior: Fills blank connector-supported fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

idTMS_series

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: idTMS_series, id tms series, series tms id Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
2	Avails input	Behavior: Overrides episode and series/show rows from TV-tab series retailer IDs. Details: TV!RetailerSeriesID Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

descriptionLong

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: descriptionLong, description long, long description, long description printed press, listing description, description, synopsis Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	Behavior: Fills blank connector-supported fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Short Description [110 Characters]. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

descriptionMedium

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: descriptionMedium, description medium, medium description, listing description, description Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Short Description [110 Characters]. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

descriptionShort

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: descriptionShort, description short, listing description, short synopsis Transform: CVP shortDescription is preferred only at 150 characters or less. Longer values can populate but warn.
3	CVP Metadata knowledge base	Behavior: Preferred over mapped values only when CVP Short Description is 150 characters or less. Longer CVP values fill blanks only and are reported in warnings. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: CVP shortDescription is preferred only at 150 characters or less. Longer values can populate but warn.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Short Description [110 Characters]. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: CVP shortDescription is preferred only at 150 characters or less. Longer values can populate but warn.

descriptionSeason

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: descriptionSeason, description season, season description, short description, additional description 2 Transform: Longer than 150 characters warns. Movie rows clear these fields because season/series descriptions do not apply.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Longer than 150 characters warns. Movie rows clear these fields because season/series descriptions do not apply.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Matched parent season Short Description [110 Characters]. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Longer than 150 characters warns. Movie rows clear these fields because season/series descriptions do not apply.

descriptionSeries

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: descriptionSeries, description series, series description, short description Transform: Longer than 150 characters warns. Movie rows clear these fields because season/series descriptions do not apply.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Longer than 150 characters warns. Movie rows clear these fields because season/series descriptions do not apply.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Matched parent series Short Description [110 Characters]. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Longer than 150 characters warns. Movie rows clear these fields because season/series descriptions do not apply.

studio

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: studio, recording studio, company display credit, company, production company Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	Behavior: Fills blank connector-supported fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Provider. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

productionCompany

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: productionCompany, production company, productioncompany Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Provider. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

countryOrigin

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: countryOrigin, country origin, country of origin, origin country, production regions Transform: Normalizes recognized country names and aliases to MovieLabs ISO 3166 alpha-2 codes. Nonblank values that cannot be normalized to two letters remain warning-eligible.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Normalizes recognized country names and aliases to MovieLabs ISO 3166 alpha-2 codes. Nonblank values that cannot be normalized to two letters remain warning-eligible.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Country of Origin. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Normalizes recognized country names and aliases to MovieLabs ISO 3166 alpha-2 codes. Nonblank values that cannot be normalized to two letters remain warning-eligible.

actorName1

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: actorName1, actor name 1, actor 1, cast 1, principal cast 1 Transform: From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
1	WhatsOn Cast (sorted)	Behavior: Uses comma-separated Cast (sorted) value 1; only the first four cast names are used. Details: Cast (sorted), Cast sorted, cast, cast names, actors, principal cast, principalcast, actor names, actornames Transform: From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Narrator, Actors. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.

actorOrder1

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: actorOrder1 Transform: Fills the matching numeric order only when the corresponding actorName field is populated.
1	WhatsOn Cast (sorted)	Behavior: Fills 1 when actorName1 is populated from the comma-separated Cast (sorted) value. Details: Cast (sorted), Cast sorted, cast, cast names, actors, principal cast, principalcast, actor names, actornames Transform: Fills the matching numeric order only when the corresponding actorName field is populated.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Fills the matching numeric order only when the corresponding actorName field is populated.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Narrator, Actors. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Fills the matching numeric order only when the corresponding actorName field is populated.

actorName2

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: actorName2, actor name 2, actor 2, cast 2, principal cast 2 Transform: From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
1	WhatsOn Cast (sorted)	Behavior: Uses comma-separated Cast (sorted) value 2; only the first four cast names are used. Details: Cast (sorted), Cast sorted, cast, cast names, actors, principal cast, principalcast, actor names, actornames Transform: From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Actors. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.

actorOrder2

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: actorOrder2 Transform: Fills the matching numeric order only when the corresponding actorName field is populated.
1	WhatsOn Cast (sorted)	Behavior: Fills 2 when actorName2 is populated from the comma-separated Cast (sorted) value. Details: Cast (sorted), Cast sorted, cast, cast names, actors, principal cast, principalcast, actor names, actornames Transform: Fills the matching numeric order only when the corresponding actorName field is populated.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Fills the matching numeric order only when the corresponding actorName field is populated.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Actors. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Fills the matching numeric order only when the corresponding actorName field is populated.

actorName3

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: actorName3, actor name 3, actor 3, cast 3, principal cast 3 Transform: From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
1	WhatsOn Cast (sorted)	Behavior: Uses comma-separated Cast (sorted) value 3; only the first four cast names are used. Details: Cast (sorted), Cast sorted, cast, cast names, actors, principal cast, principalcast, actor names, actornames Transform: From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Actors. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.

actorOrder3

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: actorOrder3 Transform: Fills the matching numeric order only when the corresponding actorName field is populated.
1	WhatsOn Cast (sorted)	Behavior: Fills 3 when actorName3 is populated from the comma-separated Cast (sorted) value. Details: Cast (sorted), Cast sorted, cast, cast names, actors, principal cast, principalcast, actor names, actornames Transform: Fills the matching numeric order only when the corresponding actorName field is populated.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Fills the matching numeric order only when the corresponding actorName field is populated.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Actors. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Fills the matching numeric order only when the corresponding actorName field is populated.

actorName4

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: actorName4, actor name 4, actor 4, cast 4, principal cast 4 Transform: From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
1	WhatsOn Cast (sorted)	Behavior: Uses comma-separated Cast (sorted) value 4; only the first four cast names are used. Details: Cast (sorted), Cast sorted, cast, cast names, actors, principal cast, principalcast, actor names, actornames Transform: From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Actors. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.

actorOrder4

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: actorOrder4 Transform: Fills the matching numeric order only when the corresponding actorName field is populated.
1	WhatsOn Cast (sorted)	Behavior: Fills 4 when actorName4 is populated from the comma-separated Cast (sorted) value. Details: Cast (sorted), Cast sorted, cast, cast names, actors, principal cast, principalcast, actor names, actornames Transform: Fills the matching numeric order only when the corresponding actorName field is populated.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Fills the matching numeric order only when the corresponding actorName field is populated.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Actors. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Fills the matching numeric order only when the corresponding actorName field is populated.

director1

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: director1, director 1, director, directors Transform: Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
4	Connector knowledge base	Behavior: Fills blank connector-supported fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Directors. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.

director2

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: director2, director 2 Transform: Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Directors. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.

producer1

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: producer1, producer 1, producer, producers Transform: Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Producer, Producers. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.

producer2

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: producer2, producer 2 Transform: Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Producer, Producers. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.

writer1

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: writer1, writer 1, writer Transform: Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Writers. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.

writer2

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: writer2, writer 2 Transform: Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Writers. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.

genreMain

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: genreMain, genre main, main genre, genre, category Transform: Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1. On the final pass, a genreMain value of Animation is overwritten with For Kids.
3	CVP Metadata knowledge base	Behavior: Fills blank values only. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1. On the final pass, a genreMain value of Animation is overwritten with For Kids.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Genre. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1. On the final pass, a genreMain value of Animation is overwritten with For Kids.
7	Final pass normalization	Behavior: After all source and enrichment passes, Animation is overwritten with For Kids. Details: Animation -> For Kids Transform: Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1. On the final pass, a genreMain value of Animation is overwritten with For Kids.

genreSub1

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: genreSub1, genre sub 1, subgenre 1, genre 2 Transform: Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1.
3	CVP Metadata knowledge base	Behavior: Fills blank values only. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Genre. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1.

genreSub2

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: genreSub2, genre sub 2, subgenre 2, genre 3 Transform: Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1.
3	CVP Metadata knowledge base	Behavior: Fills blank values only. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Genre. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1.

productionYear

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: productionYear, production year, release year, releaseyear Transform: Preserves the mapped source year; used only as a final fallback for blank premiereYear and premiereDate.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Preserves the mapped source year; used only as a final fallback for blank premiereYear and premiereDate.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Global Premiere Date year. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Preserves the mapped source year; used only as a final fallback for blank premiereYear and premiereDate.

premiereDate

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: premiereDate, premiere date, date 1, date1, pubdate, pub date, release history original, original release date Transform: Final output is always YYYY-MM-DD. Parses YYYY-MM-DD, MM/DD/YYYY, MM/DD/YY, YYYY/MM/DD, and ISO date-time prefixes. A four-digit year becomes YYYY-01-01. Unparseable nonblank values are blanked so they can be corrected from warnings. If still blank, the final fallback can derive YYYY-01-01 from premiereYear or productionYear.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Final output is always YYYY-MM-DD. Parses YYYY-MM-DD, MM/DD/YYYY, MM/DD/YY, YYYY/MM/DD, and ISO date-time prefixes. A four-digit year becomes YYYY-01-01. Unparseable nonblank values are blanked so they can be corrected from warnings. If still blank, the final fallback can derive YYYY-01-01 from premiereYear or productionYear.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Global Premiere Date. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Final output is always YYYY-MM-DD. Parses YYYY-MM-DD, MM/DD/YYYY, MM/DD/YY, YYYY/MM/DD, and ISO date-time prefixes. A four-digit year becomes YYYY-01-01. Unparseable nonblank values are blanked so they can be corrected from warnings. If still blank, the final fallback can derive YYYY-01-01 from premiereYear or productionYear.

premiereYear

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: premiereYear, premiere year Transform: Uses the mapped source value when present. If blank, derives the year from premiereDate; if premiereDate is blank too, productionYear can be copied as the final fallback.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Uses the mapped source value when present. If blank, derives the year from premiereDate; if premiereDate is blank too, productionYear can be copied as the final fallback.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Global Premiere Date year. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Uses the mapped source value when present. If blank, derives the year from premiereDate; if premiereDate is blank too, productionYear can be copied as the final fallback.

Series_Release_Date

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: Series_Release_Date, series release date, series_release_date Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

ratingCSA

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: ratingCSA, rating csa, csa rating Transform: Normalizes rating text by removing scheme labels/placeholders and lowercasing the rating value.
3	CVP Metadata knowledge base	Behavior: Fills blank values only. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Normalizes rating text by removing scheme labels/placeholders and lowercasing the rating value.

ratingCSAAdvisory

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: ratingCSAAdvisory, rating csa advisory, csa advisory Transform: CVP parental warning is copied only to the advisory field that corresponds to the rating scheme found.
3	CVP Metadata knowledge base	Behavior: Fills blank values only. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: CVP parental warning is copied only to the advisory field that corresponds to the rating scheme found.

ratingMPA

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: ratingMPA, rating mpa, rating mpaa, mpa rating, mpaa rating Transform: Normalizes rating text by removing scheme labels/placeholders and lowercasing the rating value.
3	CVP Metadata knowledge base	Behavior: Fills blank values only. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Normalizes rating text by removing scheme labels/placeholders and lowercasing the rating value.

ratingMPAAdvisory

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: ratingMPAAdvisory, rating mpa advisory, rating mpaa advisory, mpa advisory Transform: CVP parental warning is copied only to the advisory field that corresponds to the rating scheme found.
3	CVP Metadata knowledge base	Behavior: Fills blank values only. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: CVP parental warning is copied only to the advisory field that corresponds to the rating scheme found.

ratingTV

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: ratingTV, rating tv, tv rating, parental rating, parental rating and regulator, parental rating and regulator default regulator, parental rating and regulator (default regulator) Transform: Normalizes TV ratings to tv-g, tv-pg, tv-14, tv-ma, etc. A bare [FCC] placeholder is treated as blank. WhatsOn Parental rating and regulator (default regulator) is recognized as a ratingTV source. CVP fills ratingTV only when blank. If ratingCSA, ratingMPA, and ratingTV are all blank on the final pass, ratingTV defaults to tv-pg.
3	CVP Metadata knowledge base	Behavior: Fills blank values only. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Normalizes TV ratings to tv-g, tv-pg, tv-14, tv-ma, etc. A bare [FCC] placeholder is treated as blank. WhatsOn Parental rating and regulator (default regulator) is recognized as a ratingTV source. CVP fills ratingTV only when blank. If ratingCSA, ratingMPA, and ratingTV are all blank on the final pass, ratingTV defaults to tv-pg.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Rating. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Normalizes TV ratings to tv-g, tv-pg, tv-14, tv-ma, etc. A bare [FCC] placeholder is treated as blank. WhatsOn Parental rating and regulator (default regulator) is recognized as a ratingTV source. CVP fills ratingTV only when blank. If ratingCSA, ratingMPA, and ratingTV are all blank on the final pass, ratingTV defaults to tv-pg.
7	Final pass default	Behavior: If ratingCSA, ratingMPA, and ratingTV are all blank after enrichment, ratingTV is set to tv-pg. Details: ratingCSA blank + ratingMPA blank + ratingTV blank -> ratingTV tv-pg Transform: Normalizes TV ratings to tv-g, tv-pg, tv-14, tv-ma, etc. A bare [FCC] placeholder is treated as blank. WhatsOn Parental rating and regulator (default regulator) is recognized as a ratingTV source. CVP fills ratingTV only when blank. If ratingCSA, ratingMPA, and ratingTV are all blank on the final pass, ratingTV defaults to tv-pg.

ratingTVAdvisory

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: ratingTVAdvisory, rating tv advisory, tv advisory, rating reason Transform: CVP parental warning is copied only to the advisory field that corresponds to the rating scheme found.
3	CVP Metadata knowledge base	Behavior: Fills blank values only. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: CVP parental warning is copied only to the advisory field that corresponds to the rating scheme found.

language

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: language, language 1, asset language, assetlanguage Transform: Normalizes known language values to app syntax; if blank on the final pass, defaults to en-US.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Normalizes known language values to app syntax; if blank on the final pass, defaults to en-US.
5	Final pass default	Behavior: Fills blank final values after source mapping and enrichment. Existing values are preserved. Details: en-US Transform: Normalizes known language values to app syntax; if blank on the final pass, defaults to en-US.

languageSubtitle

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: languageSubtitle, language subtitle, language 1, subtitle language, subtitling language, caption language Transform: Normalizes known language values to app syntax; if blank on the final pass, defaults to en-US.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Normalizes known language values to app syntax; if blank on the final pass, defaults to en-US.
5	Final pass default	Behavior: Fills blank final values after source mapping and enrichment. Existing values are preserved. Details: en-US Transform: Normalizes known language values to app syntax; if blank on the final pass, defaults to en-US.

rightsAllowDownload

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: rightsAllowDownload, rights allow download, download Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	Behavior: Fills blank connector-supported fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
5	Default value	Behavior: Applied when no source filled the field. Details: Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

rightsLicenseRightsDescription

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: rightsLicenseRightsDescription, rights license rights description, license rights description, rights description, all streaming rights Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	Behavior: Fills blank connector-supported fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
5	Default value	Behavior: Applied when no source filled the field. Details: SWP Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

rightsLicenseType

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: rightsLicenseType, rights license type, license type, licensetype Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	Behavior: Fills blank connector-supported fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
5	Default value	Behavior: Applied when no source filled the field. Details: SVOD Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

rightsPricingTier

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: rightsPricingTier, rights pricing tier, price type, pricing tier Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
5	Default value	Behavior: Applied when no source filled the field. Details: Category Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

rightsTerritory

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: rightsTerritory, rights territory, territory Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	Behavior: Fills blank connector-supported fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
5	Default value	Behavior: Applied when no source filled the field. Details: US Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

idParentRef

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: idParentRef, id parent ref, parent ref, parent id Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

mediaExpectedFormat

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: mediaExpectedFormat, media expected format, format profile Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	Behavior: Fills blank connector-supported fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

mediaHouseNumber

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: mediaHouseNumber, media house number, house number Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	Behavior: Overrides connector cross-reference fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

Marker_programStart:start

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: Marker_programStart:start Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

Marker_programSegment:start

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: Marker_programSegment:start Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

Marker_openingCredits:start

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: Marker_openingCredits:start Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

Marker_closingCredits:start

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: Marker_closingCredits:start Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

idMedia (MediaGenix)

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: idMedia (MediaGenix), id media, media id, mediagenix media id, mpx media id, cvp media id, cvpmediaid Transform: Normalizes MPX/CVP URLs and numeric-looking values to the trailing numeric Media ID or Program ID.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Normalizes MPX/CVP URLs and numeric-looking values to the trailing numeric Media ID or Program ID.
4	Connector knowledge base	Behavior: Overrides connector cross-reference fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: Normalizes MPX/CVP URLs and numeric-looking values to the trailing numeric Media ID or Program ID.

idProduct (MediaGenix)

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: idProduct (MediaGenix), id product, program id, mediagenix product id, mp program id, cvp program id, cvpprogramid Transform: Normalizes MPX/CVP URLs and numeric-looking values to the trailing numeric Media ID or Program ID.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Normalizes MPX/CVP URLs and numeric-looking values to the trailing numeric Media ID or Program ID.
4	Connector knowledge base	Behavior: Overrides connector cross-reference fields on identifier match. Details: External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS Transform: Normalizes MPX/CVP URLs and numeric-looking values to the trailing numeric Media ID or Program ID.

titleKeywords

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: titleKeywords, title keywords, keywords, key words, category Transform: Splits comma- or semicolon-separated inputs, trims each value, and outputs keywords separated by '; '.
3	CVP Metadata knowledge base	Behavior: Fills blank values only. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: Splits comma- or semicolon-separated inputs, trims each value, and outputs keywords separated by '; '.
5	Metadata Smart Sheet	Behavior: Optional final metadata override for selected fields only. Details: Key Words. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. Transform: Splits comma- or semicolon-separated inputs, trims each value, and outputs keywords separated by '; '.

titleSchedule

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: titleSchedule, title schedule, schedule title Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

vodMediaId (SKU)

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: vodMediaId (SKU), vod media id, media sku Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.

vodProgramId (SKU)

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	Behavior: Exact source headers and configured aliases are read first. Details: vodProgramId (SKU), vod program id, program sku Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	Behavior: Overrides mapped source values on match. Details: Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match Transform: No field-specific syntax transform beyond blank/null handling and source priority rules.