Rally Connect Input CSV Maker Mapping Guide V1.54

Last mapping update: October 9, 2026 - V1.54

This readable guide summarizes source priority, output-field transforms, warning behavior, and the current output schema. The field rightsDRMrequired is excluded from output files, Validator schema checks, and Show Mappings.

Workflow Priority

Priority	Source	What It Does
1	WhatsOn and row-producing sources	Creates output rows and maps direct fields/aliases first.
2	Connector knowledge base	Applies strict cross-reference fields such as source media, SKUs, and MediaGenix IDs.
3	Avails	Supplies VOD dates and selected identifiers on strict matches.
4	CVP Metadata	Enriches matched records with descriptions, people, genres, ratings, keywords, dates, and GUIDs when enabled.
5	Metadata Smart Sheet	Optional final override for the approved metadata fields only.
6	Publish selection	Fills selected endpoint fields with the selected publish type.
7	Final defaults/normalization	Applies final genre, rating, language, and date cleanup rules.

Important Output Rules

assetVodStartDate and assetVodEndDate are sourced from Avails only.

assetNameSDVI maps directly from the WhatsOn external reference with no exceptions.

premiereDate is always normalized to YYYY-MM-DD; unparseable values are blanked so warnings can drive correction.

titleKeywords uses semicolon separators, such as Drama; Family; Ranch.

If genreMain finishes as Animation, it is overwritten with For Kids.

If ratingCSA, ratingMPA, and ratingTV are all blank after enrichment, ratingTV defaults to tv-pg.

At startup, endpoint fields are set for all endpoints except Truth; users can change that before building.

rightsDRMrequired is not an output field.

Warning Rules

Warnings cover required blanks, final metadata gaps, invalid country codes, missing SKU identifiers, Avails parent SKU conflicts, blank episodeAirOrder on episode rows, and descriptionShort/descriptionSeason/descriptionSeries values over 150 characters.

Field Mapping Reference

The table below is grouped by output field. The downloadable spreadsheet contains the same data in a sortable field-by-field format.

assetNameSDVI

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** assetNameSDVI, asset name sdvi, asset name, sdvi asset, external reference, internal asset name, title internal alias, episode title internal alias, series title internal alias **Transform:** WhatsOn External reference maps directly with no exceptions. If no direct value exists, a fallback asset code may be generated from title/series text plus S##E## and truncated to 64 characters.
4	Connector knowledge base	**Behavior:** Fills blank connector-supported fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** WhatsOn External reference maps directly with no exceptions. If no direct value exists, a fallback asset code may be generated from title/series text plus S##E## and truncated to 64 characters.

Grandfathered

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** Grandfathered, grandfathered, is grandfathered **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
5	Default value	**Behavior:** Applied when no source filled the field. **Details:** True **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

SourceMedia

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** SourceMedia, source media, source path, source, s3 path, s3 feature path, media path, feature path, source url **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	**Behavior:** Overrides connector cross-reference fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

endpoint_Amazon

Priority	Source	Behavior / Details / Transform
6	Home screen publish selection	**Behavior:** Final pass fills selected endpoint fields with the selected publish kind. Unselected endpoints stay blank. At startup, All except Truth is selected. **Details:** Full Delivery, Full package replacement, Full Delete, Metadata Update. Default selected endpoints: all except Truth. **Transform:** Selected endpoints get the publish type selected on the home screen. At startup, all endpoint fields except endpoint_Truth are selected. Unselected endpoints stay blank.

endpoint_Roku

Priority	Source	Behavior / Details / Transform
6	Home screen publish selection	**Behavior:** Final pass fills selected endpoint fields with the selected publish kind. Unselected endpoints stay blank. At startup, All except Truth is selected. **Details:** Full Delivery, Full package replacement, Full Delete, Metadata Update. Default selected endpoints: all except Truth. **Transform:** Selected endpoints get the publish type selected on the home screen. At startup, all endpoint fields except endpoint_Truth are selected. Unselected endpoints stay blank.

endpoint_Frndly

Priority	Source	Behavior / Details / Transform
6	Home screen publish selection	**Behavior:** Final pass fills selected endpoint fields with the selected publish kind. Unselected endpoints stay blank. At startup, All except Truth is selected. **Details:** Full Delivery, Full package replacement, Full Delete, Metadata Update. Default selected endpoints: all except Truth. **Transform:** Selected endpoints get the publish type selected on the home screen. At startup, all endpoint fields except endpoint_Truth are selected. Unselected endpoints stay blank.

endpoint_YouTube

Priority	Source	Behavior / Details / Transform
6	Home screen publish selection	**Behavior:** Final pass fills selected endpoint fields with the selected publish kind. Unselected endpoints stay blank. At startup, All except Truth is selected. **Details:** Full Delivery, Full package replacement, Full Delete, Metadata Update. Default selected endpoints: all except Truth. **Transform:** Selected endpoints get the publish type selected on the home screen. At startup, all endpoint fields except endpoint_Truth are selected. Unselected endpoints stay blank.

endpoint_Truth

Priority	Source	Behavior / Details / Transform
6	Home screen publish selection	**Behavior:** Final pass fills selected endpoint fields with the selected publish kind. Unselected endpoints stay blank. At startup, All except Truth is selected. **Details:** Full Delivery, Full package replacement, Full Delete, Metadata Update. Default selected endpoints: all except Truth. **Transform:** Selected endpoints get the publish type selected on the home screen. At startup, all endpoint fields except endpoint_Truth are selected. Unselected endpoints stay blank.

assetVodStartDate

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** assetVodStartDate, asset vod start date, tvod start date, start, start date, window start, rights start, license start **Transform:** Uses Avails only. Common date formats are normalized to YYYY-MM-DD when recognized.
2	Avails input	**Behavior:** Direct Avails match overrides VOD dates. Parent series and season rows roll up earliest matched episode dates. **Details:** ExternalReference, NewSku, CVP SKU, GUID, TMS, MediaGenix IDs, exact title, or WhatsOn VOD ID SKU/VOD ID SKU CVP to Avails ALID when Connector did not match **Transform:** Uses Avails only. Common date formats are normalized to YYYY-MM-DD when recognized.

assetVodEndDate

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** assetVodEndDate, asset vod end date, tvod end date, end, end date, window end, fixed end date, rights end, license end **Transform:** Uses Avails only. Common date formats are normalized to YYYY-MM-DD when recognized.
2	Avails input	**Behavior:** Direct Avails match overrides VOD dates. Parent series and season rows roll up earliest matched episode dates. **Details:** ExternalReference, NewSku, CVP SKU, GUID, TMS, MediaGenix IDs, exact title, or WhatsOn VOD ID SKU/VOD ID SKU CVP to Avails ALID when Connector did not match **Transform:** Uses Avails only. Common date formats are normalized to YYYY-MM-DD when recognized.

contentType

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** contentType, content type, work type, worktype, asset type, type **Transform:** Normalizes film/feature/program to movie, episode variants to episode, parent series to series, and WhatsOn Series rows with season data to season.
4	Connector knowledge base	**Behavior:** Fills blank connector-supported fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** Normalizes film/feature/program to movie, episode variants to episode, parent series to series, and WhatsOn Series rows with season data to season.

titleVod

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** titleVod, title vod, title, whats on title, program title, movie title, episode title display unlimited, episode title internal alias, episode title **Transform:** Uses direct title mapping for movies, episodes, and parent series rows. Season rows can be formed from the parent series title plus ' Season ' plus the season number when creating season placeholders.
4	Connector knowledge base	**Behavior:** Fills blank connector-supported fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** Uses direct title mapping for movies, episodes, and parent series rows. Season rows can be formed from the parent series title plus ' Season ' plus the season number when creating season placeholders.

titleSeries

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** titleSeries, title series, series title, series name, parent series, series title display unlimited, series title internal alias **Transform:** Uses the parent series title. Parent series rows also keep titleVod populated with the same series title.

titleEpisode

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** titleEpisode, title episode, episode title, episode name, episode title display, episode title display unlimited, episode title internal alias **Transform:** For episode rows, copies titleVod into titleEpisode when titleEpisode is blank.

seasonNumber

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** seasonNumber, season number, season, seasonnumber **Transform:** Converts numeric-looking values to an integer; season placeholder rows use the related season number.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Converts numeric-looking values to an integer; season placeholder rows use the related season number.
4	Connector knowledge base	**Behavior:** Fills blank connector-supported fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** Converts numeric-looking values to an integer; season placeholder rows use the related season number.

episodeAirOrder

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** episodeAirOrder, episode air order, episode number, episode #, product code, episode, distribution number, episodenumber **Transform:** Uses WhatsOn Episode # first and Product code as its fallback. Converts numeric-looking values to a normalized episode order; blank episode values warn.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Uses WhatsOn Episode # first and Product code as its fallback. Converts numeric-looking values to a normalized episode order; blank episode values warn.

IdGUID

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** IdGUID, id guid, guid, global id, uuid, mpx guid **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	**Behavior:** Fills blank values only. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	**Behavior:** Fills blank connector-supported fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

idSku

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** idSku, id sku, vod id sku, newsku, new sku **Transform:** Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.
2	Avails input	**Behavior:** Fills blank SKU fields after WhatsOn and before CVP. **Details:** NewSku, New SKU **Transform:** Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.
3	CVP Metadata knowledge base	**Behavior:** Fills blank values only. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.
4	Connector knowledge base	**Behavior:** Fills blank connector-supported fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** New SKU. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.

idSku_CVP

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** idSku_CVP, id sku cvp, vod id sku cvp, cvp sku, content id **Transform:** CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.
2	Avails input	**Behavior:** Fills blank SKU fields after WhatsOn and before CVP. **Details:** ContentID, EpisodeContentID, Episode ContentID, CVP_SKU, CVP SKU **Transform:** CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.
3	CVP Metadata knowledge base	**Behavior:** Fills blank values only. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.
4	Connector knowledge base	**Behavior:** Fills blank connector-supported fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.

vodSeriesId (SKU)

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** vodSeriesId (SKU), series newsku, series new sku, parentseriesmediaid **Transform:** Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.
2	Avails input	**Behavior:** Fills blank SKU fields after WhatsOn and before CVP. **Details:** Series NewSku, Series New SKU, ParentSeriesMediaID, SeriesAltID, Series Alt ID **Transform:** Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.
3	CVP Metadata knowledge base	**Behavior:** Fills blank values only. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.

vodSeriesId (SKU)_CVP

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** vodSeriesId (SKU)_CVP, vod series id cvp, series cvp sku, series content id, cvp series id **Transform:** CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.
2	Avails input	**Behavior:** Fills blank SKU fields after WhatsOn and before CVP. **Details:** vodSeriesId (SKU)_CVP, Series ContentID, Series CVP_SKU, Series CVP SKU, CVP Series ID, SeriesAltID, Series Alt ID **Transform:** CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.
3	CVP Metadata knowledge base	**Behavior:** Fills blank values only. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.
4	Connector knowledge base	**Behavior:** Overrides connector cross-reference fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.

vodSeasonId (SKU)

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** vodSeasonId (SKU), season newsku, season new sku **Transform:** Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.
2	Avails input	**Behavior:** Fills blank SKU fields after WhatsOn and before CVP. **Details:** Season NewSku, Season New SKU, SeasonAltID, Season Alt ID **Transform:** Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.
3	CVP Metadata knowledge base	**Behavior:** Fills blank values only. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.

vodSeasonId (SKU)_CVP

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** vodSeasonId (SKU)_CVP, vod season id cvp, season cvp sku, season content id, cvp season id **Transform:** CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.
2	Avails input	**Behavior:** Fills blank SKU fields after WhatsOn and before CVP. **Details:** vodSeasonId (SKU)_CVP, Season ContentID, Season CVP_SKU, Season CVP SKU, CVP Season ID, SeasonAltID, Season Alt ID **Transform:** CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.
3	CVP Metadata knowledge base	**Behavior:** Fills blank values only. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.
4	Connector knowledge base	**Behavior:** Overrides connector cross-reference fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.

idTMS

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** idTMS, id tms, tms id, tmsnumber, tms number **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
2	Avails input	**Behavior:** Overrides with tab-specific Avails retailer IDs. Season rows stay blank. **Details:** Movies!RetailerID1, TV!RetailerEpisodeID1, TV!RetailerSeriesID **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	**Behavior:** Fills blank connector-supported fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

idTMS_series

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** idTMS_series, id tms series, series tms id **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
2	Avails input	**Behavior:** Overrides episode and series/show rows from TV-tab series retailer IDs. **Details:** TV!RetailerSeriesID **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

descriptionLong

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** descriptionLong, description long, long description, long description printed press, listing description, description, synopsis **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	**Behavior:** Fills blank connector-supported fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Short Description [110 Characters]. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

descriptionMedium

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** descriptionMedium, description medium, medium description, listing description, description **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Short Description [110 Characters]. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

descriptionShort

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** descriptionShort, description short, listing description, short synopsis **Transform:** CVP shortDescription is preferred only at 150 characters or less. Longer values can populate but warn.
3	CVP Metadata knowledge base	**Behavior:** Preferred over mapped values only when CVP Short Description is 150 characters or less. Longer CVP values fill blanks only and are reported in warnings. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** CVP shortDescription is preferred only at 150 characters or less. Longer values can populate but warn.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Short Description [110 Characters]. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** CVP shortDescription is preferred only at 150 characters or less. Longer values can populate but warn.

descriptionSeason

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** descriptionSeason, description season, season description, short description, additional description 2 **Transform:** Longer than 150 characters warns. Movie rows clear these fields because season/series descriptions do not apply.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Longer than 150 characters warns. Movie rows clear these fields because season/series descriptions do not apply.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Matched parent season Short Description [110 Characters]. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Longer than 150 characters warns. Movie rows clear these fields because season/series descriptions do not apply.

descriptionSeries

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** descriptionSeries, description series, series description, short description **Transform:** Longer than 150 characters warns. Movie rows clear these fields because season/series descriptions do not apply.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Longer than 150 characters warns. Movie rows clear these fields because season/series descriptions do not apply.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Matched parent series Short Description [110 Characters]. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Longer than 150 characters warns. Movie rows clear these fields because season/series descriptions do not apply.

studio

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** studio, recording studio, company display credit, company, production company, production company (single) **Transform:** WhatsOn Production company (single) maps to both studio and productionCompany. Existing studio and production-company aliases remain supported.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** WhatsOn Production company (single) maps to both studio and productionCompany. Existing studio and production-company aliases remain supported.
4	Connector knowledge base	**Behavior:** Fills blank connector-supported fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** WhatsOn Production company (single) maps to both studio and productionCompany. Existing studio and production-company aliases remain supported.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Provider. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** WhatsOn Production company (single) maps to both studio and productionCompany. Existing studio and production-company aliases remain supported.

productionCompany

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** productionCompany, production company, productioncompany, production company (single) **Transform:** WhatsOn Production company (single) maps to both studio and productionCompany. Existing studio and production-company aliases remain supported.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** WhatsOn Production company (single) maps to both studio and productionCompany. Existing studio and production-company aliases remain supported.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Provider. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** WhatsOn Production company (single) maps to both studio and productionCompany. Existing studio and production-company aliases remain supported.

countryOrigin

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** countryOrigin, country origin, country of origin, origin country, production regions **Transform:** Normalizes recognized country names and aliases to MovieLabs ISO 3166 alpha-2 codes. Nonblank values that cannot be normalized to two letters remain warning-eligible.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Normalizes recognized country names and aliases to MovieLabs ISO 3166 alpha-2 codes. Nonblank values that cannot be normalized to two letters remain warning-eligible.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Country of Origin. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Normalizes recognized country names and aliases to MovieLabs ISO 3166 alpha-2 codes. Nonblank values that cannot be normalized to two letters remain warning-eligible.

actorName1

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** actorName1, actor name 1, actor 1, cast 1, principal cast 1 **Transform:** From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
1	WhatsOn Cast (sorted)	**Behavior:** Uses comma-separated Cast (sorted) value 1; only the first four cast names are used. **Details:** Cast (sorted), Cast sorted, cast, cast names, actors, principal cast, principalcast, actor names, actornames **Transform:** From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Narrator, Actors. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.

actorOrder1

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** actorOrder1 **Transform:** Fills the matching numeric order only when the corresponding actorName field is populated.
1	WhatsOn Cast (sorted)	**Behavior:** Fills 1 when actorName1 is populated from the comma-separated Cast (sorted) value. **Details:** Cast (sorted), Cast sorted, cast, cast names, actors, principal cast, principalcast, actor names, actornames **Transform:** Fills the matching numeric order only when the corresponding actorName field is populated.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Fills the matching numeric order only when the corresponding actorName field is populated.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Narrator, Actors. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Fills the matching numeric order only when the corresponding actorName field is populated.

actorName2

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** actorName2, actor name 2, actor 2, cast 2, principal cast 2 **Transform:** From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
1	WhatsOn Cast (sorted)	**Behavior:** Uses comma-separated Cast (sorted) value 2; only the first four cast names are used. **Details:** Cast (sorted), Cast sorted, cast, cast names, actors, principal cast, principalcast, actor names, actornames **Transform:** From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Actors. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.

actorOrder2

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** actorOrder2 **Transform:** Fills the matching numeric order only when the corresponding actorName field is populated.
1	WhatsOn Cast (sorted)	**Behavior:** Fills 2 when actorName2 is populated from the comma-separated Cast (sorted) value. **Details:** Cast (sorted), Cast sorted, cast, cast names, actors, principal cast, principalcast, actor names, actornames **Transform:** Fills the matching numeric order only when the corresponding actorName field is populated.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Fills the matching numeric order only when the corresponding actorName field is populated.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Actors. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Fills the matching numeric order only when the corresponding actorName field is populated.

actorName3

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** actorName3, actor name 3, actor 3, cast 3, principal cast 3 **Transform:** From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
1	WhatsOn Cast (sorted)	**Behavior:** Uses comma-separated Cast (sorted) value 3; only the first four cast names are used. **Details:** Cast (sorted), Cast sorted, cast, cast names, actors, principal cast, principalcast, actor names, actornames **Transform:** From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Actors. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.

actorOrder3

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** actorOrder3 **Transform:** Fills the matching numeric order only when the corresponding actorName field is populated.
1	WhatsOn Cast (sorted)	**Behavior:** Fills 3 when actorName3 is populated from the comma-separated Cast (sorted) value. **Details:** Cast (sorted), Cast sorted, cast, cast names, actors, principal cast, principalcast, actor names, actornames **Transform:** Fills the matching numeric order only when the corresponding actorName field is populated.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Fills the matching numeric order only when the corresponding actorName field is populated.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Actors. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Fills the matching numeric order only when the corresponding actorName field is populated.

actorName4

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** actorName4, actor name 4, actor 4, cast 4, principal cast 4 **Transform:** From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
1	WhatsOn Cast (sorted)	**Behavior:** Uses comma-separated Cast (sorted) value 4; only the first four cast names are used. **Details:** Cast (sorted), Cast sorted, cast, cast names, actors, principal cast, principalcast, actor names, actornames **Transform:** From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Actors. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.

actorOrder4

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** actorOrder4 **Transform:** Fills the matching numeric order only when the corresponding actorName field is populated.
1	WhatsOn Cast (sorted)	**Behavior:** Fills 4 when actorName4 is populated from the comma-separated Cast (sorted) value. **Details:** Cast (sorted), Cast sorted, cast, cast names, actors, principal cast, principalcast, actor names, actornames **Transform:** Fills the matching numeric order only when the corresponding actorName field is populated.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Fills the matching numeric order only when the corresponding actorName field is populated.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Actors. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Fills the matching numeric order only when the corresponding actorName field is populated.

director1

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** director1, director 1, director, directors **Transform:** Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
4	Connector knowledge base	**Behavior:** Fills blank connector-supported fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Directors. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.

director2

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** director2, director 2 **Transform:** Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Directors. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.

producer1

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** producer1, producer 1, producer, producers **Transform:** Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Producer, Producers. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.

producer2

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** producer2, producer 2 **Transform:** Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Producer, Producers. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.

writer1

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** writer1, writer 1, writer **Transform:** Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Writers. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.

writer2

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** writer2, writer 2 **Transform:** Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Writers. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.

genreMain

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** genreMain, genre main, main genre, genre, category, on-demand content categories **Transform:** Uses WhatsOn Category first and On-demand content categories as its fallback. Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1. On the final pass, a genreMain value of Animation is overwritten with For Kids.
1	WhatsOn category fields	**Behavior:** Uses Category first; On-demand content categories is the fallback when Category is blank or absent. **Details:** Category, On-demand content categories **Transform:** Uses WhatsOn Category first and On-demand content categories as its fallback. Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1. On the final pass, a genreMain value of Animation is overwritten with For Kids.
3	CVP Metadata knowledge base	**Behavior:** Fills blank values only. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Uses WhatsOn Category first and On-demand content categories as its fallback. Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1. On the final pass, a genreMain value of Animation is overwritten with For Kids.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Genre. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Uses WhatsOn Category first and On-demand content categories as its fallback. Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1. On the final pass, a genreMain value of Animation is overwritten with For Kids.
7	Final pass normalization	**Behavior:** After all source and enrichment passes, Animation is overwritten with For Kids. **Details:** Animation -> For Kids **Transform:** Uses WhatsOn Category first and On-demand content categories as its fallback. Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1. On the final pass, a genreMain value of Animation is overwritten with For Kids.

genreSub1

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** genreSub1, genre sub 1, subgenre 1, genre 2 **Transform:** Uses WhatsOn Category first and On-demand content categories as its fallback. Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1.
1	WhatsOn category fields	**Behavior:** Uses Category first; On-demand content categories is the fallback when Category is blank or absent. **Details:** Category, On-demand content categories **Transform:** Uses WhatsOn Category first and On-demand content categories as its fallback. Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1.
3	CVP Metadata knowledge base	**Behavior:** Fills blank values only. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Uses WhatsOn Category first and On-demand content categories as its fallback. Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Genre. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Uses WhatsOn Category first and On-demand content categories as its fallback. Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1.

genreSub2

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** genreSub2, genre sub 2, subgenre 2, genre 3 **Transform:** Uses WhatsOn Category first and On-demand content categories as its fallback. Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1.
1	WhatsOn category fields	**Behavior:** Uses Category first; On-demand content categories is the fallback when Category is blank or absent. **Details:** Category, On-demand content categories **Transform:** Uses WhatsOn Category first and On-demand content categories as its fallback. Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1.
3	CVP Metadata knowledge base	**Behavior:** Fills blank values only. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Uses WhatsOn Category first and On-demand content categories as its fallback. Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Genre. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Uses WhatsOn Category first and On-demand content categories as its fallback. Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1.

productionYear

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** productionYear, production year, release year, releaseyear **Transform:** Preserves the mapped source year; used only as a final fallback for blank premiereYear and premiereDate.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Preserves the mapped source year; used only as a final fallback for blank premiereYear and premiereDate.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Global Premiere Date year. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Preserves the mapped source year; used only as a final fallback for blank premiereYear and premiereDate.

premiereDate

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** premiereDate, premiere date, date 1, date1, pubdate, pub date, release history original, original release date **Transform:** Final output is always YYYY-MM-DD. Parses YYYY-MM-DD, MM/DD/YYYY, MM/DD/YY, YYYY/MM/DD, and ISO date-time prefixes. A four-digit year becomes YYYY-01-01. Unparseable nonblank values are blanked so they can be corrected from warnings. If still blank, the final fallback can derive YYYY-01-01 from premiereYear or productionYear.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Final output is always YYYY-MM-DD. Parses YYYY-MM-DD, MM/DD/YYYY, MM/DD/YY, YYYY/MM/DD, and ISO date-time prefixes. A four-digit year becomes YYYY-01-01. Unparseable nonblank values are blanked so they can be corrected from warnings. If still blank, the final fallback can derive YYYY-01-01 from premiereYear or productionYear.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Global Premiere Date. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Final output is always YYYY-MM-DD. Parses YYYY-MM-DD, MM/DD/YYYY, MM/DD/YY, YYYY/MM/DD, and ISO date-time prefixes. A four-digit year becomes YYYY-01-01. Unparseable nonblank values are blanked so they can be corrected from warnings. If still blank, the final fallback can derive YYYY-01-01 from premiereYear or productionYear.

premiereYear

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** premiereYear, premiere year **Transform:** Uses the mapped source value when present. If blank, derives the year from premiereDate; if premiereDate is blank too, productionYear can be copied as the final fallback.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Uses the mapped source value when present. If blank, derives the year from premiereDate; if premiereDate is blank too, productionYear can be copied as the final fallback.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Global Premiere Date year. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Uses the mapped source value when present. If blank, derives the year from premiereDate; if premiereDate is blank too, productionYear can be copied as the final fallback.

Series_Release_Date

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** Series_Release_Date, series release date, series_release_date **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

ratingCSA

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** ratingCSA, rating csa, csa rating **Transform:** Normalizes rating text by removing scheme labels/placeholders and lowercasing the rating value.
3	CVP Metadata knowledge base	**Behavior:** Fills blank values only. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Normalizes rating text by removing scheme labels/placeholders and lowercasing the rating value.

ratingCSAAdvisory

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** ratingCSAAdvisory, rating csa advisory, csa advisory **Transform:** CVP parental warning is copied only to the advisory field that corresponds to the rating scheme found.
3	CVP Metadata knowledge base	**Behavior:** Fills blank values only. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** CVP parental warning is copied only to the advisory field that corresponds to the rating scheme found.

ratingMPA

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** ratingMPA, rating mpa, rating mpaa, mpa rating, mpaa rating **Transform:** Normalizes rating text by removing scheme labels/placeholders and lowercasing the rating value.
3	CVP Metadata knowledge base	**Behavior:** Fills blank values only. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Normalizes rating text by removing scheme labels/placeholders and lowercasing the rating value.

ratingMPAAdvisory

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** ratingMPAAdvisory, rating mpa advisory, rating mpaa advisory, mpa advisory **Transform:** CVP parental warning is copied only to the advisory field that corresponds to the rating scheme found.
3	CVP Metadata knowledge base	**Behavior:** Fills blank values only. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** CVP parental warning is copied only to the advisory field that corresponds to the rating scheme found.

ratingTV

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** ratingTV, rating tv, tv rating, parental rating, parental rating and regulator, parental rating and regulator default regulator, parental rating and regulator (default regulator) **Transform:** Normalizes TV ratings to tv-g, tv-pg, tv-14, tv-ma, etc. A bare [FCC] placeholder is treated as blank. WhatsOn Parental rating and regulator (default regulator) is recognized as a ratingTV source. CVP fills ratingTV only when blank. If ratingCSA, ratingMPA, and ratingTV are all blank on the final pass, ratingTV defaults to tv-pg.
3	CVP Metadata knowledge base	**Behavior:** Fills blank values only. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Normalizes TV ratings to tv-g, tv-pg, tv-14, tv-ma, etc. A bare [FCC] placeholder is treated as blank. WhatsOn Parental rating and regulator (default regulator) is recognized as a ratingTV source. CVP fills ratingTV only when blank. If ratingCSA, ratingMPA, and ratingTV are all blank on the final pass, ratingTV defaults to tv-pg.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Rating. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Normalizes TV ratings to tv-g, tv-pg, tv-14, tv-ma, etc. A bare [FCC] placeholder is treated as blank. WhatsOn Parental rating and regulator (default regulator) is recognized as a ratingTV source. CVP fills ratingTV only when blank. If ratingCSA, ratingMPA, and ratingTV are all blank on the final pass, ratingTV defaults to tv-pg.
7	Final pass default	**Behavior:** If ratingCSA, ratingMPA, and ratingTV are all blank after enrichment, ratingTV is set to tv-pg. **Details:** ratingCSA blank + ratingMPA blank + ratingTV blank -> ratingTV tv-pg **Transform:** Normalizes TV ratings to tv-g, tv-pg, tv-14, tv-ma, etc. A bare [FCC] placeholder is treated as blank. WhatsOn Parental rating and regulator (default regulator) is recognized as a ratingTV source. CVP fills ratingTV only when blank. If ratingCSA, ratingMPA, and ratingTV are all blank on the final pass, ratingTV defaults to tv-pg.

ratingTVAdvisory

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** ratingTVAdvisory, rating tv advisory, tv advisory, rating reason **Transform:** CVP parental warning is copied only to the advisory field that corresponds to the rating scheme found.
3	CVP Metadata knowledge base	**Behavior:** Fills blank values only. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** CVP parental warning is copied only to the advisory field that corresponds to the rating scheme found.

language

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** language, language 1, asset language, assetlanguage **Transform:** Normalizes known language values to app syntax; if blank on the final pass, defaults to en-US.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Normalizes known language values to app syntax; if blank on the final pass, defaults to en-US.
5	Final pass default	**Behavior:** Fills blank final values after source mapping and enrichment. Existing values are preserved. **Details:** en-US **Transform:** Normalizes known language values to app syntax; if blank on the final pass, defaults to en-US.

languageSubtitle

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** languageSubtitle, language subtitle, language 1, subtitle language, subtitling language, caption language **Transform:** Normalizes known language values to app syntax; if blank on the final pass, defaults to en-US.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Normalizes known language values to app syntax; if blank on the final pass, defaults to en-US.
5	Final pass default	**Behavior:** Fills blank final values after source mapping and enrichment. Existing values are preserved. **Details:** en-US **Transform:** Normalizes known language values to app syntax; if blank on the final pass, defaults to en-US.

rightsAllowDownload

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** rightsAllowDownload, rights allow download, download **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	**Behavior:** Fills blank connector-supported fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
5	Default value	**Behavior:** Applied when no source filled the field. **Details:** **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

rightsLicenseRightsDescription

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** rightsLicenseRightsDescription, rights license rights description, license rights description, rights description, all streaming rights **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	**Behavior:** Fills blank connector-supported fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
5	Default value	**Behavior:** Applied when no source filled the field. **Details:** SWP **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

rightsLicenseType

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** rightsLicenseType, rights license type, license type, licensetype **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	**Behavior:** Fills blank connector-supported fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
5	Default value	**Behavior:** Applied when no source filled the field. **Details:** SVOD **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

rightsPricingTier

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** rightsPricingTier, rights pricing tier, price type, pricing tier **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
5	Default value	**Behavior:** Applied when no source filled the field. **Details:** Category **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

rightsTerritory

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** rightsTerritory, rights territory, territory **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	**Behavior:** Fills blank connector-supported fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
5	Default value	**Behavior:** Applied when no source filled the field. **Details:** US **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

idParentRef

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** idParentRef, id parent ref, parent ref, parent id **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

mediaExpectedFormat

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** mediaExpectedFormat, media expected format, format profile **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	**Behavior:** Fills blank connector-supported fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

mediaHouseNumber

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** mediaHouseNumber, media house number, house number **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
4	Connector knowledge base	**Behavior:** Overrides connector cross-reference fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

Marker_programStart:start

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** Marker_programStart:start **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

Marker_programSegment:start

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** Marker_programSegment:start **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

Marker_openingCredits:start

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** Marker_openingCredits:start **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

Marker_closingCredits:start

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** Marker_closingCredits:start **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

idMedia (MediaGenix)

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** idMedia (MediaGenix), id media, media id, mediagenix media id, mpx media id, cvp media id, cvpmediaid **Transform:** Normalizes MPX/CVP URLs and numeric-looking values to the trailing numeric Media ID or Program ID.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Normalizes MPX/CVP URLs and numeric-looking values to the trailing numeric Media ID or Program ID.
4	Connector knowledge base	**Behavior:** Overrides connector cross-reference fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** Normalizes MPX/CVP URLs and numeric-looking values to the trailing numeric Media ID or Program ID.

idProduct (MediaGenix)

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** idProduct (MediaGenix), id product, program id, mediagenix product id, mpx program id, cvp program id, cvpprogramid **Transform:** Normalizes MPX/CVP URLs and numeric-looking values to the trailing numeric Media ID or Program ID.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Normalizes MPX/CVP URLs and numeric-looking values to the trailing numeric Media ID or Program ID.
4	Connector knowledge base	**Behavior:** Overrides connector cross-reference fields on identifier match. **Details:** External reference, NewSku, ParentSeriesMediaID, valid CVP SKU, GUID, TMS **Transform:** Normalizes MPX/CVP URLs and numeric-looking values to the trailing numeric Media ID or Program ID.

titleKeywords

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** titleKeywords, title keywords, keywords, key words, category, on-demand content categories **Transform:** Splits comma- or semicolon-separated inputs, trims each value, and outputs keywords separated by '; '.
1	WhatsOn category fields	**Behavior:** Uses Category first; On-demand content categories is the fallback when Category is blank or absent. **Details:** Category, On-demand content categories **Transform:** Splits comma- or semicolon-separated inputs, trims each value, and outputs keywords separated by '; '.
3	CVP Metadata knowledge base	**Behavior:** Fills blank values only. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** Splits comma- or semicolon-separated inputs, trims each value, and outputs keywords separated by '; '.
5	Metadata Smart Sheet	**Behavior:** Optional final metadata override for selected fields only. **Details:** Key Words. Matches by External ID -> assetNameSDVI or New SKU -> idSku. After a TVSHOW/PODCAST series row is matched, child seasons and episodes can match by parent SKU, Season, and Episode. **Transform:** Splits comma- or semicolon-separated inputs, trims each value, and outputs keywords separated by '; '.

titleSchedule

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** titleSchedule, title schedule, schedule title **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

vodMediaId (SKU)

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** vodMediaId (SKU), vod media id, media sku **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.

vodProgramId (SKU)

Priority	Source	Behavior / Details / Transform
1	WhatsOn and row-producing sources	**Behavior:** Exact source headers and configured aliases are read first. **Details:** vodProgramId (SKU), vod program id, program sku **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.
3	CVP Metadata knowledge base	**Behavior:** Overrides mapped source values on match. **Details:** Title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID match **Transform:** No field-specific syntax transform beyond blank/null handling and source priority rules.