

Rally Connect Input CSV Maker Mapping Guide V1.47

Readable PDF guide. Description and mapping last updated August 3, 2026 - V1.47.

This guide explains the mapping flow and the transformations used to convert input values into the required Rally Connect output syntax. The field-by-field mapping spreadsheet remains the exhaustive table for exact source headers, aliases, and priority rows.

How The App Builds Output Rows

- WhatsOn is the main input and creates the output rows.
- Connector metadata is matched strictly by identifiers such as external reference, NewSku, parent IDs, valid CVP SKU, GUID, and TMS values.
- Avails is optional and is the only source for assetVodStartDate and assetVodEndDate.
- CVP Metadata can enrich matched rows with descriptions, people, genres, ratings, keywords, IDs, production year, and premiere date.
- Metadata Smart Sheet is optional and overrides only its approved fields after other enrichment.
- Final passes normalize syntax, derive parent rows and fallback dates, apply selected endpoints, apply language defaults, and create warnings.

Source Priority Summary

Priority	Source	What It Does
1	WhatsOn and row-producing sources	Creates rows and fills direct field aliases first.
2	Avails input	Fills VOD windows and supported ID/SKU fields after strict matching.
3	CVP Metadata knowledge base	Enriches matched rows unless the output field is protected by app rules.
4	Connector knowledge base	Fills or overrides connector-supported cross-reference fields on strict identifier match.
5	Metadata Smart Sheet or defaults	Smart Sheet overrides approved fields; defaults fill selected blank fields.
6	Home screen publish selection	Selected endpoints receive the selected publish type; unselected endpoints stay blank.

Important Rules

- premiereDate is always written as YYYY-MM-DD. Unparseable date text is blanked so the warning report can catch it.

- `assetVodStartDate` and `assetVodEndDate` come from Avails only, never from WhatsOn, Connector, or CVP Metadata.
- WhatsOn External reference maps directly to `assetNameSDVI` with no exceptions.
- If a record cannot be matched strictly in Connector, Avails, or CVP, enrichment fields stay blank instead of borrowing values from a different title or episode.
- Endpoint fields stay blank unless the user selects endpoints on the home screen.
- The warning report is the review surface for required blanks, invalid country codes, missing rating groups, SKU conflicts, and selected long descriptions.

Transformation And Formula Reference

These are the non-generic transformations in the app. Fields not listed here use blank/null handling and the source priority rules without extra syntax manipulation.

Fields: `premiereDate`

Final output is always YYYY-MM-DD. Parses YYYY-MM-DD, MM/DD/YYYY, MM/DD/YY, YYYY/MM/DD, and ISO date-time prefixes. A four-digit year becomes YYYY-01-01. Unparseable nonblank values are blanked so they can be corrected from warnings. If still blank, the final fallback can derive YYYY-01-01 from `premiereYear` or `productionYear`.

Fields: `premiereYear`

Uses the mapped source value when present. If blank, derives the year from `premiereDate`; if `premiereDate` is blank too, `productionYear` can be copied as the final fallback.

Fields: `productionYear`

Preserves the mapped source year; used only as a final fallback for blank `premiereYear` and `premiereDate`.

Fields: `assetVodStartDate`, `assetVodEndDate`

Uses Avails only. Common date formats are normalized to YYYY-MM-DD when recognized.

Fields: `assetNameSDVI`

WhatsOn External reference maps directly with no exceptions. If no direct value exists, a fallback asset code may be generated from title/series text plus S##E## and truncated to 64 characters.

Fields: `contentType`

Normalizes film/feature/program to movie, episode variants to episode, parent series to series, and WhatsOn Series rows with season data to season.

Fields: `titleVod`

Uses direct title mapping for movies, episodes, and parent series rows. Season rows can be formed from the parent series title plus ' Season ' plus the season number when creating season placeholders.

Fields: titleEpisode

For episode rows, copies titleVod into titleEpisode when titleEpisode is blank.

Fields: titleSeries

Uses the parent series title. Parent series rows also keep titleVod populated with the same series title.

Fields: titleKeywords

Splits comma- or semicolon-separated inputs, trims each value, and outputs keywords separated by '; '.

Fields: genreMain, genreSub1, genreSub2

Splits category/genre values on commas or semicolons and fills main/sub genres in order. If genreMain is blank after enrichment and genreSub1 exists, genreMain is copied from genreSub1.

Fields: countryOrigin

Normalizes recognized country names and aliases to MovieLabs ISO 3166 alpha-2 codes. Nonblank values that cannot be normalized to two letters remain warning-eligible.

Fields: language, languageSubtitle

Normalizes known language values to app syntax; if blank on the final pass, defaults to en-US.

Fields: ratingTV

Normalizes TV ratings to tv-g, tv-pg, tv-14, tv-ma, etc. A bare [FCC] placeholder is treated as blank.

Fields: ratingCSA, ratingMPA

Normalizes rating text by removing scheme labels/placeholders and lowercasing the rating value.

Fields: ratingCSAAdvisory, ratingMPAAdvisory, ratingTVAdvisory

CVP parental warning is copied only to the advisory field that corresponds to the rating scheme found.

Fields: actorName1, actorName2, actorName3, actorName4

From WhatsOn Cast (sorted), splits comma-separated cast and uses only the first four names. CVP/Smart Sheet people lists are also split into ordered name fields when available.

Fields: actorOrder1, actorOrder2, actorOrder3, actorOrder4

Fills the matching numeric order only when the corresponding actorName field is populated.

Fields: director1, director2, producer1, producer2, writer1, writer2

Splits comma- or semicolon-separated people lists and keeps the first two ordered values for that role.

Fields: idMedia (MediaGenix), idProduct (MediaGenix)

Normalizes MPX/CVP URLs and numeric-looking values to the trailing numeric Media ID or Program ID.

Fields: idSku_CVP, vodSeriesId (SKU)_CVP, vodSeasonId (SKU)_CVP

CVP SKU fields only accept CVP-shaped values such as M_..., S_..., S1_..., or S1_E...; TMS IDs, Retailer IDs, and non-CVP aliases are ignored.

Fields: idSku, vodSeriesId (SKU), vodSeasonId (SKU)

Non-CVP SKU fields preserve WhatsOn VOD ID SKU first and can fill from NewSku, ParentSeriesMediaID, UUIDs, or numeric SKU values. Parent season/series IDs are copied from related rows.

Fields: rightsDRMrequired

Connector DRM text maps DRM Concurrency to True and NDRM Concurrency to False. Metadata Smart Sheet DRM Protected maps Yes to True; No or blank stays blank.

Fields: endpoint_Amazon, endpoint_Roku, endpoint_Frndly, endpoint_YouTube, endpoint_Truth

Selected endpoints get the publish type selected on the home screen. Unselected endpoints stay blank.

Fields: descriptionShort

CVP shortDescription is preferred only at 150 characters or less. Longer values can populate but warn.

Fields: descriptionSeason, descriptionSeries

Longer than 150 characters warns. Movie rows clear these fields because season/series descriptions do not apply.

Fields: seasonNumber

Converts numeric-looking values to an integer; season placeholder rows use the related season number.

Fields: episodeAirOrder

Converts numeric-looking values to a normalized episode order; blank episode values warn.

Warning Rules

- Missing SourceMedia no longer creates a warning.
- Rows warn when both idSku and idSku_CVP are blank after enrichment.
- Rows warn when ratingCSA, ratingMPA, and ratingTV are all blank. Individual blank rating fields do not warn if one rating exists.

- Rows warn when descriptionShort, studio, productionCompany, countryOrigin, productionYear, premiereDate, or premiereYear remain blank.
- Episode rows additionally warn when descriptionSeason, descriptionSeries, or episodeAirOrder remain blank.
- descriptionShort, descriptionSeason, and descriptionSeries warn when populated values exceed 150 characters, including spaces.
- Country of Origin warns when a nonblank value cannot be normalized to a MovieLabs ISO 3166 alpha-2 country code.

Where To Find The Full Table

Use the mapping spreadsheet for the full 228-row reference with every output field, source priority, exact matched WhatsOn headers, aliases, behavior, details, and transform/formula text.