

Rally Connect Input CSV Maker Mapping Guide V1.48

Readable mapping summary. Last updated August 4, 2026.

This PDF is the human-readable guide. The downloadable XLSX mapping reference remains the exhaustive field-by-field table with all output columns, priorities, aliases, and formulas.

The app builds output rows in this order: WhatsOn and row-producing sources, strict Connector match, Avails, CVP Metadata, optional Metadata Smart Sheet, parent-row normalization, final output normalizations, warnings, then workbook/CSV export.

Stage	Main Purpose	Important Rule
WhatsOn source	Creates the output rows and maps direct fields.	External reference maps directly to assetNameSDVI.
Connector KB	Matches strict cross-reference records.	Fills SourceMedia and trusted SKU/media IDs only on safe matches.
Avails	Supplies VOD dates and selected retailer/SKU data.	assetVodStartDate and assetVodEndDate come from Avails only.
CVP Metadata	Enriches matched rows with metadata.	Does not override protected fields such as title fields or existing genreMain.
Metadata Smart Sheet	Optional override for approved metadata fields.	Can override selected fields after other enrichment.
Final pass	Normalizes final syntax and fills safe defaults.	Animation in genreMain becomes For Kids; blank languages become en-US.

Core Source Priorities

WhatsOn and row-producing sources

- WhatsOn is the first and main input. It creates the row set used by the output workbook and CSV.
- Exact matching headers and configured aliases are read before later enrichment sources.
- External reference maps directly to assetNameSDVI with no exception when available.
- Category fills titleKeywords and genre fields; keywords are output with semicolon separators.
- Date1 or Date 1 maps to premiereDate and is normalized to YYYY-MM-DD.
- Cast (sorted) splits comma-separated cast into actorName1 through actorName4 and actorOrder1 through actorOrder4.

Connector knowledge base

- Connector matching is strict. If no safe connector match exists, connector-backed fields stay blank instead of borrowing another row.
- Connector is the only source for SourceMedia and can supply NewSku, CVP SKU, GUID, MediaGenix IDs, DRM, and path values.
- Connector never supplies Avails dates, premiereDate, or Series_Release_Date.

Avails input

- Avails is optional and does not create output rows.
- assetVodStartDate and assetVodEndDate are cleared before Avails and are filled from Avails only.
- Avails can fill blank parent SKU fields when the values pass the CVP/non-CVP SKU format checks.
- If WhatsOn-derived parent SKUs conflict with Avails parent SKUs, the WhatsOn value is preserved and a warning is written.

Metadata Enrichment

CVP Metadata knowledge base

- CVP can match by title, GUID, SKU, MPX/CVP Media ID, or MPX/CVP Program ID.
- CVP can enrich cast, writers, directors, producers, ratings, genre tags, keywords, production year, pubDate, and descriptions.
- Protected fields are not overridden by CVP, including assetNameSDVI, VOD dates, SourceMedia, contentType, title fields, genreMain, and endpoint fields.
- CVP shortDescription is preferred for descriptionShort only when it is 150 characters or less. Longer values can populate blanks and warn.

Metadata Smart Sheet

- The Smart Sheet is optional and runs after Connector, Avails, and CVP.
- It matches by External ID to assetNameSDVI or New SKU to idSku.
- When a TVSHOW/PODCAST series row matches, child seasons and episodes can match under that parent by Season and Episode.
- It can override only the approved metadata fields: people, country, genre, premiere date, keywords, SKU, provider, rating, DRM, and short description fields.

Final Output Normalizations

- premiereDate is always output as YYYY-MM-DD. Unparseable nonblank text is blanked and warning-eligible.
- If premiereYear is blank, it can be derived from premiereDate. If premiereDate and premiereYear are blank, productionYear can derive both as YYYY and YYYY-01-01.
- If language or languageSubtitle is blank on the final pass, it defaults to en-US.
- If genreMain is blank and genreSub1 exists, genreMain can be copied from genreSub1.
- If the completed output value for genreMain is Animation, it is overwritten with For Kids.
- ratingTV values normalize to tv-g, tv-pg, tv-14, tv-ma, and related TV rating syntax. A bare placeholder such as [FCC] is treated as blank.
- Country of Origin normalizes recognized names and aliases to MovieLabs ISO 3166 alpha-2 codes.

Parent Rows and SKU Handling

- Episode uploads must include or generate separate season and series parent rows.
- Parent series rows output titleVod and titleSeries directly from the WhatsOn Title value.
- Season rows output titleVod as Parent Series plus Season plus season number, and titleSeries from Parent Series.
- Series rows never output vodSeasonId (SKU) or vodSeasonId (SKU)_CVP.
- Season rows can copy their idSku and idSku_CVP into vodSeasonId (SKU) and vodSeasonId (SKU)_CVP.
- Series rows can copy their idSku and idSku_CVP into vodSeriesId (SKU) and vodSeriesId (SKU)_CVP.
- WhatsOn VOD ID SKU maps to idSku. WhatsOn VOD ID SKU CVP maps to idSku_CVP.
- CVP SKU fields must use CVP-shaped values like M_..., S_..., S1_..., or S1_E.... Non-CVP SKU fields use UUID or numeric SKU/media ID style values.
- SKU fields are never populated from TMS IDs, Retailer IDs, idTMS, or idTMS_series.

Warnings

- Missing SourceMedia is not a warning.
- Missing director1 is a warning.
- Missing studio or productionCompany is a warning.
- Rows warn when both idSku and idSku_CVP are blank.
- Rows warn only when ratingCSA, ratingMPA, and ratingTV are all blank.
- descriptionShort, descriptionSeason, and descriptionSeries warn when populated values exceed 150 characters including spaces.
- Rows warn when countryOrigin, productionYear, premiereDate, or premiereYear are blank after final derivations.
- Episode rows additionally warn when descriptionSeason, descriptionSeries, or episodeAirOrder are blank.

Key Field Transform Examples

Output Field	Input/Condition	Final Output
assetNameSDVI	WhatsOn External reference = BrdrtwnS01E13	BrdrtwnS01E13
premiereDate	Date 1 = 9/5/2026	2026-09-05
premiereDate	productionYear = 2024 and premiere fields blank	2024-01-01
titleKeywords	Drama, Family, Ranch	Drama; Family; Ranch
genreMain	Animation after all sources finish	For Kids
countryOrigin	United States	US
ratingTV	PG	tv-pg
language	blank final value	en-US

For the exhaustive table, use the downloadable XLSX mapping reference. It contains every output field, source priority, source details, aliases, and transform/formula text generated from the same mapping catalog shown in the local app.