

Module Interface Specification for Natural Language Processing for Mental Health Risk Prediction

Team 13, The Cognitive Care Crew

Jessica Dawson

Michael Breau

Matthew Curtis

Benjamin Chinnery

Yaruo Tian

April 4, 2024

1 Revision History

Date	Version	Notes
January 17, 2024	1.0	Revision 0

2 Symbols, Abbreviations and Acronyms

See SRS Documentation at <https://github.com/MichaelBreau/nlp-mentalhealth/blob/main/docs/SRS/index.pdf>

Contents

1	Revision History	i
2	Symbols, Abbreviations and Acronyms	ii
3	Introduction	1
4	Notation	1
5	Module Decomposition	1
6	MIS for Search for Symptoms of Depression Module	3
6.1	depression_main	3
6.2	Uses	3
6.3	Syntax	3
6.3.1	Exported Constants	3
6.3.2	Exported Access Programs	3
6.4	Semantics	3
6.4.1	State Variables	3
6.4.2	Environment Variables	3
6.4.3	Assumptions	3
6.4.4	Access Routine Semantics	3
6.4.5	Local Functions	3
6.5	depression_process_data	4
6.6	Uses	4
6.7	Syntax	4
6.7.1	Exported Constants	4
6.7.2	Exported Access Programs	4
6.8	Semantics	4
6.8.1	State Variables	4
6.8.2	Environment Variables	4
6.8.3	Assumptions	4
6.8.4	Access Routine Semantics	4
6.8.5	Local Functions	5
6.9	depression_feature_extraction	5
6.10	Uses	5
6.11	Syntax	5
6.11.1	Exported Constants	5
6.11.2	Exported Access Programs	6
6.12	Semantics	6
6.12.1	State Variables	6
6.12.2	Environment Variables	6
6.12.3	Assumptions	6

6.12.4	Access Routine Semantics	6
6.12.5	Local Functions	7
6.13	depression_output	7
6.14	Uses	7
6.15	Syntax	8
6.15.1	Exported Constants	8
6.15.2	Exported Access Programs	8
6.16	Semantics	8
6.16.1	State Variables	8
6.16.2	Environment Variables	8
6.16.3	Assumptions	8
6.16.4	Access Routine Semantics	8
6.16.5	Local Functions	9
6.17	depression_accuracy_evaluation	9
6.18	Uses	9
6.19	Syntax	9
6.19.1	Exported Constants	9
6.19.2	Exported Access Programs	9
6.20	Semantics	9
6.20.1	State Variables	9
6.20.2	Environment Variables	10
6.20.3	Assumptions	10
6.20.4	Access Routine Semantics	10
6.20.5	Local Functions	10
7	MIS for Early Detection of Signs of Anorexia Module	11
7.1	anorexia_main	11
7.2	Uses	11
7.3	Syntax	11
7.3.1	Exported Constants	11
7.3.2	Exported Access Programs	11
7.4	Semantics	11
7.4.1	State Variables	11
7.4.2	Environment Variables	11
7.4.3	Assumptions	11
7.4.4	Access Routine Semantics	11
7.4.5	Local Functions	11
7.5	anorexia_parser	11
7.6	Uses	12
7.7	Syntax	12
7.7.1	Exported Constants	12
7.7.2	Exported Access Programs	12
7.8	Semantics	12

7.8.1	State Variables	12
7.8.2	Environment Variables	12
7.8.3	Assumptions	12
7.8.4	Access Routine Semantics	12
7.8.5	Local Functions	13
7.9	anorexia_training	13
7.10	Uses	13
7.11	Syntax	13
7.11.1	Exported Constants	13
7.11.2	Exported Access Programs	13
7.12	Semantics	13
7.12.1	State Variables	13
7.12.2	Environment Variables	13
7.12.3	Assumptions	14
7.12.4	Access Routine Semantics	14
7.12.5	Local Functions	14
7.13	anorexia_predictor	14
7.14	Uses	15
7.15	Syntax	15
7.15.1	Exported Constants	15
7.15.2	Exported Access Programs	15
7.16	Semantics	15
7.16.1	State Variables	15
7.16.2	Environment Variables	15
7.16.3	Assumptions	15
7.16.4	Access Routine Semantics	15
7.16.5	Local Functions	15
8	MIS for Measuring the Severity of the Signs of Eating Disorders	16
8.1	Module ed_input	16
8.2	Uses	16
8.3	Syntax	16
8.3.1	Exported Constants	16
8.3.2	Exported Access Programs	16
8.4	Semantics	16
8.4.1	State Variables	16
8.4.2	Environment Variables	16
8.4.3	Assumptions	16
8.4.4	Access Routine Semantics	16
8.4.5	Local Functions	16
8.5	Module ed_output	17
8.6	Uses	17
8.7	Syntax	17

8.7.1	Exported Constants	17
8.7.2	Exported Access Programs	17
8.8	Semantics	17
8.8.1	State Variables	17
8.8.2	Environment Variables	17
8.8.3	Assumptions	17
8.8.4	Access Routine Semantics	17
8.8.5	Local Functions	17
8.9	Module ed_pipeline	18
8.10	Uses	18
8.11	Syntax	18
8.11.1	Exported Constants	18
8.11.2	Exported Access Programs	18
8.12	Semantics	18
8.12.1	State Variables	18
8.12.2	Environment Variables	18
8.12.3	Assumptions	18
8.12.4	Access Routine Semantics	18
8.12.5	Local Functions	18
8.13	Module ed_tokenizer	19
8.14	Uses	19
8.15	Syntax	19
8.15.1	Exported Constants	19
8.15.2	Exported Access Programs	19
8.16	Semantics	19
8.16.1	State Variables	19
8.16.2	Environment Variables	19
8.16.3	Assumptions	19
8.16.4	Access Routine Semantics	19
8.16.5	Local Functions	19
8.17	Module ed_rep_model	20
8.18	Uses	20
8.19	Syntax	20
8.19.1	Exported Constants	20
8.19.2	Exported Access Programs	20
8.20	Semantics	20
8.20.1	State Variables	20
8.20.2	Environment Variables	20
8.20.3	Assumptions	20
8.20.4	Access Routine Semantics	20
8.20.5	Local Functions	20
8.21	Module ed_pred_model	21

8.22	Uses	21
8.23	Syntax	21
8.23.1	Exported Constants	21
8.23.2	Exported Access Programs	21
8.24	Semantics	21
8.24.1	State Variables	21
8.24.2	Environment Variables	21
8.24.3	Assumptions	21
8.24.4	Access Routine Semantics	21
8.24.5	Local Functions	21
8.25	Module <code>ed_transform</code>	22
8.26	Uses	22
8.27	Syntax	22
8.27.1	Exported Constants	22
8.27.2	Exported Access Programs	22
8.28	Semantics	22
8.28.1	State Variables	22
8.28.2	Environment Variables	22
8.28.3	Assumptions	22
8.28.4	Access Routine Semantics	22
8.28.5	Local Functions	22
9	Appendix	24
9.1	Reflection	24
9.1.1	Limitations of the proposed solution.	24
9.1.2	Benefits and trade-offs of other potential solutions.	24

3 Introduction

The following document details the Module Interface Specifications for Natural Language Processing for Mental Health Risk Prediction

Complementary documents include the System Requirement Specifications and Module Guide. The full documentation and implementation can be found at <https://github.com/MichaelBreau/nlp-mentalhealth>.

4 Notation

The structure of the MIS for modules comes from ?, with the addition that template modules have been adapted from ?. The mathematical notation comes from Chapter 3 of ?. For instance, the symbol $:=$ is used for a multiple assignment statement and conditional rules follow the form $(c_1 \Rightarrow r_1 | c_2 \Rightarrow r_2 | \dots | c_n \Rightarrow r_n)$.

The following table summarizes the primitive data types used by Natural Language Processing for Mental Health Risk Prediction.

Data Type	Notation	Description
character	char	a single symbol or digit
list	[item, item,...]	a list of objects of the same type
dict	$\langle key : T, val : T \rangle$	a dictionary of key value pairs
integer	\mathbb{Z}	a number without a fractional component in $(-\infty, \infty)$
natural number	\mathbb{N}	a number without a fractional component in $[1, \infty)$
real	\mathbb{R}	any number in $(-\infty, \infty)$

The specification of Natural Language Processing for Mental Health Risk Prediction uses some derived data types: sequences, strings, and tuples. Sequences are lists filled with elements of the same data type. Strings are sequences of characters. Tuples contain a list of values, potentially of different types. In addition, Natural Language Processing for Mental Health Risk Prediction uses functions, which are defined by the data types of their inputs and outputs. Local functions are described by giving their type signature followed by their specification.

5 Module Decomposition

The following table is taken directly from the Module Guide document for this project.

Level 1	Level 2	Level 3
Hardware-Hiding	None	
Behaviour-Hiding	Eating Disorder IO	ED Input ED Output
Software Decision	Depression Pipeline	Depression Main Depression Data Processing Depression Feature Extraction Depression Output Depression Evaluation
	Anorexia Pipeline	Anorexia Main Anorexia Parser Anorexia Training Anorexia Predictor
	Eating Disorder Pipeline	ED Pipeline Manager ED Tokenizer ED Representation Model ED Prediction Model ED Transformation 1...n (represents multiple modules)

Table 1: Module Hierarchy

6 MIS for Search for Symptoms of Depression Module

6.1 depression_main

Task 1 - Search for Symptoms of Depression for User Sentences - Main Module

6.2 Uses

Used for combining the various module functionalities in a pipeline format.
Uses depression_process_data, depression_feature_extraction, depression_output,
depression_accuracy_evaluation

6.3 Syntax

6.3.1 Exported Constants

None

6.3.2 Exported Access Programs

Name	In	Out	Exceptions
N/A	N/A	N/A	-

6.4 Semantics

6.4.1 State Variables

None

6.4.2 Environment Variables

None

6.4.3 Assumptions

None

6.4.4 Access Routine Semantics

None

6.4.5 Local Functions

None

6.5 depression_process_data

Task 1 - Search for Symptoms of Depression for User Sentences - Data Processing Module

6.6 Uses

Used for parsing user posts and golden truth files

6.7 Syntax

6.7.1 Exported Constants

None

6.7.2 Exported Access Programs

Name	In	Out	Exceptions
pathaddress	String	String	-
parsedata	String	Dictionary	-
processdata	String	Dictionary	-
goldentruthsentences	String	Dictionary	-

6.8 Semantics

6.8.1 State Variables

None

6.8.2 Environment Variables

None

6.8.3 Assumptions

- Data from user posts are in multiple trec file and the ground truth file is in a csv file and are present in the current task directory.

6.8.4 Access Routine Semantics

pathaddress():

- transition: None
- output: The path address for the data files
- exception: None

parsedata():

- transition: None
- output: Dictionary with usernames as keys connected to a list of strings containing user posts
- exception: None

parsedata():

- transition: None
- output: Dictionary with usernames as keys connected to a list of strings containing user posts, with gibberish information removed
- exception: None

goldentruthsentences():

- transition: None
- output: Dictionary with usernames as keys connected to an integer representing their depression symptom
- exception: None

6.8.5 Local Functions

None

6.9 depression_feature_extraction

Task 1 - Search for Symptoms of Depression for User Sentences - Feature Extraction Module

6.10 Uses

Used for predicting the top depression sentences that matches each symptom of depression

6.11 Syntax

6.11.1 Exported Constants

None

6.11.2 Exported Access Programs

Name	In	Out	Exceptions
getFeatureWords	List	Dictionary	-
feature_2_vec	Dictionary, Dictionary	Dictionary	-
getEmbeddings	Dictionary, Dictionary, Dictionary	Dictionary	-
tf_idf	Dictionary, Dictionary Integer	Dictionary	-
vectorizePosts	Dictionary, Dictionary Dictionary	Dictionary	-
cosine_sim	Dictionary, List	Dictionary	-

6.12 Semantics

6.12.1 State Variables

None

6.12.2 Environment Variables

None

6.12.3 Assumptions

None

6.12.4 Access Routine Semantics

getFeatureWords():

- transition: None
- output: A dictionary where each key represents a depression symptom, and the corresponding value is a list of strings representing feature words extracted from files.
- exception: None

feature_2_vec():

- transition: None
- output: Produces a dictionary where each key corresponds to a question number, and the associated value is a numpy array representing the vectorized features for that question.
- exception: None

getEmbeddings():

- transition: None
- output: Outputs a dictionary containing word embeddings, filtered based on words present in the data, feature sets, and a given set of word embeddings
- exception: None

tfidf():

- transition: None
- output: Generates a dictionary where each key represents a document ID, and the associated value is a list of strings representing the top-k words based on TF-IDF scores.
- exception: None

vectorizePosts():

- transition: None
- output: A dictionary where each key represents a sentence, and the corresponding value is a numpy array representing the vectorized representation of the sentence.
- exception: None

cosine_sim():

- transition: None
- output: A dictionary where each key represents a sentence, and the associated value is a float representing the cosine similarity between the sentence vector and a target vector.
- exception: None

6.12.5 Local Functions

None

6.13 depression_output

Task 1 - Search for Symptoms of Depression for User Sentences - Ouput Module

6.14 Uses

Used for generating output into a specific format

6.15 Syntax

6.15.1 Exported Constants

None

6.15.2 Exported Access Programs

Name	In	Out	Exceptions
write_to_text_file	Any, String	-	-
write_dict_to_file	Dictionary, String	-	-
get_questions	String	List	-
get_top_matches	String, Dictionary	Dictionary	-

6.16 Semantics

6.16.1 State Variables

None

6.16.2 Environment Variables

None

6.16.3 Assumptions

None

6.16.4 Access Routine Semantics

write_to_text_file():

- transition: None
- output: None
- exception: None

write_dict_to_file():

- transition: None
- output: None
- exception: None

get_questions():

- transition: None

- output: A list of strings representing symptom names extracted from a JSON questionnaire file.
- exception: None

get_top_matches():

- transition: None
- output: A dictionary where each key represents a question index, and the associated value is a list of top matches based on user responses.
- exception: None

6.16.5 Local Functions

None

6.17 depression_accuracy_evaluation

Task 1 - Search for Symptoms of Depression for User Sentences - Accuracy Evaluation Module

6.18 Uses

Used for determining the accuracy of generated results using various metrics

6.19 Syntax

6.19.1 Exported Constants

None

6.19.2 Exported Access Programs

Name	In	Out	Exceptions
golden_truth_sentence_data	String	Dictionary	-
get_average_precisions	Dictionary, Dictionary	List	-
print_accuracy	List, List, String	-	-

6.20 Semantics

6.20.1 State Variables

None

6.20.2 Environment Variables

None

6.20.3 Assumptions

None

6.20.4 Access Routine Semantics

`golden_truth_sentence_data()`:

- transition: None
- output: A dictionary where each key represents a question index, and the associated value is a list of sentence IDs and their relevances based on a provided CSV file.
- exception: None

`get_average_precisions()`:

- transition: None
- output: A list containing precision values and NDCG values calculated based on the provided sentence scores and golden truth values.
- exception: None

`print_accuracy()`:

- transition: None
- output: None
- exception: None

6.20.5 Local Functions

None

7 MIS for Early Detection of Signs of Anorexia Module

7.1 anorexia_main

Task 2 - Early Detection of Signs of Anorexia using User Posts - Main Module

7.2 Uses

Used for combining the various module functionalities in a pipeline format

7.3 Syntax

7.3.1 Exported Constants

None

7.3.2 Exported Access Programs

Name	In	Out	Exceptions
N/A	N/A	N/A	-

7.4 Semantics

7.4.1 State Variables

None

7.4.2 Environment Variables

None

7.4.3 Assumptions

None

7.4.4 Access Routine Semantics

None

7.4.5 Local Functions

None

7.5 anorexia_parser

Task 2 - Early Detection of Signs of Anorexia using User Posts - Parser Module

7.6 Uses

Used for parsing user posts and golden truth files

7.7 Syntax

7.7.1 Exported Constants

None

7.7.2 Exported Access Programs

Name	In	Out	Exceptions
pathaddress	String	String	-
parsedata	String	Dictionary	-
goldentruth	String	Dictionary	-

7.8 Semantics

7.8.1 State Variables

None

7.8.2 Environment Variables

None

7.8.3 Assumptions

- Data from user posts are in an xml file and the ground truth file is in a txt file and are present in the current working directory.

7.8.4 Access Routine Semantics

pathaddress():

- transition: None
- output: The path address for the data files
- exception: None

parsedata():

- transition: None
- output: Dictionary with usernames as keys connected to a list of strings containing user posts

- exception: None

goldentruth():

- transition: None
- output: Dictionary with usernames as keys connected to an integer representing their anorexia status (0 or 1)
- exception: None

7.8.5 Local Functions

None

7.9 anorexia_training

Task 2 - Early Detection of Signs of Anorexia using User Posts - Training Module

7.10 Uses

Used for training bertopic model on parsed data using golden truth values

7.11 Syntax

7.11.1 Exported Constants

None

7.11.2 Exported Access Programs

Name	In	Out	Exceptions
bert	Dictionary	List, List	-
predictor	List, List	Dictionary	-
calculateaccuracy	Dictionary, Dictionary	None	-

7.12 Semantics

7.12.1 State Variables

None

7.12.2 Environment Variables

None

7.12.3 Assumptions

- The model is trained on accurate data with correctly linked user-truth values.

7.12.4 Access Routine Semantics

bert():

- transition: None
- output: List 1: List of usernames, List 2: List of topics generated from the bertopic model with the indexes corresponding to the usernames from the first list
- exception: None

predictor():

- transition: None
- output: Dictionary with usernames as keys and the predicted 0 or 1 integer linked
- exception: None

calculateaccuracy():

- transition: None
- output: Accuracy scores comparing golden truth to predictor values

$$Precision(P) = \frac{|u \in U : d = g = 1|}{|u \in U : d = 1|}$$

$$Recall(R) = \frac{|u \in U : d = g = 1|}{|u \in U : g = 1|}$$

$$F - Score(F) = \frac{2 * P * R}{P + R}$$

- exception: None

7.12.5 Local Functions

None

7.13 anorexia_predictor

Task 2 - Early Detection of Signs of Anorexia using User Posts - Predictor Module

7.14 Uses

Used for predicting new documents unseen by training

7.15 Syntax

7.15.1 Exported Constants

None

7.15.2 Exported Access Programs

Name	In	Out	Exceptions
predict_new	String	Integer	-

7.16 Semantics

7.16.1 State Variables

None

7.16.2 Environment Variables

None

7.16.3 Assumptions

None

7.16.4 Access Routine Semantics

predict_new():

- transition: None
- output: Integer 0 or 1 corresponding to the model prediction of anorexia negative or positive
- exception: None

7.16.5 Local Functions

None

8 MIS for Measuring the Severity of the Signs of Eating Disorders

8.1 Module ed input

8.2 Uses

None

8.3 Syntax

8.3.1 Exported Constants

None

8.3.2 Exported Access Programs

Name	In	Out	Exceptions
read_file	<i>String</i>	<i>Dict</i>	<i>IncorrectFileFormat</i>

8.4 Semantics

8.4.1 State Variables

None

8.4.2 Environment Variables

None

8.4.3 Assumptions

The input to read_file will be a path to a file on the disk.

8.4.4 Access Routine Semantics

read_file(*pathaddress* : *String*):

- transition: None
- output: *Dict of* $\langle \text{username} : \text{String}, \text{posts} : [\text{post} : \text{String} | \text{post} \in \text{user's posts}] \rangle$
- exception: If the input file is not correctly formatted

8.4.5 Local Functions

None

8.5 Module ed_output

8.6 Uses

None

8.7 Syntax

8.7.1 Exported Constants

None

8.7.2 Exported Access Programs

Name	In	Out	Exceptions
write_file	$Str,$ $Dict < Str : List[Int] >$	None	None

8.8 Semantics

8.8.1 State Variables

None

8.8.2 Environment Variables

None

8.8.3 Assumptions

The rest of the pipeline up to this point will produce a *Dict of* $< username : String, scores : [s_1, s_2, \dots, s_{22}] >$ where s_1, s_2, \dots, s_{22} are the predicted scores for each of the eating disorder questionnaire's 22 questions

8.8.4 Access Routine Semantics

`write_file(file : Str, scores : Dict of < username : Str, scores : [s1, s2, ..., s22] >):`

- transition: writes *scores* to the file specified by *file* where each line is of the format "username: s1, s2, ..., s22" for each user.
- output: None
- exception: None

8.8.5 Local Functions

None

8.9 Module ed_pipeline

8.10 Uses

ed_input, ed_tokenizer, ed_rep_model, ed_pred_model, ed_output

8.11 Syntax

8.11.1 Exported Constants

None

8.11.2 Exported Access Programs

Name	In	Out	Exceptions
run_pipeline	<i>Str</i> , <i>Str</i>	None	None

8.12 Semantics

8.12.1 State Variables

None

8.12.2 Environment Variables

None

8.12.3 Assumptions

The first input to run_pipeline is a path to a file on the disk

8.12.4 Access Routine Semantics

write_file(*in_file* : *Str*, *out_file* : *Str*):

- transition: calls ed_input to read from *in_file*, runs the full pipeline, and calls ed_output to write user scores to *out_file*.
- output: None
- exception: None

8.12.5 Local Functions

None

8.13 Module `ed_tokenizer`

8.14 Uses

None

8.15 Syntax

8.15.1 Exported Constants

None

8.15.2 Exported Access Programs

Name	In	Out	Exceptions
<code>tokenize</code>	<i>Str</i> , [<i>Bool</i>]	<i>List of Str</i>	None

8.16 Semantics

8.16.1 State Variables

None

8.16.2 Environment Variables

None

8.16.3 Assumptions

None

8.16.4 Access Routine Semantics

`write_file(text : Str, options : [Bool]):`

- transition: None
- output: A list of words representing *text* split by whitespace after *text* is processed in a number of ways specified by *options*.
- exception: None

8.16.5 Local Functions

None

8.17 Module `ed_rep_model`

8.18 Uses

None

8.19 Syntax

8.19.1 Exported Constants

None

8.19.2 Exported Access Programs

Name	In	Out	Exceptions
<code>represent</code>	<code>[Str]</code> , <code>[Bool]</code>	<code>[Float]</code>	None

8.20 Semantics

8.20.1 State Variables

None

8.20.2 Environment Variables

None

8.20.3 Assumptions

The first input to `represent` will be the output of `ed_tokenizer`: a processed list of the words in the input text split by whitespace.

8.20.4 Access Routine Semantics

`represent(text : [Str], options : [Bool]):`

- transition: None
- output: A list of floats representing *text* encoded by some method into a numerical format, the details of the conversion are specified by *options*.
- exception: None

8.20.5 Local Functions

None

8.21 Module `ed_pred_model`

8.22 Uses

`ed_transform`

8.23 Syntax

8.23.1 Exported Constants

None

8.23.2 Exported Access Programs

Name	In	Out	Exceptions
<code>predict</code>	$\langle Str, [Float] \rangle, [Bool]$	$\langle Str, [Float] \rangle$	None

8.24 Semantics

8.24.1 State Variables

None

8.24.2 Environment Variables

None

8.24.3 Assumptions

The first input to `predict` will be a dictionary of the outputs of `ed_rep_model` for each user.

8.24.4 Access Routine Semantics

`represent(user_data : $\langle username : text, representation : [Float] \rangle$, options : List of Bool):`

- transition: None
- output: A dictionary of $\langle username : String, scores : [s_1, s_2, \dots, s_{22}] \rangle$ where s_1, s_2, \dots, s_{22} are the predicted scores for each of the eating disorder questionnaire's 22 questions for each user *username*.
- exception: None

8.24.5 Local Functions

None

8.25 Module `ed_transform`

8.26 Uses

`ed_transform`

8.27 Syntax

8.27.1 Exported Constants

None

8.27.2 Exported Access Programs

Name	In	Out	Exceptions
<code>predict</code>	$\langle Str, [Float] \rangle, [Bool]$	$\langle Str, [Float] \rangle$	None

8.28 Semantics

8.28.1 State Variables

None

8.28.2 Environment Variables

None

8.28.3 Assumptions

None

8.28.4 Access Routine Semantics

`represent`(*user_data* : $\langle username : text, representation : [Float] \rangle$, *options* : $[Bool]$):

- transition: None
- output: A dictionary of $\langle username : String, representation : [Float] \rangle$ where each of the output's *representations* is a transformation of the input *representations*.
- exception: None

8.28.5 Local Functions

None

References

9 Appendix

9.1 Reflection

9.1.1 Limitations of the proposed solution.

One of the primary limitations recognized in our design is that the performance of the various risk detectors are all turtlenecked with the spread of training data available to them. This primarily being enforced by biases present in the data which may skew results incorrectly, a prominent issue with all projects that rely on artificial intelligence to help predict an outcome. This bias can present itself as a decreased effectiveness for variations in cultural and linguistic backgrounds of the analyzed user data.

Additionally, this ties into the overall limitation of the system of how this tool is intended to be assistive and supplementary to trained mental health professionals, it is not meant to be the sole source of a diagnosis. Biases and limitations of the code structure will always offer an amount of machine error, which is why this program is to be used under the guidance of professionals who can help corroborate the results using their situation context and emotional intelligence, an ability that cannot ever truly be given to a computer.

9.1.2 Benefits and trade-offs of other potential solutions.

Early in the design and planning process, the team experimented with the idea of using large language models similar to ChatGPT for diagnosis. This would allow us to leverage well documented and existing technologies in our efforts, providing a strong jumping off point for our workflow. Unfortunately, the team was able to soon discover research which showed that models like ChatGPT tend to draw undesirable parallels with their training data, resulting in the system unknowingly fabricating information in the input data which would provide incorrect results.