

Package ‘GWPR.light’

October 4, 2021

Type Package

Title Geographically Weighted Panel Regression (GWPR)

Version 0.1.0

Author Chao Li [aut, cre], Shunsuke Managi [aut]

Maintainer Chao Li <chaoli0394@gmail.com>

Description This package includes the function for the optimal bandwidth selection in GWPR, the function for GWPR, the function for the local Hausman test, the function for the local F test for individual effects, the function for the local Lagrange Multiplier Breusch-Pagan test, and the function for panel Moran's I test. The functions have been optimized, which require the less memory in the calculation.

License AGPL (>= 3)

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

Imports data.table,
doParallel,
dplyr,
foreach,
GWmodel,
iterators,
lmtest,
parallel,
plm,
sp,
stats

Depends R (>= 2.10)

Suggests rmarkdown,
knitr

VignetteBuilder knitr

URL <https://github.com/MichaelChaoLi-cpu/GWPR.light>

BugReports <https://github.com/MichaelChaoLi-cpu/GWPR.light/issues>

R topics documented:

| | |
|------------------------------|-----------|
| GWPR.light-package | 2 |
| bw.GWPR | 3 |
| California | 4 |
| GWPR | 5 |
| GWPR.moran.test | 7 |
| GWPR.pFtest | 8 |
| GWPR.phtest | 10 |
| GWPR.plmtest | 11 |
| TransAirPolCalif | 13 |
| Index | 15 |

| | |
|--------------------|---|
| GWPR.light-package | <i>A Package for Geographically Weighted Panel Regression (light version)</i> |
|--------------------|---|

Description

This package includes the function for the optimal bandwidth selection in GWPR, the function for GWPR, the function for the local Hausman test, the function for the local F test for individual effects, the function for the local Lagrange Multiplier Breusch-Pagan test, and the function for panel Moran's I test. The functions have been optimized, which require the less memory in the calculation.

Details

Package: GWPR.light

Type: Package

Version: 0.1.0

Date: 2021-10-02

License: AGPL (>= 3)

LazyLoad: yes

Author(s)

Chao Li <chaoli0394@gmail.com> [aut, cre] Shunsuke Managi <managi@doc.kyushu-u.ac.jp> [aut]

bw.GWPR

*Bandwidth selection for basic GWPR***Description**

A function for automatic bandwidth selection to calibrate a GWPR model

Usage

```
bw.GWPR(formula, data, index, SDF, adaptive = F, p = 2, bigdata = F, upperratio = 0.25,
        effect = "individual", model = c("pooling", "within", "random"),
        random.method = "swar", approach = c("CV", "AIC"), kernel = "bisquare",
        longlat = F, doParallel = F, cluster.number = 2, human.set.range = F,
        h.upper = NULL, h.lower = NULL)
```

Arguments

| | |
|-----------------|---|
| formula | The regression formula: $Y \sim X_1 + \dots + X_k$ |
| data | data.frame for the Panel data |
| index | A vector for the indexes: <code>(c("ID", "Time"))</code> |
| SDF | Spatial*DataFrame on which is based the data, with the "ID" in the index |
| adaptive | If TRUE, adaptive distance bandwidth is used, otherwise, fixed distance bandwidth. |
| p | The power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| bigdata | TRUE or FALSE, if the dataset exceeds 40,000, we strongly recommend set it true |
| upperratio | Set the ratio between upper boundary of potential bandwidth range and the fortheft distance of SDF, if bigdata = T. (default value: 0.25) |
| effect | The effects introduced in the model, one of "individual" (default) , "time", "twoways", or "nested" |
| model | Panel model transformation: <code>(c("within", "random", "pooling"))</code> |
| random.method | Method of estimation for the variance components in the random effects model, one of "swar" (default), "amemiya", "walhus", or "nerlove" |
| approach | Score used to optimize the bandwidth, <code>c("CV", "AIC")</code> |
| kernel | bisquare: $wgt = (1 - (vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise (default); gaussian: $wgt = \exp(-.5 * (vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; tricube: $wgt = (1 - (vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| longlat | If TRUE, great circle distances will be calculated |
| doParallel | If TRUE, "cluster": multi-process technique with the parallel package would be used. |
| cluster.number | The number of the clusters that user wants to use |
| human.set.range | If TRUE, the range of bandwidth selection could be set by the user |
| h.upper | The lower boundary of potential bandwidth range. |
| h.lower | The upper boundary of potential bandwidth range. |

Value

The optimal bandwidth

Author(s)

Chao Li <chaoli0394@gmail.com> Shunsuke Managi <managi.s@gmail.com>

References

Fotheringham, A. Stewart, Chris Brunsdon, and Martin Charlton. Geographically weighted regression: the analysis of spatially varying relationships. John Wiley & Sons, 2003.

Examples

```
## Not run:
data(TransAirPolCalif)
data(California)
formula.GWPR <- pm25 ~ co2_mean + Developed_Open_Space_perc + Developed_Low_Intensity_perc +
  Developed_Medium_Intensity_perc + Developed_High_Intensity_perc +
  Open_Water_perc + Woody_Wetlands_perc + Emergent_Herbaceous_Wetlands_perc +
  Deciduous_Forest_perc + Evergreen_Forest_perc + Mixed_Forest_perc +
  Shrub_perc + Grassland_perc + Pasture_perc + Cultivated_Crops_perc +
  pop_density + summer_tmmx + winter_tmmx + summer_rmax + winter_rmax

bw.CV.F <- bw.GWPR(formula = formula.GWPR, data = TransAirPolCalif, index = c("GEOID", "year"),
  SDF = California, adaptive = F, p = 2, bigdata = F, effect = "individual",
  model = "within", approach = "CV", kernel = "bisquare", longlat = F)

bw.CV.F

bw.AIC.F <- bw.GWPR(formula = formula.GWPR, data = TransAirPolCalif, index = c("GEOID", "year"), SDF = California,
  adaptive = F, p = 2, bigdata = F, effect = "individual",
  model = "within", approach = "AIC", kernel = "bisquare", longlat = F,
  doParallel = T, cluster.number = 4)

bw.AIC.F

## End(Not run)
```

California

California (SpatialPolygonsDataFrame)

Description

The counties' boundary in California

Usage

```
data(California)
```

Format

A `sp::SpatialPolygonsDataFrame` with 'GEOID':

GEOID a numeric vector, fips IDs of the counties

Author(s)

Chao Li <chaoli0394@gmail.com> Shunsuke Managi <managi.s@gmail.com>

Examples

```
## Not run:
data(California)
plot(California)

## End(Not run)
```

GWPR

Geographically Weighted Panel Regression Model

Description

This function implements GWPR

Usage

```
GWPR(formula, data, index, SDF, bw = NULL, adaptive = F, p = 2,
      effect = "individual", model = c("pooling", "within", "random"),
      random.method = "swar", kernel = "bisquare", longlat = F)
```

Arguments

| | |
|---------------|---|
| formula | The regression formula: $Y \sim X_1 + \dots + X_k$ |
| data | A data.frame for the Panel data |
| index | A vector for the indexes: (c("ID", "Time")) |
| SDF | Spatial*DataFrame on which is based the data, with the "ID" in the index |
| bw | The optimal bandwidth, either adaptive or fixed distance |
| adaptive | If TRUE, adaptive distance bandwidth is used, otherwise, fixed distance bandwidth. |
| p | The power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| effect | The effects introduced in the model, one of "individual" (default) , "time", "twoways", or "nested" |
| model | Panel model transformation: (c("within", "random", "pooling")) |
| random.method | Method of estimation for the variance components in the random effects model, one of "swar" (default), "amemiya", "walhus", or "nerlove" |
| kernel | bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise (default); gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| longlat | If TRUE, great circle distances will be calculated |

Value

A list of result:

GW.arguments a list class object including the model fitting parameters for generating the report file

R2 global r2

index the index used in the result, Note: in order to avoid mistakes, we forced a rename of the individuals'ID as id.

plm.result an object of class inheriting from plm, see plm

raw.data the data.frame used in the regression

GWPR.residuals the data.frame includes Y, Y hat, and residuals from GWPR

SDF a Spatial*DataFrame (either Points or Polygons, see sp) integrated with fit.points,GWPR coefficient estimates,coefficient standard errors and t-values in its data slot.

Author(s)

Chao Li <chaoli0394@gmail.com> Shunsuke Managi <managi.s@gmail.com>

References

Fotheringham, A. Stewart, Chris Brunsdon, and Martin Charlton. Geographically weighted regression: the analysis of spatially varying relationships. John Wiley & Sons, 2003.

Examples

```
## Not run:
data(TransAirPolCalif)
data(California)
formula.GWPR <- pm25 ~ co2_mean + Developed_Open_Space_perc + Developed_Low_Intensity_perc +
  Developed_Medium_Intensity_perc + Developed_High_Intensity_perc +
  Open_Water_perc + Woody_Wetlands_perc + Emergent_Herbaceous_Wetlands_perc +
  Deciduous_Forest_perc + Evergreen_Forest_perc + Mixed_Forest_perc +
  Shrub_perc + Grassland_perc + Pasture_perc + Cultivated_Crops_perc +
  pop_density + summer_tmmx + winter_tmmx + summer_rmax + winter_rmax

bw.AIC.F <- bw.GWPR(formula = formula.GWPR, data = TransAirPolCalif, index = c("GEOID", "year"), SDF = California,
  adaptive = F, p = 2, bigdata = F, effect = "individual",
  model = "within", approach = "AIC", kernel = "bisquare", longlat = F,
  doParallel = T, cluster.number = 4)

result.F.AIC <- GWPR(bw = bw.AIC.F, formula = formula.GWPR, data = TransAirPolCalif, index = c("GEOID", "year"),
  SDF = California, adaptive = F, p = 2, effect = "individual", model = "within",
  kernel = "bisquare", longlat = F)
summary(result.F.AIC$SDF$Local_R2)
library(tmap)
tm_shape(result.F.AIC$SDF) +
tm_polygons(col = "Local_R2", pal = "Reds", auto.palette.mapping = F,
  style = 'cont')

## End(Not run)
```

GWPR.moran.test

Moran's I Test for Panel Regression

Description

Moran's I Test for Panel Regression

Usage

```
GWPR.moran.test(
  plm_model,
  SDF,
  bw,
  adaptive = F,
  p = 2,
  kernel = "bisquare",
  longlat = F,
  alternative = "greater"
)
```

Arguments

| | |
|-------------|---|
| plm_model | An object of class inheriting from "plm", see plm |
| SDF | Spatial*DataFrame on which is based the data, with the "ID" in the index |
| bw | The optimal bandwidth, either adaptive or fixed distance |
| adaptive | If TRUE, adaptive distance bandwidth is used, otherwise, fixed distance bandwidth. |
| p | The power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| kernel | bisquare: $\text{wgt} = (1 - (\text{vdist}/\text{bw})^2)^2$ if $\text{vdist} < \text{bw}$, $\text{wgt}=0$ otherwise (default); gaussian: $\text{wgt} = \exp(-.5 * (\text{vdist}/\text{bw})^2)$; exponential: $\text{wgt} = \exp(-\text{vdist}/\text{bw})$; tricube: $\text{wgt} = (1 - (\text{vdist}/\text{bw})^3)^3$ if $\text{vdist} < \text{bw}$, $\text{wgt}=0$ otherwise; boxcar: $\text{wgt}=1$ if $\text{dist} < \text{bw}$, $\text{wgt}=0$ otherwise |
| longlat | If TRUE, great circle distances will be calculated |
| alternative | A character string specifying the alternative hypothesis, must be one of greater (default), less or two.sided. |

Value

A list of result:

statistic the value of the standard deviate of Moran's I.

p.value the p-value of the test.

Estimated.I the value of the observed Moran's I.

Expected.I the value of the expectation of Moran's I.

V2 the value of the variance of Moran's I.

alternative a character string describing the alternative hypothesis.

Note

: Current version of panel Moran's I test can only check the balanced panel data.

Author(s)

Chao Li <chaoli0394@gmail.com> Shunsuke Managi <managi.s@gmail.com>

References

Beenstock, M., Felsenstein, D., 2019. The econometric analysis of non-stationary spatial panel data. Springer.

Examples

```
## Not run:
data(TransAirPolCalif)
data(California)
formula.GWPR <- pm25 ~ co2_mean + Developed_Open_Space_perc + Developed_Low_Intensity_perc +
  Developed_Medium_Intensity_perc + Developed_High_Intensity_perc +
  Open_Water_perc + Woody_Wetlands_perc + Emergent_Herbaceous_Wetlands_perc +
  Deciduous_Forest_perc + Evergreen_Forest_perc + Mixed_Forest_perc +
  Shrub_perc + Grassland_perc + Pasture_perc + Cultivated_Crops_perc +
  pop_density + summer_tmmx + winter_tmmx + summer_rmax + winter_rmax

pdata <- plm::pdata.frame(TransAirPolCalif, index = c("GEOID", "year"))
moran.plm.model <- plm::plm(formula = formula.GWPR, data = pdata, model = "within")
summary(moran.plm.model)

bw.AIC.F <- bw.GWPR(formula = formula.GWPR, data = TransAirPolCalif, index = c("GEOID", "year"), SDF = California,
  adaptive = F, p = 2, bigdata = F, effect = "individual",
  model = "within", approach = "AIC", kernel = "bisquare", longlat = F,
  doParallel = T, cluster.number = 4)

# moran's I test
GWPR.moran.test(moran.plm.model, SDF = California, bw = bw.AIC.F, kernel = "bisquare",
  adaptive = F, p = 2, longlat=F, alternative = "greater")

## End(Not run)
```

GWPR.pFtest

Locally F Test based on GWPR

Description

This function perform F test in each regression based on different subsamples

Usage

```
GWPR.pFtest(formula, data, index, SDF, bw = NULL, adaptive = F, p = 2, effect = "individual",
  kernel = "bisquare", longlat = F)
```


Arguments

| | |
|----------|---|
| formula | The regression formula: : $Y \sim X_1 + \dots + X_k$ |
| data | A data.frame for the Panel data. |
| index | A vector for the indexes : (c("ID", "Time")). |
| SDF | Spatial*DataFrame on which is based the data, with the "ID" in the index. |
| bw | The optimal bandwidth, either adaptive or fixed distance. |
| adaptive | If TRUE, adaptive distance bandwidth is used, otherwise, fixed distance bandwidth. |
| p | The power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| effect | The effects introduced in the fixed effects model, one of "individual" (default) , "time", "twoways" |
| kernel | bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise (default); gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| longlat | If TRUE, great circle distances will be calculated |

Value

A list of result:

GW.arguments a list class object including the model fitting parameters for generating the report file

SDF a Spatial*DataFrame (either Points or Polygons, see sp) integrated with fit.points, test value, p value, df1, df2

Author(s)

Chao Li <chaoli0394@gmail.com> Shunsuke Managi <managi.s@gmail.com>

Examples

```
## Not run:
data(TransAirPolCalif)
data(California)
formula.GWPR <- pm25 ~ co2_mean + Developed_Open_Space_perc + Developed_Low_Intensity_perc +
  Developed_Medium_Intensity_perc + Developed_High_Intensity_perc +
  Open_Water_perc + Woody_Wetlands_perc + Emergent_Herbaceous_Wetlands_perc +
  Deciduous_Forest_perc + Evergreen_Forest_perc + Mixed_Forest_perc +
  Shrub_perc + Grassland_perc + Pasture_perc + Cultivated_Crops_perc +
  pop_density + summer_tmmx + winter_tmmx + summer_rmax + winter_rmax

bw.AIC.F <- bw.GWPR(formula = formula.GWPR, data = TransAirPolCalif, index = c("GEOID", "year"), SDF = California,
  adaptive = F, p = 2, bigdata = F, effect = "individual",
  model = "within", approach = "AIC", kernel = "bisquare", longlat = F,
  doParallel = T, cluster.number = 4)
GWPR.pFtest.resu.F <- GWPR.pFtest(formula = formula.GWPR, data = TransAirPolCalif, index = c("GEOID", "year"),
  SDF = California, bw = bw.AIC.F, adaptive = F, p = 2, effect = "individual",
  kernel = "bisquare", longlat = F)

library(tmap)
tm_shape(GWPR.pFtest.resu.F$SDF) +
```

```
tm_polygons(col = "p.value", breaks = c(0, 0.05, 1))

## End(Not run)
```

GWPR.phtest

Locally Hausman Test based on GWPR

Description

Locally Hausman Test based on GWPR

Usage

```
GWPR.phtest(
  formula,
  data,
  index,
  SDF,
  bw = NULL,
  adaptive = F,
  p = 2,
  effect = "individual",
  random.method = "swar",
  kernel = "bisquare",
  longlat = F
)
```

Arguments

| | |
|---------------|---|
| formula | The regression formula: : $Y \sim X_1 + \dots + X_k$ |
| data | A data.frame for the Panel data. |
| index | A vector for the indexes : (c("ID", "Time")). |
| SDF | Spatial*DataFrame on which is based the data, with the "ID" in the index. |
| bw | The optimal bandwidth, either adaptive or fixed distance. |
| adaptive | If TRUE, adaptive distance bandwidth is used, otherwise, fixed distance bandwidth. |
| p | The power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| effect | The effects introduced in the fixed effects model, one of "individual" (default) , "time", "twoways" |
| random.method | Method of estimation for the variance components in the random effects model, one of "swar" (default), "amemiya", "walhus", or "nerlove" |
| kernel | bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise (default); gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| longlat | If TRUE, great circle distances will be calculated |

Value

A list of result:

GW.arguments a list class object including the model fitting parameters for generating the report file

SDF a Spatial*DataFrame (either Points or Polygons, see sp) integrated with fit.points, test value, p value, df

Note

If the random method is "swar", to perform this test, bandwidth selection must guarantee that enough individuals in the subsamples. Using bw.GWPR function can avoid mistake.

Author(s)

Chao Li <chaoli0394@gmail.com> Shunsuke Managi <managi.s@gmail.com>

Examples

```
## Not run:
data(TransAirPolCalif)
data(California)
formula.GWPR <- pm25 ~ co2_mean + Developed_Open_Space_perc + Developed_Low_Intensity_perc +
  Developed_Medium_Intensity_perc + Developed_High_Intensity_perc +
  Open_Water_perc + Woody_Wetlands_perc + Emergent_Herbaceous_Wetlands_perc +
  Deciduous_Forest_perc + Evergreen_Forest_perc + Mixed_Forest_perc +
  Shrub_perc + Grassland_perc + Pasture_perc + Cultivated_Crops_perc +
  pop_density + summer_tmmx + winter_tmmx + summer_rmax + winter_rmax

bw.AIC.F <- bw.GWPR(formula = formula.GWPR, data = TransAirPolCalif, index = c("GEOID", "year"), SDF = Californ
  adaptive = F, p = 2, bigdata = F, effect = "individual",
  model = "random", approach = "AIC", kernel = "bisquare", longlat = F,
  doParallel = T, cluster.number = 4)
GWPR.phtest.resu.F <- GWPR.phtest(formula = formula.GWPR, data = TransAirPolCalif, index = c("GEOID", "year"),
  SDF = California, bw = bw.AIC.F, adaptive = F, p = 2, effect = "individual",
  kernel = "bisquare", longlat = F)

library(tmap)
tm_shape(GWPR.phtest.resu.F$SDF) +
  tm_polygons(col = "p.value", breaks = c(0, 0.05, 1))

## End(Not run)
```

GWPR.plmtest

Locally Breusch-Pagan Lagrange Multiplier Test Based on GWPR

Description

This function perform Breusch-Pagan Lagrange Multiplier test in each regression based on different subsamples

Usage

```
GWPR.plmtest(formula, data, index, SDF, bw = NULL, adaptive = F, p = 2,
  kernel = "bisquare", longlat = F)
```

Arguments

| | |
|----------|---|
| formula | The regression formula: : $Y \sim X_1 + \dots + X_k$ |
| data | A data.frame for the Panel data. |
| index | A vector for the indexes : (c("ID", "Time")). |
| SDF | Spatial*DataFrame on which is based the data, with the "ID" in the index. |
| bw | The optimal bandwidth, either adaptive or fixed distance. |
| adaptive | If TRUE, adaptive distance bandwidth is used, otherwise, fixed distance bandwidth. |
| p | The power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| kernel | bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise (default); gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| longlat | If TRUE, great circle distances will be calculated |

Value

A list of result:

GW.arguments a list class object including the model fitting parameters for generating the report file

SDF a Spatial*DataFrame (either Points or Polygons, see sp) integrated with fit.points, test value, p value, df1, df2

Author(s)

Chao Li <chaoli0394@gmail.com> Shunsuke Managi <managi.s@gmail.com>

Examples

```
## Not run:
data(TransAirPolCalif)
data(California)
formula.GWPR <- pm25 ~ co2_mean + Developed_Open_Space_perc + Developed_Low_Intensity_perc +
  Developed_Medium_Intensity_perc + Developed_High_Intensity_perc +
  Open_Water_perc + Woody_Wetlands_perc + Emergent_Herbaceous_Wetlands_perc +
  Deciduous_Forest_perc + Evergreen_Forest_perc + Mixed_Forest_perc +
  Shrub_perc + Grassland_perc + Pasture_perc + Cultivated_Crops_perc +
  pop_density + summer_tmmx + winter_tmmx + summer_rmax + winter_rmax

bw.AIC.F <- bw.GWPR(formula = formula.GWPR, data = TransAirPolCalif, index = c("GEOID", "year"), SDF = California,
  adaptive = F, p = 2, bigdata = F, effect = "individual",
  model = "within", approach = "AIC", kernel = "bisquare", longlat = F,
  doParallel = T, cluster.number = 4)
GWPR.plmtest.resu.F <- GWPR.plmtest(formula = formula.GWPR, data = TransAirPolCalif, index = c("GEOID", "year"),
  SDF = California, bw = bw.AIC.F, adaptive = F, p = 2,
  kernel = "bisquare", longlat = F)

library(tmap)
tm_shape(GWPR.plmtest.resu.F$SDF) +
  tm_polygons(col = "p.value", breaks = c(0, 0.05, 1))

## End(Not run)
```

TransAirPolCalif

*Panel Dataset for Testing GWPR***Description**

Panel dataset to estimate the relationship between county-level PM2.5 concentration and on-road transportation in California.

Usage

```
data(TransAirPolCalif)
```

Format

A data.frame with 23 variables, and 928 observations, which are:

GEOID a numeric vector, fips IDs of the counties

year a numeric vector, year

pm25 a numeric vector, annually average PM2.5 concentration in the counties

co2_mean a numeric vector, geographically average CO2 emission from on-road transportation in each year, million tons/km2

Developed_Open_Space_perc a numeric vector, percentage of developed open space of total area in each county

Developed_Low_Intensity_perc a numeric vector, percentage of low-intensity developed area of total area in each county

Developed_Medium_Intensity_perc a numeric vector, percentage of medium-intensity developed area of total area in each county

Developed_High_Intensity_perc a numeric vector, percentage of high-intensity developed area of total area in each county

Open_Water_perc a numeric vector, percentage of open water of total area in each county

Woody_Wetlands_perc a numeric vector, percentage of woody wetland of total area in each county

Emergent_Herbaceous_Wetlands_perc a numeric vector, percentage of emergent herbaceous wetland of total area in each county

Deciduous_Forest_perc a numeric vector, percentage of deciduous forest of total area in each county

Evergreen_Forest_perc a numeric vector, percentage of evergreen forest of total area in each county

Mixed_Forest_perc a numeric vector, percentage of mixed forest of total area in each county

Shrub_perc a numeric vector, percentage of shrub of total area in each county

Grassland_perc a numeric vector, percentage of grassland of total area in each county

Pasture_perc a numeric vector, percentage of pasture of total area in each county

Cultivated_Crops_perc a numeric vector, percentage of cultivated crops of total area in each county

pop_density a numeric vector, average population density in each county

summer_tmmx a numeric vector, average temperature in summer

winter_tmmx a numeric vector, average temperature in winter

summer_rmax a numeric vector, average humidity in summer

winter_rmax a numeric vector, average humidity in winter

Author(s)

Chao Li <chaoli0394@gmail.com> Shunsuke Managi <managi.s@gmail.com>

Examples

```
## Not run:  
data(TransAirPolCalif)  
head(TransAirPolCalif)
```

```
## End(Not run)
```

Index

- * **datasets**

- California, [4](#)

- TransAirPolCalif, [13](#)

- * **package**

- GWPR.light-package, [2](#)

bw.GWPR, [3](#)

California, [4](#)

GWPR, [5](#)

GWPR.light (GWPR.light-package), [2](#)

GWPR.light-package, [2](#)

GWPR.moran.test, [7](#)

GWPR.pFtest, [8](#)

GWPR.phtest, [10](#)

GWPR.plmtest, [11](#)

TransAirPolCalif, [13](#)