

Package ‘zeitgebr’

July 29, 2018

Title Analysis of Circadian Behaviours

Date 2018-06-23

Version 0.3.3

Description Use behavioural variables to compute period, rhythmicity and other circadian parameters. Methods include computation of chi square periodograms (Sokolove and Bushell (1978) <DOI:10.1016/0022-5193(78)90022-X>), Lomb-Scargle periodograms (Lomb (1976) <DOI:10.1007/BF00648343>, Scargle (1982) <DOI:10.1086/160554>, Ruf (1999) <DOI:10.1076/brhm.30.2.178.1422>), and autocorrelation-based periodograms.

Depends R (>= 3.00),
behavr

Imports data.table,
lomb,
pracma

Suggests testthat,
covr,
knitr,
ggetho,
damr

License GPL-3

Encoding UTF-8

LazyData true

URL <https://github.com/rethomics/zeitgebr>

BugReports <https://github.com/rethomics/zeitgebr/issues>

RoxygenNote 6.0.1

Roxygen list(markdown = TRUE)

R topics documented:

dams_sample	2
find_peaks	2

periodogram	3
periodogram_methods	5

Index	7
--------------	----------

dams_sample	<i>A behavr table with approximately ten days of DAM2 recording for 32 fruit flies. The first 10, the following 11 and the last 11 animals have long, short and wild type period, respectively (see meta(dams_sample)).</i>
-------------	---

Description

A behavr table with approximately ten days of DAM2 recording for 32 fruit flies. The first 10, the following 11 and the last 11 animals have long, short and wild type period, respectively (see meta(dams_sample)).

Usage

```
dams_sample
```

Format

An object of class behavr (inherits from data.table, data.frame) with 415040 rows and 3 columns.

Author(s)

Luis Garcia

References

Raw data stored at https://github.com/rethomics/zeitgebr/tree/master/raw_data

find_peaks	<i>Find peaks in a periodogram</i>
------------	------------------------------------

Description

This function locates the peaks in a pregenerated periodogram. Detection is based on [pracma::findpeaks](#). Only the significant (i.e. power > signif_threshold) peaks are extracted.

Usage

```
find_peaks(data, n_peaks = 3)
```

Arguments

`data` [behavr::behavr](#) table representing a periodogram, as returned by [periodogram](#)

`n_peaks` maximal numbers of peak to be detected

Value

[behavr::behavr](#) table that is data with an extra column `peak`. `peak` is filled with zeros except for rows match a peak. In which case, rows have an integer value corresponding to the rank of the peak (e.g. 1 for the first peak).

References

- [zeitgebr tutorial](#) – the relevant rehtomics tutorial

See Also

- [periodogram](#) – to generate a periodogram in a first place
- [ggetho::geom_peak](#) – a layer to show peaks on a periodogram

Examples

```
data(dams_sample)
# only a half of the individuals for the sake of the example
dt <- dams_sample[xmv(region_id) %in% (1:16 * 2)]
per_dt_xs <- periodogram(activity, dt, FUN = chi_sq_periodogram)
per_dt_xs_with_peaks <- find_peaks(per_dt_xs)
per_dt_xs_with_peaks[peak == 1]
```

periodogram	<i>Computes periodograms</i>
-------------	------------------------------

Description

This function builds periodograms, with one of several methods, for each individual of a [behavr](#) table

Usage

```
periodogram(var, data, period_range = c(hours(16), hours(32)),
  resample_rate = 1/mins(15), alpha = 0.01, FUN = chi_sq_periodogram, ...)
```

Arguments

<code>var</code>	variable to analyse
<code>data</code>	behavr table
<code>period_range</code>	vector of size 2 defining minimal and maximal range of period to study (in seconds)
<code>resample_rate</code>	frequency to resample (up or down) the data at (in hertz)
<code>alpha</code>	significance level
<code>FUN</code>	function used to compute periodogram (see periodogram_methods)
<code>...</code>	additional arguments to be passed to FUN

Value

A [behavr::behavr](#) table. In addition to the metadata, it contains data that encodes a periodogram (i.e. power vs period). The data contains the columns:

- `power` – the power the or equivalent (according to FUN)
- `period` – the period at which power is computed (in seconds)
- `p_value` – the p value associated to the power estimation
- `signif_threshold` – the threshold above which power is considered significant

References

- [zeitgebr tutorial](#) – the relevant rehtomics tutorial

See Also

- [periodogram_methods](#) – the list of built-in methods
- [find_peaks](#) – to find peaks in the periodogram
- [ggetho::ggperio](#) – to plot periodograms

Examples

```
data(dams_sample)
# only a half of the individuals for the sake of the example
dt <- dams_sample[xmv(region_id) %in% (1:16 * 2)]
pdt <- periodogram(activity, dt, FUN = ls_periodogram, oversampling = 4)
pdt <- periodogram(activity, dt, FUN = chi_sq_periodogram)

require(ggetho)
ggperio(pdt, aes(colour=period_group)) + stat_pop_etho()
```

Description

These functions provides a series of methods to assess periodicity of circadian processes.

Usage

```
ac_periodogram(x, period_range = c(hours(16), hours(32)),
  sampling_rate = 1/mins(1), alpha = 0.05)

chi_sq_periodogram(x, period_range = c(hours(16), hours(32)),
  sampling_rate = 1/mins(1), alpha = 0.05, time_resolution = hours(0.1))

fourier_periodogram(x, period_range = c(hours(16), hours(32)),
  sampling_rate = 1/mins(1), alpha = 0.05)

ls_periodogram(x, period_range = c(hours(16), hours(32)),
  sampling_rate = 1/mins(1), alpha = 0.05, oversampling = 8)
```

Arguments

x	numeric vector
period_range	vector of size 2 defining minimal and maximal range of period to study (in seconds)
sampling_rate	the – implicitly regular – sampling rate of x (in hertz)
alpha	significance level
time_resolution	the resolution of periods to scan
oversampling	the oversampling factor (see lomb::lsp)

Value

a [data.table](#) with the columns:

- period – the period (in s)
- power – the power (or equivalent) for a given period
- p_value – the significance of the power
- signif_threshold – the significance threshold of the power (at alpha)

References

- [zeitgeber tutorial](#) – the relevant rehtomics tutorial

See Also

- [lomb::lsp](#) – the original function for `ls_periodogram`
- [xsp::chiSqPeriodogram](#) – code modified from
- [stats::acf](#) – the original function for `ac_periodogram`

Index

*Topic **datasets**

- dams_sample, [2](#)
- ac_periodogram (periodogram_methods), [5](#)
- behavr, [3](#), [4](#)
- behavr::behavr, [3](#), [4](#)
- chi_sq_periodogram
(periodogram_methods), [5](#)
- dams_sample, [2](#)
- data.table, [5](#)
- find_peaks, [2](#), [4](#)
- fourier_periodogram
(periodogram_methods), [5](#)
- ggetho::geom_peak, [3](#)
- ggetho::ggperio, [4](#)
- lomb::lsp, [5](#), [6](#)
- ls_periodogram (periodogram_methods), [5](#)
- periodogram, [3](#), [3](#)
- periodogram_methods, [4](#), [5](#)
- pracma::findpeaks, [2](#)
- stats::acf, [6](#)
- xsp::chiSqPeriodogram, [6](#)