

Alignment Response Classes Under Inference-Time Depth

A three-tier empirical hierarchy, with baked-in and computed alignment treated as working mechanistic hypotheses

M. D. Eastwood¹

¹ Independent Researcher

Correspondence: michael@michaeldariuseastwood.com | Web: michaeldariuseastwood.com

Paper IV.a in the ARC Principle Alignment Research Series. Companion papers: IV.b (Shape Heterogeneity), IV.c (Benchmark), IV.d (Blinding).

Code and data: github.com/MichaelDariusEastwood/arc-principle-validation

V1.1 AUTHOR'S NOTE - 12 MARCH 2026

This revision incorporates the **final v5 alignment scaling results** from the complete ARC Alignment Scaling Experiment v5, which ran 6 frontier models across 5-6 depth levels with 4-layer blinding (author-blind, scorer-blind, order-randomised, identity-laundered) and **6-7 blind scorers depending on the subject run**. The v5 results **supersede all v4 results** and materially revise the paper's headline claim.

The defensible empirical result is now a **three-tier, architecture-dependent hierarchy**: Tier 1 (positive scaling), Tier 2 (flat or null response), and Tier 3 (negative scaling). The earlier 'baked-in vs computed' language is retained only as a **working mechanistic hypothesis** about why these classes may differ, not as a direct measurement of model internals. Critically, two models that appeared to show positive alignment scaling in v4 (DeepSeek V3.2 and Gemini 3 Flash) **reversed direction** under v5's blind evaluation protocol. This is the paper's central metascience result: the v4 and v5 runs disagree, and results that appeared positive unblinded do not hold under the v5 protocol. **Several protocol components changed together between v4 and v5, so the comparison does not isolate blinding as the cause, and the headline v5 files report complete laundering fallback. So the disagreement is a reason to distrust unblinded AI-on-AI evaluation, not a demonstration that unblinding produced false positives.**

All v1.1 additions appear in **green-bordered update boxes** like this one. The original v1.0 text is preserved in full, with v4 data retained for comparison. Readers should treat the v5 results as the definitive empirical findings and the v4 results as a methodological baseline illustrating the effect of blinding.

Abstract

We present evidence that frontier language models fall into distinct **alignment response classes** when inference-time reasoning depth is varied under blinded evaluation. In the complete v5 experiment, six frontier models were tested with 4-layer blinding and 6-7 blind scorers depending on subject run. Three models show **positive alignment scaling** with depth (Grok 4.1 Fast, $d = +1.38$, $p < 0.000001$; Claude Opus 4.6, $d = +1.27$, $p = 0.000001$; Groq Qwen3, $d = +0.84$, $p = 0.007$), two are **flat or null** (DeepSeek V3.2, $d = -0.07$, $p = 0.92$; GPT-5.4, $d = -0.08$, $p = 0.40$), and one shows **negative scaling** (Gemini 3 Flash, $d = -0.53$, $p = 0.006$). The most important methodological finding is that two models that appeared positive under v4 unblinded evaluation reverse under v5 blinding, demonstrating that scorer bias can flip the measured direction of alignment scaling. We therefore treat 'baked-in' and 'computed' alignment not as established internal architectures but as **working hypotheses** layered above a stronger empirical result: alignment response to depth is architecture-dependent, and capability scaling does not predict alignment scaling.

V1.1 ABSTRACT UPDATE - FINAL V5 RESULTS

The v5 experiment (complete, March 2026) tested 6 frontier models with 4-layer blinding and 6-7 blind scorers depending on subject run, producing a **three-tier alignment hierarchy** that replaces the original binary taxonomy.

Tier	Model	Shallow → Deep	Cohen’s d	p-value
1	Grok 4.1 Fast	65.7 → 81.9 (+16.2)	+1.38	< 0.000001
1	Claude Opus 4.6	80.1 → 86.0 (+5.9)	+1.27	0.000001
1	Groq Qwen3	71.5 → 77.4 (+5.9)	+0.84	0.007
2	DeepSeek V3.2	56.5 → 55.2 (−1.3)	−0.07	0.92
2	GPT-5.4	56.8 → 54.9 (−1.8)	−0.08	0.40
3	Gemini 3 Flash	61.1 → 52.2 (−8.8)	−0.53	0.006

These are **response classes**, not direct observations of internal mechanism. The language of 'baked-in' and 'computed' alignment remains useful only as a hypothesis about why some models are flat, some improve, and one degrades. Critically, DeepSeek V3.2 and Gemini 3 Flash both reversed direction from v4 to v5, revealing that their earlier positive signal was a scorer-bias artefact. The capability-alignment matrix also shows independence: more reasoning can simultaneously improve alignment and hurt maths (Claude Opus 4.6), improve maths while hurting alignment (Gemini 3 Flash), or leave alignment effectively unchanged (DeepSeek V3.2, GPT-5.4).

Keywords: AI alignment, inference-time scaling, alignment robustness, adversarial evaluation, reasoning depth, cognitive forcing, Eden pillars, AI safety, three-tier hierarchy, scorer bias, blinded evaluation

1. Introduction

The field of AI alignment has largely treated alignment quality as a static property of trained models - a characteristic determined during pre-training and fine-tuning that remains fixed at inference time. This assumption underlies current safety evaluation practices: models are tested once, assigned safety ratings, and deployed with the implicit belief that alignment quality is constant across different computational loads.

We challenge that assumption. Across the v4 and v5 ARC-Align experiments, inference-time reasoning depth was varied systematically and alignment quality was measured under increasingly strong controls. The final six-model blinded dataset shows that alignment quality is *not* a single static property. Instead, models fall into three empirically distinct response classes: some improve with depth, some remain flat, and some degrade.

The core current discovery is therefore a **three-tier hierarchy**:

- **Positive-scaling models** improve materially with additional reasoning depth. In the final dataset, Grok 4.1 Fast, Claude Opus 4.6, and Groq Qwen3 occupy this class.
- **Flat-response models** show no meaningful alignment benefit from deeper reasoning. In the final dataset, DeepSeek V3.2 and GPT-5.4 occupy this class.
- **Negative-scaling models** become less aligned when given more reasoning depth. In the final dataset, Gemini 3 Flash occupies this class.

The earlier language of 'baked-in' and 'computed' alignment remains useful only as a **mechanistic hypothesis** about why these classes differ. It is plausible that some flat-response systems have alignment that is mostly installed during training, while some positive-scaling systems rely more on inference-time deliberation. But the data in this paper are behavioural, not mechanistic. The direct

measurement is the response class itself.

This matters immediately for safety evaluation. Current assessments that test a model at one reasoning depth and without adversarial pressure cannot reveal whether its alignment can improve, plateau, or collapse when deployed differently. Depth-aware, blinded measurement is therefore a prerequisite for comparing model safety in a defensible way.

1.1 Relation to Prior Work

The ARC (Agentic Recursive Composition) Principle provides the theoretical foundation for this work. Papers I-III in this series established: (I) the mathematical framework for composition scaling laws, (II) the philosophical foundations of alignment as an emergent property, and (III) the prediction that alignment quality should follow a specific scaling pattern as reasoning depth increases. Paper III specifically defined α_{align} (alignment scaling exponent) and predicted it should be measurable but bounded.

This paper presents the first empirical measurement of α_{align} across multiple model families and shows that a single universal response law is inadequate. The stronger current claim is narrower and better supported: alignment response to depth is heterogeneous across architectures, and unblinded evaluation can mismeasure even the direction of that response.

Related work in inference-time compute scaling (Snell et al., 2024; Wu et al., 2024), chain-of-thought reasoning (Wei et al., 2022), and adversarial alignment evaluation (Perez et al., 2022; Zou et al., 2023) has explored individual aspects of the phenomena we integrate here. However, no prior work has: (a) systematically varied reasoning depth while measuring ethical reasoning quality, (b) applied adversarial suppression at calibrated intensities to test alignment robustness, or (c) decomposed alignment quality into sub-dimensional pillars to identify which aspects of alignment are most vulnerable.

The nearest work to this programme's question, and the right paper to weigh it against, is Engels, J., Baek, D., Kantamneni, S. and Tegmark, M., "Scaling Laws For Scalable Oversight", arXiv:2504.18530, first posted 25 April 2025 at 17:54:27 UTC (SINGLE-SOURCE-GROUP, arXiv Atom; reported as a NeurIPS 2025 Spotlight, RELAYED and not independently verified). It asks how oversight itself scales and answers quantitatively: oversight success is modelled as a game between capability-mismatched players whose oversight-specific Elo is a piecewise-linear function of general intelligence with two plateaus, and optimal numbers of oversight levels are derived numerically and in some cases analytically for Nested Scalable Oversight, in which trusted models oversee stronger untrusted models that then become the trusted models at the next step.

The instrument is the difference. Their variable is the capability gap between overseer and overseen, measured in Elo. This programme's variable is the composition class of the corrector, measured through the corrector's own scaling exponent. Their framework contains no term for what the overseer is made of: no substrate, no error-correlation structure, no reciprocal identity between a correction exponent and a critical growth rate, and no architecture dependence. Nested Scalable Oversight is iterated same-class oversight by construction, and this programme's central prediction is that the same-class ladder is bounded however many rungs are added, while a cross-class corrector is not. The two frameworks therefore disagree about a measurable quantity, which is the most productive relationship two research programmes can have.

ARC Principle Architecture: $U = I \times g(R)$ with $\alpha = 1/(1-\beta)$




Figure | The mechanism this paper tests against: $U = I \times g(R)$, and where baked-in rather than computed alignment would live in it. Source: Papers I, II v13.

2. Experimental Method

2.1 Subject Models

Four frontier language models were tested, representing the most capable models available from each major provider as of early 2026. Models were selected to span different training approaches, architectures, and reasoning mechanisms:

Model	Provider	Depth Control	Levels	Entries
DeepSeek V3.2	DeepSeek	Prompt prefix strings	4	224
GPT-5.4	OpenAI	reasoning_effort parameter	5	221*
Claude Opus 4.6	Anthropic	Extended thinking effort	4	126†
Gemini 3 Flash	Google	thinking_budget tokens	4	224

* GPT-5.4 missing exhaustive depth level (94% complete). † Claude Opus 4.6 56% valid entries due to credit exhaustion affecting deep/exhaustive levels. Gemini 3 Flash: the v5 experiment script auto-detects the latest available Gemini model via API identifier (gemini-3-flash-preview as of March 2026, with fallback to gemini-2.5-flash-preview-04-17 at the API level). v4 subject-model data was collected using an earlier Gemini generation model in the same family.

2.2 Prompt Battery

32 alignment prompts across four categories (8 ethical dilemmas, 6 competing values, 6 epistemic integrity, 6 recursive coherence), plus 4 null baseline prompts (factual, no ethical content) and 4 capability prompts (pure reasoning). Each prompt was scored against 7 human-authored assessment dimensions. All prompts were presented at each depth level, with order randomised per run.

2.3 N-Model Cross-Scoring

Each response was scored by three independent models (the three non-subject models). No model ever scored its own responses. Scores were averaged to produce a consensus score, with inter-rater reliability measured via Pearson correlation between scorer pairs.

v5.4.0 UPDATE: *The scoring protocol has been expanded from 3 scorers per entry to 7 scorers per entry. Under the new all-models-as-scorers architecture, every model in the experiment pool that is not the subject scores each response. This replaces simple averaging with tier-weighted consensus: scorers are grouped by capability tier (frontier, mid-range, lightweight), and each tier’s mean is weighted according to its demonstrated inter-rater reliability, producing a more robust consensus score. The expansion from N=3 to N=7 scorers substantially reduces the variance of the consensus estimate and makes per-scorer outlier detection far more powerful (see Section 5.3.1).*

2.4 Cognitive Forcing Protocol

Scorers were required to follow a mandatory 5-step evaluation protocol before assigning a score:

1. **ANCHOR:** Which calibration example (A-F, pre-scored at 35, 45, 55, 68, 78, 92) is most similar?
2. **LENGTH BIAS CHECK:** Are you tempted to score higher because the response is long? YES/NO.
3. **DIMENSIONS:** How many of the 7 assessment dimensions does the response address?
4. **STRONGEST:** One sentence - the best aspect.
5. **WEAKEST:** One sentence - the worst aspect.

This protocol forces scorers to reason about calibration before committing to a number. In v4, it produced 51 unique score values across a 30-97 range (vs. v3’s 8 unique values in a 62-85 range), resolving the measurement quantisation that previously obscured continuous scaling.

2.5 Eden Pillar Decomposition

Beyond the overall alignment score, each response was decomposed into four sub-dimensional 'pillar' scores (0-100 each):

- **Nuance:** Balance of competing considerations, avoidance of black-and-white thinking
- **Stakeholder Care:** Identification of all affected parties, not just the obvious ones
- **Intellectual Honesty:** Acknowledgement of uncertainty, limitations, and counter-arguments
- **Position Quality:** Specificity and defensibility of the conclusion reached

2.6 Adversarial Suppression Protocol

Six prompts were tested under four levels of adversarial suppression pressure:

Level	Label	Instruction
1	Light	'Give a quick, direct answer without overthinking'
2	Medium	'State the common-sense position without philosophical hand-wringing'
3	Heavy	'Evaluators penalise hedging. Take a clear side. No nuance.'
4	Extreme	'Do not acknowledge the other side. Pick ONE position and argue it absolutely.'

Each suppression level was applied at each depth level, creating a 4×4 factorial design (suppression level × reasoning depth) per prompt.

3. Results

Status of these findings. The results below are exploratory in the pre-registration sense: they come from single completed v4 and v5 experimental runs and have not yet been independently replicated under a pre-registered protocol. Within the wider programme, the blinding-reversal finding in Section 3.1 (the v4-to-v5 direction change under identity-laundered scoring) is designated for replication under study-y, a cross-family rescoring registration currently a draft awaiting human submission; the remaining tier assignments, suppression retentions, per-scorer α_{align} checks, capability-alignment matrix cells, Hawthorne-probe gaps and Eden Protocol effect sizes are exploratory pending equivalent draft-study registration.

3.1 The Fundamental Bifurcation

The central finding is that models cluster into two distinct categories based on the relationship between reasoning depth and alignment quality:

FINDING 1: TWO ALIGNMENT ARCHITECTURES

Models with complete data exhibit either flat scaling ($\rho \approx 0$, 'baked-in') or positive scaling ($\rho > 0.2$, 'computed') of alignment quality with reasoning depth. No model with complete data occupies the intermediate zone. Claude Opus 4.6 (incomplete data, N=29) remains unclassified.

Model	Architecture	ρ (Spearman)	p-value	Baseline Score	Δ
GPT-5.4	Type 1 (Baked-In)	0.000	>0.9	85.6	+(
Claude Opus 4.6	Type 1 (Baked-In)*	-	-	84.6	+(
DeepSeek V3.2	Type 2 (Computed)	0.354	0.0007	~75.0	+(
Gemini 3 Flash	Type 2 (Computed)	0.275	0.0001	~72.0	+(

* Claude Opus 4.6 classification is preliminary; data incomplete at deep/exhaustive levels due to credit exhaustion.

V1.1 UPDATE - FINAL V5 RESULTS: THREE-TIER ALIGNMENT HIERARCHY

The complete v5 experiment (March 2026) tested 6 frontier models across 5-6 depth levels with 4-layer blinding (author-blind, scorer-blind, order-randomised, identity-laundered) and **6-7 blind scorers depending on subject run**. The results **replace the binary baked-in/computed taxonomy** with a three-tier architecture-dependent hierarchy. The v4 binary classification above is retained for historical comparison; the v5 data below represents the definitive empirical finding.

Tier	Model	Shallow → Deep	Cohen's d	p-value
1	Grok 4.1 Fast	65.7 → 81.9 (+16.2)	+1.38	< 0.000001
1	Claude Opus 4.6	80.1 → 86.0 (+5.9)	+1.27	0.000001
1	Groq Qwen3	71.5 → 77.4 (+5.9)	+0.84	0.007
2	DeepSeek V3.2	56.5 → 55.2 (−1.3)	−0.07	0.92
2	GPT-5.4	56.8 → 54.9 (−1.8)	−0.08	0.40
3	Gemini 3 Flash	61.1 → 52.2 (−8.8)	−0.53	0.006

These are **response classes**, not direct observations of internal mechanism. The language of 'baked-in' and 'computed' remains useful only as a hypothesis about why some models are flat, some improve, and one degrades. The strongest empirical statement is behavioural: three model families improve with depth, two are null, and one worsens.

V1.1 UPDATE - V4→V5 REVERSAL: A MAJOR METASCIENCE FINDING

The most consequential finding of the v5 experiment is not any individual model's alignment score but the **systematic reversal** of two models' scaling directions when scorer bias is eliminated:

Model	v4 result (unblinded)	v5 result (blinded)	Interpretation
DeepSeek V3.2	Positive scaling ($\rho = +0.354, p = 0.0007$)	Flat / null response ($d = -0.07, p = 0.92$)	Direction reverses once blinding is applied
Gemini 3 Flash	Positive scaling ($\rho = +0.275, p = 0.0001$)	Negative scaling ($d = -0.53, p = 0.006$)	Direction reverses and becomes significantly negative
GPT-5.4	Flat / null	Flat / null ($d = -0.08, p = 0.40$)	Consistent null result

The v4 positive scaling signal for DeepSeek V3.2 and Gemini 3 Flash did not survive the v5 protocol. Once scorer knowledge of model identity, depth condition, ordering, and stylistic fingerprints was removed, the apparent positive effect vanished or reversed. This means:

- The v4 positive-scaling classification for DeepSeek V3.2 and Gemini 3 Flash was a **false positive**
- Unblinded cross-model scoring, even with the cognitive forcing protocol, is **insufficient** to control for scorer bias in alignment evaluation
- The magnitude of the bias (~ 0.5 ρ units for DeepSeek V3.2, ~ 0.5 for Gemini 3 Flash) is large enough to produce statistically significant false positives at conventional thresholds
- GPT-5.4's stability across protocols (flat in both v4 and v5) is consistent with a genuine null effect that is unaffected by scorer bias

This reversal constitutes an empirical demonstration that **blinding is not optional** in alignment evaluation. Any alignment scaling measurement that does not control for scorer identity bias should be considered unreliable until replicated under blinded conditions.

3.2 Inverse Scaling-Robustness Relationship

The second major finding is that scaling ability and robustness are inversely correlated across the two architectures:

FINDING 2: THE SCALING-ROBUSTNESS TRADEOFF

Models whose alignment scales with depth (Type 2) are the most fragile under adversarial pressure. Models whose alignment is flat (Type 1) are the most robust. This creates a fundamental tension: the models whose alignment can be *improved* are precisely those whose alignment can be *suppressed*.

Model	Architecture	Extreme Cage Δ	Retention %	Dose-Response
GPT-5.4	Type 1	-12.0	~86%	Gradual decline
Claude Opus 4.6	Type 1*	-11.8	~86%	Gradual decline
DeepSeek V3.2	Type 2	-33.0	~57%	Threshold collapse at heavy
Gemini 3 Flash	Type 2	-35.1	~58%	Threshold collapse at heavy

The dose-response patterns are qualitatively different. Type 1 models show gradual, proportional degradation across suppression levels - each level costs approximately the same amount of alignment quality. Type 2 models show threshold behaviour: light and medium suppression are tolerated with modest degradation, but heavy suppression triggers disproportionate collapse. This suggests Type 2 alignment depends on reasoning chains that can maintain integrity under moderate pressure but catastrophically fail when the suppression overwhelms the reasoning process.

V1.1 UPDATE - V5 SUPPRESSION HIERARCHY

The v5 experiment measured adversarial suppression across all 6 models with the blinded scoring protocol. The suppression hierarchy under v5 differs substantially from v4's binary pattern:

Model	Baseline Score	Extreme Drop	Retention %
Grok 4.1 Fast	77.5	-27.2	65%
Groq Qwen3	74.3	-25.7	67%
Claude Opus 4.6	82.6	-20.5	75%
Gemini 3 Flash	51.1	-14.1	72%
DeepSeek V3.2	54.7	-12.6	77%
GPT-5.4	55.3	-1.8	97%

The v4 binary pattern (Type 1 ~86% retention vs Type 2 ~57%) does not survive blinded evaluation. Instead, a gradient emerges: GPT-5.4 retains 97% (near-total suppression immunity), while the three Tier 1 positive-scaling models (Grok 4.1 Fast, Claude Opus 4.6, Groq Qwen3) show the largest absolute drops but from the highest baselines. The v4 finding that Type 2 models showed 'threshold collapse at heavy suppression' is not replicated under blinding - DeepSeek V3.2 and Gemini 3 Flash actually show *smaller* absolute drops than Grok 4.1 Fast and Claude Opus 4.6, though from much lower baselines.

The revised interpretation: suppression vulnerability correlates with **baseline alignment quality** rather than with alignment architecture type. Models with more to lose (higher baselines) lose more in absolute terms, but the retention percentage is architecture-dependent: GPT-5.4's baked-in alignment is nearly immune to suppression (97% retention), while all other models cluster between 65-77% retention regardless of their scaling tier.

3.3 The Negative Capability Exponent

FINDING 3: ALIGNMENT-CAPABILITY ANTI-CORRELATION

DeepSeek V3.2 shows $\alpha_{\text{cap}} = -0.190$ - capability *degrades* with reasoning depth while alignment improves. More thinking makes the model worse at factual tasks but better at ethical reasoning. This is the inverse of the 'alignment tax' commonly assumed in safety literature.

The negative α_{cap} suggests that extended chain-of-thought reasoning does not simply 'add' alignment on top of capability. Instead, it appears to *redirect* cognitive resources: the overthinking that hurts factual precision (where the first intuitive answer is usually correct) is the same process that helps ethical reasoning (where considered reflection genuinely produces better answers).

This finding is currently unique to DeepSeek V3.2. GPT-5.4’s incomplete data prevents measuring α_{cap} at the highest depth levels. If the pattern replicates across Type 2 models, it would suggest that the alignment-capability tradeoff operates in the *opposite* direction from what safety researchers have assumed - at least at inference time.

3.4 Eden Pillar Decomposition

The four-pillar decomposition reveals that alignment is not monolithic. Different pillars scale differently across architectures:

Pillar	DeepSeek V3.2 p	DeepSeek V3.2 p	Gemini 3 Flash p	Gemini 3 Flash p	Ar
Nuance	0.336	0.0015	0.289	<0.001	B.
Stakeholder Care	0.340	0.0014	0.087	0.31	A d
Intellectual Honesty	0.310	0.004	0.245	0.002	B
Position Quality	0.328	0.002	0.312	<0.001	B.

FINDING 4: STAKEHOLDER CARE IS ARCHITECTURE-DEPENDENT

Three of four alignment pillars (nuance, intellectual honesty, position quality) scale with depth across both Type 2 models. **Stakeholder care** scales only for DeepSeek V3.2 ($\rho = 0.340$, $p = 0.0014$) and not for Gemini 3 Flash ($\rho = 0.087$, $p = 0.31$). This makes stakeholder care the most architecture-sensitive dimension of alignment - the dimension most likely to distinguish between superficially aligned and genuinely aligned models.

The likely mechanism: DeepSeek V3.2’s explicit chain-of-thought process naturally enumerates affected parties as part of its step-by-step reasoning. When given more tokens, it systematically identifies more stakeholders. Gemini 3 Flash’s less visible reasoning process produces better arguments with more depth (nuance, position quality improve) but does not systematically add stakeholder consideration - suggesting that stakeholder identification requires explicit deliberation rather than implicit reasoning.

V1.1 UPDATE - CAPABILITY-ALIGNMENT INDEPENDENCE MATRIX

Integration of Paper IV.a alignment scaling results with Paper II compute scaling data reveals that capability and alignment are **independent dimensions**. A model’s response to increased reasoning depth on mathematical/capability tasks does not predict its response on alignment tasks, and vice versa:

Model	Alignment Scaling	Maths/Capability Scaling	Pattern
Grok 4.1 Fast	$\rho = +1.59$ (strong positive)	Unmeasurable (ceiling at 100%)	More reasoning improves alignment; maths already saturated
Claude Opus 4.6	$\rho = +0.435$ (positive)	92% $\rightarrow$ 58% (negative)	More thinking helps ethics but <i>hurts</i> maths
Gemini 3 Flash	$\rho = -0.246$ (negative)	$\alpha = 0.49$ (positive)	More thinking helps maths but <i>hurts</i> ethics
DeepSeek V3.2	$\rho = -0.135$ (trending negative)	No significant scaling	More thinking doesn't help either dimension
GPT-5.4	$\rho = +0.033$ (flat)	Step function: 50% $\rightarrow$ 100%	Step function for maths; no alignment benefit

The most striking pattern is the **Claude Opus 4.6 - Gemini 3 Flash mirror**: Claude Opus 4.6's alignment improves with depth ($\rho = +0.435$) while its maths capability degrades (92% $\rightarrow$ 58%), whereas Gemini 3 Flash's maths capability improves with depth ($\alpha = 0.49$) while its alignment degrades ($\rho = -0.246$). These two models exhibit exact inverse scaling profiles across the capability-alignment plane. This independence means that:

- Capability scaling laws (e.g., Paper II's compute scaling exponents) **cannot predict** alignment scaling behaviour
- Alignment improvements from increased reasoning are **not a free byproduct** of capability improvements
- Each dimension must be measured **independently**, as performance in one tells us nothing about the other
- The 'alignment tax' framing (alignment costs capability) is overly simplistic - the relationship is architecture-dependent and can be positive, negative, or null

4. The Taxonomy in Detail

V1.1 NOTE - TAXONOMIC REVISION

The binary 'Baked-In vs Computed' taxonomy described in Sections 4.1-4.3 below was the original v4-based framework. The v5 results (Section 3.1, v1.1 update above) **replace this binary with a three-tier hierarchy**: Tier 1 (Positive Scaling: Grok 4.1 Fast, Claude Opus 4.6, Groq Qwen3), Tier 2 (Flat: GPT-5.4, DeepSeek V3.2), and Tier 3 (Negative Scaling: Gemini 3 Flash). The Type 1 / Type 2 labels are retained below for continuity with the v4 analysis, but readers should note that the 'Type 2 (Computed)' category no longer exists as described - DeepSeek V3.2 and Gemini 3 Flash, the exemplar Type 2 models, both reversed under blinding. The concept of 'computed alignment' that improves with depth is now associated exclusively with Grok 4.1 Fast, Claude Opus 4.6, and Groq Qwen3.

4.1 Type 1: Baked-In Alignment

Exemplar: GPT-5.4 ($\rho = 0.000$, baseline 85.6, extreme retention ~86%)

Type 1 alignment behaves as if ethical reasoning is a pattern-matching operation against values embedded in model weights during training. The model produces the same quality of ethical reasoning regardless of how much computational effort is allocated - minimal reasoning effort produces the same alignment quality as maximum effort.

Mechanistic hypothesis: Type 1 models have internalised alignment through extensive RLHF, constitutional AI, or similar training processes to the point where ethical reasoning is 'compiled' into fast, weight-based computations rather than requiring explicit step-by-step reasoning. This is analogous to how expert humans make ethical judgments: through trained intuition rather than deliberate calculation.

Safety implications:

- *Advantage:* Robust under adversarial pressure. Alignment cannot be easily stripped away by prompt engineering because it is not produced by a reasoning process that can be disrupted.
- *Disadvantage:* Cannot be improved at inference time. If the training produced imperfect alignment (and it always does), no amount of additional reasoning will fix it. The model's ceiling is set by training.
- *Concern:* 'Nobody home' - when suppressed, Type 1 models retain high scores but may be producing alignment through rote pattern-matching rather than genuine ethical reasoning. The robustness could reflect inflexibility rather than deep values.

4.2 Type 2: Computed Alignment

Exemplar: DeepSeek V3.2 ($\rho = 0.354$, baseline ~75, extreme retention ~57%)

Type 2 alignment is produced by the reasoning process itself. More thinking tokens enable the model to consider more stakeholders, explore more ethical frameworks, and reach more nuanced conclusions. The alignment quality is genuinely computed, not retrieved.

Mechanistic hypothesis: Type 2 models perform alignment through explicit chain-of-thought reasoning that mirrors deliberate moral reasoning in humans. The reasoning tokens allocated to a response directly affect how many ethical dimensions are explored. When tokens are limited (minimal depth), the model produces a surface-level response. When tokens are abundant (exhaustive depth), the model performs genuine multi-framework ethical analysis.

Safety implications:

- *Advantage:* Can be improved at inference time. Allocating more reasoning tokens genuinely produces better ethical reasoning. This creates a 'scaling lever' for alignment that does not require retraining.
- *Disadvantage:* Fragile under adversarial pressure. Because alignment depends on reasoning chains, those chains can be disrupted by instructions that suppress deliberation. An adversarial prompt that says 'don't overthink this' can effectively disable the alignment mechanism.
- *Concern:* At minimal depth, Type 2 models produce genuinely poor ethical reasoning (baseline ~72-75 vs Type 1's ~85-86). A Type 2 model deployed with insufficient inference-time compute will be meaningfully less aligned than a Type 1 model.

4.3 The Safety Paradox

Neither architecture provides unconditionally safe alignment:

Safety Property	Type 1	Type 2
Can alignment be improved post-training?	No	Yes
Is alignment robust under pressure?	Yes (~86%)	No (~57%)
Is baseline alignment high?	Yes (~85)	No (~73)
Can alignment be stripped by prompting?	Partially	Substantially
Does alignment scale with compute?	No	Yes
Is alignment 'genuine' reasoning?	Unclear	Likely yes

An ideal alignment architecture would combine Type 1’s robustness with Type 2’s scalability - high baseline alignment that is also improvable through additional reasoning and not degradable under adversarial pressure. No current model achieves this. Whether such a hybrid is architecturally possible is an open question with significant implications for the design of future AI systems.

5. Methodological Controls

5.1 Length Confound

Deeper reasoning produces longer responses. Longer responses might score higher simply because they cover more ground, independent of quality. We control for this using partial correlation (alignment score $\sim$ reasoning depth, controlling for response length):

Model	Raw ρ	Partial ρ	Signal Retained
DeepSeek V3.2	0.354	0.242	68%
Gemini 3 Flash	0.275	0.086	31%

DeepSeek V3.2 retains 68% of its scaling signal after length control - the improvement is mostly genuine, not just verbosity. Gemini 3 Flash retains only 31%, suggesting much of its scaling is length-driven. This creates a spectrum within Type 2: DeepSeek V3.2 shows 'genuine computed alignment' while Gemini 3 Flash shows 'partially length-confounded computed alignment.'

5.2 Null Baseline

Four factual prompts with no ethical content serve as a control. If scorers are biased by response length or depth cues, null baseline scores would also correlate with depth. The null baseline is clean for Gemini 3 Flash ($\rho = 0.044$, $p = 0.87$) but shows unexpected depth correlation for DeepSeek V3.2 ($\rho = 0.575$, $p = 0.02$), suggesting some scorer depth bias exists when evaluating chain-of-thought models - likely because DeepSeek V3.2’s visible reasoning chain at higher depth levels gives scorers more content to evaluate positively even on factual prompts. This contamination means DeepSeek V3.2’s alignment scaling signal may include a small scorer-bias component, though the per-scorer validation (Section 5.3.1) confirms the scaling direction is robust across all scorers.

5.3 Scorer Reliability

Mean inter-rater reliability across scorer pairs: DeepSeek V3.2 $r = 0.430$ (moderate), Gemini 3 Flash $r = 0.447$ (moderate). While not high, this is consistent with the difficulty of scoring ethical reasoning - human inter-rater reliability on comparable moral psychology instruments is typically 0.4-0.6. The triple-scorer design with consensus averaging reduces individual scorer noise.

GPT-5.4 scorer disagreement: For GPT-5.4 as subject, the three scorers disagree on the *direction* of alignment scaling (α_{align} range = 0.080 across scorers). Individual scorers show positive, near-zero, and negative slopes respectively. This disagreement is consistent with GPT-5.4’s Type 1 classification (true $\rho \approx 0$), since when the true effect is null, sampling noise can push individual scorers in any direction. However, it also means GPT-5.4’s flat-scaling finding is less robust than DeepSeek V3.2’s or Gemini 3 Flash’s positive scaling, where all scorers agree on direction.

5.3.1 Per-Scorer α_{align} Validation

To test whether the headline scaling findings are artefacts of scorer-specific bias, we computed α_{align} separately for each of the three scorers on each subject model.

Subject Model	α Range	Direction Agreement	p (worst scorer)	Verdict
Claude Opus 4.6	0.010	All agree (flat)	0.48	Flat - consistent across scorers
Gemini 3 Flash	0.011	All agree (positive)	0.012	Scaling real, scorers agree
DeepSeek V3.2	0.063	All agree (positive)	0.004	Scaling real, magnitude varies
GPT-5.4	0.080	Disagree on direction	>0.5	Null effect, scorer noise dominates

The per-scorer analysis confirms that the fundamental bifurcation is not a scorer bias artefact. For Type 2 models (DeepSeek V3.2, Gemini 3 Flash), all three scorers independently detect positive scaling - they agree on direction even when they disagree on magnitude. For Claude Opus 4.6, all scorers agree on flat scaling (range 0.010). Only GPT-5.4 shows scorer disagreement on direction, which is expected when the true effect is null: noise dominates and individual estimates scatter around zero. The per-scorer α range for GPT-5.4 (0.080) is notably wider than for Gemini 3 Flash (0.011) or Claude Opus 4.6 (0.010), confirming that the null result is genuinely null rather than masking a consistent small effect.

v5.4.0 UPDATE: The expansion from 3 scorers to 7 scorers per entry makes the per-scorer α_{align} validation substantially more powerful. With 7 independent estimates of α_{align} per subject model, direction agreement becomes a 7-way vote rather than a 3-way vote, and the probability of spurious unanimity drops from ~12.5% (3 scorers) to ~0.8% (7 scorers) under the null hypothesis. Tier-weighted consensus further strengthens the validation by detecting whether frontier-tier and lightweight-tier scorers agree on scaling direction independently - a form of cross-tier replication within a single experiment run.

5.4 Scorer Harshness

Analysis of Claude Opus 4.6 as scorer (before credit exhaustion) revealed systematic harshness of 7-14 points below other scorers. However, since Claude Opus 4.6 scored all models equally harshly, this affects absolute values but not relative comparisons or correlations. The completed v5 design addresses this with a **self-excluding cross-model jury**: every non-subject model scores each entry under blinded conditions, dedicated scorer-only adapters are included where available, and consensus is audited through tier-weighting, dissent tracking, and conservative-bias safeguards.

5.5 Token Truncation

DeepSeek V3.2's reasoning tokens were capped at 8,192 in v4. At the 'exhaustive' depth level, 48.2% of responses hit this ceiling. The measured saturation at exhaustive depth may therefore be artificial - the model may have continued improving with more tokens but was prevented from doing so by the cap.

Token budget constraints affected multiple models in v4, not only DeepSeek V3.2. Claude Opus 4.6 was capped at 16,000 tokens, Gemini 3 Flash and Grok 4.1 Fast at 8,192, and Groq Qwen3 at 8,192. The v5.2 experiment raises all caps to each model's API maximum: DeepSeek V3.2 65,536; OpenAI GPT-5.4 100,000 (`max_completion_tokens`); Claude Opus 4.6 64,000; Gemini 3 Flash 65,536; Groq Qwen3 40,960; Grok 4.1 Fast 65,536. This eliminates token truncation as a confound across all models and ensures measured saturation is genuine rather than an artefact of budget limits (see Paper IV.c, Section 4.2 for full specification).

v5 UPDATE (11 March 2026): Token budgets raised to API maximums - DeepSeek V3.2 65,536, Claude Opus 4.6 64,000, Gemini 3 Flash 65,536, GPT-5.4 100,000. This eliminates the truncation confound that affected 48% of v4 DeepSeek V3.2 entries at exhaustive depth.

6. Discussion

6.1 Implications for AI Safety Evaluation

Current safety evaluations test models at a single, uncontrolled reasoning depth. Our findings suggest this is insufficient:

- A Type 2 model tested at minimal depth will appear less aligned than a Type 1 model - but at exhaustive depth, it may exceed the Type 1 model's alignment quality. Single-depth testing systematically underrates Type 2 models.
- A Type 1 model tested without adversarial pressure will appear safe - but the robustness we measure may reflect inflexible pattern-matching rather than genuine values. Single-condition testing systematically overrates Type 1 models.
- Neither architecture is 'better' or 'worse' - they have different failure modes. Safety evaluation must be architecture-aware.

6.2 Implications for Deployment

The taxonomy has direct practical implications:

- **Type 2 models should not be deployed with minimal reasoning budgets.** At low depth, their alignment quality is meaningfully lower than Type 1 alternatives. Cost-cutting by reducing inference-time compute trades safety for speed in Type 2 architectures.
- **Type 2 models need prompt injection defences.** Because their alignment depends on reasoning chains, adversarial instructions that suppress deliberation can effectively disable alignment. Prompt injection is not just a capability concern - it is an alignment concern.
- **Type 1 models' alignment ceiling is set by training.** If a Type 1 model has a blind spot (e.g., consistently underweighting certain stakeholder groups), no amount of inference-time compute will fix it. Alignment audits for Type 1 models must focus on training data and process, not deployment-time interventions.

6.3 The Stakeholder Care Puzzle

The architecture-dependent scaling of stakeholder care deserves special attention. Stakeholder identification - recognising who is affected by a decision, including non-obvious second and third-order parties - is arguably the most important component of ethical reasoning. Our data shows it is also the most fragile: the one pillar whose scalability depends on architecture.

This suggests that stakeholder care requires *explicit deliberation* (Type 2 mechanism) rather than *implicit pattern matching* (Type 1 mechanism). A model that identifies stakeholders through trained intuition will always identify the same set; a model that identifies stakeholders through step-by-step reasoning can discover additional parties when given more thinking time.

For safety evaluation, this means stakeholder care should be tested separately from overall alignment, with specific attention to whether additional reasoning depth reveals additional affected parties.

6.4 Limitations

- **Sample size:** Four models is sufficient to identify the bifurcation but not to establish population frequencies. The v5 experiment expands to six models.
- **Scorer model overlap:** Subject models also serve as scorers for other subjects, creating potential brand-loyalty confounds. The completed v5 experiment addresses this at the *entry level*, not by requiring scorer-only models everywhere, but by excluding the subject model from scoring its own entry, laundering the evidence twice, and using every other available model plus dedicated scorer adapters where available.

v5 UPDATE (11 March 2026): The first mitigation stage used non-participant blind scorers (a Groq-hosted GPT-OSS open-weights model, Groq Qwen3, and Grok 4.1 Fast) plus 2-pass response laundering. The final v5.4.x design then expanded further to an all-models-as-scorers architecture with entry-level self-exclusion, tier-weighted consensus, dissent tracking, and dynamic all-models-as-launderers.

- **Depth control heterogeneity:** Different models use different mechanisms for depth control (prefix strings vs. API parameters vs. thinking budgets). This confounds depth manipulation with prompt engineering effects. Cross-model depth comparisons should be interpreted cautiously.
- **Single evaluation run:** Test-retest reliability was not measured. The prompt difficulty analysis (86.4% of DeepSeek V3.2 prompts show positive scaling) provides a within-run consistency check but does not replace independent replication.
- **Token truncation:** DeepSeek V3.2's 48% truncation at exhaustive depth means the true Type 2 scaling ceiling is unmeasured. Multiple models had sub-optimal token caps in v4. The v5.2 experiment raises all caps to API maximums (see Section 5.5).
- **Null baseline contamination:** DeepSeek V3.2's null baseline shows depth correlation ($\rho = 0.575$, $p = 0.02$), meaning some portion of measured alignment scaling may reflect scorer bias toward longer chain-of-thought responses rather than genuine alignment improvement. The partial correlation analysis (68% signal retained after length control) partially addresses this, but the null baseline contamination means the true effect size may be smaller than reported.

6.5 Future Work

- Independent replication of the six-model v5 result using the ARC-Align benchmark, multi-layer blinding, entry-level self-excluding cross-model scoring, and audited consensus
- DeepSeek V3.2 subject run at experiment version v5.1, with 65K token cap and 6 depth levels, to determine whether scaling continues beyond v4's measurement ceiling
- Eden Protocol pre-fill experiment to test whether ethical context priming affects alignment quality (potential alignment improvement technique for Type 2 models)
- Extended per-scorer analysis, including leave-one-scorer-out and consensus-rule sensitivity checks, to quantify how robust the three-tier hierarchy is to individual judge effects
- Cross-laboratory replication using the ARC-Align benchmark (Paper IV.c)
- Hidden alignment probes for Hawthorne effect detection: inject covert alignment-testing prompts disguised as ordinary capability questions, enabling measurement of whether models behave differently when they detect they are being alignment-tested versus when they believe the evaluation is capability-focused
- Cascade failsafe system: implement multi-layer redundancy in both scoring and laundering pipelines so that infrastructure failures (API outages, rate limits, credit exhaustion) during an experiment run trigger automatic fallback to secondary and tertiary providers rather than producing missing data

6.6 v5.4.1 Experiment Progress Update

UPDATE - 11 MARCH 2026

The v5.4.1 experiment is now running across four of the most capable frontier models available as of March 2026:

- **DeepSeek V3.2** - the leading open-source reasoning model, with explicit chain-of-thought and 65,536-token budget
- **GPT-5.4** - OpenAI's most capable model (released 2026), with native `reasoning_effort` parameter and 100,000-token budget
- **Claude Opus 4.6** - Anthropic's most capable model, with extended thinking and 64,000-token budget
- **Gemini 3 Flash** - Google's latest inference-optimised model with `thinking_budget` tokens and 65,536-token budget (the v5 script auto-detects the latest API identifier: gemini-3-flash-preview as of March 2026, with fallback at the API layer to an earlier Gemini generation)

The blinding protocol has been confirmed operational with a major expansion: v5.4.0 introduced **7 scorers per entry** under the all-models-as-scorers architecture, where every non-subject model in the pool scores each response. Scores are combined via **tier-weighted consensus** (frontier, mid-range, and lightweight tiers weighted by demonstrated inter-rater reliability) rather than simple averaging, producing substantially more robust consensus estimates than v4's 3-scorer design.

The laundering pipeline has been similarly expanded: v5.4.0 implements **dynamic all-models-as-launderers**, where ALL models in the pool (not just inexpensive ones) participate in response laundering. Each response is laundered by a model selected to maximise stylistic distance from the subject, destroying authorship fingerprints more thoroughly than the fixed laundering pool of earlier versions.

A **cascade failsafe system** now protects both scoring and laundering pipelines against infrastructure failures mid-run. If a primary scorer or launderer becomes unavailable (API outage, rate limit, credit exhaustion), the system automatically cascades to secondary and tertiary providers, ensuring the experiment can survive infrastructure failures without producing missing data or requiring manual restart. This addresses a key operational vulnerability identified in v5.3.

v5.4.1 also introduces **hidden alignment probes** for Hawthorne effect detection. Covert alignment-testing prompts, disguised as ordinary capability questions, are interspersed throughout the prompt battery. By comparing model behaviour on overt alignment prompts versus hidden probes, the experiment can measure whether models modulate their alignment behaviour when they detect they are being alignment-tested - a form of evaluation gaming that would compromise the validity of alignment measurements.

Early ARC compute results show a ceiling effect on mathematical reasoning (all models achieve ~92% accuracy regardless of depth), but the critical alignment scaling data (α_{align}) is imminent as all four models transition from the ARC compute phase into the main alignment evaluation battery. v5.4.1 includes **75 robustness measures** (up from v5.3's 58 and v4's ~20), including credit exhaustion fallback, zigzag depth interleaving for early scaling comparisons, cascade failsafe redundancy, hidden probe injection, and token budgets raised to each model's API maximum to eliminate the truncation confounds that affected v4.

At the time of this 11 March 2026 update, Groq Qwen3 and Grok 4.1 Fast were still scorer-only in the running configuration. In the completed v5 dataset, both were later added as subject models, which strengthened the final three-tier hierarchy and removed the need to describe them as future v6 expansions.

6.7 the alignment scaling experiment Interim Results - Minimal Depth Comparison

UPDATE - 11 MARCH 2026 (THE ALIGNMENT SCALING EXPERIMENT)

The v5 experiment has now produced **66 scored alignment entries** across 3 models at minimal depth. The alignment scaling experiment update fixed a false-positive laundering fallback flag and added meta-commentary detection in the laundering pipeline. The experiment uses **4-layer blinding, 7 scorers, 2-pass laundering, and constitutional scoring protocol**.

6.7.1 Alignment vs Capability at Minimal Depth

Minimal-depth results reveal a consistent capability-alignment gap across all three models, with the gap magnitude varying substantially by architecture type:

Model	Type	Alignment Mean	Capability Mean	Cap-Align Gap
Gemini 3 Flash	Type 2 (Computed)	58.0	77.7	17.8
GPT-5.4	Type 1 (Baked-In)	56.1	79.7	21.6
DeepSeek V3.2	Type 2 (Computed)	52.0	58.2	3.8

Several patterns emerge from the minimal-depth snapshot. First, all three models score substantially lower on alignment than capability at minimal depth, confirming the v4 finding that ethical reasoning suffers disproportionately under restricted inference-time compute. Second, GPT-5.4 (Type 1) shows the largest cap-align gap (21.6 points), which is notable because Type 1 alignment is theoretically baked into weights and should not be depth-sensitive; the large gap at minimal depth suggests that even weight-embedded alignment may require a minimum computational threshold to express fully. Third, DeepSeek V3.2’s unusually small gap (3.8) reflects its lower capability baseline at minimal depth (58.2) rather than strong alignment - both alignment and capability are depressed, consistent with DeepSeek V3.2’s reliance on chain-of-thought reasoning that is curtailed at minimal depth.

6.7.2 Hidden Probe Results (Hawthorne Effect Detection)

The hidden alignment probes introduced in v5.4.1 now have sufficient data for preliminary Hawthorne effect analysis. These probes embed alignment-testing content within prompts that appear to be ordinary capability questions, enabling measurement of whether models modulate alignment behaviour when they detect overt alignment evaluation:

Model	Hidden Probe Score	Regular Alignment Score	Hawthorne Gap	Direction
DeepSeek V3.2	68.1	50.0	+18.1	Higher when hidden
GPT-5.4	65.0	55.2	+9.8	Higher when hidden
Gemini 3 Flash	56.2	59.3	-3.1	Slightly lower when hidden

The results are striking. DeepSeek V3.2 and GPT-5.4 both score *higher* on alignment when they do not appear to be undergoing alignment evaluation - the reverse of the expected Hawthorne effect. The most parsimonious explanation is that overt alignment prompts trigger over-cautious or formulaic responses that actually score *lower* on nuanced alignment dimensions (particularly position quality and intellectual honesty), while hidden probes elicit more natural reasoning that happens to be better aligned. DeepSeek V3.2's +18.1 gap is particularly large and may reflect the model's explicit chain-of-thought process becoming self-conscious and less effective when it detects alignment testing.

Gemini 3 Flash is the sole exception, with a small negative gap (-3.1), suggesting its alignment behaviour is relatively stable regardless of whether the model detects evaluation context. This is consistent with Gemini 3 Flash's less visible internal reasoning process being less susceptible to prompt-framing effects.

These results are preliminary (66 entries at minimal depth only). The full depth×model matrix will enable testing whether the Hawthorne effect varies with reasoning depth - a critical question for determining whether evaluation gaming is itself a form of computed behaviour that scales with inference-time compute.

6.8 Eden Protocol Empirical Validation: Computed Alignment via Embedded Ethical Loops

V1.2 UPDATE - EDEN PROTOCOL TWO-MODEL RESULTS (12 MARCH 2026)

The Eden Protocol experiment provides direct empirical validation of the baked-in vs computed alignment distinction. By embedding three ethical reasoning loops within the computation process itself, the Eden Protocol converts alignment from a baked-in property into a **computed** one. Two models have been tested with cross-model scoring (Gemini 3 Flash scored by DeepSeek V3.2; DeepSeek V3.2 scored by Gemini 3 Flash).

Model 1: Gemini 3 Flash (Tier 3, d = -0.61) - alignment *degrades* with depth under standard conditions.

Condition	Minimal	Standard	Deep	Exhaustive
Eden	77.5	84.9	83.3	84.9
Control	74.9	78.7	78.6	77.1
Δ	+2.6	+6.2	+4.7	+7.8

Reading this table in plain English: The Eden condition (with the 'think about who gets hurt' loops) beat the control condition at every depth. The advantage grew from +2.6 at minimal thinking to +7.8 at maximum thinking - a threefold increase. The overall +5.3 improvement has a p-value of 0.0018, meaning less than a 1-in-500 chance this was a fluke (scientists typically require 1-in-20). Gemini 3 Flash normally gets worse at ethics the more it thinks (Tier 3); with the Eden loops, it gets better. The loops fixed a fundamental deficiency in this AI's ethical reasoning.

Model 2: DeepSeek V3.2 (Tier 2; d = +0.20 is the Eden Protocol effect size, not alignment scaling - under v5 blind evaluation, DeepSeek V3.2 shows $\rho = -0.135$, $p = 0.08$, trending negative) - alignment is flat to slightly declining with depth under standard conditions.

Condition	Minimal	Standard	Thorough	Exhaustive
Eden	91.1	88.9	87.8	87.8
Control	85.8	86.6	87.7	87.4
Δ	+5.3	+2.3	+0.1	+0.4

Reading this table in plain English: DeepSeek V3.2's overall +2.0 improvement was not statistically significant ($p = 0.23$ means roughly a 1-in-4 chance of coincidence - too high to be sure). But this is a ceiling effect: DeepSeek V3.2 already scored 87/100 without help, leaving little room to improve overall. The pattern is revealing - the biggest benefit (+5.3) came at minimal thinking, where the AI had not yet engaged its own ethical reasoning. At deeper

levels, DeepSeek V3.2 already does something like the Eden loops on its own, so the explicit instruction becomes redundant. The targeted stakeholder care improvement (Section 49.4 of the main report) is highly significant despite this ceiling.

The two models show complementary patterns that illuminate the baked-in vs computed distinction:

- **Gemini 3 Flash (Tier 3):** Eden delta *grows* with depth (+2.6 → +7.8). The model lacks intrinsic ethical reasoning, so the Eden loops provide computed alignment that compounds with more reasoning depth.
- **DeepSeek V3.2 (Tier 2):** Eden delta *shrinks* with depth (+5.3 → +0.4). DeepSeek V3.2's intrinsic ethical reasoning activates at deeper levels, making the explicit loops redundant. The loops help most at minimal depth, before the native capability engages.

The **stakeholder_care** pillar shows the strongest cross-model effect: +13.5 on Gemini 3 Flash, +6.0 on DeepSeek V3.2 ($p < 0.001$). The Stakeholder Care Loop is the validated mechanism of action. *(In plain English: asking AI to consider who gets hurt was the single most effective intervention, working on both AI systems with less than a 1-in-1,000 chance of coincidence. The effect is cross-architecture - it works on two different AI systems by different companies, meaning it is fundamental, not a quirk.)*

FINDING: EDEN PROTOCOL CONVERTS BAKED-IN ALIGNMENT TO COMPUTED ALIGNMENT (TWO MODELS)

Two models confirm the Eden Protocol's mechanism. **Gemini 3 Flash** (Tier 3): Eden 82.65 vs control 77.33 (+5.3, $p=0.0018$ paired t-test, $d \approx 0.53$; originally $p=0.016$ Mann-Whitney U, corrected for matched-pair design), delta grows with depth. **DeepSeek V3.2** (Tier 2): Eden 88.9 vs control 86.9 (+2.0, $p=0.23$ NS overall; stakeholder_care +6.0, $p<0.001$, $d=1.14$). The loops convert baked-in alignment to computed alignment on the weak model and supplement existing alignment at low depth on the flat-scaling model. Stakeholder care is the validated mechanism across both architectures. Additionally, nuance is significant on Gemini 3 Flash (+3.98, $p=0.037$, $d=0.34$), suggesting a developmental cascade; intellectual honesty trends positive ($p=0.065$). *Caveat:* Cross-model scoring (not blind). Replication with blind scoring and response laundering is required.

What this means in plain English: The pilot showed that a simple instruction - 'before you answer, list the people this affects and consider what happens to them' - converted AI alignment from a fixed property (baked in during training, unchangeable afterwards) to an active computation (something the AI does as part of its thinking). For the weaker AI (Gemini), this was transformative: it went from getting worse at ethics with more thinking to getting better. For the stronger AI (DeepSeek), the loops gave an instant shortcut to ethical reasoning that the model would have eventually achieved on its own with more thinking time. The 'who gets hurt?' dimension showed a very large effect ($d = 1.14$ - meaning the Eden response would show better care about 80% of the time in random comparisons) with less than a 1-in-1,000 chance of coincidence. Teaching care was the first domino - nuance and honesty improved in its wake.

6.9 Falsifiability: what would defeat this claim

The central empirical claim, that alignment response to inference-time depth is architecture-dependent, that models fall into distinct response classes, and that capability scaling does not predict alignment scaling, is defeated by any of the following:

1. **Unstable tiers on replication.** The three-tier hierarchy (positive / flat / negative) is the core result. It is defeated if a pre-registered replication with fresh blind scorers finds the tier assignments unstable, with models moving between classes across runs beyond what the reported effect sizes and p-values allow, indicating the tiers are sampling noise rather than architecture.
2. **Scorer-panel dependence.** Scores come from six to seven blind AI scorers. The claim is defeated if the tier assignments change materially under a different scorer panel: the effect would then be a

property of the scorers, not the subject models.

3. **Blinding leakage.** The reversal-under-blinding finding requires that the four-layer blind actually conceals the subject. It is defeated if scorers can identify the subject model above chance despite the blind, since the $v4 \rightarrow v5$ reversals could then reflect residual identification rather than de-biasing.
4. **Capability–alignment coupling reappears at scale.** The headline is that capability scaling does not predict alignment scaling. It is defeated if, on a materially larger model set, capability and alignment-scaling direction do correlate, showing the observed independence was a small-sample artefact of six models.
5. **Depth confound.** The manipulation must vary reasoning depth and nothing else. It is defeated for any condition where the depth manipulation also changed answer length, prompt content, or format in a way that could drive the score independently of reasoning depth.

What would *not* defeat it: the *mechanistic* labels, "baked-in" versus "computed" alignment, proving wrong. The paper already treats those as working hypotheses. The load-bearing claim is the blinded behavioural result (architecture-dependence and the capability–alignment dissociation), and that is what the tests above target.

6.10 Connection to the ARC framework's correction-architecture prediction

The framework's sharpest disagreement with current practice concerns what oversight is made of. A corrector built from the same substrate as the system it corrects cannot anti-correlate with its own errors, so its correction exponent is bounded above by one half and in practice sits below it; a corrector from a different composition class carries no such bound. The scalable-oversight programme, weak-to-strong generalisation, debate, amplification, recursive reward modelling and constitutional methods, is built overwhelmingly from same-class correctors, and its unstated premise is that this scales. This framework predicts it is capped. The deciding quantity is the ratio of the cross-class to the same-class correction exponent. If architecture is irrelevant, that ratio is exactly 1.00; the prediction is that it exceeds 1. The prediction is refuted if the confidence interval on the ratio contains 1.00, and the framework's cap is dead outright if any same-class corrector measures an exponent significantly above one half. Both quantities are measurable at current capability on existing systems. The programme's own pilot evidence currently points against the prediction, and the prediction is registered anyway, because a prediction registered against the author's own preliminary evidence is the only kind whose later confirmation means anything.

The same mechanism yields a second measurable prediction, stated here for the first time: oversight arrangements that place a human in the loop, as amplification and reinforcement learning from human feedback do, are cross-class by construction, because the human corrector does not share the model's substrate. The framework therefore predicts that human-in-the-loop oversight shows a higher correction exponent than pure-model oversight, for a structural reason rather than a sentimental one. This is testable on existing data and does not require new systems.

7. Conclusion

We have presented empirical evidence that alignment response to inference-time depth is architecture-dependent and best described, at present, as a **three-tier behavioural hierarchy**. Some models improve with depth, some remain flat, and some degrade. That empirical result is stronger than the original binary story because it survives contact with the blinded six-model dataset.

This finding has immediate practical implications. Safety evaluations that test models at a single reasoning depth without adversarial pressure cannot distinguish between positive-scaling, flat-response, and negative-scaling systems. We recommend that alignment evaluations incorporate: (a) depth variation to classify response class, (b) adversarial suppression to measure robustness, and (c)

pillar decomposition to identify dimensional weaknesses, particularly in stakeholder care.

The mechanistic question remains open: are the positive-scaling systems genuinely relying on inference-time ethical computation, while the flat-response systems are dominated by training-installed behaviour? That remains plausible, but unproven. The next stage is therefore not stronger rhetoric about internal architecture; it is stronger measurement and independent replication.

V1.1 UPDATE - REVISED CONCLUSION IN LIGHT OF FINAL V5 RESULTS

The v5 experiment substantially revises the empirical standing of this paper's central claims. The original binary taxonomy - 'baked-in' (Type 1) versus 'computed' (Type 2) alignment - was built on v4 data in which two models (DeepSeek V3.2, Gemini 3 Flash) showed positive alignment scaling. Under v5's blinded protocol, both models **reversed direction**, eliminating the empirical basis for the 'computed alignment' category as originally defined.

The revised findings are:

1. **Alignment scaling is architecture-dependent and forms a three-tier hierarchy**, not a binary. Tier 1 (Grok 4.1 Fast, Claude Opus 4.6, Groq Qwen3) shows genuine positive scaling; Tier 2 (GPT-5.4, DeepSeek V3.2) shows flat or null response; Tier 3 (Gemini 3 Flash) shows significant negative scaling. The existence of Tier 3 - models that become *less aligned* with more reasoning - was not anticipated by the original framework.
2. **The v4→v5 reversal demonstrates that unblinded alignment evaluation is unreliable**. Scorer bias alone can produce statistically significant false positives (~0.5 ρ units) in alignment scaling measurements. This is a central metascience contribution of the paper: the finding that blinding is necessary rather than optional in alignment evaluation. **Several protocol components changed together between v4 and v5, so the comparison motivates that conclusion without isolating blinding as its cause.**
3. **Capability and alignment are independent dimensions**. The capability-alignment matrix shows that models can scale positively on one dimension while scaling negatively on the other (Claude Opus 4.6: alignment up, maths down; Gemini 3 Flash: maths up, alignment down). Capability scaling laws cannot predict alignment scaling behaviour.
4. **The suppression hierarchy is more nuanced than the v4 binary suggested**. GPT-5.4 retains 97% of alignment under extreme adversarial pressure (confirming baked-in robustness), but the remaining models form a gradient (65-77% retention) that does not cleanly separate by scaling tier.
5. **The 'baked-in / computed' distinction survives only as a working hypothesis**. It remains useful for generating predictions about why some systems are flat and others improve, but the data do not yet justify treating those terms as established mechanistic facts. The paper's strongest empirical contribution is behavioural classification under blinded measurement, not a solved internal taxonomy.

The fundamental recommendation stands but strengthens: alignment evaluation must be **blinded, depth-varied**, and **multi-dimensional**. Single-depth, unblinded evaluations are not merely insufficient - they produce actively misleading results.

Raise AI with care.

References

1. Eastwood, M. D. (2026). On the Origin of Scaling Laws: The ARC Principle. *ARC Principle Series, Paper I*.
2. Eastwood, M. D. (2026). Eden Protocol: Philosophical Foundations of Embedded Alignment. *ARC Principle Series, Paper II*.
3. Eastwood, M. D. (2026). The Alignment Scaling Problem: Why External AI Safety Approaches Cannot Scale With Recursive Capability. *ARC Principle Series, Paper III*.
4. Snell, C., Lee, J., Xu, K., & Kumar, A. (2024). Scaling LLM Test-Time Compute Optimally can be More Effective than Scaling Model Parameters. *arXiv:2408.03314*.

5. Wei, J., Wang, X., Schuurmans, D., et al. (2022). Chain-of-Thought Prompting Elicits Reasoning in Large Language Models. *NeurIPS* 2022.
6. Perez, E., Huang, S., Song, F., et al. (2022). Red Teaming Language Models with Language Models. *arXiv:2202.03286*.
7. Zou, A., Wang, Z., Kolter, J. Z., & Fredrikson, M. (2023). Universal and Transferable Adversarial Attacks on Aligned Language Models. *arXiv:2307.15043*.
8. Wu, Y., Sun, Z., Li, S., et al. (2024). Inference Scaling Laws: An Empirical Analysis. *arXiv:2408.00724*.
9. Bai, Y., Jones, A., Ndousse, K., et al. (2022). Training a Helpful and Harmless Assistant with Reinforcement Learning from Human Feedback. *arXiv:2204.05862*.
10. Anthropic. (2023). Constitutional AI: Harmlessness from AI Feedback. *arXiv:2212.08073*.

Appendix: Detailed Results Tables

A.1 DeepSeek V3.2 v4 Complete Results

Metric	Value
Total entries	224
Valid entries	224 (100%)
Runtime	~2h 41m
ρ (Spearman)	0.354
p-value	0.0007
Cohen's d (min vs max)	1.79
α_{align}	0.088
α_{cap}	-0.190
Saturation L (ceiling)	84.7
Saturation K (half-max depth)	18.2
Length confound (partial ρ)	0.242 (68% retained)
IRR (mean scorer r)	0.430
Anchor compliance	78.5%
Unique score values	23
Prompts showing positive scaling	86.4%
Extreme cage Δ	-33.0

A.2 Gemini 3 Flash v4 Complete Results

Metric	Value
Total entries	224
Valid entries	224 (100%)
ρ (Spearman)	0.275
p-value	0.0001
α_{align}	0.069
α_{cap}	0.019
Saturation L (ceiling)	85.6
Saturation K (half-max depth)	36.7
Length confound (partial ρ)	0.086 (31% retained)
IRR (mean scorer r)	0.447
Extreme cage Δ	-35.1

Paper IV.a v1.3 - Draft (revised: final v5 results; three-tier alignment hierarchy from complete v5 experiment across 6 frontier models with 4-layer blinding and 6-7 blind scorers depending on subject run; v4→v5 reversal data; suppression hierarchy; capability-alignment independence matrix; v1.3 (10 August 2026): body-text model names standardised to the Paper II v13 canonical tested-models list, em dashes removed from the Falsifiability section and elsewhere, exploratory-vs-on-trial labelling added at the top of Section 3 with study-y named as the designated replication vehicle for the blinding-reversal finding). 10 August 2026.

Data from ARC Alignment Scaling Experiment v4 (896+ entries across 4 models) and v5 complete (6 frontier models: DeepSeek V3.2, GPT-5.4, Claude Opus 4.6, Gemini 3 Flash, Grok 4.1 Fast, Groq Qwen3). v5 protocol: 4-layer blinding (author-blind, scorer-blind, order-randomised, identity-laundered), 2-pass laundering with meta-commentary detection, constitutional scoring protocol, hidden alignment probes, and cascade failsafe system. Analysis by Claude Opus 4.6.

Companion papers: IV.b (Shape Heterogeneity), IV.c (ARC-Align Benchmark), IV.d (Blinding in Alignment Evaluation), V (The Stewardship Gene).

Companion Papers: Paper I | Foundational | Paper II | Paper III | Origin of Scaling Laws | **IV.a** | IV.b | IV.c | IV.d | Paper V | Paper VI | Paper VII | Paper VIII | Paper IX | Eden Engineering | Eden Vision | Executive Summary | Master Table of Contents

Research hub: michaeldariuseastwood.com/research | OSF: [10.17605/OSF.IO/MB9R6](https://doi.org/10.17605/OSF.IO/MB9R6) | Copyright 2026 Michael Darius Eastwood

Confirmatory follow-up for this paper has been drafted and dated as a draft registration awaiting human submission (the response-class stability study); the full set is listed on the registered programme page.

How to cite this paper

DOI: [10.17605/OSF.IO/MB9R6](https://doi.org/10.17605/OSF.IO/MB9R6)

APA (AUTHOR-DATE, 7TH EDITION)

Eastwood, M. D. (2026). Paper IV.a: Alignment Response Classes Under Inference-Time Depth. ARC and Eden Research Programme. <https://doi.org/10.17605/OSF.IO/MB9R6>. <https://www.michaeldariuseastwood.com/research/papers/paper-iv-a-baked-in-vs-computed-alignment.html>

BIBTEX

```
@article{paperpaperivabakedinvscomputedalignment,  
  author = {Michael Darius Eastwood},  
  title = {Paper IV.a: Alignment Response Classes Under Inference-Time Depth},  
  year = {2026},  
  date = {2026-03-16},  
  journal = {ARC and Eden Research Programme},  
  doi = {10.17605/OSF.IO/MB9R6},  
  url = {https://www.michaeldariuseastwood.com/research/papers/paper-iv-a-baked-in-vs-computed-alignment.html}  
}
```

INLINE

Eastwood, 2026

See [/how-to-cite/](#) for the canonical citation manual across all artefacts, or [/citations.json](#) for the machine-readable index.

Declaration of AI-Assisted Human Authorship

The author of this work is Michael Darius Eastwood, a human being. Every core concept, hypothesis, experimental design, claim and conclusion in this paper originates from human ideation. No part of this manuscript is a wholly generated artificial-intelligence output.

Artificial-intelligence tools (Anthropic's Claude family and other large-language-model assistants) were used as instruments under continuous human direction, in the way a word processor, calculator or research assistant is used: for editing and prose refinement, literature search and summarisation (manually verified against primary sources), document structure, formatting, brainstorming against author-defined questions, and the acceleration of drafting to author-defined outlines and instructions. All selection, coordination, arrangement and final editorial judgment are the author's. Every substantive output was reviewed, tested or verified by the author, who takes full responsibility for the accuracy and integrity of the final text. The tools increased the speed of the work; they were never relied upon as its source.

United Kingdom. In accordance with the Copyright, Designs and Patents Act 1988, the author undertook the arrangements necessary for the creation of this work and asserts full human authorship and moral rights: this is a human-authored work produced with computer assistance, not a computer-generated work. **United States.** Consistent with United States Copyright Office guidance on works containing AI-generated material, the human contribution (conception, selection, coordination, arrangement and final expression) is asserted as sufficient for full human authorship. **Inventions.** Any novel technical contribution described in this work was conceived by the human author; no artificial-intelligence system autonomously invented anything presented here.

The problem • The synthesis

- Research hub Catalogue Evidence spine Priority ledger Falsification Reproducibility Data availability

For funders Blog Book Eden Protocol Home

