



**Stephan Fischli**

# Introduction

- Spring Boot's primary goals are:
  - faster getting-started experience for Spring development
  - opinionated view of the Spring platform and third-party libraries
  - non-functional features that are common to most projects
  - no code generation and no XML configuration
- Spring Boot can be used to create stand-alone applications or traditional WAR deployments

*Spring Boot makes it easy to create stand-alone, production-grade Spring-based applications.*

# Spring Applications

# Bootstrapping

- The static run method of the SpringApplication class provides a convenient way to bootstrap a Spring application
  - defines an environment by loading properties and activating profiles
  - creates an application context and loads all singleton beans into it
  - triggers any commandline runners

```
public class BookstoreApplication {  
    public static void main(String[] args) {  
        SpringApplication.run(BookstoreApplication.class, args);  
    }  
}
```

## Bootstrapping (cont.)

- The meta-annotation `@SpringBootApplication` consists of the following annotations:
  - `@Configuration` allows programmatic registration of beans
  - `@ComponentScan` enables annotation-based scanning of components
  - `@EnableAutoConfiguration` enables Spring Boot's auto-configuration

```
@SpringBootApplication
public class BookstoreApplication {

    public static void main(String[] args) {
        SpringApplication.run(BookstoreApplication.class, args);
    }
}
```

# Auto-Configuration

- Spring Boot's auto-configuration configures an application based on the JAR dependencies
- For example, if H2 is on the classpath, an in-memory database is configured
- Specific auto-configuration classes can be disabled using the `exclude` attribute of the `@EnableAutoConfiguration` annotation

```
@SpringBootApplication
@EnableAutoConfiguration(exclude = DataSourceAutoConfiguration.class)
public class BookstoreApplication {

    public static void main(String[] args) {
        SpringApplication.run(BookstoreApplication.class, args);
    }
}
```

## The CommandLineRunner

- If code needs to be run once, a bean can implement the CommandLineRunner interface
- The interface defines a run method, which is called before the run method of SpringApplication completes
- The command line arguments are passed as parameters

```
@Component
public class BookstoreRunner implements CommandLineRunner {
    public void run(String[] args) {
        ...
    }
}
```

# Application Arguments

- If any bean needs access to the application arguments, an `ApplicationArguments` bean can be injected
- The `ApplicationArguments` interface provides access to parsed options and non-option arguments

```
@Component
public class CustomerService {

    public CustomerService(ApplicationArguments args) {
        boolean debug = args.containsOption("debug");
        List<String> files = args.getNonOptionArgs();
        ...
    }
}
```



# Spring Development

## Project Setup

- For the development of Spring applications, a build system such as Maven or Gradle is recommended
- Each release of Spring Boot provides a list of supported dependencies (see **Reference Guide**)
- A convenient way to create a Spring project is to use the **Spring Initializr** web tool

# Maven Projects

- Maven projects can inherit from the spring-boot-starter-parent project which provides dependency management and some sensible configurations
  - Java 21 compiler level
  - UTF-8 source encoding
  - execution of the repackaging goal
  - plugin configuration
  - resource filtering

```
<parent>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-starter-parent</artifactId>
  <version>3.5.7</version>
</parent>
```

# Starters

- **Starters** are dependency descriptors for particular types of Spring Boot applications
- As a general purpose starter, the spring-boot-starter dependency can be included
- Spring Boot also provides starters to exclude or exchange specific technical facets (e.g. logging)

```
<dependencies>
  <dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter</artifactId>
  </dependency>
</dependencies>
```

# Maven Plugin

- The Spring Boot Maven plugin is used to run and to package an application

```
<plugins>
  <plugin>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-maven-plugin</artifactId>
  </plugin>
</plugins>
```



```
=====|_|=====|___/=/_/_/_/  
:: Spring Boot :: (v3.5.7)
```

# Startup Failure

- If an application fails to start, failure analyzers try to provide a dedicated error message and a concrete action to fix the problem

```
*****  
APPLICATION FAILED TO START  
*****
```

Description:

Embedded servlet container failed to start. Port 8080 was already in use.

Action:

Identify and stop the process that's listening on port 8080 or  
configure  
this application to listen on another port.s

- The full evaluation conditions report can be displayed by enabling the debug property



```
> java -jar target/bookstore-1.0.jar --debug
```

## Customizing the Banner

- By adding a `banner.txt` file to the classpath, the startup banner can be changed
- Inside the file, the following placeholders can be used:
  - `${application.title}` for the application title as declared in the manifest file
  - `${application.version}` for the application version as declared in the manifest file
  - `${spring-boot.version}` for the Spring Boot version

```
      _\|/_  
      (o o)  
-----oOo-( )-Oo-----  
${application.title} ${application.version}  
Spring Boot ${spring-boot.version}  
-----
```

## Developer Tools

- Spring Boot provides tools that make the application development more efficient by
  - defining property defaults (e.g. disable caching, enable debug logging)
  - automatically restarting the application whenever files on the classpath change
  - including an embedded LiveReload server that can be used to trigger a browser refresh
- The developer tools can be added by including the spring-boot-devtools module

```
<dependencies>  
  <dependency>  
    <groupId>org.springframework.boot</groupId>  
    <artifactId>spring-boot-devtools</artifactId>  
    <optional>true</optional>
```

```
</dependency>  
</dependencies>
```

## Code Structure

- The following code structure is recommended:
  - the main application class is located in a root package
  - a different subpackage is provided for each application domain

```
org
├── example
│   ├── bookstore
│   │   ├── BookstoreApplication.java
│   │   ├── customer
│   │   │   ├── Customer.java
│   │   │   ├── CustomerController.java
│   │   │   ├── CustomerService.java
│   │   │   └── CustomerRepository.java
│   │   └── order
│   │       ├── Order.java
│   │       ├── OrderController.java
│   │       ├── OrderService.java
│   │       └── OrderRepository.java
```