

# 08 - Superlative Streams

CS 2043: Unix Tools and Scripting, Spring 2016 [1]

---

Stephen McDowell

February 12th, 2016

Cornell University

# Table of contents

1. Cutting and Pasting
2. Splitting and Joining
3. The Stream Editor (**sed**)
4. Sed Practice

## Some Logistics

- HW1 due today at 5pm.

## Some Logistics

- HW1 due today at 5pm.
- OH Today: only 2pm - 3pm...thanks (again) Joe!

## Some Logistics

- HW1 due today at 5pm.
- OH Today: only 2pm - 3pm...thanks (again) Joe!
- On my usage of `>`, which will now become `>>>` for safety.

## Some Logistics

- HW1 due **today** at 5pm.
- OH Today: only 2pm - 3pm...thanks (again) Joe!
- On my usage of `>`, which will now become `>>>` for safety.
- **Repository confusion:**

## Some Logistics

- HW1 due **today** at 5pm.
- OH Today: only 2pm - 3pm...thanks (again) Joe!
- On my usage of `>`, which will now become `>>>` for safety.
- Repository confusion:
  - *Do NOT fork the `<usr>-assignments` repositories!!!!!!*

# Some Logistics

- HW1 due **today** at 5pm.
- OH Today: only 2pm - 3pm...thanks (again) Joe!
- On my usage of `>`, which will now become `>>>` for safety.
- Repository confusion:
  - Do **NOT** fork the `<usr>-assignments` repositories!!!!!!
  - Getting lectures easily: **clone** the **lecture-slides** repo, **pull** as needed.



# Some Logistics

- HW1 due **today** at 5pm.
- OH Today: only 2pm - 3pm...thanks (again) Joe!
- On my usage of `>`, which will now become `>>>` for safety.
- Repository confusion:
  - Do **NOT** fork the `<usr>-assignments` repositories!!!!!!
  - Getting lectures easily: `clone` the `lecture-slides` repo, `pull` as needed.
  - **Only fork** the `lecture-demos` repo.

# Some Logistics

- HW1 due **today** at 5pm.
- OH Today: only 2pm - 3pm...thanks (again) Joe!
- On my usage of `>`, which will now become `>>>` for safety.
- Repository confusion:
  - Do **NOT** fork the `<usr>-assignments` repositories!!!!!!
  - Getting lectures easily: `clone` the `lecture-slides` repo, `pull` as needed.
  - Only `fork` the `lecture-demos` repo.
    - This allows you to put your demo work online, get more practice with **git**.

# Cutting and Pasting

---

# Chopping up Input

## Cut

`cut <options> [file]`

- *Must* specify a list of bytes, characters, or fields.
  - 1 The **file** is optional this time, uses **STDIN** if unspecified.
- Use **-b** to extract using range of *bytes*.
- Use **-c** to extract using a range of *characters*.
- Use **-f** to extract a range of *fields* separated by a delimiter.

<b>N</b>	$N^{\text{th}}$ byte, character or field, counted from 1
<b>N-</b>	from $N^{\text{th}}$ byte, character or field, to end of line
<b>N-M</b>	from $N^{\text{th}}$ to $M^{\text{th}}$ (included) byte, character or field
<b>-M</b>	from first to $M^{\text{th}}$ (included) byte, character or field

- Use **-d** to specify a delimiter (**TAB** by default).
- Use **-s** to suppress line if **delimiter** not found.

# Cut Examples

## employees.csv

```
Alice,female,607-123-4567,11 Sunny Place,Ithaca,NY,14850
Bob,male,607-765-4321,1892 Rim Trail,Ithaca,NY,14850
Andy,n/a,607-706-6007,1 To Rule Them All,Ithaca,NY,14850
Bad employee data without proper delimiter
```

## Examples

- Get names, ignore improper lines:  

```
>>> cut -d , -f 1 -s employees.csv
```
- Get names and phone numbers, ignore improper lines:  

```
>>> cut -d , -f 1,3 -s employees.csv
```
- Get address (4th col and after), ignore improper lines:  

```
>>> cut -d , -f 4- -s employees.csv
```
- Get 11<sup>th</sup> character of every line:  

```
>>> cut -c 11 employees.csv
```

## Paste

```
paste [options] [file1] [file2] ...
```

- No **options** or **files** necessary...  
...but relatively useless program without them.
- Use **-d** to specify the delimiter (**TAB** by default).
- Use **-s** to concatenates serially instead of side-by-side.
- No options and one **file** specified: just like **cat**.
  - Use with **-s** to join all lines of file!

## Paste Examples I

names.txt

Alice

Bob

Andy

phones.txt

607-123-4567

607-765-4321

607-706-6007

```
>>> paste -d , names.txt phones.txt > result.csv
```

result.csv

Alice,607-123-4567

Bob,607-765-4321

Andy,607-706-6007

## Paste Examples II

names.txt

Alice

Bob

Andy

phones.txt

607-123-4567

607-765-4321

607-706-6007

```
>>> paste -d , -s names.txt phones.txt > result.csv
```

result.csv

Alice,Bob,Andy

607-123-4567,607-765-4321,607-706-6007



## Paste Examples III

### employees.csv

```
Alice,female,607-123-4567,11 Sunny Place,Ithaca,NY,14850
Bob,male,607-765-4321,1892 Rim Trail,Ithaca,NY,14850
Andy,n/a,607-706-6007,1 To Rule Them All,Ithaca,NY,14850
Bad employee data without proper delimiter
```

```
>>> paste -d "" -s employees.csv | \
      cut -d , -f 1- --output-delimiter="" | \
      tr -d "[:space:]"
```

### output (all on one line...)

```
Alicefemale607-123-456711SunnyPlaceIthacaNY14850Bobmale6
07-765-43211892RimTrailIthacaNY14850Andyn/a607-706-60071
ToRuleThemAllIthacaNY14850Bademployeedatawithoutproperde
limiter
```

# Splitting and Joining

---

## Split

`split [options] [input] [prefix]`

- Use `-l` to specify how many lines in each file.
  - Default is 1000.
- Use `-b` to specify how many bytes in each file.
- The **prefix** is prepended to each file produced.
- Use `-d` to produce numeric suffixes instead of lexographic.
  - Not available on OSX.

# Splitting Files

## Split

`split [options] [input] [prefix]`

- Use `-l` to specify how many lines in each file.
  - Default is 1000.
- Use `-b` to specify how many bytes in each file.
- The **prefix** is prepended to each file produced.
- Use `-d` to produce numeric suffixes instead of lexographic.
  - Not available on OSX.

- Extremely useful for managing large streams of data.

# Splitting Files

## Split

`split [options] [input] [prefix]`

- Use `-l` to specify how many lines in each file.
  - Default is 1000.
- Use `-b` to specify how many bytes in each file.
- The **prefix** is prepended to each file produced.
- Use `-d` to produce numeric suffixes instead of lexographic.
  - Not available on OSX.

- Extremely useful for managing large streams of data.
- Remember that annoying *dungeon* folder?

# Splitting Files

## Split

`split [options] [input] [prefix]`

- Use `-l` to specify how many lines in each file.
  - Default is 1000.
- Use `-b` to specify how many bytes in each file.
- The **prefix** is prepended to each file produced.
- Use `-d` to produce numeric suffixes instead of lexographic.
  - Not available on OSX.

- Extremely useful for managing large streams of data.
- Remember that annoying *dungeon* folder?
  - `split -l 5` is what we did.

# Joining Files

Join lines containing the same keys between two different files.

## Join

```
join [options] file1 file2
```

- Join two files at a time, no more, no less.
- Default: files are assumed to be delimited by *whitespace*.
- Use **-t <char>** to specify an alternative *single-character* delimiter.
- Use **-1 field\_number** to join by the  $n^{\text{th}}$  field of **file1**.
- Use **-2 field\_number** to join by the  $n^{\text{th}}$  field of **file2**.
  - Field numbers start at 1, like **cut** and **paste**.
- Use **-a f\_num** to display unpaired lines of file **f\_num**.

## Join Examples I

ages.txt

Alice 44  
Bob 30  
Candy 12

salaries.txt

Bob 300,000  
Candy 120,000

```
>>> join ages.txt salaries.txt > results.txt
```

results.txt

Bob 30 300,000  
Candy 12 120,000



## Join Examples II

ages.txt

Alice 44  
Bob 30  
Candy 12

salaries.txt

Bob 300,000  
Candy 120,000

```
>>> join -a1 ages.txt salaries.txt > results.txt
```

results.txt

Alice 44  
Bob 30 300,000  
Candy 12 120,000

# The Stream Editor (**sed**)

---

# Introducing...

## Stream Editor

`sed [options] [script] [file]`

- Stream editor for filtering and transforming text.
- We will focus on `sed`'s '`s/<regex>/<text>`' `[file]`.
  - Replace anything that matches `<regex>` with `<text>`.
- `sed` goes line by line searching for the regular expression.

# Introducing...

## Stream Editor

`sed [options] [script] [file]`

- Stream editor for filtering and transforming text.
  - We will focus on `sed`'s '`s/<regex>/<text>`' `[file]`.
    - Replace anything that matches `<regex>` with `<text>`.
  - `sed` goes line by line searching for the regular expression.
- 
- We will only cover the *basics*, as `sed` is an entire programming language.

# Introducing...

## Stream Editor

`sed` [options] [script] [file]

- Stream editor for filtering and transforming text.
  - We will focus on `sed`'s '`s/<regex>/<text>`' [file].
    - Replace anything that matches `<regex>` with `<text>`.
  - `sed` goes line by line searching for the regular expression.
- 
- We will only cover the *basics*, as `sed` is an entire programming language.
    - As in there are entire books on it...

# Introducing...

## Stream Editor

`sed` [options] [script] [file]

- Stream editor for filtering and transforming text.
  - We will focus on `sed`'s '`s/<regex>/<text>`' [file].
    - Replace anything that matches `<regex>` with `<text>`.
  - `sed` goes line by line searching for the regular expression.
- 
- We will only cover the *basics*, as `sed` is an entire programming language.
    - As in there are entire books on it...
  - What is the difference between `sed` and `tr`?

# Introducing...

## Stream Editor

`sed [options] [script] [file]`

- Stream editor for filtering and transforming text.
  - We will focus on `sed`'s '`s/<regex>/<text>`' `[file]`.
    - Replace anything that matches `<regex>` with `<text>`.
  - `sed` goes line by line searching for the regular expression.
- 
- We will only cover the *basics*, as `sed` is an entire programming language.
    - As in there are entire books on it...
  - What is the difference between `sed` and `tr`?
    - `sed` can match regular expressions!

# Introducing...

## Stream Editor

`sed [options] [script] [file]`

- Stream editor for filtering and transforming text.
  - We will focus on `sed`'s '`s/<regex>/<text>`' `[file]`.
    - Replace anything that matches `<regex>` with `<text>`.
  - `sed` goes line by line searching for the regular expression.
- 
- We will only cover the *basics*, as `sed` is an entire programming language.
    - As in there are entire books on it...
  - What is the difference between `sed` and `tr`?
    - `sed` can match regular expressions!
    - `sed` also does a *lot* more.



## A Basic Example

```
>>> sed 's/not guilty/guilty/g' filename
```

## A Basic Example

```
>>> sed 's/not guilty/guilty/g' filename
```

- Replaces *not guilty* with *guilty* everywhere in the file.

## A Basic Example

```
>>> sed 's/not guilty/guilty/g' filename
```

- Replaces *not guilty* with *guilty* everywhere in the file.
- CAUTION: You should be in the habit of using *single-quotes* for strings with **sed**.

## A Basic Example

```
>>> sed 's/not guilty/guilty/g' filename
```

- Replaces *not guilty* with *guilty* everywhere in the file.
- CAUTION: You should be in the habit of using *single-quotes* for strings with **sed**.
  - don't have to escape every double-quote (").

## A Basic Example

```
>>> sed 's/not guilty/guilty/g' filename
```

- Replaces *not guilty* with *guilty* everywhere in the file.
- CAUTION: You should be in the habit of using *single-quotes* for strings with **sed**.
  - don't have to escape every double-quote (").
- What happens if we do not have the **g**?

## A Basic Example

```
>>> sed 's/not guilty/guilty/g' filename
```

- Replaces *not guilty* with *guilty* everywhere in the file.
- CAUTION: You should be in the habit of using *single-quotes* for strings with **sed**.
  - don't have to escape every double-quote (").
- What happens if we do not have the **g**?
  - Without the **g**, it will only do one substitution per line.

## A Basic Example

```
>>> sed 's/not guilty/guilty/g' filename
```

- Replaces *not guilty* with *guilty* everywhere in the file.
- CAUTION: You should be in the habit of using *single-quotes* for strings with **sed**.
  - don't have to escape every double-quote (").
- What happens if we do not have the **g**?
  - Without the **g**, it will only do one substitution per line.
    - There are definitely cases where you would want that!

# Deletion

- Just like with `tr` we can do deletion with `sed`.



# Deletion

- Just like with `tr` we can do deletion with `sed`.
- `sed '/regex/d'` - deletes all lines that contain `regex`.

# Deletion

- Just like with `tr` we can do deletion with `sed`.
- `sed '/regex/d'` - deletes all **lines** that contain **regex**.
- **Example:**

# Deletion

- Just like with `tr` we can do deletion with `sed`.
- `sed '/regex/d'` - deletes all `lines` that contain `regex`.
- Example:

```
>>> sed '/[Dd]avid/d' file1 > file2
```

# Deletion

- Just like with **tr** we can do deletion with **sed**.
- **sed** `'/regex/d'` - deletes all **lines** that contain **regex**.
- Example:

```
>>> sed '/[Dd]avid/d' file1 > file2
```

- Deletes all lines in **file1** that contain either *David* or *david*, and saves the result into **file2**.

# Regular Expressions

- The power of **sed** is that it treats everything between the first pair of `/`'s as a regular expression.

# Regular Expressions

- The power of **sed** is that it treats everything between the first pair of `/`'s as a regular expression.
- What does this do?

# Regular Expressions

- The power of **sed** is that it treats everything between the first pair of **/**'s as a regular expression.
- What does this do?

```
>>> sed 's/[[[:alpha:]]\{1,3\}[[[:digit:]]*@cornell\.edu/REMOVED/g' file
```

# Regular Expressions

- The power of **sed** is that it treats everything between the first pair of **/**'s as a regular expression.
- What does this do?

```
>>> sed 's/[[[:alpha:]]\{1,3\}[[[:digit:]]*@cornell\.edu/REMOVED/g' file
```

- Print a file with all **netID@cornell.edu** emails removed!



# Regular Expressions

- The power of **sed** is that it treats everything between the first pair of **/**'s as a regular expression.
- What does this do?

```
>>> sed 's/[[[:alpha:]]\{1,3\}[[[:digit:]]*@cornell\.edu/REMOVED/g' file
```

- Print a file with all **netID@cornell.edu** emails removed!
- Use **-r** (**-E** on BSD/OSX) to use *extended* regular expressions.

# Saving Strings

- What does this do?

# Saving Strings

- What does this do?

```
>>> sed 's/^\([A-Z][A-Za-z]*\), \([A-Z][A-Za-z]*\)/\2 \1/' file
```

# Saving Strings

- What does this do?

```
>>> sed 's/^\([A-Z][A-Za-z]*\) , \([A-Z][A-Za-z]*\) / \2 \1/' file
```

- Searches for an expression at the beginning of the line of the form **e1**, **e2** where **e1** and **e2** are "words" starting with capital letters.

# Saving Strings

- What does this do?

```
>>> sed 's/^\([A-Z][A-Za-z]*\) , \([A-Z][A-Za-z]*\)/\2 \1/' file
```

- Searches for an expression at the beginning of the line of the form **e1**, **e2** where **e1** and **e2** are "words" starting with capital letters.
- Placing an expression inside ( ) tells the editor to save whatever string matches the expression.

# Saving Strings

- What does this do?

```
>>> sed 's/^\([A-Z][A-Za-z]*\) , \([A-Z][A-Za-z]*\) / \2 \1/' file
```

- Searches for an expression at the beginning of the line of the form **e1**, **e2** where **e1** and **e2** are "words" starting with capital letters.
- Placing an expression inside ( ) tells the editor to save whatever string matches the expression.
- Since ( ) are special characters, we escape them e.g. with **\( \)**.

# Saving Strings

- What does this do?

```
>>> sed 's/^\([A-Z][A-Za-z]*\) , \( [A-Z][A-Za-z]*\) /\2 \1/' file
```

- Searches for an expression at the beginning of the line of the form **e1**, **e2** where **e1** and **e2** are "words" starting with capital letters.
- Placing an expression inside ( ) tells the editor to save whatever string matches the expression.
- Since ( ) are special characters, we escape them e.g. with `\( \)`.
- We access the saved strings as `\1` and `\2`.

# Saving Strings

- What does this do?

```
>>> sed 's/^\([A-Z][A-Za-z]*\) , \([A-Z][A-Za-z]*\) / \2 \1/' file
```

- Searches for an expression at the beginning of the line of the form **e1, e2** where **e1** and **e2** are "words" starting with capital letters.
- Placing an expression inside **( )** tells the editor to save whatever string matches the expression.
- Since **( )** are special characters, we escape them e.g. with **\( \)**.
- We access the saved strings as **\1** and **\2**.
- This script for example could convert a database file from **Lastname, Firstname** - to - **Firstname Lastname**



## More **sed**

- You can specify which lines to check by numbers or with regular expressions:

## More sed

- You can specify which lines to check by numbers or with regular expressions:

```
# checks lines 1 to 20
>>> sed '1,20s/john/John/g' file
# checks lines beginning with "The"
>>> sed '/^The/s/john/John/g' file
```

## More sed

- You can specify which lines to check by numbers or with regular expressions:

```
# checks lines 1 to 20
>>> sed '1,20s/john/John/g' file
# checks lines beginning with "The"
>>> sed '/^The/s/john/John/g' file
```

- The **&** corresponds to the pattern found:

## More sed

- You can specify which lines to check by numbers or with regular expressions:

```
# checks lines 1 to 20
>>> sed '1,20s/john/John/g' file
# checks lines beginning with "The"
>>> sed '/^The/s/john/John/g' file
```

- The & corresponds to the pattern found:

```
# replace words with words in quotes
>>> sed 's/[a-z]\+/"&"/g' file
```

## More sed

- You can specify which lines to check by numbers or with regular expressions:

```
# checks lines 1 to 20
>>> sed '1,20s/john/John/g' file
# checks lines beginning with "The"
>>> sed '/^The/s/john/John/g' file
```

- The & corresponds to the pattern found:

```
# replace words with words in quotes
>>> sed 's/[a-z]\+/"&"/g' file
```

- Many more resources here:  
<http://www.grymoire.com/Unix/Sed.html>

# Sed Practice

---

## Extra Practice

Can be found here: <https://github.com/cs2043-sp16/lecture-demos/tree/master/lec08>

[1] B. Abrahao, H. Abu-Libdeh, N. Savva, D. Slater, and others over the years.

Previous cornell cs 2043 course slides.