

Defining and Simulating Populations

Vijay Ivaturi, Chris Rackauckas

February 10, 2019

```
using PuMaS, DataFrames, LinearAlgebra, Plots
```

1 Introduction

In this tutorial, we will cover the fundamentals of generating populations to simulate with PuMaS. We will demonstrate how to specify dosage regimens and covariates, and then how to piece these together to form a population to simulate.

1.1 The model

Below is a PuMaS model that specifies a 1-compartment oral absorption system with between-subject variability on all the parameters. Details of the model specification are provided in the introduction tutorial.

```
model = @model begin
  @param begin
     $\theta \in \text{VectorDomain}(4)$ 
     $\Omega \in \text{PSDDomain}(3)$ 
     $\sigma_{\text{prop}} \in \text{RealDomain}(\text{init}=0.1)$ 
  end

  @random begin
     $\eta \sim \text{MvNormal}(\Omega)$ 
  end

  @covariates isPM Wt

  @pre begin
    TVCL = isPM == 1 ?  $\theta[1]$  :  $\theta[4]$ 
    CL =  $\theta[1] * (\text{Wt}/70)^{0.75} * \exp(\eta[1])$ 
    V =  $\theta[2] * (\text{Wt}/70)^{0.75} * \exp(\eta[2])$ 
    Ka =  $\theta[3] * \exp(\eta[3])$ 
  end

  @dynamics begin
    Depot' = -Ka*Depot
    Central' = Ka*Depot - Central*CL/V
```

```

end

@vars begin
    conc = Central/V
end

@derived begin
    dv ~ @.Normal(conc, sqrt(conc^2*σ_prop+ eps()))
end

end

```

```

PKPDMModel
Parameters: θ, Ω, σ_prop
Random effects: η
Covariates: isPM, Wt
Dynamical variables: Depot, Central
Derived: conc, dv

```

1.2 Setting up parameters

Next we provide the initial estimates of the parameters to simulate from. The fixed effects are provided in the θ vector (CL, V, Ka) and the between-subject variability parameters are provided in the Ω vector as variances. So, 0.04 variance on Ω_{11} suggests a 20% coefficient of variation. Similarly, σ_{prop} has a 20% proportional residual error.

```

p = (
    θ = [0.4, 20, 1.1, 2],
    Ω = PDMat(diagm(0 => [0.04, 0.04, 0.04])),
    σ_prop = 0.04
)

```

```

(θ = [0.4, 20.0, 1.1, 2.0], Ω = PDMats.PDMat{Float64, Array{Float64, 2}}(3, [
0.04 0.0 0.0; 0.0 0.04 0.0; 0.0 0.0 0.04], LinearAlgebra.Cholesky{Float64, A
rray{Float64, 2}}([0.2 0.0 0.0; 0.0 0.2 0.0; 0.0 0.0 0.2], 'U', 0)), σ_prop
= 0.04)

```

1.3 Single dose example

`DosageRegimen()` is the function that lets you construct a dosing regimen. The first argument of the `DosageRegimen` is `amt` and is not a named argument. All subsequent arguments need to be named. Lets try a simple example where you provide a 100 mg dose at `time=0`.

```

ev = DosageRegimen(100, time=0)
first(ev.data)

```

	time	cmt	amt	evid	ii	addl	rate	ss
	Float64	Int64	Float64	Int8	Float64	Int64	Float64	Int8
1	0.0	1	100.0	1	0.0	0	0.0	0

As you can see above, we provided a single 100 mg dose. `DosageRegimen` provides some defaults when it creates the dataset, `time=0`, `evid=1`, `cmt=1`, `rate=0`, `ii=0` & `addl=0`. We can also provide units to the `amt` and any other variable that is derived from `amt`, e.g. `rate`, will have associated units. Handling of units will be covered in a different tutorial.

Note that `ev` is of type `DosageRegimen`. Specified like above, `DosageRegimen` is one of the four fundamental building block of a `Subject` (more on `Subject` below).

1.3.1 Building Subjects

Let's create a single subject

```
s1 = Subject(id=1, evs=ev, cvs=(isPM=0, Wt=70))
for fn in fieldnames(Subject)
    x = getproperty(s1, fn)
    if !isa(x, Nothing)
        println(fn)
        println(x)
    end
end

id
1
observations
NamedTuple{(), Tuple{}}[]
covariates
(isPM = 0, Wt = 70)
events
PuMaS.Event{Float64, Float64, Float64, Float64, Float64, Float64}[Dose event
    dose amount = 100.0
    dose time = 0.0
    compartment = 1
    instantaneous
    interdose interval = 0.0
    infusion start time = 0.0
]
time
Int64[]
```

Note that each `Subject` is an individual composed of:

- `id`: an unique identifier
- `obs`: observations, represented by `PuMaS.Observation[]`
- `cvs`: covariates
- `evs`: events, represented by `PuMaS.Event[]`

In the example above, we only provided the `id`, `evs`, and the `cvs`. Since `obs` were not provided, they are represented by an empty array. Lets take a closer at the events for this subject 1.

```
s1.events
```

```
1-element Array{PuMaS.Event{Float64,Float64,Float64,Float64,Float64,Float64},1}:
Dose event
  dose amount = 100.0
  dose time = 0.0
  compartment = 1
  instantaneous
  interdose interval = 0.0
  infusion start time = 0.0
```

The events are presented by basic information such as the dose of drug and associated units if specified, the time of dose administration, the compartment number for administration and whether the dose is an instantaneous input or an infusion.

Below is how the covariates are represented


```
s1.covariates
```

```
(isPM = 0, Wt = 70)
```

(Note: defining distributions for covariates will be discussed in detail later.)

Using this one subject, `s1`, let us simulate a simple concentration time profile using the model above:

```
obs = simobs(model,s1,p,obstimes=0:0.1:120)
plot(obs)
```



1.3.2 Building Populations

Now, lets create one more subject, `s2`.

```
s2 = Subject(id=2, evs=ev, cvs=(isPM=1, Wt=70))
```

```
Subject
  ID: 2
  Events: 1
  Observations: 0
  Covariates: isPM, Wt
```

If we want to simulate both `s1` and `s2` together, we need to bring these subjects together to form a `Population`. A `Population` is essentially a collection of subjects.

```
twosubjs = Population([s1,s2])
```

```
2-element PuMaS.Population{PuMaS.Subject{StructArrays.StructArray{NamedTupl
e{(), Tuple{}}}, 1, NamedTuple{(), Tuple{}}}, NamedTuple{(:isPM, :Wt), Tuple{Int64
, Int64}}, Array{PuMaS.Event{Float64, Float64, Float64, Float64, Float64, Float64}
, 1}, Int64}}:
Subject
  ID: 1
  Events: 1
  Observations: 0
```

```
Covariates: isPM, Wt
```

```
Subject
```

```
ID: 2
```

```
Events: 1
```

```
Observations: 0
```

```
Covariates: isPM, Wt
```

Let's see the details of the first and the second subject

```
twosubjs.subjects[1]
```

```
Subject
```

```
ID: 1
```

```
Events: 1
```

```
Observations: 0
```

```
Covariates: isPM, Wt
```

```
twosubjs.subjects[2]
```

```
Subject
```

```
ID: 2
```

```
Events: 1
```

```
Observations: 0
```

```
Covariates: isPM, Wt
```

Now, we can simulate this Population of 2 subjects as below


```
obs = simobs(model,twosubjs,p,obstimes=0:0.1:120)
```

```
PuMaS.SimulatedPopulation{Array{PuMaS.SimulatedObservations{PuMaS.Subject{StructArrays.StructArray{NamedTuple{(), Tuple{}}}, 1, NamedTuple{(), Tuple{}}}, NamedTuple{(:isPM, :Wt), Tuple{Int64, Int64}}, Array{PuMaS.Event{Float64, Float64, Float64, Float64, Float64, Float64}, 1}, Int64}, StepRangeLen{Float64, Base.TwicePrecision{Float64}, Base.TwicePrecision{Float64}}, NamedTuple{(:conc, :dv), Tuple{Array{Float64, 1}, Array{Float64, 1}}}}, 1}}(PuMaS.SimulatedObservations{PuMaS.Subject{StructArrays.StructArray{NamedTuple{(), Tuple{}}}, 1, NamedTuple{(), Tuple{}}}, NamedTuple{(:isPM, :Wt), Tuple{Int64, Int64}}, Array{PuMaS.Event{Float64, Float64, Float64, Float64, Float64, Float64}, 1}, Int64}, StepRangeLen{Float64, Base.TwicePrecision{Float64}, Base.TwicePrecision{Float64}}, NamedTuple{(:conc, :dv), Tuple{Array{Float64, 1}, Array{Float64, 1}}}}[SimulatedObservations{Subject{StructArray{NamedTuple{(), Tuple{}}}, 1, NamedTuple{(), Tuple{}}}, NamedTuple{(:isPM, :Wt), Tuple{Int64, Int64}}, Array{Event{Float64, Float64, Float64, Float64, Float64, Float64}, 1}, Int64}, StepRangeLen{Float64, TwicePrecision{Float64}, TwicePrecision{Float64}}, NamedTuple{(:conc, :dv), Tuple{Array{Float64, 1}, Array{Float64, 1}}}}(Subject{ID: 1Events: 1Observations: 0Covariates: isPM, Wt
```

```
, 0.0:0.1:120.0, (conc = [0.0, 0.476283, 0.911031, 1.30777, 1.66974, 1.9998
8, 2.3009, 2.57528, 2.82528, 3.05296 ... 0.362588, 0.361747, 0.360907, 0.36
007, 0.359234, 0.358401, 0.357569, 0.356739, 0.355911, 0.355085], dv = [-1.
17936e-8, 0.458922, 0.526968, 0.932889, 1.30379, 1.98207, 1.836, 2.47078, 2
.52104, 2.35757 ... 0.315556, 0.403436, 0.380987, 0.384172, 0.360975, 0.405
097, 0.240697, 0.338874, 0.475553, 0.328769])), SimulatedObservations{Subje
ct{StructArray{NamedTuple{(),Tuple{}}},1,NamedTuple{(),Tuple{}}},NamedTuple{
(:isPM, :Wt),Tuple{Int64,Int64}},Array{Event{Float64,Float64,Float64,Float6
4,Float64,Float64},1},Int64},StepRangeLen{Float64,TwicePrecision{Float64},T
wicePrecision{Float64}},NamedTuple{(:conc, :dv),Tuple{Array{Float64,1},Arra
y{Float64,1}}}}}(Subject
ID: 2
Events: 1
Observations: 0
Covariates: isPM, Wt
, 0.0:0.1:120.0, (conc = [0.0, 0.443756, 0.842963, 1.20201, 1.52484, 1.8150
2, 2.07577, 2.30997, 2.52025, 2.70896 ... 0.408045, 0.407216, 0.406388, 0.4
05562, 0.404737, 0.403914, 0.403093, 0.402273, 0.401456, 0.400639], dv = [-
1.94538e-8, 0.400692, 0.634565, 1.01431, 1.31017, 1.89752, 2.61175, 2.94681
, 3.69441, 2.47212 ... 0.466908, 0.417494, 0.35545, 0.418326, 0.394422, 0.4
98405, 0.362985, 0.250041, 0.391517, 0.427633]))))
```

When using `simobs` on more than one subject, i.e., on a Population, the simulation is automatically parallelized across the subjects.

```
plot(obs)
```



Similarly, we can build a population of any number of subjects. But before we do that, let's dive into covariate generation.

1.3.3 Covariates

As was discussed earlier, a `Subject` can also be provided details regarding covariates. In the model above, there are two covariates, `isPM` which stands for *is the subject a poor metabolizer* and takes a boolean of *yes* and *no*. The second covariate is a continuous covariate where body weight `Wt` impacts both `CL` and `V`. Let us now specify covariates to a population of 10 subjects.

```
choose_covariates() = (isPM = rand([1, 0]),  
                      Wt = rand(55:80))
```

`choose_covariates` (generic function with 1 method)

`choose_covariates` will randomly choose a `isPM` and an `Wt` between 55-80 kgs

We can make a list with covariates for ten subjects through a list comprehension

```
cvs = [ choose_covariates() for i in 1:10 ]  
DataFrame(cvs)
```

	isPM	Wt
	Int64	Int64
1	1	70
2	0	55
3	0	61
4	0	68
5	1	69
6	0	78
7	0	76
8	0	73
9	0	73
10	1	77

Now, we add these covariates to the population as below. The `map(f,xs)` will return the result of `f` on each element of `xs`. Let's map a function that build's a subject with the randomly chosen covariates in order to build a population:

```
pop_with_covariates = Population(map(i ->  
    Subject(id=i, evs=ev, cvs=choose_covariates()), 1:10))
```

```
10-element PuMaS.Population{PuMaS.Subject{StructArrays.StructArray{NamedTuple{(), Tuple{}}}, 1, NamedTuple{(), Tuple{}}}, NamedTuple{(:isPM, :Wt), Tuple{Int64, Int64}}, Array{PuMaS.Event{Float64, Float64, Float64, Float64, Float64, Float64}, 1}, Int64}}:
```

Subject

ID: 1

Events: 1

Observations: 0

Covariates: isPM, Wt

Subject
ID: 2
Events: 1
Observations: 0
Covariates: isPM, Wt

Subject
ID: 3
Events: 1
Observations: 0
Covariates: isPM, Wt

Subject
ID: 4
Events: 1
Observations: 0
Covariates: isPM, Wt

Subject
ID: 5
Events: 1
Observations: 0
Covariates: isPM, Wt

Subject
ID: 6
Events: 1
Observations: 0
Covariates: isPM, Wt

Subject
ID: 7
Events: 1
Observations: 0
Covariates: isPM, Wt

Subject
ID: 8
Events: 1
Observations: 0
Covariates: isPM, Wt

Subject
ID: 9
Events: 1
Observations: 0
Covariates: isPM, Wt

Subject
ID: 10
Events: 1
Observations: 0
Covariates: isPM, Wt

Simulate into the population

```
obs = simobs(model,pop_with_covariates,p,obstimes=0:0.1:120)
```

```

PuMaS.SimulatedPopulation{Array{PuMaS.SimulatedObservations{PuMaS.Subject{S
tructArrays.StructArray{NamedTuple{(),Tuple{}}},1,NamedTuple{(),Tuple{}}},Na
medTuple{(:isPM, :Wt),Tuple{Int64,Int64}},Array{PuMaS.Event{Float64,Float64
,Float64,Float64,Float64,Float64},1},Int64},StepRangeLen{Float64,Base.Twice
Precision{Float64},Base.TwicePrecision{Float64}},NamedTuple{(:conc, :dv),Tu
ple{Array{Float64,1},Array{Float64,1}}}},1}}(PuMaS.SimulatedObservations{Pu
MaS.Subject{StructArrays.StructArray{NamedTuple{(),Tuple{}}},1,NamedTuple{()
,Tuple{}}},NamedTuple{(:isPM, :Wt),Tuple{Int64,Int64}},Array{PuMaS.Event{Fl
oat64,Float64,Float64,Float64,Float64,Float64},1},Int64},StepRangeLen{Float
64,Base.TwicePrecision{Float64},Base.TwicePrecision{Float64}},NamedTuple{(:
conc, :dv),Tuple{Array{Float64,1},Array{Float64,1}}}}[SimulatedObservations
{Subject{StructArray{NamedTuple{(),Tuple{}}},1,NamedTuple{(),Tuple{}}},Named
Tuple{(:isPM, :Wt),Tuple{Int64,Int64}},Array{Event{Float64,Float64,Float64,
Float64,Float64,Float64},1},Int64},StepRangeLen{Float64,TwicePrecision{Floa
t64},TwicePrecision{Float64}},NamedTuple{(:conc, :dv),Tuple{Array{Float64,1
},Array{Float64,1}}}}(Subject
  ID: 1
  Events: 1
  Observations: 0
  Covariates: isPM, Wt
, 0.0:0.1:120.0, (conc = [0.0, 0.729178, 1.38952, 1.98735, 2.52843, 3.01799
, 3.46077, 3.86107, 4.22281, 4.54954 ... 0.45245, 0.451354, 0.45026, 0.4491
68, 0.44808, 0.446994, 0.44591, 0.44483, 0.443752, 0.442676], dv = [9.2934e
-9, 0.82438, 1.85971, 1.03861, 2.115, 3.56022, 4.08858, 3.58914, 4.48772, 3
.23587 ... 0.503902, 0.508107, 0.478315, 0.348275, 0.536031, 0.562746, 0.41
7846, 0.477359, 0.435768, 0.426195])), SimulatedObservations{Subject{Struct
Array{NamedTuple{(),Tuple{}}},1,NamedTuple{(),Tuple{}}},NamedTuple{(:isPM, :
Wt),Tuple{Int64,Int64}},Array{Event{Float64,Float64,Float64,Float64,Float64
,Float64},1},Int64},StepRangeLen{Float64,TwicePrecision{Float64},TwicePreci
sion{Float64}},NamedTuple{(:conc, :dv),Tuple{Array{Float64,1},Array{Float64
,1}}}}(Subject
  ID: 2
  Events: 1
  Observations: 0
  Covariates: isPM, Wt
, 0.0:0.1:120.0, (conc = [0.0, 0.361922, 0.694905, 1.00122, 1.28294, 1.5420
1, 1.78019, 1.99911, 2.20029, 2.38512 ... 0.60727, 0.606224, 0.60518, 0.604
138, 0.603098, 0.602059, 0.601022, 0.599987, 0.598954, 0.597923], dv = [-1.
14395e-8, 0.45181, 0.786159, 1.27764, 0.871541, 1.32584, 1.86144, 1.42189,
1.69654, 2.07526 ... 0.637028, 0.640555, 0.529206, 0.378685, 0.602126, 0.63
8773, 0.556894, 0.568587, 0.704131, 0.584633])), SimulatedObservations{Subj
ect{StructArray{NamedTuple{(),Tuple{}}},1,NamedTuple{(),Tuple{}}},NamedTuple
{(:isPM, :Wt),Tuple{Int64,Int64}},Array{Event{Float64,Float64,Float64,Float
64,Float64,Float64},1},Int64},StepRangeLen{Float64,TwicePrecision{Float64},
TwicePrecision{Float64}},NamedTuple{(:conc, :dv),Tuple{Array{Float64,1},Arr
ay{Float64,1}}}}(Subject
  ID: 3
  Events: 1
  Observations: 0
  Covariates: isPM, Wt
, 0.0:0.1:120.0, (conc = [0.0, 0.77546, 1.43968, 2.00834, 2.49491, 2.91094,
3.26639, 3.56979, 3.82848, 4.04876 ... 0.257021, 0.256357, 0.255694, 0.255
033, 0.254374, 0.253716, 0.253061, 0.252406, 0.251754, 0.251103], dv = [8.5
4521e-9, 0.879599, 1.5326, 1.96391, 2.60365, 0.90838, 3.56207, 2.37018, 3.2
7964, 4.25229 ... 0.238743, 0.274564, 0.262219, 0.322722, 0.193341, 0.27976
9, 0.281557, 0.176578, 0.26967, 0.25432])), SimulatedObservations{Subject{S
tructArray{NamedTuple{(),Tuple{}}},1,NamedTuple{(),Tuple{}}},NamedTuple{(:is
PM, :Wt),Tuple{Int64,Int64}},Array{Event{Float64,Float64,Float64,Float64,Fl

```

```

oat64,Float64},1},Int64},StepRangeLen{Float64,TwicePrecision{Float64},Twice
Precision{Float64}},NamedTuple{(:conc, :dv),Tuple{Array{Float64,1},Array{Fl
oat64,1}}}}(Subject
  ID: 4
  Events: 1
  Observations: 0
  Covariates: isPM, Wt
  , 0.0:0.1:120.0, (conc = [0.0, 0.678551, 1.26373, 1.76822, 2.20298, 2.57746
  , 2.89986, 3.17725, 3.41573, 3.6206 ... 0.551382, 0.550356, 0.549332, 0.548
  31, 0.547289, 0.546271, 0.545254, 0.54424, 0.543227, 0.542216], dv = [6.457
  06e-9, 0.752238, 1.1282, 1.52995, 1.93964, 2.19559, 2.96548, 3.27029, 3.208
  23, 3.91128 ... 0.593741, 0.669842, 0.712707, 0.536356, 0.474066, 0.620865,
  0.603265, 0.643726, 0.593435, 0.657224])), SimulatedObservations{Subject{S
  tructArray{NamedTuple{(),Tuple{}}},1,NamedTuple{(),Tuple{}}},NamedTuple{(:is
  PM, :Wt),Tuple{Int64,Int64}},Array{Event{Float64,Float64,Float64,Float64,Fl
  oat64,Float64},1},Int64},StepRangeLen{Float64,TwicePrecision{Float64},Twice
  Precision{Float64}},NamedTuple{(:conc, :dv),Tuple{Array{Float64,1},Array{Fl
  oat64,1}}}}(Subject
  ID: 5
  Events: 1
  Observations: 0
  Covariates: isPM, Wt
  , 0.0:0.1:120.0, (conc = [0.0, 0.704847, 1.31498, 1.84295, 2.29965, 2.69453
  , 3.03577, 3.33049, 3.58484, 3.8042 ... 0.575996, 0.574915, 0.573836, 0.572
  759, 0.571684, 0.570611, 0.56954, 0.568471, 0.567404, 0.566339], dv = [7.46
  286e-9, 0.870484, 1.06095, 2.00635, 2.30881, 2.98657, 2.76305, 3.22807, 3.0
  9006, 3.36156 ... 0.756032, 0.543685, 0.510593, 0.733823, 0.7235, 0.507981,
  0.589356, 0.424463, 0.657873, 0.385307])), SimulatedObservations{Subject{S
  tructArray{NamedTuple{(),Tuple{}}},1,NamedTuple{(),Tuple{}}},NamedTuple{(:is
  PM, :Wt),Tuple{Int64,Int64}},Array{Event{Float64,Float64,Float64,Float64,Fl
  oat64,Float64},1},Int64},StepRangeLen{Float64,TwicePrecision{Float64},Twice
  Precision{Float64}},NamedTuple{(:conc, :dv),Tuple{Array{Float64,1},Array{Fl
  oat64,1}}}}(Subject
  ID: 6
  Events: 1
  Observations: 0
  Covariates: isPM, Wt
  , 0.0:0.1:120.0, (conc = [0.0, 0.371111, 0.702565, 0.998552, 1.26282, 1.498
  72, 1.70926, 1.8971, 2.06466, 2.21407 ... 0.851569, 0.850548, 0.849528, 0.8
  4851, 0.847493, 0.846478, 0.845463, 0.84445, 0.843438, 0.842427], dv = [6.7
  4393e-9, 0.360352, 0.783443, 1.01854, 0.942222, 1.11593, 2.34172, 2.54843,
  2.47978, 1.70091 ... 0.954338, 1.00104, 0.510512, 0.842209, 1.06187, 0.8533
  33, 0.984699, 0.815559, 0.961517, 0.851323])), SimulatedObservations{Subjec
  t{StructArray{NamedTuple{(),Tuple{}}},1,NamedTuple{(),Tuple{}}},NamedTuple{(
  :isPM, :Wt),Tuple{Int64,Int64}},Array{Event{Float64,Float64,Float64,Float64
  ,Float64,Float64},1},Int64},StepRangeLen{Float64,TwicePrecision{Float64},Tw
  icePrecision{Float64}},NamedTuple{(:conc, :dv),Tuple{Array{Float64,1},Array
  {Float64,1}}}}(Subject
  ID: 7
  Events: 1
  Observations: 0
  Covariates: isPM, Wt
  , 0.0:0.1:120.0, (conc = [0.0, 0.648328, 1.21282, 1.70415, 2.13165, 2.50345
  , 2.82664, 3.10742, 3.35119, 3.56267 ... 0.51163, 0.510637, 0.509647, 0.508
  658, 0.507671, 0.506686, 0.505703, 0.504722, 0.503743, 0.502766], dv = [-1.
  24014e-8, 0.786094, 1.64821, 1.83204, 1.74729, 1.68114, 2.52244, 2.43087, 4
  .05953, 3.91379 ... 0.329432, 0.379354, 0.548085, 0.520046, 0.660907, 0.475
  851, 0.466824, 0.359359, 0.533765, 0.65386])), SimulatedObservations{Subjec
  t{StructArray{NamedTuple{(),Tuple{}}},1,NamedTuple{(),Tuple{}}},NamedTuple{(

```


```

:isPM, :Wt),Tuple{Int64,Int64}},Array{Event{Float64,Float64,Float64,Float64
,Float64,Float64},1},Int64},StepRangeLen{Float64,TwicePrecision{Float64},Tw
icePrecision{Float64}},NamedTuple{(:conc, :dv),Tuple{Array{Float64,1},Array
{Float64,1}}}}(Subject
  ID: 8
  Events: 1
  Observations: 0
  Covariates: isPM, Wt
, 0.0:0.1:120.0, (conc = [0.0, 1.33609, 2.48041, 3.45995, 4.29788, 5.0141,
5.62576, 6.14754, 6.59211, 6.97033 ... 0.287799, 0.28695, 0.286104, 0.28526
, 0.284418, 0.283579, 0.282743, 0.281909, 0.281077, 0.280248], dv = [-4.025
71e-8, 1.29123, 1.64654, 3.0992, 5.34063, 4.69692, 7.84568, 3.91446, 4.1135
6, 9.88473 ... 0.312626, 0.145839, 0.355418, 0.325724, 0.267007, 0.248355,
0.333758, 0.290667, 0.28733, 0.24323])), SimulatedObservations{Subject{Stru
ctArray{NamedTuple{(),Tuple{}},1,NamedTuple{(),Tuple{}}},NamedTuple{(:isPM,
:Wt),Tuple{Int64,Int64}},Array{Event{Float64,Float64,Float64,Float64,Float
64,Float64},1},Int64},StepRangeLen{Float64,TwicePrecision{Float64},TwicePre
cision{Float64}},NamedTuple{(:conc, :dv),Tuple{Array{Float64,1},Array{Float
64,1}}}}(Subject
  ID: 9
  Events: 1
  Observations: 0
  Covariates: isPM, Wt
, 0.0:0.1:120.0, (conc = [0.0, 0.792406, 1.48963, 2.10292, 2.64219, 3.11616
, 3.53256, 3.89818, 4.21902, 4.50036 ... 0.575644, 0.574449, 0.573257, 0.57
2067, 0.57088, 0.569696, 0.568513, 0.567334, 0.566156, 0.564982], dv = [-1.
22759e-8, 0.727147, 1.70424, 1.83412, 2.3937, 3.04355, 2.83978, 3.64647, 4.
92105, 3.81413 ... 0.725282, 0.506416, 0.593127, 0.808433, 0.528969, 0.6734
56, 0.409417, 0.468674, 0.507839, 0.439346])), SimulatedObservations{Subjec
t{StructArray{NamedTuple{(),Tuple{}},1,NamedTuple{(),Tuple{}}},NamedTuple{(:
isPM, :Wt),Tuple{Int64,Int64}},Array{Event{Float64,Float64,Float64,Float64
,Float64,Float64},1},Int64},StepRangeLen{Float64,TwicePrecision{Float64},Tw
icePrecision{Float64}},NamedTuple{(:conc, :dv),Tuple{Array{Float64,1},Array
{Float64,1}}}}(Subject
  ID: 10
  Events: 1
  Observations: 0
  Covariates: isPM, Wt
, 0.0:0.1:120.0, (conc = [0.0, 0.412254, 0.786366, 1.1258, 1.4337, 1.71293,
1.9661, 2.19557, 2.40349, 2.59182 ... 0.556691, 0.555702, 0.554714, 0.5537
28, 0.552743, 0.551761, 0.55078, 0.549801, 0.548823, 0.547848], dv = [-3.74
486e-8, 0.374697, 0.875346, 0.881369, 1.94601, 1.66904, 1.43351, 2.37134, 2
.33702, 2.15593 ... 0.509283, 0.602815, 0.540703, 0.521426, 0.509352, 0.498
394, 0.482031, 0.442769, 0.64733, 0.569325]))))

```

and visualize the output

```
plot(obs)
```



1.4 Multiple dose example

The additional dosage regimen controls of the NMTRAN format are available in `DosageRegimen`. For example, `ii` defines the "interdose interval", or the time distance between two doses, while `addl` defines how many additional times to repeat a dose. Thus, let's define a dose of 100 that's repeated 7 times at 24 hour intervals:

```
md = DosageRegimen(100,ii=24,addl=6)
```

```
PuMaS.DosageRegimen(1×8 DataFrames.DataFrame
  Row  time      cmt    amt    evid  ii      addl    rate    ss
      Float64  Int64  Float64  Int8  Float64  Int64  Float64  Int8

1     0.0      1     100.0    1     24.0    6     0.0    0
)
```

Let's create a new subject, `s3` with this dosage regimen:


```
s3 = Subject(id=3, evs=md, cvs=(isPM=0, Wt=70))
```

```
Subject
```

```
ID: 3
Events: 7
Observations: 0
Covariates: isPM, Wt
```

and see the results:

```
obs = simobs(model, s3, p, obstimes=0:0.1:240)
plot(obs)
```



1.5 Combining dosage regimens

We can also combine dosage regimens to build a more complex regimen. Recall from the introduction that using arrays will build the element-wise combinations. Thus let's build a dose of 500 into compartment 1 at time 0, and 7 doses into compartment 1 of 100 spaced by 24 hours:

```
ldmd = DosageRegimen([500,100],cmt=1, time=[0,24], addl=[0,6],ii=[0,24])
```

```
PuMaS.DosageRegimen(2x8 DataFrame.DataFrame
  Row  time      cmt    amt    evid  ii      addl    rate    ss
      Float64  Int64  Float64  Int8  Float64  Int64  Float64  Int8
```

```

1    0.0    1    500.0    1    0.0    0    0.0    0
2    24.0    1    100.0    1    24.0    6    0.0    0
)


```

Let's see if this result matches our intuition:

```

s4 = Subject(id=4, evs=ldmd, cvs=(isPM=0,Wt=70))
obs = simobs(model, s4, p, obstimes=0:0.1:120)
plot(obs, ylims=(0,50))

```




Another way to build complex dosage regimens is to combine previously constructed regimens into a single regimen. For example:

```

e1 = DosageRegimen(500,cmt=1, time=0, addl=0,ii=0)
e2 = DosageRegimen(100,cmt=1, time=24, addl=6,ii=24)
evs = DosageRegimen(e1,e2)
obs = simobs(model, s4, p, obstimes=0:0.1:120)
plot(obs, ylims=(0,50))

```



is the same regimen as before.

Putting these ideas together, we can define a population where individuals with different covariates undergo different regimens, and simulate them all together with automatic parallelism:

```
e1 = DosageRegimen(100, ii=24, addl=6)
e2 = DosageRegimen(50, ii=12, addl=13)
e3 = DosageRegimen(200, ii=24, addl=2)
```

```
PuMaS.DosageRegimen(1x8 DataFrames.DataFrame
Row time cmt amt evid ii addl rate ss
Float64 Int64 Float64 Int8 Float64 Int64 Float64 Int8
1 0.0 1 200.0 1 24.0 2 0.0 0
)
```

```
pop1 = Population(map(i -> Subject(id=i, evs=e1, cvs=choose_covariates()), 1:5))
pop2 = Population(map(i -> Subject(id=i, evs=e2, cvs=choose_covariates()), 6:8))
pop3 = Population(map(i -> Subject(id=i, evs=e3, cvs=choose_covariates()), 9:10))
pop = Population(vcat(pop1, pop2, pop3))
```

```
10-element PuMaS.Population{PuMaS.Subject{StructArrays.StructArray{NamedTup
```



```
le{(),Tuple{}},1,NamedTuple{(),Tuple{}}},NamedTuple{(:isPM, :Wt),Tuple{Int64,Int64}},Array{PuMaS.Event{Float64,Float64,Float64,Float64,Float64,Float64},1},Int64}}:
```

Subject

ID: 1

Events: 7

Observations: 0

Covariates: isPM, Wt

Subject

ID: 2

Events: 7

Observations: 0

Covariates: isPM, Wt

Subject

ID: 3

Events: 7

Observations: 0

Covariates: isPM, Wt

Subject

ID: 4

Events: 7

Observations: 0

Covariates: isPM, Wt

Subject

ID: 5

Events: 7

Observations: 0

Covariates: isPM, Wt

Subject

ID: 6

Events: 14

Observations: 0

Covariates: isPM, Wt

Subject

ID: 7

Events: 14

Observations: 0

Covariates: isPM, Wt

Subject

ID: 8

Events: 14

Observations: 0

Covariates: isPM, Wt

Subject

ID: 9

Events: 3

Observations: 0


Covariates: isPM, Wt

Subject

ID: 10

```
Events: 3
Observations: 0
Covariates: isPM, Wt
```

```
obs = simobs(model,pop,p,obstimes=0:0.1:120)
plot(obs)
```



1.6 Defining Infusions

As specified in the NMTRAN format, an infusion is a dosage which is defined as having a non-zero positive rate at which the drug enters the system. Let’s define a single infusion dose of total amount 100 with a rate of 3 into the second compartment:


```
inf = DosageRegimen(100, rate=3, cmt=2)
```

```
PuMaS.DosageRegimen(1x8 DataFrames.DataFrame
  Row  time      cmt  amt      evid  ii      addl    rate    ss
      Float64  Int64  Float64  Int8   Float64  Int64   Float64  Int8

1  0.0        2    100.0      1     0.0      0      3.0    0
)
```

Now let's simulate a subject undergoing this treatment strategy:

```
s5 = Subject(id=5, evs=inf, cvs=(isPM=0,Wt=70))
obs = simobs(model, s5, p, obstimes=0:0.1:120)
plot(obs)
```



1.7 Final Note on Julia Programming

Note that all of these functions are standard Julia functions, and thus standard Julia programming constructions can be utilized to simplify the construction of large populations. We already demonstrated the use of `map` and a comprehension, but we can also make use of constructs like `for` loops.

1.8 Conclusion

This tutorial shows the tools for generating populations of infinite complexity, defining covariates and dosage regimens on the fly and simulating the results of the model.