

## Java test classes

### CardNodeTest.java

```
package test;

import junit.framework.TestCase;
import main.Card;
import main.CardNode;
import main.House;
import main.Rank;

/**
 * Unit tests for CardNode Class
 */
public class CardNodeTest extends TestCase {

    /**
     * Test Get Data returns the correct card.
     */
    public void testGetData() {
        Card testCard = new Card(House.CLUBS, Rank.ACE);
        CardNode cardNodeTest = new CardNode(testCard);

        var expected = testCard.toString();
        var actual = cardNodeTest.getData().toString();

        assertEquals(expected, actual);
    }

    /**
     * Test Set Data, sets the data to the supplied Card.
     */
    public void testSetData() {
        Card testCard = new Card(House.CLUBS, Rank.ACE);
        CardNode cardNodeTest = new CardNode(null);

        //set the data
        cardNodeTest.setData(testCard);

        var expected = testCard.toString();
        var actual = cardNodeTest.getData().toString();

        //Assert
        assertEquals(expected, actual);
    }

    /**
     * Test get next Card Node returns the next CardNode
     */
    public void testGetNext() {
        Card testCard = new Card(House.CLUBS, Rank.ACE);
        Card testNextCard = new Card(House.CLUBS, Rank.TWO);
        CardNode cardNodeTest = new CardNode(testCard);

        //set next
        cardNodeTest.setNext(new CardNode(testNextCard));
    }
}
```

```

        var expected = testNextCard.toString();
        var actual = cardNodeTest.getNext().getData().toString();

        //Assert
        assertEquals(expected, actual);
    }

    /**
     * test Set Next CardNode sets the correct next cardNode
     */
    public void testSetNext() {
        Card testCard = new Card(House.CLUBS, Rank.ACE);
        Card testNextCard = new Card(House.CLUBS, Rank.TWO);
        CardNode cardNodeTest = new CardNode(testCard);

        //set next
        cardNodeTest.setNext(new CardNode(testNextCard));

        var expected = testNextCard.toString();
        var actual = cardNodeTest.getNext().getData().toString();

        //Assert
        assertEquals(expected, actual);
    }
}

```

## CardSlotsBagTest.java

```

package test;

import main.Card;
import main.CardSlotsBag;
import main.House;
import main.Rank;
import org.junit.Assert;
import org.junit.Test;

/**
 * Units test for all the methods in CardSlotsBag
 */
public class CardSlotsBagTest {

    private Card testCard1 = new Card(House.CLUBS, Rank.ACE);
    private Card testCard2 = new Card(House.DIAMONDS, Rank.TWO);
    private Card testCard3 = new Card(House.SPADES, Rank.KING);

    private Card testCardElevensPair1 = new Card(House.SPADES, Rank.ACE);
    private Card testCardElevensPair2 = new Card(House.SPADES, Rank.TEN);

    private Card testKing = new Card(House.SPADES, Rank.KING);
    private Card testQueen = new Card(House.SPADES, Rank.QUEEN);
    private Card testJack = new Card(House.SPADES, Rank.JACK);

    /**
     * Test 1 Assert containsCardValue() returns true when it finds a card
     with the same int value
     * Test 2 Assert containsCardValue() returns false when it does not
     find a card with the input in value.
     */
    @Test

```

```

public void containsCardValue() {
    CardSlotsBag bag = new CardSlotsBag();
    bag.addNewEntry(testCard1);

    //Test 1 Assert containsCardValue() returns true when it finds a
card with the same int value
    Assert.assertTrue(bag.containsCardValue(1));

    //Test 2 Assert containsCardValue() returns false when it does not
find a card with the input in value.
    Assert.assertFalse(bag.containsCardValue(2));
}

/**
 * Test 1 Assert findsAndReturnsCardValue() finds and returns a card
value when the asked for card are present
 * Test 2 Assert findsAndReturnsCardValue() returns null when the asked
for cards are not in the bag
 */
@Test
public void findsAndReturnsCardValue() {
    CardSlotsBag bag = new CardSlotsBag();
    bag.addNewEntry(testCard1);

    //Test 1 Assert findsAndReturnsCardValue() finds and returns a card
value when the asked for card are present
    Assert.assertEquals(bag.findsAndReturnsCardValue(1), testCard1);

    //Test 2 Assert findsAndReturnsCardValue() returns null when the
asked for cards are not in the bag
    CardSlotsBag bag2 = new CardSlotsBag();
    Assert.assertNull(bag2.findsAndReturnsCardValue(1));
}

/**
 * Test 1 Assert containsKingQueenJack() should return false when there
is no face cards in the bag
 * Test 2 Assert containsKingQueenJack() should return false when there
is only a King and a Queen in the bag.
 * Test 3 Assert containsKingQueenJack() should return true when there
is a King Queen and a Jack in the bag
 */
@Test
public void containsKingQueenJack() {
    CardSlotsBag bag = new CardSlotsBag();

    //Test 1 Assert containsKingQueenJack() should return false when
there is no face cards in the bag.
    Assert.assertFalse(bag.containsKingQueenJack());

    //Test 2 Assert containsKingQueenJack() should return false when
there is only a King and a Queen in the bag
    bag.addNewEntry(testKing);
    bag.addNewEntry(testQueen);
    Assert.assertFalse(bag.containsKingQueenJack());

    //Test 3 Assert containsKingQueenJack() should return true when
there is a King Queen and a Jack in the bag
    bag.addNewEntry(testJack);
    Assert.assertTrue(bag.containsKingQueenJack());
}

```

```

    /**
     * Test 1 Assert findAndReturnKingQueenJackPair() returns null when the
     bag does not contain a King Queen Jack set.
     * Test 2 Assert findAndReturnKingQueenJackPair() finds and returns a
     card King Queen Jack set are in the bag.
     */
    @Test
    public void findAndReturnKingQueenJackPair() {
        CardSlotsBag bag = new CardSlotsBag();

        //Test 1 Assert findAndReturnKingQueenJackPair() returns null when
the bag does not contain a King Queen Jack set.
        Assert.assertNull(bag.findAndReturnKingQueenJackPair());

        //Test 2 Assert findAndReturnKingQueenJackPair() finds and returns
a card King Queen Jack set are in the bag.
        Card[] test2Expected = {testKing, testQueen, testJack};
        bag.addNewEntry(testKing);
        bag.addNewEntry(testQueen);
        bag.addNewEntry(testJack);

        Assert.assertEquals(test2Expected,
bag.findAndReturnKingQueenJackPair());
    }

    /**
     * Test 1 Assert containsElevensPair() returns null when it cant find a
     valid elevens pair when the bag is empty
     * Test 2 Assert containsElevensPair() returns false when the bag does
     not contain an elevens pair
     * Test 3 Assert containsElevensPair() returns true when the bag
     contains an elevens pair
     */
    @Test
    public void containsElevensPair() {
        CardSlotsBag bag = new CardSlotsBag();

        //Test 1 Assert containsElevensPair() returns null when it cant
find a valid elevens pair when the bag is empty
        Assert.assertFalse(bag.containsElevensPair());

        //Test 2 Assert containsElevensPair() returns false when the bag
does not contain an elevens pair
        bag.addNewEntry(testCard2);
        bag.addNewEntry(testCard3);
        Assert.assertFalse(bag.containsElevensPair());

        //Test 3 Assert containsElevensPair() returns true when the bag
contains an elevens pair
        bag.addNewEntry(testCardElevensPair1);
        bag.addNewEntry(testCardElevensPair2);
        Assert.assertTrue(bag.containsElevensPair());
    }

    /**
     * Test 1 Assert returns null when it cant find a valid elevens pair
     when the bag is empty
     * Test 2 Assert returns null when it cant find a valid elevens pair.
     * Test 3 Assert findAndReturnElevensPair() returns the found elevens
     pair cards

```

```

    */
    @Test
    public void findAndReturnElevensPair() {
        CardSlotsBag bag = new CardSlotsBag();

        //Test 1 Assert returns null when it cant find a valid elevens pair
        when the bag is empty
        Assert.assertNull(bag.findAndReturnElevensPair());

        //Test 2 Assert returns null when it cant find a valid elevens
        pair.
        bag.addNewEntry(testCard2);
        bag.addNewEntry(testCard3);
        Assert.assertNull(bag.findAndReturnElevensPair());

        //Test 3 Assert findAndReturnElevensPair() returns the found
        elevens pair cards
        bag.addNewEntry(testCardElevensPair1);
        bag.addNewEntry(testCardElevensPair2);
        Card[] test2Expected = {testCardElevensPair1,
        testCardElevensPair2};
        Assert.assertEquals(bag.findAndReturnElevensPair(), test2Expected);
    }

    /**
     * Test 1 Assert that countCards() returns 0 when there is zero cards
     * Test 2 Assert that countCards() returns 2 when there is 2 cards
     * Test 3 Assert that countCards() returns 9 when the bag is full
     */
    @Test
    public void countCards() {
        CardSlotsBag bag = new CardSlotsBag();

        //Test 1 Assert that countCards() returns 0 when there is zero
        cards
        Assert.assertEquals(bag.countCards(), 0);

        //Test 2 Assert that countCards() returns 2 when there is 2 cards
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        Assert.assertEquals(bag.countCards(), 2);

        //Test 3 Assert that countCards() returns 9 when the bag is full
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        Assert.assertEquals(bag.countCards(), 9);
    }

    /**
     * Test 1 Assert that countEmptySlots() returns 9 when there is zero
     cards in the bag.
     * Test 2 Assert that countEmptySlots() returns 2 when there is 2 empty
     slots
     * Test 3 Assert that countEmptySlots() returns 0 when the bag is full
     */
    @Test

```

```

public void countEmptySlots() {
    CardSlotsBag bag = new CardSlotsBag();

    //Fill up the cardSlotBag
    bag.addNewEntry(testCard1);
    bag.addNewEntry(testCard1);
    bag.addNewEntry(testCard1);
    bag.addNewEntry(testCard1);
    bag.addNewEntry(testCard1);
    bag.addNewEntry(testCard1);
    bag.addNewEntry(testCard1);
    bag.addNewEntry(testCard1);

    //Test 1 Assert that countEmptySlots() returns 9 when there is zero
cards in the bag.
    Assert.assertEquals(bag.countEmptySlots(),0);

    //Test 2 Assert that countEmptySlots() returns 2 when there is 2
empty slots
    bag.remove();
    bag.remove();
    Assert.assertEquals(bag.countEmptySlots(),2);

    //Test 3 Assert that countEmptySlots() returns 0 when the bag is
full
    bag.remove();
    bag.remove();
    bag.remove();
    bag.remove();
    bag.remove();
    bag.remove();
    bag.remove();
    Assert.assertEquals(bag.countEmptySlots(),9);
}

/**
 * Test 1 Assert cardAtPosition() returns null when the slot asked for
is empty.
 * Test 2 Assert cardAtPosition() returns a Card at the correct
position when the slot is not empty
 */
@Test
public void cardAtPosition() {
    CardSlotsBag bag = new CardSlotsBag();

    //Test 1 Assert cardAtPosition() returns null when the slot asked
for is empty.
    Assert.assertNull(bag.cardAtPosition(0));

    //Test 2 Assert cardAtPosition() returns a Card at the correct
position when the slot is not empty
    bag.addNewEntry(testCard1);
    Assert.assertEquals(bag.cardAtPosition(0),testCard1);
}

/**
 * Test 1 Assert getCurrentSize() returns 0 when bag is empty
 * Test 2 Assert getCurrentSize() returns 2 when bag has 2 cards
 * Test 3 Assert getCurrentSize() returns 9 when the bag is full
 * Test 4 Assert getCurrentSize() returns 8 when 1 card is removed

```

```

    */
    @Test
    public void getCurrentSize() {
        CardSlotsBag bag = new CardSlotsBag();

        //Test 1 Assert getCurrentSize() returns 0 when bag is empty
        Assert.assertEquals(bag.getCurrentSize(), 0);

        //Test 2 Assert getCurrentSize() returns 2 when bag has 2 cards
        bag.addNewEntry(testCard1);
        Assert.assertEquals(bag.getCurrentSize(), 1);

        //Test 3 Assert getCurrentSize() returns 9 when the bag is full
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        Assert.assertEquals(bag.getCurrentSize(), 9);

        //Test 4 Assert getCurrentSize() returns 8 when 1 card is removed
        bag.remove();
        Assert.assertEquals(bag.getCurrentSize(), 8);
    }

    /**
     * Test 1 Assert Test 1 is isEmpty() returns true when it is empty
     * Test 2 Assert Test 2 isEmpty() returns false when it is not empty
     */
    @Test
    public void isEmpty() {
        CardSlotsBag bag = new CardSlotsBag();

        //Assert is isEmpty() returns true when it is empty
        Assert.assertTrue(bag.isEmpty());

        //Assert is isEmpty() returns false when it is not empty
        bag.addNewEntry(testCard1);
        Assert.assertFalse(bag.isEmpty());
    }

    /**
     * Test 1: Assert that addNewEntry() adds a new card to an empty that
has card but is not full.
     * Test 2: Assert that addNewEntry() does not add a new card to a bag
that is full.
     */
    @Test
    public void addNewEntry() {
        //Assert that addNewEntry() adds a new card to an empty bag
        CardSlotsBag bag = new CardSlotsBag();

        //Test 1: test that addNewEntry() adds a new card to an empty that
has card but is not full
        //Assert that the bag is empty
        Assert.assertTrue(bag.isEmpty());

        //add the card

```

```

        bag.addNewEntry(testCard1);

        //Assert that the addNewEntry(testCard1) add the card to the bag.
        Assert.assertEquals(bag.cardAtPosition(0),testCard1);

        //Test 2: test that addNewEntry() does not add a new card to a bag
that is full.
        //fill the bag until its full, add 8 more cards
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);

        //Assert that testCard2 does not get added when the bag contains is
full
        //Assert that the bag is full
        Assert.assertTrue(bag.isArrayFull());

        //try to add testCard2
        bag.addNewEntry(testCard2);

        //Assert that the bag does not contain testCard2
        Assert.assertFalse(bag.contains(testCard2));
    }

    /**
     * Test 1 Assert that isArrayFull() returns false when it is not full
but is empty.
     * Test 2 Assert that isArrayFull() returns false when it is not full
but has 1 card.
     * Test 3 Assert that isArrayFull() returns true when it is full
     */
    @Test
    public void isArrayFull() {
        CardSlotsBag bag = new CardSlotsBag();

        //Assert that isArrayFull() returns false when it is not full but
is empty.
        Assert.assertFalse(bag.isArrayFull());

        //Assert that isArrayFull() returns false when it is not full but
has 1 card.
        bag.addNewEntry(testCard1);
        Assert.assertFalse(bag.isArrayFull());

        //Add 8 more cards to fill up the bag.
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);
        bag.addNewEntry(testCard1);

        //Assert that isArrayFull() returns true when it is full
        Assert.assertTrue(bag.isArrayFull());
    }

```



```

    }

    /**
     * Testing the remove(), which takes no params that it removes the last
     card in the bag
     */
    @Test
    public void remove() {
        CardSlotsBag bag = new CardSlotsBag();
        bag.addNewEntry(testCard1);

        //Assert bag is not empty
        Assert.assertFalse(bag.isEmpty());

        //Assert that remove removes the last element in the bag, and
        assert bag is now empty.
        bag.remove();
        Assert.assertTrue(bag.isEmpty());

        //Assert that removing when the bag is empty, should still be empty
        bag.remove();
        Assert.assertTrue(bag.isEmpty());
    }

    /**
     * Testing the remove(Card aCard), that it removes the last card in the
     bag
     */
    @Test
    public void testRemove() {
        CardSlotsBag bag = new CardSlotsBag();
        bag.addNewEntry(testCard1);

        //Assert bag is not empty
        Assert.assertFalse(bag.isEmpty());

        //Assert that remove remove(param) is called the last element in
        the bag, and assert bag is now empty.
        bag.remove(testCard1);
        Assert.assertTrue(bag.isEmpty());

        //Assert that remove(param) is called when the card cant be found,
        does not remove any cards in the bag
        bag.addNewEntry(testCard1);
        bag.remove(testCard2);
        Assert.assertFalse(bag.isEmpty());

        //Assert that remove(param) does remove a card when it can be found
        and the bag is now empty
        bag.remove(testCard1);
        Assert.assertTrue(bag.isEmpty());
    }

    /**
     * Test, clear(), clears the CardSlotsBag
     */
    @Test
    public void clear() {
        CardSlotsBag bag = new CardSlotsBag();
        bag.addNewEntry(new Card(House.CLUBS, Rank.ACE));
    }

```

```

        //Assert bag is not empty
        Assert.assertFalse(bag.isEmpty());

        //Assert bag is empty after clear()
        bag.clear();
        var expected = true;
        var actual = bag.isEmpty();
        Assert.assertEquals(expected, actual);
    }

    /**
     * Test that contains() returns true when it finds a card and false
    when it does not.
     */
    @Test
    public void contains() {
        /*
         * Test 1, Assert that contains returns true when the bag contains
    the input card.
         */
        CardSlotsBag bag = new CardSlotsBag();
        bag.addNewEntry(testCard1);

        //Assert that bag does Contain a card of Card(House.CLUBS,
    Rank.ACE)
        var actual = bag.contains(testCard1);
        var expected = true;

        Assert.assertEquals(expected, actual);

        /*
         * Test 2, Assert that contains returns false when the bag does not
    contain the input card.
         */
        CardSlotsBag bag2 = new CardSlotsBag();
        var actual2 = bag2.contains(testCard1);
        var expected2 = false;
        Assert.assertEquals(expected2, actual2);
    }

    /**
     * Test that toArrayCopy can copy the bag object
     */
    @Test
    public void toArrayCopy() {
        //Assert that toArrayCopy() creates a new Card[] of size 9
        CardSlotsBag bag = new CardSlotsBag();

        //Create expected and set first slot in array.
        Card[] expectedCardArray = new Card[9];
        expectedCardArray[0] = testCard1;

        //Add testCard1
        bag.addNewEntry(testCard1);

        //Assert that toArrayCopy() creates a new Card[] of size 9
        var actual = bag.toArrayCopy();
        Assert.assertEquals(9, actual.length);

        //Assert that bag.toArrayCopy() when testCard1 has been added

```

```

equals expectedCardArray
    Assert.assertEquals(actual, expectedCardArray);
}

/**
 * Test that display does not crash the application by calling
 * .display()
 * as we cant test system.out without illegal libraries
 */
@Test
public void display() {

    CardSlotsBag bag = new CardSlotsBag();
    bag.addNewEntry(testCard1);

    //Assert that .display(true), does not crash the application
    bag.display(true);

    //Assert that .display(true), does not crash the application
    bag.display(false);
}
}

```

## CardTest.java

```

package test;

import junit.framework.TestCase;
import main.Card;
import main.House;
import main.Rank;

/**
 * Unit tests for Card Class
 */
public class CardTest extends TestCase {
    private Card test1Card = new Card(House.CLUBS, Rank.ACE);
    private Card test2Card = new Card(House.DIAMONDS, Rank.TWO);
    private Card test3Card = new Card(House.DIAMONDS, Rank.KING);

    /**
     * Test ToString
     */
    public void testToString() {

        /*
         new Card(House.CLUBS, Rank.ACE).ToString() should equal "Ace of
         Clubs"
         */
        assertEquals(test1Card.toString(), "Ace of Clubs");

        /*
         new Card(House.DIAMONDS, Rank.TWO).ToString() should equal "2 of
         Diamonds"
         */
        assertEquals(test2Card.toString(), "2 of Diamonds");
    }

    /**
     * Test getHouse()
     */
}

```

```

    */
    public void testGetHouse() {

        /*
            test that a new Card(House.CLUBS, Rank.ACE).getHouse() should
            equal House.CLUBS
        */
        assertEquals(test1Card.getHouse(), House.CLUBS);

        /*
            test that a new Card(House.DIAMONDS, Rank.TWO).getHouse()
            should equal House.DIAMONDS
        */
        assertEquals(test2Card.getHouse(), House.DIAMONDS);
    }

    /**
     * Test getRank()
     */
    public void testGetRank() {
        /*
            test that a new Card(House.CLUBS, Rank.ACE).getRank() should
            equal ,Rank.ACE
        */
        assertEquals(test1Card.getRank(), Rank.ACE);

        /*
            test that a new Card(House.DIAMONDS, Rank.TWO).getRank() should
            equal Rank.TWO
        */
        assertEquals(test2Card.getRank(), Rank.TWO);

        /*
            test that a new Card(House.DIAMONDS, Rank.KING).getRank()
            should equal Rank.KING
        */
        assertEquals(test3Card.getRank(), Rank.KING);
    }

    /**
     * Test extractRankAsDigit() returns the correct Digit, Face cards and
     * A should return a letter and
     * all other cards should return a number
     */
    public void testExtractRankAsDigit() {
        assertEquals(Card.extractRankAsDigit(test1Card), "A"); // ace card
        assertEquals(Card.extractRankAsDigit(test2Card), "2"); // number
card
        assertEquals(Card.extractRankAsDigit(test3Card), "K"); // face card
    }

    /**
     * Test extractHouseAsDigit() returns the correct colored Digit
     */
    public void testExtractHouseAsDigit() {
        String COLOR_RED = "\u001B[31m";
        String COLOR_GREEN = "\u001B[32m";
        String COLOR_WHITE = "\u001B[0m";

        assertEquals(Card.extractHouseAsDigitWithColor(test1Card).toString(),
            COLOR_GREEN + "C" + COLOR_WHITE);
    }

```

```

assertEquals(Card.extractHouseAsDigitWithColor(test2Card).toString(),
COLOR_RED + "D" + COLOR_WHITE);
    }
}

```

## DeckTest.java

```

package test;

import junit.framework.TestCase;
import main.Card;
import main.Deck;
import main.House;
import main.Rank;
import org.junit.Test;

/**
 * Units test for the class Deck
 */
public class DeckTest extends TestCase {

    //A valid array of cards
    private Card[] validDeckOfCardsArray = {
        new Card(House.SPADES, Rank.KING), new Card(House.SPADES,
Rank.QUEEN), new Card(House.SPADES, Rank.JACK), new Card(House.SPADES,
Rank.TEN),
        new Card(House.SPADES, Rank.NINE), new Card(House.SPADES,
Rank.EIGHT), new Card(House.SPADES, Rank.SEVEN), new Card(House.SPADES,
Rank.SIX),
        new Card(House.SPADES, Rank.FIVE), new Card(House.SPADES,
Rank.FOUR), new Card(House.SPADES, Rank.THREE), new Card(House.SPADES,
Rank.TWO),
        new Card(House.SPADES, Rank.ACE), new Card(House.DIAMONDS,
Rank.KING), new Card(House.DIAMONDS, Rank.QUEEN), new Card(House.DIAMONDS,
Rank.JACK),
        new Card(House.DIAMONDS, Rank.TEN), new Card(House.DIAMONDS,
Rank.NINE), new Card(House.DIAMONDS, Rank.EIGHT), new Card(House.DIAMONDS,
Rank.SEVEN),
        new Card(House.DIAMONDS, Rank.SIX), new Card(House.DIAMONDS,
Rank.FIVE), new Card(House.DIAMONDS, Rank.FOUR), new Card(House.DIAMONDS,
Rank.THREE),
        new Card(House.DIAMONDS, Rank.TWO), new Card(House.DIAMONDS,
Rank.ACE), new Card(House.CLUBS, Rank.KING), new Card(House.CLUBS,
Rank.QUEEN),
        new Card(House.CLUBS, Rank.JACK), new Card(House.CLUBS,
Rank.TEN), new Card(House.CLUBS, Rank.NINE), new Card(House.CLUBS,
Rank.EIGHT),
        new Card(House.CLUBS, Rank.SEVEN), new Card(House.CLUBS,
Rank.SIX), new Card(House.CLUBS, Rank.FIVE), new Card(House.CLUBS,
Rank.FOUR),
        new Card(House.CLUBS, Rank.THREE), new Card(House.CLUBS,
Rank.TWO), new Card(House.CLUBS, Rank.ACE), new Card(House.HEARTS,
Rank.KING),
        new Card(House.HEARTS, Rank.QUEEN), new Card(House.HEARTS,
Rank.JACK), new Card(House.HEARTS, Rank.TEN), new Card(House.HEARTS,
Rank.NINE),
        new Card(House.HEARTS, Rank.EIGHT), new Card(House.HEARTS,
Rank.SEVEN), new Card(House.HEARTS, Rank.SIX), new Card(House.HEARTS,
Rank.FIVE),
        new Card(House.HEARTS, Rank.FOUR), new Card(House.HEARTS,

```

```

Rank.THREE), new Card(House.HEARTS, Rank.TWO), new Card(House.HEARTS,
Rank.ACE)
};

/**
 * Utility method used in this test file to check if a card is within a
 * Card Array, as we cant use Java.Arrays Lib.
 *
 * @param card card to search for.
 * @return true if the input card can be found in the valid array of
 * card
 */
private boolean validArrayOfCardsContains(Card card) {
    boolean found = false;
    for (int i = 0; i < validDeckOfCardsArray.length; i++) {
        if
(card.toString().equals(validDeckOfCardsArray[i].toString())) {
            found = true;
            break;
        }
    }
    return found;
}

/**
 * Test that create fullDeckOfCards creates a valid deck of cards.\
 */
@Test
public void testCreateFullDeckOfCards() {
    //Setup test
    Deck actualDeck = new Deck();
    Deck expectedDeck = new Deck();

    //Actual
    actualDeck.createFullDeckOfCards();

    //for each house, loop through each rank and push that card to the
    stack.
    for (Card card : validDeckOfCardsArray) {
        expectedDeck.push(card);
    }

    Card[] actualAsArray = actualDeck.toArray();
    Card[] expectedAsArray = expectedDeck.toArray();

    // We had to do this as we could not use the library Arrays.
    // this was the only successful solution we could find without
    using illegal libraries, as we are not allowed to use an java collections.
    boolean testResult = true;
    for (int i = 0; i < actualAsArray.length; i++) {
        if (actualAsArray[i].getHouse() !=
expectedAsArray[i].getHouse() && actualAsArray[i].getRank() !=
expectedAsArray[i].getRank()) {
            testResult = false;
        }
    }

    //Assert
    assertTrue(testResult);
}

```

```

/**
 * 1. Test push() can push a card to an empty deck.
 * 2. Test push() can push a card to a stack with a top Card already
existing.
 */
@Test
public void testPush() {
    //Setup test
    Deck testDeck = new Deck();

    testDeck.push(new Card(House.SPADES, Rank.ACE));

    //Assertions
    //1. Test push() can push a card to an empty deck..
    assertEquals("Ace of Spades", testDeck.peek().toString());

    testDeck.push(new Card(House.SPADES, Rank.TWO));

    //2. Test push() can push a card to a stack with a top Card already
existing.
    assertEquals("2 of Spades", testDeck.peek().toString());
}

/**
 * 1. Test that pop() removes a card and returns it from the top of the
deck.
 * 2. Test that pop() returns null when there is no top card.
 */
@Test
public void testPop() {
    //Setup test
    Deck testDeck = new Deck();
    testDeck.push(new Card(House.SPADES, Rank.ACE));

    var actual = testDeck.pop();
    var expected = new Card(House.SPADES, Rank.ACE);

    //1. Test that pop() removes a card and returns it from the top of
the deck.
    assertEquals(actual.toString(), expected.toString());

    //2. Test that pop() returns null when there is no top card.
    assertNull(testDeck.peek());
}

/**
 * Test to peek the top card of a deck, should return the top card of
the deck, and not remove it
 */
@Test
public void testPeek() {
    //Setup test
    Deck testDeck = new Deck();
    testDeck.push(new Card(House.SPADES, Rank.ACE));

    var testPeek = testDeck.peek();

    //Assert peek top card
    assertEquals("Ace of Spades", testPeek.toString());

    //Second Assert to make sure the last peek did not remove the Card.

```

```

        assertEquals("Ace of Spades", testPeek.toString());
    }

    /**
     * Test to check if isEmpty returns true when a deck is empty
     */
    @Test
    public void testIsEmpty() {
        //Setup test
        Deck testDeck = new Deck();

        //Assert
        assertTrue(testDeck.isEmpty());
    }

    /**
     * Make sure .clear() clears the deck
     */
    @Test
    public void testClear() {
        //Setup test
        Deck testDeck = new Deck();

        testDeck.push(new Card(House.SPADES, Rank.ACE));

        testDeck.clear();

        //Assert
        assertNull(testDeck.peek());
    }

    /**
     * Test rigorousShuffle() to make sure the deck is not altered, eg a
     * card is remove and the deck is no longer
     * a valid 52 card deck.
     */
    @Test
    public void testRigorousShuffle() {
        Deck actualDeck = new Deck();
        actualDeck.createFullDeckOfCards();

        //shuffle
        actualDeck.rigorousShuffle();

        //make sure shuffle does alter the deck.
        Card[] actualAsArray = actualDeck.toArray();

        // We had to do this as we could not use the library Arrays.
        boolean testResult = true;
        for (int i = 0; i < actualAsArray.length; i++) {
            if (!validArrayOfCardsContains(actualAsArray[i])) {
                //set to false if we cant find the card.
                testResult = false;
            }
        }

        //Assert
        assertTrue(testResult);
    }
}

```



## GameMechanicsTest.java

```
package test;

import main.Card;
import main.GameMechanics;
import main.House;
import main.Rank;
import org.junit.Assert;
import org.junit.Test;

import static org.junit.Assert.*;

/**
 * Unit tests for GameMechanics Class
 */
public class GameMechanicsTest {

    private Card testCardAce = new Card(House.CLUBS, Rank.ACE);
    private Card testCardTen = new Card(House.CLUBS, Rank.TEN);
    private Card testCardKing = new Card(House.CLUBS, Rank.KING);
    private Card testCardQueen = new Card(House.CLUBS, Rank.QUEEN);
    private Card testCardJack = new Card(House.CLUBS, Rank.JACK);

    /**
     * Unit test for isFaceCard
     *
     * Test 1, returns true when the card param is a face Card.
     * Test 2, returns false when the card param is a not a face Card.
     */
    @Test
    public void isFaceCard() {
        //Test 1, returns true when the card param is a face Card.
        Assert.assertTrue(GameMechanics.isFaceCard(testCardKing));

        //Test 2, returns false when the card param is a not a face Card.
        Assert.assertFalse(GameMechanics.isFaceCard(testCardAce));
    }

    /**
     * Unit Test for isFacePairs
     *
     * Test 1, returns true when the cards supplied are face pairs eg King,
     * Queen and Jack.
     * Test 2, returns false when the cards supplied are not face pairs.
     * Test 3, returns false when the cards supplied are not face pairs and
     * one is null.
     */
    @Test
    public void isFacePairs() {
        //Test 1, returns true when the cards supplied are face pairs eg
        King, Queen and Jack.
        Assert.assertTrue(GameMechanics.isFacePairs(testCardKing,
        testCardJack, testCardQueen));

        //Test 2, returns false when the cards supplied are not face pairs.
        Assert.assertFalse(GameMechanics.isFacePairs(testCardAce,
        testCardJack, testCardQueen));

        //Test 3, returns false when the cards supplied are not face pairs
        and one is null.
    }
}
```

```

        Assert.assertFalse(GameMechanics.isFacePairs(testCardAce,
testCardJack, null));
    }

    /**
     * Unit tests for isElevensPair
     *
     * Test 1, returns true when isElevensPair() input params are an
     elevens pair
     * Test 2, returns false when isElevensPair() input params are not an
     elevens pair
     * Test 3, returns false when isElevensPair() input params are not an
     elevens pair and 1 is null
     */
    @Test
    public void isElevensPair() {
        //Test 1, returns true when isElevensPair() input params are an
        elevens pair
        Assert.assertTrue(GameMechanics.isElevensPair(testCardAce,
testCardTen));

        //Test 2, returns false when isElevensPair() input params are not
        an elevens pair
        Assert.assertFalse(GameMechanics.isElevensPair(testCardAce,
testCardJack));

        //Test 3, returns false when isElevensPair() input params are not
        an elevens pair and 1 is null
        Assert.assertFalse(GameMechanics.isElevensPair(testCardAce, null));
    }

    /**
     * Units tests for cardSelectionCharToInt
     *
     * Test 1, GameMechanics.cardSelectionCharToInt() returns 0 when input
     is 'a'
     * Test 2, GameMechanics.cardSelectionCharToInt() returns 1 when input
     is 'b'
     * Test 3, GameMechanics.cardSelectionCharToInt() returns 2 when input
     is 'c'
     * Test 4, GameMechanics.cardSelectionCharToInt() returns 3 when input
     is 'd'
     * Test 5, GameMechanics.cardSelectionCharToInt() returns 4 when input
     is 'e'
     * Test 6, GameMechanics.cardSelectionCharToInt() returns 5 when input
     is 'f'
     * Test 7, GameMechanics.cardSelectionCharToInt() returns 6 when input
     is 'g'
     * Test 8, GameMechanics.cardSelectionCharToInt() returns 7 when input
     is 'h'
     * Test 9, GameMechanics.cardSelectionCharToInt() returns 8 when input
     is 'i'
     * Test 10, GameMechanics.cardSelectionCharToInt() returns -1 when
     input is 'z'
     */
    @Test
    public void cardSelectionCharToInt() {
        //Test 1, GameMechanics.cardSelectionCharToInt() returns 0 when
        input is 'a'
        Assert.assertEquals(0, GameMechanics.cardSelectionCharToInt('a'));
    }

```

```

        //Test 2, GameMechanics.cardSelectionCharToInt() returns 1 when
input is 'b'
        Assert.assertEquals(1, GameMechanics.cardSelectionCharToInt('b'));

        //Test 3, GameMechanics.cardSelectionCharToInt() returns 2 when
input is 'c'
        Assert.assertEquals(2, GameMechanics.cardSelectionCharToInt('c'));

        //Test 4, GameMechanics.cardSelectionCharToInt() returns 3 when
input is 'd'
        Assert.assertEquals(3, GameMechanics.cardSelectionCharToInt('d'));

        //Test 5, GameMechanics.cardSelectionCharToInt() returns 4 when
input is 'e'
        Assert.assertEquals(4, GameMechanics.cardSelectionCharToInt('e'));

        //Test 6, GameMechanics.cardSelectionCharToInt() returns 5 when
input is 'f'
        Assert.assertEquals(5, GameMechanics.cardSelectionCharToInt('f'));

        //Test 7, GameMechanics.cardSelectionCharToInt() returns 6 when
input is 'g'
        Assert.assertEquals(6, GameMechanics.cardSelectionCharToInt('g'));

        //Test 8, GameMechanics.cardSelectionCharToInt() returns 7 when
input is 'h'
        Assert.assertEquals(7, GameMechanics.cardSelectionCharToInt('h'));

        //Test 9, GameMechanics.cardSelectionCharToInt() returns 8 when
input is 'i'
        Assert.assertEquals(8, GameMechanics.cardSelectionCharToInt('i'));

        //Test 10, GameMechanics.cardSelectionCharToInt() returns -1 when
input is 'z'
        Assert.assertEquals(-1, GameMechanics.cardSelectionCharToInt('z'));
    }

    /**
     * Unit tests for cardSelectionNumberToString
     *
     * Test 1, GameMechanics.cardSelectionCharToInt() returns 'a' when
input is 0
     * Test 2, GameMechanics.cardSelectionCharToInt() returns 'b' when
input is 1
     * Test 3, GameMechanics.cardSelectionCharToInt() returns 'c' when
input is 2
     * Test 4, GameMechanics.cardSelectionCharToInt() returns 'd' when
input is 3
     * Test 5, GameMechanics.cardSelectionCharToInt() returns 'e' when
input is 4
     * Test 6, GameMechanics.cardSelectionCharToInt() returns 'f' when
input is 5
     * Test 7, GameMechanics.cardSelectionCharToInt() returns 'g' when
input is 6
     * Test 8, GameMechanics.cardSelectionCharToInt() returns 'h' when
input is 7
     * Test 9, GameMechanics.cardSelectionCharToInt() returns 'i' when
input is 8
     * Test 10, GameMechanics.cardSelectionCharToInt() returns '-z' when
input is -1

```

```

    */
    @Test
    public void cardSelectionNumberToString() {
        //Test 1, GameMechanics.cardSelectionNumberToString() returns a
        when input is 0
        Assert.assertEquals("a",
        GameMechanics.cardSelectionNumberToString(0));

        //Test 2, GameMechanics.cardSelectionNumberToString() returns b
        when input is 1
        Assert.assertEquals("b",
        GameMechanics.cardSelectionNumberToString(1));

        //Test 3, GameMechanics.cardSelectionNumberToString() returns c
        when input is 2
        Assert.assertEquals("c",
        GameMechanics.cardSelectionNumberToString(2));

        //Test 4, GameMechanics.cardSelectionNumberToString() returns d
        when input is 3
        Assert.assertEquals("d",
        GameMechanics.cardSelectionNumberToString(3));

        //Test 5, GameMechanics.cardSelectionNumberToString() returns e
        when input is 4
        Assert.assertEquals("e",
        GameMechanics.cardSelectionNumberToString(4));

        //Test 6, GameMechanics.cardSelectionNumberToString() returns f
        when input is 5
        Assert.assertEquals("f",
        GameMechanics.cardSelectionNumberToString(5));

        //Test 7, GameMechanics.cardSelectionNumberToString() returns g
        when input is 6
        Assert.assertEquals("g",
        GameMechanics.cardSelectionNumberToString(6));

        //Test 8, GameMechanics.cardSelectionNumberToString() returns h
        when input is 7
        Assert.assertEquals("h",
        GameMechanics.cardSelectionNumberToString(7));

        //Test 9, GameMechanics.cardSelectionNumberToString() returns i
        when input is 8
        Assert.assertEquals("i",
        GameMechanics.cardSelectionNumberToString(8));

        //Test 10, GameMechanics.cardSelectionNumberToString() returns
        ERROR when input is 99
        Assert.assertEquals("ERROR",
        GameMechanics.cardSelectionNumberToString(99));
    }

    /**
     * Unit tests for validStringSelection
     *
     * Test 1, returns true when 3 valid chars are selected
     * Test 2, returns true when 2 valid chars are selected
     * Test 3, returns false when 3 invalid chars are selected
     * Test 4, returns false when 2 invalid chars are selected
    */

```

```

    * Test 5, returns false when 2 valid and 1 invalid chars are selected
    * Test 6, returns false when 1 valid and 1 invalid chars are selected
    * Test 7, returns false when 1 letter is provided
    * Test 8, returns false when 0 letters is provided
    */
    @Test
    public void validStringSelection() {
        // Test 1, returns true when 3 valid chars are selected
        Assert.assertTrue(GameMechanics.validStringSelection("abc"));

        // Test 2, returns true when 2 valid chars are selected
        Assert.assertTrue(GameMechanics.validStringSelection("de"));

        // Test 3, returns false when 3 invalid chars are selected
        Assert.assertFalse(GameMechanics.validStringSelection("xyz"));

        // Test 4, returns false when 2 invalid chars are selected
        Assert.assertFalse(GameMechanics.validStringSelection("pq"));

        // Test 5, returns false when 2 valid and 1 invalid chars are
selected
        Assert.assertFalse(GameMechanics.validStringSelection("abz"));

        // Test 6, returns false when 1 valid and 1 invalid chars are
selected
        Assert.assertFalse(GameMechanics.validStringSelection("az"));

        // Test 7, returns false when 1 letter is provided
        Assert.assertFalse(GameMechanics.validStringSelection("a"));

        // Test 8, returns false when 0 letters is provided
        Assert.assertFalse(GameMechanics.validStringSelection(""));
    }

    /**
     * Unit tests for allowedCharacter
     *
     * Test 1, returns true when input is a
     * Test 2, returns true when input is b
     * Test 3, returns true when input is c
     * Test 4, returns true when input is d
     * Test 5, returns true when input is e
     * Test 6, returns true when input is f
     * Test 7, returns true when input is g
     * Test 8, returns true when input is h
     * Test 9, returns true when input is i
     * Test 10, returns false when not one of (a b c d e f g h i)
     */
    @Test
    public void allowedCharacter() {
        // Test 1, returns true when input is a
        Assert.assertTrue(GameMechanics.allowedCharacter('a'));

        // Test 2, returns true when input is b
        Assert.assertTrue(GameMechanics.allowedCharacter('b'));

        // Test 3, returns true when input is c
        Assert.assertTrue(GameMechanics.allowedCharacter('c'));

        // Test 4, returns true when input is d
        Assert.assertTrue(GameMechanics.allowedCharacter('d'));
    }

```

```

        // Test 5, returns true when input is e
        Assert.assertTrue(GameMechanics.allowedCharacter('e'));

        // Test 6, returns true when input is f
        Assert.assertTrue(GameMechanics.allowedCharacter('f'));

        // Test 7, returns true when input is g
        Assert.assertTrue(GameMechanics.allowedCharacter('g'));

        // Test 8, returns true when input is h
        Assert.assertTrue(GameMechanics.allowedCharacter('h'));

        // Test 9, returns true when input is i
        Assert.assertTrue(GameMechanics.allowedCharacter('i'));

        // Test 10, returns false when not one of (a b c d e f g h i)
        Assert.assertFalse(GameMechanics.allowedCharacter('z'));
    }
}

```

## GameTest.java

```

package test;

import main.Game;
import org.junit.Assert;
import org.junit.Test;

import static org.junit.Assert.*;

/**
 * Unit tests for Game Class
 *
 * Developer Note: unit tests here are bare as we do not have many Setters
 for this class.
 * As they are not required for this object.
 *
 * Methods that have only be tested Manually, as we cannot via unit test
 without illegal libraries.
 * computerDemonstrationGame()
 * userPlayableGame()
 * getDeck()
 * getDiscardDeck()
 */
public class GameTest {

    /**
     * Test 1 getRoundQueue should return null, when a new game is created
     as no round Queue has been created
     */
    @Test
    public void getRoundQueue() {
        Game game = new Game();

        //Test 1 getRoundQueue should return null, when a new game is
        created as no rounds have be generated
        assertNull(game.getRoundQueue());
    }
}

```

```

    /**
     * Test 1 getCurrentRound should return null, when a new game is
     created as no rounds has been created
     */
    @Test
    public void getCurrentRound() {
        Game game = new Game();

        //Test 1 getCurrentRound should return null, when a new game is
        created as no rounds have be generated
        assertNull(game.getCurrentRound());
    }

    /**
     * Test 1 .getGameResult() returns false when a unplayed game object is
     created.
     */
    @Test
    public void getGameResult() {
        Game game = new Game();

        //Test 1 .getGameResult() returns false when a unplayed game object
        is created.
        Assert.assertFalse(game.getGameResult());
    }
}

```

## HouseTest.java

```

package test;

import junit.framework.TestCase;
import main.House;

/**
 * Units Tests for the Class House
 */
public class HouseTest extends TestCase {

    /**
     * Test for House.toString()
     */
    public void testToString() {
        //Test House.CLUBS.toString() equals "Clubs"
        assertEquals(House.CLUBS.toString(), "Clubs");

        //Test House.DIAMONDS.toString() equals "Diamonds"
        assertEquals(House.DIAMONDS.toString(), "Diamonds");

        //Test House.SPADES.toString() equals "Spades"
        assertEquals(House.SPADES.toString(), "Spades");

        //Test House.HEARTS.toString() equals "Hearts"
        assertEquals(House.HEARTS.toString(), "Hearts");
    }
}

```

## RankTest.java

```
package test;

import junit.framework.TestCase;
import main.Rank;

/**
 * Unit tests for the class Rank
 */
public class RankTest extends TestCase {

    private Rank testRankKing = Rank.KING;
    private Rank testRankAce = Rank.ACE;
    private Rank testRankTwo = Rank.TWO;

    /**
     * Test getRank() returns the correct Rank of the Card
     */
    public void testGetRank() {
        //a card with Rank.KING .getRank() should equal "King"
        assertEquals(testRankKing.getRank(), "King");

        //a card with Rank.ACE .getRank() should equal "Ace"
        assertEquals(testRankAce.getRank(), "Ace");

        //a card with Rank.TWO .getRank() should equal "Two"
        assertEquals(testRankTwo.getRank(), "Two");
    }

    /**
     * Test getValue() returns the correct value of the card
     */
    public void testGetValue() {
        //a card with Rank.KING .getRank() should equal -1
        assertEquals(testRankKing.getValue(), -1);

        //a card with Rank.Ace .getRank() should equal 1
        assertEquals(testRankAce.getValue(), 1);

        //a card with Rank.Two .getRank() should equal 2
        assertEquals(testRankTwo.getValue(), 2);
    }

    /**
     * Test toString returns the Rank as a String
     */
    public void testTestToString() {
        //a card with Rank.KING .toString() should equal "King"
        assertEquals(testRankKing.toString(), "King");

        //a card with Rank.ACE .toString() should equal "Ace"
        assertEquals(testRankAce.toString(), "Ace");

        //a card with Rank.TWO .toString() should equal "Two"
        assertEquals(testRankTwo.toString(), "Two");
    }
}
```



## RoundQueueTest.java

```
package test;

import main.CardSlotsBag;
import main.Round;
import main.RoundQueue;
import org.junit.Assert;
import org.junit.Test;

public class RoundQueueTest {

    /**
     * Test RoundQueue enqueue() method
     */
    @Test
    public void enqueue() {

        Round front = new Round(0, new CardSlotsBag());
        RoundQueue roundQueue = new RoundQueue();

        /*
         * Should add Round to the front of the queue
         */

        //Assert is currently null
        Assert.assertNull(roundQueue.getFront());

        roundQueue.enqueue(front);

        var actual = roundQueue.getFront();
        var expected = front;

        //Assert .enqueue(front) added the round.
        Assert.assertEquals(actual, expected);

        /*
         * Should add Round too be the next round after the first Round and
         be the rear Node.
         */
        Round nextRound = new Round(0, new CardSlotsBag());
        roundQueue.enqueue(nextRound);

        var actual2 = roundQueue.getRear();
        var expected2 = nextRound;

        //Assert that is nextRound is rear
        Assert.assertEquals(actual2, expected2);

    }

    /**
     * Test RoundQueue dequeue() method
     */
    @Test
    public void dequeue() {
        Round front = new Round(0, new CardSlotsBag());
        Round rear = new Round(1, new CardSlotsBag());
        RoundQueue roundQueue = new RoundQueue();
        /*
```

```

        * Should not remove a round from an empty queue
        */
        var actual = roundQueue.getFront();

        //Assert roundQueue is null
        Assert.assertNull(actual);

        //Assert roundQueue is still null after a .dequeue null
        roundQueue.dequeue();
        Assert.assertNull(actual);

        /*
        * Should remove a round from a queue with 1 Round in it.
        */
        //Assert queue is not null
        roundQueue.enqueue(front);
        Assert.assertNotNull(roundQueue.getFront());

        //Assert queue is null after calling .dequeue()
        roundQueue.dequeue();
        var actual1 = roundQueue.getFront();
        Assert.assertNull(actual1);

        /*
        * Should remove a round from a queue with 2 Round's in it.
        * and the rear round should now be both the front and rear
        */
        roundQueue.enqueue(front);
        roundQueue.enqueue(rear);

        //Assert front and rear are correct
        Assert.assertEquals(roundQueue.getFront(), front);
        Assert.assertEquals(roundQueue.getRear(), rear);

        //Assert dequeue removes the front round in the queue, so that rear
is now rear and front
        roundQueue.dequeue();
        Assert.assertEquals(roundQueue.getFront(), rear);
        Assert.assertEquals(roundQueue.getRear(), rear);
    }

    /**
     * Test RoundQueue getFront method
     */
    @Test
    public void getFront() {
        Round front = new Round(0, new CardSlotsBag());
        RoundQueue roundQueue = new RoundQueue();

        /*
        Test getFront() returns the front Round.
        */
        roundQueue.enqueue(front);

        var expected = front;
        var actual = roundQueue.getFront();

        Assert.assertEquals(expected, actual);
    }
}

```

```

/**
 * Test RoundQueues isEmpty Method
 */
@Test
public void isEmpty() {
    Round front = new Round(0, new CardSlotsBag());
    RoundQueue roundQueue = new RoundQueue();
    /*
     * Test isEmpty returns true when the RoundQueue is empty.
     */
    var expected = true;
    var actual = roundQueue.isEmpty();

    Assert.assertEquals(expected, actual);

    /*
     * Test isEmpty returns false when the RoundQueue is not empty.
     */
    roundQueue.enqueue(front);
    var expected1 = false;
    var actual1 = roundQueue.isEmpty();

    Assert.assertEquals(expected1, actual1);
}

/**
 * Test RoundQueues clear() method
 */
@Test
public void clear() {
    Round front = new Round(0, new CardSlotsBag());
    RoundQueue roundQueue = new RoundQueue();

    /*
     * Test clear clears the RoundQueue, when it was not empty.
     */

    //first add and element and assert is not empty
    roundQueue.enqueue(front);
    Assert.assertEquals(roundQueue.getFront(), front);

    //Assert clear clears the queue and front and rear equal null
    roundQueue.clear();
    Assert.assertNull(roundQueue.getFront());
    Assert.assertNull(roundQueue.getRear());
}
}

```

## RoundTest.java

```
package test;

import junit.framework.TestCase;
import main.*;

/**
 * Unit tests for the Round Class methods.
 */
public class RoundTest extends TestCase {

    /**
     * Test 1 Returns true when there is no elevens pairs and no pairs of
     face cards
     * Test 2 Returns false when there is a elevens pair
     * Test 3 Returns false when there is face card pairs.
     */
    public void testIsStalemate() {
        //Test 1 Returns true when there is no elevens pairs and no pairs
of face cards
        CardSlotsBag bag1 = new CardSlotsBag();
        bag1.addNewEntry(new Card(House.DIAMONDS, Rank.ACE));
        bag1.addNewEntry(new Card(House.CLUBS, Rank.ACE));
        Round round1 = new Round(1, bag1);
        //Assert Test 1
        assertTrue(round1.isStalemate());

        //Test 2 Returns false when there is a elevens pair
        CardSlotsBag bag2 = new CardSlotsBag();
        bag2.addNewEntry(new Card(House.DIAMONDS, Rank.ACE));
        bag2.addNewEntry(new Card(House.DIAMONDS, Rank.TEN));
        Round round2 = new Round(2, bag2);
        //Assert Test 2
        assertFalse(round2.isStalemate());

        //Test 3 Returns false when there is face card pairs.
        CardSlotsBag bag3 = new CardSlotsBag();
        bag3.addNewEntry(new Card(House.DIAMONDS, Rank.ACE));
        bag3.addNewEntry(new Card(House.DIAMONDS, Rank.TEN));
        bag3.addNewEntry(new Card(House.CLUBS, Rank.KING));
        bag3.addNewEntry(new Card(House.DIAMONDS, Rank.QUEEN));
        bag3.addNewEntry(new Card(House.CLUBS, Rank.JACK));
        Round round3 = new Round(2, bag2);

        //Assert Test 3
        assertFalse(round3.isStalemate());
    }

    /**
     * Test 1
     * replaceEmptyCardSlots() should add 9 cards to bag1
     * Test 2
     * replaceEmptyCardSlots should add 1 card to the bag2 when bag2 has 8
     cards inside it.
     */
    public void testReplaceEmptyCardSlots() {
        Deck deck = new Deck();
        deck.createFullDeckOfCards();

        // Test 1
    }
```

```

        // replaceEmptyCardSlots() should add 9 cards to bag1
        CardSlotsBag bag1 = new CardSlotsBag();
        Round round1 = new Round(1, bag1);
        assertEquals(bag1.countCards(), 0);
        round1.replaceEmptyCardSlots(deck);

        //Assert Test 1
        assertEquals(bag1.countCards(), 9);

        // Test 2
        // ReplaceEmptyCardSlots should add 1 card to the bag2 when bag2
has 8 cards inside it.
        CardSlotsBag bag2 = new CardSlotsBag();
        bag2.addNewEntry(new Card(House.CLUBS, Rank.ACE));
        bag2.addNewEntry(new Card(House.CLUBS, Rank.TWO));
        bag2.addNewEntry(new Card(House.CLUBS, Rank.THREE));
        bag2.addNewEntry(new Card(House.CLUBS, Rank.FOUR));
        bag2.addNewEntry(new Card(House.CLUBS, Rank.FIVE));
        bag2.addNewEntry(new Card(House.CLUBS, Rank.SIX));
        bag2.addNewEntry(new Card(House.CLUBS, Rank.SEVEN));
        bag2.addNewEntry(new Card(House.CLUBS, Rank.EIGHT));
        Round round2 = new Round(2, bag2);

        //Assertions Test 2
        assertEquals(bag2.countCards(), 8);
        round2.replaceEmptyCardSlots(deck);
        assertEquals(bag2.countCards(), 9);
    }

    /**
     * getRoundNumber() should return 1
     */
    public void testGetRoundNumber() {
        CardSlotsBag bag1 = new CardSlotsBag();
        Round round1 = new Round(1, bag1);
        assertEquals(round1.getRoundNumber(), 1);
    }

    /**
     * setRoundNumber() should set the round number to 2.
     */
    public void testSetRoundNumber() {
        CardSlotsBag bag1 = new CardSlotsBag();
        Round round1 = new Round(1, bag1);
        round1.setRoundNumber(2);
        assertEquals(round1.getRoundNumber(), 2);
    }

    /**
     * getCardSlotBag should return a empty bag.
     */
    public void testGetCardSlotBag() {
        CardSlotsBag bag1 = new CardSlotsBag();
        Round round1 = new Round(1, bag1);
        assertEquals(round1.getCardsInPlayBag(), bag1);
    }

    /**
     * setCardSlotBag should set the rounds bag 'bagWithCard' with a Card
in it
     */

```

```

public void testSetCardSlotBag() {
    CardSlotsBag bag1 = new CardSlotsBag();
    CardSlotsBag bagWithCard = new CardSlotsBag();
    Round round1 = new Round(1, bag1);
    bagWithCard.addNewEntry(new Card(House.CLUBS, Rank.ACE));
    round1.setCardsInPlayBag(bagWithCard);
    assertEquals(round1.getCardsInPlayBag(), bagWithCard);
}

/**
 * round1.getNextRound() should return CardSlotsBag round2
 */
public void testGetNextRound() {
    CardSlotsBag bag1 = new CardSlotsBag();
    CardSlotsBag bag2 = new CardSlotsBag();
    Round round1 = new Round(1, bag1);
    Round round2 = new Round(2, bag2);
    round1.setNextRound(round2);
    assertEquals(round1.getNextRound(), round2);
}

/**
 * round1.setNext Round should set round1's nextRound to Round2.
 */
public void testSetNextRound() {
    CardSlotsBag bag1 = new CardSlotsBag();
    CardSlotsBag bag2 = new CardSlotsBag();
    Round round1 = new Round(1, bag1);
    Round round2 = new Round(2, bag2);
    round1.setNextRound(round2);
    assertEquals(round1.getNextRound(), round2);
}
}

```

## ElevenTest.java

```

package test;

/**
 * Developer Note: Testing is not required here as to test we require
 * illegal libraries
 * due to System.in requirements.
 *
 * So test for this class we be performed manually
 *
 * This class will not be run when unit tests are ran.
 */
public class ElevenTest {
}

```

## ColorsTest.java

```
package test;

/**
 * Developer Note: Testing for the Class is not required.
 *
 * This class will not be run when unit tests are ran.
 */
public class ColorsTest {}
```

## DisplayTest.java

```
package test;

/**
 * Developer Note: All Testing for Display will be perform manually as all
 * methods here only
 * perform System.out
 *
 * This class will not be run when unit tests are ran.
 */
public class DisplayTest {}
```