

Retail Manager Development Manual

Michael Kaip

August 15, 2019

Contents

1	Introduction	1
1.1	Project Summary	1
2	Initial Plan	2
2.1	Outline	2
2.2	Technologies	2
3	Initial Setup in Visual Studio	3
4	Creating a WebAPI with Authentication	4
4.1	Indentity Configuration	4
4.2	Getting authorized for development	4
4.2.1	Postman	4
4.2.2	Getting User Information	5
5	Installing and configuring SWAGGER	6
5.1	Installing SWAGGER	6
5.2	Channging the configuration of SWAGGER	6
5.3	Adding OAuth ability	7
6	SQL Database Setup	11
6.1	Adding new Database Project to the solution	11
6.2	Adding several folders to the project	11
6.3	Creating a profile and publishing the Database	12
7	WPF with MVVM Project Setup	13
7.1	Adding the WPF Project to the solution	13
7.2	Changing the Assambley Name to the name of the solution in Properties	13
7.3	Adding Caliburn Micro MVVM-Framework	14
7.3.1	Adding the folder structure for the MVVM-Framework	14
7.3.2	Adding a new ShellViewModel class and a SchellView window	14
7.3.3	Adding a Bootstrapper class to DesktopUI	14
7.3.4	Removing StartUpURI from App.xaml and adding a new Ressource Dictionary	15
8	Dependency Injection in WPF	16
8.1	SimpleContainer in Caliburn Micro	16
8.1.1	Implementing SimpleContainer in Bootstrapper.cs	16
8.2	Overriding Configure() Method for the container	17
9	Datamodel - planning and setup	18
9.1	Planning the Register	18
9.2	SQL Database Table Creation	19
10	WPF Login Form Creation	20
10.1	Inheritance from the conductor class in Caliburn Micro	20
10.2	Implementing the menue bar	20
10.3	Adding a UserControl	20
10.3.1	Adding a class LoginViewModel (public) and UserControl LoginView	20
10.3.2	Designing the UserControl	21
10.3.3	Activating the LoginView on startup in the ShellView	21
10.3.4	Implementing LoginViewModel.cs	22
10.3.5	Connecting the LoginViewModel to Caliburn.Micro	23
11	Wiring up the WPF Login Form	24

11.1 Implementing a class <code>AuthenticatedUser.cs</code>	24
11.2 Implementing a helper class to handle API call interactions	25
11.3 Implementing a Interface <code>IAPIHelper.cs</code>	26
11.4 Adding <code><appsettings></code> to <code>App.Config</code>	26
11.5 Adding <code>APIHelper</code> and <code>IAPIHelper</code> to the container in <code>Bootstrapper.cs</code>	26
11.6 Applying some changings to <code>LoginViewModel.cs</code>	26
11.6.1 Adding a new private property as a backing field	26
11.6.2 Adding a constructor and initializing the property from within	27
11.6.3 Implementig the <code>Login()</code> method	27
11.7 Enabling the solution to start multiple projects	27
12 Login Form Error Handling	29
13 Getting User Data	29
14 Sales Page Creation	29
15 Event Aggregation in WPF	29
16 Displaying Product data	29
17 Wiring up WPF Shopping Cart	29
18 Modifying SQL, the API and WPF to add Taxes	29

1 Introduction

1.1 Project Summary

The goal of this project is to build a desktop app that runs a cash register, handles inventory and manages an entire retail store. Creating and implementing a **WebAPI layer**, will allow the whole project to grow. This layer will be able to serve each kind of application (desktop, mobile, web, ...).

2 Initial Plan

2.1 Outline

The App is going to be build as a MVP (Minimum Viable Product) that can be expanded to cover all of the features, which are needed over time - so it can grow into a full featured application. First step is getting all of the major pieces set up, including:

- Git on Azure DevOps
- SQL Database (SSDT)
- WebAPI with Authentication
- WPF application that can log into the API

2.2 Technologies

- | | |
|--------------------------------|-------------------|
| • Unit Testing | • Async |
| • Dependency Injection | • Reporting |
| • WPF | • WebAPI |
| • MVVM with Caliburn Micro | • Logging |
| • ASP.NET MVC (Web Frontend) | • Data Validation |
| • .NET Framework | • HTML |
| • .NET Core 3.0 | • CSS |
| • SSDT - SQL Server Data Tools | • JavaScript |
| • Git | • Authentication |
| • Azure DevOps | |

3 Initial Setup in Visual Studio

1. Setting up a Git-Repository, including README, GitIgnore (for VS) and License
2. Creating a **Blank Solution**: Other Project Types → Blank Solution
Such type of solution isn't language specific.

4 Creating a WebAPI with Authentication

1. Adding new Project to the Solution:

Web → ASP.NET Web Application (.NET Framework) → WebAPI

Add folders and references for:

- MVC
- Web API

Change Authentication to

- Individual User Accounts

2. Upgrading all NuGet-Packages

4.1 Indentity Configuration

App_Start → IdentityConfig.cs

In there are some settings for setting up the WebAPI, especially for authentication:


- UserValidator
- PasswordValidator

4.2 Getting authorized for development

4.2.1 Postman

The following calls has to be applied in the given order:

1. POST



Creates a new user account and stores this information into the user database.
If **Status: 200 OK**, username and password has been succesfully created.

2. GET

GET http://localhost:54756/token

Params Authorization Headers (1) Body Pre-request Script Tests

none form-data x-www-form-urlencoded raw binary GraphQL BETA

	KEY	VALUE	DESCRIPTION
<input checked="" type="checkbox"/>	grant_type	password	
<input checked="" type="checkbox"/>	username	michael.kaip@gmx.net	
<input checked="" type="checkbox"/>	password	Pwd12345.	

It will return an **access_token** which is, by default, valid for 14 days. Token is needed for all further interaction with the server. Can be also configured for shorter valid periods.

3. POST

POST http://localhost:54756/api/values

Params Authorization Headers (1) Body Pre-request Script Tests

Headers (1)

	KEY	VALUE	DESCRIPTION
<input checked="" type="checkbox"/>	Authorization	Bearer VuQDu7NWP8J-yd-tCRvkiqFwjBMZlaURbN...	
	Key	Value	Description

Response

4.2.2 Getting User Information

In order to get the Identity of users returned, some changes have to be implemented. Through this it's becomes possible to apply different accessibility rules, based on the user-group a certain user is part of.

1. *RMDataManager.Controllers.ValuesController*

```
using System.Web.Http;
using Microsoft.AspNet.Identity; // Needed for getting information about the user


namespace RMDataManager.Controllers
{
    [Authorize]
    0 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
    public class ValuesController : ApiController
    {
        // GET api/values
        0 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
        public IEnumerable<string> Get()
        {
            // Stores the ID of each user
            var userId = RequestContext.Principal.Identity.GetUserId();
            return new string[] { "value1", "value2", userId };
        }
    }
}
```


5 Installing and configuring SWAGGER

SWAGGER is an API documentation and demonstration tool.


5.1 Installing SWAGGER

1. NuGet-Manager



Adds a SWAGGER to WebAPI-Projects.

2. Starting SWAGGER



5.2 Changing the configuration of SWAGGER

RMDDataManager.App_Start.SwaggerConfig.cs

1. Changing title

```
// Use "SingleApiVersion" to describe a single version API. Swagger 2.0 includes an "Info" object to
// hold additional metadata for an API. Version and title are required but you can also provide
// additional fields by chaining methods off SingleApiVersion.
//
c.SingleApiVersion("v1", title: "Retail Manager API"); // Changed to a proper name
```

2. Enabling proper printing of documents

```
// If you want the output Swagger docs to be indented properly, enable the "PrettyPrint" option.
//
c.PrettyPrint(); // enabled
```

3. Treating Enums as Strings


```
// In accordance with the built in JsonSerializer, Swashbuckle will, by default, describe enums as integers.
// You can change the serializer behavior by configuring the StringToEnumConverter globally or for a given
// enum type. Swashbuckle will honor this change out-of-the-box. However, if you use a different
// approach to serialize enums as strings, you can also force Swashbuckle to describe them as strings.
//
c.DescribeAllEnumsAsStrings(); // enabled
```

4. Changing document title

```
.EnableSwaggerUi(configure: c =>
{
    // Use the "DocumentTitle" option to change the Document title.
    // Very helpful when you have multiple Swagger pages open, to tell them apart.
    //
    c.DocumentTitle("RM API"); // changed the name
});
```

5.3 Adding OAuth ability

1. Enabling token endpoint allowance in the SWAGGER documentation

(a) Adding a new Class to `RMDataManager.App_Start`

(b) Implementing the required Interface

```

public class AuthTokenOperation : IDocumentFilter
{
    // Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
    public void Apply(SwaggerDocument swaggerDoc, SchemaRegistry schemaRegistry, IApiExplorer apiExplorer)
    {
        swaggerDoc.paths.Add("/token", new PathItem
        {
            post = new Operation
            {
                tags = new List<string> { "Auth" },
                consumes = new List<string>
                {
                    "application/x-www-form-urlencoded"
                },
                parameters = new List<Parameter>
                {
                    new Parameter
                    {
                        type = "string",
                        name = "grant_type",
                        required = true,
                        @in = "formData",
                        @default = "password"
                    },
                    new Parameter
                    {
                        type = "string",
                        name = "username",
                        required = false,
                        @in = "formData"
                    },
                    new Parameter
                    {
                        type = "string",
                        name = "password",
                        required = false,
                        @in = "formData"
                    }
                }
            }
        });
    }
}

```

(c) Applying it to SwaggerConfig.cs

```
GlobalConfiguration.Configuration
    .EnableSwagger(c =>
    {
        c.DocumentFilter<AuthTokenOperation>(); // adding the implemented document filter
    })
```

(d) Logging into the application using SWAGGER and get the token

Retail Manager API

Account	ShowHide	List Operations	Expand Operations
Values	ShowHide	List Operations	Expand Operations
Auth	ShowHide	List Operations	Expand Operations

POST /token

Parameters

Parameter	Value	Description	Parameter Type	Data Type
grant_type	<input type="text" value="password"/>		formData	string
username	<input type="text" value="michael.kaip@gmx.net"/>		formData	string
password	<input type="text" value="Pwd12345"/>		formData	string

[Hide Response](#)

Curl

```
curl -X POST --header 'Content-Type: application/x-www-form-urlencoded' --header 'Accept: application/json' -d 'grant_type=password&username=michael.kaip@gmx.net&password=Pwd12345'
```

Request URL

```
http://localhost:54756/token
```

Response Body

```
{
  "access_token": "MofCpsbIKqt1Owslj4fhP4BuJY3HFLyxtlqp-c3G59vOlKzc-tME9zxVP-RcBT9dUjZuhvEQPtl-4QqkKoxKhKLQqMeSekBjHZ5XC-pTr",
  "token_type": "bearer",
  "expires_in": 1209559,
  "userName": "michael.kaip@gmx.net",
  ".issued": "Thu, 08 Aug 2019 12:18:18 GMT",
  ".expires": "Thu, 22 Aug 2019 12:18:18 GMT"
}
```

Response Code


```
200
```

Response Headers

```
{
  "pragma": "no-cache",
  "date": "Thu, 08 Aug 2019 12:18:20 GMT",
  "server": "Microsoft-IIS/10.0",
  "x-powered-by": "ASP.NET",
  "content-type": "application/json;charset=UTF-8",
  "cache-control": "no-cache",
  "> sourcefile": "\r\n\r\nXFxWYwNCSG9tZVxEb2N1hWudhMcUUR1zL1bVxZXRhawMYWShZVyXFJNRGF0YU1hbWFnZW50ZW4=/?=",
  "content-length": "693",
  "expires": "-1"
}
```

2. Enabling to paste in the bearer token in order to authorize restricted commands

- (a) Adding a new Class to
- `RMDataManager.App_Start`



- (b) Implementing the required Interface

```

0 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
public class AuthorizationOperationFilter : IOperationFilter
{
    0 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
    public void Apply(Operation operation, SchemaRegistry schemaRegistry, ApiDescription apiDescription)
    {
        // Adding a parameter to each operation.
        if (operation.parameters == null)
        {
            operation.parameters = new List<Parameter>();
        }

        operation.parameters.Add(new Parameter
        {
            name = "Authorization",
            @in = "header",
            description = "access token",
            type = "string"
        });
    }
}

```

- (c) Applying it to SwaggerConfig.cs

```

.EnableSwagger(configure: c =>
{
    c.DocumentFilter<AuthTokenOperation>(); // adding the implemented document filter
    c.OperationFilter<AuthorizationOperationFilter>(); // adding the implmented operation filter
}

```

- (d) Get user information from the application via SWAGGER using the token

Values [Show/Hide](#) [List Operations](#) [Expand Operations](#)

GET /api/Values

Response Class (Status 200)
OK

Model: **Example Value**

```
[
  "string"
]
```

Response Content Type: application/json ▼

Parameters

Parameter	Value	Description	Parameter Type	Data Type
Authorization	bearer PbvcDU53IDWQvxxWnxBaBOs57EWmT6	access token	header	string

[Try it out!](#) [Hide Response](#)

Curl

```
curl -X GET --header 'Accept: application/json' --header 'Authorization: bearer PbvcDU53IDWQvxxWnxBaBOs57EWmT6NoXhgIdem07kJoP1Vvh' http://localhost:54756/api/Values
```

Request URL

```
http://localhost:54756/api/Values
```

Response Body

```
[
  "value1",
  "value2",
  "2268F0be-21b1-4b31-98a5-8b9e32c2ea75"
]
```

Response Code


```
200
```

Response Headers


```
{
  "pragma": "no-cache",
  "date": "Thu, 08 Aug 2019 13:04:28 GMT",
  "server": "Microsoft-IIS/10.0",
  "x-aspnet-version": "4.0.30319",
  "x-powered-by": "ASP.NET",
  "content-type": "application/json; charset=utf-8",
  "cache-control": "no-cache",
  "x-sourcefiles": "~7UTF-878fXfxNvMlc569t2VxEb2N1bMvudHncU3R1ZG11bVxSZXRhbmRvYXhZVzVvYXZJNRGF0YU1hbmFnZXIjCvXBpXFZhbmVlcw==7-",
  "content-length": "58",
  "expires": "-1"
}
```

6 SQL Database Setup

6.1 Adding new Database Project to the solution




6.2 Adding several folders to the project




6.3 Creating a profile and publishing the Database

1. *RightClick on RMDatabase → Publish → Edit → Browse*




2. Naming and saving profile to PublishLocations




7 WPF with MVVM Project Setup

7.1 Adding the WPF Project to the solution



7.2 Changing the Assembly Name to the name of the solution in Properties




Also set project as the default startup-project.


7.3 Adding Caliburn Micro MVVM-Framework

Add NuGet-Package to references.


7.3.1 Adding the folder structure for the MVVM-Framework




7.3.2 Adding a new ShellViewModel class and a SchellView window



7.3.3 Adding a Bootstrapper class to DesktopUI



7.3.4 Removing StartUpURI from App.xaml and adding a new Ressource Dictionary




MainWindow.xaml can be deleted afterwards!!!

8 Dependency Injection in WPF

8.1 SimpleContainer in Caliburn Micro

Caliburn.Micro comes pre-bundled with a Dependency Injection container called SimpleContainer. A dependency injection container is an object that is used to hold dependency mappings for use later in an app via Dependency Injection. Dependency Injection is actually a pattern typically using the container element instead of manual service mapping.

8.1.1 Implementing SimpleContainer in Bootstrapper.cs



8.2 Overriding Configure() Method for the container

```
1-Verweis | 0 Änderungen | 0 Autoren, 0 Änderungen
public class Bootstrapper : BootstrapperBase
{
    private SimpleContainer _container = new SimpleContainer();
    // Constructor
    0 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
    public Bootstrapper()
    {
        Initialize();
    }


    0 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
    protected override void Configure()
    {
        _container.Instance(_container);

        _container
            .Singleton<IWindowManager, WindowManager>()
            .Singleton<EventAggregator, EventAggregator>();

        // Connecting the ViewModel to the Views using reflection
        GetType().Assembly.GetTypes()
            .Where(type => type.IsClass)
            .Where(type => type.Name.EndsWith(value: "ViewModel"))
            .ToList()
            .ForEach(action: viewModelType => _container.RegisterPerRequest(
                service: viewModelType, viewModelType.ToString(), implementation: viewModelType));
    }
}
```

9 Datamodel - planning and setup

9.1 Planning the Register



9.2 SQL Database Table Creation

User.sql

Name	Datentyp	NULL-Werte zulassen	Standard
Id	nvarchar(128)	<input type="checkbox"/>	
FirstName	nvarchar(50)	<input type="checkbox"/>	
LastName	nvarchar(50)	<input type="checkbox"/>	
EmailAddress	nvarchar(256)	<input type="checkbox"/>	
CreatedDate	datetime2(7)	<input type="checkbox"/>	getutcdate()


```

1 CREATE TABLE [dbo].[User]
2 (
3     [Id] NVARCHAR(128) NOT NULL,
4     [FirstName] NVARCHAR(50) NOT NULL,
5     [LastName] NVARCHAR(50) NOT NULL,
6     [EmailAddress] NVARCHAR(256) NOT NULL,
7     [CreatedDate] DATETIME2 NOT NULL DEFAULT getutcdate()
8 )
9

```

Product.sql

Name	Datentyp	NULL-Werte zulassen	Standard
Id	int	<input type="checkbox"/>	
ProductName	nvarchar(100)	<input type="checkbox"/>	
Description	nvarchar(MAX)	<input type="checkbox"/>	
RetailPrice	money	<input type="checkbox"/>	
CreateDate	datetime2(7)	<input type="checkbox"/>	getutcdate()
LastModified	datetime2(7)	<input type="checkbox"/>	getutcdate()


```

1 CREATE TABLE [dbo].[Product]
2 (
3     [Id] INT NOT NULL PRIMARY KEY IDENTITY,
4     [ProductName] NVARCHAR(100) NOT NULL,
5     [Description] NVARCHAR(MAX) NOT NULL,
6     [RetailPrice] MONEY NOT NULL,
7     [CreateDate] DATETIME2 NOT NULL DEFAULT getutcdate(),
8     /* Has to be modified manually everytime the entry gets modified.*/
9     [LastModified] DATETIME2 NOT NULL DEFAULT getutcdate()
10 )

```

Sale.sql

Name	Datentyp	NULL-Werte zulassen	Standard
Id	int	<input type="checkbox"/>	
CashierId	nvarchar(128)	<input type="checkbox"/>	
SaleDate	datetime2(7)	<input type="checkbox"/>	
SubTotal	money	<input type="checkbox"/>	
Tax	money	<input type="checkbox"/>	
Total	money	<input type="checkbox"/>	


```

1 CREATE TABLE [dbo].[Sale]
2 (
3     [Id] INT NOT NULL PRIMARY KEY IDENTITY, /* IDENTITY Makes the Id auto increment */
4     [CashierId] NVARCHAR(128) NOT NULL,
5     [SaleDate] DATETIME2 NOT NULL,
6     [SubTotal] MONEY NOT NULL,
7     [Tax] MONEY NOT NULL,
8     [Total] MONEY NOT NULL
9 )

```

SaleDetail.sql

Name	Datentyp	NULL-Werte zulassen	Standard
Id	int	<input type="checkbox"/>	
SaleId	int	<input type="checkbox"/>	
ProductId	int	<input type="checkbox"/>	
Quantity	nchar(10)	<input checked="" type="checkbox"/>	1
PurchasePrice	money	<input type="checkbox"/>	
Tax	money	<input type="checkbox"/>	0


```

1 CREATE TABLE [dbo].[SaleDetail]
2 (
3     [Id] INT NOT NULL PRIMARY KEY IDENTITY,
4     [SaleId] INT NOT NULL,
5     [ProductId] INT NOT NULL,
6     [Quantity] NCHAR(10) NOT NULL DEFAULT 1,
7     [PurchasePrice] MONEY NOT NULL,
8     [Tax] MONEY NOT NULL DEFAULT 0,
9 )

```

Inventory.sql


Name	Datentyp	NULL-Werte zulassen	Standard
Id	int	<input type="checkbox"/>	
ProductId	int	<input type="checkbox"/>	
Quantity	nchar(10)	<input type="checkbox"/>	1
PurchasePrice	money	<input type="checkbox"/>	
PurchaseDate	datetime2(7)	<input checked="" type="checkbox"/>	getutcdate()


```

1 CREATE TABLE [dbo].[Inventory]
2 (
3     [Id] INT NOT NULL PRIMARY KEY IDENTITY,
4     [ProductId] INT NOT NULL,
5     [Quantity] NCHAR(10) NOT NULL DEFAULT 1,
6     [PurchasePrice] MONEY NOT NULL,
7     [PurchaseDate] DATETIME2 NOT NULL DEFAULT getutcdate()
8 )
9


```

!!! Publishing Tables !!!



10 WPF Login Form Creation

10.1 Inheritance from the conductor class in Caliburn Micro



```


using System;
using System.Collections.Generic;
using System.Linq;
using System.Text;
using System.Threading.Tasks;
using Caliburn.Micro;

namespace RMDesktopUI.ViewModels
{
    1-Verweis | 0 Änderungen | 0 Autoren, 0 Änderungen
    public class ShellViewModel : Conductor<object> // Could also be set up more specifically
                                                // for certain types, or even use an interface.
    {
    }
}

```

Conductor is a base class which inherits from Screen. Its responsibility is to conduct other objects by managing an active item and maintain a strict lifecycle of this conducted item. The conductor exists in multiple variants such as the one item conductor simple called Conductor, the multiple item conductors such as *Conductor.Collection.OneActive* and *Conductor.Collection.AllActive*.

10.2 Implementing the menu bar




```

<Window x:Class="RMDesktopUI.Views.ShellView"
        xmlns="http://schemas.microsoft.com/winfx/2006/xaml/presentation"
        xmlns:x="http://schemas.microsoft.com/winfx/2006/xaml"
        xmlns:d="http://schemas.microsoft.com/expression/blend/2008"
        xmlns:mc="http://schemas.openxmlformats.org/markup-compatibility/2006"
        xmlns:local="clr-namespace:RMDesktopUI.Views"
        mc:Ignorable="d"
        Title="ShellView" Height="450" Width="800">
    <DockPanel>
        <Menu DockPanel.Dock="Top" FontSize="14">
            <MenuItem Header="_File">
            </MenuItem>
            <MenuItem Header="Account">
            <MenuItem x:Name="LoginScreen" Header="_Login"/>
            </MenuItem>
        </Menu>
        <Grid>
        </Grid>
    </DockPanel>
</Window>



```

10.3 Adding a UserControl



10.3.1 Adding a class LoginViewModel (public) and UserControl LoginView



10.3.2 Designing the UserControl




10.3.3 Activating the LoginView on startup in the ShellView



Sealed is used to restrict the users from inheriting. A class can be sealed by using the sealed keyword or a single method. The keyword tells the compiler that class or method cannot be extended. No class can be derived from a sealed class.

10.3.4 Implementing LoginViewModel.cs



```

LoginViewModel.cs
PasswordBoxHelper.cs
LoginView.xaml
LoginViewModel.cs*
RMDesktopUI
using System;
using Caliburn.Micro;

namespace RMDesktopUI.ViewModels
{
    2 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
    public class LoginViewModel : Screen
    {
        /*
         * Backing fields
         */
        private string _userName;
        private string _password;

        /*
         * Public properties
         */
        2 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
        public string UserName
        {
            get => _userName;
            set
            {
                _userName = value;
                // It's going to be fired every time we change the user value
                NotifyOfPropertyChange(() => UserName);
            }
        }

        2 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
        public string Password
        {
            get => _password;
            set
            {
                _password = value;
                NotifyOfPropertyChange(() => Password);
            }
        }

        0 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
        public bool CanLogIn(string userName, string password)
        {
            // Includes checking for null (?)
            var output = UserName?.Length > 0 && Password?.Length > 0;

            return output;
        }

        0 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
        public void LogIn(string userName, string password)
        {
            Console.WriteLine(); // Just for now
        }
    }
}

```

10.3.5 Connecting the LoginViewModel to Caliburn.Micro

1. Adding a helper class (PasswordBoxHelper.cs) to RMDesktopUI

```
using System.Reflection;
using System.Windows;
using System.Windows.Controls;

namespace RMDesktopUI.Helpers
{
    /*
     * The aim of this class is to include a binding convention so that binding in Caliburn.Micro
     * Source: https://stackoverflow.com/questions/30631522/caliburn-micro-support-for-password
     */
    1-Verweis | 0 Änderungen | 0 Autoren, 0 Änderungen
    public static class PasswordBoxHelper
    {
        public static readonly DependencyProperty BoundPasswordProperty =
            DependencyProperty.RegisterAttached(name: "BoundPassword",
                propertyType: typeof(string),
                ownerType: typeof(PasswordBoxHelper),
                new FrameworkPropertyMetadata(defaultValue: string.Empty, OnBoundPasswordChanged));

        2 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
        public static string GetBoundPassword(DependencyObject d)
        {
            if (!(d is PasswordBox box)) return (string) d.GetValue(dp: BoundPasswordProperty);

            // this funny little dance here ensures that we've hooked the
            // PasswordChanged event once, and only once.
            box.PasswordChanged -= PasswordChanged;
            box.PasswordChanged += PasswordChanged;

            return (string)d.GetValue(dp: BoundPasswordProperty);
        }

        1-Verweis | 0 Änderungen | 0 Autoren, 0 Änderungen
        public static void SetBoundPassword(DependencyObject d, string value)
        {
            ...
        }
    }
}
```

2. Adding some lines to the constructor of Bootstrapper.cs

```
1-Verweis | 0 Änderungen | 0 Autoren, 0 Änderungen
public class Bootstrapper : BootstrapperBase
{
    private readonly SimpleContainer _container = new SimpleContainer();
    // Constructor
    0 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
    public Bootstrapper()
    {
        Initialize();


        // Source: https://stackoverflow.com/questions/30631522/caliburn-micro-support-for-passwordbox
        ConventionManager.AddElementConvention<PasswordBox>(
            bindableProperty: PasswordBoxHelper.BoundPasswordProperty,
            parameterProperty: "Password",
            eventName: "PasswordChanged");
    }
}
```

See the example on stackoverflow.com...


11 Wiring up the WPF Login Form

11.1 Implementing a class `AuthenticatedUser.cs`

Holds the information for already authenticated users.



11.2 Implementing a helper class to handle API call interactions



```
User.cs    App.config    APIHelper.cs    Bootstrapper.cs*    LoginViewModel.cs*
opUI
namespace RMDesktopUI.Helpers
{
    /*
     * The aim of this class is to handle all API call interactions between the different views and the API.
     */
    2 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
    public class APIHelper : IAPIHelper
    {
        4 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
        private HttpClient ApiClient { get; set; }

        0 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
        public APIHelper()
        {
            InitializeClient();
        }

        1-Verweis | 0 Änderungen | 0 Autoren, 0 Änderungen
        private void InitializeClient()
        {
            var api = ConfigurationManager.AppSettings["api"];

            ApiClient = new HttpClient {BaseAddress = new Uri(uriString: "")};
            ApiClient.DefaultRequestHeaders.Accept.Clear();
            ApiClient.DefaultRequestHeaders.Accept.Add(new MediaTypeWithQualityHeaderValue(mediaType: "application/json"));
        }

        2 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
        public async Task<AuthenticatedUser> Authenticate(string username, string password)
        {
            var data = new FormUrlEncodedContent(nameValueCollection: new []
            {
                new KeyValuePair<string, string>("grant_type", "password"),
                new KeyValuePair<string, string>("username", username),
                new KeyValuePair<string, string>("password", password),
            });

            // Getting the token
            using (HttpResponseMessage response = await ApiClient.PostAsync(requestUri: "/Token", data))
            {
                if (response.IsSuccessStatusCode)
                {
                    // ReadAsStringAsync needs Microsoft.AspNet.WebApi.Client (NuGet-Package)
                    var result = await response.Content.ReadAsStringAsync<AuthenticatedUser>();
                    return result;
                }
                else
                {
                    throw new Exception(response.ReasonPhrase);
                }
            }
        }
    }
}
```

11.3 Implementing a Interface IAPIHelper.cs

Needed for dependency injection, in order to add it to the Configure() method in Bootstrapper.cs

```

AuthenticatedUser.cs  App.config  APIHelper.cs  Bootstrapper.cs*  LoginViewModel.cs*
opUI
using System.Threading.Tasks;
using RMDesktopUI.Models;

namespace RMDesktopUI.Helpers
{
    4 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
    public interface IAPIHelper
    {
        2 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
        Task<AuthenticatedUser> Authenticate(string username, string password);
    }
}

```

11.4 Adding <appsettings> to App.Config

```

<configuration>
<appSettings>
    <!--The value here is the project url, which can be found in properties/web.
        Can be changed at any time on runtime. It's possible to create several App.Config overrides.-->
    <add key="api" value="http://localhost:54756/" />
</appSettings>
<startup>

```

11.5 Adding APIHelper and IAPIHelper to the container in Bootstrapper.cs

```

        _container
            .Singleton<IWindowManager, WindowManager>()
            .Singleton<IEventAggregator, EventAggregator>()
            .Singleton<IAPIHelper, APIHelper>(); // Enables keeping the http-client open
                                                // until the application gets closed

```

11.6 Applying some changings to LoginViewModel.cs

11.6.1 Adding a new private property as a backing field

```

3 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
public class LoginViewModel : Screen
{
    /*
     * Backing fields
     */
    private string _userName;
    private string _password;

    private readonly IAPIHelper _apiHelper;
}

```

11.6.2 Adding a constructor and initializing the property from within

```

/*
 * Constructor
 */
0 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
public LoginViewModel(IAPIHelper apiHelper)
{
    _apiHelper = apiHelper;
}

```


11.6.3 Implementing the Login() method



```

0 Verweise | 0 Änderungen | 0 Autoren, 0 Änderungen
public async Task LogIn(string userName, string password)
{
    try
    {
        var result = await _apiHelper.Authenticate(username: UserName, Password);
    }
    catch (Exception ex)
    {
        Console.WriteLine(ex.Message);
    }
}

```

11.7 Enabling the solution to start multiple projects





- 12 Login Form Error Handling
- 13 Getting User Data
- 14 Sales Page Creation
- 15 Event Aggregation in WPF
- 16 Displaying Product data
- 17 Wiring up WPF Shopping Cart
- 18 Modifying SQL, the API and WPF to add Taxes