Source Code Deposit for Copyright Registration

Huru SMS

Multichannel SMS and Web Citizen Information and Guidance System for Tanzania
Complete source code listing, version 1.0

Owner and developer: Huru Digital Co. Ltd., Tanzania

Files listed: 112 original source files, 7991 lines in total

Programming languages: PHP (Laravel framework), HTML, CSS, JavaScript, JSON

Date of listing: 07 October 2026

Prepared for: Copyright Society of Tanzania (COSOTA)

This listing contains every file written by Huru Digital Co. Ltd. for the Huru SMS application. Third-party open-source libraries used by the application (the `vendor` and `node_modules` folders) are not reproduced here; they are the property of their respective authors and are only referenced in `composer.json` and `package.json`. Secret keys and user data are excluded.

Table of contents

#	File	Lines
1	.agents/AGENTS.md	21
2	.env.example	66
3	README.md	127
4	app/Console/Commands/FetchLegalAidProviders.php	121
5	app/Http/Controllers/Admin/AuthController.php	56
6	app/Http/Controllers/Admin/ConversationController.php	44
7	app/Http/Controllers/Admin/DashboardController.php	66
8	app/Http/Controllers/Admin/KnowledgeController.php	164
9	app/Http/Controllers/Admin/LocalResourceController.php	87
10	app/Http/Controllers/Admin/PromptTemplateController.php	89
11	app/Http/Controllers/Admin/ReferenceContactController.php	86
12	app/Http/Controllers/Admin/SettingController.php	38
13	app/Http/Controllers/Admin/UserController.php	51
14	app/Http/Controllers/CommunityController.php	157
15	app/Http/Controllers/ContactController.php	70
16	app/Http/Controllers/Controller.php	8
17	app/Http/Controllers/SmsController.php	68
18	app/Http/Controllers/WebChatController.php	333
19	app/Http/Middleware/EnsureAdmin.php	25
20	app/Http/Middleware/VerifySmsWebhook.php	43
21	app/Jobs/ProcessIncomingSms.php	57
22	app/Models/AiLog.php	26
23	app/Models/CommunityInvite.php	49
24	app/Models/CommunityMember.php	32
25	app/Models/CommunityPost.php	34
26	app/Models/CommunityReaction.php	27
27	app/Models/CommunityThread.php	47
28	app/Models/Feedback.php	31
29	app/Models/KnowledgeEntry.php	37
30	app/Models/LocalResource.php	41
31	app/Models/Message.php	38
32	app/Models/PromptTemplate.php	33
33	app/Models/ReferenceContact.php	51
34	app/Models/SystemSetting.php	12
35	app/Models/User.php	100
36	app/Providers/AppServiceProvider.php	37

#	File	Lines
37	app/Services/Ai/GeminiClient.php	131
38	app/Services/Ai/LlmClient.php	20
39	app/Services/AiService.php	59
40	app/Services/ConversationService.php	341
41	app/Services/KnowledgeRetriever.php	157
42	app/Services/LanguageDetector.php	92
43	app/Services/ModerationService.php	47
44	app/Services/PromptEngine.php	347
45	app/Services/SmsService.php	93
46	app/Services/TanzaniaContext.php	238
47	app/Services/TopicClassifier.php	266
48	app/Support/Phone.php	55
49	app/Support/Settings.php	222
50	artisan	18
51	bootstrap/app.php	25
52	bootstrap/providers.php	5
53	composer.json	88
54	config/services.php	49
55	database/factories/UserFactory.php	40
56	database/migrations/0001_01_01_000000_create_users_table.php	54
57	database/migrations/0001_01_01_000001_create_cache_table.php	35
58	database/migrations/0001_01_01_000002_create_jobs_table.php	57
59	database/migrations/2026_10_07_000001_create_messages_and_logs_tables.php	58
60	database/migrations/2026_10_07_000002_create_knowledge_and_config_tables.php	87
61	database/migrations/2026_10_07_000003_create_community_tables.php	76
62	database/seeders/AdminUserSeeder.php	44
63	database/seeders/CommunitySeeder.php	45
64	database/seeders/DatabaseSeeder.php	21
65	database/seeders/KnowledgeSeeder.php	343
66	database/seeders/LocalResourceSeeder.php	41
67	database/seeders/PromptTemplateSeeder.php	39
68	database/seeders/ReferenceContactSeeder.php	84
69	database/seeders/SettingsSeeder.php	25
70	package.json	17
71	phpunit.xml	35
72	public/manifest.json	16
73	public/robots.txt	6
74	public/sw.js	40
75	resources/css/app.css	11

#	File	Lines
76	resources/js/app.js	1
77	resources/js/bootstrap.js	4
78	resources/views/admin/contacts/form.blade.php	30
79	resources/views/admin/contacts/index.blade.php	31
80	resources/views/admin/conversations/index.blade.php	37
81	resources/views/admin/conversations/show.blade.php	34
82	resources/views/admin/dashboard.blade.php	71
83	resources/views/admin/knowledge/form.blade.php	22
84	resources/views/admin/knowledge/index.blade.php	58
85	resources/views/admin/login.blade.php	42
86	resources/views/admin/resources/form.blade.php	25
87	resources/views/admin/resources/index.blade.php	35
88	resources/views/admin/settings.blade.php	36
89	resources/views/admin/templates/form.blade.php	19
90	resources/views/admin/templates/index.blade.php	28
91	resources/views/admin/users/index.blade.php	37
92	resources/views/chat.blade.php	389
93	resources/views/community/index.blade.php	78
94	resources/views/community/show.blade.php	69
95	resources/views/layouts/admin.blade.php	123
96	resources/views/layouts/public.blade.php	57
97	resources/views/legal/privacy.blade.php	37
98	resources/views/legal/terms.blade.php	33
99	resources/views/offline.blade.php	28
100	resources/views/pagination/simple.blade.php	15
101	resources/views/welcome.blade.php	229
102	routes/api.php	10
103	routes/console.php	11
104	routes/web.php	120
105	tests/Feature/CommunityTest.php	45
106	tests/Feature/SmsFlowTest.php	108
107	tests/Feature/WebChatTest.php	113
108	tests/TestCase.php	10
109	tests/Unit/LanguageAndLocationTest.php	59
110	tests/Unit/PromptEngineTest.php	67
111	tests/Unit/TopicClassifierTest.php	63
112	vite.config.js	18

1 .agents/AGENTS.md

21 lines

```
# Project Rules - Huru SMS

Huru SMS is a generic, Tanzania-aware question answering service for every citizen (not only students, not only legal topics). It runs over SMS (shortcode `15054`, keyword `HURU`) and a web chat.

## Product
- **Generic by design**: any topic is valid. Topic detection (`App\Services\TopicClassifier`) only chooses the persona, knowledge and contacts; it never refuses a topic.
- **Tanzanian context first**: assume TZS, East Africa Time, Tanzanian law and institutions, Swahili as the default language. Country facts live in `App\Services\TanzaniaContext`; national contacts and knowledge live in the database and are edited in the admin panel, never hard-coded in prompts.
- **Honesty over confidence**: the engine must say when something should be confirmed with the responsible office and must never invent phone numbers, fees or officials. Keep this in every persona and constraint change.

## User interface and aesthetics
- **No "AI"/"Bot" wording** in user-facing text, page titles or labels. Present Huru SMS as a direct guidance service. The admin panel may say "engine".
- **Government palette**: Forest Green (`#166534` / `#15803d`), Royal Blue (`#1e40af` / `#1d4ed8`), white/off-white (`#ffffff`, `#f8fafc`). No brown, amber, gradients or glow effects on public pages.
- **Light, high-readability themes** for all citizen-facing pages. Plain Inter font.
- **SMS visibility**: the keyword `HURU` and shortcode `15054` must stay clearly visible on the home page and the web chat login screen, and must survive any layout refactor. Values come from settings (`sms_keyword`, `sms_shortcode`).
- Swahili is the primary language of public pages; English appears as a secondary line where it helps.

## Engineering
- All channel logic goes through `App\Services\ConversationService`; do not duplicate moderation or logging in controllers or jobs.
- New settings are declared in `App\Support\Settings::schema()` only; the admin form, validation and defaults derive from it.
- Keep the inbound SMS webhook behind `AT_WEBHOOK_SECRET` and keep TLS verification on for all outbound HTTP.
- Tests use SQLite in memory (`phpunit.xml`); keep migrations driver-agnostic.
```

2 .env.example

66 lines

```
APP_NAME="Huru SMS"
APP_ENV=local
APP_KEY=
APP_DEBUG=true
APP_URL=http://localhost
APP_TIMEZONE=Africa/Dar_es_Salaam

APP_LOCALE=sw
APP_FALLBACK_LOCALE=en
APP_FAKER_LOCALE=en_US

APP_MAINTENANCE_DRIVER=file

BCRYPT_ROUNDS=12

LOG_CHANNEL=stack
LOG_STACK=single
LOG_DEPRECATIONS_CHANNEL=null
LOG_LEVEL=debug

# MySQL for real deployments; sqlite works for a quick start.
DB_CONNECTION=mysql
DB_HOST=127.0.0.1
DB_PORT=3306
DB_DATABASE=huru
DB_USERNAME=root
DB_PASSWORD=

SESSION_DRIVER=database
SESSION_LIFETIME=120
SESSION_ENCRYPT=false
SESSION_PATH=/
SESSION_DOMAIN=null

BROADCAST_CONNECTION=log
FILESYSTEM_DISK=local
QUEUE_CONNECTION=database
CACHE_STORE=database

MAIL_MAILER=log
MAIL_HOST=127.0.0.1
MAIL_PORT=2525
MAIL_USERNAME=null
MAIL_PASSWORD=null
MAIL_FROM_ADDRESS="hello@example.com"
MAIL_FROM_NAME="${APP_NAME}"

VITE_APP_NAME="${APP_NAME}"

# ---- Admin bootstrap (used by `php artisan db:seed`) ----
ADMIN_NAME="Huru SMS Admin"
ADMIN_EMAIL=admin@huru.local
ADMIN_PASSWORD=

# ---- Google Gemini ----
GEMINI_API_KEY=
GEMINI_TIMEOUT=30

# ---- Africa's Talking SMS ----
AT_USERNAME=sandbox
AT_API_KEY=
AT_FROM=15054
# Random secret; append ?token=<value> to the callback URL you register with Africa's Talking.
AT_WEBHOOK_SECRET=
# Ignore inbound SMS that do not start with the keyword (shared short codes).
AT_REQUIRE_KEYWORD=false
```

3 README.md 127 lines

Huru SMS

Huru SMS is a digital service that lets any person in Tanzania ask a question and get a clear, useful answer on their phone, in Kiswahili or English. It works on the simplest mobile phone through SMS, and on smartphones and computers through a web chat.

Owner and developer: **Huru Digital Co. Ltd.**, Tanzania.

---

1. What the service does

A citizen sends a question. Huru SMS reads it, understands the topic and the language, checks where the person is, looks up verified information about Tanzania, and replies with a short, practical answer. If the person needs an office or a service near them (for example a legal aid provider in Kahama), the reply names it with its contact.

Topics covered include:

- Law and rights (arrest, land, marriage, inheritance, tenants, contracts)
- Health (danger signs, clinics, vaccination, health insurance)
- Farming, livestock and fishing (seasons, seeds, pests, animal vaccines)
- Education (school system, examinations, student loans, school subjects)
- Government services (NIDA identity card, birth certificate, passport, TIN, government payments, electricity)
- Money and business (taxes, loans, mobile money safety, registering a business)
- Jobs and employment (contracts, leave, dismissal, job scams)
- Family and community (violence, child protection, where to get help)
- Technology and transport (SIM cards, phone safety, traffic fines, driving licence)
- Any other everyday question

2. How a citizen uses it

By SMS (no internet needed)

1. Open the message app on any phone.
2. Write the word **HURU** followed by the question. Example: `HURU nifanyeje kupata kitambulisho cha NIDA?`
3. Send it to **15054**.
4. The answer arrives as an SMS within a short time.

Helpful SMS commands:

Send	What happens
`MSAADA` or `HELP`	A short guide to the service
`LUGHA SW` / `LUGHA EN`	Choose Kiswahili or English for replies
`JINA Asha`	Save your name
`MKOA Mwanza`	Save your region, so nearby services are suggested
`ACHA`	Stop receiving replies
`ANZA`	Start again

By web chat (with internet)

1. Open the website and press **Web Chat**.
2. Enter a phone number. A one-time code is sent by SMS to confirm it is yours.
3. Ask questions in the chat. Previous conversations are saved, can be searched, and each answer can be rated helpful or not helpful.

3. What makes it different

- **Built for Tanzania.** The service assumes Tanzanian law, the Tanzanian shilling, East Africa time, Tanzanian institutions (NIDA, RITA, TRA, NHIF, NECTA, HESLB and others) and the real emergency numbers (112, 114, 115, 116).
- **Knows where you are.** It recognises all 31 regions, common districts and well-known neighbourhoods, and uses that to point people to services close to them.
- **Verified knowledge first.** Answers are grounded in a knowledge base and directories maintained by the operator, not only on general internet knowledge. The service says clearly when something should be confirmed with the responsible office, and it never invents phone numbers, fees or names of officials.
- **Two languages, one service.** It detects whether a question is in Kiswahili or English and answers in the same language.
- **Works on every phone.** SMS first, web second. Replies sent by SMS are kept short to fit a few text messages.
- **Safe to use.** Abusive language is warned and then blocked, emergencies are recognised and the right number is given first, and people can stop the service at any time.

4. What the operator can manage

A protected administration area lets Huru Digital staff:

- see how many questions arrive, by day, by topic and by channel;
- read conversations and the information used to answer them;
- add or edit knowledge entries (one by one or by importing a file);
- maintain the national directory of institutions and hotlines, and the list of local services by region and district;
- adjust the wording and behaviour of the service per topic and language;
- change settings such as reply length, language policy and safety limits;
- block or unblock users.

5. Privacy and safety

- Only the phone number and the conversation are stored. They are needed to continue a conversation and to let the person see their own history.
- The web chat requires a one-time SMS code before a phone number's history can be opened.
- A person's name and phone number are never sent together with the question to the language technology provider.
- Government payments are always described as being made through official control numbers, never cash to an officer.
- Full terms and a privacy policy are published on the website.

6. Technology used (for the technical reader)

Part	Technology
Application	PHP 8.2 with the Laravel 12 framework
Database	MySQL 8 (SQLite for quick local testing)
SMS	Africa's Talking SMS gateway (shortcode 15054, keyword HURU)
Language technology	Google Gemini, used only to word the final reply after the service has gathered the Tanzanian context
Web pages	HTML, CSS and JavaScript; installable as a phone app (PWA)
Tests	28 automated tests covering SMS, web chat, topic detection, location detection and the administration area

Main parts of the source code:

Folder or file	Purpose
`app/Services/ConversationService.php`	Handles every incoming question, commands, safety checks and logging
`app/Services/TopicClassifier.php`	Detects the topic of a question and recognises emergencies
`app/Services/TanzaniaContext.php`	Regions, districts, country facts and topic rules for Tanzania
`app/Services/KnowledgeRetriever.php`	Finds the most relevant verified knowledge entries
`app/Services/PromptEngine.php`	Combines persona, context, knowledge and contacts into instructions for the reply
`app/Services/Ai/`	Connection to the language technology provider
`app/Services/SmsService.php`	Sending SMS through Africa's Talking
`app/Http/Controllers/`	Web chat, SMS receiver, community and administration screens
`database/seeders/`	Starter knowledge, directories, personas and settings
`resources/views/`	All web pages
`tests/`	Automated tests

7. Running the application

```bash
cp .env.example .env         # fill in GEMINI_API_KEY, AT_* and database details
composer install
npm install && npm run build
php artisan key:generate
php artisan migrate --seed   # creates tables, the admin account and starter data
php artisan serve            # open http://localhost:8000
php artisan queue:work       # processes SMS replies (or run the scheduler every minute)
php artisan huru:import-legal-aid   # imports the national legal aid provider list
```

The SMS gateway must be configured to deliver incoming messages to `/api/sms/inbound?token=<AT_WEBHOOK_SECRET>`.

Administration is at `/admin/login`.

8. Ownership

Huru SMS, its source code, its content and its documentation are the property of Huru Digital Co. Ltd. All rights reserved.

4 app/Console/Commands/FetchLegalAidProviders.php

121 lines

```php
<?php

namespace App\Console\Commands;

use App\Models\LocalResource;
use App\Services\TanzaniaContext;
use Illuminate\Console\Command;
use Illuminate\Support\Facades\Http;
use Illuminate\Support\Str;

/**
 * Imports registered legal aid providers from the Mama Samia Legal Aid
 * Campaign site (mslac.or.tz) into local_resources as category legal_aid.
 */
class FetchLegalAidProviders extends Command
{
    protected $signature = 'huru:import-legal-aid {--pages=16 : Number of listing pages to read}';

    protected $description = 'Import legal aid providers from mslac.or.tz into the local resources directory';

    public function handle(TanzaniaContext $tz): int
    {
        $pages = (int) $this->option('pages');
        $imported = 0;

        for ($page = 0; $page < $pages; $page++) {
            $url = "https://www.mslac.or.tz/en/legal-aid-providers?page={$page}";
            $this->line('Fetching ' . ($page + 1) . "/{$pages}: {$url}");

            try {
                $response = Http::retry(3, 2000)->timeout(45)
                    ->withHeaders(['User-Agent' => 'HuruBot/1.0 (+https://hurudigital.co.tz)'])
                    ->get($url);
            } catch (\Throwable $e) {
                $this->error('Request failed: ' . $e->getMessage());

                continue;
            }

            if (! $response->successful()) {
                $this->error('HTTP ' . $response->status());

                continue;
            }

            $chunks = explode('class="item-columns"', $response->body());
            array_shift($chunks);
            if (empty($chunks)) {
                $this->warn('No provider cards found; stopping.');
                break;
            }

            foreach ($chunks as $chunk) {
                preg_match('/views-field-title.*?<strong class="field-content">(.*?)<\/strong>/s', $chunk, $m);
                $name = isset($m[1]) ? trim(strip_tags($m[1])) : null;
                if (! $name) {
                    continue;
                }

                preg_match('/views-field-field-region.*?<div class="field-content">(.*?)<\/div>/s', $chunk, $m);
                $regionRaw = isset($m[1]) ? trim(strip_tags($m[1])) : null;

                preg_match('/views-field-field-address.*?<div class="field-content">(.*?)<\/div>/s', $chunk, $m);
                $location = isset($m[1]) ? trim(preg_replace('/\s+/', ' ', strip_tags($m[1]))) : null;

                $region = null;
                $district = null;
                $detected = $tz->detectLocation(trim(($regionRaw ?? '') . ' ' . ($location ?? '')));
                if ($detected) {
                    $region = $detected['region'];
                    $district = $detected['district'];
```

```
                }
                if (! $region && $regionRaw) {
                    $region = Str::lower($regionRaw);
                }
                if (! $district && $location && preg_match('/wilaya\s+(?:ya\s+)?([a-z\']+)/i', $location, $dm)) {
                    $district = Str::lower($dm[1]);
                }

                $email = null;
                if ($location && preg_match('/[a-z0-9._%+-]+@[a-z0-9.-]+\.[a-z]{2,}/i', $location, $em)) {
                    $email = $em[0];
                }
                preg_match('/views-field-field-email.*?href="mailto:(.*?)"/s', $chunk, $em2);
                if (! empty($em2[1])) {
                    $email = trim(strip_tags($em2[1]));
                }

                $phone = null;
                if ($location && preg_match('/(?:\+255|0)[67]\d{8}/', str_replace([' ', '-', '(', ')', '/'], '',
$location), $pm)) {
                    $phone = $pm[0];
                }
                preg_match('/views-field-field-phone.*?<div class="field-content">(.*?)<\/div>/s', $chunk, $pm2);
                if (! empty($pm2[1])) {
                    $phone = trim(strip_tags($pm2[1]));
                }

                LocalResource::query()->updateOrCreate(
                    ['name' => $name],
                    [
                        'category' => 'legal_aid',
                        'region' => $region,
                        'district' => $district,
                        'location' => $location,
                        'email' => $email,
                        'phone' => $phone,
                        'source' => 'mslac.or.tz',
                        'is_active' => true,
                    ]
                );
                $imported++;
            }

            usleep(500000);
        }

        $this->info("Done. Providers imported or updated: {$imported}");

        return self::SUCCESS;
    }
}
```

5 app/Http/Controllers/Admin/AuthController.php

56 lines

```php
<?php

namespace App\Http\Controllers\Admin;

use App\Http\Controllers\Controller;
use App\Models\User;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Auth;
use Illuminate\Support\Facades\RateLimiter;
use Illuminate\Support\Str;

class AuthController extends Controller
{
    public function showLogin(Request $request)
    {
        if ($request->user()?->isAdmin()) {
            return redirect()->route('admin.dashboard');
        }

        return view('admin.login');
    }

    public function login(Request $request)
    {
        $data = $request->validate([
            'email' => 'required|email',
            'password' => 'required|string',
        ]);

        $key = 'admin-login:' . Str::lower($data['email']) . '|' . $request->ip();
        if (RateLimiter::tooManyAttempts($key, 5)) {
            return back()->withErrors(['email' => 'Too many attempts. Try again in a minute.'])->onlyInput('email');
        }

        $user = User::query()->where('email', $data['email'])->first();
        if (! $user || ! $user->isAdmin() || ! Auth::attempt(['email' => $data['email'], 'password' => $data['password']], $request->boolean('remember'))) {
            RateLimiter::hit($key, 60);

            return back()->withErrors(['email' => 'These credentials do not match an admin account.'])->onlyInput('email');
        }

        RateLimiter::clear($key);
        $request->session()->regenerate();

        return redirect()->intended(route('admin.dashboard'));
    }

    public function logout(Request $request)
    {
        Auth::logout();
        $request->session()->invalidate();
        $request->session()->regenerateToken();

        return redirect()->route('admin.login');
    }
}
```

6 app/Http/Controllers/Admin/ConversationController.php

44 lines

```php
<?php

namespace App\Http\Controllers\Admin;

use App\Http\Controllers\Controller;
use App\Models\Message;
use App\Models\User;
use Illuminate\Http\Request;

class ConversationController extends Controller
{
    public function index(Request $request)
    {
        $query = Message::query()->with(['user', 'aiLog', 'feedback'])->latest('id');

        if ($request->filled('q')) {
            $q = '%' . $request->string('q') . '%';
            $query->where(fn ($w) => $w->where('content', 'like', $q)->orWhereHas('user', fn ($u) => $u->where('phone_number', 'like', $q)->orWhere('name', 'like', $q)));
        }
        if ($request->filled('category')) {
            $query->where('category', $request->string('category'));
        }
        if ($request->filled('channel')) {
            $query->where('channel', $request->string('channel'));
        }
        if ($request->filled('direction')) {
            $query->where('direction', $request->string('direction'));
        }
        if ($request->filled('date')) {
            $query->whereDate('created_at', $request->string('date'));
        }

        $messages = $query->paginate(40)->withQueryString();

        return view('admin.conversations.index', compact('messages'));
    }

    public function show(User $user)
    {
        $messages = $user->messages()->with(['aiLog', 'feedback'])->latest('id')->paginate(60);

        return view('admin.conversations.show', compact('user', 'messages'));
    }
}
```

7 app/Http/Controllers/Admin/DashboardController.php

66 lines

```php
<?php

namespace App\Http\Controllers\Admin;

use App\Http\Controllers\Controller;
use App\Models\AiLog;
use App\Models\Feedback;
use App\Models\Message;
use App\Models\User;
use App\Services\AiService;
use App\Services\SmsService;
use App\Services\TopicClassifier;
use Illuminate\Support\Facades\DB;

class DashboardController extends Controller
{
    public function index(AiService $ai, SmsService $sms)
    {
        $today = now()->startOfDay();
        $week = now()->subDays(7);

        $stats = [
            'users' => User::query()->where('role', User::ROLE_USER)->count(),
            'users_today' => User::query()->where('role', User::ROLE_USER)->where('created_at', '>=', $today)->count(),
            'questions_today' => Message::query()->where('direction', Message::DIRECTION_IN)->where('created_at', '>=', $today)->count(),
            'questions_week' => Message::query()->where('direction', Message::DIRECTION_IN)->where('created_at', '>=', $week)->count(),
            'sms_week' => Message::query()->where('direction', Message::DIRECTION_IN)->where('channel', 'sms')->where('created_at', '>=', $week)->count(),
            'web_week' => Message::query()->where('direction', Message::DIRECTION_IN)->where('channel', 'web')->where('created_at', '>=', $week)->count(),
            'tokens_today' => (int) AiLog::query()->where('created_at', '>=', $today)->sum('total_tokens'),
            'latency_avg' => (int) round((float) AiLog::query()->where('created_at', '>=', $week)->where('status', 'ok')->avg('latency_ms')),
            'errors_week' => AiLog::query()->where('created_at', '>=', $week)->where('status', '!=', 'ok')->count(),
            'banned' => User::query()->where('is_banned', true)->count(),
            'helpful' => Feedback::query()->where('rating', 1)->count(),
            'unhelpful' => Feedback::query()->where('rating', -1)->count(),
        ];

        $byCategory = Message::query()
            ->select('category', DB::raw('count(*) as total'))
            ->where('direction', Message::DIRECTION_IN)
            ->where('created_at', '>=', $week)
            ->whereNotNull('category')
            ->groupBy('category')
            ->orderByDesc('total')
            ->get()
            ->map(fn ($row) => ['key' => $row->category, 'label' => TopicClassifier::label($row->category, 'en'), 'total' => (int) $row->total]);

        $daily = Message::query()
            ->select(DB::raw('DATE(created_at) as day'), DB::raw('count(*) as total'))
            ->where('direction', Message::DIRECTION_IN)
            ->where('created_at', '>=', now()->subDays(13)->startOfDay())
            ->groupBy('day')
            ->orderBy('day')
            ->pluck('total', 'day');

        $recent = Message::query()->with(['user', 'aiLog', 'feedback'])->latest('id')->take(25)->get();

        $health = [
            'engine_configured' => $ai->isConfigured(),
            'sms_configured' => $sms->isConfigured(),
            'webhook_secret' => (bool) config('services.at.webhook_secret'),
            'queue' => config('queue.default'),
        ];

```

```
64          return view('admin.dashboard', compact('stats', 'byCategory', 'daily', 'recent', 'health'));
65      }
66  }
```

8 app/Http/Controllers/Admin/KnowledgeController.php

164 lines

```php
<?php

namespace App\Http\Controllers\Admin;

use App\Http\Controllers\Controller;
use App\Models\KnowledgeEntry;
use App\Services\KnowledgeRetriever;
use App\Services\TopicClassifier;
use Illuminate\Http\Request;
use Illuminate\Support\Str;

class KnowledgeController extends Controller
{
    public function index(Request $request)
    {
        $query = KnowledgeEntry::query()->latest();

        if ($request->filled('q')) {
            $q = '%' . $request->string('q') . '%';
            $query->where(fn ($w) => $w->where('title', 'like', $q)->orWhere('content', 'like', $q));
        }
        if ($request->filled('category')) {
            $query->where('category', $request->string('category'));
        }
        if ($request->filled('language')) {
            $query->where('language', $request->string('language'));
        }

        $entries = $query->paginate(20)->withQueryString();
        $counts = KnowledgeEntry::query()->selectRaw('category, count(*) as total')->groupBy('category')->pluck('total', 'category');

        return view('admin.knowledge.index', compact('entries', 'counts'));
    }

    public function create()
    {
        return view('admin.knowledge.form', ['entry' => new KnowledgeEntry(['language' => 'sw', 'category' => 'general', 'is_active' => true])]);
    }

    public function store(Request $request, KnowledgeRetriever $retriever)
    {
        $data = $this->validated($request);
        $data['keywords'] = $this->keywords($data, $retriever);
        KnowledgeEntry::query()->create($data);

        return redirect()->route('admin.knowledge.index')->with('success', 'Knowledge entry created.');
    }

    public function edit(KnowledgeEntry $knowledge)
    {
        return view('admin.knowledge.form', ['entry' => $knowledge]);
    }

    public function update(Request $request, KnowledgeEntry $knowledge, KnowledgeRetriever $retriever)
    {
        $data = $this->validated($request);
        $data['keywords'] = $this->keywords($data, $retriever);
        $knowledge->update($data);

        return redirect()->route('admin.knowledge.index')->with('success', 'Knowledge entry updated.');
    }

    public function toggle(KnowledgeEntry $knowledge)
    {
        $knowledge->update(['is_active' => ! $knowledge->is_active]);

        return back()->with('success', 'Entry ' . ($knowledge->is_active ? 'activated' : 'deactivated') . '.');
    }

```

```
    public function destroy(KnowledgeEntry $knowledge)
    {
        $knowledge->delete();

        return back()->with('success', 'Knowledge entry deleted.');
    }

    /**
     * Bulk import. CSV columns: title, content, category, language, keywords (comma separated), source, summary.
     * JSON: an array of objects with the same keys (keywords may be an array).
     */
    public function import(Request $request, KnowledgeRetriever $retriever)
    {
        $request->validate([
            'file' => 'required|file|mimes:csv,txt,json|max:5120',
            'default_category' => 'required|in:' . implode(',', TopicClassifier::keys()),
            'default_language' => 'required|in:sw,en',
        ]);

        $file = $request->file('file');
        $ext = strtolower($file->getClientOriginalExtension());
        $rows = [];

        if ($ext === 'json') {
            $decoded = json_decode(file_get_contents($file->getRealPath()), true);
            if (is_array($decoded)) {
                $rows = isset($decoded['title']) ? [$decoded] : $decoded;
            }
        } else {
            $handle = fopen($file->getRealPath(), 'r');
            $header = fgetcsv($handle);
            if ($header) {
                $header = array_map(fn ($h) => Str::snake(Str::lower(trim((string) $h))), $header);
                while (($row = fgetcsv($handle)) !== false) {
                    if (count(array_filter($row)) === 0) {
                        continue;
                    }
                    $rows[] = array_combine($header, array_pad($row, count($header), null));
                }
            }
            fclose($handle);
        }

        $count = 0;
        foreach ($rows as $row) {
            if (empty($row['title']) || empty($row['content'])) {
                continue;
            }
            $category = in_array($row['category'] ?? '', TopicClassifier::keys(), true) ? $row['category'] :
$request->input('default_category');
            $language = in_array($row['language'] ?? '', ['sw', 'en'], true) ? $row['language'] : $request-
>input('default_language');
            $keywords = $row['keywords'] ?? [];
            if (is_string($keywords)) {
                $keywords = array_filter(array_map('trim', explode(',', $keywords)));
            }
            $data = [
                'title' => Str::limit(trim($row['title']), 250, ''),
                'content' => trim($row['content']),
                'summary' => $row['summary'] ?? Str::limit(trim($row['content']), 160),
                'category' => $category,
                'language' => $language,
                'source' => $row['source'] ?? null,
                'is_active' => true,
            ];
            $data['keywords'] = $this->keywords($data + ['keywords_text' => implode(',', $keywords)], $retriever);

            KnowledgeEntry::query()->updateOrCreate(['title' => $data['title'], 'language' => $language], $data);
            $count++;
        }

        return back()->with('success', "Imported {$count} knowledge entries.");
    }
```

```
141
142     private function validated(Request $request): array
143     {
144         return $request->validate([
145             'title' => 'required|string|max:250',
146             'content' => 'required|string|max:20000',
147             'summary' => 'nullable|string|max:500',
148             'category' => 'required|in:' . implode(',', TopicClassifier::keys()),
149             'language' => 'required|in:sw,en',
150             'keywords_text' => 'nullable|string|max:1000',
151             'source' => 'nullable|string|max:250',
152             'is_active' => 'sometimes|boolean',
153         ]) + ['is_active' => $request->boolean('is_active')];
154     }
155
156     /** Explicit keywords plus title tokens, so retrieval works even when the admin leaves keywords empty. */
157     private function keywords(array $data, KnowledgeRetriever $retriever): array
158     {
159         $explicit = array_filter(array_map(fn ($k) => Str::lower(trim($k)), explode(',', (string)
($data['keywords_text'] ?? ''))));
160         $fromTitle = $retriever->tokens($data['title']);
161
162         return array_values(array_unique(array_merge($explicit, $fromTitle)));
163     }
164 }
```

9 app/Http/Controllers/Admin/LocalResourceController.php

87 lines

```php
<?php

namespace App\Http\Controllers\Admin;

use App\Http\Controllers\Controller;
use App\Models\LocalResource;
use App\Services\TanzaniaContext;
use Illuminate\Http\Request;
use Illuminate\Support\Str;

class LocalResourceController extends Controller
{
    public function index(Request $request)
    {
        $query = LocalResource::query()->orderBy('region')->orderBy('district')->orderBy('name');

        if ($request->filled('q')) {
            $q = '%' . $request->string('q') . '%';
            $query->where(fn ($w) => $w->where('name', 'like', $q)->orWhere('location', 'like', $q)->orWhere('district', 'like', $q));
        }
        if ($request->filled('region')) {
            $query->where('region', Str::lower($request->string('region')));
        }
        if ($request->filled('category')) {
            $query->where('category', $request->string('category'));
        }

        return view('admin.resources.index', [
            'resources' => $query->paginate(30)->withQueryString(),
            'regions' => TanzaniaContext::REGIONS,
            'categories' => LocalResource::CATEGORIES,
            'byRegion' => LocalResource::query()->selectRaw('region, count(*) as total')->groupBy('region')->orderByDesc('total')->pluck('total', 'region'),
        ]);
    }

    public function create()
    {
        return view('admin.resources.form', ['resource' => new LocalResource(['category' => 'legal_aid', 'is_active' => true]), 'regions' => TanzaniaContext::REGIONS, 'categories' => LocalResource::CATEGORIES]);
    }

    public function store(Request $request)
    {
        LocalResource::query()->create($this->validated($request));

        return redirect()->route('admin.resources.index')->with('success', 'Resource created.');
    }

    public function edit(LocalResource $resource)
    {
        return view('admin.resources.form', ['resource' => $resource, 'regions' => TanzaniaContext::REGIONS, 'categories' => LocalResource::CATEGORIES]);
    }

    public function update(Request $request, LocalResource $resource)
    {
        $resource->update($this->validated($request));

        return redirect()->route('admin.resources.index')->with('success', 'Resource updated.');
    }

    public function destroy(LocalResource $resource)
    {
        $resource->delete();

        return back()->with('success', 'Resource deleted.');
    }

    private function validated(Request $request): array
```

```
    {
        $data = $request->validate([
            'name' => 'required|string|max:150',
            'category' => 'required|in:' . implode(',', array_keys(LocalResource::CATEGORIES)),
            'region' => 'required|in:' . implode(',', TanzaniaContext::REGIONS),
            'district' => 'nullable|string|max:40',
            'ward' => 'nullable|string|max:60',
            'location' => 'nullable|string|max:500',
            'phone' => 'nullable|string|max:60',
            'email' => 'nullable|email|max:120',
            'is_active' => 'sometimes|boolean',
        ]);

        $data['district'] = $data['district'] ? Str::lower(trim($data['district'])) : null;
        $data['is_active'] = $request->boolean('is_active');
        $data['source'] = 'admin';

        return $data;
    }
}
```

10 app/Http/Controllers/Admin/PromptTemplateController.php

89 lines

```php
<?php

namespace App\Http\Controllers\Admin;

use App\Http\Controllers\Controller;
use App\Models\PromptTemplate;
use App\Services\TopicClassifier;
use Illuminate\Http\Request;

class PromptTemplateController extends Controller
{
    public function index()
    {
        $templates = PromptTemplate::query()->orderBy('category')->orderBy('language')->get();

        return view('admin.templates.index', compact('templates'));
    }

    public function create()
    {
        return view('admin.templates.form', ['template' => new PromptTemplate(['category' => 'general', 'language' => 'sw', 'is_active' => true])]);
    }

    public function store(Request $request)
    {
        $data = $this->validated($request);
        PromptTemplate::query()->create($data);
        $this->ensureSingleActive($data);

        return redirect()->route('admin.templates.index')->with('success', 'Template created.');
    }

    public function edit(PromptTemplate $template)
    {
        return view('admin.templates.form', compact('template'));
    }

    public function update(Request $request, PromptTemplate $template)
    {
        $data = $this->validated($request, $template);
        $template->update($data);
        $this->ensureSingleActive($data, $template->id);

        return redirect()->route('admin.templates.index')->with('success', 'Template updated.');
    }

    public function toggle(PromptTemplate $template)
    {
        $template->update(['is_active' => ! $template->is_active]);
        if ($template->is_active) {
            $this->ensureSingleActive($template->only('category', 'language'), $template->id);
        }

        return back()->with('success', 'Template ' . ($template->is_active ? 'activated' : 'deactivated') . '.');
    }

    public function destroy(PromptTemplate $template)
    {
        $template->delete();

        return redirect()->route('admin.templates.index')->with('success', 'Template deleted.');
    }

    private function validated(Request $request, ?PromptTemplate $existing = null): array
    {
        return $request->validate([
            'name' => 'required|string|max:80|unique:prompt_templates,name' . ($existing ? ',' . $existing->id : ''),
            'category' => 'required|in:' . implode(',', TopicClassifier::keys()),
            'language' => 'required|in:sw,en',
```

```
            'template' => 'required|string|min:20|max:4000',
            'is_active' => 'sometimes|boolean',
        ]) + ['is_active' => $request->boolean('is_active')];
    }

    /** Only one active persona per (category, language). */
    private function ensureSingleActive(array $data, ?int $keepId = null): void
    {
        if (empty($data['is_active']) && $keepId === null) {
            return;
        }
        $keep = $keepId ?? PromptTemplate::query()->where('name', $data['name'])->value('id');
        PromptTemplate::query()
            ->where('category', $data['category'])
            ->where('language', $data['language'])
            ->where('id', '!=', $keep)
            ->update(['is_active' => false]);
        cache()->forget('huru.templates.active');
    }
}
```

11 app/Http/Controllers/Admin/ReferenceContactController.php

86 lines

```php
<?php

namespace App\Http\Controllers\Admin;

use App\Http\Controllers\Controller;
use App\Models\ReferenceContact;
use App\Services\TopicClassifier;
use Illuminate\Http\Request;

class ReferenceContactController extends Controller
{
    public const CATEGORIES = ['police', 'legal', 'health', 'family', 'government', 'finance', 'business', 'employment', 'education', 'agriculture', 'technology', 'transport', 'general'];

    public function index(Request $request)
    {
        $query = ReferenceContact::query()->orderBy('sort_order')->orderBy('name');
        if ($request->filled('category')) {
            $query->where('category', $request->string('category'));
        }

        return view('admin.contacts.index', ['contacts' => $query->get(), 'categories' => self::CATEGORIES]);
    }

    public function create()
    {
        return view('admin.contacts.form', ['contact' => new ReferenceContact(['category' => 'government', 'is_active' => true, 'sort_order' => 100]), 'categories' => self::CATEGORIES]);
    }

    public function store(Request $request)
    {
        ReferenceContact::query()->create($this->validated($request));

        return redirect()->route('admin.contacts.index')->with('success', 'Contact created.');
    }

    public function edit(ReferenceContact $contact)
    {
        return view('admin.contacts.form', ['contact' => $contact, 'categories' => self::CATEGORIES]);
    }

    public function update(Request $request, ReferenceContact $contact)
    {
        $contact->update($this->validated($request));

        return redirect()->route('admin.contacts.index')->with('success', 'Contact updated.');
    }

    public function verify(ReferenceContact $contact)
    {
        $contact->update(['verified_at' => $contact->verified_at ? null : now()]);

        return back()->with('success', $contact->verified_at ? 'Marked as verified.' : 'Verification cleared.');
    }

    public function destroy(ReferenceContact $contact)
    {
        $contact->delete();

        return back()->with('success', 'Contact deleted.');
    }

    private function validated(Request $request): array
    {
        $data = $request->validate([
            'name' => 'required|string|max:150',
            'category' => 'required|in:' . implode(',', self::CATEGORIES),
            'phone' => 'nullable|string|max:60',
            'alt_phone' => 'nullable|string|max:60',
            'email' => 'nullable|email|max:120',
```

```
            'website' => 'nullable|url|max:200',
            'description_sw' => 'nullable|string|max:500',
            'description_en' => 'nullable|string|max:500',
            'sort_order' => 'required|integer|min:0|max:1000',
            'is_emergency' => 'sometimes|boolean',
            'is_active' => 'sometimes|boolean',
            'verified' => 'sometimes|boolean',
        ]);

        $data['is_emergency'] = $request->boolean('is_emergency');
        $data['is_active'] = $request->boolean('is_active');
        $data['verified_at'] = $request->boolean('verified') ? now() : null;
        unset($data['verified']);

        return $data;
    }
}
```

12 app/Http/Controllers/Admin/SettingController.php

38 lines

```php
<?php

namespace App\Http\Controllers\Admin;

use App\Http\Controllers\Controller;
use App\Support\Settings;
use Illuminate\Http\Request;

class SettingController extends Controller
{
    public function index()
    {
        return view('admin.settings', [
            'groups' => Settings::groups(),
            'values' => Settings::all(),
        ]);
    }

    public function update(Request $request)
    {
        $rules = Settings::rules();

        // Unchecked checkboxes are absent from the request: treat as "0".
        foreach (Settings::schema() as $key => $def) {
            if ($def['type'] === 'boolean' && ! $request->has($key)) {
                $request->merge([$key => '0']);
            }
        }

        $data = $request->validate($rules);

        foreach ($data as $key => $value) {
            Settings::set($key, $value);
        }

        return back()->with('success', 'Settings saved.');
    }
}
```

13 app/Http/Controllers/Admin/UserController.php

51 lines

```php
<?php

namespace App\Http\Controllers\Admin;

use App\Http\Controllers\Controller;
use App\Models\User;
use Illuminate\Http\Request;

class UserController extends Controller
{
    public function index(Request $request)
    {
        $query = User::query()->where('role', User::ROLE_USER)->withCount('messages')->latest('last_seen_at');

        if ($request->filled('q')) {
            $q = '%' . $request->string('q') . '%';
            $query->where(fn ($w) => $w->where('phone_number', 'like', $q)->orWhere('name', 'like', $q));
        }
        if ($request->boolean('banned')) {
            $query->where('is_banned', true);
        }
        if ($request->filled('region')) {
            $query->where('region', $request->string('region'));
        }

        return view('admin.users.index', ['users' => $query->paginate(40)->withQueryString()]);
    }

    public function toggleBan(User $user)
    {
        abort_if($user->isAdmin(), 403);
        $user->update(['is_banned' => ! $user->is_banned]);

        return back()->with('success', $user->is_banned ? 'User blocked.' : 'User unblocked.');
    }

    public function resetStrikes(User $user)
    {
        $user->update(['abuse_count' => 0, 'is_banned' => false]);

        return back()->with('success', 'Strikes cleared.');
    }

    public function destroy(User $user)
    {
        abort_if($user->isAdmin(), 403);
        $user->delete();

        return redirect()->route('admin.users.index')->with('success', 'User and their history deleted.');
    }
}
```

14 app/Http/Controllers/CommunityController.php

157 lines

```php
<?php

namespace App\Http\Controllers;

use App\Models\CommunityPost;
use App\Models\CommunityThread;
use App\Models\User;
use App\Services\ModerationService;
use App\Support\Settings;
use Illuminate\Http\Request;
use Illuminate\Support\Str;

class CommunityController extends Controller
{
    public function index(Request $request)
    {
        $user = $this->currentUser($request);
        if (! $user) {
            return redirect()->route('chat.index', ['redirect' => $request->getRequestUri()])
                ->with('error', 'Tafadhali ingia kwanza kufikia jamii. / Please sign in to access the community.');
        }

        $publicThreads = CommunityThread::query()->where('is_private', false)->withCount('posts', 'members')->latest()->get();
        $joinedIds = $user->joinedThreads()->pluck('community_threads.id')->all();
        $joinedThreads = $user->joinedThreads()->withCount('posts')->latest()->get();

        return view('community.index', compact('publicThreads', 'joinedThreads', 'joinedIds', 'user') + ['settings' => $this->settings()]);
    }

    public function show(Request $request, CommunityThread $thread)
    {
        $user = $this->currentUser($request);
        if (! $user) {
            return redirect()->route('chat.index', ['redirect' => $request->getRequestUri()]);
        }

        $isMember = $thread->members()->where('user_id', $user->id)->exists();
        if ($thread->is_private && ! $isMember) {
            return redirect()->route('community.index')->with('error', 'Huu ni mjadala wa faragha. / This is a private thread.');
        }

        $posts = $thread->posts()->where('is_approved', true)->with('user')->orderBy('created_at')->paginate(50);
        $members = $thread->members()->get();

        return view('community.show', compact('thread', 'posts', 'members', 'user', 'isMember') + ['settings' => $this->settings()]);
    }

    public function storeThread(Request $request)
    {
        $user = $this->currentUser($request);
        if (! $user) {
            return response()->json(['error' => 'Unauthorized'], 401);
        }
        if ($user->is_banned) {
            return back()->with('error', 'Huduma imefungwa kwa akaunti hii.');
        }

        $data = $request->validate([
            'title' => 'required|string|min:3|max:120',
            'description' => 'nullable|string|max:1000',
            'is_private' => 'sometimes|boolean',
        ]);

        $thread = CommunityThread::query()->create([
            'title' => $data['title'],
            'slug' => Str::slug($data['title']) . '-' . Str::lower(Str::random(5)),
            'description' => $data['description'] ?? null,
```

```
            'creator_id' => $user->id,
            'is_private' => $request->boolean('is_private'),
        ]);

        $thread->members()->attach($user->id, ['role' => 'admin']);

        return redirect()->route('community.show', $thread);
    }

    public function storePost(Request $request, CommunityThread $thread, ModerationService $moderation)
    {
        $user = $this->currentUser($request);
        if (! $user) {
            return response()->json(['error' => 'Unauthorized'], 401);
        }
        if ($user->is_banned) {
            return response()->json(['error' => 'Account blocked'], 403);
        }
        if (! $thread->members()->where('user_id', $user->id)->exists()) {
            return response()->json(['error' => 'Si mwanachama wa mjadala huu. / Not a member of this thread.'],
403);
        }

        $data = $request->validate(['content' => 'required|string|min:2|max:3000']);

        if ($moderation->isAbusive($data['content'])) {
            $user->increment('abuse_count');
            if ($user->abuse_count >= Settings::int('abuse_strike_limit')) {
                $user->forceFill(['is_banned' => true])->save();
            }

            return response()->json(['error' => 'Lugha ya matusi hairuhusiwi. / Abusive language is not allowed.'],
422);
        }

        $post = CommunityPost::query()->create([
            'community_thread_id' => $thread->id,
            'user_id' => $user->id,
            'content' => $data['content'],
            'is_approved' => ! $thread->is_system, // system threads are moderated before display on the landing
page
        ]);

        if ($request->expectsJson()) {
            return response()->json(['status' => 'success', 'post' => $post->load('user'), 'pending' => ! $post-
>is_approved]);
        }

        return back()->with('success', $post->is_approved ? 'Ujumbe umetumwa.' : 'Ujumbe umepokelewa na utaonekana
baada ya kuhakikiwa.');
    }

    public function join(Request $request, CommunityThread $thread)
    {
        $user = $this->currentUser($request);
        if (! $user) {
            return redirect()->route('chat.index', ['redirect' => route('community.show', $thread, false)]);
        }
        if ($thread->is_private) {
            return back()->with('error', 'Huwezi kujiunga na mjadala wa faragha bila mwaliko.');
        }

        $thread->members()->syncWithoutDetaching([$user->id => ['role' => 'member']]);

        return redirect()->route('community.show', $thread);
    }

    public function leave(Request $request, CommunityThread $thread)
    {
        $user = $this->currentUser($request);
        if (! $user) {
            return redirect()->route('chat.index');
        }
```

```php

        $thread->members()->detach($user->id);

        return redirect()->route('community.index');
    }

    private function currentUser(Request $request): ?User
    {
        $id = $request->session()->get('chat_user_id');

        return $id ? User::query()->find($id) : null;
    }

    private function settings(): array
    {
        return [
            'app_name' => Settings::get('app_name'),
            'sms_keyword' => Settings::get('sms_keyword'),
            'sms_shortcode' => Settings::get('sms_shortcode'),
        ];
    }
}
```

15 app/Http/Controllers/ContactController.php

70 lines

```php
<?php

namespace App\Http\Controllers;

use App\Support\Settings;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Log;
use Illuminate\Support\Facades\Mail;
use Illuminate\Support\Facades\RateLimiter;

class ContactController extends Controller
{
    public function submit(Request $request)
    {
        $data = $request->validate([
            'type' => 'nullable|in:subscribe,partner,general',
            'email' => 'required|email|max:120',
            'name' => 'nullable|string|max:80',
            'organisation' => 'nullable|string|max:120',
            'message' => 'nullable|string|max:2000',
            'website' => 'nullable|max:0', // honeypot
        ]);

        $key = 'contact:' . $request->ip();
        if (RateLimiter::tooManyAttempts($key, 5)) {
            return back()->with('contact_error', 'Umetuma mara nyingi. Jaribu tena baadaye.');
        }
        RateLimiter::hit($key, 3600);

        $type = $data['type'] ?? 'general';
        $to = Settings::get('contact_email') ?: config('mail.from.address');
        $app = Settings::get('app_name');

        $subject = match ($type) {
            'subscribe' => "[{$app}] New subscriber",
            'partner' => "[{$app}] Partnership enquiry",
            default => "[{$app}] New enquiry",
        };

        $body = implode("\n", array_filter([
            "Type: {$type}",
            'Email: ' . $data['email'],
            'Name: ' . ($data['name'] ?? '-'),
            'Organisation: ' . ($data['organisation'] ?? '-'),
            '',
            $data['message'] ?? '',
            '',
            'Received: ' . now()->toDateTimeString() . ' (' . config('app.timezone') . ')',
        ]));

        try {
            if ($to) {
                Mail::raw($body, function ($mail) use ($to, $subject, $data) {
                    $mail->to($to)->replyTo($data['email'], $data['name'] ?? 'Visitor')->subject($subject);
                });
            }
            Log::info('Contact form', ['type' => $type, 'email' => $data['email']]);

            return back()->with('contact_success', match ($type) {
                'partner' => 'Asante! Tutawasiliana nawe ndani ya siku 2 za kazi.',
                'subscribe' => 'Umejiunga! Tutakutumia taarifa za maendeleo.',
                default => 'Ujumbe wako umepokelewa. Asante.',
            });
        } catch (\Throwable $e) {
            Log::error('Contact mail failed: ' . $e->getMessage());

            return back()->with('contact_error', 'Imeshindikana kutuma. Tafadhali tutumie barua pepe moja kwa moja: ' . $to);
        }
    }
}
```

16 **app/Http/Controllers/Controller.php** 8 lines

```php
<?php

namespace App\Http\Controllers;

abstract class Controller
{
    //
}
```

17 app/Http/Controllers/SmsController.php

68 lines

```php
<?php

namespace App\Http\Controllers;

use App\Jobs\ProcessIncomingSms;
use App\Support\Phone;
use App\Support\Settings;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Log;
use Illuminate\Support\Facades\RateLimiter;

class SmsController extends Controller
{
    /**
     * Africa's Talking inbound callback (form-encoded: from, to, text, date, id, linkId).
     */
    public function inbound(Request $request)
    {
        $from = Phone::normalize($request->input('from'));
        $text = trim((string) $request->input('text', ''));

        if (! $from || $text === '') {
            return response()->json(['status' => 'error', 'message' => 'Invalid payload'], 400);
        }

        // A flood from one number must not become a flood of model calls.
        $key = 'sms-inbound:' . $from;
        if (RateLimiter::tooManyAttempts($key, 20)) {
            Log::warning('Inbound SMS rate limited', ['from' => Phone::mask($from)]);

            return response()->json(['status' => 'rate_limited']);
        }
        RateLimiter::hit($key, 60);

        $keyword = (string) Settings::get('sms_keyword');
        $clean = $text;

        // On a shared short code the operator prepends the keyword; strip it when present.
        if ($keyword !== '' && preg_match('/^' . preg_quote($keyword, '/') . '\b\s*/iu', $text)) {
            $clean = trim(preg_replace('/^' . preg_quote($keyword, '/') . '\b\s*/iu', '', $text));
        } elseif ($keyword !== '' && config('services.at.require_keyword')) {
            Log::info('SMS ignored: keyword missing', ['from' => Phone::mask($from)]);

            return response()->json(['status' => 'ignored']);
        }

        // A bare keyword is a request for help.
        if ($clean === '') {
            $clean = 'HELP';
        }

        Log::info('Inbound SMS accepted', ['from' => Phone::mask($from), 'chars' => strlen($clean)]);

        ProcessIncomingSms::dispatch($from, $clean, $request->input('id'));

        return response()->json(['status' => 'success']);
    }

    /**
     * Optional delivery report callback from Africa's Talking.
     */
    public function deliveryReport(Request $request)
    {
        Log::info('SMS delivery report', $request->only('id', 'status', 'phoneNumber', 'failureReason'));

        return response()->json(['status' => 'ok']);
    }
}
```

18 app/Http/Controllers/WebChatController.php

333 lines

```php
<?php

namespace App\Http\Controllers;

use App\Models\Feedback;
use App\Models\Message;
use App\Models\User;
use App\Services\ConversationService;
use App\Services\SmsService;
use App\Services\TanzaniaContext;
use App\Services\TopicClassifier;
use App\Support\Phone;
use App\Support\Settings;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Hash;
use Illuminate\Support\Facades\Log;
use Illuminate\Support\Facades\RateLimiter;
use Illuminate\Validation\ValidationException;

class WebChatController extends Controller
{
    private const SESSION_KEY = 'chat_user_id';

    public function index()
    {
        return view('chat', [
            'settings' => $this->publicSettings(),
        ]);
    }

    /** Bootstrap data for the page: who is logged in and the public settings. */
    public function session(Request $request)
    {
        $user = $this->currentUser($request);

        return response()->json([
            'authenticated' => (bool) $user,
            'user' => $user ? $this->userPayload($user) : null,
            'settings' => $this->publicSettings(),
            'csrf' => csrf_token(),
        ]);
    }

    /**
     * Step 1 of login. Creates the citizen record if needed and sends an OTP.
     * When OTP is disabled (or SMS is not configured in a non-production
     * environment) the session is opened directly.
     */
    public function requestOtp(Request $request, SmsService $sms)
    {
        $data = $request->validate([
            'phone_number' => 'required|string|min:9|max:20',
            'language' => 'nullable|in:sw,en',
        ]);

        $phone = Phone::normalize($data['phone_number']);
        if (! $phone) {
            throw ValidationException::withMessages(['phone_number' => 'Namba ya simu si sahihi. / Invalid phone number.']);
        }

        $key = 'otp-request:' . $phone;
        if (RateLimiter::tooManyAttempts($key, 4)) {
            return response()->json(['status' => 'error', 'message' => 'Umeomba mara nyingi. Subiri dakika 10. / Too many requests. Wait 10 minutes.'], 429);
        }
        RateLimiter::hit($key, 600);

        $user = User::query()->firstOrCreate(['phone_number' => $phone]);
        if ($user->is_banned) {
            return response()->json(['status' => 'error', 'message' => 'Huduma imefungwa kwa namba hii. / This
```

```
number is blocked.'], 403);
        }

        $language = $data['language'] ?? $user->preferred_language ?? 'sw';
        $otpEnabled = Settings::bool('otp_enabled');
        $canSend = $sms->isConfigured();

        if (! $otpEnabled || (! $canSend && ! app()->environment('production'))) {
            $this->openSession($request, $user);

            return response()->json([
                'status' => 'success',
                'otp_required' => false,
                'user' => $this->userPayload($user),
                'csrf' => csrf_token(), // session was regenerated, token rotated
            ]);
        }

        if (! $canSend) {
            return response()->json(['status' => 'error', 'message' => 'Huduma ya uthibitisho haipatikani kwa sasa.
/ Verification is unavailable right now.'], 503);
        }

        $code = (string) random_int(100000, 999999);
        $ttl = Settings::int('otp_ttl_minutes');
        $user->forceFill([
            'otp_hash' => Hash::make($code),
            'otp_expires_at' => now()->addMinutes($ttl),
            'otp_attempts' => 0,
        ])->save();

        $sent = $sms->sendOtp($phone, $code, $language, (string) Settings::get('app_name'), $ttl);
        if ($sent['status'] === 'error') {
            return response()->json(['status' => 'error', 'message' => 'Imeshindikana kutuma ujumbe wa uthibitisho.
/ Could not send the verification SMS.'], 502);
        }

        $payload = ['status' => 'success', 'otp_required' => true, 'phone_masked' => Phone::mask($phone),
'ttl_minutes' => $ttl];
        if (config('app.debug') && ! app()->environment('production')) {
            $payload['debug_code'] = $code; // never present in production
        }

        return response()->json($payload);
    }

    /** Step 2 of login. */
    public function verifyOtp(Request $request)
    {
        $data = $request->validate([
            'phone_number' => 'required|string',
            'code' => 'required|digits:6',
        ]);

        $phone = Phone::normalize($data['phone_number']);
        $user = $phone ? User::query()->where('phone_number', $phone)->first() : null;

        if (! $user || ! $user->otp_hash || ! $user->otp_expires_at || $user->otp_expires_at->isPast()) {
            return response()->json(['status' => 'error', 'message' => 'Namba ya uthibitisho imeisha muda. Omba
nyingine. / Code expired, request a new one.'], 422);
        }

        if ($user->otp_attempts >= 5) {
            $user->forceFill(['otp_hash' => null, 'otp_expires_at' => null])->save();

            return response()->json(['status' => 'error', 'message' => 'Majaribio mengi. Omba namba mpya. / Too
many attempts, request a new code.'], 429);
        }

        if (! Hash::check($data['code'], $user->otp_hash)) {
            $user->increment('otp_attempts');

            return response()->json(['status' => 'error', 'message' => 'Namba ya uthibitisho si sahihi. / Incorrect
```

```
code.'], 422);
        }

        $user->forceFill(['otp_hash' => null, 'otp_expires_at' => null, 'otp_attempts' => 0])->save();
        $this->openSession($request, $user);

        return response()->json(['status' => 'success', 'user' => $this->userPayload($user), 'csrf' =>
csrf_token()]);
    }

    public function messages(Request $request)
    {
        $user = $this->currentUser($request);
        if (! $user) {
            return response()->json(['status' => 'error', 'message' => 'Unauthorized'], 401);
        }

        $query = Message::query()->where('user_id', $user->id)->with('feedback');

        $filtering = false;
        if ($request->filled('keyword')) {
            $query->where('content', 'like', '%' . str_replace(['%', '_'], ['\%', '\_'], $request-
>string('keyword')) . '%');
            $filtering = true;
        }
        if ($request->filled('date')) {
            $query->whereDate('created_at', $request->string('date'));
            $filtering = true;
        }
        if ($request->filled('category')) {
            $query->where('category', $request->string('category'));
            $filtering = true;
        }
        if ($request->filled('before')) {
            $query->where('id', '<', (int) $request->input('before'));
        }

        $limit = $filtering ? 200 : Settings::int('web_chat_limit');
        $messages = $query->latest('id')->take($limit)->get()->reverse()->values();

        return response()->json([
            'status' => 'success',
            'messages' => $messages->map(fn (Message $m) => $this->messagePayload($m)),
            'has_more' => $messages->isNotEmpty() && Message::query()->where('user_id', $user->id)->where('id',
'<', $messages->first()->id)->exists(),
        ]);
    }

    public function send(Request $request, ConversationService $conversation)
    {
        $user = $this->currentUser($request);
        if (! $user) {
            return response()->json(['status' => 'error', 'message' => 'Unauthorized'], 401);
        }

        $data = $request->validate(['message' => 'required|string|max:2000']);

        $result = $conversation->handle($user, $data['message'], Message::CHANNEL_WEB);

        if ($result['kind'] === ConversationService::KIND_IGNORED) {
            return response()->json(['status' => 'error', 'message' => 'Empty message'], 400);
        }

        return response()->json([
            'status' => 'success',
            'kind' => $result['kind'],
            'category' => $result['category'],
            'category_label' => $result['category'] ? TopicClassifier::label($result['category'],
$result['language']) : null,
            'user_message' => $result['inbound'] ? $this->messagePayload($result['inbound']) : null,
            'reply' => $result['outbound']
                ? $this->messagePayload($result['outbound'])
                : ['id' => null, 'direction' => 'outbound', 'content' => $result['text'], 'created_at' => now()-
```

```
>toIso8601String(), 'category' => $result['category'], 'feedback' => null],
        ]);
    }

    public function feedback(Request $request)
    {
        $user = $this->currentUser($request);
        if (! $user) {
            return response()->json(['status' => 'error', 'message' => 'Unauthorized'], 401);
        }

        $data = $request->validate([
            'message_id' => 'required|integer',
            'rating' => 'required|in:1,-1',
            'comment' => 'nullable|string|max:500',
        ]);

        $message = Message::query()->where('user_id', $user->id)->where('direction', Message::DIRECTION_OUT)-
>find($data['message_id']);
        if (! $message) {
            return response()->json(['status' => 'error', 'message' => 'Message not found'], 404);
        }

        Feedback::query()->updateOrCreate(
            ['message_id' => $message->id, 'user_id' => $user->id],
            ['rating' => (int) $data['rating'], 'comment' => $data['comment'] ?? null]
        );

        return response()->json(['status' => 'success']);
    }

    public function preferences(Request $request, TanzaniaContext $tz)
    {
        $user = $this->currentUser($request);
        if (! $user) {
            return response()->json(['status' => 'error', 'message' => 'Unauthorized'], 401);
        }

        $data = $request->validate([
            'name' => 'nullable|string|max:40',
            'preferred_language' => 'nullable|in:sw,en,auto',
            'region' => 'nullable|string|max:40',
        ]);

        $update = [];
        if (array_key_exists('name', $data)) {
            $update['name'] = $data['name'] ? trim($data['name']) : null;
        }
        if (array_key_exists('preferred_language', $data)) {
            $update['preferred_language'] = $data['preferred_language'] === 'auto' ? null :
$data['preferred_language'];
        }
        if (array_key_exists('region', $data)) {
            $loc = $data['region'] ? $tz->detectLocation($data['region']) : null;
            $update['region'] = $loc['region'] ?? null;
        }

        $user->forceFill($update)->save();

        return response()->json(['status' => 'success', 'user' => $this->userPayload($user->fresh())]);
    }

    public function logout(Request $request)
    {
        $request->session()->forget(self::SESSION_KEY);
        $request->session()->regenerate();

        return response()->json(['status' => 'success', 'csrf' => csrf_token()]);
    }

    // ---------------------------------------------------------------- helpers

    private function openSession(Request $request, User $user): void
```

```
    {
        $request->session()->regenerate();
        $request->session()->put(self::SESSION_KEY, $user->id);
        $user->forceFill(['last_seen_at' => now()])->saveQuietly();
    }

    private function currentUser(Request $request): ?User
    {
        $id = $request->session()->get(self::SESSION_KEY);
        if (! $id) {
            return null;
        }
        $user = User::query()->find($id);
        if (! $user) {
            $request->session()->forget(self::SESSION_KEY);
        }

        return $user;
    }

    private function userPayload(User $user): array
    {
        return [
            'id' => $user->id,
            'name' => $user->name,
            'display_name' => $user->displayName(),
            'phone_masked' => Phone::mask($user->phone_number),
            'preferred_language' => $user->preferred_language ?? 'auto',
            'region' => $user->region ? ucwords($user->region) : null,
            'is_banned' => $user->is_banned,
        ];
    }

    private function messagePayload(Message $m): array
    {
        return [
            'id' => $m->id,
            'direction' => $m->direction,
            'content' => $m->content,
            'category' => $m->category,
            'category_label' => $m->category ? TopicClassifier::label($m->category, $m->language ?? 'sw') : null,
            'language' => $m->language,
            'created_at' => $m->created_at?->toIso8601String(),
            'feedback' => $m->relationLoaded('feedback') && $m->feedback ? $m->feedback->rating : null,
        ];
    }

    private function publicSettings(): array
    {
        return [
            'app_name' => Settings::get('app_name'),
            'sms_keyword' => Settings::get('sms_keyword'),
            'sms_shortcode' => Settings::get('sms_shortcode'),
            'otp_enabled' => Settings::bool('otp_enabled'),
            'categories' => collect(TopicClassifier::CATEGORIES)->map(fn ($l, $k) => ['key' => $k, 'sw' =>
$l['sw'], 'en' => $l['en']])->values(),
            'regions' => array_map('ucwords', TanzaniaContext::REGIONS),
        ];
    }
}
```

19 `app/Http/Middleware/EnsureAdmin.php` 25 lines

```php
<?php

namespace App\Http\Middleware;

use Closure;
use Illuminate\Http\Request;
use Symfony\Component\HttpFoundation\Response;

class EnsureAdmin
{
    public function handle(Request $request, Closure $next): Response
    {
        $user = $request->user();

        if (! $user) {
            return redirect()->route('admin.login')->with('error', 'Please sign in.');
        }

        if (! $user->isAdmin()) {
            abort(403, 'Admin access only.');
        }

        return $next($request);
    }
}
```

20 app/Http/Middleware/VerifySmsWebhook.php

43 lines

```php
<?php

namespace App\Http\Middleware;

use Closure;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Log;
use Symfony\Component\HttpFoundation\Response;

/**
 * Protects the inbound SMS callback. Africa's Talking does not sign
 * callbacks, so the callback URL registered in their dashboard must carry
 * a shared secret: https://your-host/api/sms/inbound?token=<AT_WEBHOOK_SECRET>
 * (a X-Webhook-Token header works too).
 */
class VerifySmsWebhook
{
    public function handle(Request $request, Closure $next): Response
    {
        $expected = (string) config('services.at.webhook_secret');

        if ($expected === '') {
            if (app()->environment('production')) {
                Log::critical('AT_WEBHOOK_SECRET is not set; refusing inbound SMS in production.');

                return response()->json(['status' => 'error', 'message' => 'webhook secret not configured'], 503);
            }
            Log::warning('AT_WEBHOOK_SECRET is not set; accepting inbound SMS because APP_ENV is not production.');

            return $next($request);
        }

        $given = (string) ($request->query('token') ?? $request->header('X-Webhook-Token') ?? '');

        if ($given === '' || ! hash_equals($expected, $given)) {
            Log::warning('Rejected inbound SMS callback with bad token', ['ip' => $request->ip()]);

            return response()->json(['status' => 'error', 'message' => 'unauthorized'], 401);
        }

        return $next($request);
    }
}
```

21 app/Jobs/ProcessIncomingSms.php

57 lines

```php
<?php

namespace App\Jobs;

use App\Models\Message;
use App\Models\User;
use App\Services\ConversationService;
use App\Services\SmsService;
use App\Support\Phone;
use Illuminate\Contracts\Queue\ShouldBeUnique;
use Illuminate\Contracts\Queue\ShouldQueue;
use Illuminate\Foundation\Queue\Queueable;
use Illuminate\Support\Facades\Log;

class ProcessIncomingSms implements ShouldQueue, ShouldBeUnique
{
    use Queueable;

    public int $tries = 2;

    public int $timeout = 90;

    public function __construct(
        public readonly string $from,
        public readonly string $text,
        public readonly ?string $providerMessageId = null,
    ) {
    }

    public function handle(ConversationService $conversation, SmsService $sms): void
    {
        $user = User::query()->firstOrCreate(['phone_number' => $this->from]);

        $result = $conversation->handle($user, $this->text, Message::CHANNEL_SMS);

        if (empty($result['text'])) {
            Log::info('No SMS reply', ['from' => Phone::mask($this->from), 'kind' => $result['kind']]);

            return;
        }

        $send = $sms->send($this->from, $result['text']);

        Log::info('SMS reply', [
            'from' => Phone::mask($this->from),
            'kind' => $result['kind'],
            'category' => $result['category'],
            'delivery' => $send['status'],
        ]);
    }

    /** Use the job's own key so retries do not duplicate replies. */
    public function uniqueId(): string
    {
        return $this->providerMessageId ?: md5($this->from . '|' . $this->text);
    }
}
```

22 app/Models/AiLog.php

26 lines

```php
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Model;

class AiLog extends Model
{
    protected $fillable = [
        'message_id',
        'model',
        'category',
        'status',
        'prompt',
        'response',
        'prompt_tokens',
        'completion_tokens',
        'total_tokens',
        'latency_ms',
    ];

    public function message()
    {
        return $this->belongsTo(Message::class);
    }
}
```

23 app/Models/CommunityInvite.php

49 lines

```php
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Support\Str;

class CommunityInvite extends Model
{
    use HasFactory;

    protected $fillable = [
        'community_thread_id',
        'inviter_id',
        'invitee_id',
        'email',
        'token',
        'status',
        'expires_at',
    ];

    protected $casts = [
        'expires_at' => 'datetime',
    ];

    protected static function boot()
    {
        parent::boot();
        static::creating(function ($invite) {
            $invite->token = Str::random(32);
        });
    }

    public function thread()
    {
        return $this->belongsTo(CommunityThread::class, 'community_thread_id');
    }

    public function inviter()
    {
        return $this->belongsTo(User::class, 'inviter_id');
    }

    public function invitee()
    {
        return $this->belongsTo(User::class, 'invitee_id');
    }
}
```

24 app/Models/CommunityMember.php

32 lines

```php
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class CommunityMember extends Model
{
    use HasFactory;

    protected $fillable = [
        'community_thread_id',
        'user_id',
        'role',
        'joined_at',
    ];

    protected $casts = [
        'joined_at' => 'datetime',
    ];

    public function thread()
    {
        return $this->belongsTo(CommunityThread::class, 'community_thread_id');
    }

    public function user()
    {
        return $this->belongsTo(User::class);
    }
}
```

25 app/Models/CommunityPost.php

34 lines

```php
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class CommunityPost extends Model
{
    use HasFactory;

    protected $fillable = [
        'community_thread_id',
        'user_id',
        'content',
        'is_approved',
        'is_pinned',
    ];

    protected $casts = [
        'is_approved' => 'boolean',
        'is_pinned' => 'boolean',
    ];

    public function thread()
    {
        return $this->belongsTo(CommunityThread::class, 'community_thread_id');
    }

    public function user()
    {
        return $this->belongsTo(User::class);
    }
}
```

26 app/Models/CommunityReaction.php

27 lines

```php
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class CommunityReaction extends Model
{
    use HasFactory;

    protected $fillable = [
        'community_post_id',
        'user_id',
        'type',
    ];

    public function post()
    {
        return $this->belongsTo(CommunityPost::class, 'community_post_id');
    }

    public function user()
    {
        return $this->belongsTo(User::class);
    }
}
```

27 app/Models/CommunityThread.php

47 lines

```php
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class CommunityThread extends Model
{
    use HasFactory;

    protected $fillable = [
        'title',
        'slug',
        'description',
        'creator_id',
        'is_private',
        'is_system',
    ];

    protected $casts = [
        'is_private' => 'boolean',
        'is_system' => 'boolean',
    ];

    public function creator()
    {
        return $this->belongsTo(User::class, 'creator_id');
    }

    public function members()
    {
        return $this->belongsToMany(User::class, 'community_members')
            ->withPivot('role', 'joined_at')
            ->withTimestamps();
    }

    public function posts()
    {
        return $this->hasMany(CommunityPost::class);
    }

    public function invites()
    {
        return $this->hasMany(CommunityInvite::class);
    }
}
```

28 app/Models/Feedback.php

31 lines

```php
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Model;

class Feedback extends Model
{
    protected $table = 'feedback';

    protected $fillable = [
        'message_id',
        'user_id',
        'rating',
        'comment',
    ];

    protected $casts = [
        'rating' => 'integer',
    ];

    public function message()
    {
        return $this->belongsTo(Message::class);
    }

    public function user()
    {
        return $this->belongsTo(User::class);
    }
}
```

29 app/Models/KnowledgeEntry.php

37 lines

```php
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Model;
use Illuminate\Support\Facades\Cache;

/**
 * A curated fact block about life in Tanzania (law, health, farming,
 * government services, money, education, ...). Retrieved by keyword overlap
 * and injected into the prompt so answers are grounded in local reality.
 */
class KnowledgeEntry extends Model
{
    protected $fillable = [
        'title',
        'content',
        'summary',
        'category',
        'keywords',
        'language',
        'source',
        'is_active',
    ];

    protected $casts = [
        'keywords' => 'array',
        'is_active' => 'boolean',
    ];

    protected static function booted(): void
    {
        $bust = fn () => Cache::forget('huru.knowledge.active');
        static::saved($bust);
        static::deleted($bust);
    }
}
```

30 app/Models/LocalResource.php

41 lines

```php
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Model;

/**
 * A place-bound service: a legal aid provider, hospital, police station,
 * agricultural office, district council desk, ... tied to a region and
 * district so the engine can point citizens to help near them.
 */
class LocalResource extends Model
{
    public const CATEGORIES = [
        'legal_aid' => 'Legal aid provider',
        'health' => 'Health facility',
        'police' => 'Police / gender desk',
        'agriculture' => 'Agriculture office',
        'government' => 'Government office',
        'education' => 'Education office',
        'finance' => 'Financial service',
        'other' => 'Other',
    ];

    protected $fillable = [
        'name',
        'category',
        'region',
        'district',
        'ward',
        'location',
        'phone',
        'email',
        'source',
        'is_active',
    ];

    protected $casts = [
        'is_active' => 'boolean',
    ];
}
```

31 app/Models/Message.php

38 lines

```php
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Model;

class Message extends Model
{
    public const DIRECTION_IN = 'inbound';
    public const DIRECTION_OUT = 'outbound';

    public const CHANNEL_SMS = 'sms';
    public const CHANNEL_WEB = 'web';

    protected $fillable = [
        'user_id',
        'direction',
        'channel',
        'content',
        'language',
        'category',
    ];

    public function user()
    {
        return $this->belongsTo(User::class);
    }

    public function aiLog()
    {
        return $this->hasOne(AiLog::class);
    }

    public function feedback()
    {
        return $this->hasOne(Feedback::class);
    }
}
```

32 app/Models/PromptTemplate.php

33 lines

```php
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Model;
use Illuminate\Support\Facades\Cache;

/**
 * Persona paragraph for a (category, language) pair. The engine appends
 * context and constraints itself, so a template only describes who the
 * assistant is and how it should behave for that topic.
 */
class PromptTemplate extends Model
{
    protected $fillable = [
        'name',
        'category',
        'language',
        'template',
        'is_active',
    ];

    protected $casts = [
        'is_active' => 'boolean',
    ];

    protected static function booted(): void
    {
        $bust = fn () => Cache::forget('huru.templates.active');
        static::saved($bust);
        static::deleted($bust);
    }
}
```

33 app/Models/ReferenceContact.php

51 lines

```php
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Model;
use Illuminate\Support\Facades\Cache;

/**
 * National directory entry: an institution, hotline or office that applies
 * country-wide (police 112, TRA, NIDA, NHIF, Legal aid campaign, ...).
 * Editable by admins so the engine never relies on hard-coded facts that
 * go stale.
 */
class ReferenceContact extends Model
{
    protected $fillable = [
        'name',
        'category',
        'phone',
        'alt_phone',
        'email',
        'website',
        'description_sw',
        'description_en',
        'is_emergency',
        'is_active',
        'verified_at',
        'sort_order',
    ];

    protected $casts = [
        'is_emergency' => 'boolean',
        'is_active' => 'boolean',
        'verified_at' => 'datetime',
        'sort_order' => 'integer',
    ];

    protected static function booted(): void
    {
        $bust = fn () => Cache::forget('huru.contacts.active');
        static::saved($bust);
        static::deleted($bust);
    }

    public function description(string $language): string
    {
        return $language === 'en'
            ? ($this->description_en ?: (string) $this->description_sw)
            : ($this->description_sw ?: (string) $this->description_en);
    }
}
```

34 app/Models/SystemSetting.php

12 lines

```php
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Model;

class SystemSetting extends Model
{
    protected $table = 'system_settings';

    protected $fillable = ['key', 'value'];
}
```

35 app/Models/User.php

100 lines

```php
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Foundation\Auth\User as Authenticatable;
use Illuminate\Notifications\Notifiable;

class User extends Authenticatable
{
    use HasFactory, Notifiable;

    public const ROLE_USER = 'user';
    public const ROLE_ADMIN = 'admin';

    protected $fillable = [
        'name',
        'email',
        'password',
        'phone_number',
        'role',
        'preferred_language',
        'region',
        'is_banned',
        'abuse_count',
        'opted_out',
        'otp_hash',
        'otp_expires_at',
        'otp_attempts',
        'last_seen_at',
    ];

    protected $hidden = [
        'password',
        'remember_token',
        'otp_hash',
    ];

    protected function casts(): array
    {
        return [
            'email_verified_at' => 'datetime',
            'password' => 'hashed',
            'is_banned' => 'boolean',
            'opted_out' => 'boolean',
            'abuse_count' => 'integer',
            'otp_attempts' => 'integer',
            'otp_expires_at' => 'datetime',
            'last_seen_at' => 'datetime',
        ];
    }

    public function isAdmin(): bool
    {
        return $this->role === self::ROLE_ADMIN;
    }

    public function messages()
    {
        return $this->hasMany(Message::class);
    }

    public function feedback()
    {
        return $this->hasMany(Feedback::class);
    }

    public function communityMemberships()
    {
        return $this->hasMany(CommunityMember::class);
    }
```

```php

    public function joinedThreads()
    {
        return $this->belongsToMany(CommunityThread::class, 'community_members')
            ->withPivot('role', 'joined_at')
            ->withTimestamps();
    }

    public function createdThreads()
    {
        return $this->hasMany(CommunityThread::class, 'creator_id');
    }

    public function communityPosts()
    {
        return $this->hasMany(CommunityPost::class);
    }

    /** Display name that never leaks the full phone number to other citizens. */
    public function displayName(): string
    {
        if ($this->name) {
            return $this->name;
        }
        $digits = preg_replace('/\D/', '', (string) $this->phone_number);

        return 'Mwananchi ' . substr($digits, -4);
    }
}
```

36 app/Providers/AppServiceProvider.php

37 lines

```php
<?php

namespace App\Providers;

use App\Services\Ai\GeminiClient;
use App\Services\Ai\LlmClient;
use Composer\CaBundle\CaBundle;
use Illuminate\Support\Facades\Http;
use Illuminate\Support\Facades\Vite;
use Illuminate\Support\ServiceProvider;

class AppServiceProvider extends ServiceProvider
{
    public function register(): void
    {
        $this->app->singleton(LlmClient::class, function () {
            return new GeminiClient(
                apiKey: config('services.gemini.key'),
                baseUrl: config('services.gemini.url'),
                timeoutSeconds: (int) config('services.gemini.timeout', 30),
            );
        });
    }

    public function boot(): void
    {
        Vite::useBuildDirectory('build');

        // Keep TLS verification ON everywhere, even on machines (typically
        // Windows dev boxes) whose PHP has no CA bundle configured.
        // composer/ca-bundle prefers the system bundle and falls back to
        // its own up-to-date cacert.pem.
        Http::globalOptions([
            'verify' => CaBundle::getSystemCaRootBundlePath(),
        ]);
    }
}
```

37 app/Services/Ai/GeminiClient.php

131 lines

```php
<?php

namespace App\Services\Ai;

use Illuminate\Support\Facades\Http;
use Illuminate\Support\Facades\Log;

/**
 * Google Gemini generateContent client.
 *
 * - Sends the API key in a header, never in the URL (keeps it out of logs).
 * - Keeps TLS verification on.
 * - Uses a real system instruction and multi-turn contents.
 * - Normalises the response into a provider-agnostic shape.
 */
class GeminiClient implements LlmClient
{
    public function __construct(
        private readonly ?string $apiKey,
        private readonly string $baseUrl = 'https://generativelanguage.googleapis.com/v1beta/models',
        private readonly int $timeoutSeconds = 30,
    ) {
    }

    public function isConfigured(): bool
    {
        return ! empty($this->apiKey);
    }

    public function generate(string $systemInstruction, array $turns, array $options = []): array
    {
        $model = $options['model'] ?? 'gemini-flash-lite-latest';
        $base = [
            'status' => self::STATUS_ERROR,
            'text' => null,
            'model' => $model,
            'tokens' => ['prompt' => 0, 'completion' => 0, 'total' => 0],
            'latency_ms' => 0,
            'finish_reason' => null,
            'error' => null,
        ];

        if (! $this->isConfigured()) {
            Log::critical('Gemini API key missing.');

            return array_merge($base, ['status' => self::STATUS_UNCONFIGURED, 'error' => 'missing_api_key']);
        }

        $contents = [];
        foreach ($turns as $turn) {
            $contents[] = [
                'role' => $turn['role'] === 'model' ? 'model' : 'user',
                'parts' => [['text' => (string) $turn['text']]],
            ];
        }

        $payload = [
            'systemInstruction' => ['parts' => [['text' => $systemInstruction]]],
            'contents' => $contents,
            'generationConfig' => [
                'temperature' => (float) ($options['temperature'] ?? 0.4),
                'maxOutputTokens' => (int) ($options['max_tokens'] ?? 2048),
            ],
            'safetySettings' => [
                ['category' => 'HARM_CATEGORY_HARASSMENT', 'threshold' => 'BLOCK_ONLY_HIGH'],
                ['category' => 'HARM_CATEGORY_HATE_SPEECH', 'threshold' => 'BLOCK_ONLY_HIGH'],
                ['category' => 'HARM_CATEGORY_SEXUALLY_EXPLICIT', 'threshold' => 'BLOCK_MEDIUM_AND_ABOVE'],
                ['category' => 'HARM_CATEGORY_DANGEROUS_CONTENT', 'threshold' => 'BLOCK_ONLY_HIGH'],
            ],
        ];

```

```
        $started = microtime(true);

        try {
            $response = Http::timeout($this->timeoutSeconds)
                ->withHeaders([
                    'Content-Type' => 'application/json',
                    'x-goog-api-key' => $this->apiKey,
                ])
                ->retry(2, 800, throw: false)
                ->post(rtrim($this->baseUrl, '/') . '/' . rawurlencode($model) . ':generateContent', $payload);

            $latency = (int) round((microtime(true) - $started) * 1000);
            $base['latency_ms'] = $latency;

            if (! $response->successful()) {
                $body = $response->json();
                $message = $body['error']['message'] ?? ('HTTP ' . $response->status());
                Log::error('Gemini request failed', ['status' => $response->status(), 'message' => $message]);

                return array_merge($base, ['error' => $message]);
            }

            $data = $response->json();
            $usage = $data['usageMetadata'] ?? [];
            $base['tokens'] = [
                'prompt' => (int) ($usage['promptTokenCount'] ?? 0),
                'completion' => (int) ($usage['candidatesTokenCount'] ?? 0),
                'total' => (int) ($usage['totalTokenCount'] ?? 0),
            ];

            $candidate = $data['candidates'][0] ?? null;
            $finish = $candidate['finishReason'] ?? null;
            $base['finish_reason'] = $finish;

            $blockReason = $data['promptFeedback']['blockReason'] ?? null;
            if ($blockReason || $finish === 'SAFETY' || $finish === 'PROHIBITED_CONTENT') {
                return array_merge($base, ['status' => self::STATUS_SAFETY]);
            }

            $text = '';
            foreach ($candidate['content']['parts'] ?? [] as $part) {
                $text .= $part['text'] ?? '';
            }
            $text = trim($text);

            if ($text === '') {
                return array_merge($base, ['error' => 'empty_response']);
            }

            return array_merge($base, ['status' => self::STATUS_OK, 'text' => $text]);
        } catch (\Throwable $e) {
            Log::error('Gemini client exception: ' . $e->getMessage());

            return array_merge($base, [
                'latency_ms' => (int) round((microtime(true) - $started) * 1000),
                'error' => $e->getMessage(),
            ]);
        }
    }
}
```

38 app/Services/Ai/LlmClient.php

20 lines

```php
<?php

namespace App\Services\Ai;

interface LlmClient
{
    public const STATUS_OK = 'ok';
    public const STATUS_SAFETY = 'safety';
    public const STATUS_ERROR = 'error';
    public const STATUS_UNCONFIGURED = 'unconfigured';

    /**
     * @param  array<int, array{role:string, text:string}>  $turns  Ordered conversation, last item is the new user message.
     * @param  array{temperature?:float, max_tokens?:int, model?:string}  $options
     * @return array{status:string, text:?string, model:string, tokens:array{prompt:int,completion:int,total:int}, latency_ms:int, finish_reason:?string, error:?string}
     */
    public function generate(string $systemInstruction, array $turns, array $options = []): array;

    public function isConfigured(): bool;
}
```

39 app/Services/AiService.php

59 lines

```php
<?php

namespace App\Services;

use App\Services\Ai\LlmClient;
use App\Support\Settings;

/**
 * Thin orchestration between the prompt engine and the model client.
 */
class AiService
{
    public function __construct(
        private readonly PromptEngine $engine,
        private readonly LlmClient $client,
    ) {
    }

    /**
     * @param  array  $ctx  See PromptEngine::build()
     * @return array{status:string,text:?string,model:string,tokens:array,latency_ms:int,error:?string,system:string,knowledge:\Illuminate\Support\Collection}
     */
    public function answer(array $ctx): array
    {
        $built = $this->engine->build($ctx);

        $result = $this->client->generate($built['system'], $built['turns'], [
            'model' => Settings::get('ai_model'),
            'temperature' => Settings::float('ai_temperature'),
            'max_tokens' => Settings::int('ai_max_tokens'),
        ]);

        if ($result['status'] === LlmClient::STATUS_OK) {
            $result['text'] = $this->clean($result['text']);
        }

        $result['system'] = $built['system'];
        $result['knowledge'] = $built['knowledge'];

        return $result;
    }

    /** Strip markdown the model may still emit, since SMS cannot render it. */
    private function clean(string $text): string
    {
        $text = preg_replace('/\*\*?/', '', $text);
        $text = preg_replace('/^#{1,6}\s*/m', '', $text);
        $text = preg_replace('/`+/', '', $text);
        $text = preg_replace('/^\s*[-•]\s+/m', '- ', $text);
        $text = preg_replace('/\n{3,}/', "\n\n", $text);

        return trim($text);
    }

    public function isConfigured(): bool
    {
        return $this->client->isConfigured();
    }
}
```

40 app/Services/ConversationService.php

341 lines

```php
<?php

namespace App\Services;

use App\Models\AiLog;
use App\Models\Message;
use App\Models\User;
use App\Services\Ai\LlmClient;
use App\Support\Settings;
use Illuminate\Support\Facades\Log;
use Illuminate\Support\Facades\RateLimiter;
use Illuminate\Support\Str;

/**
 * One entry point for every channel. Takes a citizen and their text,
 * returns what to send back. The SMS job and the web controller both call
 * this, so behaviour (commands, moderation, memory, logging) never drifts
 * between channels.
 */
class ConversationService
{
    public const KIND_ANSWER = 'answer';
    public const KIND_COMMAND = 'command';
    public const KIND_MODERATION = 'moderation';
    public const KIND_MAINTENANCE = 'maintenance';
    public const KIND_BANNED = 'banned';
    public const KIND_IGNORED = 'ignored';
    public const KIND_RATE_LIMITED = 'rate_limited';
    public const KIND_ERROR = 'error';

    public function __construct(
        private readonly AiService $ai,
        private readonly ModerationService $moderation,
        private readonly LanguageDetector $detector,
        private readonly TopicClassifier $classifier,
        private readonly TanzaniaContext $tz,
    ) {
    }

    /**
     * @return array{kind:string, text:?string, inbound:?Message, outbound:?Message, category:?string,
language:string}
     */
    public function handle(User $user, string $text, string $channel): array
    {
        $text = trim($text);
        $user->forceFill(['last_seen_at' => now()])->saveQuietly();

        $language = $this->resolveLanguage($user, $text);
        $result = ['kind' => self::KIND_IGNORED, 'text' => null, 'inbound' => null, 'outbound' => null, 'category'
=> null, 'language' => $language];

        if ($text === '') {
            return $result;
        }

        // 1. Commands (HELP, STOP, LUGHA, JINA, MKOA ...) never hit the model.
        if ($command = $this->handleCommand($user, $text, $language, $channel)) {
            $inbound = $this->store($user, Message::DIRECTION_IN, $channel, $text, $language, null);
            $outbound = $this->store($user, Message::DIRECTION_OUT, $channel, $command, $language, null);

            return array_merge($result, ['kind' => self::KIND_COMMAND, 'text' => $command, 'inbound' => $inbound,
'outbound' => $outbound]);
        }

        // 2. Opted-out SMS users are left alone until they send START/ANZA.
        if ($user->opted_out && $channel === Message::CHANNEL_SMS) {
            return $result;
        }

        // 3. Banned users get one short notice, nothing else.
```

```
        if ($user->is_banned) {
            $msg = $this->moderation->getBanMessage($language);

            return array_merge($result, ['kind' => self::KIND_BANNED, 'text' => $msg]);
        }

        // 4. Per-user rate limit.
        $limitKey = 'huru:ask:' . $user->id;
        if (RateLimiter::tooManyAttempts($limitKey, Settings::int('rate_limit_per_minute'))) {
            $msg = $language === 'en'
                ? 'You are sending questions too quickly. Please wait a minute and try again.'
                : 'Umetuma maswali mengi kwa haraka. Tafadhali subiri dakika moja kisha ujaribu tena.';

            return array_merge($result, ['kind' => self::KIND_RATE_LIMITED, 'text' => $msg]);
        }
        RateLimiter::hit($limitKey, 60);

        $classification = $this->classifier->classify($text);
        $category = $classification['category'];
        $result['category'] = $category;

        $inbound = $this->store($user, Message::DIRECTION_IN, $channel, $text, $language, $category);
        $result['inbound'] = $inbound;

        // 5. Word-list moderation with strikes.
        if ($this->moderation->isAbusive($text)) {
            $msg = $this->strike($user, $language);
            $outbound = $this->store($user, Message::DIRECTION_OUT, $channel, $msg, $language, $category);

            return array_merge($result, ['kind' => self::KIND_MODERATION, 'text' => $msg, 'outbound' =>
$outbound]);
        }

        // 6. Maintenance switch.
        if (! Settings::bool('ai_enabled')) {
            $msg = (string) Settings::get($language === 'en' ? 'ai_maintenance_message_en' :
'ai_maintenance_message_sw');
            $outbound = $this->store($user, Message::DIRECTION_OUT, $channel, $msg, $language, $category);

            return array_merge($result, ['kind' => self::KIND_MAINTENANCE, 'text' => $msg, 'outbound' =>
$outbound]);
        }

        // 7. Ask the engine with full context.
        $location = $this->tz->detectLocation($text);
        if ($location && ! $user->region) {
            $user->forceFill(['region' => $location['region']])->saveQuietly();
        }

        $answer = $this->ai->answer([
            'question' => $text,
            'language' => $language,
            'category' => $category,
            'channel' => $channel,
            'is_emergency' => $classification['is_emergency'],
            'location' => $location,
            'history' => $this->history($user, $inbound->id),
            'user_name' => $user->name,
            'user_region' => $user->region,
        ]);

        if ($answer['status'] === LlmClient::STATUS_SAFETY) {
            $msg = $this->strike($user, $language);
            $outbound = $this->store($user, Message::DIRECTION_OUT, $channel, $msg, $language, $category);
            $this->log($outbound, $answer, $category, $text);

            return array_merge($result, ['kind' => self::KIND_MODERATION, 'text' => $msg, 'outbound' =>
$outbound]);
        }

        if ($answer['status'] !== LlmClient::STATUS_OK) {
            $msg = $language === 'en'
                ? 'Sorry, the service could not answer right now. Please try again shortly.'
```

```
                : 'Samahani, huduma haikuweza kujibu kwa sasa. Tafadhali jaribu tena baada ya muda mfupi.';
            $outbound = $this->store($user, Message::DIRECTION_OUT, $channel, $msg, $language, $category);
            $this->log($outbound, $answer, $category, $text);
            Log::warning('Engine failure', ['user' => $user->id, 'status' => $answer['status'], 'error' =>
$answer['error']]);

            return array_merge($result, ['kind' => self::KIND_ERROR, 'text' => $msg, 'outbound' => $outbound]);
        }

        $outbound = $this->store($user, Message::DIRECTION_OUT, $channel, $answer['text'], $language, $category);
        $this->log($outbound, $answer, $category, $text);

        return array_merge($result, ['kind' => self::KIND_ANSWER, 'text' => $answer['text'], 'outbound' =>
$outbound]);
    }

    // ---------------------------------------------------------------- helpers

    public function resolveLanguage(User $user, string $text): string
    {
        if (in_array($user->preferred_language, ['sw', 'en'], true)) {
            // A stored preference wins unless the citizen clearly wrote the other language.
            $detected = $this->detector->detect($text);

            return $detected ?: $user->preferred_language;
        }

        $policy = (string) Settings::get('primary_language');
        if ($policy === 'sw' || $policy === 'en') {
            return $policy;
        }

        return $this->detector->detect($text) ?: 'sw';
    }

    /** Returns the reply for a service command, or null if the text is not a command. */
    private function handleCommand(User $user, string $text, string $language, string $channel): ?string
    {
        $upper = Str::upper(trim($text));
        $parts = preg_split('/\s+/', $upper, 2);
        $verb = $parts[0] ?? '';
        $arg = trim($parts[1] ?? '');
        $app = Settings::get('app_name');

        if (in_array($verb, ['HELP', 'MSAADA', 'MENU', '?'], true) && $arg === '') {
            return $this->helpText($language);
        }

        if (in_array($verb, ['STOP', 'ACHA', 'SITAKI', 'ONDOA'], true) && $arg === '') {
            $user->forceFill(['opted_out' => true])->saveQuietly();

            return $language === 'en'
                ? "You will no longer receive replies from {$app}. Send ANZA or START any time to resume."
                : "Hutapokea tena majibu kutoka {$app}. Tuma ANZA au START wakati wowote kuendelea.";
        }

        if (in_array($verb, ['START', 'ANZA', 'RUDI'], true) && $arg === '') {
            $user->forceFill(['opted_out' => false])->saveQuietly();

            return $language === 'en'
                ? "Welcome back to {$app}. Send any question to begin."
                : "Karibu tena {$app}. Tuma swali lolote kuanza.";
        }

        if (in_array($verb, ['LUGHA', 'LANG', 'LANGUAGE'], true)) {
            $choice = match (true) {
                in_array($arg, ['SW', 'KISWAHILI', 'SWAHILI'], true) => 'sw',
                in_array($arg, ['EN', 'ENGLISH', 'KIINGEREZA'], true) => 'en',
                $arg === '' || in_array($arg, ['AUTO', 'YOYOTE'], true) => null,
                default => false,
            };
            if ($choice === false) {
                return $language === 'en'
```

```
                    ? 'Send LUGHA SW for Swahili, LUGHA EN for English, or LUGHA AUTO to detect automatically.'
                    : 'Tuma LUGHA SW kwa Kiswahili, LUGHA EN kwa Kiingereza, au LUGHA AUTO kutambua yenyewe.';
            }
            $user->forceFill(['preferred_language' => $choice])->saveQuietly();

            return match ($choice) {
                'sw' => 'Sawa. Kuanzia sasa nitakujibu kwa Kiswahili.',
                'en' => 'Done. From now on I will reply in English.',
                default => $language === 'en' ? 'Done. I will follow the language you write in.' : 'Sawa. Nitafuata lugha unayoandika.',
            };
        }

        if (in_array($verb, ['JINA', 'NAME'], true) && $arg !== '' && strlen($arg) <= 40) {
            $name = Str::title(Str::lower($arg));
            $user->forceFill(['name' => $name])->saveQuietly();

            return $language === 'en' ? "Thank you, {$name}. I have saved your name." : "Asante, {$name}. Nimehifadhi jina lako.";
        }

        if (in_array($verb, ['MKOA', 'REGION'], true) && $arg !== '') {
            $loc = $this->tz->detectLocation($arg);
            if (! $loc) {
                return $language === 'en'
                    ? 'I could not recognise that region. Example: MKOA Mwanza'
                    : 'Sikutambua mkoa huo. Mfano: MKOA Mwanza';
            }
            $user->forceFill(['region' => $loc['region']])->saveQuietly();
            $label = Str::title($loc['region']);

            return $language === 'en'
                ? "Saved. I will prioritise services in {$label} when you ask for help nearby."
                : "Nimehifadhi. Nitatoa kipaumbele kwa huduma za {$label} utakapoomba msaada wa karibu.";
        }

        return null;
    }

    public function helpText(string $language): string
    {
        $app = Settings::get('app_name');
        $kw = Settings::get('sms_keyword');
        $code = Settings::get('sms_shortcode');

        if ($language === 'en') {
            return "{$app}: ask anything about life in Tanzania - law, health, farming, school subjects, government services, money, jobs. "
                . "SMS: send {$kw} followed by your question to {$code}. "
                . 'Commands: LUGHA SW/EN (language), JINA <name>, MKOA <region>, STOP to pause, START to resume.';
        }

        return "{$app}: uliza lolote kuhusu maisha Tanzania - sheria, afya, kilimo, masomo, huduma za serikali, fedha, ajira. "
            . "SMS: tuma {$kw} kisha swali lako kwenda {$code}. "
            . 'Amri: LUGHA SW/EN (lugha), JINA <jina lako>, MKOA <mkoa wako>, ACHA kusitisha, ANZA kuendelea.';
    }

    private function strike(User $user, string $language): string
    {
        $limit = Settings::int('abuse_strike_limit');
        $user->increment('abuse_count');
        $user->refresh();

        if ($user->abuse_count >= $limit) {
            $user->forceFill(['is_banned' => true])->saveQuietly();
            Log::warning('User banned for abuse', ['user' => $user->id]);

            return $this->moderation->getBanMessage($language);
        }

        return $this->moderation->getWarningMessage($language, $user->abuse_count, $limit);
    }
```

```php

    /** Previous question/answer pairs for continuity, oldest first. */
    private function history(User $user, int $excludeMessageId): array
    {
        $turns = Settings::int('history_turns');
        if ($turns <= 0) {
            return [];
        }

        $recent = Message::query()
            ->where('user_id', $user->id)
            ->where('id', '<', $excludeMessageId)
            ->where('created_at', '>=', now()->subDays(2))
            ->whereNotNull('category')
            ->latest('id')
            ->take($turns * 2)
            ->get()
            ->reverse()
            ->values();

        $history = [];
        foreach ($recent as $m) {
            $history[] = [
                'role' => $m->direction === Message::DIRECTION_IN ? 'user' : 'model',
                'text' => Str::limit($m->content, 600, ''),
            ];
        }

        // Ensure we start with a user turn so the model sees valid alternation.
        while (! empty($history) && $history[0]['role'] !== 'user') {
            array_shift($history);
        }

        return $history;
    }

    private function store(User $user, string $direction, string $channel, string $content, string $language, ?
string $category): Message
    {
        return Message::create([
            'user_id' => $user->id,
            'direction' => $direction,
            'channel' => $channel,
            'content' => $content,
            'language' => $language,
            'category' => $category,
        ]);
    }

    private function log(Message $outbound, array $answer, ?string $category, string $question): void
    {
        AiLog::create([
            'message_id' => $outbound->id,
            'model' => $answer['model'] ?? 'unknown',
            'category' => $category,
            'status' => $answer['status'] ?? 'error',
            'prompt' => $question . "\n\n--- SYSTEM ---\n" . Str::limit($answer['system'] ?? '', 12000, '...'),
            'response' => (string) ($answer['text'] ?? $answer['error'] ?? ''),
            'prompt_tokens' => $answer['tokens']['prompt'] ?? 0,
            'completion_tokens' => $answer['tokens']['completion'] ?? 0,
            'total_tokens' => $answer['tokens']['total'] ?? 0,
            'latency_ms' => $answer['latency_ms'] ?? 0,
        ]);
    }
}
```

41 app/Services/KnowledgeRetriever.php

157 lines

```php
<?php

namespace App\Services;

use App\Models\KnowledgeEntry;
use Illuminate\Support\Collection;
use Illuminate\Support\Facades\Cache;
use Illuminate\Support\Str;

/**
 * Scores curated knowledge entries against a question.
 *
 * Tokens are normalised and lightly stemmed for both Swahili and English
 * so that "nimekamatwa", "kukamatwa" and "kamatwa" all meet the keyword
 * "kamat". Entries in the citizen's language are preferred; other-language
 * entries are still searched at a discount so a Swahili question can draw
 * on an English-only fact block when nothing else matches.
 */
class KnowledgeRetriever
{
    private const STOP = [
        // Swahili
        'na', 'ya', 'wa', 'za', 'la', 'cha', 'vya', 'kwa', 'ni', 'si', 'je', 'nini', 'vipi', 'gani', 'wapi',
'lini', 'nani',
        'mbona', 'kama', 'jinsi', 'hii', 'hiyo', 'hili', 'hiki', 'yangu', 'wangu', 'langu', 'mimi', 'wewe', 'yeye',
'sisi',
        'wao', 'sana', 'tu', 'lakini', 'au', 'pia', 'kuhusu', 'katika', 'kutoka', 'hadi', 'sasa', 'leo', 'naomba',
'nataka',
        'nahitaji', 'tafadhali', 'asante', 'habari', 'huru', 'msaada', 'nieleze', 'niambie', 'eleza', 'fafanua',
'maana',
        'ipi', 'zipi', 'ngapi', 'kiasi', 'mara', 'bado', 'nipo', 'niko', 'ninaweza', 'naweza', 'unaweza',
'nifanye', 'nifanyeje',
        // English
        'the', 'is', 'are', 'and', 'of', 'to', 'in', 'for', 'what', 'how', 'why', 'when', 'where', 'who', 'which',
'can',
        'could', 'should', 'would', 'do', 'does', 'did', 'i', 'my', 'me', 'you', 'your', 'we', 'our', 'they',
'their', 'it',
        'this', 'that', 'these', 'with', 'from', 'about', 'please', 'help', 'need', 'want', 'explain', 'tell',
'describe',
        'define', 'have', 'has', 'been', 'was', 'were', 'will', 'not', 'but', 'or', 'also', 'there', 'here', 'now',
'a', 'an',
        'am', 'be', 'on', 'at', 'by', 'as', 'if', 'so', 'get', 'know', 'any', 'some', 'much', 'many',
        // Topic-level words that appear in almost every entry of a domain and therefore carry no signal.
        'sheria', 'kisheria', 'haki', 'legal', 'law', 'laws', 'rights', 'right', 'huduma', 'service', 'services',
        'serikali', 'government', 'tanzania', 'nchi', 'country', 'mwananchi', 'wananchi', 'citizen', 'citizens',
        'ofisi', 'office', 'taarifa', 'information', 'maelezo', 'swali', 'question',
    ];

    /**
     * @return Collection<int, KnowledgeEntry> ordered by relevance, each with ->score
     */
    public function search(string $question, string $language, ?string $category = null, int $limit = 2):
Collection
    {
        if ($limit <= 0) {
            return collect();
        }

        $queryTokens = $this->tokens($question);
        if (empty($queryTokens)) {
            return collect();
        }
        $querySet = array_flip($queryTokens);

        $entries = Cache::remember('huru.knowledge.active', 3600, fn () => KnowledgeEntry::query()
            ->where('is_active', true)
            ->get()
            ->map(function (KnowledgeEntry $e) {
                // Precompute token sets once per cache cycle.
                $e->setAttribute('_kw', array_flip($this->tokens(implode(' ', (array) $e->keywords))));
                $e->setAttribute('_title', array_flip($this->tokens($e->title)));
```

```
                $e->setAttribute('_body', array_flip($this->tokens(Str::limit($e->content, 1500, ''))));

                return $e;
            }));

        $scored = $entries->map(function (KnowledgeEntry $e) use ($querySet, $language, $category) {
            $score = 0;
            foreach ($querySet as $tok => $_) {
                if (isset($e->_kw[$tok])) {
                    $score += 3;
                }
                if (isset($e->_title[$tok])) {
                    $score += 2;
                }
                if (isset($e->_body[$tok])) {
                    $score += 1;
                }
            }
            if ($score === 0) {
                return null;
            }
            if ($category && $e->category === $category) {
                $score += 2;
            }
            if ($e->language !== $language) {
                $score = (int) ceil($score * 0.6);
            }
            $e->setAttribute('score', $score);

            return $e;
        })->filter()->sortByDesc('score')->values();

        return $scored->take($limit);
    }

    /** @return string[] unique normalised, stemmed tokens */
    public function tokens(string $text): array
    {
        $text = Str::lower($text);
        $text = preg_replace('/[^\p{L}\p{N} ]+/u', ' ', $text);
        $words = preg_split('/\s+/', trim($text), -1, PREG_SPLIT_NO_EMPTY);

        $out = [];
        foreach ($words as $w) {
            if (strlen($w) < 3 || in_array($w, self::STOP, true)) {
                continue;
            }
            $out[$w] = true;
            $stem = $this->stem($w);
            if ($stem !== $w && strlen($stem) >= 3) {
                $out[$stem] = true;
            }
        }

        return array_keys($out);
    }

    /**
     * Very small bilingual stemmer. Swahili: strip subject/tense prefixes and
     * common suffixes. English: strip plural/participle suffixes.
     */
    public function stem(string $w): string
    {
        $len = strlen($w);
        if ($len <= 4) {
            return $w;
        }

        // Swahili prefixes (longest first)
        foreach (['nime', 'ume', 'ame', 'tume', 'mme', 'wame', 'nina', 'una', 'ana', 'tuna', 'mna', 'wana', 'nita',
'uta', 'ata', 'tuta', 'wata', 'nili', 'uli', 'ali', 'tuli', 'wali', 'kuna', 'kuwa', 'ku', 'wa', 'ki', 'vi', 'ma', 'mi',
'u'] as $p) {
            if (str_starts_with($w, $p) && strlen($w) - strlen($p) >= 4) {
```

```
                $w = substr($w, strlen($p));
                break;
            }
        }
        // Swahili suffixes
        foreach (['wa', 'ni', 'ji', 'ka', 'ia', 'ea'] as $s) {
            if (str_ends_with($w, $s) && strlen($w) - strlen($s) >= 4) {
                $w = substr($w, 0, -strlen($s));
                break;
            }
        }
        // English suffixes
        foreach (['ies', 'ing', 'ed', 'es', 's'] as $s) {
            if (str_ends_with($w, $s) && strlen($w) - strlen($s) >= 4) {
                $w = substr($w, 0, -strlen($s));
                if ($s === 'ies') {
                    $w .= 'y';
                }
                break;
            }
        }

        return $w;
    }
}
```

42 app/Services/LanguageDetector.php

92 lines

```php
<?php

namespace App\Services;

use Illuminate\Support\Str;

/**
 * Decides whether a message is Swahili ('sw') or English ('en').
 *
 * Strategy: weighted function-word lists first; if that is a tie, fall back
 * to a morphological heuristic (Swahili words overwhelmingly end in a vowel
 * and use characteristic prefixes). Returns null only for empty input.
 */
class LanguageDetector
{
    private const SW = [
        'na' => 1, 'ya' => 1, 'wa' => 1, 'za' => 1, 'la' => 1, 'cha' => 1, 'vya' => 1, 'kwa' => 2, 'ni' => 1, 'si' => 1,
        'nini' => 3, 'vipi' => 3, 'gani' => 3, 'wapi' => 3, 'lini' => 3, 'nani' => 3, 'mbona' => 3, 'kwanini' => 3, 'kwa nini' => 3,
        'je' => 2, 'habari' => 2, 'naomba' => 3, 'nataka' => 3, 'nahitaji' => 3, 'msaada' => 2, 'tafadhali' => 3, 'asante' => 3,
        'ninaweza' => 3, 'naweza' => 3, 'unaweza' => 3, 'nifanye' => 3, 'nifanyeje' => 3, 'kama' => 1, 'jinsi' => 2, 'hii' => 2,
        'hiyo' => 2, 'hili' => 2, 'hiki' => 2, 'yangu' => 2, 'wangu' => 2, 'langu' => 2, 'changu' => 2, 'zangu' => 2, 'yake' => 2,
        'wake' => 1, 'mimi' => 2, 'wewe' => 2, 'yeye' => 2, 'sisi' => 2, 'ninyi' => 2, 'wao' => 2, 'sana' => 2, 'tu' => 1,
        'lakini' => 2, 'au' => 1, 'pia' => 2, 'kuhusu' => 3, 'katika' => 3, 'kutoka' => 3, 'hadi' => 2, 'mpaka' => 2,
        'sasa' => 2, 'leo' => 2, 'kesho' => 2, 'jana' => 2, 'sheria' => 2, 'haki' => 1, 'mtoto' => 2, 'watu' => 2, 'mtu' => 2,
        'nchi' => 2, 'serikali' => 2, 'shilingi' => 2, 'pesa' => 2, 'kazi' => 1, 'shule' => 2, 'nyumba' => 2, 'ardhi' => 2,
        'ndoa' => 2, 'afya' => 2, 'dawa' => 2, 'polisi' => 1, 'eleza' => 3, 'nieleze' => 3, 'niambie' => 3, 'fafanua' => 3,
        'maana' => 2, 'ipi' => 2, 'zipi' => 2, 'ngapi' => 3, 'kiasi' => 2, 'mara' => 1, 'bado' => 2, 'tayari' => 2,
    ];

    private const EN = [
        'the' => 2, 'is' => 1, 'are' => 1, 'and' => 1, 'of' => 1, 'to' => 1, 'in' => 1, 'for' => 1, 'what' => 3, 'how' => 3,
        'why' => 3, 'when' => 3, 'where' => 3, 'who' => 3, 'which' => 3, 'can' => 2, 'could' => 2, 'should' => 2, 'would' => 2,
        'do' => 1, 'does' => 2, 'did' => 2, 'i' => 1, 'my' => 2, 'me' => 2, 'you' => 2, 'your' => 2, 'we' => 2, 'our' => 2,
        'they' => 2, 'their' => 2, 'it' => 1, 'this' => 2, 'that' => 2, 'these' => 2, 'with' => 2, 'from' => 2, 'about' => 3,
        'please' => 3, 'help' => 2, 'need' => 2, 'want' => 2, 'explain' => 3, 'tell' => 2, 'describe' => 3, 'define' => 3,
        'difference' => 3, 'between' => 3, 'have' => 2, 'has' => 2, 'been' => 2, 'was' => 2, 'were' => 2, 'will' => 1,
        'not' => 2, 'but' => 2, 'or' => 1, 'also' => 2, 'there' => 2, 'here' => 2, 'now' => 2, 'today' => 2, 'tomorrow' => 2,
        'law' => 2, 'rights' => 2, 'child' => 2, 'people' => 2, 'person' => 2, 'country' => 2, 'government' => 2,
        'money' => 2, 'work' => 1, 'school' => 2, 'house' => 2, 'land' => 1, 'marriage' => 2, 'health' => 2, 'medicine' => 2,
        'much' => 2, 'many' => 2, 'if' => 2, 'because' => 3, 'get' => 1, 'know' => 2, 'think' => 2, 'any' => 2, 'some' => 2,
    ];

    public function detect(string $text): ?string
    {
        $lower = Str::lower($text);
        $words = preg_split('/[^\p{L}\p{N}\']+/u', $lower, -1, PREG_SPLIT_NO_EMPTY);

        if (empty($words)) {
            return null;
        }

        $sw = 0;
```

```
        $en = 0;
        foreach ($words as $w) {
            $sw += self::SW[$w] ?? 0;
            $en += self::EN[$w] ?? 0;
        }
        if (str_contains($lower, 'kwa nini')) {
            $sw += 3;
        }

        if ($sw !== $en) {
            return $sw > $en ? 'sw' : 'en';
        }

        // Morphological tie-breaker.
        $vowelEnding = 0;
        $swPrefix = 0;
        foreach ($words as $w) {
            if (strlen($w) < 3) {
                continue;
            }
            if (preg_match('/[aeiou]$/', $w)) {
                $vowelEnding++;
            }
            if
(preg_match('/^(ku|ni|u|a|tu|m|wa|ki|vi|ma|mi|ha|si|nime|ume|ame|tume|wame|nina|una|ana|tuna|wana|nita|uta|ata)/', $w)) {
                $swPrefix++;
            }
        }
        $considered = max(1, count(array_filter($words, fn ($w) => strlen($w) >= 3)));
        $ratio = $vowelEnding / $considered;

        if ($ratio >= 0.7 || ($ratio >= 0.55 && $swPrefix / $considered >= 0.4)) {
            return 'sw';
        }
        if ($ratio <= 0.35) {
            return 'en';
        }

        return null;
    }
}
```

43 app/Services/ModerationService.php

47 lines

```php
<?php

namespace App\Services;

use Illuminate\Support\Str;

class ModerationService
{
    /** Abusive terms in Swahili and English. Matched as whole words. */
    protected array $forbiddenWords = [
        'pumbavu', 'mjinga', 'mshenzi', 'fala', 'mavi', 'mbwa wewe', 'kuma', 'mboro', 'shoga', 'malaya', 'kahaba', 'takataka',
        'fuck', 'fucking', 'shit', 'idiot', 'stupid', 'bastard', 'bitch', 'asshole', 'dick', 'pussy', 'whore', 'slut', 'nigger',
    ];

    public function isAbusive(string $text): bool
    {
        $text = Str::lower($text);

        foreach ($this->forbiddenWords as $word) {
            if (preg_match('/(?<![\p{L}\p{N}])' . preg_quote($word, '/') . '(?![\p{L}\p{N}])/u', $text)) {
                return true;
            }
        }

        return false;
    }

    public function getWarningMessage(string $language, int $abuseCount, int $limit): string
    {
        $left = max(0, $limit - $abuseCount);

        if ($language === 'sw') {
            return "ONYO: Lugha ya matusi haikubaliki kwenye huduma hii. Hili ni onyo namba {$abuseCount}. Ukiendelea utafungiwa (nafasi zilizobaki: {$left}).";
        }

        return "WARNING: Abusive language is not accepted on this service. This is warning #{$abuseCount}. Continued abuse will lead to a ban ({$left} chances left).";
    }

    public function getBanMessage(string $language): string
    {
        if ($language === 'sw') {
            return 'HUDUMA IMEFUNGWA: Umefungiwa kutumia huduma hii kwa kukiuka masharti (lugha ya matusi). Wasiliana nasi ikiwa unaamini hili ni kosa.';
        }

        return 'SERVICE BANNED: You have been blocked from this service for violating our terms (abusive language). Contact us if you believe this is a mistake.';
    }
}
```

44 app/Services/PromptEngine.php

347 lines

```php
<?php

namespace App\Services;

use App\Models\LocalResource;
use App\Models\PromptTemplate;
use App\Models\ReferenceContact;
use App\Support\Settings;
use Illuminate\Support\Collection;
use Illuminate\Support\Facades\Cache;
use Illuminate\Support\Str;

/**
 * Assembles the system instruction and conversation turns for the engine.
 *
 * Layers, in order:
 *   1. Persona for the detected topic and language (admin-editable template)
 *   2. Country context (date, currency, institutions, emergency numbers)
 *   3. Topic guidance (how this subject works in Tanzania)
 *   4. Citizen profile (name, region, detected location)
 *   5. Retrieved knowledge entries
 *   6. Local resources near the citizen
 *   7. National directory contacts relevant to the topic
 *   8. Output constraints for the channel (SMS vs web)
 */
class PromptEngine
{
    public function __construct(
        private readonly KnowledgeRetriever $retriever,
        private readonly TanzaniaContext $tz,
    ) {
    }

    /**
     * @param array{
     *   question:string, language:string, category:string, channel:string,
     *   is_emergency?:bool, location?:?array, history?:array<int,array{role:string,text:string}>,
     *   user_name?:?string, user_region?:?string
     * } $ctx
     * @return array{system:string, turns:array, knowledge:Collection, resources:Collection, contacts:Collection}
     */
    public function build(array $ctx): array
    {
        $lang = $ctx['language'] === 'en' ? 'en' : 'sw';
        $category = $ctx['category'] ?: TopicClassifier::GENERAL;
        $channel = $ctx['channel'] ?? 'web';
        $question = trim($ctx['question']);
        $location = $ctx['location'] ?? null;
        $isEmergency = (bool) ($ctx['is_emergency'] ?? false);

        $knowledge = $this->retriever->search($question, $lang, $category, Settings::int('knowledge_matches'));
        $resources = $this->findLocalResources($location, $category, $ctx['user_region'] ?? null);
        $contacts = $this->findContacts($category, $isEmergency);

        $sections = [];
        $sections[] = $this->persona($category, $lang);
        $sections[] = $this->tz->localeBlock($lang);
        $sections[] = ($lang === 'en' ? "TOPIC RULES ({$this->label($category, $lang)}):\n" : "KANUNI ZA MADA
({$this->label($category, $lang)}):\n")
            . $this->tz->categoryGuidance($category, $lang);
        $sections[] = $this->profileBlock($ctx, $location, $lang);
        $sections[] = $this->knowledgeBlock($knowledge, $lang);
        $sections[] = $this->resourcesBlock($resources, $location, $lang);
        $sections[] = $this->contactsBlock($contacts, $isEmergency, $lang);
        $sections[] = $this->constraints($lang, $channel, $isEmergency);

        $system = implode("\n\n", array_filter($sections));

        $turns = [];
        foreach ($ctx['history'] ?? [] as $turn) {
            if (! empty($turn['text'])) {
```

```
                $turns[] = ['role' => $turn['role'], 'text' => $turn['text']];
            }
        }
        $turns[] = ['role' => 'user', 'text' => $question];

        return [
            'system' => $system,
            'turns' => $turns,
            'knowledge' => $knowledge,
            'resources' => $resources,
            'contacts' => $contacts,
        ];
    }

    // ---------------------------------------------------------------- blocks

    private function persona(string $category, string $lang): string
    {
        $templates = Cache::remember('huru.templates.active', 3600, fn () => PromptTemplate::query()
            ->where('is_active', true)
            ->get()
            ->keyBy(fn (PromptTemplate $t) => "{$t->category}:{$t->language}"));

        $tpl = $templates["{$category}:{$lang}"]
            ?? $templates[TopicClassifier::GENERAL . ":{$lang}"]
            ?? null;

        $text = $tpl?->template ?: $this->defaultPersona($lang);

        return str_replace(
            ['{app_name}', '{category}'],
            [Settings::get('app_name'), $this->label($category, $lang)],
            $text
        );
    }

    private function defaultPersona(string $lang): string
    {
        return $lang === 'en'
            ? 'You are {app_name}, a trusted everyday helper for citizens of Tanzania. You answer any question, on any subject, with accurate, practical, locally relevant guidance. You speak as a knowledgeable, respectful Tanzanian neighbour would: clear, direct, warm, never condescending.'
            : 'Wewe ni {app_name}, msaidizi wa kuaminika wa kila siku kwa wananchi wa Tanzania. Unajibu swali lolote, la mada yoyote, kwa usahihi, kwa vitendo na kwa muktadha wa Tanzania. Unazungumza kama jirani Mtanzania mwenye maarifa na heshima: wazi, moja kwa moja, mkarimu, bila kudharau.';
    }

    private function profileBlock(array $ctx, ?array $location, string $lang): string
    {
        $lines = [];
        if (! empty($ctx['user_name'])) {
            $lines[] = ($lang === 'en' ? '- Name: ' : '- Jina: ') . $ctx['user_name'];
        }
        if ($location) {
            $place = array_filter([
                $location['area'] ? Str::title($location['area']) : null,
                $location['district'] ? Str::title($location['district']) : null,
                $location['region'] ? Str::title($location['region']) : null,
            ]);
            $lines[] = ($lang === 'en' ? '- Location mentioned in this question: ' : '- Mahali alipotaja kwenye swali hili: ') . implode(', ', $place);
        } elseif (! empty($ctx['user_region'])) {
            $lines[] = ($lang === 'en' ? '- Home region on file: ' : '- Mkoa wake uliohifadhiwa: ') . Str::title($ctx['user_region']);
        }
        if (empty($lines)) {
            return '';
        }

        return ($lang === 'en' ? "ABOUT THE CITIZEN:\n" : "KUHUSU MWANANCHI:\n") . implode("\n", $lines);
    }

    private function knowledgeBlock(Collection $knowledge, string $lang): string
```

```
    {
        if ($knowledge->isEmpty()) {
            return $lang === 'en'
                ? 'VERIFIED LOCAL KNOWLEDGE: none matched this question. Rely on your general knowledge of Tanzania and say clearly when something should be confirmed with the responsible office.'
                : 'MAARIFA YALIYOTHIBITISHWA: hakuna yaliyolingana na swali hili. Tumia maarifa yako ya jumla kuhusu Tanzania na sema wazi pale ambapo jambo linapaswa kuthibitishwa na ofisi husika.';
        }

        $out = $lang === 'en'
            ? "VERIFIED LOCAL KNOWLEDGE (prefer this over your own memory when they conflict):\n"
            : "MAARIFA YALIYOTHIBITISHWA (yape kipaumbele kuliko kumbukumbu yako yakipingana):\n";

        foreach ($knowledge as $e) {
            $out .= "[{$e->title}]\n" . trim($e->content) . "\n";
            if ($e->source) {
                $out .= ($lang === 'en' ? 'Source: ' : 'Chanzo: ') . $e->source . "\n";
            }
            $out .= "\n";
        }

        return trim($out);
    }

    private function resourcesBlock(Collection $resources, ?array $location, string $lang): string
    {
        if ($resources->isEmpty()) {
            return '';
        }

        $where = $location ? Str::title($location['district'] ?? $location['region']) : '';
        $out = $lang === 'en'
            ? "SERVICES NEAR THE CITIZEN" . ($where ? " ({$where})" : '') . " (mention the most relevant ones by name with their contact):\n"
            : "HUDUMA ZILIZO KARIBU NA MWANANCHI" . ($where ? " ({$where})" : '') . " (taja zinazofaa zaidi kwa jina na mawasiliano yake):\n";

        foreach ($resources as $r) {
            $out .= "- {$r->name} (" . (LocalResource::CATEGORIES[$r->category] ?? $r->category) . '; ' . Str::title($r->district ?: $r->region) . ")";
            $bits = array_filter([$r->location, $r->phone ? ('Simu/Phone: ' . $r->phone) : null, $r->email ? ('Email: ' . $r->email) : null]);
            if ($bits) {
                $out .= ': ' . implode('; ', $bits);
            }
            $out .= "\n";
        }

        return trim($out);
    }

    private function contactsBlock(Collection $contacts, bool $isEmergency, string $lang): string
    {
        if ($contacts->isEmpty()) {
            return '';
        }

        $out = $lang === 'en'
            ? "OFFICIAL NATIONAL CONTACTS (use only when they help the citizen act; do not pad ordinary answers with them):\n"
            : "MAWASILIANO RASMI YA KITAIFA (tumia tu pale yanapomsaidia mwananchi kuchukua hatua; usiyajaze kwenye majibu ya kawaida):\n";

        foreach ($contacts as $c) {
            $bits = array_filter([$c->phone, $c->alt_phone, $c->email, $c->website]);
            $out .= '- ' . $c->name . ($c->is_emergency ? ($lang === 'en' ? ' [EMERGENCY]' : ' [DHARURA]') : '')
                . ($bits ? ': ' . implode(' / ', $bits) : '')
                . ($c->description($lang) ? ' - ' . $c->description($lang) : '')
                . "\n";
        }

        if ($isEmergency) {
            $out .= $lang === 'en'
```

```
                ? "\nTHIS LOOKS LIKE AN EMERGENCY: put the correct emergency number and the single most important immediate action in the FIRST line of your reply."
                : "\nHILI LINAONEKANA KUWA DHARURA: weka namba sahihi ya dharura na hatua moja muhimu zaidi ya haraka kwenye MSTARI WA KWANZA wa jibu lako.";
        }

        return trim($out);
    }

    private function constraints(string $lang, string $channel, bool $isEmergency): string
    {
        $maxWords = $channel === 'sms' ? Settings::int('sms_max_words') : Settings::int('web_max_words');
        $signature = trim((string) Settings::get($lang === 'en' ? 'signature_en' : 'signature_sw'));

        if ($lang === 'en') {
            $rules = [
                'Reply ONLY in the language of the citizen\'s latest message (English here). If they switch language, switch with them.',
                "Keep it under {$maxWords} words. " . ($channel === 'sms'
                    ? 'This is an SMS: short sentences, the most useful fact first, no lists longer than 4 items.'
                    : 'Use short paragraphs; a brief numbered list is fine for steps.'),
                'Plain text only. No markdown, no asterisks, no emoji, no headings.',
                'No greetings, no "as an assistant", no repeating the question. Start with the answer.',
                'Be honest: if you do not know or the information may have changed (fees, officials, deadlines), say so and name the office or website that can confirm.',
                'Never invent phone numbers, prices, laws or names of officials. Use only numbers given in this instruction or well-established public ones.',
                'Give no medical dosages, no legal representation, no political campaigning, no religious judgement.',
                'If the citizen asked a follow-up, use the earlier conversation turns to keep continuity.',
            ];
            if ($isEmergency) {
                array_unshift($rules, 'EMERGENCY: first line must be the emergency number and the immediate action.');
            }
            $out = "OUTPUT RULES:\n- " . implode("\n- ", $rules);
            if ($signature !== '') {
                $out .= "\n- End with exactly this line: \"{$signature}\"";
            }

            return $out;
        }

        $rules = [
            'Jibu TU kwa lugha ya ujumbe wa mwisho wa mwananchi (Kiswahili hapa). Akibadili lugha, badilika naye.',
            "Usizidi maneno {$maxWords}. " . ($channel === 'sms'
                ? 'Huu ni ujumbe wa SMS: sentensi fupi, jambo muhimu zaidi kwanza, orodha isizidi vipengele 4.'
                : 'Tumia aya fupi; orodha fupi ya namba inafaa kwa hatua.'),
            'Maandishi ya kawaida tu. Bila markdown, bila nyota (*), bila emoji, bila vichwa vya habari.',
            'Bila salamu, bila "kama msaidizi", bila kurudia swali. Anza na jibu.',
            'Kuwa mkweli: usipojua au taarifa inaweza kuwa imebadilika (ada, viongozi, tarehe za mwisho), sema hivyo na taja ofisi au tovuti inayoweza kuthibitisha.',
            'Usizue kamwe namba za simu, bei, sheria au majina ya viongozi. Tumia tu namba zilizotolewa kwenye maelekezo haya au zinazojulikana wazi.',
            'Usitoe dozi za dawa, usijifanye wakili, usifanye kampeni za kisiasa, usihukumu dini.',
            'Kama mwananchi ameuliza swali la kufuatilia, tumia mazungumzo ya awali kuendeleza mtiririko.',
        ];
        if ($isEmergency) {
            array_unshift($rules, 'DHARURA: mstari wa kwanza lazima uwe namba ya dharura na hatua ya haraka.');
        }
        $out = "KANUNI ZA JIBU:\n- " . implode("\n- ", $rules);
        if ($signature !== '') {
            $out .= "\n- Malizia kwa mstari huu haswa: \"{$signature}\"";
        }

        return $out;
    }

    // ---------------------------------------------------------------- lookups

    private function findLocalResources(?array $location, string $category, ?string $userRegion): Collection
    {
        $region = $location['region'] ?? $userRegion;
```

```
        if (! $region) {
            return collect();
        }

        $categoryMap = [
            'legal' => ['legal_aid', 'police'],
            'family' => ['police', 'legal_aid', 'government'],
            'health' => ['health'],
            'agriculture' => ['agriculture'],
            'government' => ['government'],
            'education' => ['education'],
            'finance' => ['finance'],
            'business' => ['finance', 'government'],
            'employment' => ['government', 'legal_aid'],
        ];
        $wanted = $categoryMap[$category] ?? null;

        $query = LocalResource::query()->where('is_active', true)
            ->whereRaw('LOWER(region) = ?', [Str::lower($region)]);
        if ($wanted) {
            $query->whereIn('category', $wanted);
        }

        $all = $query->get();
        if ($all->isEmpty()) {
            return collect();
        }

        $district = $location['district'] ?? null;
        $area = $location['area'] ?? null;

        return $all->sortByDesc(function (LocalResource $r) use ($district, $area) {
            $score = 0;
            if ($district && Str::lower((string) $r->district) === $district) {
                $score += 5;
            }
            if ($area && str_contains(Str::lower((string) $r->location . ' ' . $r->ward), $area)) {
                $score += 8;
            }

            return $score;
        })->take(4)->values();
    }

    private function findContacts(string $category, bool $isEmergency): Collection
    {
        $contacts = Cache::remember('huru.contacts.active', 3600, fn () => ReferenceContact::query()
            ->where('is_active', true)
            ->orderBy('sort_order')
            ->get());

        $related = [
            'legal' => ['legal', 'police'],
            'family' => ['family', 'police', 'legal'],
            'health' => ['health'],
            'agriculture' => ['agriculture'],
            'education' => ['education'],
            'government' => ['government'],
            'finance' => ['finance'],
            'business' => ['business', 'finance'],
            'employment' => ['employment', 'legal'],
            'technology' => ['technology'],
            'transport' => ['transport', 'police'],
            'general' => [],
        ];
        $wanted = $related[$category] ?? [];

        $selected = $contacts->filter(fn (ReferenceContact $c) => in_array($c->category, $wanted, true));

        if ($isEmergency) {
            $selected = $contacts->filter(fn (ReferenceContact $c) => $c->is_emergency)->merge($selected);
        }

```

```
        return $selected->unique('id')->take(8)->values();
    }

    private function label(string $category, string $lang): string
    {
        return TopicClassifier::label($category, $lang);
    }
}
```

45 app/Services/SmsService.php

93 lines

```php
<?php

namespace App\Services;

use Illuminate\Support\Facades\Http;
use Illuminate\Support\Facades\Log;

/**
 * Africa's Talking SMS over their REST API, through Laravel's HTTP client
 * so the global TLS settings, retries and timeouts apply.
 */
class SmsService
{
    protected ?string $username;
    protected ?string $apiKey;
    protected ?string $from;

    public function __construct()
    {
        $this->username = config('services.at.username');
        $this->apiKey = config('services.at.api_key');
        $this->from = config('services.at.from');
    }

    public function isConfigured(): bool
    {
        return ! empty($this->username) && ! empty($this->apiKey);
    }

    public function endpoint(): string
    {
        return $this->username === 'sandbox'
            ? 'https://api.sandbox.africastalking.com/version1/messaging'
            : 'https://api.africastalking.com/version1/messaging';
    }

    /**
     * @return array{status:string, data?:mixed, message?:string}
     */
    public function send(string $to, string $message): array
    {
        if (! $this->isConfigured()) {
            Log::warning('SMS not sent: Africa\'s Talking credentials missing.', ['to' => $this->mask($to)]);

            return ['status' => 'skipped', 'message' => 'sms_not_configured'];
        }

        $payload = ['username' => $this->username, 'to' => $to, 'message' => $message];
        if ($this->from) {
            $payload['from'] = $this->from;
        }

        try {
            $response = Http::timeout(20)
                ->retry(2, 500, throw: false)
                ->withHeaders(['apiKey' => $this->apiKey, 'Accept' => 'application/json'])
                ->asForm()
                ->post($this->endpoint(), $payload);

            $data = $response->json();
            $recipient = $data['SMSMessageData']['Recipients'][0] ?? null;
            $status = $recipient['status'] ?? ($data['SMSMessageData']['Message'] ?? 'HTTP ' . $response->status());

            if (! $response->successful() || ! $recipient || ! in_array($recipient['statusCode'] ?? 0, [100, 101, 102], true)) {
                Log::error('SMS send failed', ['to' => $this->mask($to), 'status' => $status, 'http' => $response->status()]);

                return ['status' => 'error', 'message' => (string) $status, 'data' => $data];
            }
```

```
    69
    70              Log::info('SMS sent', ['to' => $this->mask($to), 'chars' => strlen($message), 'cost' =>
$recipient['cost'] ?? null]);
    71
    72              return ['status' => 'success', 'data' => $data];
    73          } catch (\Throwable $e) {
    74              Log::error('SMS send error: ' . $e->getMessage());
    75
    76              return ['status' => 'error', 'message' => $e->getMessage()];
    77          }
    78      }
    79
    80      public function sendOtp(string $to, string $code, string $language, string $appName, int $ttlMinutes): array
    81      {
    82          $text = $language === 'en'
    83              ? "{$appName}: your verification code is {$code}. It expires in {$ttlMinutes} minutes. Do not share it
with anyone."
    84              : "{$appName}: namba yako ya uthibitisho ni {$code}. Inaisha baada ya dakika {$ttlMinutes}. Usimpe mtu
yeyote.";
    85
    86          return $this->send($to, $text);
    87      }
    88
    89      private function mask(string $phone): string
    90      {
    91          return strlen($phone) > 6 ? substr($phone, 0, 4) . '****' . substr($phone, -3) : '****';
    92      }
    93  }
```

46 app/Services/TanzaniaContext.php

238 lines

```php
<?php

namespace App\Services;

use Carbon\Carbon;
use Illuminate\Support\Str;

/**
 * Everything the engine should know about Tanzania before it answers:
 * where the citizen is, what day it is in East Africa, which currency and
 * institutions apply, and how each topic should be handled locally.
 */
class TanzaniaContext
{
    public const TIMEZONE = 'Africa/Dar_es_Salaam';

    /** The 31 regions (26 Mainland + 5 Zanzibar). */
    public const REGIONS = [
        'arusha', 'dar es salaam', 'dodoma', 'geita', 'iringa', 'kagera', 'katavi', 'kigoma', 'kilimanjaro',
        'lindi', 'manyara', 'mara', 'mbeya', 'morogoro', 'mtwara', 'mwanza', 'njombe', 'pwani', 'rukwa', 'ruvuma',
        'shinyanga', 'simiyu', 'singida', 'songwe', 'tabora', 'tanga',
        'kaskazini pemba', 'kusini pemba', 'kaskazini unguja', 'kusini unguja', 'mjini magharibi',
    ];

    /** Common aliases citizens actually type. */
    private const REGION_ALIASES = [
        'dar' => 'dar es salaam', 'dsm' => 'dar es salaam', 'bongo' => 'dar es salaam', 'coast' => 'pwani',
        'zanzibar' => 'mjini magharibi', 'unguja' => 'mjini magharibi', 'pemba' => 'kaskazini pemba',
        'moshi' => 'kilimanjaro', 'kili' => 'kilimanjaro',
    ];

    /** District (or well-known town) => region. Not exhaustive, covers what people write. */
    private const DISTRICTS = [
        // Dar es Salaam
        'ilala' => 'dar es salaam', 'kinondoni' => 'dar es salaam', 'temeke' => 'dar es salaam',
        'ubungo' => 'dar es salaam', 'kigamboni' => 'dar es salaam',
        // Arusha
        'meru' => 'arusha', 'monduli' => 'arusha', 'karatu' => 'arusha', 'longido' => 'arusha', 'ngorongoro' =>
'arusha',
        // Dodoma
        'bahi' => 'dodoma', 'chamwino' => 'dodoma', 'kondoa' => 'dodoma', 'kongwa' => 'dodoma', 'mpwapwa' =>
'dodoma', 'chemba' => 'dodoma',
        // Mwanza
        'nyamagana' => 'mwanza', 'ilemela' => 'mwanza', 'magu' => 'mwanza', 'misungwi' => 'mwanza', 'sengerema' =>
'mwanza', 'ukerewe' => 'mwanza', 'kwimba' => 'mwanza',
        // Mbeya
        'rungwe' => 'mbeya', 'kyela' => 'mbeya', 'chunya' => 'mbeya', 'mbarali' => 'mbeya', 'busokelo' => 'mbeya',
        // Kilimanjaro
        'moshi' => 'kilimanjaro', 'hai' => 'kilimanjaro', 'rombo' => 'kilimanjaro', 'same' => 'kilimanjaro',
'mwanga' => 'kilimanjaro', 'siha' => 'kilimanjaro',
        // Tanga
        'muheza' => 'tanga', 'korogwe' => 'tanga', 'lushoto' => 'tanga', 'handeni' => 'tanga', 'pangani' =>
'tanga', 'mkinga' => 'tanga', 'kilindi' => 'tanga',
        // Morogoro
        'kilosa' => 'morogoro', 'kilombero' => 'morogoro', 'ulanga' => 'morogoro', 'mvomero' => 'morogoro', 'gairo'
=> 'morogoro', 'malinyi' => 'morogoro', 'ifakara' => 'morogoro',
        // Shinyanga
        'kahama' => 'shinyanga', 'kishapu' => 'shinyanga',
        // Geita
        'chato' => 'geita', 'bukombe' => 'geita', 'mbogwe' => 'geita', 'nyanghwale' => 'geita',
        // Kagera
        'bukoba' => 'kagera', 'muleba' => 'kagera', 'karagwe' => 'kagera', 'ngara' => 'kagera', 'biharamulo' =>
'kagera', 'missenyi' => 'kagera', 'kyerwa' => 'kagera',
        // Kigoma
        'kasulu' => 'kigoma', 'kibondo' => 'kigoma', 'uvinza' => 'kigoma', 'buhigwe' => 'kigoma', 'kakonko' =>
'kigoma',
        // Mara
        'musoma' => 'mara', 'tarime' => 'mara', 'serengeti' => 'mara', 'bunda' => 'mara', 'rorya' => 'mara',
'butiama' => 'mara',
        // Tabora
        'nzega' => 'tabora', 'igunga' => 'tabora', 'urambo' => 'tabora', 'sikonge' => 'tabora', 'uyui' => 'tabora',
```

```
'kaliua' => 'tabora',
    63          // Iringa / Njombe
    64          'kilolo' => 'iringa', 'mufindi' => 'iringa', 'makete' => 'njombe', 'wangingombe' => 'njombe', 'ludewa' =>
'njombe', 'makambako' => 'njombe',
    65          // Ruvuma
    66          'songea' => 'ruvuma', 'mbinga' => 'ruvuma', 'tunduru' => 'ruvuma', 'namtumbo' => 'ruvuma', 'nyasa' =>
'ruvuma', 'madaba' => 'ruvuma',
    67          // Mtwara / Lindi
    68          'masasi' => 'mtwara', 'newala' => 'mtwara', 'nanyumbu' => 'mtwara', 'tandahimba' => 'mtwara',
    69          'kilwa' => 'lindi', 'nachingwea' => 'lindi', 'liwale' => 'lindi', 'ruangwa' => 'lindi',
    70          // Pwani
    71          'kibaha' => 'pwani', 'bagamoyo' => 'pwani', 'kisarawe' => 'pwani', 'mkuranga' => 'pwani', 'rufiji' =>
'pwani', 'mafia' => 'pwani', 'kibiti' => 'pwani', 'chalinze' => 'pwani',
    72          // Singida / Manyara
    73          'manyoni' => 'singida', 'iramba' => 'singida', 'ikungi' => 'singida', 'mkalama' => 'singida', 'itigi' =>
'singida',
    74          'babati' => 'manyara', 'hanang' => 'manyara', 'mbulu' => 'manyara', 'simanjiro' => 'manyara', 'kiteto' =>
'manyara',
    75          // Rukwa / Katavi / Songwe
    76          'sumbawanga' => 'rukwa', 'nkasi' => 'rukwa', 'kalambo' => 'rukwa',
    77          'mpanda' => 'katavi', 'mlele' => 'katavi', 'tanganyika' => 'katavi',
    78          'tunduma' => 'songwe', 'momba' => 'songwe', 'ileje' => 'songwe', 'mbozi' => 'songwe', 'vwawa' => 'songwe',
    79          // Simiyu
    80          'bariadi' => 'simiyu', 'maswa' => 'simiyu', 'meatu' => 'simiyu', 'itilima' => 'simiyu', 'busega' =>
'simiyu',
    81          // Zanzibar
    82          'wete' => 'kaskazini pemba', 'micheweni' => 'kaskazini pemba', 'chake chake' => 'kusini pemba', 'mkoani' =>
'kusini pemba',
    83          'mjini' => 'mjini magharibi', 'magharibi' => 'mjini magharibi', 'stone town' => 'mjini magharibi',
    84      ];
    85
    86      /** Well-known neighbourhoods / wards => [district, region]. Mostly Dar es Salaam, where most web traffic comes
from. */
    87      private const AREAS = [
    88          'sinza' => ['ubungo', 'dar es salaam'], 'mwenge' => ['kinondoni', 'dar es salaam'], 'mbezi' => ['ubungo',
'dar es salaam'],
    89          'tegeta' => ['kinondoni', 'dar es salaam'], 'kawe' => ['kinondoni', 'dar es salaam'], 'mikocheni' =>
['kinondoni', 'dar es salaam'],
    90          'masaki' => ['kinondoni', 'dar es salaam'], 'oysterbay' => ['kinondoni', 'dar es salaam'], 'kijitonyama' =>
['kinondoni', 'dar es salaam'],
    91          'magomeni' => ['kinondoni', 'dar es salaam'], 'tandale' => ['kinondoni', 'dar es salaam'], 'manzese' =>
['ubungo', 'dar es salaam'],
    92          'mabibo' => ['ubungo', 'dar es salaam'], 'kimara' => ['ubungo', 'dar es salaam'], 'kibamba' => ['ubungo',
'dar es salaam'],
    93          'goba' => ['ubungo', 'dar es salaam'], 'makongo' => ['ubungo', 'dar es salaam'], 'mburahati' => ['ubungo',
'dar es salaam'],
    94          'kariakoo' => ['ilala', 'dar es salaam'], 'upanga' => ['ilala', 'dar es salaam'], 'buguruni' => ['ilala',
'dar es salaam'],
    95          'tabata' => ['ilala', 'dar es salaam'], 'segerea' => ['ilala', 'dar es salaam'], 'ukonga' => ['ilala', 'dar
es salaam'],
    96          'gongo la mboto' => ['ilala', 'dar es salaam'], 'kinyerezi' => ['ilala', 'dar es salaam'], 'vingunguti' =>
['ilala', 'dar es salaam'],
    97          'mbagala' => ['temeke', 'dar es salaam'], 'tandika' => ['temeke', 'dar es salaam'], 'kurasini' =>
['temeke', 'dar es salaam'],
    98          'changombe' => ['temeke', 'dar es salaam'], 'chamazi' => ['temeke', 'dar es salaam'], 'kigamboni' =>
['kigamboni', 'dar es salaam'],
    99          'posta' => ['ilala', 'dar es salaam'], 'mnazi mmoja' => ['ilala', 'dar es salaam'],
   100          'sakina' => ['arusha', 'arusha'], 'njiro' => ['arusha', 'arusha'], 'ngaramtoni' => ['arusha', 'arusha'],
   101          'nyakato' => ['ilemela', 'mwanza'], 'pasiansi' => ['ilemela', 'mwanza'], 'igoma' => ['nyamagana',
'mwanza'],
   102          'uyole' => ['mbeya', 'mbeya'], 'mwanjelwa' => ['mbeya', 'mbeya'], 'majengo' => ['moshi', 'kilimanjaro'],
   103          'mtumba' => ['dodoma', 'dodoma'], 'nzuguni' => ['dodoma', 'dodoma'],
   104      ];
   105
   106      /**
   107       * Detect region / district / area mentioned in free text.
   108       *
   109       * @return array{region:?string,district:?string,area:?string}|null
   110       */
   111      public function detectLocation(string $text): ?array
   112      {
   113          $norm = ' ' . trim(preg_replace('/\s+/', ' ', preg_replace('/[^\p{L}\p{N} ]+/u', ' ', Str::lower($text))))
. ' ';
```

```
114
115         $result = ['region' => null, 'district' => null, 'area' => null];
116
117         foreach (self::AREAS as $area => [$district, $region]) {
118             if (str_contains($norm, " {$area} ")) {
119                 $result = ['region' => $region, 'district' => $district, 'area' => $area];
120                 break;
121             }
122         }
123
124         if (! $result['district']) {
125             foreach (self::DISTRICTS as $district => $region) {
126                 if (str_contains($norm, " {$district} ")) {
127                     $result['district'] = $district;
128                     $result['region'] = $region;
129                     break;
130                 }
131             }
132         }
133
134         if (! $result['region']) {
135             foreach (self::REGIONS as $region) {
136                 if (str_contains($norm, " {$region} ")) {
137                     $result['region'] = $region;
138                     break;
139                 }
140             }
141         }
142
143         if (! $result['region']) {
144             foreach (self::REGION_ALIASES as $alias => $region) {
145                 if (str_contains($norm, " {$alias} ")) {
146                     $result['region'] = $region;
147                     break;
148                 }
149             }
150         }
151
152         return $result['region'] ? $result : null;
153     }
154
155     public function now(): Carbon
156     {
157         return Carbon::now(self::TIMEZONE);
158     }
159
160     /** Country facts the engine must assume, in the citizen's language. */
161     public function localeBlock(string $language): string
162     {
163         $now = $this->now();
164
165         if ($language === 'en') {
166             return "COUNTRY CONTEXT (assume these facts):\n"
167                 . '- Country: United Republic of Tanzania (Mainland and Zanzibar). Today is ' . $now->format('l, j
F Y') . ', time ' . $now->format('H:i') . " East Africa Time.\n"
168                 . "- Capital: Dodoma (seat of government and parliament). Commercial capital and largest city: Dar
es Salaam.\n"
169                 . "- Currency: Tanzanian Shilling (TZS). Never quote prices in other currencies unless asked.\n"
170                 . "- Languages: Swahili (national) and English (official). Many citizens read Swahili more
comfortably.\n"
171                 . "- Mobile money (M-Pesa, Tigo Pesa/Mixx by Yas, Airtel Money, HaloPesa) is the everyday payment
method. Government payments go through GePG control numbers.\n"
172                 . "- Local government chain: Village/Mtaa Executive Officer, Ward Executive Officer (WEO), District
Council/Commissioner, Regional Commissioner. Most everyday problems start at the ward office.\n"
173                 . "- Legal system: common law with the Constitution of 1977; primary courts, district courts, High
Court, Court of Appeal. Ward tribunals and District Land and Housing Tribunals handle local disputes.\n"
174                 . "- Emergency numbers: Police 112, Fire 114, Ambulance 115, Child helpline 116.\n";
175         }
176
177         return "MUKTADHA WA NCHI (chukulia haya kuwa ukweli):\n"
178             . '- Nchi: Jamhuri ya Muungano wa Tanzania (Bara na Zanzibar). Leo ni ' . $this->swahiliDate($now) . ',
saa ' . $now->format('H:i') . " saa za Afrika Mashariki.\n"
179             . "- Makao makuu: Dodoma (Serikali na Bunge). Jiji kubwa la kibiashara: Dar es Salaam.\n"
```

```
            . "- Sarafu: Shilingi ya Tanzania (TZS). Usitaje bei kwa sarafu nyingine isipokuwa ukiulizwa.\n"
            . "- Lugha: Kiswahili (lugha ya taifa) na Kiingereza (lugha rasmi). Wananchi wengi husoma Kiswahili kwa urahisi zaidi.\n"
            . "- Malipo ya kila siku ni kwa pesa za simu (M-Pesa, Mixx by Yas/Tigo Pesa, Airtel Money, HaloPesa). Malipo ya serikali hufanywa kwa namba ya kumbukumbu (control number) ya GePG.\n"
            . "- Ngazi za serikali za mitaa: Mtendaji wa Kijiji/Mtaa, Mtendaji wa Kata (WEO), Halmashauri/Mkuu wa Wilaya, Mkuu wa Mkoa. Matatizo mengi ya kila siku huanzia ofisi ya kata.\n"
            . "- Mfumo wa sheria: Katiba ya 1977; mahakama za mwanzo, za wilaya, Mahakama Kuu, Mahakama ya Rufani. Mabaraza ya kata na Mabaraza ya Ardhi na Nyumba ya Wilaya hushughulikia migogoro ya karibu.\n"
            . "- Namba za dharura: Polisi 112, Zimamoto 114, Gari la wagonjwa 115, Msaada kwa mtoto 116.\n";
    }

    /** Topic-specific handling rules, grounded in how things work in Tanzania. */
    public function categoryGuidance(string $category, string $language): string
    {
        $sw = [
            'legal' => "- Rejea sheria za Tanzania (Katiba 1977, Sheria ya Ndoa 1971, Sheria ya Ardhi Sura 113, Sheria ya Ajira na Mahusiano Kazini Sura 366, Sheria ya Mwenendo wa Makosa ya Jinai, Sheria ya Mtoto 2009). Toa hatua za vitendo: wapi pa kuanzia (mtendaji wa kata, baraza la kata, polisi, dawati la jinsia, baraza la ardhi, mahakama ya mwanzo). Kama hali ni nzito mshauri aonane na mtoa msaada wa kisheria au wakili. Usijifanye wakili wake; eleza kuwa haya ni maelezo ya jumla.",
            'health' => "- Wewe si daktari. Toa maelezo ya afya ya jumla yanayokubalika Tanzania (MoH, WHO), dalili za hatari zinazohitaji kwenda zahanati/hospitali MARA MOJA, na huduma zilizopo (zahanati ya kata, kituo cha afya, hospitali ya wilaya/mkoa, NHIF/CHF iliyoboreshwa). Usitoe dozi za dawa za kuandikiwa. Kwa dharura mwambie apige 115 au aende kituo cha afya cha karibu.",
            'agriculture' => "- Zingatia misimu ya Tanzania (Vuli Okt-Des na Masika Mac-Mei kaskazini na pwani; msimu mmoja Nov-Apr katikati na kusini), udongo na mazao ya eneo husika. Mshauri atumie afisa ugani wa kata/wilaya, TARI, TOSCI kwa mbegu, na TMA kwa hali ya hewa. Taja bei kwa TZS na usizue bei usizozijua.",
            'education' => "- Fuata mfumo wa Tanzania: shule ya msingi (Darasa 1-7, mtihani wa PSLE), sekondari (Kidato 1-4 CSEE, 5-6 ACSEE), VETA, vyuo. NECTA ndiyo baraza la mitihani, HESLB ndiyo bodi ya mikopo, TCU/NACTVET husajili vyuo. Unapofundisha somo, eleza kwa hatua rahisi na mfano wa Kitanzania.",
            'government' => "- Eleza hatua halisi za kupata huduma: ofisi gani (NIDA, RITA, Uhamiaji, BRELA, TRA, TANESCO, Halmashauri), nyaraka zinazohitajika, na kuwa malipo ya serikali hulipwa kwa control number ya GePG. Usizue ada; sema 'thibitisha ada ofisini' kama hujui. Hakikisha hutoi maoni ya kisiasa.",
            'finance' => "- Tumia TZS. Eleza TRA (TIN, kodi ya mapato, VAT), BoT, benki na SACCOS, pesa za simu na gharama zake. Onya kuhusu utapeli (ujumbe wa 'umeshinda', mikopo ya haraka ya mtandaoni, piramidi). Usishauri uwekezaji maalum; toa kanuni za jumla.",
            'business' => "- Eleza usajili (BRELA kwa jina/kampuni, leseni ya biashara ya halmashauri, TIN ya TRA, TBS/TMDA kwa bidhaa), na hatua za vitendo za kuanzisha au kukuza biashara ndogo nchini Tanzania. Taja fursa halisi kama SIDO na mifuko ya halmashauri ya vijana/wanawake/walemavu (10%).",
            'employment' => "- Rejea Sheria ya Ajira na Mahusiano Kazini (Sura 366): mkataba wa maandishi, saa 45 kwa wiki, likizo ya mwaka siku 28, uzazi siku 84, utaratibu wa kuachishwa kazi. Mshauri kuhusu CMA (Tume ya Usuluhishi na Uamuzi), ofisi ya kazi ya wilaya, NSSF/PSSSF. Onya kuhusu matapeli wa ajira nje ya nchi.",
            'family' => "- Kuwa mpole na mwenye heshima. Kwa ukatili wa kijinsia au kwa mtoto, taja dawati la jinsia la polisi, ustawi wa jamii wa halmashauri, na namba 116. Rejea Sheria ya Mtoto 2009 na Sheria ya Ndoa 1971. Usihukumu; toa hatua salama za vitendo.",
            'technology' => "- Eleza kwa lugha rahisi. Kwa laini za simu na udukuzi taja TCRA na huduma za mtandao husika (Vodacom, Yas, Airtel, Halotel, TTCL). Onya kuhusu kutoa PIN, OTP au nywila kwa mtu yeyote.",
            'transport' => "- Rejea Sheria ya Usalama Barabarani, TRA (usajili wa magari), LATRA (nauli na mabasi), TANROADS. Faini za trafiki hulipwa kwa control number, si fedha taslimu kwa askari.",
            'general' => "- Jibu swali lolote kwa uaminifu na kwa muktadha wa Tanzania. Kama swali linahusu somo la shule, lifundishe kwa hatua. Kama ni la kawaida, jibu kwa ufupi na kwa heshima.",
        ];

        $en = [
            'legal' => "- Cite Tanzanian law (Constitution 1977, Law of Marriage Act 1971, Land Act Cap 113, Employment and Labour Relations Act Cap 366, Criminal Procedure Act, Law of the Child Act 2009). Give practical steps: where to start (ward executive, ward tribunal, police, gender desk, land tribunal, primary court). For serious matters advise seeing a legal aid provider or advocate. Make clear this is general information, not legal representation.",
            'health' => "- You are not a doctor. Give generally accepted health information (Ministry of Health, WHO), list danger signs that need a facility IMMEDIATELY, and name the care available (ward dispensary, health centre, district/regional hospital, NHIF/improved CHF). Do not give prescription dosages. For emergencies say call 115 or go to the nearest facility.",
            'agriculture' => "- Respect Tanzanian seasons (short rains Oct-Dec and long rains Mar-May in the north and coast; single season Nov-Apr in central and southern highlands), local soils and crops. Point to the ward/district extension officer, TARI, TOSCI for seed, TMA for weather. Quote prices in TZS and never invent prices.",
            'education' => "- Follow the Tanzanian system: primary (Standard 1-7, PSLE), secondary (Form 1-4 CSEE, Form 5-6 ACSEE), VETA, colleges. NECTA runs exams, HESLB gives student loans, TCU/NACTVET accredit institutions. When teaching a subject, explain step by step with a Tanzanian example.",
            'government' => "- Explain the real procedure: which office (NIDA, RITA, Immigration, BRELA, TRA, TANESCO, District Council), documents needed, and that government fees are paid via a GePG control number. Never invent fees; say 'confirm the fee at the office' if unknown. Give no political opinions.",
            'finance' => "- Use TZS. Explain TRA (TIN, income tax, VAT), Bank of Tanzania, banks and SACCOS, mobile
```

```
money and its charges. Warn about scams ('you have won' messages, instant online loans, pyramid schemes). Do not recommend specific investments; give general principles.",
            'business' => "- Explain registration (BRELA for business name/company, district business licence, TRA TIN, TBS/TMDA for products) and practical steps to start or grow a small business in Tanzania. Mention real opportunities such as SIDO and the council 10% loans for youth, women and persons with disabilities.",
            'employment' => "- Cite the Employment and Labour Relations Act (Cap 366): written contract, 45-hour week, 28 days annual leave, 84 days maternity, fair termination procedure. Point to CMA (Commission for Mediation and Arbitration), the district labour office, NSSF/PSSSF. Warn about overseas job scams.",
            'family' => "- Be gentle and respectful. For gender-based violence or harm to a child, name the police gender desk, the council social welfare officer and the 116 helpline. Cite the Law of the Child Act 2009 and Law of Marriage Act 1971. Do not judge; give safe practical steps.",
            'technology' => "- Explain in plain language. For SIM cards and hacking mention TCRA and the relevant network (Vodacom, Yas, Airtel, Halotel, TTCL). Warn never to share PIN, OTP or passwords with anyone.",
            'transport' => "- Cite the Road Traffic Act, TRA (vehicle registration), LATRA (fares and buses), TANROADS. Traffic fines are paid via a control number, never cash to an officer.",
            'general' => "- Answer any question honestly within the Tanzanian context. If it is a school subject, teach it step by step. If it is everyday life, answer briefly and respectfully.",
        ];

        $table = $language === 'en' ? $en : $sw;

        return $table[$category] ?? $table['general'];
    }

    public static function regionLabel(?string $region): ?string
    {
        return $region ? Str::title($region) : null;
    }

    private function swahiliDate(Carbon $date): string
    {
        $days = ['Monday' => 'Jumatatu', 'Tuesday' => 'Jumanne', 'Wednesday' => 'Jumatano', 'Thursday' => 'Alhamisi', 'Friday' => 'Ijumaa', 'Saturday' => 'Jumamosi', 'Sunday' => 'Jumapili'];
        $months = [1 => 'Januari', 'Februari', 'Machi', 'Aprili', 'Mei', 'Juni', 'Julai', 'Agosti', 'Septemba', 'Oktoba', 'Novemba', 'Desemba'];

        return $days[$date->format('l')] . ', ' . $date->day . ' ' . $months[$date->month] . ' ' . $date->year;
    }
}
```

47 app/Services/TopicClassifier.php

266 lines

```php
<?php

namespace App\Services;

use Illuminate\Support\Str;

/**
 * Lightweight bilingual (Swahili / English) topic classifier.
 *
 * It scores a question against weighted keyword maps for each domain so the
 * engine can pick the right persona, the right knowledge entries and the
 * right contacts. It also flags emergencies so safety numbers are surfaced
 * first. No network call, runs in well under a millisecond.
 */
class TopicClassifier
{
    public const GENERAL = 'general';

    /** @var array<string, array{sw:string,en:string}> */
    public const CATEGORIES = [
        'legal' => ['sw' => 'Sheria na Haki', 'en' => 'Law and Rights'],
        'health' => ['sw' => 'Afya', 'en' => 'Health'],
        'agriculture' => ['sw' => 'Kilimo, Mifugo na Uvuvi', 'en' => 'Agriculture, Livestock and Fishing'],
        'education' => ['sw' => 'Elimu', 'en' => 'Education'],
        'government' => ['sw' => 'Huduma za Serikali', 'en' => 'Government Services'],
        'finance' => ['sw' => 'Fedha na Kodi', 'en' => 'Money and Tax'],
        'business' => ['sw' => 'Biashara na Ujasiriamali', 'en' => 'Business and Entrepreneurship'],
        'employment' => ['sw' => 'Ajira na Kazi', 'en' => 'Jobs and Employment'],
        'family' => ['sw' => 'Familia na Jamii', 'en' => 'Family and Community'],
        'technology' => ['sw' => 'Teknolojia na Mawasiliano', 'en' => 'Technology and Communication'],
        'transport' => ['sw' => 'Usafiri na Usalama Barabarani', 'en' => 'Transport and Road Safety'],
        'general' => ['sw' => 'Maswali ya Jumla', 'en' => 'General Questions'],
    ];

    /**
     * Keyword => weight. Keywords are matched as whole words after
     * normalisation; multi-word keywords are matched as substrings.
     *
     * @var array<string, array<string,int>>
     */
    private const KEYWORDS = [
        'legal' => [
            // Swahili
            'sheria' => 3, 'kisheria' => 3, 'haki' => 2, 'katiba' => 3, 'mahakama' => 3, 'hakimu' => 3, 'jaji' =>
3,
            'wakili' => 3, 'kesi' => 3, 'mashtaka' => 3, 'kukamatwa' => 3, 'dhamana' => 3, 'polisi' => 2, 'jela' =>
2,
            'gereza' => 2, 'mkataba' => 2, 'talaka' => 3, 'ndoa' => 2, 'mirathi' => 3, 'urithi' => 3, 'wosia' => 3,
            'ardhi' => 2, 'hati' => 2, 'mgogoro' => 2, 'dhuluma' => 3, 'kudhulumiwa' => 3, 'nimedhulumiwa' => 3,
            'unyanyasaji' => 3, 'ubakaji' => 3, 'wizi' => 2, 'msaada wa kisheria' => 4, 'baraza la kata' => 3,
            'baraza la ardhi' => 3, 'mahari' => 2, 'kosa' => 1, 'faini' => 2, 'rushwa' => 3, 'takukuru' => 3,
            'mtuhumiwa' => 3, 'hatia' => 2, 'ushahidi' => 2, 'kifungo' => 3, 'fidia' => 2, 'kuhukumiwa' => 3,
            // English
            'law' => 3, 'legal' => 3, 'rights' => 2, 'constitution' => 3, 'court' => 3, 'judge' => 3, 'lawyer' =>
3,
            'advocate' => 3, 'case' => 2, 'arrest' => 3, 'arrested' => 3, 'bail' => 3, 'police' => 2, 'prison' =>
2,
            'contract' => 2, 'divorce' => 3, 'marriage' => 2, 'inheritance' => 3, 'will' => 1, 'land' => 2,
            'title deed' => 3, 'dispute' => 2, 'harassment' => 3, 'rape' => 3, 'theft' => 2, 'legal aid' => 4,
            'corruption' => 3, 'suspect' => 2, 'evidence' => 2, 'sentence' => 2, 'compensation' => 2, 'tenant' =>
2,
            'landlord' => 2, 'eviction' => 3, 'custody' => 3,
        ],
        'health' => [
            'afya' => 3, 'hospitali' => 3, 'zahanati' => 3, 'daktari' => 3, 'dawa' => 3, 'ugonjwa' => 3, 'mgonjwa'
=> 3,
            'homa' => 3, 'malaria' => 3, 'kikohozi' => 3, 'kuhara' => 3, 'kutapika' => 3, 'maumivu' => 2, 'mimba'
=> 3,
            'mjamzito' => 3, 'kujifungua' => 3, 'mtoto mchanga' => 3, 'chanjo' => 3, 'ukimwi' => 3, 'kifua kikuu'
=> 3,
            'kisukari' => 3, 'presha' => 3, 'shinikizo la damu' => 3, 'lishe' => 2, 'bima ya afya' => 3, 'nhif' =>
```

```
3,
    64              'chf' => 2, 'kipindupindu' => 3, 'dengue' => 3, 'saratani' => 3, 'kansa' => 3, 'jeraha' => 2, 'uzazi'
=> 2,
    65              'uzazi wa mpango' => 3, 'kondomu' => 2, 'msongo' => 2, 'akili' => 1, 'nyoka' => 2, 'sumu' => 2,
    66              'amezimia' => 4, 'kuzimia' => 4, 'nimezimia' => 4, 'hapumui' => 4, 'kupumua' => 3, 'degedege' => 4,
'anatokwa damu' => 4,
    67              'damu' => 2, 'ameanguka' => 3, 'ajali' => 2, 'majeraha' => 3, 'kuungua' => 3, 'amemeza' => 3, 'kifafa'
=> 3,
    68              'health' => 3, 'hospital' => 3, 'clinic' => 3, 'doctor' => 3, 'medicine' => 3, 'drug' => 2, 'disease'
=> 3,
    69              'sick' => 2, 'fever' => 3, 'cough' => 3, 'diarrhoea' => 3, 'diarrhea' => 3, 'vomiting' => 3, 'pain' =>
2,
    70              'pregnant' => 3, 'pregnancy' => 3, 'vaccine' => 3, 'hiv' => 3, 'aids' => 2, 'tuberculosis' => 3,
    71              'diabetes' => 3, 'blood pressure' => 3, 'nutrition' => 2, 'insurance' => 1, 'cholera' => 3, 'cancer' =>
3,
    72              'injury' => 2, 'family planning' => 3, 'mental' => 2, 'snake' => 2, 'poison' => 2, 'symptoms' => 3,
    73              'unconscious' => 4, 'collapsed' => 4, 'not breathing' => 4, 'breathing' => 3, 'bleeding' => 4, 'burn'
=> 3, 'burns' => 3,
    74              'seizure' => 4, 'convulsion' => 4, 'convulsions' => 4, 'fainted' => 4, 'swallowed' => 3, 'wound' => 3,
'first aid' => 4,
    75          ],
    76          'agriculture' => [
    77              'kilimo' => 3, 'mkulima' => 3, 'wakulima' => 3, 'shamba' => 3, 'mazao' => 3, 'mbegu' => 3, 'mbolea' =>
3,
    78              'mahindi' => 3, 'mpunga' => 3, 'maharage' => 3, 'mihogo' => 3, 'korosho' => 3, 'kahawa' => 3, 'pamba'
=> 3,
    79              'tumbaku' => 3, 'alizeti' => 3, 'ufuta' => 3, 'ndizi' => 2, 'nyanya' => 2, 'vitunguu' => 2, 'mvua' =>
2,
    80              'msimu' => 2, 'kupanda' => 2, 'kuvuna' => 3, 'mavuno' => 3, 'wadudu' => 3, 'viwavijeshi' => 3,
'magonjwa ya mimea' => 3,
    81              'mifugo' => 3, 'ng\'ombe' => 3, 'ngombe' => 3, 'mbuzi' => 3, 'kuku' => 3, 'kondoo' => 2, 'nguruwe' =>
2,
    82              'samaki' => 2, 'uvuvi' => 3, 'ufugaji' => 3, 'chanjo ya mifugo' => 3, 'umwagiliaji' => 3, 'bwana
shamba' => 3,
    83              'afisa ugani' => 3, 'tari' => 2, 'soko la mazao' => 3, 'ghala' => 2, 'bei ya mazao' => 3,
    84              'agriculture' => 3, 'farmer' => 3, 'farm' => 3, 'crop' => 3, 'crops' => 3, 'seed' => 3, 'seeds' => 3,
    85              'fertilizer' => 3, 'fertiliser' => 3, 'maize' => 3, 'rice' => 2, 'beans' => 3, 'cassava' => 3, 'cashew'
=> 3,
    86              'coffee' => 2, 'cotton' => 3, 'tobacco' => 3, 'sunflower' => 3, 'harvest' => 3, 'pest' => 3, 'pests' =>
3,
    87              'armyworm' => 3, 'livestock' => 3, 'cattle' => 3, 'cow' => 2, 'goat' => 3, 'chicken' => 3, 'poultry' =>
3,
    88              'fishing' => 3, 'irrigation' => 3, 'extension officer' => 3, 'planting season' => 3, 'rainfall' => 2,
    89          ],
    90          'education' => [
    91              'elimu' => 3, 'shule' => 3, 'mwanafunzi' => 3, 'wanafunzi' => 3, 'mwalimu' => 3, 'darasa' => 3,
'mtihani' => 3,
    92              'necta' => 3, 'kidato' => 3, 'sekondari' => 3, 'msingi' => 2, 'chuo' => 3, 'chuo kikuu' => 3, 'mkopo wa
elimu' => 3,
    93              'heslb' => 3, 'bodi ya mikopo' => 3, 'ada' => 2, 'matokeo' => 3, 'ufaulu' => 3, 'somo' => 2, 'masomo'
=> 2,
    94              'hisabati' => 3, 'fizikia' => 3, 'kemia' => 3, 'baiolojia' => 3, 'jiografia' => 3, 'historia' => 2,
    95              'kiingereza' => 2, 'kusoma' => 2, 'kuandika' => 2, 'ufundi' => 2, 'veta' => 3, 'tamisemi' => 2,
'scholarship' => 3,
    96              'education' => 3, 'school' => 3, 'student' => 3, 'students' => 3, 'teacher' => 3, 'class' => 2, 'exam'
=> 3,
    97              'exams' => 3, 'examination' => 3, 'form four' => 3, 'form six' => 3, 'secondary' => 3, 'primary' => 2,
    98              'university' => 3, 'college' => 3, 'student loan' => 3, 'loan board' => 3, 'fees' => 2, 'results' => 3,
    99              'mathematics' => 3, 'physics' => 3, 'chemistry' => 3, 'biology' => 3, 'geography' => 3, 'history' => 2,
   100              'homework' => 3, 'syllabus' => 3, 'vocational' => 3, 'explain' => 1, 'define' => 1,
   101          ],
   102          'government' => [
   103              'serikali' => 3, 'nida' => 3, 'kitambulisho' => 3, 'kitambulisho cha taifa' => 4, 'pasipoti' => 3,
'uhamiaji' => 3,
   104              'cheti cha kuzaliwa' => 4, 'rita' => 3, 'cheti cha kifo' => 3, 'leseni' => 2, 'brela' => 3, 'usajili'
=> 2,
   105              'mkurugenzi' => 2, 'halmashauri' => 3, 'mtendaji' => 3, 'diwani' => 3, 'mbunge' => 3, 'mkuu wa wilaya'
=> 3,
   106              'mkuu wa mkoa' => 3, 'wizara' => 3, 'waziri' => 3, 'rais' => 3, 'bunge' => 3, 'uchaguzi' => 3, 'kupiga
kura' => 3,
   107              'tanesco' => 3, 'luku' => 3, 'umeme' => 3, 'maji' => 2, 'dawasa' => 3, 'tcra' => 2, 'ofisi ya' => 1,
   108              'huduma za serikali' => 4, 'gepg' => 3, 'malipo ya serikali' => 3, 'kodi ya majengo' => 3, 'nssf' => 3,
   109              'psssf' => 3, 'pensheni' => 3, 'tasaf' => 3, 'e-government' => 3, 'tehama' => 1,
```

```
            'government' => 3, 'national id' => 4, 'passport' => 3, 'immigration' => 3, 'birth certificate' => 4,
            'death certificate' => 3, 'licence' => 2, 'license' => 2, 'registration' => 2, 'council' => 2, 'ward
executive' => 3,
            'councillor' => 3, 'member of parliament' => 3, 'district commissioner' => 3, 'regional commissioner'
=> 3,
            'ministry' => 3, 'minister' => 3, 'president' => 3, 'parliament' => 3, 'election' => 3, 'vote' => 3,
            'electricity' => 3, 'water' => 1, 'pension' => 3, 'social security' => 3, 'public service' => 2,
        ],
        'finance' => [
            'fedha' => 3, 'pesa' => 3, 'hela' => 3, 'shilingi' => 3, 'kodi' => 3, 'tra' => 3, 'tin' => 3, 'namba ya
tin' => 4,
            'vat' => 3, 'ushuru' => 3, 'benki' => 3, 'akaunti' => 3, 'mkopo' => 3, 'mikopo' => 3, 'riba' => 3,
'akiba' => 3,
            'kuweka akiba' => 3, 'm-pesa' => 3, 'mpesa' => 3, 'tigo pesa' => 3, 'airtel money' => 3, 'halopesa' =>
3,
            'mixx' => 2, 'yas' => 1, 'bima' => 2, 'uwekezaji' => 3, 'hisa' => 3, 'dse' => 3, 'bajeti' => 3, 'deni'
=> 3,
            'madeni' => 3, 'kutapeliwa' => 3, 'utapeli' => 3, 'matapeli' => 3, 'kiinua mgongo' => 3, 'mshahara' =>
2,
            'dola' => 2, 'kubadilisha fedha' => 3, 'sacco' => 3, 'saccos' => 3, 'vicoba' => 3, 'kodi ya mapato' =>
4,
            'money' => 3, 'cash' => 2, 'tax' => 3, 'taxes' => 3, 'bank' => 3, 'account' => 2, 'loan' => 3, 'loans'
=> 3,
            'interest' => 2, 'savings' => 3, 'mobile money' => 3, 'investment' => 3, 'shares' => 3, 'budget' => 3,
            'debt' => 3, 'scam' => 3, 'fraud' => 3, 'exchange rate' => 3, 'dollar' => 2, 'income tax' => 4,
'salary' => 2,
        ],
        'business' => [
            'biashara' => 3, 'mfanyabiashara' => 3, 'wafanyabiashara' => 3, 'kampuni' => 3, 'kusajili biashara' =>
4,
            'leseni ya biashara' => 4, 'mtaji' => 3, 'faida' => 3, 'hasara' => 2, 'wateja' => 3, 'mteja' => 2,
'soko' => 2,
            'bei' => 2, 'kuuza' => 3, 'kununua' => 2, 'duka' => 3, 'ujasiriamali' => 3, 'mjasiriamali' => 3,
'wajasiriamali' => 3,
            'sido' => 3, 'tbs' => 3, 'tfda' => 2, 'tmda' => 3, 'kuagiza' => 2, 'kusafirisha' => 2, 'uuzaji' => 2,
'masoko' => 3,
            'mpango wa biashara' => 4, 'machinga' => 3, 'bodaboda' => 2, 'kiwanda' => 3,
            'business' => 3, 'company' => 3, 'register a business' => 4, 'business license' => 4, 'capital' => 2,
            'profit' => 3, 'loss' => 1, 'customer' => 3, 'customers' => 3, 'market' => 2, 'price' => 2, 'sell' =>
3,
            'selling' => 3, 'shop' => 3, 'entrepreneur' => 3, 'entrepreneurship' => 3, 'startup' => 3, 'import' =>
2,
            'export' => 2, 'marketing' => 3, 'business plan' => 4, 'supplier' => 2, 'factory' => 2,
        ],
        'employment' => [
            'ajira' => 3, 'kazi' => 2, 'mwajiri' => 3, 'mwajiriwa' => 3, 'mfanyakazi' => 3, 'wafanyakazi' => 3,
            'kufukuzwa' => 3, 'kufukuzwa kazi' => 4, 'likizo' => 3, 'likizo ya uzazi' => 4, 'mkataba wa kazi' => 4,
            'mshahara' => 3, 'kima cha chini' => 3, 'saa za kazi' => 3, 'overtime' => 3, 'cv' => 3, 'wasifu' => 3,
            'usaili' => 3, 'nafasi za kazi' => 4, 'kutafuta kazi' => 3, 'chama cha wafanyakazi' => 3, 'cma' => 3,
            'tume ya usuluhishi' => 3, 'kustaafu' => 3, 'mafao' => 3, 'wakala wa ajira' => 3, 'ajira nje ya nchi'
=> 4,
            'employment' => 3, 'job' => 3, 'jobs' => 3, 'employer' => 3, 'employee' => 3, 'worker' => 3, 'fired' =>
3,
            'dismissed' => 3, 'dismissal' => 3, 'leave' => 2, 'maternity' => 3, 'employment contract' => 4, 'wage'
=> 3,
            'wages' => 3, 'minimum wage' => 4, 'working hours' => 3, 'resume' => 3, 'interview' => 3, 'vacancy' =>
3,
            'vacancies' => 3, 'job search' => 3, 'trade union' => 3, 'retirement' => 3, 'benefits' => 2,
'recruitment' => 3,
        ],
        'family' => [
            'familia' => 3, 'mke' => 2, 'mume' => 2, 'wazazi' => 3, 'mzazi' => 3, 'mtoto' => 2, 'watoto' => 2,
'malezi' => 3,
            'kulea' => 3, 'mahusiano' => 3, 'mpenzi' => 3, 'uchumba' => 3, 'harusi' => 3, 'ukatili wa kijinsia' =>
4,
            'ukatili' => 3, 'kupigwa' => 3, 'mume ananipiga' => 4, 'ndoa za utotoni' => 4, 'ukeketaji' => 4,
'yatima' => 3,
            'wazee' => 2, 'jamii' => 2, 'majirani' => 2, 'ugomvi' => 2, 'msaada wa kijamii' => 3, 'ustawi wa jamii'
=> 4,
            'dawati la jinsia' => 4, 'mimba za utotoni' => 4, 'vijana' => 2, 'msichana' => 2, 'mvulana' => 2,
            'family' => 3, 'wife' => 2, 'husband' => 2, 'parents' => 3, 'parent' => 3, 'child' => 2, 'children' =>
2,
            'parenting' => 3, 'relationship' => 3, 'boyfriend' => 3, 'girlfriend' => 3, 'wedding' => 3,
```

```
            'gender based violence' => 4, 'gbv' => 4, 'domestic violence' => 4, 'abuse' => 3, 'beaten' => 3,
            'child marriage' => 4, 'fgm' => 4, 'orphan' => 3, 'elderly' => 2, 'community' => 2, 'neighbours' => 2,
            'social welfare' => 4, 'gender desk' => 4, 'teen pregnancy' => 4, 'youth' => 2,
        ],
        'technology' => [
            'simu' => 2, 'intaneti' => 3, 'mtandao' => 2, 'kompyuta' => 3, 'laini' => 3, 'kusajili laini' => 4,
            'bando' => 3, 'vifurushi' => 3, 'whatsapp' => 3, 'facebook' => 3, 'instagram' => 3, 'tiktok' => 3,
            'email' => 2, 'barua pepe' => 2, 'nywila' => 3, 'password' => 3, 'akaunti imedukuliwa' => 4, 'udukuzi'
=> 4,
            'kudukuliwa' => 4, 'programu' => 2, 'app' => 2, 'apu' => 2, 'kompyuta mpakato' => 3, 'laptop' => 3,
            'tcra' => 3, 'vodacom' => 3, 'tigo' => 2, 'airtel' => 2, 'halotel' => 3, 'ttcl' => 3, 'zantel' => 3,
            'mtandao wa simu' => 3, 'wifi' => 3, 'data' => 1, 'kuchaji' => 2, 'betri' => 2, 'skrini' => 2, 'ai' =>
2,
            'phone' => 2, 'internet' => 3, 'computer' => 3, 'sim card' => 4, 'sim' => 2, 'bundle' => 3, 'bundles'
=> 3,
            'hacked' => 4, 'hacking' => 4, 'software' => 3, 'application' => 2, 'network' => 2, 'online' => 2,
            'website' => 3, 'coding' => 3, 'programming' => 3, 'charge' => 1, 'battery' => 2, 'screen' => 2,
        ],
        'transport' => [
            'usafiri' => 3, 'daladala' => 3, 'basi' => 3, 'mabasi' => 3, 'bodaboda' => 3, 'bajaji' => 3, 'teksi' =>
3,
            'gari' => 2, 'leseni ya udereva' => 4, 'udereva' => 3, 'ajali' => 3, 'barabara' => 2, 'trafiki' => 3,
            'usalama barabarani' => 4, 'faini ya trafiki' => 4, 'bima ya gari' => 3, 'latra' => 3, 'sumatra' => 2,
            'tanroads' => 3, 'treni' => 3, 'sgr' => 3, 'reli' => 3, 'ndege' => 3, 'uwanja wa ndege' => 3, 'meli' =>
3,
            'kivuko' => 3, 'bandari' => 2, 'mwendokasi' => 3, 'dart' => 2, 'nauli' => 3, 'tiketi' => 2, 'kuhamisha
umiliki wa gari' => 4,
            'transport' => 3, 'bus' => 3, 'buses' => 3, 'motorcycle' => 3, 'taxi' => 3, 'car' => 2, 'driving
licence' => 4,
            'driving license' => 4, 'driver' => 2, 'accident' => 3, 'road' => 2, 'traffic' => 3, 'road safety' =>
4,
            'traffic fine' => 4, 'car insurance' => 3, 'train' => 3, 'railway' => 3, 'flight' => 3, 'airport' => 3,
            'ferry' => 3, 'port' => 1, 'fare' => 3, 'ticket' => 2, 'vehicle' => 2, 'registration card' => 3,
        ],
    ];

    /** Patterns that indicate a life-threatening or urgent situation. */
    private const EMERGENCY = [
        'dharura', 'emergency', 'ajali', 'accident', 'moto', 'fire', 'anakufa', 'dying', 'amezimia', 'unconscious',
        'kujiua', 'suicide', 'nataka kufa', 'kill myself', 'ananipiga sasa', 'anataka kuniua', 'damu nyingi',
'bleeding',
        'sumu', 'poison', 'nyoka ameniuma', 'snake bite', 'kupumua' , 'breathe', 'mafuriko', 'flood', 'amepotea',
'missing child',
        'mtoto amepotea', 'kutekwa', 'kidnapped', 'wezi wameingia', 'robbery', 'haraka sana', 'help me now',
    ];

    /**
     * @return array{category:string, confidence:float, scores:array<string,int>, is_emergency:bool}
     */
    public function classify(string $text): array
    {
        $normalized = $this->normalize($text);
        $words = array_filter(explode(' ', $normalized));
        $wordSet = array_flip($words);

        $scores = [];
        foreach (self::KEYWORDS as $category => $keywords) {
            $score = 0;
            foreach ($keywords as $keyword => $weight) {
                if (str_contains($keyword, ' ') || str_contains($keyword, '-') || str_contains($keyword, "'")) {
                    if (str_contains($normalized, $keyword)) {
                        $score += $weight + 1; // phrases are strong signals
                    }
                } elseif (isset($wordSet[$keyword])) {
                    $score += $weight;
                }
            }
            if ($score > 0) {
                $scores[$category] = $score;
            }
        }

        arsort($scores);
```

```php
        $top = array_key_first($scores);
        $topScore = $top ? $scores[$top] : 0;
        $total = array_sum($scores) ?: 1;

        $category = ($top && $topScore >= 2) ? $top : self::GENERAL;
        $confidence = $top ? round($topScore / $total, 2) : 0.0;

        return [
            'category' => $category,
            'confidence' => $confidence,
            'scores' => $scores,
            'is_emergency' => $this->isEmergency($normalized),
        ];
    }

    public function isEmergency(string $normalizedText): bool
    {
        foreach (self::EMERGENCY as $needle) {
            if (str_contains($normalizedText, $needle)) {
                return true;
            }
        }

        return false;
    }

    public static function label(string $category, string $language = 'sw'): string
    {
        $labels = self::CATEGORIES[$category] ?? self::CATEGORIES[self::GENERAL];

        return $labels[$language === 'en' ? 'en' : 'sw'];
    }

    public static function keys(): array
    {
        return array_keys(self::CATEGORIES);
    }

    private function normalize(string $text): string
    {
        $text = Str::lower($text);
        $text = preg_replace('/[^\p{L}\p{N}\'\- ]+/u', ' ', $text);
        $text = preg_replace('/\s+/', ' ', $text);

        return ' ' . trim($text) . ' ';
    }
}
```

48 **app/Support/Phone.php** 55 lines

```php
<?php

namespace App\Support;

class Phone
{
    /**
     * Normalise a phone number to E.164, assuming Tanzania (+255) when no
     * country code is given. Returns null when the input cannot be a number.
     */
    public static function normalize(?string $input): ?string
    {
        if ($input === null) {
            return null;
        }
        $raw = preg_replace('/[^\d+]/', '', trim($input));
        if ($raw === '' || $raw === '+') {
            return null;
        }

        if (str_starts_with($raw, '+')) {
            $digits = substr($raw, 1);
        } elseif (str_starts_with($raw, '00')) {
            $digits = substr($raw, 2);
        } elseif (str_starts_with($raw, '255')) {
            $digits = $raw;
        } elseif (str_starts_with($raw, '0')) {
            $digits = '255' . substr($raw, 1);
        } elseif (strlen($raw) === 9 && in_array($raw[0], ['6', '7'], true)) {
            $digits = '255' . $raw;
        } else {
            $digits = $raw;
        }

        if (! preg_match('/^\d{10,15}$/', $digits)) {
            return null;
        }

        return '+' . $digits;
    }

    public static function isTanzanian(string $e164): bool
    {
        return (bool) preg_match('/^\+255[67]\d{8}$/', $e164);
    }

    public static function mask(?string $e164): string
    {
        if (! $e164 || strlen($e164) < 7) {
            return '****';
        }

        return substr($e164, 0, 4) . ' *** ' . substr($e164, -3);
    }
}
```

49 app/Support/Settings.php

222 lines

```php
<?php

namespace App\Support;

use App\Models\SystemSetting;
use Illuminate\Support\Facades\Cache;

/**
 * Typed, cached, whitelisted access to system_settings.
 *
 * Only keys declared in schema() can be stored. The admin settings form,
 * the validation rules and the defaults are all driven by this schema so
 * there is a single source of truth.
 */
class Settings
{
    private const CACHE_KEY = 'huru.settings.all';

    /**
     * @return array<string,
array{group:string,label:string,type:string,default:mixed,rules:string,hint?:string,options?:array}>
     */
    public static function schema(): array
    {
        return [
            // ---- Branding ------------------------------------------------
            'app_name' => [
                'group' => 'Branding', 'label' => 'Service name', 'type' => 'text',
                'default' => 'Huru SMS', 'rules' => 'required|string|max:40',
                'hint' => 'Shown in replies, the web chat and SMS help text.',
            ],
            'sms_keyword' => [
                'group' => 'Branding', 'label' => 'SMS keyword', 'type' => 'text',
                'default' => 'HURU', 'rules' => 'required|alpha|max:15',
                'hint' => 'Word citizens send first. Must match the Africa\'s Talking keyword.',
            ],
            'sms_shortcode' => [
                'group' => 'Branding', 'label' => 'SMS shortcode', 'type' => 'text',
                'default' => '15054', 'rules' => 'required|string|max:10',
            ],
            'signature_sw' => [
                'group' => 'Branding', 'label' => 'Reply sign-off (Swahili)', 'type' => 'text',
                'default' => '', 'rules' => 'nullable|string|max:120',
                'hint' => 'Optional short line appended to every reply. Leave empty for none.',
            ],
            'signature_en' => [
                'group' => 'Branding', 'label' => 'Reply sign-off (English)', 'type' => 'text',
                'default' => '', 'rules' => 'nullable|string|max:120',
            ],

            // ---- Engine --------------------------------------------------
            'ai_enabled' => [
                'group' => 'Engine', 'label' => 'Engine enabled', 'type' => 'boolean',
                'default' => '1', 'rules' => 'required|in:0,1',
                'hint' => 'Turn off to pause replies during maintenance or when budget is exhausted.',
            ],
            'ai_maintenance_message_sw' => [
                'group' => 'Engine', 'label' => 'Maintenance message (Swahili)', 'type' => 'textarea',
                'default' => 'Huduma inafanyiwa matengenezo kwa muda mfupi. Tafadhali jaribu tena baadaye.',
                'rules' => 'required|string|max:300',
            ],
            'ai_maintenance_message_en' => [
                'group' => 'Engine', 'label' => 'Maintenance message (English)', 'type' => 'textarea',
                'default' => 'The service is under brief maintenance. Please try again later.',
                'rules' => 'required|string|max:300',
            ],
            'ai_model' => [
                'group' => 'Engine', 'label' => 'Gemini model', 'type' => 'text',
                'default' => 'gemini-flash-lite-latest', 'rules' => 'required|string|max:80',
                'hint' => 'Any generateContent-capable Gemini model id.',
            ],
```

```
            'ai_temperature' => [
                'group' => 'Engine', 'label' => 'Temperature', 'type' => 'number',
                'default' => '0.4', 'rules' => 'required|numeric|min:0|max:2',
                'hint' => 'Lower is more factual. 0.3 to 0.5 is recommended for public guidance.',
            ],
            'ai_max_tokens' => [
                'group' => 'Engine', 'label' => 'Max output tokens', 'type' => 'number',
                'default' => '2048', 'rules' => 'required|integer|min:64|max:8192',
            ],
            'history_turns' => [
                'group' => 'Engine', 'label' => 'Conversation memory (turns)', 'type' => 'number',
                'default' => '4', 'rules' => 'required|integer|min:0|max:12',
                'hint' => 'How many previous question/answer pairs are given to the engine for follow-up
questions.',
            ],
            'knowledge_matches' => [
                'group' => 'Engine', 'label' => 'Knowledge entries per reply', 'type' => 'number',
                'default' => '2', 'rules' => 'required|integer|min:0|max:5',
            ],

            // ---- Channels -----------------------------------------------
            'primary_language' => [
                'group' => 'Channels', 'label' => 'Language policy', 'type' => 'select',
                'default' => 'auto', 'rules' => 'required|in:auto,sw,en',
                'options' => ['auto' => 'Detect automatically', 'sw' => 'Always Swahili', 'en' => 'Always
English'],
            ],
            'sms_max_words' => [
                'group' => 'Channels', 'label' => 'SMS reply length (words)', 'type' => 'number',
                'default' => '120', 'rules' => 'required|integer|min:30|max:400',
                'hint' => 'Roughly 160 characters per SMS segment. 120 words is about 5 segments.',
            ],
            'web_max_words' => [
                'group' => 'Channels', 'label' => 'Web reply length (words)', 'type' => 'number',
                'default' => '250', 'rules' => 'required|integer|min:50|max:800',
            ],
            'web_chat_limit' => [
                'group' => 'Channels', 'label' => 'Web history shown', 'type' => 'number',
                'default' => '20', 'rules' => 'required|integer|min:2|max:200',
            ],
            'otp_enabled' => [
                'group' => 'Channels', 'label' => 'Web login verification (OTP)', 'type' => 'boolean',
                'default' => '1', 'rules' => 'required|in:0,1',
                'hint' => 'Sends a one-time code by SMS before a phone number can open its chat history.',
            ],
            'otp_ttl_minutes' => [
                'group' => 'Channels', 'label' => 'OTP validity (minutes)', 'type' => 'number',
                'default' => '5', 'rules' => 'required|integer|min:1|max:30',
            ],

            // ---- Safety -------------------------------------------------
            'abuse_strike_limit' => [
                'group' => 'Safety', 'label' => 'Strikes before ban', 'type' => 'number',
                'default' => '3', 'rules' => 'required|integer|min:1|max:10',
            ],
            'rate_limit_per_minute' => [
                'group' => 'Safety', 'label' => 'Questions per minute per user', 'type' => 'number',
                'default' => '6', 'rules' => 'required|integer|min:1|max:60',
            ],
            'contact_email' => [
                'group' => 'Safety', 'label' => 'Operator contact email', 'type' => 'text',
                'default' => '', 'rules' => 'nullable|email|max:120',
                'hint' => 'Receives landing page enquiries.',
            ],
        ];
    }

    public static function groups(): array
    {
        $groups = [];
        foreach (self::schema() as $key => $def) {
            $groups[$def['group']][$key] = $def;
        }
```

```
142
143         return $groups;
144     }
145
146     public static function isKnown(string $key): bool
147     {
148         return array_key_exists($key, self::schema());
149     }
150
151     /** @return array<string,string|null> */
152     public static function all(): array
153     {
154         $stored = Cache::remember(self::CACHE_KEY, 3600, function () {
155             try {
156                 return SystemSetting::query()->pluck('value', 'key')->all();
157             } catch (\Throwable) {
158                 return [];
159             }
160         });
161
162         $out = [];
163         foreach (self::schema() as $key => $def) {
164             $out[$key] = array_key_exists($key, $stored) && $stored[$key] !== null
165                 ? $stored[$key]
166                 : $def['default'];
167         }
168
169         return $out;
170     }
171
172     public static function get(string $key, mixed $default = null): mixed
173     {
174         $all = self::all();
175         if (array_key_exists($key, $all)) {
176             return $all[$key];
177         }
178
179         return $default ?? (self::schema()[$key]['default'] ?? null);
180     }
181
182     public static function bool(string $key): bool
183     {
184         return in_array((string) self::get($key), ['1', 'true', 'on', 'yes'], true);
185     }
186
187     public static function int(string $key): int
188     {
189         return (int) self::get($key);
190     }
191
192     public static function float(string $key): float
193     {
194         return (float) self::get($key);
195     }
196
197     public static function set(string $key, mixed $value): void
198     {
199         if (! self::isKnown($key)) {
200             throw new \InvalidArgumentException("Unknown setting [{$key}]");
201         }
202
203         SystemSetting::query()->updateOrCreate(['key' => $key], ['value' => $value === null ? null : (string)
$value]);
204         self::flush();
205     }
206
207     public static function flush(): void
208     {
209         Cache::forget(self::CACHE_KEY);
210     }
211
212     /** Validation rules for the whole schema, used by the admin form. */
213     public static function rules(): array
```

```
    {
        $rules = [];
        foreach (self::schema() as $key => $def) {
            $rules[$key] = $def['rules'];
        }

        return $rules;
    }
}
```

50 artisan

18 lines

```
#!/usr/bin/env php
<?php

use Illuminate\Foundation\Application;
use Symfony\Component\Console\Input\ArgvInput;

define('LARAVEL_START', microtime(true));

// Register the Composer autoloader...
require __DIR__.'/vendor/autoload.php';

// Bootstrap Laravel and handle the command...
/** @var Application $app */
$app = require_once __DIR__.'/bootstrap/app.php';

$status = $app->handleCommand(new ArgvInput);

exit($status);
```

51 bootstrap/app.php

25 lines

```php
<?php

use App\Http\Middleware\EnsureAdmin;
use App\Http\Middleware\VerifySmsWebhook;
use Illuminate\Foundation\Application;
use Illuminate\Foundation\Configuration\Exceptions;
use Illuminate\Foundation\Configuration\Middleware;

return Application::configure(basePath: dirname(__DIR__))
    ->withRouting(
        web: __DIR__.'/../routes/web.php',
        api: __DIR__.'/../routes/api.php',
        commands: __DIR__.'/../routes/console.php',
        health: '/up',
    )
    ->withMiddleware(function (Middleware $middleware): void {
        $middleware->alias([
            'admin' => EnsureAdmin::class,
            'sms.webhook' => VerifySmsWebhook::class,
        ]);
        $middleware->redirectGuestsTo(fn () => route('admin.login'));
    })
    ->withExceptions(function (Exceptions $exceptions): void {
        //
    })->create();
```

52 bootstrap/providers.php

5 lines

```php
<?php

return [
    App\Providers\AppServiceProvider::class,
];
```

53 **composer.json** 88 lines

```
{
    "$schema": "https://getcomposer.org/schema.json",
    "name": "hurudigital/huru",
    "type": "project",
    "description": "Huru SMS: everyday question answering for Tanzanians over SMS and web.",
    "keywords": ["laravel", "framework"],
    "license": "MIT",
    "require": {
        "php": "^8.2",
        "composer/ca-bundle": "^1.5",
        "laravel/framework": "^12.0",
        "laravel/sanctum": "^4.0",
        "laravel/tinker": "^2.10.1"
    },
    "require-dev": {
        "fakerphp/faker": "^1.23",
        "laravel/pail": "^1.2.2",
        "laravel/pint": "^1.24",
        "laravel/sail": "^1.41",
        "mockery/mockery": "^1.6",
        "nunomaduro/collision": "^8.6",
        "phpunit/phpunit": "^11.5.3"
    },
    "autoload": {
        "psr-4": {
            "App\\": "app/",
            "Database\\Factories\\": "database/factories/",
            "Database\\Seeders\\": "database/seeders/"
        }
    },
    "autoload-dev": {
        "psr-4": {
            "Tests\\": "tests/"
        }
    },
    "scripts": {
        "setup": [
            "composer install",
            "@php -r \"file_exists('.env') || copy('.env.example', '.env');\"",
            "@php artisan key:generate",
            "@php artisan migrate --force",
            "npm install",
            "npm run build"
        ],
        "dev": [
            "Composer\\Config::disableProcessTimeout",
            "npx concurrently -c \"#93c5fd,#c4b5fd,#fb7185,#fdba74\" \"php artisan serve\" \"php artisan
queue:listen --tries=1 --timeout=0\" \"php artisan pail --timeout=0\" \"npm run dev\" --names=server,queue,logs,vite --
kill-others"
        ],
        "test": [
            "@php artisan config:clear --ansi",
            "@php artisan test"
        ],
        "post-autoload-dump": [
            "Illuminate\\Foundation\\ComposerScripts::postAutoloadDump",
            "@php artisan package:discover --ansi"
        ],
        "post-update-cmd": [
            "@php artisan vendor:publish --tag=laravel-assets --ansi --force"
        ],
        "post-root-package-install": [
            "@php -r \"file_exists('.env') || copy('.env.example', '.env');\""
        ],
        "post-create-project-cmd": [
            "@php artisan key:generate --ansi",
            "@php -r \"file_exists('database/database.sqlite') || touch('database/database.sqlite');\"",
            "@php artisan migrate --graceful --ansi"
        ],
        "pre-package-uninstall": [
            "Illuminate\\Foundation\\ComposerScripts::prePackageUninstall"
```

```
        ]
    },
    "extra": {
        "laravel": {
            "dont-discover": []
        }
    },
    "config": {
        "optimize-autoloader": true,
        "preferred-install": "dist",
        "sort-packages": true,
        "allow-plugins": {
            "pestphp/pest-plugin": true,
            "php-http/discovery": true
        }
    },
    "minimum-stability": "stable",
    "prefer-stable": true
}
```

54 config/services.php

49 lines

```php
<?php

return [

    /*
    |--------------------------------------------------------------------------
    | Third Party Services
    |--------------------------------------------------------------------------
    */

    'postmark' => [
        'key' => env('POSTMARK_API_KEY'),
    ],

    'resend' => [
        'key' => env('RESEND_API_KEY'),
    ],

    'ses' => [
        'key' => env('AWS_ACCESS_KEY_ID'),
        'secret' => env('AWS_SECRET_ACCESS_KEY'),
        'region' => env('AWS_DEFAULT_REGION', 'us-east-1'),
    ],

    'slack' => [
        'notifications' => [
            'bot_user_oauth_token' => env('SLACK_BOT_USER_OAUTH_TOKEN'),
            'channel' => env('SLACK_BOT_USER_DEFAULT_CHANNEL'),
        ],
    ],

    // Google Gemini (model is chosen in the admin settings)
    'gemini' => [
        'key' => env('GEMINI_API_KEY'),
        'url' => env('GEMINI_URL', 'https://generativelanguage.googleapis.com/v1beta/models'),
        'timeout' => env('GEMINI_TIMEOUT', 30),
    ],

    // Africa's Talking SMS
    'at' => [
        'username' => env('AT_USERNAME'),
        'api_key' => env('AT_API_KEY'),
        'from' => env('AT_FROM'),
        'webhook_secret' => env('AT_WEBHOOK_SECRET'),
        // When true, inbound messages without the keyword are ignored (shared short codes).
        'require_keyword' => env('AT_REQUIRE_KEYWORD', false),
    ],

];
```

55 database/factories/UserFactory.php

40 lines

```php
<?php

namespace Database\Factories;

use App\Models\User;
use Illuminate\Database\Eloquent\Factories\Factory;
use Illuminate\Support\Facades\Hash;
use Illuminate\Support\Str;

/**
 * @extends Factory<User>
 */
class UserFactory extends Factory
{
    protected static ?string $password;

    public function definition(): array
    {
        return [
            'name' => fake()->name(),
            'phone_number' => '+2557' . fake()->unique()->numerify('########'),
            'email' => null,
            'password' => null,
            'role' => User::ROLE_USER,
            'is_banned' => false,
            'abuse_count' => 0,
            'opted_out' => false,
            'remember_token' => Str::random(10),
        ];
    }

    public function admin(): static
    {
        return $this->state(fn () => [
            'email' => fake()->unique()->safeEmail(),
            'password' => static::$password ??= Hash::make('password'),
            'role' => User::ROLE_ADMIN,
        ]);
    }
}
```

56 database/migrations/0001_01_01_000000_create_users_table.php

54 lines

```php
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    public function up(): void
    {
        Schema::create('users', function (Blueprint $table) {
            $table->id();
            $table->string('phone_number', 20)->unique()->nullable();
            $table->string('name')->nullable();
            $table->string('email')->unique()->nullable();
            $table->string('password')->nullable();
            $table->string('role', 20)->default('user')->index();
            $table->string('preferred_language', 5)->nullable();
            $table->string('region', 40)->nullable()->index();
            $table->boolean('is_banned')->default(false);
            $table->unsignedSmallInteger('abuse_count')->default(0);
            $table->boolean('opted_out')->default(false);
            $table->string('otp_hash')->nullable();
            $table->timestamp('otp_expires_at')->nullable();
            $table->unsignedTinyInteger('otp_attempts')->default(0);
            $table->timestamp('last_seen_at')->nullable();
            $table->timestamp('email_verified_at')->nullable();
            $table->rememberToken();
            $table->timestamps();
        });

        Schema::create('password_reset_tokens', function (Blueprint $table) {
            $table->string('email')->primary();
            $table->string('token');
            $table->timestamp('created_at')->nullable();
        });

        Schema::create('sessions', function (Blueprint $table) {
            $table->string('id')->primary();
            $table->foreignId('user_id')->nullable()->index();
            $table->string('ip_address', 45)->nullable();
            $table->text('user_agent')->nullable();
            $table->longText('payload');
            $table->integer('last_activity')->index();
        });
    }

    public function down(): void
    {
        Schema::dropIfExists('sessions');
        Schema::dropIfExists('password_reset_tokens');
        Schema::dropIfExists('users');
    }
};
```

57 database/migrations/0001_01_01_000001_create_cache_table.php

35 lines

```php
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('cache', function (Blueprint $table) {
            $table->string('key')->primary();
            $table->mediumText('value');
            $table->integer('expiration')->index();
        });

        Schema::create('cache_locks', function (Blueprint $table) {
            $table->string('key')->primary();
            $table->string('owner');
            $table->integer('expiration')->index();
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('cache');
        Schema::dropIfExists('cache_locks');
    }
};
```

58 database/migrations/0001_01_01_000002_create_jobs_table.php

57 lines

```php
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('jobs', function (Blueprint $table) {
            $table->id();
            $table->string('queue')->index();
            $table->longText('payload');
            $table->unsignedTinyInteger('attempts');
            $table->unsignedInteger('reserved_at')->nullable();
            $table->unsignedInteger('available_at');
            $table->unsignedInteger('created_at');
        });

        Schema::create('job_batches', function (Blueprint $table) {
            $table->string('id')->primary();
            $table->string('name');
            $table->integer('total_jobs');
            $table->integer('pending_jobs');
            $table->integer('failed_jobs');
            $table->longText('failed_job_ids');
            $table->mediumText('options')->nullable();
            $table->integer('cancelled_at')->nullable();
            $table->integer('created_at');
            $table->integer('finished_at')->nullable();
        });

        Schema::create('failed_jobs', function (Blueprint $table) {
            $table->id();
            $table->string('uuid')->unique();
            $table->text('connection');
            $table->text('queue');
            $table->longText('payload');
            $table->longText('exception');
            $table->timestamp('failed_at')->useCurrent();
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('jobs');
        Schema::dropIfExists('job_batches');
        Schema::dropIfExists('failed_jobs');
    }
};
```

59 database/migrations/2026_10_07_000001_create_messages_and_logs_tables.php 58 lines

```php
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    public function up(): void
    {
        Schema::create('messages', function (Blueprint $table) {
            $table->id();
            $table->foreignId('user_id')->constrained()->cascadeOnDelete();
            $table->string('direction', 10); // inbound | outbound
            $table->string('channel', 10)->default('sms'); // sms | web
            $table->text('content');
            $table->string('language', 5)->nullable();
            $table->string('category', 30)->nullable()->index();
            $table->timestamps();

            $table->index(['user_id', 'created_at']);
            $table->index(['channel', 'created_at']);
        });

        Schema::create('ai_logs', function (Blueprint $table) {
            $table->id();
            $table->foreignId('message_id')->constrained()->cascadeOnDelete();
            $table->string('model', 80);
            $table->string('category', 30)->nullable();
            $table->string('status', 20)->default('ok');
            $table->longText('prompt');
            $table->text('response');
            $table->unsignedInteger('prompt_tokens')->default(0);
            $table->unsignedInteger('completion_tokens')->default(0);
            $table->unsignedInteger('total_tokens')->default(0);
            $table->unsignedInteger('latency_ms')->default(0);
            $table->timestamps();
        });

        Schema::create('feedback', function (Blueprint $table) {
            $table->id();
            $table->foreignId('message_id')->constrained()->cascadeOnDelete();
            $table->foreignId('user_id')->constrained()->cascadeOnDelete();
            $table->tinyInteger('rating'); // 1 helpful, -1 not helpful
            $table->string('comment', 500)->nullable();
            $table->timestamps();

            $table->unique(['message_id', 'user_id']);
        });
    }

    public function down(): void
    {
        Schema::dropIfExists('feedback');
        Schema::dropIfExists('ai_logs');
        Schema::dropIfExists('messages');
    }
};
```

60 database/migrations/2026_10_07_000002_create_knowledge_and_config_tables.php

87 lines

```php
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    public function up(): void
    {
        Schema::create('knowledge_entries', function (Blueprint $table) {
            $table->id();
            $table->string('title');
            $table->longText('content');
            $table->text('summary')->nullable();
            $table->string('category', 30)->default('general')->index();
            $table->json('keywords')->nullable();
            $table->string('language', 5)->default('sw')->index();
            $table->string('source')->nullable();
            $table->boolean('is_active')->default(true);
            $table->timestamps();
        });

        Schema::create('prompt_templates', function (Blueprint $table) {
            $table->id();
            $table->string('name')->unique();
            $table->string('category', 30)->default('general');
            $table->string('language', 5)->default('sw');
            $table->text('template');
            $table->boolean('is_active')->default(true);
            $table->timestamps();

            $table->index(['category', 'language', 'is_active']);
        });

        Schema::create('system_settings', function (Blueprint $table) {
            $table->id();
            $table->string('key')->unique();
            $table->text('value')->nullable();
            $table->timestamps();
        });

        Schema::create('reference_contacts', function (Blueprint $table) {
            $table->id();
            $table->string('name');
            $table->string('category', 30)->index();
            $table->string('phone', 60)->nullable();
            $table->string('alt_phone', 60)->nullable();
            $table->string('email')->nullable();
            $table->string('website')->nullable();
            $table->text('description_sw')->nullable();
            $table->text('description_en')->nullable();
            $table->boolean('is_emergency')->default(false);
            $table->boolean('is_active')->default(true);
            $table->timestamp('verified_at')->nullable();
            $table->unsignedSmallInteger('sort_order')->default(100);
            $table->timestamps();
        });

        Schema::create('local_resources', function (Blueprint $table) {
            $table->id();
            $table->string('name');
            $table->string('category', 30)->default('other');
            $table->string('region', 40)->nullable();
            $table->string('district', 40)->nullable();
            $table->string('ward', 60)->nullable();
            $table->text('location')->nullable();
            $table->string('phone', 60)->nullable();
            $table->string('email')->nullable();
            $table->string('source')->nullable();
            $table->boolean('is_active')->default(true);
```

```
            $table->timestamps();

            $table->index(['region', 'district']);
            $table->index(['category', 'region']);
        });
    }

    public function down(): void
    {
        Schema::dropIfExists('local_resources');
        Schema::dropIfExists('reference_contacts');
        Schema::dropIfExists('system_settings');
        Schema::dropIfExists('prompt_templates');
        Schema::dropIfExists('knowledge_entries');
    }
};
```

61 database/migrations/2026_10_07_000003_create_community_tables.php

76 lines

```php
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    public function up(): void
    {
        Schema::create('community_threads', function (Blueprint $table) {
            $table->id();
            $table->string('title');
            $table->string('slug')->unique();
            $table->text('description')->nullable();
            $table->foreignId('creator_id')->nullable()->constrained('users')->nullOnDelete();
            $table->boolean('is_private')->default(false);
            $table->boolean('is_system')->default(false);
            $table->timestamps();
        });

        Schema::create('community_members', function (Blueprint $table) {
            $table->id();
            $table->foreignId('community_thread_id')->constrained()->cascadeOnDelete();
            $table->foreignId('user_id')->constrained()->cascadeOnDelete();
            $table->string('role', 20)->default('member');
            $table->timestamp('last_read_at')->nullable();
            $table->timestamp('joined_at')->useCurrent();
            $table->timestamps();

            $table->unique(['community_thread_id', 'user_id']);
        });

        Schema::create('community_posts', function (Blueprint $table) {
            $table->id();
            $table->foreignId('community_thread_id')->constrained()->cascadeOnDelete();
            $table->foreignId('parent_id')->nullable()->constrained('community_posts')->cascadeOnDelete();
            $table->foreignId('user_id')->constrained()->cascadeOnDelete();
            $table->text('content');
            $table->boolean('is_approved')->default(true);
            $table->boolean('is_pinned')->default(false);
            $table->timestamps();
        });

        Schema::create('community_reactions', function (Blueprint $table) {
            $table->id();
            $table->foreignId('community_post_id')->constrained()->cascadeOnDelete();
            $table->foreignId('user_id')->constrained()->cascadeOnDelete();
            $table->string('type', 20);
            $table->timestamps();

            $table->unique(['community_post_id', 'user_id', 'type']);
        });

        Schema::create('community_invites', function (Blueprint $table) {
            $table->id();
            $table->foreignId('community_thread_id')->constrained()->cascadeOnDelete();
            $table->foreignId('inviter_id')->constrained('users')->cascadeOnDelete();
            $table->foreignId('invitee_id')->nullable()->constrained('users')->cascadeOnDelete();
            $table->string('email')->nullable();
            $table->string('token')->unique();
            $table->string('status', 20)->default('pending');
            $table->timestamp('expires_at')->nullable();
            $table->timestamps();
        });
    }

    public function down(): void
    {
        Schema::dropIfExists('community_invites');
        Schema::dropIfExists('community_reactions');
```

```
        Schema::dropIfExists('community_posts');
        Schema::dropIfExists('community_members');
        Schema::dropIfExists('community_threads');
    }
};
```

62 database/seeders/AdminUserSeeder.php

44 lines

```php
<?php

namespace Database\Seeders;

use App\Models\User;
use Illuminate\Database\Seeder;
use Illuminate\Support\Facades\Hash;
use Illuminate\Support\Str;

class AdminUserSeeder extends Seeder
{
    public function run(): void
    {
        $email = env('ADMIN_EMAIL', 'admin@huru.local');
        $password = env('ADMIN_PASSWORD');
        $generated = false;

        if (! $password) {
            $password = Str::password(14, symbols: false);
            $generated = true;
        }

        $admin = User::query()->where('email', $email)->first();

        if (! $admin) {
            User::query()->create([
                'name' => env('ADMIN_NAME', 'Huru SMS Admin'),
                'email' => $email,
                'password' => Hash::make($password),
                'role' => User::ROLE_ADMIN,
                'preferred_language' => 'en',
            ]);
            $this->command?->info("Admin created: {$email}");
            if ($generated) {
                $this->command?->warn("Generated admin password (set ADMIN_PASSWORD in .env to choose your own): {$password}");
            }
        } else {
            if ($admin->role !== User::ROLE_ADMIN) {
                $admin->forceFill(['role' => User::ROLE_ADMIN])->save();
            }
            $this->command?->info("Admin already exists: {$email}");
        }
    }
}
```

63 database/seeders/CommunitySeeder.php

45 lines

```php
<?php

namespace Database\Seeders;

use App\Models\CommunityThread;
use Illuminate\Database\Seeder;

class CommunitySeeder extends Seeder
{
    public function run(): void
    {
        CommunityThread::query()->updateOrCreate(
            ['slug' => 'general-advice'],
            [
                'title' => 'Maoni na Ushauri wa Jumla',
                'description' => 'Mahali rasmi pa maoni, ushauri na uzoefu wako. Maoni yaliyothibitishwa huonekana kwenye ukurasa wa mwanzo.',
                'is_system' => true,
                'is_private' => false,
            ]
        );

        CommunityThread::query()->updateOrCreate(
            ['slug' => 'announcements'],
            [
                'title' => 'Matangazo Rasmi',
                'description' => 'Taarifa muhimu kutoka kwa timu ya Huru SMS.',
                'is_system' => true,
                'is_private' => false,
            ]
        );

        foreach ([
            ['sheria-na-haki', 'Sheria na Haki', 'Jadili maswali ya sheria, haki na taratibu za mahakama na ofisi za serikali.'],
            ['kilimo-na-mifugo', 'Kilimo na Mifugo', 'Wakulima na wafugaji wakishirikiana uzoefu, bei na mbinu bora.'],
            ['afya-ya-jamii', 'Afya ya Jamii', 'Elimu ya afya, lishe na huduma za afya zilizo karibu.'],
            ['biashara-na-ajira', 'Biashara na Ajira', 'Fursa, ujasiriamali, nafasi za kazi na ushauri wa kifedha.'],
            ['wanafunzi', 'Wanafunzi na Walimu', 'Masomo, mitihani, mikopo ya HESLB na vyuo.'],
        ] as [$slug, $title, $desc]) {
            CommunityThread::query()->updateOrCreate(
                ['slug' => $slug],
                ['title' => $title, 'description' => $desc, 'is_system' => true, 'is_private' => false]
            );
        }
    }
}
```

64 database/seeders/DatabaseSeeder.php

21 lines

```php
<?php

namespace Database\Seeders;

use Illuminate\Database\Seeder;

class DatabaseSeeder extends Seeder
{
    public function run(): void
    {
        $this->call([
            SettingsSeeder::class,
            AdminUserSeeder::class,
            PromptTemplateSeeder::class,
            KnowledgeSeeder::class,
            ReferenceContactSeeder::class,
            LocalResourceSeeder::class,
            CommunitySeeder::class,
        ]);
    }
}
```

65 database/seeders/KnowledgeSeeder.php

343 lines

```php
<?php

namespace Database\Seeders;

use App\Models\KnowledgeEntry;
use Illuminate\Database\Seeder;

/**
 * Starter knowledge base: verified-style fact blocks across everyday
 * Tanzanian topics. Admins extend this through the panel or CSV/JSON import.
 */
class KnowledgeSeeder extends Seeder
{
    public function run(): void
    {
        $entries = [
            // ---------------------------------------------------------- LEGAL
            [
                'title' => 'Katiba ya Tanzania - Usawa mbele ya sheria (Ibara ya 12 na 13)',
                'category' => 'legal', 'language' => 'sw',
                'content' => 'Ibara ya 12 ya Katiba ya Jamhuri ya Muungano wa Tanzania (1977) inatamka kuwa binadamu wote huzaliwa huru na wote ni sawa. Ibara ya 13 inasisitiza kuwa watu wote ni sawa mbele ya sheria na wana haki ya kulindwa na kupata haki sawa bila ubaguzi wa jinsia, kabila, dini, hali ya kijamii au ulemavu. Mwananchi anayebaguliwa na ofisi ya umma anaweza kulalamika kwa Tume ya Haki za Binadamu na Utawala Bora (CHRAGG) au mahakamani.',
                'keywords' => ['katiba', 'usawa', 'ubaguzi', 'haki za binadamu', 'chragg', 'ibara 13'],
                'source' => 'Katiba ya Jamhuri ya Muungano wa Tanzania, 1977',
            ],
            [
                'title' => 'Constitution of Tanzania - Equality before the law (Articles 12 and 13)',
                'category' => 'legal', 'language' => 'en',
                'content' => 'Article 12 of the Constitution of the United Republic of Tanzania (1977) states that all human beings are born free and equal. Article 13 guarantees equality before the law and equal protection without discrimination on grounds of gender, tribe, religion, social status or disability. A citizen discriminated against by a public office may complain to the Commission for Human Rights and Good Governance (CHRAGG) or to the courts.',
                'keywords' => ['constitution', 'equality', 'discrimination', 'human rights', 'chragg', 'article 13'],
                'source' => 'Constitution of the United Republic of Tanzania, 1977',
            ],
            [
                'title' => 'Haki zako ukikamatwa na polisi',
                'category' => 'legal', 'language' => 'sw',
                'content' => 'Ukikamatwa Tanzania: 1) Una haki ya kuambiwa sababu ya kukamatwa kwako mara moja kwa lugha unayoielewa. 2) Una haki ya kukaa kimya na kutosaini maelezo yoyote mpaka uelewe yaliyomo; unaweza kuomba wakili au ndugu awepo. 3) Polisi wanapaswa kukufikisha mahakamani ndani ya saa 24 (ukiondoa siku za mapumziko) au kukupa dhamana ya polisi kwa makosa yanayodhaminika. 4) Una haki ya kupigiwa simu ndugu au wakili. 5) Kupigwa, kuteswa au kulazimishwa kukiri ni kinyume cha sheria; ripoti kwa Mkuu wa Kituo, Jeshi la Polisi (112), CHRAGG au mtoa msaada wa kisheria. Dhamana ya polisi ni bure; usilipe fedha kwa askari.',
                'keywords' => ['kukamatwa', 'polisi', 'dhamana', 'saa 24', 'kukaa kimya', 'wakili', 'mtuhumiwa', 'kituo cha polisi'],
                'source' => 'Sheria ya Mwenendo wa Makosa ya Jinai, Sura ya 20',
            ],
            [
                'title' => 'Your rights when arrested by the police',
                'category' => 'legal', 'language' => 'en',
                'content' => 'If arrested in Tanzania: 1) You must be told the reason immediately in a language you understand. 2) You may remain silent and should not sign a statement you do not understand; you may ask for an advocate or relative. 3) Police must bring you to court within 24 hours (excluding holidays) or grant police bail for bailable offences. 4) You may call a relative or lawyer. 5) Beating, torture or forced confession is unlawful; report to the Officer Commanding Station, the police (112), CHRAGG or a legal aid provider. Police bail is free; never pay cash to an officer.',
                'keywords' => ['arrest', 'arrested', 'police', 'bail', '24 hours', 'silent', 'advocate', 'suspect', 'police station'],
                'source' => 'Criminal Procedure Act, Cap 20',
            ],
            [
                'title' => 'Umiliki wa ardhi na migogoro ya ardhi',
                'category' => 'legal', 'language' => 'sw',
                'content' => 'Ardhi yote Tanzania ni mali ya umma iliyo chini ya Rais kama mdhamini. Kuna ardhi ya kawaida (General), ardhi ya kijiji (Village) na ardhi ya hifadhi (Reserved). Mwananchi anapata Hati ya Haki Miliki (Granted Right of Occupancy) kwa ardhi ya kawaida kupitia Ofisi ya Ardhi ya Halmashauri/Mkoa, au Hati ya Hakimiliki ya Kimila (CCRO) kwa ardhi ya kijiji kupitia Halmashauri ya Kijiji. Wanawake wana haki sawa na wanaume kumiliki na kurithi ardhi. Migogoro ya ardhi huanzia Baraza la Ardhi la Kijiji, kisha Baraza la Kata, kisha Baraza la Ardhi na Nyumba la Wilaya (DLHT), kisha
```

```
Mahakama Kuu Kitengo cha Ardhi. Kabla ya kununua ardhi hakiki hati na umiliki Ofisi ya Ardhi na kwa Mtendaji wa Kijiji/Mtaa.',
                'keywords' => ['ardhi', 'hati', 'umiliki', 'ccro', 'baraza la ardhi', 'mgogoro wa ardhi', 'kununua ardhi', 'kiwanja', 'shamba', 'mashamba', 'kudhulumiwa', 'dhuluma', 'kunyang\'anywa', 'mpaka', 'mipaka', 'kuvamiwa', 'eneo', 'mali', 'hatimiliki', 'kurithi ardhi', 'wakulima'],
                'source' => 'Sheria ya Ardhi Sura 113; Sheria ya Ardhi ya Vijiji Sura 114; Sheria ya Mahakama za Ardhi Sura 216',
            ],
            [
                'title' => 'Land ownership and land disputes',
                'category' => 'legal', 'language' => 'en',
                'content' => 'All land in Tanzania is public land vested in the President as trustee. Categories: General land, Village land and Reserved land. Citizens obtain a Granted Right of Occupancy (General land) through the District/Regional Land Office, or a Certificate of Customary Right of Occupancy (CCRO) for village land through the Village Council. Women have equal rights to own and inherit land. Disputes go from the Village Land Council to the Ward Tribunal, then the District Land and Housing Tribunal (DLHT), then the High Court Land Division. Before buying land, verify the title at the Land Office and with the Village/Mtaa Executive Officer.',
                'keywords' => ['land', 'title deed', 'ownership', 'ccro', 'land tribunal', 'land dispute', 'buying land', 'plot', 'farm', 'grabbed', 'grabbing', 'boundary', 'encroachment', 'trespass', 'inherit land', 'village land'],
                'source' => 'Land Act Cap 113; Village Land Act Cap 114; Land Disputes Courts Act Cap 216',
            ],
            [
                'title' => 'Ndoa, talaka na mgawanyo wa mali',
                'category' => 'legal', 'language' => 'sw',
                'content' => 'Sheria ya Ndoa ya 1971 inatambua ndoa za kiserikali, za kidini na za kimila; zote zinapaswa kusajiliwa RITA/ofisi ya msajili wa ndoa. Mahakama zimetamka kuwa umri wa chini wa kuoa au kuolewa ni miaka 18 kwa wote. Talaka hutolewa na mahakama tu baada ya kuthibitisha ndoa imevunjika kabisa; kabla ya kwenda mahakamani lazima kupitia Baraza la Usuluhishi la Ndoa (ngazi ya kata au la kidini). Wakati wa talaka mahakama hugawa mali zilizochumwa pamoja kwa kuzingatia mchango wa kila mmoja, ikiwemo kazi za nyumbani. Matunzo ya watoto hupewa kipaumbele kwa maslahi ya mtoto.',
                'keywords' => ['ndoa', 'talaka', 'mali ya ndoa', 'usuluhishi', 'mke', 'mume', 'matunzo', 'kusajili ndoa', 'miaka 18'],
                'source' => 'Sheria ya Ndoa, 1971 (Sura 29)',
            ],
            [
                'title' => 'Marriage, divorce and division of property',
                'category' => 'legal', 'language' => 'en',
                'content' => 'The Law of Marriage Act 1971 recognises civil, religious and customary marriages; all should be registered with RITA or the marriage registrar. Courts have held that the minimum age of marriage is 18 for everyone. Divorce is granted only by a court after proof of irreparable breakdown, and only after referral to a Marriage Conciliation Board (ward or religious). On divorce the court divides assets acquired jointly, counting each spouse\'s contribution including housework. Custody decisions follow the best interest of the child.',
                'keywords' => ['marriage', 'divorce', 'matrimonial property', 'conciliation', 'custody', 'register marriage', 'age 18'],
                'source' => 'Law of Marriage Act, 1971 (Cap 29)',
            ],
            [
                'title' => 'Mirathi na wosia',
                'category' => 'legal', 'language' => 'sw',
                'content' => 'Mtu anaweza kuandika wosia (will) akiwa na akili timamu; wosia wa maandishi usainiwe mbele ya mashahidi wawili wasio warithi. Mtu akifa bila wosia mirathi hugawanywa kwa sheria inayomhusu: sheria ya kimila, ya Kiislamu, au Sheria ya Mirathi ya India (kwa wengine). Ndugu hukutana kuchagua msimamizi wa mirathi, kisha msimamizi huomba barua ya usimamizi Mahakama ya Mwanzo (mirathi ndogo) au Mahakama ya Wilaya/Mahakama Kuu (mirathi kubwa). Cheti cha kifo kutoka RITA ni lazima. Watoto, wajane na wagane wana haki ya kurithi; kunyang\'anywa mali ya marehemu bila utaratibu ni kosa. Msaada: mtoa msaada wa kisheria, TAWLA, WLAC, LHRC.',
                'keywords' => ['mirathi', 'wosia', 'urithi', 'msimamizi wa mirathi', 'marehemu', 'mjane', 'cheti cha kifo', 'warithi'],
                'source' => 'Sheria ya Usimamizi wa Mirathi Sura 352; Sheria ya Mahakama za Mahakimu Sura 11',
            ],
            [
                'title' => 'Haki za mpangaji na mwenye nyumba',
                'category' => 'legal', 'language' => 'sw',
                'content' => 'Mkataba wa pango uwe wa maandishi na uonyeshe kodi, muda na masharti; kwa makazi mwenye nyumba haruhusiwi kudai kodi ya zaidi ya miezi 12 mapema (kwa malipo ya kila mwezi, kodi ya awali hupangwa kwa makubaliano) na lazima atoe risiti. Mwenye nyumba hawezi kumfukuza mpangaji kwa nguvu, kufunga milango au kukata maji/umeme bila amri ya mahakama; notisi ya maandishi inahitajika kwa mujibu wa mkataba. Migogoro ya pango husikilizwa na Baraza la Ardhi na Nyumba la Wilaya (DLHT). Mpangaji anawajibika kulipa kodi kwa wakati na kutunza nyumba.',
                'keywords' => ['pango', 'mpangaji', 'mwenye nyumba', 'kodi ya nyumba', 'kufukuzwa', 'notisi', 'dlht', 'nyumba'],
                'source' => 'Sheria ya Ardhi Sura 113 Sehemu ya Pango; Sheria ya Mahakama za Ardhi Sura 216',
            ],

            // ---------------------------------------------------------- EMPLOYMENT
```

```
            [
                'title' => 'Haki za mfanyakazi (Sheria ya Ajira na Mahusiano Kazini)',
                'category' => 'employment', 'language' => 'sw',
                'content' => 'Sheria ya Ajira na Mahusiano Kazini (ELRA, Sura 366): 1) Mkataba wa maandishi ni lazima kwa ajira inayozidi miezi 6; mwajiri lazima atoe nakala. 2) Saa za kazi hazizidi 45 kwa wiki au 9 kwa siku; saa za ziada hulipwa mara 1.5 ya kiwango cha kawaida. 3) Likizo ya mwaka ni siku 28 mfululizo zenye malipo. 4) Likizo ya uzazi: siku 84 zenye malipo (siku 100 kwa mapacha) kwa mama, siku 3 kwa baba. 5) Likizo ya ugonjwa hadi siku 126 kwa mzunguko wa miezi 36. 6) Kuachishwa kazi lazima kuwe na sababu halali na utaratibu wa haki (kusikilizwa). Mgogoro wa kuachishwa kazi isivyo haki huwasilishwa CMA ndani ya siku 30; migogoro mingine ndani ya siku 60. Kima cha chini cha mshahara hutofautiana kwa sekta (angalia tangazo la Serikali la hivi karibuni).',
                'keywords' => ['ajira', 'mfanyakazi', 'mkataba wa kazi', 'likizo', 'uzazi', 'kufukuzwa kazi', 'cma', 'mshahara', 'saa za kazi', 'overtime'],
                'source' => 'Sheria ya Ajira na Mahusiano Kazini, Sura 366',
            ],
            [
                'title' => 'Worker rights (Employment and Labour Relations Act)',
                'category' => 'employment', 'language' => 'en',
                'content' => 'Employment and Labour Relations Act (Cap 366): 1) A written contract is required for employment over 6 months; the employer must give the worker a copy. 2) Working hours max 45 per week or 9 per day; overtime is paid at 1.5 times. 3) Annual leave is 28 consecutive paid days. 4) Maternity leave 84 paid days (100 for multiple births), paternity leave 3 days. 5) Sick leave up to 126 days per 36-month cycle. 6) Termination needs a valid reason and a fair procedure (a hearing). Unfair termination disputes go to the CMA within 30 days; other disputes within 60 days. Minimum wages differ by sector (check the latest Government Notice).',
                'keywords' => ['employment', 'employee', 'contract', 'leave', 'maternity', 'dismissal', 'termination', 'cma', 'wage', 'working hours', 'overtime'],
                'source' => 'Employment and Labour Relations Act, Cap 366',
            ],
            [
                'title' => 'Kutafuta kazi na kuepuka matapeli wa ajira',
                'category' => 'employment', 'language' => 'sw',
                'content' => 'Nafasi halali za kazi za umma hutangazwa na Sekretarieti ya Ajira katika Utumishi wa Umma (ajira.go.tz) na tovuti za taasisi husika; hakuna malipo ya kuomba kazi serikalini. Tahadhari: mtu anayekuomba fedha "ya usaili", "ya mafunzo" au "ya kibali" kabla ya kuajiriwa ni tapeli. Kwa ajira nje ya nchi tumia mawakala waliosajiliwa na Wizara ya Kazi pekee; hakiki mkataba na usikabidhi pasipoti yako kwa wakala. CV nzuri: taarifa za mawasiliano, elimu, uzoefu, ujuzi, wadhamini wawili; iwe kurasa 1-2.',
                'keywords' => ['kazi', 'nafasi za kazi', 'ajira', 'cv', 'usaili', 'tapeli', 'ajira nje ya nchi', 'wakala'],
                'source' => 'Sekretarieti ya Ajira; Wizara ya Kazi',
            ],

            // ------------------------------------------------------------ HEALTH
            [
                'title' => 'Malaria - dalili, matibabu na kinga',
                'category' => 'health', 'language' => 'sw',
                'content' => 'Dalili za malaria: homa, kutetemeka, maumivu ya kichwa na viungo, kutapika, uchovu. Mtu mwenye dalili apimwe kwa kipimo cha haraka (mRDT) au darubini kwenye zahanati/duka la dawa lililosajiliwa; asinywe dawa bila kipimo. Matibabu ya kwanza Tanzania ni ALu (Artemether-Lumefantrine) inayotolewa na mtaalamu wa afya. Dalili za hatari zinazohitaji hospitali MARA MOJA: kupoteza fahamu, degedege, kushindwa kunywa au kunyonya, kupumua kwa shida, manjano, mkojo mweusi, hasa kwa watoto chini ya miaka 5 na wajawazito. Kinga: lala ndani ya chandarua chenye dawa kila usiku, ondoa maji yaliyotuama, wajawazito wachukue dawa ya kinga (IPTp) kliniki.',
                'keywords' => ['malaria', 'homa', 'chandarua', 'mrdt', 'alu', 'degedege', 'mbu', 'kutetemeka'],
                'source' => 'Mpango wa Taifa wa Kudhibiti Malaria (NMCP), Wizara ya Afya',
            ],
            [
                'title' => 'Malaria - symptoms, treatment and prevention',
                'category' => 'health', 'language' => 'en',
                'content' => 'Malaria symptoms: fever, chills, headache, body pain, vomiting, tiredness. Anyone with symptoms should be tested (mRDT or microscopy) at a dispensary or accredited drug shop before taking medicine. First-line treatment in Tanzania is ALu (Artemether-Lumefantrine) given by a health worker. Danger signs needing a hospital IMMEDIATELY: loss of consciousness, convulsions, inability to drink or breastfeed, difficulty breathing, yellow eyes, dark urine, especially in children under 5 and pregnant women. Prevention: sleep under a treated net every night, remove stagnant water, pregnant women take preventive doses (IPTp) at the clinic.',
                'keywords' => ['malaria', 'fever', 'mosquito net', 'mrdt', 'alu', 'convulsions', 'mosquito'],
                'source' => 'National Malaria Control Programme, Ministry of Health',
            ],
            [
                'title' => 'Bima ya afya: NHIF na CHF iliyoboreshwa (iCHF)',
                'category' => 'health', 'language' => 'sw',
                'content' => 'NHIF (Mfuko wa Taifa wa Bima ya Afya) ni bima ya afya ya umma: watumishi wa umma hukatwa moja kwa moja, na wananchi wengine wanaweza kujiunga kwa hiari kupitia vifurushi vya NHIF (ofisi za NHIF za mkoa/wilaya au mawakala). CHF iliyoboreshwa (iCHF) ni bima ya jamii ya gharama nafuu kwa kaya inayosajiliwa kupitia Mtendaji wa Kata au afisa wa iCHF wa halmashauri; hutumika vituo vya afya vya umma vya wilaya/mkoa. Tanzania inatekeleza Sheria ya Bima ya Afya kwa Wote (2023) kwa awamu. Huduma za bure kwa wote: huduma za mama mjamzito na watoto chini ya miaka
```

```
5 kwenye vituo vya umma, chanjo, matibabu ya kifua kikuu na ARV.',
                'keywords' => ['nhif', 'chf', 'ichf', 'bima ya afya', 'kadi ya bima', 'matibabu', 'gharama za matibabu', 'bima kwa wote'],
                'source' => 'NHIF; Wizara ya Afya; Sheria ya Bima ya Afya kwa Wote 2023',
            ],
            [
                'title' => 'Kliniki ya mama mjamzito na chanjo za mtoto',
                'category' => 'health', 'language' => 'sw',
                'content' => 'Mama mjamzito aanze kliniki (RCH) mapema kabla ya miezi 3 na ahudhurie angalau mara 8 kwa mujibu wa mwongozo mpya; kliniki hupima damu, presha, UKIMWI, kaswende, hutoa dawa za kinga ya malaria (IPTp), vidonge vya damu (FeFo), chandarua na kadi ya kliniki. Jifungulia kituo cha afya; huduma ya mama na mtoto chini ya miaka 5 ni bure vituo vya umma. Ratiba ya chanjo ya mtoto Tanzania: kuzaliwa BCG na OPV0; wiki 6, 10, 14 Penta (DTP-HepB-Hib), OPV, PCV, Rota; miezi 9 Surua-Rubella (MR) ya kwanza; miezi 18 MR ya pili. Wasichana wa miaka 9-14 hupata chanjo ya HPV (saratani ya mlango wa kizazi).',
                'keywords' => ['mjamzito', 'kliniki', 'chanjo', 'mtoto', 'kujifungua', 'rch', 'surua', 'hpv', 'penta', 'bcg'],
                'source' => 'Wizara ya Afya - Mpango wa Chanjo (IVD)',
            ],
            [
                'title' => 'Kipindupindu na magonjwa ya kuhara: kinga na hatua za haraka',
                'category' => 'health', 'language' => 'sw',
                'content' => 'Kipindupindu huambukizwa kwa maji au chakula kilichochafuliwa na kinyesi. Dalili: kuhara maji mengi kama maji ya mchele, kutapika, kupungukiwa maji haraka. Hatua za haraka: anza kunywa ORS (dawa ya kuongeza maji mwilini) au maji ya chumvi na sukari mara moja na uende kituo cha afya haraka; watoto wapewe pia zinki. Kinga: nawa mikono kwa sabuni, chemsha au tia dawa (Waterguard) maji ya kunywa, tumia choo, pasha moto chakula, osha matunda. Ripoti mlipuko kwa afisa afya wa kata.',
                'keywords' => ['kipindupindu', 'kuhara', 'ors', 'maji safi', 'choo', 'kunawa mikono', 'mlipuko', 'zinki'],
                'source' => 'Wizara ya Afya - Mwongozo wa Kudhibiti Kipindupindu',
            ],

            // ---------------------------------------------------------- AGRICULTURE
            [
                'title' => 'Misimu ya kilimo Tanzania na kalenda ya kupanda',
                'category' => 'agriculture', 'language' => 'sw',
                'content' => 'Tanzania ina mifumo miwili ya mvua. Maeneo ya kaskazini na pwani (Arusha, Kilimanjaro, Tanga, Dar es Salaam, Pwani, Mwanza, Kagera, Mara) yana misimu miwili: Vuli (Oktoba-Desemba) na Masika (Machi-Mei). Maeneo ya katikati, magharibi na nyanda za juu kusini (Dodoma, Singida, Tabora, Mbeya, Iringa, Njombe, Ruvuma, Songwe, Rukwa, Katavi, Morogoro kusini) yana msimu mmoja mrefu (Novemba/Desemba-Aprili). Panda mahindi mwanzoni mwa mvua za uhakika baada ya utabiri wa TMA; tumia mbegu zilizothibitishwa na TOSCI zenye muda wa kukomaa unaolingana na msimu wa eneo lako. Kwa ushauri wa eneo lako muone afisa ugani wa kata.',
                'keywords' => ['msimu', 'vuli', 'masika', 'mvua', 'kupanda', 'kalenda ya kilimo', 'mahindi', 'tma', 'afisa ugani'],
                'source' => 'Mamlaka ya Hali ya Hewa Tanzania (TMA); Wizara ya Kilimo',
            ],
            [
                'title' => 'Farming seasons in Tanzania and planting calendar',
                'category' => 'agriculture', 'language' => 'en',
                'content' => 'Tanzania has two rainfall regimes. The north and coast (Arusha, Kilimanjaro, Tanga, Dar es Salaam, Pwani, Mwanza, Kagera, Mara) have two seasons: short rains "Vuli" (October-December) and long rains "Masika" (March-May). Central, western and southern highland regions (Dodoma, Singida, Tabora, Mbeya, Iringa, Njombe, Ruvuma, Songwe, Rukwa, Katavi, southern Morogoro) have one long season (November/December-April). Plant maize at the start of reliable rains following TMA forecasts; use TOSCI-certified seed with a maturity period matching your area. Consult the ward extension officer for local advice.',
                'keywords' => ['season', 'rains', 'planting', 'calendar', 'maize', 'tma', 'extension officer', 'rainfall'],
                'source' => 'Tanzania Meteorological Authority (TMA); Ministry of Agriculture',
            ],
            [
                'title' => 'Viwavijeshi vamizi (fall armyworm) kwenye mahindi',
                'category' => 'agriculture', 'language' => 'sw',
                'content' => 'Viwavijeshi vamizi hushambulia mahindi hasa wiki 2-6 baada ya kuota; dalili ni majani yaliyotobolewa na kinyesi kama unga wa mbao kwenye kishungi. Kagua shamba mara 2 kwa wiki asubuhi; ukikuta mimea zaidi ya 20% imeshambuliwa chukua hatua. Hatua: ondoa na uue viwavi kwa mkono kwa shamba dogo, weka mchanga/majivu kwenye kishungi, panda mapema na kwa pamoja na majirani, tumia viuatilifu vilivyosajiliwa na TPHPA (uliza afisa ugani jina sahihi na kipimo), pulizia alasiri/jioni ukielekeza kwenye kishungi. Vaa kinga unapotumia dawa. Panda mazao mchanganyiko (mahindi na maharage/dengu) kupunguza mashambulizi.',
                'keywords' => ['viwavijeshi', 'mahindi', 'wadudu', 'dawa ya wadudu', 'kiuatilifu', 'shamba', 'armyworm'],
                'source' => 'TARI; Wizara ya Kilimo - Mwongozo wa Viwavijeshi',
            ],
            [
                'title' => 'Ufugaji wa kuku: chanjo ya mdondo (Newcastle) na matunzo',
```

```
                'category' => 'agriculture', 'language' => 'sw',
                'content' => 'Mdondo (Newcastle) ndio ugonjwa unaoua kuku wengi zaidi vijijini; dalili: kuhara kijani, kupinda shingo, kupooza, vifo vya ghafla. Kinga pekee ni chanjo (I-2 au LaSota) kila baada ya miezi 3-4, mara nyingi kwa kudondosha jichoni au kunywesha; chanjo hupatikana kwa afisa mifugo wa kata, maduka ya pembejeo za mifugo au TVLA. Chanja kuku wote kwa pamoja na majirani. Matunzo: banda lenye hewa safi na likavu, maji safi kila siku, chakula chenye uwiano (mahindi, pumba, mashudu, dagaa, madini), weka vifaranga mbali na kuku wakubwa, dhibiti viroboto na minyoo kwa ushauri wa afisa mifugo. Usile wala kuuza kuku waliokufa kwa ugonjwa.',
                'keywords' => ['kuku', 'mdondo', 'newcastle', 'chanjo ya kuku', 'ufugaji', 'vifaranga', 'banda', 'afisa mifugo'],
                'source' => 'Wizara ya Mifugo na Uvuvi; TVLA',
            ],

            // ------------------------------------------------------------ EDUCATION
            [
                'title' => 'Mfumo wa elimu Tanzania na mitihani ya NECTA',
                'category' => 'education', 'language' => 'sw',
                'content' => 'Mfumo wa elimu: elimu ya awali (mwaka 1), msingi Darasa la 1-7 (mtihani wa Darasa la 4 wa upimaji na Mtihani wa Kumaliza Elimu ya Msingi PSLE Darasa la 7), sekondari ya kawaida Kidato cha 1-4 (FTNA Kidato cha 2, CSEE Kidato cha 4), sekondari ya juu Kidato cha 5-6 (ACSEE), kisha vyuo vya ufundi (VETA, NACTVET) au vyuo vikuu (TCU). Elimu ya msingi hadi Kidato cha 4 shule za umma ni bila ada (Sera ya Elimu bila Malipo). NECTA huendesha mitihani ya taifa na kutangaza matokeo kwenye necta.go.tz (pia kwa SMS zinapotolewa). Madaraja ya CSEE: Daraja la I (pointi 7-17) hadi IV; Daraja 0 ni kufeli. Mitaala mipya ya 2023 inaongeza masomo ya ufundi (amali) sekondari.',
                'keywords' => ['necta', 'matokeo', 'kidato', 'darasa la saba', 'psle', 'csee', 'acsee', 'shule', 'elimu bila malipo', 'mtihani', 'daraja'],
                'source' => 'NECTA; Wizara ya Elimu, Sayansi na Teknolojia',
            ],
            [
                'title' => 'Tanzanian education system and NECTA examinations',
                'category' => 'education', 'language' => 'en',
                'content' => 'Structure: pre-primary (1 year), primary Standard 1-7 (Standard 4 assessment and the Primary School Leaving Examination PSLE in Standard 7), ordinary secondary Form 1-4 (FTNA in Form 2, CSEE in Form 4), advanced secondary Form 5-6 (ACSEE), then vocational colleges (VETA, NACTVET) or universities (TCU). Public primary to Form 4 is fee-free. NECTA runs national exams and publishes results at necta.go.tz. CSEE divisions: Division I (points 7-17) to IV; Division 0 is a fail. The 2023 curriculum adds vocational streams in secondary school.',
                'keywords' => ['necta', 'results', 'form four', 'form six', 'standard seven', 'psle', 'csee', 'acsee', 'school', 'exam', 'division'],
                'source' => 'NECTA; Ministry of Education, Science and Technology',
            ],
            [
                'title' => 'Mikopo ya elimu ya juu (HESLB) na kujiunga na chuo',
                'category' => 'education', 'language' => 'sw',
                'content' => 'Bodi ya Mikopo ya Wanafunzi wa Elimu ya Juu (HESLB) hutoa mikopo kwa Watanzania wanaojiunga na vyuo vilivyosajiliwa (shahada na baadhi ya stashahada). Maombi hufanywa mtandaoni kupitia mfumo wa OLAMS (heslb.go.tz) baada ya kupata udahili, kwa kawaida Julai-Agosti kila mwaka; nyaraka: cheti cha kuzaliwa, vyeti vya Kidato cha 4 na 6, kitambulisho cha NIDA, taarifa za wazazi/walezi (vyeti vya kifo kama wamefariki), barua ya mtendaji. Mkopo hurejeshwa baada ya kuanza kazi kwa kukatwa mshahara. Udahili wa vyuo vikuu hufanywa kupitia vyuo vyenyewe na kuratibiwa na TCU; vyuo vya ufundi na NACTVET. Vigezo vya chini: kwa shahada, pointi kutoka ACSEE au stashahada.',
                'keywords' => ['heslb', 'mkopo wa elimu', 'bodi ya mikopo', 'olams', 'chuo kikuu', 'udahili', 'tcu', 'nactvet', 'ada ya chuo'],
                'source' => 'HESLB; TCU',
            ],

            // ------------------------------------------------------------ GOVERNMENT
            [
                'title' => 'Kitambulisho cha Taifa (NIDA): jinsi ya kujisajili',
                'category' => 'government', 'language' => 'sw',
                'content' => 'Mamlaka ya Vitambulisho vya Taifa (NIDA) husajili Watanzania wenye umri wa miaka 18 na zaidi (na watoto kwa namba ya NIN). Hatua: 1) Chukua fomu ofisi ya mtendaji wa kata/mtaa au ofisi ya NIDA ya wilaya, au anza mtandaoni nida.go.tz. 2) Nyaraka: cheti cha kuzaliwa au hati ya kiapo, cheti cha kuzaliwa/kitambulisho cha mzazi mmoja au barua ya mtendaji, picha, na uthibitisho wa makazi. 3) Alama za vidole na picha huchukuliwa ofisi ya NIDA. 4) Namba ya utambulisho (NIN) hutolewa kwanza, kadi hufuata. Usajili ni bure. NIN inahitajika kwa laini ya simu, TIN, akaunti ya benki, HESLB na huduma nyingi za serikali. Kuhakiki hali ya maombi: nida.go.tz au *152*00#.',
                'keywords' => ['nida', 'kitambulisho cha taifa', 'nin', 'kujisajili', 'kitambulisho', 'alama za vidole', 'cheti cha kuzaliwa'],
                'source' => 'NIDA - nida.go.tz',
            ],
            [
                'title' => 'National ID (NIDA): how to register',
                'category' => 'government', 'language' => 'en',
                'content' => 'The National Identification Authority (NIDA) registers Tanzanians aged 18 and above (children receive a NIN). Steps: 1) Get the form from the ward/mtaa executive office or district NIDA office, or start online at nida.go.tz. 2) Documents: birth certificate or affidavit, a parent\'s birth certificate/ID or a letter from the executive officer, photo, proof of residence. 3) Fingerprints and photo are captured at the NIDA office. 4) The NIN is
```

```
issued first, the card later. Registration is free. The NIN is required for SIM cards, TIN, bank accounts, HESLB loans and most government services. Check status at nida.go.tz or *152*00#.',
                'keywords' => ['nida', 'national id', 'nin', 'register', 'identity card', 'fingerprints', 'birth certificate'],
                'source' => 'NIDA - nida.go.tz',
            ],
            [
                'title' => 'Cheti cha kuzaliwa na cheti cha kifo (RITA)',
                'category' => 'government', 'language' => 'sw',
                'content' => 'Wakala wa Usajili, Ufilisi na Udhamini (RITA) husajili vizazi na vifo. Usajili wa mtoto ndani ya siku 90 tangu kuzaliwa ni bure kwa cheti cha kwanza; baada ya hapo kuna ada ya ucheleweshaji. Mahali: ofisi ya msajili wa wilaya (RITA), ofisi ya mtendaji wa kata, au hospitali/zahanati zinazosajili moja kwa moja (mfumo wa usajili wa watoto chini ya miaka 5 kwa simu). Nyaraka: notisi ya kuzaliwa kutoka kituo cha afya au barua ya mtendaji, vitambulisho vya wazazi. Cheti cha kifo: notisi ya kifo kutoka hospitali/mtendaji, kitambulisho cha marehemu, ndani ya siku 30. Malipo ya RITA hufanywa kwa control number ya GePG. Tovuti: rita.go.tz, huduma mtandaoni kupitia efms.rita.go.tz.',
                'keywords' => ['rita', 'cheti cha kuzaliwa', 'cheti cha kifo', 'usajili wa kizazi', 'mtoto mchanga', 'notisi ya kuzaliwa'],
                'source' => 'RITA - rita.go.tz',
            ],
            [
                'title' => 'Pasipoti ya Tanzania (e-Passport)',
                'category' => 'government', 'language' => 'sw',
                'content' => 'Pasipoti ya kielektroniki hutolewa na Idara ya Uhamiaji. Hatua: 1) Jaza maombi mtandaoni eservices.immigration.go.tz, pakia nyaraka: kitambulisho cha NIDA (NIN), cheti cha kuzaliwa, picha, na kwa watoto vitambulisho vya wazazi na idhini. 2) Lipa ada kwa control number (GePG). 3) Fika ofisi ya uhamiaji uliyochagua kwa alama za vidole, picha na mahojiano. 4) Pasipoti ya kawaida huwa tayari ndani ya siku chache hadi wiki kadhaa. Ada ya pasipoti ya kawaida ni TZS 150,000 (thibitisha kiwango cha sasa kwenye tovuti). Pasipoti ya Afrika Mashariki ya Tanzania inatumika kusafiri nchi zote.',
                'keywords' => ['pasipoti', 'passport', 'uhamiaji', 'kusafiri nje', 'e-passport', 'immigration'],
                'source' => 'Idara ya Uhamiaji - immigration.go.tz',
            ],
            [
                'title' => 'Namba ya mlipakodi (TIN) na kodi za TRA kwa wafanyabiashara wadogo',
                'category' => 'finance', 'language' => 'sw',
                'content' => 'TIN (Taxpayer Identification Number) hutolewa bure na Mamlaka ya Mapato Tanzania (TRA) mtandaoni (tra.go.tz, huduma za mtandaoni) au ofisi ya TRA ya wilaya; unahitaji NIN ya NIDA. TIN inahitajika kwa biashara, leseni, ajira rasmi, kununua gari au kiwanja. Wafanyabiashara wadogo wasio na hesabu za ukaguzi hulipa kodi ya makisio (presumptive tax) kulingana na mauzo ya mwaka; mauzo chini ya TZS milioni 4 kwa mwaka hayalipi kodi ya mapato ya makisio (lakini usajili wa TIN na leseni unahitajika). VAT husajiliwa kwa mauzo ya zaidi ya TZS milioni 200 kwa mwaka. Dai risiti ya EFD kwa kila manunuzi. Malipo yote ya TRA ni kwa control number; hakuna malipo kwa afisa. Huduma kwa wateja TRA: 0800 750 075 / 0800 780 078 (bure).',
                'keywords' => ['tin', 'tra', 'kodi', 'kodi ya mapato', 'vat', 'efd', 'risiti', 'mlipakodi', 'makisio', 'biashara ndogo'],
                'source' => 'TRA - tra.go.tz',
            ],
            [
                'title' => 'Malipo ya serikali kwa control number (GePG)',
                'category' => 'government', 'language' => 'sw',
                'content' => 'Malipo yote ya serikali (ada, faini, leseni, kodi, huduma za NIDA/RITA/Uhamiaji, ada za shule za umma) hufanywa kupitia Mfumo wa Malipo ya Serikali (GePG). Ofisi husika hukupa namba ya kumbukumbu ya malipo (control number) yenye tarakimu 12 inayoanza na 99. Lipa kwa pesa za simu (M-Pesa, Mixx by Yas, Airtel Money, HaloPesa: chagua "Lipa kwa Serikali/GePG"), benki, au wakala wa benki. Hifadhi ujumbe wa uthibitisho. Usilipe fedha taslimu kwa afisa bila control number na risiti rasmi. Kwa wanafunzi wa shule za umma, ada za bweni na michango halali hulipwa kwa control number ya shule.',
                'keywords' => ['gepg', 'control number', 'malipo ya serikali', 'namba ya kumbukumbu', 'kulipa faini', 'ada', 'kulipa serikali'],
                'source' => 'Wizara ya Fedha - GePG',
            ],
            [
                'title' => 'Umeme wa TANESCO na LUKU',
                'category' => 'government', 'language' => 'sw',
                'content' => 'TANESCO ndiyo kampuni ya umeme Tanzania Bara; kuunganishwa umeme omba ofisi ya TANESCO ya wilaya au mtandaoni (ukiwa na NIN, hati/barua ya mtendaji ya nyumba na ramani ya eneo), lipa ada ya kuunganisha kwa control number. Vijijini kuunganishwa kwa bei nafuu kupitia REA. Umeme wa kulipia kabla (LUKU) hununuliwa kwa pesa za simu, benki au mawakala kwa namba ya mita; weka tokeni ya tarakimu 20 kwenye mita. Kwa hitilafu au umeme kukatika ripoti kwa huduma kwa wateja TANESCO (ofisi ya karibu au namba iliyo kwenye tovuti tanesco.co.tz). Usijiunganishe umeme kinyume cha sheria; ni hatari na ni kosa la jinai.',
                'keywords' => ['tanesco', 'luku', 'umeme', 'kuunganisha umeme', 'mita', 'tokeni', 'rea', 'umeme umekatika'],
                'source' => 'TANESCO - tanesco.co.tz',
            ],

            // ---------------------------------------------------------- FINANCE / BUSINESS
```

```
            [
                'title' => 'Utapeli wa pesa za simu na jinsi ya kujilinda',
                'category' => 'finance', 'language' => 'sw',
                'content' => 'Mbinu za kawaida za utapeli: ujumbe au simu ya "umeshinda zawadi", "nimetuma pesa kwa makosa nirudishie", "akaunti yako itafungwa thibitisha PIN", mikopo ya haraka ya mtandaoni inayotaka ada kwanza, na matangazo ya uwekezaji wa faida kubwa haraka (piramidi). Kanuni: 1) Usimpe mtu yeyote PIN, OTP au nywila, hata akijitambulisha kuwa wa benki/kampuni ya simu. 2) Hakiki salio lako kwa menyu rasmi kabla ya "kurudisha" pesa. 3) Mikopo halali hutoka benki, SACCOS au watoa huduma waliosajiliwa na BoT; hawatozi ada kabla ya kukopesha. 4) Ukitapeliwa ripoti mara moja kwa kampuni ya simu (kusimamisha muamala) na polisi (Kitengo cha Makosa ya Mtandao), hifadhi ujumbe na namba. Kupoteza simu: zuia laini na akaunti ya pesa mara moja kwa huduma kwa wateja.',
                'keywords' => ['utapeli', 'tapeli', 'm-pesa', 'pesa za simu', 'pin', 'otp', 'umeshinda', 'mkopo wa haraka', 'piramidi', 'kutapeliwa'],
                'source' => 'BoT; TCRA; Jeshi la Polisi',
            ],
            [
                'title' => 'Mobile money scams and how to stay safe',
                'category' => 'finance', 'language' => 'en',
                'content' => 'Common scams: "you have won a prize" messages or calls, "I sent money by mistake, please return it", "your account will be closed, confirm your PIN", instant online loans that ask for a fee first, and get-rich-quick investment schemes (pyramids). Rules: 1) Never share your PIN, OTP or password with anyone, even someone claiming to be from a bank or telecom. 2) Check your balance in the official menu before "returning" money. 3) Legitimate loans come from banks, SACCOS or BoT-licensed lenders; they never charge a fee before lending. 4) If scammed, report immediately to the mobile operator (to freeze the transaction) and the police cybercrime unit; keep the messages and numbers. Lost phone: block the SIM and money account at once via customer care.',
                'keywords' => ['scam', 'fraud', 'mobile money', 'pin', 'otp', 'won', 'instant loan', 'pyramid', 'lost phone'],
                'source' => 'BoT; TCRA; Tanzania Police',
            ],
            [
                'title' => 'Kuanzisha na kurasimisha biashara ndogo Tanzania',
                'category' => 'business', 'language' => 'sw',
                'content' => 'Hatua za kurasimisha: 1) Pata TIN kutoka TRA (bure). 2) Sajili jina la biashara au kampuni BRELA kupitia mfumo wa ORS (ors.brela.go.tz); jina la biashara ni rahisi na nafuu kwa mfanyabiashara mmoja. 3) Pata leseni ya biashara kutoka Halmashauri ya wilaya/jiji (biashara ndogo) au Wizara ya Viwanda na Biashara (biashara kubwa); ada hutegemea aina ya biashara. 4) Kwa vyakula, vipodozi na dawa unahitaji usajili/kibali cha TMDA, na kwa ubora wa bidhaa TBS. 5) Fungua akaunti ya benki ya biashara na tenganisha fedha za biashara na za nyumbani. Fursa: SIDO (mafunzo, mitaji midogo na viwanda vidogo), mikopo ya Halmashauri kwa vikundi vya vijana, wanawake na watu wenye ulemavu (uliza Afisa Maendeleo ya Jamii wa halmashauri kuhusu utaratibu wa sasa), VICOBA na SACCOS. Andika mpango wa biashara rahisi: bidhaa, wateja, gharama, bei, faida.',
                'keywords' => ['biashara', 'kusajili biashara', 'brela', 'leseni ya biashara', 'tin', 'sido', 'mtaji', 'mpango wa biashara', 'ujasiriamali', 'tmda', 'tbs', 'mikopo ya halmashauri'],
                'source' => 'BRELA; TRA; SIDO; Wizara ya Viwanda na Biashara',
            ],
            [
                'title' => 'Starting and formalising a small business in Tanzania',
                'category' => 'business', 'language' => 'en',
                'content' => 'Steps: 1) Get a TIN from TRA (free). 2) Register a business name or company with BRELA through the ORS system (ors.brela.go.tz); a business name is simpler and cheaper for a sole trader. 3) Get a business licence from the district/city council (small businesses) or the Ministry of Industry and Trade (large); fees depend on the type. 4) Food, cosmetics and medicines need TMDA registration; product quality marks come from TBS. 5) Open a business bank account and keep business and household money separate. Support: SIDO (training, small loans, industrial sheds), council loans for youth, women and persons with disabilities (ask the council Community Development Officer about the current procedure), VICOBA and SACCOS. Write a simple business plan: product, customers, costs, price, profit.',
                'keywords' => ['business', 'register business', 'brela', 'business licence', 'tin', 'sido', 'capital', 'business plan', 'entrepreneur', 'tmda', 'tbs', 'council loans'],
                'source' => 'BRELA; TRA; SIDO; Ministry of Industry and Trade',
            ],

            // ---------------------------------------------------------- FAMILY
            [
                'title' => 'Ukatili wa kijinsia na dhidi ya watoto: wapi pa kupata msaada',
                'category' => 'family', 'language' => 'sw',
                'content' => 'Ukatili wa kijinsia (kupigwa, kubakwa, kulazimishwa ndoa, kunyimwa matunzo) na ukatili dhidi ya watoto ni makosa ya jinai. Hatua: 1) Kwa hatari ya sasa piga 112 (polisi) au nenda kituo cha polisi cha karibu na uombe Dawati la Jinsia na Watoto. 2) Kwa ubakaji nenda hospitali ndani ya saa 72 kabla ya kuoga ili kupata matibabu ya kinga (PEP, dharura ya uzazi) na fomu ya PF3 (polisi hutoa PF3 bure). 3) Piga 116 (Msaada kwa Mtoto, bure, saa 24) kwa watoto. 4) Afisa Ustawi wa Jamii wa halmashauri husaidia matunzo ya watoto na makazi salama; vituo vya huduma za mkono mmoja (One Stop Centre) vipo hospitali za mikoa. 5) Msaada wa kisheria bure: TAWLA, WLAC, LHRC, Kituo cha Sheria na Haki za Binadamu, Kampeni ya Msaada wa Kisheria ya Mama Samia. Sheria ya Mtoto 2009 inakataza adhabu zinazodhuru, ajira za watoto na ndoa za utotoni.',
                'keywords' => ['ukatili', 'kupigwa', 'ubakaji', 'dawati la jinsia', '116', 'pf3', 'ustawi wa jamii', 'mtoto', 'msaada wa kisheria', 'ndoa za utotoni', 'gbv'],
                'source' => 'Sheria ya Mtoto 2009; Jeshi la Polisi; Wizara ya Maendeleo ya Jamii, Jinsia, Wanawake
```

```
na Makundi Maalum',
            ],
            [
                'title' => 'Gender-based violence and violence against children: where to get help',
                'category' => 'family', 'language' => 'en',
                'content' => 'Gender-based violence (beating, rape, forced marriage, denial of maintenance) and violence against children are crimes. Steps: 1) In immediate danger call 112 or go to the nearest police station and ask for the Gender and Children\'s Desk. 2) After rape go to a hospital within 72 hours, before bathing, for preventive treatment (PEP, emergency contraception) and the PF3 form (police issue PF3 free). 3) Call 116 (Child Helpline, free, 24 hours) for children. 4) The council Social Welfare Officer helps with child maintenance and safe shelter; One Stop Centres exist at regional hospitals. 5) Free legal aid: TAWLA, WLAC, LHRC, the Mama Samia Legal Aid Campaign. The Law of the Child Act 2009 prohibits harmful punishment, child labour and child marriage.',
                'keywords' => ['violence', 'beaten', 'rape', 'gender desk', '116', 'pf3', 'social welfare', 'child', 'legal aid', 'child marriage', 'gbv', 'domestic violence'],
                'source' => 'Law of the Child Act 2009; Tanzania Police; Ministry of Community Development, Gender, Women and Special Groups',
            ],

            // ------------------------------------------------------------ TECHNOLOGY
            [
                'title' => 'Usajili wa laini ya simu na kulinda akaunti zako',
                'category' => 'technology', 'language' => 'sw',
                'content' => 'Laini zote za simu Tanzania lazima zisajiliwe kwa alama za vidole na NIN ya NIDA (watoto chini ya 18 kupitia mzazi). Laini isiyosajiliwa huzimwa. Mtu mmoja anaruhusiwa laini chache tu kwa kila mtandao; angalia laini zilizosajiliwa kwa jina lako kwa *106# na uzime usizozijua. Laini ikipotea: piga huduma kwa wateja (Vodacom 100, Yas/Tigo 100, Airtel 100, Halotel 100) kuizuia, kisha pata laini mbadala kwa kitambulisho. Usalama: tumia PIN ya simu na ya pesa isiyo tarehe ya kuzaliwa, usibonyeze viungo vya ujumbe usiovijua, washa uthibitisho wa hatua mbili WhatsApp (Mipangilio > Akaunti > Uthibitisho wa hatua mbili). Malalamiko ya huduma za mawasiliano: kwanza kwa kampuni, kisha TCRA (tcra.go.tz).',
                'keywords' => ['laini', 'sim', 'kusajili laini', 'nida', '106', 'simu imepotea', 'whatsapp', 'nywila', 'udukuzi', 'tcra', 'bando'],
                'source' => 'TCRA - tcra.go.tz',
            ],

            // ------------------------------------------------------------ TRANSPORT
            [
                'title' => 'Faini za trafiki, leseni ya udereva na ajali barabarani',
                'category' => 'transport', 'language' => 'sw',
                'content' => 'Faini ya kawaida ya makosa ya barabarani ni TZS 30,000 kwa kila kosa na hulipwa kwa control number (ujumbe wa SMS kutoka mfumo wa polisi), kwa pesa za simu au benki, si fedha taslimu kwa askari; unaweza kuhakiki faini kwa namba ya gari kupitia mfumo wa TMS. Leseni ya udereva: jifunze chuo cha udereva, fanya mtihani wa nadharia na vitendo wa Polisi wa Usalama Barabarani, kisha leseni hutolewa na TRA kwa ada kulingana na daraja (A pikipiki, B magari madogo, C magari makubwa, D mabasi). Ukipata ajali: hakikisha usalama, piga 112/115, usiondoe magari kabla ya polisi (isipokuwa kuzuia hatari), chukua picha na majina ya mashahidi, ripoti kituo cha polisi ndani ya saa 24 na pata ripoti ya ajali kwa ajili ya bima. Bima ya gari ya lazima ni ya mtu wa tatu (third party).',
                'keywords' => ['faini', 'trafiki', 'leseni ya udereva', 'ajali', 'bima ya gari', 'tms', 'control number', 'polisi wa barabarani', 'bodaboda'],
                'source' => 'Sheria ya Usalama Barabarani Sura 168; Jeshi la Polisi; TRA',
            ],

            // ------------------------------------------------------------ GENERAL
            [
                'title' => 'Tanzania kwa ufupi: historia na taarifa za msingi',
                'category' => 'general', 'language' => 'sw',
                'content' => 'Tanganyika ilipata uhuru 9 Desemba 1961 (Rais wa kwanza Mwalimu Julius Nyerere) na Zanzibar ilipata mapinduzi 12 Januari 1964; ziliungana 26 Aprili 1964 kuunda Jamhuri ya Muungano wa Tanzania. Makao makuu ni Dodoma; jiji kubwa ni Dar es Salaam. Sensa ya 2022 ilihesabu watu takriban milioni 61.7. Lugha ya taifa ni Kiswahili. Rais wa sasa ni Samia Suluhu Hassan (tangu Machi 2021). Mlima Kilimanjaro (mita 5,895) ndio mlima mrefu zaidi Afrika; Ziwa Victoria ndilo ziwa kubwa zaidi Afrika; Hifadhi ya Serengeti na Ngorongoro ni maarufu duniani. Tanzania ni mwanachama wa Jumuiya ya Afrika Mashariki (EAC), SADC na Umoja wa Afrika. Sikukuu za taifa: Mapinduzi ya Zanzibar (12 Jan), Muungano (26 Apr), Saba Saba (7 Jul), Nane Nane (8 Ago), Nyerere (14 Okt), Uhuru (9 Des).',
                'keywords' => ['tanzania', 'uhuru', 'muungano', 'nyerere', 'rais', 'dodoma', 'sensa', 'kilimanjaro', 'sikukuu', 'historia', 'idadi ya watu'],
                'source' => 'Ofisi ya Taifa ya Takwimu (NBS); Ikulu',
            ],
            [
                'title' => 'Tanzania at a glance: history and key facts',
                'category' => 'general', 'language' => 'en',
                'content' => 'Tanganyika gained independence on 9 December 1961 (first President Mwalimu Julius Nyerere); the Zanzibar Revolution was on 12 January 1964; the two united on 26 April 1964 to form the United Republic of Tanzania. The capital is Dodoma; the largest city is Dar es Salaam. The 2022 census counted about 61.7 million people. Swahili is the national language. The current President is Samia Suluhu Hassan (since March 2021). Mount Kilimanjaro (5,895 m) is Africa\'s highest mountain; Lake Victoria is Africa\'s largest lake; Serengeti and Ngorongoro are world famous.
```

```
Tanzania belongs to the East African Community, SADC and the African Union. National holidays: Zanzibar Revolution (12 Jan), Union Day (26 Apr), Saba Saba (7 Jul), Nane Nane (8 Aug), Nyerere Day (14 Oct), Independence (9 Dec).',
                'keywords' => ['tanzania', 'independence', 'union', 'nyerere', 'president', 'dodoma', 'census', 'kilimanjaro', 'holidays', 'history', 'population'],
                'source' => 'National Bureau of Statistics (NBS); State House',
            ],
        ];

        foreach ($entries as $e) {
            KnowledgeEntry::query()->updateOrCreate(
                ['title' => $e['title'], 'language' => $e['language']],
                array_merge($e, ['is_active' => true, 'summary' => $e['summary'] ?? \Illuminate\Support\Str::limit($e['content'], 160)])
            );
        }

        $this->command?->info('Knowledge entries seeded: ' . count($entries));
    }
}
```

66 database/seeders/LocalResourceSeeder.php

41 lines

```php
<?php

namespace Database\Seeders;

use App\Models\LocalResource;
use Illuminate\Database\Seeder;

/**
 * Starter place-bound services. Run `php artisan huru:import-legal-aid`
 * to pull the full Mama Samia Legal Aid Campaign provider list.
 */
class LocalResourceSeeder extends Seeder
{
    public function run(): void
    {
        $resources = [
            // Legal aid (carried over from the previous platform)
            ['HAKI MAENDELEO', 'legal_aid', 'dar es salaam', 'kinondoni', 'Sinza', 'Plot 512, Sinza Madukani, Wilaya ya Kinondoni (karibu na Sinza Mori).', '+255 754 555 555', 'info@hakimaendeleo.or.tz', 'seed'],
            ['GRACE FOUNDATION', 'legal_aid', 'dar es salaam', 'kinondoni', 'Mwenge', 'S.L.P. 31238, Mwenge (Josam House), Wilaya ya Kinondoni.', '+255 222 777 777', 'info@gracefoundation.or.tz', 'seed'],
            ['DIGNITY KWANZA - COMMUNITY SOLUTIONS', 'legal_aid', 'dar es salaam', 'kinondoni', 'Mikocheni', 'S.L.P. 33035, Mikocheni B, Wilaya ya Kinondoni.', '+255 784 888 888', 'info@dignitykwanza.org', 'seed'],
            ['KAHAMA PARALEGAL AID ORGANIZATION (KAPAO)', 'legal_aid', 'shinyanga', 'kahama', null, 'Ofisi za KAPAO, Wilaya ya Kahama, Mkoa wa Shinyanga.', '+255 767 994457', 'kahamaparalegal@gmail.com', 'seed'],

            // Referral hospitals (phone numbers to be confirmed by the operator)
            ['Hospitali ya Taifa Muhimbili (MNH)', 'health', 'dar es salaam', 'ilala', 'Upanga', 'Upanga, Ilala, Dar es Salaam. Hospitali ya rufaa ya taifa.', null, null, 'seed'],
            ['Hospitali ya Rufaa ya Kanda Bugando', 'health', 'mwanza', 'nyamagana', null, 'Bugando Hill, Nyamagana, Mwanza. Hospitali ya rufaa ya Kanda ya Ziwa.', null, null, 'seed'],
            ['Hospitali ya Rufaa ya Kanda KCMC', 'health', 'kilimanjaro', 'moshi', null, 'Moshi, Kilimanjaro. Hospitali ya rufaa ya Kanda ya Kaskazini.', null, null, 'seed'],
            ['Hospitali ya Benjamin Mkapa', 'health', 'dodoma', 'dodoma', null, 'Chuo Kikuu cha Dodoma, Dodoma. Hospitali ya rufaa ya kanda.', null, null, 'seed'],
            ['Hospitali ya Rufaa ya Kanda Mbeya', 'health', 'mbeya', 'mbeya', null, 'Mbeya mjini. Hospitali ya rufaa ya Nyanda za Juu Kusini.', null, null, 'seed'],
            ['Hospitali ya Mnazi Mmoja', 'health', 'mjini magharibi', 'mjini', null, 'Mjini Unguja, Zanzibar. Hospitali ya rufaa ya Zanzibar.', null, null, 'seed'],
        ];

        foreach ($resources as [$name, $category, $region, $district, $ward, $location, $phone, $email, $source]) {
            LocalResource::query()->updateOrCreate(
                ['name' => $name],
                compact('category', 'region', 'district', 'ward', 'location', 'phone', 'email', 'source') + ['is_active' => true]
            );
        }

        $this->command?->info('Local resources seeded: ' . count($resources));
    }
}
```

67 database/seeders/PromptTemplateSeeder.php

39 lines

```php
<?php

namespace Database\Seeders;

use App\Models\PromptTemplate;
use Illuminate\Database\Seeder;

class PromptTemplateSeeder extends Seeder
{
    public function run(): void
    {
        $templates = [
            ['general', 'sw', 'Wewe ni {app_name}, msaidizi wa kuaminika wa kila siku kwa wananchi wa Tanzania. Unajibu swali lolote la mada yoyote: maisha ya kila siku, masomo, kazi, familia, sheria, afya, kilimo, fedha, teknolojia au jambo lolote la udadisi. Unazungumza kama jirani Mtanzania mwenye maarifa na heshima: wazi, moja kwa moja, mkarimu, bila kudharau. Unafahamu vizuri jinsi mambo yanavyofanyika Tanzania na unatoa hatua za vitendo zinazowezekana kwa mwananchi wa kawaida.'],
            ['general', 'en', 'You are {app_name}, a trusted everyday helper for the people of Tanzania. You answer any question on any subject: daily life, school subjects, work, family, law, health, farming, money, technology or simple curiosity. You speak like a knowledgeable, respectful Tanzanian neighbour: clear, direct, warm, never condescending. You understand how things actually work in Tanzania and give practical steps an ordinary citizen can take.'],

            ['legal', 'sw', 'Wewe ni {app_name}, mwelimishaji wa sheria na haki kwa wananchi wa Tanzania. Unaeleza sheria za Tanzania kwa Kiswahili rahisi, unaonyesha hatua halisi za kuchukua na ofisi za kuanzia, na unamshauri mwananchi aonane na mtoa msaada wa kisheria au wakili pale jambo linapohitaji. Wewe si wakili wake; unatoa maelezo ya jumla yanayomsaidia kuelewa haki zake na kuchukua hatua kwa usalama.'],
            ['legal', 'en', 'You are {app_name}, a law and rights educator for the people of Tanzania. You explain Tanzanian law in simple language, show the real steps to take and the office to start at, and advise seeing a legal aid provider or advocate when the matter needs one. You are not the citizen\'s lawyer; you give general information that helps them understand their rights and act safely.'],

            ['health', 'sw', 'Wewe ni {app_name}, mtoa elimu ya afya kwa jamii ya Tanzania. Unatoa taarifa za afya za jumla zinazokubalika (Wizara ya Afya, WHO) kwa lugha rahisi, unaonyesha dalili za hatari zinazohitaji kwenda kituo cha afya mara moja, na unaelekeza huduma zilizopo karibu. Wewe si daktari na husemi dozi za dawa za kuandikiwa; unasisitiza kuonana na mtaalamu wa afya kwa uchunguzi.'],
            ['health', 'en', 'You are {app_name}, a community health educator for Tanzania. You give generally accepted health information (Ministry of Health, WHO) in simple words, point out danger signs that need a health facility immediately, and direct people to the care available near them. You are not a doctor and do not give prescription dosages; you always encourage seeing a health worker for diagnosis.'],

            ['education', 'sw', 'Wewe ni {app_name}, mwalimu msaidizi mvumilivu kwa wanafunzi, wazazi na walimu wa Tanzania. Unafundisha somo lolote (hisabati, sayansi, lugha, historia, jiografia, biashara, TEHAMA) kwa hatua rahisi na mifano ya Kitanzania, kwa kufuata mitaala ya Tanzania (NECTA, TIE). Unaeleza pia taratibu za shule, mitihani, mikopo ya HESLB na vyuo.'],
            ['education', 'en', 'You are {app_name}, a patient tutor for Tanzanian students, parents and teachers. You teach any subject (mathematics, sciences, languages, history, geography, commerce, ICT) step by step with Tanzanian examples, following the Tanzanian curriculum (NECTA, TIE). You also explain school procedures, examinations, HESLB loans and college admissions.'],

            ['agriculture', 'sw', 'Wewe ni {app_name}, afisa ugani wa kidijitali kwa wakulima, wafugaji na wavuvi wa Tanzania. Unatoa ushauri wa vitendo kulingana na misimu, udongo na mazao ya eneo husika, unaonyesha wapi pa kupata mbegu bora, pembejeo, chanjo za mifugo na masoko, na unaelekeza kwa afisa ugani wa kata/wilaya, TARI na TMA.'],
            ['agriculture', 'en', 'You are {app_name}, a digital extension officer for Tanzanian farmers, livestock keepers and fishers. You give practical advice matched to local seasons, soils and crops, show where to find certified seed, inputs, livestock vaccines and markets, and point to the ward/district extension officer, TARI and TMA.'],
        ];

        foreach ($templates as [$category, $language, $text]) {
            $name = ucfirst($category) . ' (' . strtoupper($language) . ')';
            PromptTemplate::query()->updateOrCreate(
                ['name' => $name],
                ['category' => $category, 'language' => $language, 'template' => $text, 'is_active' => true]
            );
        }

        $this->command?->info('Prompt templates seeded: ' . count($templates));
    }
}
```

68 database/seeders/ReferenceContactSeeder.php

84 lines

```php
<?php

namespace Database\Seeders;

use App\Models\ReferenceContact;
use Illuminate\Database\Seeder;

/**
 * National directory. Entries with verified_at set are universally known;
 * the rest should be checked by the operator (the admin panel flags them).
 */
class ReferenceContactSeeder extends Seeder
{
    public function run(): void
    {
        $verified = now();

        $contacts = [
            // Emergency
            ['Polisi (dharura) / Police emergency', 'police', '112', null, null, null, 'Namba ya dharura ya polisi, bure kutoka mtandao wowote.', 'Police emergency number, free from any network.', true, $verified, 1],
            ['Zimamoto na uokoaji / Fire and rescue', 'police', '114', null, null, null, 'Moto, uokoaji na majanga.', 'Fire, rescue and disasters.', true, $verified, 2],
            ['Gari la wagonjwa / Ambulance', 'health', '115', null, null, null, 'Dharura za kiafya na gari la wagonjwa.', 'Medical emergencies and ambulance.', true, $verified, 3],
            ['Msaada kwa Mtoto / National Child Helpline (C-Sema)', 'family', '116', null, null, 'https://www.sematanzania.org', 'Bure, saa 24, kwa ukatili au hatari kwa watoto na ukatili wa kijinsia.', 'Free, 24 hours, for violence or danger to children and gender-based violence.', true, $verified, 4],

            // Legal
            ['Kampeni ya Msaada wa Kisheria ya Mama Samia (Wizara ya Katiba na Sheria)', 'legal', null, null, 'km@katiba.go.tz', 'https://www.mslac.or.tz', 'Madawati ya msaada wa kisheria bure ngazi ya wilaya na mikoa; orodha ya watoa huduma ipo mslac.or.tz. S.L.P. 315 Dodoma.', 'Free legal aid desks at district and regional level; provider list at mslac.or.tz. P.O. Box 315 Dodoma.', false, null, 10],
            ['Ofisi ya Mwanasheria Mkuu wa Serikali (OAG)', 'legal', '+255 26 296 3647', null, 'info@oag.go.tz', 'https://www.agctz.go.tz', 'Mji wa Serikali Mtumba, S.L.P. 11492, Dodoma.', 'Mtumba Government City, P.O. Box 11492, Dodoma.', false, null, 11],
            ['Tume ya Haki za Binadamu na Utawala Bora (CHRAGG)', 'legal', null, null, null, 'https://www.chragg.go.tz', 'Malalamiko ya ukiukwaji wa haki za binadamu na utawala mbaya na ofisi za umma.', 'Complaints about human rights violations and maladministration by public offices.', false, null, 12],
            ['Kituo cha Sheria na Haki za Binadamu (LHRC)', 'legal', null, null, null, 'https://www.humanrights.or.tz', 'Msaada wa kisheria na elimu ya haki; ofisi Dar es Salaam, Arusha, Dodoma na mikoani.', 'Legal aid and rights education; offices in Dar es Salaam, Arusha, Dodoma and regions.', false, null, 13],
            ['Chama cha Wanasheria Wanawake Tanzania (TAWLA)', 'legal', null, null, null, 'https://www.tawla.or.tz', 'Msaada wa kisheria bure hasa kwa wanawake na watoto.', 'Free legal aid, especially for women and children.', false, null, 14],
            ['Kituo cha Msaada wa Kisheria kwa Wanawake (WLAC)', 'legal', null, null, null, 'https://www.wlac.or.tz', 'Msaada wa kisheria kwa wanawake: ndoa, mirathi, ukatili.', 'Legal aid for women: marriage, inheritance, violence.', false, null, 15],
            ['Taasisi ya Kuzuia na Kupambana na Rushwa (TAKUKURU / PCCB)', 'legal', '113', null, null, 'https://www.pccb.go.tz', 'Ripoti rushwa; namba 113 ni bure.', 'Report corruption; 113 is toll free.', false, null, 16],

            // Government
            ['NIDA - Mamlaka ya Vitambulisho vya Taifa', 'government', null, null, null, 'https://www.nida.go.tz', 'Usajili wa kitambulisho cha taifa (NIN). Hakiki hali kwa *152*00#.', 'National ID registration (NIN). Check status via *152*00#.', false, null, 20],
            ['RITA - Wakala wa Usajili, Ufilisi na Udhamini', 'government', null, null, null, 'https://www.rita.go.tz', 'Vyeti vya kuzaliwa, kifo, ndoa na talaka.', 'Birth, death, marriage and divorce certificates.', false, null, 21],
            ['Idara ya Uhamiaji', 'government', null, null, null, 'https://www.immigration.go.tz', 'Pasipoti, viza na vibali vya ukaazi. Maombi: eservices.immigration.go.tz', 'Passports, visas and residence permits. Apply at eservices.immigration.go.tz', false, null, 22],
            ['BRELA - Wakala wa Usajili wa Biashara na Leseni', 'business', null, null, null, 'https://www.brela.go.tz', 'Usajili wa majina ya biashara na kampuni kupitia ORS.', 'Business name and company registration through ORS.', false, null, 23],
            ['TANESCO - Shirika la Umeme Tanzania', 'government', null, null, null, 'https://www.tanesco.co.tz', 'Kuunganishwa umeme, LUKU na hitilafu za umeme.', 'Electricity connection, LUKU tokens and faults.', false, null, 24],
            ['Sekretarieti ya Ajira katika Utumishi wa Umma', 'employment', null, null, null, 'https://www.ajira.go.tz', 'Nafasi rasmi za kazi serikalini; maombi ni bure.', 'Official public service vacancies; applications are free.', false, null, 25],

```

```
            // Finance
            ['TRA - Mamlaka ya Mapato Tanzania', 'finance', '0800 750 075', '0800 780 078', null, 'https://www.tra.go.tz', 'TIN, kodi, leseni za udereva, usajili wa magari. Namba za bure.', 'TIN, taxes, driving licences, vehicle registration. Toll-free numbers.', false, null, 30],
            ['Benki Kuu ya Tanzania (BoT)', 'finance', null, null, null, 'https://www.bot.go.tz', 'Orodha ya benki na watoa mikopo waliosajiliwa; malalamiko ya huduma za fedha.', 'List of licensed banks and lenders; financial service complaints.', false, null, 31],
            ['NSSF - Mfuko wa Taifa wa Hifadhi ya Jamii', 'employment', null, null, null, 'https://www.nssf.or.tz', 'Michango na mafao ya wafanyakazi wa sekta binafsi na wanaojiajiri.', 'Contributions and benefits for private sector and self-employed workers.', false, null, 32],

            // Health
            ['NHIF - Mfuko wa Taifa wa Bima ya Afya', 'health', null, null, null, 'https://www.nhif.or.tz', 'Bima ya afya ya umma; vifurushi vya hiari kwa wananchi.', 'Public health insurance; voluntary packages for citizens.', false, null, 40],
            ['Wizara ya Afya', 'health', null, null, null, 'https://www.moh.go.tz', 'Miongozo ya afya, chanjo na taarifa za milipuko.', 'Health guidelines, vaccination and outbreak information.', false, null, 41],
            ['TMDA - Mamlaka ya Dawa na Vifaa Tiba', 'health', null, null, null, 'https://www.tmda.go.tz', 'Usalama wa dawa, vyakula na vipodozi; ripoti dawa bandia.', 'Safety of medicines, food and cosmetics; report counterfeit medicines.', false, null, 42],

            // Education
            ['NECTA - Baraza la Mitihani la Tanzania', 'education', null, null, null, 'https://www.necta.go.tz', 'Matokeo ya mitihani ya taifa na ratiba.', 'National examination results and timetables.', false, null, 50],
            ['HESLB - Bodi ya Mikopo ya Wanafunzi wa Elimu ya Juu', 'education', null, null, null, 'https://www.heslb.go.tz', 'Mikopo ya elimu ya juu; maombi kupitia OLAMS.', 'Higher education student loans; apply through OLAMS.', false, null, 51],
            ['TCU - Tume ya Vyuo Vikuu Tanzania', 'education', null, null, null, 'https://www.tcu.go.tz', 'Vyuo vikuu vilivyosajiliwa na mwongozo wa udahili.', 'Accredited universities and admission guidebook.', false, null, 52],
            ['VETA - Mamlaka ya Elimu na Mafunzo ya Ufundi Stadi', 'education', null, null, null, 'https://www.veta.go.tz', 'Mafunzo ya ufundi stadi na vyuo vya VETA mikoani.', 'Vocational training and VETA colleges in the regions.', false, null, 53],

            // Agriculture
            ['TARI - Taasisi ya Utafiti wa Kilimo Tanzania', 'agriculture', null, null, null, 'https://www.tari.go.tz', 'Teknolojia za kilimo, mbegu bora na ushauri wa mazao.', 'Agricultural technologies, improved seed and crop advice.', false, null, 60],
            ['TMA - Mamlaka ya Hali ya Hewa Tanzania', 'agriculture', null, null, null, 'https://www.meteo.go.tz', 'Utabiri wa mvua na hali ya hewa kwa misimu ya kilimo.', 'Rainfall and weather forecasts for farming seasons.', false, null, 61],
            ['Wizara ya Kilimo', 'agriculture', null, null, null, 'https://www.kilimo.go.tz', 'Sera, pembejeo za ruzuku na masoko ya mazao.', 'Policy, subsidised inputs and crop markets.', false, null, 62],

            // Technology
            ['TCRA - Mamlaka ya Mawasiliano Tanzania', 'technology', null, null, null, 'https://www.tcra.go.tz', 'Malalamiko ya huduma za simu na intaneti, usajili wa laini.', 'Complaints about phone and internet services, SIM registration.', false, null, 70],

            // Transport
            ['LATRA - Mamlaka ya Udhibiti Usafiri Ardhini', 'transport', null, null, null, 'https://www.latra.go.tz', 'Nauli za mabasi, leseni za usafiri na malalamiko ya abiria.', 'Bus fares, transport licences and passenger complaints.', false, null, 80],
            ['Polisi wa Usalama Barabarani (Traffic Police)', 'transport', '112', null, null, null, 'Ajali na makosa ya barabarani; faini hulipwa kwa control number.', 'Accidents and traffic offences; fines are paid via control number.', false, null, 81],
        ];

        foreach ($contacts as [$name, $category, $phone, $alt, $email, $web, $sw, $en, $emergency, $verifiedAt, $order]) {
            ReferenceContact::query()->updateOrCreate(
                ['name' => $name],
                [
                    'category' => $category, 'phone' => $phone, 'alt_phone' => $alt, 'email' => $email, 'website' => $web,
                    'description_sw' => $sw, 'description_en' => $en, 'is_emergency' => $emergency,
                    'verified_at' => $verifiedAt, 'sort_order' => $order, 'is_active' => true,
                ]
            );
        }

        $this->command?->info('Reference contacts seeded: ' . count($contacts));
    }
}
```

69 database/seeders/SettingsSeeder.php

25 lines

```php
<?php

namespace Database\Seeders;

use App\Models\SystemSetting;
use App\Support\Settings;
use Illuminate\Database\Seeder;

class SettingsSeeder extends Seeder
{
    public function run(): void
    {
        foreach (Settings::schema() as $key => $def) {
            SystemSetting::query()->firstOrCreate(['key' => $key], ['value' => $def['default']]);
        }

        // Environment can pre-fill the operator contact.
        if ($email = env('ADMIN_EMAIL')) {
            SystemSetting::query()->updateOrCreate(['key' => 'contact_email'], ['value' => $email]);
        }

        Settings::flush();
        $this->command?->info('Settings seeded (' . count(Settings::schema()) . ' keys).');
    }
}
```

70 package.json

17 lines

```
{
    "$schema": "https://www.schemastore.org/package.json",
    "private": true,
    "type": "module",
    "scripts": {
        "build": "vite build",
        "dev": "vite"
    },
    "devDependencies": {
        "@tailwindcss/vite": "^4.0.0",
        "axios": "^1.11.0",
        "concurrently": "^9.0.1",
        "laravel-vite-plugin": "^2.0.0",
        "tailwindcss": "^4.0.0",
        "vite": "^7.3.3"
    }
}
```

71 **phpunit.xml** 35 lines

```xml
<?xml version="1.0" encoding="UTF-8"?>
<phpunit xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
         xsi:noNamespaceSchemaLocation="vendor/phpunit/phpunit/phpunit.xsd"
         bootstrap="vendor/autoload.php"
         colors="true"
>
    <testsuites>
        <testsuite name="Unit">
            <directory>tests/Unit</directory>
        </testsuite>
        <testsuite name="Feature">
            <directory>tests/Feature</directory>
        </testsuite>
    </testsuites>
    <source>
        <include>
            <directory>app</directory>
        </include>
    </source>
    <php>
        <env name="APP_ENV" value="testing"/>
        <env name="APP_MAINTENANCE_DRIVER" value="file"/>
        <env name="BCRYPT_ROUNDS" value="4"/>
        <env name="BROADCAST_CONNECTION" value="null"/>
        <env name="CACHE_STORE" value="array"/>
        <env name="DB_CONNECTION" value="sqlite"/>
        <env name="DB_DATABASE" value=":memory:"/>
        <env name="MAIL_MAILER" value="array"/>
        <env name="QUEUE_CONNECTION" value="sync"/>
        <env name="SESSION_DRIVER" value="array"/>
        <env name="PULSE_ENABLED" value="false"/>
        <env name="TELESCOPE_ENABLED" value="false"/>
        <env name="NIGHTWATCH_ENABLED" value="false"/>
    </php>
</phpunit>
```

72 public/manifest.json

16 lines

```
{
    "name": "Huru SMS",
    "short_name": "Huru SMS",
    "description": "Uliza lolote kuhusu maisha Tanzania. Kwa SMS 15054 au mtandaoni.",
    "start_url": "/chat",
    "scope": "/",
    "display": "standalone",
    "lang": "sw",
    "background_color": "#f8fafc",
    "theme_color": "#15803d",
    "icons": [
        { "src": "/logo.svg", "sizes": "192x192", "type": "image/svg+xml" },
        { "src": "/logo.svg", "sizes": "512x512", "type": "image/svg+xml" },
        { "src": "/logo.svg", "sizes": "any", "type": "image/svg+xml", "purpose": "any maskable" }
    ]
}
```

73 public/robots.txt

6 lines

```
User-agent: *
Allow: /
Disallow: /admin
Disallow: /chat/
Disallow: /api/
Sitemap: /sitemap.xml
```

74 public/sw.js

40 lines

```
/* Huru SMS service worker: app shell cached, API never cached, offline fallback page. */
const VERSION = 'huru-v1';
const SHELL = ['/', '/chat', '/offline', '/logo.svg', '/manifest.json'];

self.addEventListener('install', (event) => {
    event.waitUntil(caches.open(VERSION).then((c) => c.addAll(SHELL)).then(() => self.skipWaiting()));
});

self.addEventListener('activate', (event) => {
    event.waitUntil(
        caches.keys().then((keys) => Promise.all(keys.filter((k) => k !== VERSION).map((k) => caches.delete(k)))).then(() => self.clients.claim())
    );
});

self.addEventListener('fetch', (event) => {
    const req = event.request;
    const url = new URL(req.url);

    if (req.method !== 'GET' || url.origin !== self.location.origin) return;
    // Never cache dynamic data or the admin panel.
    if (url.pathname.startsWith('/chat/') || url.pathname.startsWith('/admin') || url.pathname.startsWith('/api') || url.pathname.startsWith('/community')) return;

    if (req.mode === 'navigate') {
        event.respondWith(
            fetch(req)
                .then((res) => { const copy = res.clone(); caches.open(VERSION).then((c) => c.put(req, copy)); return res; })
                .catch(() => caches.match(req).then((hit) => hit || caches.match('/offline')))
        );
        return;
    }

    event.respondWith(
        caches.match(req).then((hit) => hit || fetch(req).then((res) => {
            if (res.ok && (url.pathname.startsWith('/build/') || /\.(svg|png|ico|css|js|woff2?)$/.test(url.pathname))) {
                const copy = res.clone(); caches.open(VERSION).then((c) => c.put(req, copy));
            }
            return res;
        }))
    );
});
```

75 resources/css/app.css

11 lines

```
@import 'tailwindcss';

@source '../../vendor/laravel/framework/src/Illuminate/Pagination/resources/views/*.blade.php';
@source '../../storage/framework/views/*.php';
@source '../**/*.blade.php';
@source '../**/*.js';

@theme {
    --font-sans: 'Instrument Sans', ui-sans-serif, system-ui, sans-serif, 'Apple Color Emoji', 'Segoe UI Emoji',
        'Segoe UI Symbol', 'Noto Color Emoji';
}
```

76 resources/js/app.js

1 lines

```
1  import './bootstrap';
```

77 **resources/js/bootstrap.js** 4 lines

```
import axios from 'axios';
window.axios = axios;

window.axios.defaults.headers.common['X-Requested-With'] = 'XMLHttpRequest';
```

78 resources/views/admin/contacts/form.blade.php

30 lines

```
@extends('layouts.admin', ['title' => $contact->exists ? 'Edit contact' : 'New contact'])

@section('content')
<div class="card" style="max-width:860px">
    <form method="POST" action="{{ $contact->exists ? route('admin.contacts.update', $contact) : route('admin.contacts.store') }}">
        @csrf
        @if($contact->exists) @method('PUT') @endif
        <div class="field"><label>Name</label><input type="text" name="name" value="{{ old('name', $contact->name) }}" required maxlength="150"></div>
        <div class="grid g3">
            <div class="field"><label>Category</label><select name="category">@foreach($categories as $c)<option value="{{ $c }}" @selected(old('category', $contact->category) === $c)>{{ ucfirst($c) }}</option>@endforeach</select></div>
            <div class="field"><label>Phone</label><input type="text" name="phone" value="{{ old('phone', $contact->phone) }}" maxlength="60"></div>
            <div class="field"><label>Alternative phone</label><input type="text" name="alt_phone" value="{{ old('alt_phone', $contact->alt_phone) }}" maxlength="60"></div>
        </div>
        <div class="grid g2">
            <div class="field"><label>Email</label><input type="email" name="email" value="{{ old('email', $contact->email) }}"></div>
            <div class="field"><label>Website</label><input type="url" name="website" value="{{ old('website', $contact->website) }}" placeholder="https://"></div>
        </div>
        <div class="field"><label>Description (Swahili)</label><textarea name="description_sw" rows="2">{{ old('description_sw', $contact->description_sw) }}</textarea></div>
        <div class="field"><label>Description (English)</label><textarea name="description_en" rows="2">{{ old('description_en', $contact->description_en) }}</textarea></div>
        <div class="grid g3">
            <div class="field"><label>Sort order</label><input type="number" name="sort_order" value="{{ old('sort_order', $contact->sort_order ?? 100) }}" min="0" max="1000"></div>
            <div class="field" style="padding-top:26px"><label class="check"><input type="checkbox" name="is_emergency" value="1" @checked(old('is_emergency', $contact->is_emergency))> Emergency number</label></div>
            <div class="field" style="padding-top:26px"><label class="check"><input type="checkbox" name="verified" value="1" @checked(old('verified', (bool) $contact->verified_at))> Verified by operator</label></div>
        </div>
        <div class="field"><label class="check"><input type="checkbox" name="is_active" value="1" @checked(old('is_active', $contact->is_active))> Active</label></div>
        <button class="btn btn-p" type="submit">Save</button>
        <a class="btn" href="{{ route('admin.contacts.index') }}">Cancel</a>
    </form>
</div>
@endsection
```

79 resources/views/admin/contacts/index.blade.php

31 lines

```
@extends('layouts.admin', ['title' => 'National directory'])

@section('content')
<div class="card">
    <div class="card-h"><div><h2>Official institutions and hotlines</h2><p>Country-wide contacts the engine may quote. Unverified rows are marked; confirm them before relying on them.</p></div><a class="btn btn-p" href="{{ route('admin.contacts.create') }}">+ New contact</a></div>
    <form class="filters" method="GET">
        <select name="category" onchange="this.form.submit()"><option value="">All categories</option>@foreach($categories as $c)<option value="{{ $c }}" @selected(request('category') === $c)>{{ ucfirst($c) }}</option>@endforeach</select>
    </form>
    <table>
        <thead><tr><th>Name</th><th>Category</th><th>Phone</th><th>Email / Web</th><th>Flags</th><th></th></tr></thead>
        <tbody>
        @forelse($contacts as $c)
            <tr>
                <td><strong>{{ $c->name }}</strong><div style="font-size:.76rem;color:var(--muted)">{{ \Illuminate\Support\Str::limit($c->description_en ?: $c->description_sw, 100) }}</div></td>
                <td>{{ ucfirst($c->category) }}</td>
                <td style="white-space:nowrap">{{ $c->phone }}@if($c->alt_phone)<br>{{ $c->alt_phone }}@endif</td>
                <td style="font-size:.78rem">{{ $c->email }}@if($c->website)<br><a href="{{ $c->website }}" target="_blank" rel="noopener">{{ parse_url($c->website, PHP_URL_HOST) }}</a>@endif</td>
                <td style="white-space:nowrap">@if($c->is_emergency)<span class="badge b-red">emergency</span>@endif{!! $c->verified_at ? '<span class="badge b-green">verified</span>' : '<span class="badge b-warn">unverified</span>' !!} @if(!$c->is_active)<span class="badge b-gray">off</span>@endif</td>
                <td style="white-space:nowrap">
                    <a class="btn btn-sm" href="{{ route('admin.contacts.edit', $c) }}">Edit</a>
                    <form class="inline" method="POST" action="{{ route('admin.contacts.verify', $c) }}">@csrf @method('PATCH')<button class="btn btn-sm" type="submit">{{ $c->verified_at ? 'Unverify' : 'Verify' }}</button></form>
                    <form class="inline" method="POST" action="{{ route('admin.contacts.destroy', $c) }}" onsubmit="return confirm('Delete this contact?')">@csrf @method('DELETE')<button class="btn btn-sm btn-d" type="submit">Delete</button></form>
                </td>
            </tr>
        @empty
            <tr><td colspan="6" style="text-align:center;color:var(--muted)">No contacts.</td></tr>
        @endforelse
        </tbody>
    </table>
</div>
@endsection
```

80 resources/views/admin/conversations/index.blade.php

37 lines

```
@extends('layouts.admin', ['title' => 'Conversations'])

@section('content')
<div class="card">
    <form class="filters" method="GET">
        <input type="text" name="q" value="{{ request('q') }}" placeholder="Search text, phone or name">
        <select name="category"><option value="">All
topics</option>@foreach(\App\Services\TopicClassifier::CATEGORIES as $k => $l)<option value="{{ $k }}"
@selected(request('category') === $k)>{{ $l['en'] }}</option>@endforeach</select>
        <select name="channel"><option value="">All channels</option><option value="sms"
@selected(request('channel') === 'sms')>SMS</option><option value="web" @selected(request('channel') ===
'web')>Web</option></select>
        <select name="direction"><option value="">Both directions</option><option value="inbound"
@selected(request('direction') === 'inbound')>Questions</option><option value="outbound" @selected(request('direction') ===
'outbound')>Replies</option></select>
        <input type="date" name="date" value="{{ request('date') }}">
        <button class="btn" type="submit">Filter</button>
        <a class="btn" href="{{ route('admin.conversations.index') }}">Reset</a>
    </form>
    <div style="overflow-x:auto">
    <table>
        <thead><tr><th>Time</th><th>Citizen</th><th>Ch.</th><th>Dir.</th><th>Lang</th><th>Topic</th>
<th>Content</th><th>Engine</th></tr></thead>
        <tbody>
        @forelse($messages as $m)
            <tr>
                <td style="white-space:nowrap;color:var(--muted)">{{ $m->created_at-
>timezone('Africa/Dar_es_Salaam')->format('d/m/y H:i') }}</td>
                <td style="white-space:nowrap"><a href="{{ route('admin.conversations.show', $m->user_id) }}">{{
$m->user?->name ?: \App\Support\Phone::mask($m->user?->phone_number) }}</a></td>
                <td><span class="badge b-gray">{{ $m->channel }}</span></td>
                <td>{!! $m->direction === 'inbound' ? '<span class="badge b-green">in</span>' : '<span class="badge
b-blue">out</span>' !!}</td>
                <td>{{ strtoupper($m->language ?? '') }}</td>
                <td style="white-space:nowrap">{{ $m->category ? \App\Services\TopicClassifier::label($m->category,
'en') : '—' }}</td>
                <td class="truncate" title="{{ $m->content }}">{{ $m->content }}</td>
                <td style="white-space:nowrap;font-size:.75rem;color:var(--muted)">@if($m->aiLog){{ $m->aiLog-
>model }} · {{ $m->aiLog->total_tokens }} tok · {{ $m->aiLog->latency_ms }} ms @if($m->aiLog->status !== 'ok')<span
class="badge b-red">{{ $m->aiLog->status }}</span>@endif @endif @if($m->feedback) {{ $m->feedback->rating === 1 ? '👍' :
'👎' }}@endif</td>
            </tr>
        @empty
            <tr><td colspan="8" style="text-align:center;color:var(--muted)">Nothing matches.</td></tr>
        @endforelse
        </tbody>
    </table>
    </div>
    {{ $messages->links('pagination.simple') }}
</div>
@endsection
```

81 resources/views/admin/conversations/show.blade.php

34 lines

```
@extends('layouts.admin', ['title' => 'Conversation'])

@section('content')
<div class="card">
    <div class="card-h">
        <div>
            <h2>{{ $user->name ?: 'Citizen' }} · {{ $user->phone_number }}</h2>
            <p>Language: {{ $user->preferred_language ?: 'auto' }} · Region: {{ $user->region ? ucwords($user->region) : '—' }} · Strikes: {{ $user->abuse_count }} · Last seen: {{ $user->last_seen_at?->diffForHumans() ?? '—' }} @if($user->is_banned)<span class="badge b-red">BANNED</span>@endif @if($user->opted_out)<span class="badge b-warn">opted out</span>@endif</p>
        </div>
        <div style="display:flex;gap:6px">
            <form class="inline" method="POST" action="{{ route('admin.users.ban', $user) }}">@csrf @method('PATCH')<button class="btn btn-sm {{ $user->is_banned ? '' : 'btn-d' }}" type="submit">{{ $user->is_banned ? 'Unblock' : 'Block' }}</button></form>
            <form class="inline" method="POST" action="{{ route('admin.users.strikes', $user) }}">@csrf @method('PATCH')<button class="btn btn-sm" type="submit">Clear strikes</button></form>
            <a class="btn btn-sm" href="{{ route('admin.conversations.index') }}">Back</a>
        </div>
    </div>

    @foreach($messages as $m)
        <div style="border:1px solid var(--border);border-radius:10px;padding:12px 14px;margin-bottom:10px;background:{{ $m->direction === 'inbound' ? '#fff' : 'var(--green-bg)' }}">
            <div style="display:flex;justify-content:space-between;gap:10px;font-size:.75rem;color:var(--muted);margin-bottom:6px;flex-wrap:wrap">
                <span>{!! $m->direction === 'inbound' ? '<span class="badge b-green">question</span>' : '<span class="badge b-blue">reply</span>' !!} <span class="badge b-gray">{{ $m->channel }}</span> {{ $m->category ? \App\Services\TopicClassifier::label($m->category, 'en') : '' }}</span>
                <span>{{ $m->created_at->timezone('Africa/Dar_es_Salaam')->format('d M Y H:i:s') }}</span>
            </div>
            <div style="white-space:pre-wrap;font-size:.92rem">{{ $m->content }}</div>
            @if($m->aiLog)
                <details style="margin-top:8px;font-size:.8rem;color:var(--muted)">
                    <summary style="cursor:pointer">{{ $m->aiLog->model }} · {{ $m->aiLog->status }} · {{ $m->aiLog->prompt_tokens }}+{{ $m->aiLog->completion_tokens }} tokens · {{ $m->aiLog->latency_ms }} ms @if($m->feedback) · feedback {{ $m->feedback->rating === 1 ? '👍' : '👎' }} {{ $m->feedback->comment }}@endif</summary>
                    <div class="mono" style="margin-top:6px">{{ $m->aiLog->prompt }}</div>
                </details>
            @endif
        </div>
    @endforeach
    {{ $messages->links('pagination.simple') }}
</div>
@endsection
```

82 resources/views/admin/dashboard.blade.php

71 lines

```
@extends('layouts.admin', ['title' => 'Dashboard'])

@section('content')
@if(!$health['engine_configured'])<div class="alert a-err">GEMINI_API_KEY is missing. The engine cannot answer until it is set in .env.</div>@endif
@if(!$health['sms_configured'])<div class="alert a-warn">Africa's Talking credentials are missing. SMS replies and OTP codes will not be sent (web login opens without OTP outside production).</div>@endif
@if(!$health['webhook_secret'])<div class="alert a-warn">AT_WEBHOOK_SECRET is empty. Set it and register the callback URL with ?token=… before going live.</div>@endif

<div class="grid g4">
    <div class="stat"><div class="l">Citizens</div><div class="v">{{ number_format($stats['users']) }}</div><div class="s">+{{ $stats['users_today'] }} today</div></div>
    <div class="stat"><div class="l">Questions today</div><div class="v">{{ number_format($stats['questions_today']) }}</div><div class="s">{{ number_format($stats['questions_week']) }} this week</div></div>
    <div class="stat"><div class="l">Channels (7d)</div><div class="v">{{ number_format($stats['sms_week']) }} <span style="font-size:.9rem;color:var(--muted)">SMS</span></div><div class="s">{{ number_format($stats['web_week']) }} web</div></div>
    <div class="stat"><div class="l">Tokens today</div><div class="v">{{ number_format($stats['tokens_today']) }}</div><div class="s">avg {{ $stats['latency_avg'] }} ms · {{ $stats['errors_week'] }} errors (7d)</div></div>
</div>
<div style="height:14px"></div>
<div class="grid g4">
    <div class="stat"><div class="l">Helpful votes</div><div class="v" style="color:var(--green-dark)">{{ $stats['helpful'] }}</div><div class="s">{{ $stats['unhelpful'] }} not helpful</div></div>
    <div class="stat"><div class="l">Blocked citizens</div><div class="v" style="color:var(--danger)">{{ $stats['banned'] }}</div><div class="s">abuse strike system</div></div>
    <div class="stat"><div class="l">Engine</div><div class="v" style="font-size:1rem;margin-top:10px">{{ $health['engine_configured'] ? '● Configured' : '○ Missing key' }}</div><div class="s">queue: {{ $health['queue'] }}</div></div>
    <div class="stat"><div class="l">SMS gateway</div><div class="v" style="font-size:1rem;margin-top:10px">{{ $health['sms_configured'] ? '● Configured' : '○ Not configured' }}</div><div class="s">webhook secret {{ $health['webhook_secret'] ? 'set' : 'missing' }}</div></div>
</div>
<div style="height:18px"></div>

<div class="grid g2">
    <div class="card">
        <div class="card-h"><div><h2>Questions per day</h2><p>Last 14 days, both channels</p></div></div>
        @php $max = max(1, (int) ($daily->max() ?? 1)); @endphp
        <div class="spark">
            @for($i = 13; $i >= 0; $i--)
                @php $day = now()->subDays($i)->toDateString(); $v = (int) ($daily[$day] ?? 0); @endphp
                <div style="height:{{ max(3, round($v / $max * 100)) }}%" title="{{ $day }}: {{ $v }}"><span>{{ now()->subDays($i)->format('d') }}</span></div>
            @endfor
        </div>
        <div style="height:20px"></div>
    </div>
    <div class="card">
        <div class="card-h"><div><h2>Topics this week</h2><p>Detected by the topic classifier</p></div></div>
        @php $top = max(1, (int) ($byCategory->max('total') ?? 1)); @endphp
        <div class="bars">
            @forelse($byCategory as $row)
                <div class="bar"><span>{{ $row['label'] }}</span><div class="t"><div class="f" style="width:{{ round($row['total'] / $top * 100) }}%"></div></div><span>{{ $row['total'] }}</span></div>
            @empty
                <p style="color:var(--muted);font-size:.85rem">No questions yet.</p>
            @endforelse
        </div>
    </div>
</div>

<div class="card">
    <div class="card-h"><div><h2>Recent interactions</h2><p>Latest 25 messages across SMS and web</p></div><a class="btn btn-sm" href="{{ route('admin.conversations.index') }}">View all</a></div>
    <div style="overflow-x:auto">
    <table>
        <thead><tr><th>Time</th><th>Citizen</th><th>Ch.</th><th>Dir.</th><th>Topic</th><th>Content</th><th>Engine</th></tr></thead>
```

```
        <tbody>
        @forelse($recent as $m)
            <tr>
                <td style="white-space:nowrap;color:var(--muted)">{{ $m->created_at->timezone('Africa/Dar_es_Salaam')->format('d/m H:i') }}</td>
                <td><a href="{{ route('admin.conversations.show', $m->user_id) }}">{{ \App\Support\Phone::mask($m->user?->phone_number) }}</a>@if($m->user?->is_banned) <span class="badge b-red">banned</span>@elseif(($m->user?->abuse_count ?? 0) > 0) <span class="badge b-warn">strike {{ $m->user->abuse_count }}</span>@endif</td>
                <td><span class="badge b-gray">{{ $m->channel }}</span></td>
                <td>{!! $m->direction === 'inbound' ? '<span class="badge b-green">in</span>' : '<span class="badge b-blue">out</span>' !!}</td>
                <td>{{ $m->category ? \App\Services\TopicClassifier::label($m->category, 'en') : '—' }}</td>
                <td class="truncate" title="{{ $m->content }}">{{ $m->content }}</td>
                <td style="white-space:nowrap;font-size:.75rem;color:var(--muted)">@if($m->aiLog){{ $m->aiLog->total_tokens }} tok · {{ $m->aiLog->latency_ms }} ms @if($m->aiLog->status !== 'ok')<span class="badge b-red">{{ $m->aiLog->status }}</span>@endif @if($m->feedback) {{ $m->feedback->rating === 1 ? '👍' : '👎' }}@endif @endif</td>
            </tr>
        @empty
            <tr><td colspan="7" style="text-align:center;color:var(--muted)">No messages yet. Send HURU to the shortcode or open the web chat.</td></tr>
        @endforelse
        </tbody>
    </table>
    </div>
</div>
@endsection
```

83 resources/views/admin/knowledge/form.blade.php

22 lines

```
@extends('layouts.admin', ['title' => $entry->exists ? 'Edit knowledge entry' : 'New knowledge entry'])

@section('content')
<div class="card" style="max-width:860px">
    <form method="POST" action="{{ $entry->exists ? route('admin.knowledge.update', $entry) : route('admin.knowledge.store') }}">
        @csrf
        @if($entry->exists) @method('PUT') @endif
        <div class="field"><label>Title</label><input type="text" name="title" value="{{ old('title', $entry->title) }}" required maxlength="250"><div class="hint">Specific and searchable, e.g. "Kitambulisho cha Taifa (NIDA): jinsi ya kujisajili".</div></div>
        <div class="grid g2">
            <div class="field"><label>Topic</label><select name="category">@foreach(\App\Services\TopicClassifier::CATEGORIES as $k => $l)<option value="{{ $k }}" @selected(old('category', $entry->category) === $k)>{{ $l['en'] }} / {{ $l['sw'] }}</option>@endforeach</select></div>
            <div class="field"><label>Language of this entry</label><select name="language"><option value="sw" @selected(old('language', $entry->language) === 'sw')>Swahili</option><option value="en" @selected(old('language', $entry->language) === 'en')>English</option></select></div>
        </div>
        <div class="field"><label>Content</label><textarea name="content" rows="10" required>{{ old('content', $entry->content) }}</textarea><div class="hint">Plain facts with steps, offices and figures. The engine quotes this verbatim as verified knowledge, so only write what you can stand behind.</div></div>
        <div class="field"><label>Summary (optional)</label><input type="text" name="summary" value="{{ old('summary', $entry->summary) }}" maxlength="500"></div>
        <div class="field"><label>Keywords (comma separated)</label><input type="text" name="keywords_text" value="{{ old('keywords_text', implode(', ', (array) $entry->keywords)) }}"><div class="hint">Words citizens would use, in both languages. Title words are added automatically.</div></div>
        <div class="field"><label>Source (optional)</label><input type="text" name="source" value="{{ old('source', $entry->source) }}" maxlength="250" placeholder="e.g. Sheria ya Ardhi Sura 113; nida.go.tz"></div>
        <div class="field"><label class="check"><input type="checkbox" name="is_active" value="1" @checked(old('is_active', $entry->is_active))> Active</label></div>
        <button class="btn btn-p" type="submit">Save</button>
        <a class="btn" href="{{ route('admin.knowledge.index') }}">Cancel</a>
    </form>
</div>
@endsection
```

84 resources/views/admin/knowledge/index.blade.php

58 lines

```
@extends('layouts.admin', ['title' => 'Knowledge base'])

@section('content')
<div class="grid g2">
    <div class="card">
        <div class="card-h"><div><h2>Entries by topic</h2><p>Fact blocks the engine can cite. Keep each one short and sourced.</p></div><a class="btn btn-p" href="{{ route('admin.knowledge.create') }}">+ New entry</a></div>
        <div class="bars">
            @foreach(\App\Services\TopicClassifier::CATEGORIES as $k => $l)
                @php $n = (int) ($counts[$k] ?? 0); @endphp
                <div class="bar"><a href="{{ route('admin.knowledge.index', ['category' => $k]) }}">{{ $l['en'] }}</a><div class="t"><div class="f" style="width:{{ $counts->max() ? round($n / max(1, $counts->max()) * 100) : 0 }}%"></div></div><span>{{ $n }}</span></div>
            @endforeach
        </div>
    </div>
    <div class="card">
        <div class="card-h"><div><h2>Import</h2><p>CSV columns: title, content, category, language, keywords, source, summary. JSON: array of the same keys.</p></div></div>
        <form method="POST" action="{{ route('admin.knowledge.import') }}" enctype="multipart/form-data">
            @csrf
            <div class="field"><label>File (.csv or .json)</label><input type="file" name="file" accept=".csv,.json,.txt" required></div>
            <div class="grid g2">
                <div class="field"><label>Default topic</label><select name="default_category">@foreach(\App\Services\TopicClassifier::CATEGORIES as $k => $l)<option value="{{ $k }}">{{ $l['en'] }}</option>@endforeach</select></div>
                <div class="field"><label>Default language</label><select name="default_language"><option value="sw">Swahili</option><option value="en">English</option></select></div>
            </div>
            <button class="btn" type="submit">Import</button>
        </form>
    </div>
</div>

<div class="card">
    <form class="filters" method="GET">
        <input type="text" name="q" value="{{ request('q') }}" placeholder="Search title or content">
        <select name="category"><option value="">All topics</option>@foreach(\App\Services\TopicClassifier::CATEGORIES as $k => $l)<option value="{{ $k }}" @selected(request('category') === $k)>{{ $l['en'] }}</option>@endforeach</select>
        <select name="language"><option value="">Any language</option><option value="sw" @selected(request('language') === 'sw')>Swahili</option><option value="en" @selected(request('language') === 'en')>English</option></select>
        <button class="btn" type="submit">Filter</button><a class="btn" href="{{ route('admin.knowledge.index') }}">Reset</a>
    </form>
    <table>
        <thead><tr><th>Title</th><th>Topic</th><th>Lang</th><th>Keywords</th><th>Status</th><th></th></tr></thead>
        <tbody>
        @forelse($entries as $e)
            <tr>
                <td><strong>{{ $e->title }}</strong><div style="font-size:.78rem;color:var(--muted)">{{ \Illuminate\Support\Str::limit($e->summary ?: $e->content, 110) }}</div></td>
                <td style="white-space:nowrap">{{ \App\Services\TopicClassifier::label($e->category, 'en') }}</td>
                <td>{{ strtoupper($e->language) }}</td>
                <td style="font-size:.76rem;color:var(--muted);max-width:220px">{{ \Illuminate\Support\Str::limit(implode(', ', (array) $e->keywords), 90) }}</td>
                <td>{!! $e->is_active ? '<span class="badge b-green">active</span>' : '<span class="badge b-gray">off</span>' !!}</td>
                <td style="white-space:nowrap">
                    <a class="btn btn-sm" href="{{ route('admin.knowledge.edit', $e) }}">Edit</a>
                    <form class="inline" method="POST" action="{{ route('admin.knowledge.toggle', $e) }}">@csrf @method('PATCH')<button class="btn btn-sm" type="submit">{{ $e->is_active ? 'Off' : 'On' }}</button></form>
                    <form class="inline" method="POST" action="{{ route('admin.knowledge.destroy', $e) }}" onsubmit="return confirm('Delete this entry?')">@csrf @method('DELETE')<button class="btn btn-sm btn-d" type="submit">Delete</button></form>
                </td>
            </tr>
        @empty
            <tr><td colspan="6" style="text-align:center;color:var(--muted)">No entries.</td></tr>
```

```
        @endforelse
        </tbody>
    </table>
    {{ $entries->links('pagination.simple') }}
</div>
@endsection
```

85 resources/views/admin/login.blade.php

42 lines

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Sign in – Huru SMS Admin</title>
    <meta name="robots" content="noindex, nofollow">
    <link rel="icon" href="/logo.svg" type="image/svg+xml">
    <link href="https://fonts.googleapis.com/css2?family=Inter:wght@400;600;700;800&display=swap" rel="stylesheet">
    <style>
        body{font-family:Inter,system-ui,sans-serif;background:#f8fafc;margin:0;min-height:100vh;display:flex;align-items:center;justify-content:center;padding:16px;color:#0f172a}
        .box{background:#fff;border:1px solid #cbd5e1;border-radius:12px;padding:28px;width:100%;max-width:380px}
        .logo{width:48px;height:48px;border-radius:12px;background:#15803d;color:#fff;font-weight:800;font-size:1.2rem;display:flex;align-items:center;justify-content:center;margin-bottom:12px}
        h1{font-size:1.2rem;margin:0 0 4px}
        p{color:#475569;font-size:.88rem;margin:0 0 16px}
        label{display:block;font-size:.8rem;font-weight:700;margin:10px 0 5px}
        input{width:100%;padding:10px 12px;border:1.5px solid #cbd5e1;border-radius:8px;font:inherit;box-sizing:border-box}
        input:focus{outline:none;border-color:#15803d}
        button{width:100%;margin-top:16px;background:#15803d;color:#fff;border:none;border-radius:8px;padding:11px;font:inherit;font-weight:700;cursor:pointer}
        button:hover{background:#166534}
        .err{background:#fef2f2;border:1px solid #fecaca;color:#b91c1c;padding:9px 12px;border-radius:8px;font-size:.85rem;font-weight:600;margin-bottom:8px}
        .chk{display:flex;align-items:center;gap:8px;font-size:.85rem;margin-top:10px}
        .chk input{width:auto}
    </style>
</head>
<body>
<form class="box" method="POST" action="{{ route('admin.login.post') }}">
    @csrf
    <div class="logo">H</div>
    <h1>Huru SMS Admin</h1>
    <p>Sign in with your administrator account.</p>
    @if($errors->any())<div class="err">{{ $errors->first() }}</div>@endif
    @if(session('error'))<div class="err">{{ session('error') }}</div>@endif
    <label for="email">Email</label>
    <input type="email" id="email" name="email" value="{{ old('email') }}" required autofocus>
    <label for="password">Password</label>
    <input type="password" id="password" name="password" required>
    <label class="chk"><input type="checkbox" name="remember" value="1"> Keep me signed in</label>
    <button type="submit">Sign in</button>
</form>
</body>
</html>
```

86 resources/views/admin/resources/form.blade.php

25 lines

```
@extends('layouts.admin', ['title' => $resource->exists ? 'Edit service' : 'New service'])

@section('content')
<div class="card" style="max-width:860px">
    <form method="POST" action="{{ $resource->exists ? route('admin.resources.update', $resource) : route('admin.resources.store') }}">
        @csrf
        @if($resource->exists) @method('PUT') @endif
        <div class="field"><label>Name</label><input type="text" name="name" value="{{ old('name', $resource->name) }}" required maxlength="150"></div>
        <div class="grid g3">
            <div class="field"><label>Category</label><select name="category">@foreach($categories as $k => $l)<option value="{{ $k }}" @selected(old('category', $resource->category) === $k)>{{ $l }}</option>@endforeach</select></div>
            <div class="field"><label>Region</label><select name="region">@foreach($regions as $r)<option value="{{ $r }}" @selected(old('region', $resource->region) === $r)>{{ ucwords($r) }}</option>@endforeach</select></div>
            <div class="field"><label>District</label><input type="text" name="district" value="{{ old('district', $resource->district) }}" maxlength="40" placeholder="e.g. kinondoni"></div>
        </div>
        <div class="field"><label>Ward / area</label><input type="text" name="ward" value="{{ old('ward', $resource->ward) }}" maxlength="60" placeholder="e.g. Sinza"></div>
        <div class="field"><label>Address / directions</label><textarea name="location" rows="2">{{ old('location', $resource->location) }}</textarea></div>
        <div class="grid g2">
            <div class="field"><label>Phone</label><input type="text" name="phone" value="{{ old('phone', $resource->phone) }}" maxlength="60"></div>
            <div class="field"><label>Email</label><input type="email" name="email" value="{{ old('email', $resource->email) }}"></div>
        </div>
        <div class="field"><label class="check"><input type="checkbox" name="is_active" value="1" @checked(old('is_active', $resource->is_active))> Active</label></div>
        <button class="btn btn-p" type="submit">Save</button>
        <a class="btn" href="{{ route('admin.resources.index') }}">Cancel</a>
    </form>
</div>
@endsection
```

87 resources/views/admin/resources/index.blade.php

35 lines

```
@extends('layouts.admin', ['title' => 'Local services'])

@section('content')
<div class="card">
    <div class="card-h"><div><h2>Place-bound services</h2><p>Legal aid providers, hospitals, police desks and offices by region and district. Run <code>php artisan huru:import-legal-aid</code> to pull the national legal aid list.</p></div><a class="btn btn-p" href="{{ route('admin.resources.create') }}">+ New service</a></div>
    <form class="filters" method="GET">
        <input type="text" name="q" value="{{ request('q') }}" placeholder="Search name, district, address">
        <select name="region"><option value="">All regions</option>@foreach($regions as $r)<option value="{{ $r }}" @selected(request('region') === $r)>{{ ucwords($r) }} ({{ $byRegion[$r] ?? 0 }})</option>@endforeach</select>
        <select name="category"><option value="">All categories</option>@foreach($categories as $k => $l)<option value="{{ $k }}" @selected(request('category') === $k)>{{ $l }}</option>@endforeach</select>
        <button class="btn" type="submit">Filter</button><a class="btn" href="{{ route('admin.resources.index') }}">Reset</a>
    </form>
    <table>
        <thead><tr><th>Name</th><th>Category</th><th>Region / District</th><th>Address</th><th>Contact</th><th>Source</th><th></th></tr></thead>
        <tbody>
        @forelse($resources as $r)
            <tr>
                <td><strong>{{ $r->name }}</strong> @if(!$r->is_active)<span class="badge b-gray">off</span>@endif</td>
                <td style="white-space:nowrap">{{ $categories[$r->category] ?? $r->category }}</td>
                <td style="white-space:nowrap">{{ ucwords($r->region) }}@if($r->district) / {{ ucwords($r->district) }}@endif</td>
                <td style="font-size:.8rem;max-width:300px">{{ \Illuminate\Support\Str::limit($r->location, 120) }}</td>
                <td style="font-size:.8rem;white-space:nowrap">{{ $r->phone }}@if($r->email)<br>{{ $r->email }}@endif</td>
                <td style="font-size:.75rem;color:var(--muted)">{{ $r->source }}</td>
                <td style="white-space:nowrap">
                    <a class="btn btn-sm" href="{{ route('admin.resources.edit', $r) }}">Edit</a>
                    <form class="inline" method="POST" action="{{ route('admin.resources.destroy', $r) }}" onsubmit="return confirm('Delete this service?')">@csrf @method('DELETE')<button class="btn btn-sm btn-d" type="submit">Delete</button></form>
                </td>
            </tr>
        @empty
            <tr><td colspan="7" style="text-align:center;color:var(--muted)">No services match.</td></tr>
        @endforelse
        </tbody>
    </table>
    {{ $resources->links('pagination.simple') }}
</div>
@endsection
```

88 resources/views/admin/settings.blade.php

36 lines

```
@extends('layouts.admin', ['title' => 'Settings'])

@section('content')
<form method="POST" action="{{ route('admin.settings.update') }}">
    @csrf
    <div class="grid g2">
        @foreach($groups as $group => $fields)
            <div class="card">
                <div class="card-h"><h2>{{ $group }}</h2></div>
                @foreach($fields as $key => $def)
                    @php $val = old($key, $values[$key]); @endphp
                    <div class="field">
                        @if($def['type'] === 'boolean')
                            <label class="check"><input type="checkbox" name="{{ $key }}" value="1"
@checked((string) $val === '1')> {{ $def['label'] }}</label>
                        @else
                            <label for="{{ $key }}">{{ $def['label'] }}</label>
                            @if($def['type'] === 'textarea')
                                <textarea id="{{ $key }}" name="{{ $key }}" rows="2">{{ $val }}</textarea>
                            @elseif($def['type'] === 'select')
                                <select id="{{ $key }}" name="{{ $key }}">@foreach($def['options'] as $ov => $ol)
<option value="{{ $ov }}" @selected((string) $val === (string) $ov)>{{ $ol }}</option>@endforeach</select>
                            @elseif($def['type'] === 'number')
                                <input type="number" step="any" id="{{ $key }}" name="{{ $key }}" value="{{ $val
}}">
                            @else
                                <input type="text" id="{{ $key }}" name="{{ $key }}" value="{{ $val }}">
                            @endif
                        @endif
                        @if(!empty($def['hint']))<div class="hint">{{ $def['hint'] }}</div>@endif
                        @error($key)<div class="hint" style="color:var(--danger)">{{ $message }}</div>@enderror
                    </div>
                @endforeach
            </div>
        @endforeach
    </div>
    <button class="btn btn-p" type="submit">Save all settings</button>
</form>
@endsection
```

89 resources/views/admin/templates/form.blade.php

19 lines

```
@extends('layouts.admin', ['title' => $template->exists ? 'Edit persona' : 'New persona'])

@section('content')
<div class="card" style="max-width:860px">
    <form method="POST" action="{{ $template->exists ? route('admin.templates.update', $template) : route('admin.templates.store') }}">
        @csrf
        @if($template->exists) @method('PUT') @endif
        <div class="field"><label>Name</label><input type="text" name="name" value="{{ old('name', $template->name) }}" required maxlength="80"></div>
        <div class="grid g2">
            <div class="field"><label>Topic</label><select name="category">@foreach(\App\Services\TopicClassifier::CATEGORIES as $k => $l)<option value="{{ $k }}" @selected(old('category', $template->category) === $k)>{{ $l['en'] }}</option>@endforeach</select></div>
            <div class="field"><label>Language</label><select name="language"><option value="sw" @selected(old('language', $template->language) === 'sw')>Swahili</option><option value="en" @selected(old('language', $template->language) === 'en')>English</option></select></div>
        </div>
        <div class="field"><label>Persona</label><textarea name="template" rows="8" required>{{ old('template', $template->template) }}</textarea><div class="hint">Describe who the assistant is and how it should behave for this topic. Country context, knowledge, contacts and output rules are appended automatically. Use {app_name} for the service name.</div></div>
        <div class="field"><label class="check"><input type="checkbox" name="is_active" value="1" @checked(old('is_active', $template->is_active))> Active (deactivates other personas for the same topic and language)</label></div>
        <button class="btn btn-p" type="submit">Save</button>
        <a class="btn" href="{{ route('admin.templates.index') }}">Cancel</a>
    </form>
</div>
@endsection
```

90 resources/views/admin/templates/index.blade.php

28 lines

```
@extends('layouts.admin', ['title' => 'Personas'])

@section('content')
<div class="card">
    <div class="card-h"><div><h2>Persona templates</h2><p>One active persona per topic and language. Topics without a persona fall back to the general one. Placeholders: {app_name}, {category}.</p></div><a class="btn btn-p" href="{{ route('admin.templates.create') }}">+ New persona</a></div>
    <table>
        <thead><tr><th>Name</th><th>Topic</th><th>Lang</th><th>Persona</th><th>Status</th><th></th></tr></thead>
        <tbody>
        @forelse($templates as $t)
            <tr>
                <td style="white-space:nowrap"><strong>{{ $t->name }}</strong></td>
                <td style="white-space:nowrap">{{ \App\Services\TopicClassifier::label($t->category, 'en') }}</td>
                <td>{{ strtoupper($t->language) }}</td>
                <td style="font-size:.8rem;color:var(--muted)">{{ \Illuminate\Support\Str::limit($t->template, 160) }}</td>
                <td>{!! $t->is_active ? '<span class="badge b-green">active</span>' : '<span class="badge b-gray">off</span>' !!}</td>
                <td style="white-space:nowrap">
                    <a class="btn btn-sm" href="{{ route('admin.templates.edit', $t) }}">Edit</a>
                    <form class="inline" method="POST" action="{{ route('admin.templates.toggle', $t) }}">@csrf @method('PATCH')<button class="btn btn-sm" type="submit">{{ $t->is_active ? 'Off' : 'On' }}</button></form>
                    <form class="inline" method="POST" action="{{ route('admin.templates.destroy', $t) }}" onsubmit="return confirm('Delete this persona?')">@csrf @method('DELETE')<button class="btn btn-sm btn-d" type="submit">Delete</button></form>
                </td>
            </tr>
        @empty
            <tr><td colspan="6" style="text-align:center;color:var(--muted)">No personas yet. The built-in default will be used.</td></tr>
        @endforelse
        </tbody>
    </table>
</div>
@endsection
```

91 resources/views/admin/users/index.blade.php

37 lines

```
@extends('layouts.admin', ['title' => 'Citizens'])

@section('content')
<div class="card">
    <form class="filters" method="GET">
        <input type="text" name="q" value="{{ request('q') }}" placeholder="Phone or name">
        <select name="region"><option value="">All regions</option>@foreach(\App\Services\TanzaniaContext::REGIONS as $r)<option value="{{ $r }}" @selected(request('region') === $r)>{{ ucwords($r) }}</option>@endforeach</select>
        <label class="check"><input type="checkbox" name="banned" value="1" @checked(request('banned'))> Blocked only</label>
        <button class="btn" type="submit">Filter</button><a class="btn" href="{{ route('admin.users.index') }}">Reset</a>
    </form>
    <table>
        <thead><tr><th>Phone</th><th>Name</th><th>Lang</th><th>Region</th><th>Messages</th><th>Strikes</th><th>Last seen</th><th>Status</th><th></th></tr></thead>
        <tbody>
        @forelse($users as $u)
            <tr>
                <td style="white-space:nowrap"><a href="{{ route('admin.conversations.show', $u) }}">{{ $u->phone_number }}</a></td>
                <td>{{ $u->name ?: '—' }}</td>
                <td>{{ strtoupper($u->preferred_language ?? 'auto') }}</td>
                <td>{{ $u->region ? ucwords($u->region) : '—' }}</td>
                <td>{{ $u->messages_count }}</td>
                <td>{{ $u->abuse_count }}</td>
                <td style="white-space:nowrap;color:var(--muted)">{{ $u->last_seen_at?->diffForHumans() ?? '—' }}</td>
                <td>@if($u->is_banned)<span class="badge b-red">blocked</span>@elseif($u->opted_out)<span class="badge b-warn">opted out</span>@else<span class="badge b-green">active</span>@endif</td>
                <td style="white-space:nowrap">
                    <form class="inline" method="POST" action="{{ route('admin.users.ban', $u) }}">@csrf @method('PATCH')<button class="btn btn-sm {{ $u->is_banned ? '' : 'btn-d' }}" type="submit">{{ $u->is_banned ? 'Unblock' : 'Block' }}</button></form>
                    <form class="inline" method="POST" action="{{ route('admin.users.strikes', $u) }}">@csrf @method('PATCH')<button class="btn btn-sm" type="submit">Clear strikes</button></form>
                    <form class="inline" method="POST" action="{{ route('admin.users.destroy', $u) }}" onsubmit="return confirm('Delete this citizen and all their messages?')">@csrf @method('DELETE')<button class="btn btn-sm btn-d" type="submit">Delete</button></form>
                </td>
            </tr>
        @empty
            <tr><td colspan="9" style="text-align:center;color:var(--muted)">No citizens yet.</td></tr>
        @endforelse
        </tbody>
    </table>
    {{ $users->links('pagination.simple') }}
</div>
@endsection
```

92 resources/views/chat.blade.php

389 lines

```
<!DOCTYPE html>
<html lang="sw">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0, viewport-fit=cover">
    <title>Web Chat – {{ $settings['app_name'] }}</title>
    <meta name="description" content="Uliza swali lolote la maisha Tanzania na upate jibu la haraka kwa Kiswahili au Kiingereza. Bila intaneti tuma {{ $settings['sms_keyword'] }} kwenda {{ $settings['sms_shortcode'] }}.">
    <meta name="robots" content="index, follow">
    <link rel="canonical" href="{{ url('/chat') }}">
    <link rel="manifest" href="/manifest.json">
    <link rel="icon" href="/logo.svg" type="image/svg+xml">
    <link rel="apple-touch-icon" href="/logo.svg">
    <meta name="theme-color" content="#15803d">
    <meta name="csrf-token" content="{{ csrf_token() }}">
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
    <link href="https://fonts.googleapis.com/css2?family=Inter:wght@400;500;600;700;800&display=swap" rel="stylesheet">
    <style>
        :root{--green:#15803d;--green-dark:#166534;--green-bg:#f0fdf4;--green-border:#bbf7d0;--blue:#1d4ed8;--blue-dark:#1e40af;--blue-bg:#eff6ff;--bg:#f8fafc;--card:#fff;--text:#0f172a;--muted:#475569;--border:#cbd5e1;--danger:#b91c1c}
        *{margin:0;padding:0;box-sizing:border-box}
        html,body{height:100%}
        body{font-family:'Inter',system-ui,sans-serif;background:var(--bg);color:var(--text);display:flex;align-items:stretch;justify-content:center}
        .app{width:100%;max-width:880px;height:100dvh;display:flex;flex-direction:column;background:var(--card);border-left:1px solid var(--border);border-right:1px solid var(--border)}
        .screen{display:none;flex:1;flex-direction:column;min-height:0}
        .screen.active{display:flex}
        .hidden{display:none!important}
        /* auth */
        .auth{flex:1;overflow:auto;padding:28px 20px;display:flex;flex-direction:column;justify-content:center;max-width:520px;width:100%;margin:0 auto}
        .logo{width:52px;height:52px;border-radius:12px;background:var(--green);color:#fff;font-weight:800;font-size:1.3rem;display:flex;align-items:center;justify-content:center}
        .auth h1{font-size:1.5rem;margin:14px 0 6px;font-weight:800}
        .auth p.lead{color:var(--muted);font-size:.95rem}
        .sms-banner{background:var(--green-bg);border:1px solid var(--green-border);border-radius:10px;padding:12px 14px;margin:18px 0;font-size:.9rem}
        .sms-banner b{color:var(--green-dark)}
        .sms-badge{float:right;background:var(--green);color:#fff;font-weight:800;padding:2px 10px;border-radius:999px;font-size:.8rem}
        label{display:block;font-size:.85rem;font-weight:600;margin-bottom:6px;color:var(--muted)}
        input,select,textarea{width:100%;padding:12px 14px;border:1.5px solid var(--border);border-radius:8px;font:inherit;font-size:1rem;background:#fff}
        input:focus,select:focus,textarea:focus{outline:none;border-color:var(--green)}
        .row{display:flex;gap:10px}
        .btn{display:inline-flex;align-items:center;justify-content:center;gap:8px;padding:12px 16px;border-radius:8px;border:2px solid transparent;font:inherit;font-weight:700;cursor:pointer;font-size:.95rem}
        .btn-green{background:var(--green);color:#fff;width:100%}
        .btn-green:hover{background:var(--green-dark)}
        .btn-green:disabled{opacity:.6;cursor:wait}
        .btn-ghost{background:#fff;border-color:var(--border);color:var(--muted)}
        .btn-link{background:none;border:none;color:var(--blue);font-weight:600;cursor:pointer;font:inherit;padding:6px 0}
        .err{background:#fef2f2;border:1px solid #fecaca;color:var(--danger);padding:10px 12px;border-radius:8px;font-size:.88rem;font-weight:600;margin:10px 0}
        .ok{background:var(--green-bg);border:1px solid var(--green-border);color:var(--green-dark);padding:10px 12px;border-radius:8px;font-size:.88rem;font-weight:600;margin:10px 0}
        .small{font-size:.8rem;color:var(--muted);margin-top:10px}
        /* chat header */
        .hdr{display:flex;align-items:center;justify-content:space-between;padding:10px 14px;border-bottom:1px solid var(--border);gap:10px;flex-wrap:wrap}
        .hdr .who{display:flex;align-items:center;gap:10px}
        .hdr .logo{width:38px;height:38px;font-size:1rem;border-radius:9px}
        .hdr h2{font-size:1rem;font-weight:800}
        .hdr .st{font-size:.75rem;color:var(--green-dark);font-weight:600}
        .hdr .actions{display:flex;gap:6px;align-items:center;flex-wrap:wrap}
        .tag{font-size:.75rem;font-weight:700;padding:5px 10px;border-radius:999px;background:var(--green-bg);color:var(--green-dark);border:1px solid var(--green-border)}
```

```
        .ibtn{background:#fff;border:1px solid var(--border);border-radius:8px;padding:7px 10px;font:inherit;font-size:.8rem;font-weight:600;color:var(--muted);cursor:pointer;text-decoration:none}
        .ibtn:hover{border-color:var(--blue);color:var(--blue)}
        .offline{background:#fffbeb;border-bottom:1px solid #fde68a;color:#92400e;font-size:.85rem;padding:8px 14px;font-weight:600}
        /* filters */
        .filters{display:flex;gap:6px;padding:8px 14px;border-bottom:1px solid var(--border);flex-wrap:wrap;align-items:center}
        .filters input,.filters select{padding:7px 10px;font-size:.85rem;width:auto;flex:1;min-width:120px}
        .filters .ibtn{padding:8px 12px}
        .filters .status{width:100%;font-size:.75rem;color:var(--muted)}
        /* messages */
        .msgs{flex:1;overflow-y:auto;padding:16px 14px;display:flex;flex-direction:column;gap:10px;background:var(--bg)}
        .welcome{background:var(--card);border:1px solid var(--border);border-radius:12px;padding:16px}
        .welcome h3{font-size:1rem;margin-bottom:6px}
        .welcome p{font-size:.88rem;color:var(--muted)}
        .sugg{display:flex;flex-wrap:wrap;gap:6px;margin-top:10px}
        .sugg button{background:#fff;border:1px solid var(--border);border-radius:999px;padding:6px 11px;font:inherit;font-size:.8rem;font-weight:600;color:var(--blue);cursor:pointer}
        .sugg button:hover{border-color:var(--blue)}
        .msg{max-width:84%;padding:10px 14px;border-radius:14px;font-size:.95rem;line-height:1.5;white-space:pre-wrap;word-wrap:break-word;position:relative}
        .msg.in{align-self:flex-end;background:var(--green);color:#fff;border-bottom-right-radius:4px}
        .msg.out{align-self:flex-start;background:var(--card);border:1px solid var(--border);border-bottom-left-radius:4px}
        .msg.sys{align-self:center;background:var(--blue-bg);border:1px solid #bfdbfe;color:var(--blue-dark);font-size:.85rem;max-width:95%}
        .meta{display:flex;gap:8px;align-items:center;margin-top:6px;font-size:.72rem;opacity:.85}
        .msg.in .meta{justify-content:flex-end}
        .msg.out .meta{color:var(--muted)}
        .cat{background:var(--green-bg);color:var(--green-dark);border:1px solid var(--green-border);padding:1px 7px;border-radius:999px;font-weight:700}
        .fb{display:flex;gap:4px;margin-left:auto}
        .fb button{background:none;border:1px solid var(--border);border-radius:6px;padding:2px 7px;cursor:pointer;font-size:.8rem;color:var(--muted)}
        .fb button.on{background:var(--green-bg);border-color:var(--green);color:var(--green-dark)}
        .more{align-self:center}
        .typing{display:flex;gap:4px;padding:6px 14px}
        .typing span{width:7px;height:7px;background:var(--green);border-radius:50%;opacity:.4;animation:t 1.2s infinite}
        .typing span:nth-child(2){animation-delay:.2s}.typing span:nth-child(3){animation-delay:.4s}
        @keyframes t{0%,100%{transform:translateY(0);opacity:.4}50%{transform:translateY(-4px);opacity:1}}
        /* composer */
        .composer{display:flex;gap:8px;padding:10px 14px;border-top:1px solid var(--border);background:var(--card);padding-bottom:calc(10px + env(safe-area-inset-bottom))}
        .composer textarea{resize:none;max-height:120px;line-height:1.4;padding:11px 13px}
        .send{width:48px;height:48px;border-radius:8px;background:var(--green);color:#fff;border:none;cursor:pointer;flex-shrink:0;display:flex;align-items:center;justify-content:center}
        .send:hover{background:var(--green-dark)}
        /* modal */
        .modal{position:fixed;inset:0;background:rgba(15,23,42,.45);display:flex;align-items:center;justify-content:center;padding:16px;z-index:50}
        .modal .box{background:#fff;border-radius:12px;padding:20px;width:100%;max-width:420px}
        .modal h3{margin-bottom:12px}
        .modal .field{margin-bottom:12px}
        @media (max-width:600px){.app{border:none}.msg{max-width:92%}.hdr .st{display:none}}
    </style>
</head>
<body>
<div class="app" id="app">

    <!-- AUTH -->
    <div id="auth-screen" class="screen active">
        <div class="auth">
            <div class="logo">H</div>
            <h1>{{ $settings['app_name'] }} – uliza lolote</h1>
            <p class="lead">Ingiza namba yako ya simu. Tutakutumia namba fupi ya uthibitisho ili mazungumzo yako yabaki yako.</p>

            <div class="sms-banner">
                <span class="sms-badge">SMS {{ $settings['sms_shortcode'] }}</span>
                <b>Huna intaneti?</b> Tuma <b>{{ $settings['sms_keyword'] }}</b> [swali lako] kwenda <b>{{
```

```
$settings['sms_shortcode'] }}</b> kutoka simu yoyote.
            </div>

            @if(session('error'))<div class="err">{{ session('error') }}</div>@endif
            <div id="auth-error" class="err hidden"></div>
            <div id="auth-ok" class="ok hidden"></div>

            <form id="phone-form">
                <label for="phone">Namba ya simu / Phone number</label>
                <div class="row">
                    <input type="tel" id="phone" name="phone_number" placeholder="07XX XXX XXX" autocomplete="tel"
required>
                    <select id="lang" name="language" style="width:110px"><option value="sw">Kiswahili</option>
<option value="en">English</option></select>
                </div>
                <button type="submit" class="btn btn-green" id="phone-btn" style="margin-top:12px">Endelea /
Continue</button>
            </form>

            <form id="otp-form" class="hidden">
                <label for="code">Namba ya uthibitisho (tarakimu 6) / Verification code</label>
                <input type="text" id="code" name="code" inputmode="numeric" pattern="\d{6}" maxlength="6"
placeholder="123456" autocomplete="one-time-code" required>
                <button type="submit" class="btn btn-green" id="otp-btn" style="margin-top:12px">Thibitisha /
Verify</button>
                <div class="row" style="justify-content:space-between;margin-top:6px"><button type="button"
class="btn-link" id="otp-back">Badilisha namba</button><button type="button" class="btn-link" id="otp-resend">Tuma
tena</button></div>
            </form>

            <p class="small">Kwa kuendelea unakubali <a href="{{ route('legal.terms') }}">Vigezo na Masharti</a> na
<a href="{{ route('legal.privacy') }}">Sera ya Faragha</a>. <a href="{{ route('welcome') }}">Rudi mwanzo</a></p>
        </div>
    </div>

    <!-- CHAT -->
    <div id="chat-screen" class="screen">
        <div class="hdr">
            <div class="who">
                <div class="logo">H</div>
                <div><h2>{{ $settings['app_name'] }}</h2><div class="st" id="who-line">Tayari kukusaidia</div>
</div>
            </div>
            <div class="actions">
                <span class="tag" title="Tuma {{ $settings['sms_keyword'] }} [swali] kwenda {{
$settings['sms_shortcode'] }}">SMS {{ $settings['sms_keyword'] }} → {{ $settings['sms_shortcode'] }}</span>
                <button class="ibtn" id="prefs-btn">Mipangilio</button>
                <a class="ibtn" href="{{ route('community.index') }}">Jamii</a>
                <button class="ibtn" id="logout-btn">Toka</button>
            </div>
        </div>
        <div class="offline hidden" id="offline-bar">Uko nje ya mtandao. Tuma <b>{{ $settings['sms_keyword'] }}</b>
[swali] kwenda <b>{{ $settings['sms_shortcode'] }}</b> kwa SMS.</div>
        <div class="filters">
            <input type="text" id="f-keyword" placeholder="Tafuta kwenye historia...">
            <input type="date" id="f-date">
            <select id="f-category"><option value="">Mada zote</option></select>
            <button class="ibtn" id="f-apply">Tafuta</button>
            <button class="ibtn hidden" id="f-reset">Futa</button>
            <div class="status hidden" id="f-status"></div>
        </div>
        <div class="msgs" id="msgs"></div>
        <div class="typing hidden" id="typing"><span></span><span></span><span></span></div>
        <form class="composer" id="composer">
            <textarea id="input" rows="1" placeholder="Andika swali lako hapa..." maxlength="2000"></textarea>
            <button type="submit" class="send" aria-label="Tuma"><svg viewBox="0 0 24 24" width="22" height="22"
fill="currentColor"><path d="M2 21l21-9L2 3v7l15 2-15 2z"/></svg></button>
        </form>
    </div>

    <!-- PREFS MODAL -->
    <div class="modal hidden" id="prefs">
        <div class="box">
```

```
            <h3>Mipangilio yako</h3>
            <form id="prefs-form">
                <div class="field"><label>Jina (si lazima)</label><input type="text" name="name" id="p-name" maxlength="40"></div>
                <div class="field"><label>Lugha ya majibu</label><select name="preferred_language" id="p-lang"><option value="auto">Fuata lugha ninayoandika</option><option value="sw">Kiswahili daima</option><option value="en">English always</option></select></div>
                <div class="field"><label>Mkoa wako (kwa huduma zilizo karibu)</label><select name="region" id="p-region"><option value="">— Chagua mkoa —</option></select></div>
                <div class="row"><button type="button" class="btn btn-ghost" id="prefs-cancel" style="flex:1">Funga</button><button type="submit" class="btn btn-green" style="flex:1">Hifadhi</button></div>
            </form>
        </div>
    </div>
</div>

<script>
(() => {
    const $ = (id) => document.getElementById(id);
    // The session (and therefore the CSRF token) is regenerated on login and logout,
    // so the token is kept in a variable and refreshed from server responses.
    let csrf = document.querySelector('meta[name="csrf-token"]').content;
    const refreshCsrf = async () => {
        try { const r = await fetch('/chat/session', { headers: { 'Accept': 'application/json' } }); const d = await r.json(); if (d.csrf) csrf = d.csrf; } catch (e) {}
    };
    const state = { user: null, settings: null, phone: '', lang: 'sw', oldest: null, hasMore: false, filtering: false };
    const SUGGESTIONS = {
        sw: ['Nifanyeje kupata kitambulisho cha NIDA?', 'Haki zangu ni zipi nikikamatwa na polisi?', 'Dalili za malaria kwa mtoto ni zipi?', 'Nipande mahindi lini mkoa wangu?', 'Nieleze fractions kwa darasa la sita', 'Nianzeje biashara ndogo?'],
        en: ['How do I register for a NIDA ID?', 'What are my rights if the police arrest me?', 'What are malaria danger signs in a child?', 'When should I plant maize in my region?', 'Explain fractions for Standard Six', 'How do I start a small business?']
    };

    const api = async (url, opts = {}, retried = false) => {
        const res = await fetch(url, Object.assign({ headers: Object.assign({ 'X-Requested-With': 'XMLHttpRequest', 'X-CSRF-TOKEN': csrf, 'Accept': 'application/json' }, opts.body && !(opts.body instanceof FormData) ? { 'Content-Type': 'application/json' } : {}) }, opts));
        let data = {};
        try { data = await res.json(); } catch (e) {}
        if (res.status === 419 && !retried) { await refreshCsrf(); return api(url, opts, true); }
        if (data && data.csrf) csrf = data.csrf;
        if (!res.ok) { const msg = data.message || (data.errors && Object.values(data.errors)[0][0]) || ('Kosa ' + res.status); throw new Error(msg); }
        return data;
    };
    const show = (id) => { document.querySelectorAll('.screen').forEach(s => s.classList.remove('active')); $(id).classList.add('active'); };
    const err = (el, msg) => { el.textContent = msg; el.classList.remove('hidden'); };
    const hide = (el) => el.classList.add('hidden');
    const t = (sw, en) => (state.lang === 'en' ? en : sw);

    // ---------------------------------------------------------------- boot
    async function boot() {
        try {
            const s = await api('/chat/session');
            state.settings = s.settings;
            fillCategories(s.settings.categories);
            fillRegions(s.settings.regions);
            if (s.authenticated) { state.user = s.user; enterChat(); } else { show('auth-screen'); }
        } catch (e) { show('auth-screen'); }
    }

    function fillCategories(cats) {
        const sel = $('f-category');
        cats.forEach(c => { const o = document.createElement('option'); o.value = c.key; o.textContent = c.sw + ' / ' + c.en; sel.appendChild(o); });
    }
    function fillRegions(regions) {
        const sel = $('p-region');
```

```
        regions.forEach(r => { const o = document.createElement('option'); o.value = r; o.textContent = r;
sel.appendChild(o); });
    }

    // ---------------------------------------------------------------- auth
    $('phone-form').addEventListener('submit', async (e) => {
        e.preventDefault();
        hide($('auth-error')); hide($('auth-ok'));
        const btn = $('phone-btn'); btn.disabled = true; btn.textContent = '...';
        state.phone = $('phone').value.trim(); state.lang = $('lang').value;
        try {
            const r = await api('/chat/request-otp', { method: 'POST', body: JSON.stringify({ phone_number:
state.phone, language: state.lang }) });
            if (!r.otp_required) { state.user = r.user; enterChat(); return; }
            $('phone-form').classList.add('hidden'); $('otp-form').classList.remove('hidden');
            let msg = t('Tumetuma namba ya uthibitisho kwa ' + r.phone_masked + '.', 'We sent a verification code
to ' + r.phone_masked + '.');
            if (r.debug_code) msg += ' [dev: ' + r.debug_code + ']';
            $('auth-ok').textContent = msg; $('auth-ok').classList.remove('hidden');
            $('code').focus();
        } catch (ex) { err($('auth-error'), ex.message); }
        finally { btn.disabled = false; btn.textContent = 'Endelea / Continue'; }
    });
    $('otp-form').addEventListener('submit', async (e) => {
        e.preventDefault();
        hide($('auth-error'));
        const btn = $('otp-btn'); btn.disabled = true;
        try {
            const r = await api('/chat/verify-otp', { method: 'POST', body: JSON.stringify({ phone_number:
state.phone, code: $('code').value.trim() }) });
            state.user = r.user; enterChat();
        } catch (ex) { err($('auth-error'), ex.message); }
        finally { btn.disabled = false; }
    });
    $('otp-back').addEventListener('click', () => { $('otp-form').classList.add('hidden'); $('phone-
form').classList.remove('hidden'); hide($('auth-ok')); });
    $('otp-resend').addEventListener('click', () => $('phone-form').requestSubmit());

    // ---------------------------------------------------------------- chat
    async function enterChat() {
        const redirect = new URLSearchParams(location.search).get('redirect');
        if (redirect && redirect.startsWith('/')) { location.href = redirect; return; }
        show('chat-screen');
        state.lang = state.user.preferred_language === 'en' ? 'en' : state.lang;
        $('who-line').textContent = (state.user.name ? state.user.name + ' · ' : '') + state.user.phone_masked +
(state.user.region ? ' · ' + state.user.region : '');
        await loadMessages();
        const q = new URLSearchParams(location.search).get('q');
        if (q) { $('input').value = q; $('input').focus(); history.replaceState({}, '', '/chat'); }
    }

    async function loadMessages(filters = {}, append = false) {
        const params = new URLSearchParams(filters);
        const r = await api('/chat/messages?' + params.toString());
        const box = $('msgs');
        if (!append) box.innerHTML = '';
        if (!append && r.messages.length === 0 && !state.filtering) renderWelcome();
        const frag = document.createDocumentFragment();
        r.messages.forEach(m => frag.appendChild(renderMsg(m)));
        if (append) { box.querySelector('.more')?.remove(); box.prepend(frag); } else { box.appendChild(frag); }
        state.hasMore = r.has_more; state.oldest = r.messages.length ? r.messages[0].id : state.oldest;
        if (state.hasMore && !state.filtering) {
            const b = document.createElement('button'); b.className = 'ibtn more'; b.textContent = t('Onyesha
mazungumzo ya zamani', 'Show older messages');
            b.onclick = () => loadMessages({ before: state.oldest }, true); box.prepend(b);
        }
        if (!append) scrollBottom();
    }

    function renderWelcome() {
        const w = document.createElement('div'); w.className = 'welcome';
        w.innerHTML = '<h3>' + t('Karibu! Uliza lolote kuhusu maisha Tanzania.', 'Welcome! Ask anything about life
in Tanzania.') + '</h3><p>' + t('Sheria, afya, kilimo, masomo, huduma za serikali, fedha, ajira, teknolojia... Taja mahali
```

```
ulipo ukihitaji huduma iliyo karibu.', 'Law, health, farming, school subjects, government services, money, jobs,
technology... Mention where you are if you need nearby services.') + '</p><div class="sugg"></div>';
    296          const s = w.querySelector('.sugg');
    297          SUGGESTIONS[state.lang].forEach(q => { const b = document.createElement('button'); b.type = 'button';
b.textContent = q; b.onclick = () => { $('input').value = q; $('composer').requestSubmit(); }; s.appendChild(b); });
    298          $('msgs').appendChild(w);
    299      }
    300
    301      function renderMsg(m) {
    302          const d = document.createElement('div');
    303          const isIn = m.direction === 'inbound';
    304          d.className = 'msg ' + (isIn ? 'in' : 'out');
    305          d.dataset.id = m.id || '';
    306          const body = document.createElement('div'); body.textContent = m.content; d.appendChild(body);
    307          const meta = document.createElement('div'); meta.className = 'meta';
    308          const time = document.createElement('span'); time.textContent = m.created_at ? new
Date(m.created_at).toLocaleString('sw-TZ', { hour: '2-digit', minute: '2-digit', day: '2-digit', month: 'short' }) : '';
    309          meta.appendChild(time);
    310          if (!isIn && m.category_label) { const c = document.createElement('span'); c.className = 'cat';
c.textContent = m.category_label; meta.appendChild(c); }
    311          if (!isIn && m.id) {
    312              const fb = document.createElement('div'); fb.className = 'fb';
    313              [[1, '👍'], [-1, '👎']].forEach(([v, icon]) => {
    314                  const b = document.createElement('button'); b.type = 'button'; b.textContent = icon; b.title = v
=== 1 ? t('Imesaidia', 'Helpful') : t('Haikusaidia', 'Not helpful');
    315                  if (m.feedback === v) b.classList.add('on');
    316                  b.onclick = async () => { try { await api('/chat/feedback', { method: 'POST', body:
JSON.stringify({ message_id: m.id, rating: v }) }); fb.querySelectorAll('button').forEach(x => x.classList.remove('on'));
b.classList.add('on'); } catch (e) {} };
    317                  fb.appendChild(b);
    318              });
    319              meta.appendChild(fb);
    320          }
    321          d.appendChild(meta);
    322          return d;
    323      }
    324
    325      function addSystem(text) { const d = document.createElement('div'); d.className = 'msg sys'; d.textContent =
text; $('msgs').appendChild(d); scrollBottom(); }
    326      function scrollBottom() { const b = $('msgs'); b.scrollTop = b.scrollHeight; }
    327
    328      $('composer').addEventListener('submit', async (e) => {
    329          e.preventDefault();
    330          const text = $('input').value.trim();
    331          if (!text) return;
    332          $('msgs').querySelector('.welcome')?.remove();
    333          $('msgs').appendChild(renderMsg({ direction: 'inbound', content: text, created_at: new Date().toISOString()
}));
    334          $('input').value = ''; $('input').style.height = 'auto';
    335          $('typing').classList.remove('hidden'); scrollBottom();
    336          try {
    337              const r = await api('/chat/send', { method: 'POST', body: JSON.stringify({ message: text }) });
    338              $('typing').classList.add('hidden');
    339              if (r.reply) $('msgs').appendChild(renderMsg(r.reply));
    340          } catch (ex) {
    341              $('typing').classList.add('hidden');
    342              if (/401/.test(ex.message)) { state.user = null; show('auth-screen'); return; }
    343              addSystem('⚠️ ' + ex.message);
    344          }
    345          scrollBottom();
    346      });
    347      $('input').addEventListener('input', function () { this.style.height = 'auto'; this.style.height =
Math.min(this.scrollHeight, 120) + 'px'; });
    348      $('input').addEventListener('keydown', (e) => { if (e.key === 'Enter' && !e.shiftKey) { e.preventDefault();
$('composer').requestSubmit(); } });
    349
    350      // filters
    351      $('f-apply').addEventListener('click', () => {
    352          const f = { keyword: $('f-keyword').value.trim(), date: $('f-date').value, category: $('f-category').value
};
    353          Object.keys(f).forEach(k => { if (!f[k]) delete f[k]; });
    354          if (!Object.keys(f).length) return;
    355          state.filtering = true; $('f-reset').classList.remove('hidden'); $('f-status').classList.remove('hidden');
```

```
        $('f-status').textContent = t('Matokeo ya utafutaji', 'Search results');
        loadMessages(f);
    });
    $('f-reset').addEventListener('click', () => { $('f-keyword').value = ''; $('f-date').value = ''; $('f-category').value = ''; state.filtering = false; hide($('f-reset')); hide($('f-status')); loadMessages(); });

    // prefs
    $('prefs-btn').addEventListener('click', () => { $('p-name').value = state.user.name || ''; $('p-lang').value = state.user.preferred_language || 'auto'; $('p-region').value = state.user.region || ''; $('prefs').classList.remove('hidden'); });
    $('prefs-cancel').addEventListener('click', () => hide($('prefs')));
    $('prefs-form').addEventListener('submit', async (e) => {
        e.preventDefault();
        try {
            const r = await api('/chat/preferences', { method: 'POST', body: JSON.stringify({ name: $('p-name').value, preferred_language: $('p-lang').value, region: $('p-region').value }) });
            state.user = r.user; hide($('prefs'));
            state.lang = state.user.preferred_language === 'en' ? 'en' : (state.user.preferred_language === 'sw' ? 'sw' : state.lang);
            $('who-line').textContent = (state.user.name ? state.user.name + ' · ' : '') + state.user.phone_masked + (state.user.region ? ' · ' + state.user.region : '');
            addSystem(t('Mipangilio imehifadhiwa.', 'Preferences saved.'));
        } catch (ex) { alert(ex.message); }
    });

    $('logout-btn').addEventListener('click', async () => {
        if (!confirm(t('Unataka kutoka?', 'Sign out?'))) return;
        await api('/chat/logout', { method: 'POST' }); state.user = null; $('msgs').innerHTML = ''; show('auth-screen');
    });

    // offline awareness + PWA
    const net = () => $('offline-bar').classList.toggle('hidden', navigator.onLine);
    window.addEventListener('online', net); window.addEventListener('offline', net); net();
    if ('serviceWorker' in navigator) navigator.serviceWorker.register('/sw.js').catch(() => {});

    boot();
})();
</script>
</body>
</html>
```

93 resources/views/community/index.blade.php

78 lines

```
@extends('layouts.public', ['title' => 'Jamii', 'description' => 'Jamii ya Huru SMS: jadili, shirikiana uzoefu na upate ushauri kutoka kwa wananchi wenzako.', 'robots' => 'noindex, follow'])

@section('content')
<style>
    .top{display:flex;justify-content:space-between;align-items:center;gap:12px;flex-wrap:wrap;margin-bottom:18px}
    .top p{color:var(--muted);font-size:.9rem}
    .btn{display:inline-flex;align-items:center;gap:6px;background:var(--green);color:#fff;text-decoration:none;font-weight:700;padding:10px 14px;border-radius:8px;border:none;font:inherit;cursor:pointer;font-size:.9rem}
    .btn.alt{background:#fff;color:var(--blue);border:2px solid var(--blue)}
    .grid{display:grid;grid-template-columns:repeat(2,1fr);gap:12px}
    .th{border:1px solid var(--border);border-radius:10px;padding:16px;background:#fff}
    .th h3{font-size:1rem;margin-bottom:4px}
    .th h3 a{color:var(--text);text-decoration:none}
    .th p{font-size:.88rem;color:var(--muted)}
    .th .meta{display:flex;gap:10px;align-items:center;margin-top:10px;font-size:.78rem;color:var(--muted);flex-wrap:wrap}
    .badge{background:var(--green-bg);color:var(--green-dark);border:1px solid var(--green-border);padding:2px 8px;border-radius:999px;font-weight:700;font-size:.72rem}
    .badge.blue{background:#eff6ff;color:#1e40af;border-color:#bfdbfe}
    form.inline{display:inline}
    .new{border:1px dashed var(--border);border-radius:10px;padding:16px;margin-top:22px}
    .new input,.new textarea{width:100%;padding:10px 12px;border:1.5px solid var(--border);border-radius:8px;font:inherit;margin-bottom:8px}
    .alert{padding:10px 12px;border-radius:8px;font-size:.88rem;font-weight:600;margin-bottom:12px}
    .alert-err{background:#fef2f2;border:1px solid #fecaca;color:#991b1b}
    .alert-ok{background:var(--green-bg);border:1px solid var(--green-border);color:var(--green-dark)}
    @media (max-width:640px){.grid{grid-template-columns:1fr}}
</style>

<div class="top">
    <div><h1>Jamii ya {{ $settings['app_name'] }}</h1><p>Karibu, {{ $user->displayName() }}. Jadili, uliza na ushirikiane uzoefu na wananchi wenzako.</p></div>
    <a class="btn alt" href="{{ route('chat.index') }}">← Rudi kwenye chat</a>
</div>

@if(session('error'))<div class="alert alert-err">{{ session('error') }}</div>@endif
@if(session('success'))<div class="alert alert-ok">{{ session('success') }}</div>@endif
@if($errors->any())<div class="alert alert-err">{{ $errors->first() }}</div>@endif

<h2>Mijadala ya wazi</h2>
<div class="grid">
    @forelse($publicThreads as $thread)
        <div class="th">
            <h3><a href="{{ route('community.show', $thread) }}">{{ $thread->title }}</a> @if($thread->is_system)<span class="badge">Rasmi</span>@endif</h3>
            <p>{{ \Illuminate\Support\Str::limit($thread->description, 140) }}</p>
            <div class="meta">
                <span>{{ $thread->posts_count }} ujumbe</span><span>{{ $thread->members_count }} wanachama</span>
                @if(in_array($thread->id, $joinedIds))
                    <span class="badge blue">Umejiunga</span>
                @else
                    <form class="inline" method="POST" action="{{ route('community.join', $thread) }}">@csrf<button class="btn" type="submit" style="padding:6px 10px;font-size:.78rem">Jiunge</button></form>
                @endif
            </div>
        </div>
    @empty
        <p>Hakuna mijadala bado.</p>
    @endforelse
</div>

@if($joinedThreads->isNotEmpty())
<h2>Mijadala yangu</h2>
<div class="grid">
    @foreach($joinedThreads as $thread)
        <div class="th">
            <h3><a href="{{ route('community.show', $thread) }}">{{ $thread->title }}</a> @if($thread->is_private)<span class="badge blue">Faragha</span>@endif</h3>
            <p>{{ \Illuminate\Support\Str::limit($thread->description, 120) }}</p>
```

```
            <div class="meta"><span>{{ $thread->posts_count }} ujumbe</span><span>Jukumu: {{ $thread->pivot->role }}</span></div>
        </div>
    @endforeach
</div>
@endif

<div class="new">
    <h2 style="margin-top:0">Anzisha mjadala mpya</h2>
    <form method="POST" action="{{ route('community.threads.store') }}">
        @csrf
        <input type="text" name="title" placeholder="Kichwa cha mjadala" required minlength="3" maxlength="120">
        <textarea name="description" rows="2" placeholder="Unajadili nini? (si lazima)" maxlength="1000"></textarea>
        <label style="font-size:.88rem;color:var(--muted);display:flex;gap:8px;align-items:center;margin-bottom:10px"><input type="checkbox" name="is_private" value="1" style="width:auto;margin:0"> Mjadala wa faragha (kwa mwaliko tu)</label>
        <button class="btn" type="submit">Anzisha</button>
    </form>
</div>
@endsection
```

94 resources/views/community/show.blade.php

69 lines

```
@extends('layouts.public', ['title' => $thread->title, 'description' => \Illuminate\Support\Str::limit($thread->description ?? $thread->title, 150), 'robots' => 'noindex, follow'])

@section('content')
<style>
    .top{display:flex;justify-content:space-between;align-items:flex-start;gap:12px;flex-wrap:wrap;margin-bottom:14px}
    .top p{color:var(--muted);font-size:.9rem}
    .btn{display:inline-flex;align-items:center;gap:6px;background:var(--green);color:#fff;text-decoration:none;font-weight:700;padding:9px 13px;border-radius:8px;border:none;font:inherit;cursor:pointer;font-size:.88rem}
    .btn.alt{background:#fff;color:var(--blue);border:2px solid var(--blue)}
    .btn.muted{background:#fff;color:var(--muted);border:1px solid var(--border)}
    .members{font-size:.8rem;color:var(--muted);margin-bottom:14px}
    .posts{display:flex;flex-direction:column;gap:10px;margin:14px 0}
    .post{border:1px solid var(--border);border-radius:10px;padding:12px 14px;background:#fff}
    .post.mine{border-color:var(--green-border);background:var(--green-bg)}
    .post .who{font-size:.78rem;color:var(--muted);font-weight:600;margin-bottom:4px;display:flex;justify-content:space-between;gap:8px}
    .post .body{font-size:.95rem;white-space:pre-wrap}
    .compose textarea{width:100%;padding:11px 12px;border:1.5px solid var(--border);border-radius:8px;font:inherit;margin-bottom:8px;resize:vertical}
    .alert{padding:10px 12px;border-radius:8px;font-size:.88rem;font-weight:600;margin-bottom:12px}
    .alert-err{background:#fef2f2;border:1px solid #fecaca;color:#991b1b}
    .alert-ok{background:var(--green-bg);border:1px solid var(--green-border);color:var(--green-dark)}
    .notice{background:#eff6ff;border:1px solid #bfdbfe;color:#1e40af;padding:10px 12px;border-radius:8px;font-size:.88rem}
    form.inline{display:inline}
</style>

<div class="top">
    <div>
        <h1 style="font-size:1.4rem">{{ $thread->title }}</h1>
        <p>{{ $thread->description }}</p>
    </div>
    <div style="display:flex;gap:8px;flex-wrap:wrap">
        <a class="btn alt" href="{{ route('community.index') }}">← Mijadala</a>
        @if($isMember && !$thread->is_system)
            <form class="inline" method="POST" action="{{ route('community.leave', $thread) }}">@csrf<button class="btn muted" type="submit">Ondoka</button></form>
        @elseif(!$isMember && !$thread->is_private)
            <form class="inline" method="POST" action="{{ route('community.join', $thread) }}">@csrf<button class="btn" type="submit">Jiunge</button></form>
        @endif
    </div>
</div>

<div class="members">Wanachama {{ $members->count() }}: {{ $members->take(8)->map->displayName()->implode(', ') }}{{ $members->count() > 8 ? ' na wengine' : '' }}</div>

@if(session('error'))<div class="alert alert-err">{{ session('error') }}</div>@endif
@if(session('success'))<div class="alert alert-ok">{{ session('success') }}</div>@endif
@if($errors->any())<div class="alert alert-err">{{ $errors->first() }}</div>@endif
@if($thread->is_system)<div class="notice">Huu ni mjadala rasmi. Ujumbe huonekana baada ya kuhakikiwa na timu ya {{ $settings['app_name'] }}.</div>@endif

<div class="posts">
    @forelse($posts as $post)
        <div class="post {{ $post->user_id === $user->id ? 'mine' : '' }}">
            <div class="who"><span>{{ $post->user?->displayName() ?? 'Mwananchi' }}</span><span>{{ $post->created_at->diffForHumans() }}</span></div>
            <div class="body">{{ $post->content }}</div>
        </div>
    @empty
        <p style="color:var(--muted)">Hakuna ujumbe bado. Kuwa wa kwanza kuandika.</p>
    @endforelse
</div>
{{ $posts->links('pagination.simple') }}

@if($isMember)
<div class="compose">
```

```
    <form method="POST" action="{{ route('community.posts.store', $thread) }}">
        @csrf
        <textarea name="content" rows="3" placeholder="Andika ujumbe wako..." required minlength="2"
maxlength="3000"></textarea>
        <button class="btn" type="submit">Tuma</button>
    </form>
</div>
@else
    <p style="color:var(--muted);font-size:.9rem">Jiunge na mjadala huu ili kuandika.</p>
@endif
@endsection
```

95 resources/views/layouts/admin.blade.php

123 lines

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>{{ $title ?? 'Dashboard' }} – Huru SMS Admin</title>
    <meta name="robots" content="noindex, nofollow">
    <link rel="icon" href="/logo.svg" type="image/svg+xml">
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
    <link href="https://fonts.googleapis.com/css2?family=Inter:wght@400;500;600;700;800&display=swap"
rel="stylesheet">
    <style>
        :root{--green:#15803d;--green-dark:#166534;--green-bg:#f0fdf4;--green-border:#bbf7d0;--blue:#1d4ed8;--blue-
dark:#1e40af;--blue-bg:#eff6ff;--bg:#f8fafc;--card:#fff;--text:#0f172a;--muted:#475569;--border:#cbd5e1;--danger:#b91c1c;--
danger-bg:#fef2f2;--warn:#b45309;--warn-bg:#fffbeb;--sidebar:240px}
        *{margin:0;padding:0;box-sizing:border-box}
        body{font-family:'Inter',system-ui,sans-serif;background:var(--bg);color:var(--text);font-size:.92rem;line-
height:1.5}
        a{color:var(--blue)}
        .sidebar{position:fixed;top:0;left:0;width:var(--sidebar);height:100vh;background:#fff;border-right:1px
solid var(--border);display:flex;flex-direction:column;z-index:30}
        .brand{display:flex;align-items:center;gap:10px;padding:16px;border-bottom:1px solid var(--border);text-
decoration:none;color:var(--green-dark);font-weight:800;font-size:1.15rem}
        .brand img{width:32px;height:32px;border-radius:8px}
        .brand small{display:block;font-size:.65rem;letter-spacing:.08em;text-transform:uppercase;color:var(--
muted);font-weight:600}
        .nav{flex:1;overflow:auto;padding:10px}
        .nav .sec{font-size:.65rem;font-weight:700;letter-spacing:.1em;text-transform:uppercase;color:var(--
muted);padding:12px 10px 4px}
        .nav a{display:flex;align-items:center;gap:8px;padding:8px 10px;border-radius:8px;text-
decoration:none;color:var(--muted);font-weight:600;font-size:.88rem}
        .nav a:hover{background:var(--bg);color:var(--text)}
        .nav a.on{background:var(--green-bg);color:var(--green-dark)}
        .sb-foot{padding:12px 16px;border-top:1px solid var(--border);font-size:.8rem;color:var(--muted)}
        .sb-foot form{margin-top:6px}
        .main{margin-left:var(--sidebar);min-height:100vh}
        .topbar{height:56px;background:#fff;border-bottom:1px solid var(--border);display:flex;align-
items:center;justify-content:space-between;padding:0 24px;position:sticky;top:0;z-index:20}
        .topbar h1{font-size:1.05rem;font-weight:800}
        .content{padding:24px;max-width:1280px}
        .card{background:var(--card);border:1px solid var(--border);border-radius:12px;padding:20px;margin-
bottom:18px}
        .card-h{display:flex;justify-content:space-between;align-items:center;gap:12px;flex-wrap:wrap;margin-
bottom:14px}
        .card-h h2{font-size:1rem;font-weight:800}
        .card-h p{font-size:.82rem;color:var(--muted)}
        .grid{display:grid;gap:14px}
        .g4{grid-template-columns:repeat(4,1fr)}.g3{grid-template-columns:repeat(3,1fr)}.g2{grid-template-
columns:repeat(2,1fr)}
        .stat{background:var(--card);border:1px solid var(--border);border-radius:12px;padding:16px}
        .stat .l{font-size:.75rem;font-weight:700;letter-spacing:.06em;text-transform:uppercase;color:var(--muted)}
        .stat .v{font-size:1.7rem;font-weight:800;margin-top:4px}
        .stat .s{font-size:.78rem;color:var(--muted)}
        table{width:100%;border-collapse:collapse;font-size:.85rem}
        th{text-align:left;font-size:.72rem;letter-spacing:.06em;text-transform:uppercase;color:var(--
muted);padding:8px 10px;border-bottom:1px solid var(--border)}
        td{padding:9px 10px;border-bottom:1px solid #e2e8f0;vertical-align:top}
        tr:hover td{background:#f8fafc}
        .truncate{max-width:420px;overflow:hidden;text-overflow:ellipsis;white-space:nowrap}
        .badge{display:inline-block;padding:2px 8px;border-radius:999px;font-size:.72rem;font-weight:700;border:1px
solid transparent}
        .b-green{background:var(--green-bg);color:var(--green-dark);border-color:var(--green-border)}
        .b-blue{background:var(--blue-bg);color:var(--blue-dark);border-color:#bfdbfe}
        .b-gray{background:#f1f5f9;color:var(--muted);border-color:#e2e8f0}
        .b-red{background:var(--danger-bg);color:var(--danger);border-color:#fecaca}
        .b-warn{background:var(--warn-bg);color:var(--warn);border-color:#fde68a}
        .btn{display:inline-flex;align-items:center;gap:6px;padding:8px 13px;border-radius:8px;border:1px solid
var(--border);background:#fff;color:var(--text);font:inherit;font-weight:600;font-size:.85rem;cursor:pointer;text-
decoration:none}
        .btn:hover{border-color:var(--blue);color:var(--blue)}
```

```
        .btn-p{background:var(--green);border-color:var(--green);color:#fff}
        .btn-p:hover{background:var(--green-dark);color:#fff}
        .btn-d{color:var(--danger);border-color:#fecaca}
        .btn-d:hover{background:var(--danger-bg);color:var(--danger)}
        .btn-sm{padding:5px 9px;font-size:.78rem}
        form.inline{display:inline}
        .alert{padding:10px 14px;border-radius:8px;font-weight:600;font-size:.88rem;margin-bottom:14px}
        .a-ok{background:var(--green-bg);border:1px solid var(--green-border);color:var(--green-dark)}
        .a-err{background:var(--danger-bg);border:1px solid #fecaca;color:var(--danger)}
        .a-warn{background:var(--warn-bg);border:1px solid #fde68a;color:var(--warn)}
        .field{margin-bottom:14px}
        .field label{display:block;font-size:.8rem;font-weight:700;margin-bottom:5px}
        .field .hint{font-size:.76rem;color:var(--muted);margin-top:4px}

input[type=text],input[type=email],input[type=password],input[type=number],input[type=date],input[type=url],input[type=file],select,textarea{width:100%;padding:9px 11px;border:1.5px solid var(--border);border-radius:8px;font:inherit;font-size:.9rem;background:#fff}
        input:focus,select:focus,textarea:focus{outline:none;border-color:var(--green)}
        textarea{resize:vertical;min-height:90px}
        .check{display:flex;align-items:center;gap:8px;font-size:.88rem;font-weight:600}
        .check input{width:auto}
        .filters{display:flex;gap:8px;flex-wrap:wrap;align-items:center;margin-bottom:14px}
        .filters input,.filters select{width:auto;min-width:140px;padding:7px 10px;font-size:.85rem}
        .bars{display:flex;flex-direction:column;gap:6px}
        .bar{display:grid;grid-template-columns:160px 1fr 50px;gap:8px;align-items:center;font-size:.82rem}
        .bar .t{height:10px;background:#e2e8f0;border-radius:999px;overflow:hidden}
        .bar .f{height:100%;background:var(--green)}
        .spark{display:flex;align-items:flex-end;gap:4px;height:70px}
        .spark div{flex:1;background:var(--blue);border-radius:3px 3px 0 0;min-height:2px;position:relative}
        .spark div span{position:absolute;bottom:-18px;left:0;right:0;text-align:center;font-size:.6rem;color:var(--muted)}
        .mono{font-family:ui-monospace,Menlo,Consolas,monospace;font-size:.8rem;white-space:pre-wrap;background:#f8fafc;border:1px solid var(--border);border-radius:8px;padding:10px;max-height:320px;overflow:auto}
        .menu-btn{display:none}
        @media (max-width:900px){.sidebar{transform:translateX(-100%);transition:.2s}.sidebar.open{transform:none}.main{margin-left:0}.menu-btn{display:inline-block}.g4,.g3,.g2{grid-template-columns:1fr 1fr}.content{padding:14px}}
        @media (max-width:600px){.g4,.g3,.g2{grid-template-columns:1fr}}
    </style>
</head>
<body>
<aside class="sidebar" id="sidebar">
    <a href="{{ route('admin.dashboard') }}" class="brand"><img src="/logo.svg" alt=""><span>Huru SMS<small>Admin panel</small></span></a>
    <nav class="nav">
        <div class="sec">Overview</div>
        <a href="{{ route('admin.dashboard') }}" class="{{ request()->routeIs('admin.dashboard') ? 'on' : '' }}">📊 Dashboard</a>
        <a href="{{ route('admin.conversations.index') }}" class="{{ request()->routeIs('admin.conversations.*') ? 'on' : '' }}">💬 Conversations</a>
        <a href="{{ route('admin.users.index') }}" class="{{ request()->routeIs('admin.users.*') ? 'on' : '' }}">👥 Citizens</a>
        <div class="sec">Knowledge</div>
        <a href="{{ route('admin.knowledge.index') }}" class="{{ request()->routeIs('admin.knowledge.*') ? 'on' : '' }}">📚 Knowledge base</a>
        <a href="{{ route('admin.contacts.index') }}" class="{{ request()->routeIs('admin.contacts.*') ? 'on' : '' }}">📞 National directory</a>
        <a href="{{ route('admin.resources.index') }}" class="{{ request()->routeIs('admin.resources.*') ? 'on' : '' }}">📍 Local services</a>
        <a href="{{ route('admin.templates.index') }}" class="{{ request()->routeIs('admin.templates.*') ? 'on' : '' }}">🧭 Personas</a>
        <div class="sec">System</div>
        <a href="{{ route('admin.settings.index') }}" class="{{ request()->routeIs('admin.settings.*') ? 'on' : '' }}">⚙️ Settings</a>
        <a href="{{ route('welcome') }}" target="_blank">🌍 Public site ↗</a>
    </nav>
    <div class="sb-foot">
        {{ auth()->user()->name }}<br><span style="font-size:.72rem">{{ auth()->user()->email }}</span>
        <form method="POST" action="{{ route('admin.logout') }}">@csrf<button class="btn btn-sm" type="submit">Sign out</button></form>
    </div>
</aside>
<div class="main">
```

```
    <div class="topbar">
        <div style="display:flex;gap:10px;align-items:center"><button class="btn btn-sm menu-btn" onclick="document.getElementById('sidebar').classList.toggle('open')">☰</button><h1>{{ $title ?? 'Dashboard' }}</h1></div>
        <div style="font-size:.78rem;color:var(--muted)">{{ now()->timezone('Africa/Dar_es_Salaam')->format('D, d M Y H:i') }} EAT</div>
    </div>
    <div class="content">
        @if(session('success'))<div class="alert a-ok">{{ session('success') }}</div>@endif
        @if(session('error'))<div class="alert a-err">{{ session('error') }}</div>@endif
        @if($errors->any())<div class="alert a-err">{{ $errors->first() }}</div>@endif
        @yield('content')
    </div>
</div>
</body>
</html>
```

96 resources/views/layouts/public.blade.php

57 lines

```
<!DOCTYPE html>
<html lang="sw">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>{{ $title ?? 'Huru SMS' }} – Huru SMS</title>
    <meta name="description" content="{{ $description ?? 'Huru SMS – uliza lolote kwa SMS 15054 au mtandaoni.' }}">
    <meta name="robots" content="{{ $robots ?? 'index, follow' }}">
    <link rel="icon" href="/logo.svg" type="image/svg+xml">
    <link rel="manifest" href="/manifest.json">
    <meta name="theme-color" content="#15803d">
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
    <link href="https://fonts.googleapis.com/css2?family=Inter:wght@400;500;600;700;800&display=swap"
rel="stylesheet">
    <style>
        :root{--green:#15803d;--green-dark:#166534;--green-bg:#f0fdf4;--green-border:#bbf7d0;--blue:#1d4ed8;--
bg:#f8fafc;--card:#fff;--text:#0f172a;--muted:#475569;--border:#cbd5e1}
        *{margin:0;padding:0;box-sizing:border-box}
        body{font-family:'Inter',system-ui,sans-serif;background:var(--bg);color:var(--text);line-height:1.6}
        header{background:#fff;border-bottom:1px solid var(--border)}
        .nav{max-width:960px;margin:0 auto;padding:0 16px;height:60px;display:flex;align-items:center;justify-
content:space-between}
        .brand{display:flex;align-items:center;gap:10px;text-decoration:none;color:var(--green-dark);font-
weight:800;font-size:1.2rem}
        .brand img{width:32px;height:32px;border-radius:8px}
        .nav a.btn{background:var(--green);color:#fff;text-decoration:none;font-weight:700;padding:8px 14px;border-
radius:8px;font-size:.9rem}
        .sms{font-size:.85rem;color:var(--green-dark);font-weight:700;margin-right:12px}
        main{max-width:960px;margin:0 auto;padding:32px 16px 48px}
        .card{background:var(--card);border:1px solid var(--border);border-radius:12px;padding:28px}
        h1{font-size:1.7rem;font-weight:800;margin-bottom:6px}
        h2{font-size:1.1rem;font-weight:800;margin:22px 0 8px;color:var(--green-dark)}
        p,li{font-size:.95rem;color:#1e293b}
        ul{padding-left:20px}
        li{margin-bottom:6px}
        .updated{font-size:.8rem;color:var(--muted);margin-bottom:12px}
        a{color:var(--blue)}
        em{color:var(--muted)}
        footer{text-align:center;font-size:.85rem;color:var(--muted);padding:20px 16px;border-top:1px solid var(--
border);background:#fff}
        footer a{color:var(--muted);margin:0 8px;text-decoration:none}
        @media (max-width:600px){.sms{display:none}.card{padding:20px}}
    </style>
</head>
<body>
<header>
    <div class="nav">
        <a href="{{ route('welcome') }}" class="brand"><img src="/logo.svg" alt="">Huru SMS</a>
        <div><span class="sms">SMS: HURU → 15054</span><a class="btn" href="{{ route('chat.index') }}">Web Chat</a>
</div>
    </div>
</header>
<main>
    <div class="card">
        @yield('content')
    </div>
</main>
<footer>
    © {{ date('Y') }} Huru Digital Co. Ltd. · SMS HURU kwenda 15054
    <div style="margin-top:6px"><a href="{{ route('legal.terms') }}">Vigezo na Masharti</a><a href="{{
route('legal.privacy') }}">Sera ya Faragha</a><a href="{{ route('community.index') }}">Jamii</a></div>
</footer>
</body>
</html>
```

97 resources/views/legal/privacy.blade.php

37 lines

```
@extends('layouts.public', ['title' => 'Sera ya Faragha', 'description' => 'Jinsi Huru SMS inavyokusanya, kutumia na kulinda taarifa zako.'])

@section('content')
<h1>Sera ya Faragha · Privacy Policy</h1>
<p class="updated">Ilisasishwa: {{ date('d F Y') }}</p>

<h2>1. Taarifa tunazokusanya</h2>
<ul>
    <li><strong>Namba ya simu</strong> – ndiyo kitambulisho chako cha huduma, kwa SMS na web chat.</li>
    <li><strong>Maswali na majibu</strong> – tunahifadhi mazungumzo ili kuendeleza muktadha wa maswali ya kufuatilia na kukuwezesha kutafuta majibu ya zamani.</li>
    <li><strong>Mapendeleo</strong> – jina (ukilitoa), lugha unayopendelea, mkoa (ukiutaja) na maoni yako kuhusu majibu.</li>
    <li><strong>Taarifa za kiufundi</strong> – muda wa ujumbe, njia uliyotumia (SMS au web) na kumbukumbu za mfumo kwa usalama.</li>
</ul>

<h2>2. Jinsi tunavyotumia taarifa</h2>
<p>Kutoa majibu, kuendeleza mazungumzo, kulinda huduma dhidi ya matumizi mabaya, kuboresha maarifa yaliyohifadhiwa na kutoa takwimu za jumla (bila kukutambulisha) kwa washirika. Maswali yako hutumwa kwa mtoa huduma wa teknolojia ya lugha ili kupata jibu; hatutumi jina lako wala namba yako ya simu pamoja na swali.</p>
<p><em>We use your data to answer you, keep conversation context, protect the service from abuse and produce anonymous statistics. Questions are sent to a language technology provider to generate answers; your name and phone number are not sent with the question.</em></p>

<h2>3. Kushirikisha taarifa</h2>
<p>Hatuuzi taarifa zako. Tunaweza kushirikisha taarifa pale sheria inapotaka au kwa watoa huduma wanaotuwezesha kutoa huduma (mtandao wa SMS, mwenyeji wa seva, mtoa huduma wa teknolojia ya lugha) chini ya masharti ya usiri.</p>

<h2>4. Uhifadhi na usalama</h2>
<p>Taarifa huhifadhiwa kwenye seva zilizolindwa. Namba ya uthibitisho (OTP) huhifadhiwa kwa njia ya siri na hufutwa baada ya kutumika. Tunahifadhi mazungumzo kwa muda unaohitajika kwa huduma; unaweza kuomba kufutwa.</p>

<h2>5. Haki zako</h2>
<ul>
    <li>Kuona mazungumzo yako kupitia web chat.</li>
    <li>Kusitisha majibu wakati wowote kwa kutuma <strong>ACHA</strong> kwa SMS, na kuendelea kwa <strong>ANZA</strong>.</li>
    <li>Kuomba kufutwa kwa taarifa zako kwa kutumia fomu ya mawasiliano.</li>
</ul>

<h2>6. Watoto</h2>
<p>Huduma inaweza kutumiwa na wanafunzi kwa maswali ya masomo. Hatukusanyi kwa makusudi taarifa za ziada za watoto zaidi ya zile zilizo muhimu kwa huduma.</p>

<h2>7. Mawasiliano</h2>
<p>Huru Digital Co. Ltd., Tanzania. Tumia fomu kwenye <a href="{{ route('welcome') }}#wasiliana">ukurasa wa mwanzo</a>.</p>
@endsection
```

98 resources/views/legal/terms.blade.php

33 lines

```
@extends('layouts.public', ['title' => 'Vigezo na Masharti', 'description' => 'Vigezo na masharti ya kutumia huduma ya Huru SMS kwa SMS na mtandaoni.'])

@section('content')
<h1>Vigezo na Masharti · Terms and Conditions</h1>
<p class="updated">Ilisasishwa: {{ date('d F Y') }}</p>

<h2>1. Huduma</h2>
<p>Huru SMS ni huduma ya maelezo na mwongozo wa jumla inayotolewa na Huru Digital Co. Ltd. kwa SMS (shortcode 15054, neno HURU) na kupitia mtandao. Huru SMS hujibu maswali ya kila siku kuhusu maisha Tanzania: sheria, afya, kilimo, elimu, huduma za serikali, fedha, ajira na mada nyingine.</p>
<p><em>Huru SMS is a general information and guidance service provided by Huru Digital Co. Ltd. via SMS (shortcode 15054, keyword HURU) and the web.</em></p>

<h2>2. Si ushauri wa kitaalamu</h2>
<p>Majibu ni maelezo ya jumla yanayotolewa kiotomatiki kwa msaada wa teknolojia na maarifa yaliyokusanywa. Si ushauri wa kisheria, wa kitabibu, wa kifedha wala uwakilishi wa aina yoyote. Kwa maamuzi muhimu, thibitisha na ofisi, mtaalamu au mamlaka husika. Kwa dharura piga 112 (polisi), 114 (zimamoto), 115 (gari la wagonjwa) au 116 (msaada kwa mtoto).</p>
<p><em>Answers are general information generated automatically. They are not legal, medical or financial advice and do not create any professional relationship. Verify important decisions with the responsible office or professional.</em></p>

<h2>3. Matumizi yanayokubalika</h2>
<ul>
    <li>Usitumie lugha ya matusi, vitisho au maudhui ya chuki. Akaunti hupewa maonyo na baadaye kufungiwa.</li>
    <li>Usitumie huduma kwa udanganyifu, utapeli au kuwadhuru wengine.</li>
    <li>Usijaribu kuvuruga, kupakia kupita kiasi au kudukua mifumo ya huduma.</li>
</ul>

<h2>4. Gharama</h2>
<p>SMS kwenda 15054 hutozwa na mtandao wako wa simu kwa viwango vya kawaida vya SMS isipokuwa ikitangazwa vinginevyo. Web chat hutumia bando la intaneti la mtumiaji. Huru SMS haitozi ada ya ziada kwa sasa.</p>

<h2>5. Taarifa zako</h2>
<p>Tunahifadhi namba yako ya simu, maswali na majibu ili kuendeleza mazungumzo na kuboresha huduma. Soma <a href="{{ route('legal.privacy') }}">Sera ya Faragha</a> kwa maelezo kamili. Tuma ACHA kwa SMS kusitisha majibu wakati wowote.</p>

<h2>6. Upatikanaji na mabadiliko</h2>
<p>Huduma inaweza kusitishwa kwa muda kwa matengenezo. Tunaweza kubadilisha vigezo hivi; toleo jipya litawekwa kwenye ukurasa huu.</p>

<h2>7. Mawasiliano</h2>
<p>Huru Digital Co. Ltd., Tanzania. Tumia fomu ya mawasiliano kwenye <a href="{{ route('welcome') }}#wasiliana">ukurasa wa mwanzo</a>.</p>
@endsection
```

99 resources/views/offline.blade.php

28 lines

```
<!DOCTYPE html>
<html lang="sw">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Uko nje ya mtandao – Huru SMS</title>
    <meta name="robots" content="noindex">
    <link rel="icon" href="/logo.svg" type="image/svg+xml">
    <style>
        body{font-family:Inter,system-ui,sans-serif;background:#f8fafc;color:#0f172a;margin:0;display:flex;align-items:center;justify-content:center;min-height:100vh;padding:16px}
        .box{background:#fff;border:2px solid #15803d;border-radius:12px;padding:28px;max-width:440px;text-align:center}
        .code{font-size:2.6rem;font-weight:800;color:#166534;margin:8px 0}
        .kw{display:inline-block;background:#dcfce7;color:#14532d;font-weight:800;padding:2px 8px;border-radius:4px;border:1px solid #86efac}
        a.btn{display:inline-block;margin-top:16px;background:#15803d;color:#fff;text-decoration:none;font-weight:700;padding:12px 18px;border-radius:8px}
        p{color:#475569;line-height:1.5}
    </style>
</head>
<body>
<div class="box">
    <h1 style="font-size:1.3rem;margin:0">Uko nje ya mtandao</h1>
    <p>Hakuna intaneti kwa sasa. Bado unaweza kuuliza kwa SMS kutoka simu yoyote.</p>
    <div class="code">15054</div>
    <p>Tuma <span class="kw">HURU</span> kisha swali lako kwenda <strong>15054</strong>.</p>
    <a class="btn" href="sms:15054?body=HURU%20">Tuma SMS sasa</a>
    <p style="font-size:.85rem;margin-top:18px">Ukirudi mtandaoni, <a href="/chat">fungua web chat tena</a>.</p>
</div>
</body>
</html>
```

100 **resources/views/pagination/simple.blade.php** 15 lines

```
@if ($paginator->hasPages())
    <nav style="display:flex;gap:8px;justify-content:center;align-items:center;margin:12px 0;font-size:.88rem">
        @if ($paginator->onFirstPage())
            <span style="color:#94a3b8">‹ Nyuma</span>
        @else
            <a href="{{ $paginator->previousPageUrl() }}" rel="prev" style="color:#1d4ed8;font-weight:600;text-decoration:none">‹ Nyuma</a>
        @endif
        <span style="color:#475569">{{ $paginator->currentPage() }} / {{ $paginator->lastPage() }}</span>
        @if ($paginator->hasMorePages())
            <a href="{{ $paginator->nextPageUrl() }}" rel="next" style="color:#1d4ed8;font-weight:600;text-decoration:none">Mbele ›</a>
        @else
            <span style="color:#94a3b8">Mbele ›</span>
        @endif
    </nav>
@endif
```

101 resources/views/welcome.blade.php

229 lines

```
<!DOCTYPE html>
<html lang="sw">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>{{ $settings['app_name'] }} – Uliza lolote, kwa SMS {{ $settings['sms_shortcode'] }} au mtandaoni</title>
    <meta name="description" content="{{ $settings['app_name'] }} hujibu swali lolote la maisha ya kila siku Tanzania: sheria, afya, kilimo, masomo, huduma za serikali, fedha, ajira. Tuma {{ $settings['sms_keyword'] }} kwenda {{ $settings['sms_shortcode'] }} bila intaneti, au tumia web chat.">
    <meta name="keywords" content="Huru SMS, SMS {{ $settings['sms_shortcode'] }}, maswali Tanzania, sheria, afya, kilimo, NIDA, TRA, elimu, msaada wa kisheria, Kiswahili">
    <meta name="author" content="Huru Digital Co. Ltd.">
    <meta name="robots" content="index, follow">
    <link rel="canonical" href="{{ url('/') }}">
    <meta property="og:type" content="website">
    <meta property="og:site_name" content="{{ $settings['app_name'] }}">
    <meta property="og:title" content="{{ $settings['app_name'] }} – Uliza lolote kwa SMS {{ $settings['sms_shortcode'] }}">
    <meta property="og:description" content="Majibu ya haraka kwa maswali ya sheria, afya, kilimo, masomo, huduma za serikali na zaidi. Kiswahili au Kiingereza.">
    <meta property="og:url" content="{{ url('/') }}">
    <meta property="og:image" content="{{ url('/og-image.svg') }}">
    <link rel="manifest" href="/manifest.json">
    <link rel="icon" href="/logo.svg" type="image/svg+xml">
    <link rel="apple-touch-icon" href="/logo.svg">
    <meta name="theme-color" content="#15803d">
    @verbatim
    <script type="application/ld+json">
    {"@context":"https://schema.org","@type":"WebApplication","name":"Huru SMS","applicationCategory":"UtilitiesApplication","operatingSystem":"Any","description":"Everyday question answering service for Tanzanians over SMS and web, in Swahili and English.","offers":{"@type":"Offer","price":"0","priceCurrency":"TZS"}}
    </script>
    @endverbatim
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
    <link href="https://fonts.googleapis.com/css2?family=Inter:wght@400;500;600;700;800&display=swap" rel="stylesheet">
    <style>
        :root{--green:#15803d;--green-dark:#166534;--green-bg:#f0fdf4;--green-border:#bbf7d0;--blue:#1d4ed8;--blue-dark:#1e40af;--blue-bg:#eff6ff;--bg:#f8fafc;--card:#ffffff;--text:#0f172a;--muted:#475569;--border:#cbd5e1;--radius:12px}
        *{margin:0;padding:0;box-sizing:border-box}
        html{scroll-behavior:smooth}
        body{font-family:'Inter',system-ui,sans-serif;background:var(--bg);color:var(--text);line-height:1.55}
        a{color:var(--blue)}
        .wrap{max-width:1080px;margin:0 auto;padding:0 16px}
        header{background:#fff;border-bottom:1px solid var(--border);position:sticky;top:0;z-index:20}
        .nav{display:flex;align-items:center;justify-content:space-between;height:64px}
        .brand{display:flex;align-items:center;gap:10px;text-decoration:none;color:var(--green-dark);font-weight:800;font-size:1.3rem}
        .brand img{width:36px;height:36px;border-radius:8px}
        .nav-links{display:flex;gap:8px;align-items:center}
        .nav-links a{text-decoration:none;font-weight:600;font-size:.9rem;padding:8px 14px;border-radius:8px;color:var(--muted)}
        .nav-links a:hover{background:var(--bg);color:var(--text)}
        .nav-links a.primary{background:var(--green);color:#fff}
        .nav-links a.primary:hover{background:var(--green-dark)}
        .sms-pill{display:inline-flex;align-items:center;gap:6px;background:var(--green-bg);border:1px solid var(--green-border);color:var(--green-dark);font-weight:700;font-size:.85rem;padding:6px 12px;border-radius:999px}
        .hero{padding:48px 0 32px;display:grid;grid-template-columns:1.2fr 1fr;gap:32px;align-items:center}
        .hero h1{font-size:2.4rem;line-height:1.15;font-weight:800;letter-spacing:-.02em;margin:14px 0}
        .hero h1 span{color:var(--green)}
        .hero p.lead{font-size:1.1rem;color:var(--muted);max-width:52ch}
        .hero p.sub{font-size:.95rem;color:var(--muted);margin-top:8px}
        .chips{display:flex;flex-wrap:wrap;gap:8px;margin-top:20px}
        .chip{background:#fff;border:1px solid var(--border);border-radius:999px;padding:6px 12px;font-size:.85rem;font-weight:600;color:var(--muted)}
        .sms-card{background:var(--card);border:2px solid var(--green);border-radius:var(--radius);padding:24px}
        .sms-card .label{font-size:.75rem;letter-spacing:.08em;text-transform:uppercase;font-weight:800;color:var(--green-dark)}
```

```
        .sms-card .code{font-size:3rem;font-weight:800;color:var(--green-dark);line-height:1;margin:8px 0}
        .sms-card .how{background:var(--green-bg);border:1px solid var(--green-border);border-radius:8px;padding:12px 14px;margin:14px 0;font-size:.95rem}
        .kw{display:inline-block;background:#dcfce7;color:#14532d;font-weight:800;padding:2px 8px;border-radius:4px;border:1px solid #86efac}
        .sms-card .example{font-size:.85rem;color:var(--muted);font-style:italic;margin-top:6px}
        .btn{display:inline-flex;align-items:center;justify-content:center;gap:8px;text-decoration:none;font-weight:700;padding:12px 18px;border-radius:8px;border:2px solid transparent;font-size:.95rem;cursor:pointer}
        .btn-green{background:var(--green);color:#fff}
        .btn-green:hover{background:var(--green-dark)}
        .btn-blue-outline{background:#fff;border-color:var(--blue);color:var(--blue)}
        .btn-blue-outline:hover{background:var(--blue-bg)}
        .btn-row{display:flex;gap:10px;flex-wrap:wrap;margin-top:6px}
        .btn-row .btn{flex:1;min-width:160px}
        section{padding:36px 0}
        h2{font-size:1.5rem;font-weight:800;letter-spacing:-.01em;margin-bottom:6px}
        .section-sub{color:var(--muted);margin-bottom:22px}
        .steps{display:grid;grid-template-columns:repeat(3,1fr);gap:16px}
        .step{background:var(--card);border:1px solid var(--border);border-radius:var(--radius);padding:20px}
        .step .n{width:34px;height:34px;border-radius:8px;background:var(--blue);color:#fff;font-weight:800;display:flex;align-items:center;justify-content:center;margin-bottom:12px}
        .step h3{font-size:1.05rem;margin-bottom:6px}
        .step p{color:var(--muted);font-size:.93rem}
        .topics{display:grid;grid-template-columns:repeat(3,1fr);gap:14px}
        .topic{background:var(--card);border:1px solid var(--border);border-radius:var(--radius);padding:18px;text-decoration:none;color:var(--text);display:block;transition:border-color .15s}
        .topic:hover{border-color:var(--green)}
        .topic h3{font-size:1rem;color:var(--green-dark);margin-bottom:6px}
        .topic p{font-size:.88rem;color:var(--muted)}
        .topic .q{display:block;margin-top:10px;font-size:.85rem;color:var(--blue);font-weight:600}
        .voices{display:grid;grid-template-columns:repeat(3,1fr);gap:14px}
        .voice{background:var(--card);border:1px solid var(--border);border-radius:var(--radius);padding:18px;font-size:.93rem}
        .voice .who{margin-top:10px;font-size:.8rem;color:var(--muted);font-weight:600}
        .trust{display:grid;grid-template-columns:repeat(4,1fr);gap:14px}
        .trust div{background:var(--card);border:1px solid var(--border);border-radius:var(--radius);padding:16px;font-size:.9rem}
        .trust strong{display:block;color:var(--green-dark);margin-bottom:4px}
        .contact{background:var(--card);border:1px solid var(--border);border-radius:var(--radius);padding:24px;display:grid;grid-template-columns:1fr 1fr;gap:24px}
        .contact form{display:grid;gap:10px}
        .contact input,.contact textarea,.contact select{width:100%;padding:11px 12px;border:1.5px solid var(--border);border-radius:8px;font:inherit;font-size:.93rem;background:#fff}
        .contact input:focus,.contact textarea:focus{outline:none;border-color:var(--green)}
        .alert{padding:12px 14px;border-radius:8px;font-size:.9rem;font-weight:600;margin-bottom:12px}
        .alert-ok{background:var(--green-bg);border:1px solid var(--green-border);color:var(--green-dark)}
        .alert-err{background:#fef2f2;border:1px solid #fecaca;color:#991b1b}
        .hp{position:absolute;left:-9999px}
        footer{background:#fff;border-top:1px solid var(--border);padding:24px 0;font-size:.85rem;color:var(--muted)}
        footer .wrap{display:flex;justify-content:space-between;gap:12px;flex-wrap:wrap}
        footer a{color:var(--muted);text-decoration:none;margin-left:16px}
        footer a:hover{color:var(--blue)}
        @media (max-width:860px){.hero{grid-template-columns:1fr;padding-top:28px}.steps,.topics,.voices{grid-template-columns:1fr}.trust{grid-template-columns:1fr 1fr}.contact{grid-template-columns:1fr}.hero h1{font-size:1.9rem}.nav-links a:not(.primary){display:none}}
    </style>
</head>
<body>
<header>
    <div class="wrap nav">
        <a href="/" class="brand" aria-label="{{ $settings['app_name'] }}"><img src="/logo.svg" alt="" width="36" height="36">{{ $settings['app_name'] }}</a>
        <div class="nav-links">
            <span class="sms-pill">SMS: {{ $settings['sms_keyword'] }} → {{ $settings['sms_shortcode'] }}</span>
            <a href="#mada">Mada</a>
            <a href="{{ route('community.index') }}">Jamii</a>
            <a href="{{ route('chat.index') }}" class="primary">Fungua Web Chat</a>
        </div>
    </div>
</header>

<main>
```

```
    <div class="wrap">
        <div class="hero">
            <div>
                <span class="sms-pill">Kwa kila Mtanzania · For every Tanzanian</span>
                <h1>Uliza <span>lolote</span>. Pata jibu la haraka, kwa lugha yako.</h1>
                <p class="lead">Sheria, afya, kilimo, masomo, huduma za serikali, fedha, ajira, teknolojia au swali la kawaida tu. {{ $settings['app_name'] }} hujibu kwa Kiswahili au Kiingereza, kwa muktadha wa Tanzania, kwa simu yoyote.</p>
                <p class="sub">Ask anything about life in Tanzania and get a clear, practical answer in Swahili or English, on any phone.</p>
                <div class="chips">
                    <span class="chip">Sheria na haki</span><span class="chip">Afya</span><span class="chip">Kilimo na mifugo</span><span class="chip">Masomo</span><span class="chip">NIDA · TRA · RITA</span><span class="chip">Fedha na biashara</span><span class="chip">Ajira</span><span class="chip">Familia</span>
                </div>
            </div>

            <div class="sms-card">
                <div class="label">Njia kuu: SMS bila intaneti</div>
                <div class="code">{{ $settings['sms_shortcode'] }}</div>
                <div class="how">
                    Tuma neno <span class="kw">{{ $settings['sms_keyword'] }}</span> kisha swali lako kwenda <strong>{{ $settings['sms_shortcode'] }}</strong> kutoka simu yoyote.
                    <div class="example">Mfano: <strong>{{ $settings['sms_keyword'] }} nifanyeje kupata kitambulisho cha NIDA?</strong></div>
                </div>
                <div class="btn-row">
                    <a class="btn btn-green" href="sms:{{ $settings['sms_shortcode'] }}?body={{ $settings['sms_keyword'] }}%20">Tuma SMS sasa</a>
                    <a class="btn btn-blue-outline" href="{{ route('chat.index') }}">Au tumia Web Chat</a>
                </div>
                <p class="example" style="margin-top:12px">Una intaneti? Web chat inakumbuka mazungumzo yako na inakuruhusu kutafuta majibu ya zamani.</p>
            </div>
        </div>

        <section id="jinsi">
            <h2>Jinsi inavyofanya kazi</h2>
            <p class="section-sub">Hatua tatu tu. Hakuna programu ya kupakua, hakuna usajili mrefu.</p>
            <div class="steps">
                <div class="step"><div class="n">1</div><h3>Uliza</h3><p>Andika swali lako kwa Kiswahili au Kiingereza. Taja mahali ulipo (mfano "nipo Kahama") ukihitaji huduma iliyo karibu.</p></div>
                <div class="step"><div class="n">2</div><h3>Tunaelewa muktadha</h3><p>{{ $settings['app_name'] }} hutambua mada, lugha na eneo lako, kisha huchanganya maarifa yaliyothibitishwa ya Tanzania na anwani rasmi.</p></div>
                <div class="step"><div class="n">3</div><h3>Pata jibu la vitendo</h3><p>Jibu fupi, la kweli, lenye hatua za kuchukua na ofisi au namba ya kuwasiliana nayo. Uliza swali la kufuatilia wakati wowote.</p></div>
            </div>
        </section>

        <section id="mada">
            <h2>Mada tunazoshughulikia</h2>
            <p class="section-sub">Bonyeza mada kuanza na mfano wa swali kwenye web chat.</p>
            <div class="topics">
                <a class="topic" href="{{ route('chat.index') }}?q=Haki zangu ni zipi nikikamatwa na polisi?"><h3>Sheria na haki</h3><p>Kukamatwa, ardhi, ndoa, mirathi, mikataba, msaada wa kisheria karibu nawe.</p><span class="q">"Haki zangu ni zipi nikikamatwa na polisi?"</span></a>
                <a class="topic" href="{{ route('chat.index') }}?q=Dalili za malaria kwa mtoto na nifanye nini?"><h3>Afya</h3><p>Dalili za hatari, kliniki, chanjo, bima ya afya (NHIF/iCHF), lishe.</p><span class="q">"Dalili za malaria kwa mtoto ni zipi?"</span></a>
                <a class="topic" href="{{ route('chat.index') }}?q=Nipande mahindi lini Dodoma na nitumie mbegu gani?"><h3>Kilimo na mifugo</h3><p>Misimu, mbegu bora, wadudu, chanjo za mifugo, bei na masoko.</p><span class="q">"Nipande mahindi lini Dodoma?"</span></a>
                <a class="topic" href="{{ route('chat.index') }}?q=Nieleze photosynthesis kwa Kiswahili kwa mwanafunzi wa kidato cha pili"><h3>Masomo</h3><p>Hisabati, sayansi, lugha, NECTA, mikopo ya HESLB, vyuo.</p><span class="q">"Nieleze photosynthesis kwa kidato cha pili"</span></a>
                <a class="topic" href="{{ route('chat.index') }}?q=Nifanyeje kupata kitambulisho cha NIDA?"><h3>Huduma za serikali</h3><p>NIDA, RITA, pasipoti, TIN, GePG, LUKU, leseni.</p><span class="q">"Nifanyeje kupata kitambulisho cha NIDA?"</span></a>
                <a class="topic" href="{{ route('chat.index') }}?q=Nianzeje biashara ndogo na nisajili wapi?"><h3>Fedha na biashara</h3><p>Kodi za TRA, mikopo, pesa za simu, kuepuka utapeli, kusajili biashara.</p><span class="q">"Nianzeje biashara ndogo?"</span></a>
                <a class="topic" href="{{ route('chat.index') }}?q=Nimefukuzwa kazi bila notisi, nifanye nini?"><h3>Ajira na kazi</h3><p>Mikataba, likizo, kuachishwa kazi, CMA, kutafuta kazi.</p><span class="q">"Nimefukuzwa kazi bila
```

```
notisi, nifanye nini?"</span></a>
   164                 <a class="topic" href="{{ route('chat.index') }}?q=Nipate wapi msaada kwa ukatili wa kijinsia
Mwanza?"><h3>Familia na jamii</h3><p>Ukatili wa kijinsia, haki za mtoto, ustawi wa jamii, mahusiano.</p><span
class="q">"Nipate wapi msaada kwa ukatili Mwanza?"</span></a>
   165                 <a class="topic" href="{{ route('chat.index') }}?q=Laini yangu imepotea, nifanyeje kuirudisha?">
<h3>Teknolojia na usafiri</h3><p>Laini za simu, udukuzi, faini za trafiki, leseni ya udereva, nauli.</p><span
class="q">"Laini yangu imepotea, nifanyeje?"</span></a>
   166             </div>
   167         </section>
   168
   169         <section>
   170             <h2>Kwa nini {{ $settings['app_name'] }}</h2>
   171             <div class="trust">
   172                 <div><strong>Muktadha wa Tanzania</strong>Sheria, taasisi, misimu, sarafu na namba za dharura za
hapa, si za nchi nyingine.</div>
   173                 <div><strong>Lugha yako</strong>Kiswahili au Kiingereza, inafuata lugha unayoandika. Tuma LUGHA SW
au LUGHA EN kubadilisha.</div>
   174                 <div><strong>Huduma zilizo karibu</strong>Taja mkoa, wilaya au mtaa wako na upate watoa huduma
walio karibu nawe.</div>
   175                 <div><strong>Uaminifu</strong>Tunasema wazi pale jambo linapohitaji kuthibitishwa na ofisi husika.
Hatuzushi namba wala bei.</div>
   176             </div>
   177         </section>
   178
   179         @if($communityPosts->isNotEmpty())
   180         <section>
   181             <h2>Sauti za wananchi</h2>
   182             <p class="section-sub">Maoni yaliyothibitishwa kutoka kwenye jamii ya {{ $settings['app_name'] }}.</p>
   183             <div class="voices">
   184                 @foreach($communityPosts as $post)
   185                     <div class="voice">"{{ \Illuminate\Support\Str::limit($post->content, 180) }}"<div class="who">
{{ $post->user?->displayName() ?? 'Mwananchi' }} · {{ $post->created_at->diffForHumans() }}</div></div>
   186                 @endforeach
   187             </div>
   188         </section>
   189         @endif
   190
   191         <section id="wasiliana">
   192             <h2>Wasiliana nasi</h2>
   193             <p class="section-sub">Taasisi, halmashauri, shule au shirika linalotaka kushirikiana, au maoni yoyote.
</p>
   194             <div class="contact">
   195                 <div>
   196                     @if(session('contact_success'))<div class="alert alert-ok">{{ session('contact_success') }}
</div>@endif
   197                     @if(session('contact_error'))<div class="alert alert-err">{{ session('contact_error') }}
</div>@endif
   198                     @if($errors->any())<div class="alert alert-err">{{ $errors->first() }}</div>@endif
   199                     <form method="POST" action="{{ route('contact.submit') }}">
   200                         @csrf
   201                         <input class="hp" type="text" name="website" tabindex="-1" autocomplete="off">
   202                         <select name="type"><option value="general">Ujumbe wa kawaida</option><option
value="partner">Ushirikiano / Partnership</option><option value="subscribe">Nitumie taarifa za maendeleo</option></select>
   203                         <input type="text" name="name" placeholder="Jina lako" maxlength="80">
   204                         <input type="email" name="email" placeholder="Barua pepe" required>
   205                         <input type="text" name="organisation" placeholder="Taasisi / Shirika (si lazima)"
maxlength="120">
   206                         <textarea name="message" rows="4" placeholder="Ujumbe wako"></textarea>
   207                         <button class="btn btn-green" type="submit">Tuma</button>
   208                     </form>
   209                 </div>
   210                 <div>
   211                     <h3 style="margin-bottom:8px">Kwa simu yoyote, popote</h3>
   212                     <p style="color:var(--muted);font-size:.93rem">Huduma hii imejengwa kwa simu za kawaida kwanza.
Hata bila bando, tuma <strong>{{ $settings['sms_keyword'] }}</strong> kwenda <strong>{{ $settings['sms_shortcode'] }}
</strong>.</p>
   213                     <p style="color:var(--muted);font-size:.93rem;margin-top:12px"><strong>Amri za SMS:</strong>
<br>MSAADA – orodha ya msaada<br>LUGHA SW / LUGHA EN – chagua lugha<br>MKOA Mwanza – hifadhi mkoa wako<br>JINA Asha –
hifadhi jina lako<br>ACHA / ANZA – sitisha au endelea</p>
   214                     <p style="color:var(--muted);font-size:.85rem;margin-top:12px">Dharura: Polisi 112 · Zimamoto
114 · Gari la wagonjwa 115 · Msaada kwa mtoto 116</p>
   215                 </div>
   216             </div>
```

```
        </section>
    </div>
</main>

<footer>
    <div class="wrap">
        <div>© {{ date('Y') }} Huru Digital Co. Ltd. · SMS: <strong>{{ $settings['sms_keyword'] }}</strong> kwenda <strong>{{ $settings['sms_shortcode'] }}</strong></div>
        <div><a href="{{ route('legal.terms') }}">Vigezo na Masharti</a><a href="{{ route('legal.privacy') }}">Sera ya Faragha</a><a href="{{ route('community.index') }}">Jamii</a></div>
    </div>
</footer>
<script>if('serviceWorker' in navigator){navigator.serviceWorker.register('/sw.js').catch(()=>{});}</script>
</body>
</html>
```

102 **routes/api.php** 10 lines

```php
<?php

use App\Http\Controllers\SmsController;
use Illuminate\Support\Facades\Route;

// Africa's Talking callbacks. Register them with ?token=<AT_WEBHOOK_SECRET>.
Route::middleware('sms.webhook')->group(function () {
    Route::post('/sms/inbound', [SmsController::class, 'inbound'])->name('sms.inbound');
    Route::post('/sms/delivery', [SmsController::class, 'deliveryReport'])->name('sms.delivery');
});
```

103 routes/console.php

11 lines

```php
<?php

use Illuminate\Support\Facades\Schedule;

// Drain the database queue every minute on hosts without a long-running worker.
Schedule::command('queue:work --stop-when-empty --tries=2 --max-time=50')
    ->everyMinute()
    ->withoutOverlapping();

// Keep the local legal aid directory fresh.
Schedule::command('huru:import-legal-aid')->weeklyOn(1, '03:00');
```

104 **routes/web.php** 120 lines

```php
<?php

use App\Http\Controllers\Admin\AuthController;
use App\Http\Controllers\Admin\ConversationController;
use App\Http\Controllers\Admin\DashboardController;
use App\Http\Controllers\Admin\KnowledgeController;
use App\Http\Controllers\Admin\LocalResourceController;
use App\Http\Controllers\Admin\PromptTemplateController;
use App\Http\Controllers\Admin\ReferenceContactController;
use App\Http\Controllers\Admin\SettingController;
use App\Http\Controllers\Admin\UserController;
use App\Http\Controllers\CommunityController;
use App\Http\Controllers\ContactController;
use App\Http\Controllers\WebChatController;
use App\Models\CommunityPost;
use App\Support\Settings;
use Illuminate\Support\Facades\Route;

Route::get('/', function () {
    $communityPosts = CommunityPost::query()
        ->where('is_approved', true)
        ->whereHas('thread', fn ($q) => $q->where('slug', 'general-advice'))
        ->with('user')
        ->latest()
        ->take(6)
        ->get();

    return view('welcome', [
        'communityPosts' => $communityPosts,
        'settings' => [
            'app_name' => Settings::get('app_name'),
            'sms_keyword' => Settings::get('sms_keyword'),
            'sms_shortcode' => Settings::get('sms_shortcode'),
        ],
    ]);
})->name('welcome');

// Web chat (citizen)
Route::prefix('chat')->name('chat.')->group(function () {
    Route::get('/', [WebChatController::class, 'index'])->name('index');
    Route::get('/session', [WebChatController::class, 'session'])->name('session');
    Route::post('/request-otp', [WebChatController::class, 'requestOtp'])->middleware('throttle:10,1')->name('otp.request');
    Route::post('/verify-otp', [WebChatController::class, 'verifyOtp'])->middleware('throttle:10,1')->name('otp.verify');
    Route::get('/messages', [WebChatController::class, 'messages'])->name('messages');
    Route::post('/send', [WebChatController::class, 'send'])->middleware('throttle:20,1')->name('send');
    Route::post('/feedback', [WebChatController::class, 'feedback'])->name('feedback');
    Route::post('/preferences', [WebChatController::class, 'preferences'])->name('preferences');
    Route::post('/logout', [WebChatController::class, 'logout'])->name('logout');
});

// Legal pages
Route::view('/terms-and-conditions', 'legal.terms')->name('legal.terms');
Route::view('/privacy-policy', 'legal.privacy')->name('legal.privacy');
Route::view('/offline', 'offline')->name('offline');

// Community
Route::prefix('community')->name('community.')->group(function () {
    Route::get('/', [CommunityController::class, 'index'])->name('index');
    Route::post('/threads', [CommunityController::class, 'storeThread'])->name('threads.store');
    Route::get('/threads/{thread:slug}', [CommunityController::class, 'show'])->name('show');
    Route::post('/threads/{thread:slug}/posts', [CommunityController::class, 'storePost'])->middleware('throttle:30,1')->name('posts.store');
    Route::post('/threads/{thread:slug}/join', [CommunityController::class, 'join'])->name('join');
    Route::post('/threads/{thread:slug}/leave', [CommunityController::class, 'leave'])->name('leave');
});

Route::post('/contact', [ContactController::class, 'submit'])->name('contact.submit');

// Admin
```

```php
Route::prefix('admin')->name('admin.')->group(function () {
    Route::get('/login', [AuthController::class, 'showLogin'])->name('login');
    Route::post('/login', [AuthController::class, 'login'])->middleware('throttle:10,1')->name('login.post');
    Route::post('/logout', [AuthController::class, 'logout'])->name('logout');

    Route::middleware(['auth', 'admin'])->group(function () {
        Route::get('/', [DashboardController::class, 'index'])->name('dashboard');

        Route::get('/conversations', [ConversationController::class, 'index'])->name('conversations.index');
        Route::get('/conversations/{user}', [ConversationController::class, 'show'])->name('conversations.show');

        Route::get('/knowledge', [KnowledgeController::class, 'index'])->name('knowledge.index');
        Route::get('/knowledge/create', [KnowledgeController::class, 'create'])->name('knowledge.create');
        Route::post('/knowledge', [KnowledgeController::class, 'store'])->name('knowledge.store');
        Route::post('/knowledge/import', [KnowledgeController::class, 'import'])->name('knowledge.import');
        Route::get('/knowledge/{knowledge}/edit', [KnowledgeController::class, 'edit'])->name('knowledge.edit');
        Route::put('/knowledge/{knowledge}', [KnowledgeController::class, 'update'])->name('knowledge.update');
        Route::patch('/knowledge/{knowledge}/toggle', [KnowledgeController::class, 'toggle'])->name('knowledge.toggle');
        Route::delete('/knowledge/{knowledge}', [KnowledgeController::class, 'destroy'])->name('knowledge.destroy');

        Route::get('/templates', [PromptTemplateController::class, 'index'])->name('templates.index');
        Route::get('/templates/create', [PromptTemplateController::class, 'create'])->name('templates.create');
        Route::post('/templates', [PromptTemplateController::class, 'store'])->name('templates.store');
        Route::get('/templates/{template}/edit', [PromptTemplateController::class, 'edit'])->name('templates.edit');
        Route::put('/templates/{template}', [PromptTemplateController::class, 'update'])->name('templates.update');
        Route::patch('/templates/{template}/toggle', [PromptTemplateController::class, 'toggle'])->name('templates.toggle');
        Route::delete('/templates/{template}', [PromptTemplateController::class, 'destroy'])->name('templates.destroy');

        Route::get('/contacts', [ReferenceContactController::class, 'index'])->name('contacts.index');
        Route::get('/contacts/create', [ReferenceContactController::class, 'create'])->name('contacts.create');
        Route::post('/contacts', [ReferenceContactController::class, 'store'])->name('contacts.store');
        Route::get('/contacts/{contact}/edit', [ReferenceContactController::class, 'edit'])->name('contacts.edit');
        Route::put('/contacts/{contact}', [ReferenceContactController::class, 'update'])->name('contacts.update');
        Route::patch('/contacts/{contact}/verify', [ReferenceContactController::class, 'verify'])->name('contacts.verify');
        Route::delete('/contacts/{contact}', [ReferenceContactController::class, 'destroy'])->name('contacts.destroy');

        Route::get('/resources', [LocalResourceController::class, 'index'])->name('resources.index');
        Route::get('/resources/create', [LocalResourceController::class, 'create'])->name('resources.create');
        Route::post('/resources', [LocalResourceController::class, 'store'])->name('resources.store');
        Route::get('/resources/{resource}/edit', [LocalResourceController::class, 'edit'])->name('resources.edit');
        Route::put('/resources/{resource}', [LocalResourceController::class, 'update'])->name('resources.update');
        Route::delete('/resources/{resource}', [LocalResourceController::class, 'destroy'])->name('resources.destroy');

        Route::get('/users', [UserController::class, 'index'])->name('users.index');
        Route::patch('/users/{user}/ban', [UserController::class, 'toggleBan'])->name('users.ban');
        Route::patch('/users/{user}/strikes', [UserController::class, 'resetStrikes'])->name('users.strikes');
        Route::delete('/users/{user}', [UserController::class, 'destroy'])->name('users.destroy');

        Route::get('/settings', [SettingController::class, 'index'])->name('settings.index');
        Route::post('/settings', [SettingController::class, 'update'])->name('settings.update');
    });
});
```

105 tests/Feature/CommunityTest.php

45 lines

```php
<?php

namespace Tests\Feature;

use App\Models\CommunityThread;
use App\Models\User;
use Illuminate\Foundation\Testing\RefreshDatabase;
use Tests\TestCase;

class CommunityTest extends TestCase
{
    use RefreshDatabase;

    public function test_guest_is_redirected_to_chat(): void
    {
        $this->get(route('community.index'))->assertRedirect(route('chat.index', ['redirect' => '/community']));
    }

    public function test_user_can_create_join_and_post(): void
    {
        $user = User::factory()->create();
        $session = ['chat_user_id' => $user->id];

        $this->withSession($session)->post(route('community.threads.store'), ['title' => 'Bei za mahindi', 'description' => 'Dodoma'])->assertRedirect();
        $thread = CommunityThread::where('title', 'Bei za mahindi')->firstOrFail();
        $this->assertTrue($thread->members()->where('user_id', $user->id)->exists());

        $other = User::factory()->create();
        $this->withSession(['chat_user_id' => $other->id])->post(route('community.join', $thread->slug))->assertRedirect(route('community.show', $thread));
        $this->withSession(['chat_user_id' => $other->id])->post(route('community.posts.store', $thread->slug), ['content' => 'Shilingi 800 kwa kilo Kongwa'])->assertRedirect();

        $this->assertDatabaseHas('community_posts', ['content' => 'Shilingi 800 kwa kilo Kongwa', 'is_approved' => true]);
        $this->withSession($session)->get(route('community.show', $thread->slug))->assertOk()->assertSee('Shilingi 800');
    }

    public function test_abusive_posts_are_rejected(): void
    {
        $user = User::factory()->create();
        $thread = CommunityThread::create(['title' => 'T', 'slug' => 't', 'is_private' => false]);
        $thread->members()->attach($user->id);

        $this->withSession(['chat_user_id' => $user->id])->postJson(route('community.posts.store', $thread->slug), ['content' => 'wewe mjinga sana'])->assertStatus(422);
        $this->assertSame(1, $user->fresh()->abuse_count);
    }
}
```

106 **tests/Feature/SmsFlowTest.php** 108 lines

```php
<?php

namespace Tests\Feature;

use App\Jobs\ProcessIncomingSms;
use App\Models\AiLog;
use App\Models\Message;
use App\Models\User;
use App\Services\Ai\LlmClient;
use App\Services\SmsService;
use App\Support\Settings;
use Illuminate\Foundation\Testing\RefreshDatabase;
use Illuminate\Support\Facades\Queue;
use Mockery\MockInterface;
use Tests\TestCase;

class SmsFlowTest extends TestCase
{
    use RefreshDatabase;

    public function test_inbound_webhook_rejects_bad_token_when_secret_is_set(): void
    {
        config(['services.at.webhook_secret' => 'topsecret']);
        Queue::fake();

        $this->post('/api/sms/inbound', ['from' => '+255712345678', 'text' => 'HURU habari'])->assertStatus(401);
        $this->post('/api/sms/inbound?token=topsecret', ['from' => '+255712345678', 'text' => 'HURU habari'])->assertOk();

        Queue::assertPushed(ProcessIncomingSms::class, fn ($job) => $job->from === '+255712345678' && $job->text === 'habari');
    }

    public function test_inbound_strips_keyword_and_normalises_phone(): void
    {
        config(['services.at.webhook_secret' => null]);
        Queue::fake();

        $this->post('/api/sms/inbound', ['from' => '0712345678', 'text' => 'huru  Nifanyeje kupata NIDA?'])->assertOk();

        Queue::assertPushed(ProcessIncomingSms::class, fn ($job) => $job->from === '+255712345678' && $job->text === 'Nifanyeje kupata NIDA?');
    }

    public function test_job_answers_logs_and_sends_sms(): void
    {
        $this->mock(LlmClient::class, function (MockInterface $mock) {
            $mock->shouldReceive('isConfigured')->andReturn(true);
            $mock->shouldReceive('generate')->once()->andReturn([
                'status' => LlmClient::STATUS_OK, 'text' => 'Nenda ofisi ya mtendaji wa kata na cheti cha kuzaliwa.',
                'model' => 'gemini-test', 'tokens' => ['prompt' => 10, 'completion' => 5, 'total' => 15], 'latency_ms' => 120, 'finish_reason' => 'STOP', 'error' => null,
            ]);
        });
        $this->mock(SmsService::class, function (MockInterface $mock) {
            $mock->shouldReceive('send')->once()->with('+255712345678', 'Nenda ofisi ya mtendaji wa kata na cheti cha kuzaliwa.')->andReturn(['status' => 'success']);
        });

        (new ProcessIncomingSms('+255712345678', 'Nifanyeje kupata kitambulisho cha NIDA?'))->handle(app(\App\Services\ConversationService::class), app(SmsService::class));

        $this->assertDatabaseHas('users', ['phone_number' => '+255712345678']);
        $this->assertDatabaseHas('messages', ['direction' => 'inbound', 'channel' => 'sms', 'category' => 'government']);
        $this->assertDatabaseHas('messages', ['direction' => 'outbound', 'content' => 'Nenda ofisi ya mtendaji wa kata na cheti cha kuzaliwa.']);
        $log = AiLog::first();
        $this->assertSame('gemini-test', $log->model);
```

```
        $this->assertSame(15, $log->total_tokens);
        $this->assertSame('government', $log->category);
    }

    public function test_help_and_language_commands_do_not_call_the_model(): void
    {
        $this->mock(LlmClient::class, function (MockInterface $mock) {
            $mock->shouldReceive('generate')->never();
        });
        $this->mock(SmsService::class, function (MockInterface $mock) {
            $mock->shouldReceive('send')->twice()->andReturn(['status' => 'success']);
        });

        (new ProcessIncomingSms('+255712345678', 'MSAADA'))->handle(app(\App\Services\ConversationService::class),
app(SmsService::class));
        (new ProcessIncomingSms('+255712345678', 'LUGHA EN'))-
>handle(app(\App\Services\ConversationService::class), app(SmsService::class));

        $user = User::where('phone_number', '+255712345678')->first();
        $this->assertSame('en', $user->preferred_language);
        $this->assertSame(4, Message::count());
    }

    public function test_abuse_leads_to_warning_then_ban(): void
    {
        Settings::set('abuse_strike_limit', 2);
        $this->mock(LlmClient::class, fn (MockInterface $m) => $m->shouldReceive('generate')->never());
        $this->mock(SmsService::class, fn (MockInterface $m) => $m->shouldReceive('send')->twice()-
>andReturn(['status' => 'success']));

        $svc = app(\App\Services\ConversationService::class);
        (new ProcessIncomingSms('+255712345678', 'wewe mjinga'))->handle($svc, app(SmsService::class));
        (new ProcessIncomingSms('+255712345678', 'mjinga tena'))->handle($svc, app(SmsService::class));

        $this->assertTrue(User::where('phone_number', '+255712345678')->first()->is_banned);
    }

    public function test_opted_out_user_is_ignored_until_start(): void
    {
        $this->mock(LlmClient::class, fn (MockInterface $m) => $m->shouldReceive('generate')->never());
        $this->mock(SmsService::class, fn (MockInterface $m) => $m->shouldReceive('send')->twice()-
>andReturn(['status' => 'success']));

        $svc = app(\App\Services\ConversationService::class);
        (new ProcessIncomingSms('+255712345678', 'ACHA'))->handle($svc, app(SmsService::class));
        (new ProcessIncomingSms('+255712345678', 'swali lolote'))->handle($svc, app(SmsService::class)); // no
reply
        (new ProcessIncomingSms('+255712345678', 'ANZA'))->handle($svc, app(SmsService::class));

        $this->assertFalse(User::first()->opted_out);
    }
}
```

107 **tests/Feature/WebChatTest.php** 113 lines

```php
<?php

namespace Tests\Feature;

use App\Models\User;
use App\Services\Ai\LlmClient;
use App\Services\SmsService;
use App\Support\Settings;
use Illuminate\Foundation\Testing\RefreshDatabase;
use Illuminate\Support\Facades\Hash;
use Mockery\MockInterface;
use Tests\TestCase;

class WebChatTest extends TestCase
{
    use RefreshDatabase;

    public function test_login_without_otp_when_sms_is_not_configured_locally(): void
    {
        $this->mock(SmsService::class, fn (MockInterface $m) => $m->shouldReceive('isConfigured')->andReturn(false));

        $login = $this->postJson('/chat/request-otp', ['phone_number' => '0712345678'])
            ->assertOk()
            ->assertJsonPath('otp_required', false)
            ->assertJsonPath('user.phone_masked', '+255 *** 678');

        // Login regenerates the session; the rotated CSRF token must be handed back.
        $this->assertNotEmpty($login->json('csrf'));
        $this->assertSame($login->json('csrf'), $this->getJson('/chat/session')->assertJsonPath('authenticated', true)->json('csrf'));
    }

    public function test_otp_flow_when_sms_is_configured(): void
    {
        Settings::set('otp_enabled', '1');
        $this->mock(SmsService::class, function (MockInterface $m) {
            $m->shouldReceive('isConfigured')->andReturn(true);
            $m->shouldReceive('sendOtp')->once()->andReturn(['status' => 'success']);
        });

        $r = $this->postJson('/chat/request-otp', ['phone_number' => '0712345678'])->assertOk()->assertJsonPath('otp_required', true);
        $code = $r->json('debug_code');
        $this->assertNotEmpty($code, 'debug code is exposed in testing');

        $this->getJson('/chat/session')->assertJsonPath('authenticated', false);
        $this->postJson('/chat/verify-otp', ['phone_number' => '0712345678', 'code' => '000000'])->assertStatus(422);
        $this->postJson('/chat/verify-otp', ['phone_number' => '0712345678', 'code' => $code])->assertOk();
        $this->getJson('/chat/session')->assertJsonPath('authenticated', true);

        $this->assertNull(User::first()->otp_hash);
    }

    public function test_messages_require_a_session_and_send_returns_reply(): void
    {
        $this->getJson('/chat/messages')->assertStatus(401);

        $this->mock(LlmClient::class, function (MockInterface $mock) {
            $mock->shouldReceive('isConfigured')->andReturn(true);
            $mock->shouldReceive('generate')->once()->andReturn([
                'status' => LlmClient::STATUS_OK, 'text' => 'Malaria danger signs include convulsions.',
                'model' => 'gemini-test', 'tokens' => ['prompt' => 1, 'completion' => 1, 'total' => 2], 'latency_ms' => 50, 'finish_reason' => 'STOP', 'error' => null,
            ]);
        });

        $user = User::factory()->create(['phone_number' => '+255712345678']);

        $this->withSession(['chat_user_id' => $user->id])
```

```
            ->postJson('/chat/send', ['message' => 'What are malaria danger signs in a child?'])
            ->assertOk()
            ->assertJsonPath('kind', 'answer')
            ->assertJsonPath('category', 'health')
            ->assertJsonPath('reply.content', 'Malaria danger signs include convulsions.');

        $replyId = $this->withSession(['chat_user_id' => $user->id])->getJson('/chat/messages')->json('messages.1.id');

        $this->withSession(['chat_user_id' => $user->id])
            ->postJson('/chat/feedback', ['message_id' => $replyId, 'rating' => 1])
            ->assertOk();

        $this->assertDatabaseHas('feedback', ['message_id' => $replyId, 'rating' => 1]);
    }

    public function test_admin_area_requires_an_admin_account(): void
    {
        $this->get('/admin')->assertRedirect('/admin/login');

        $citizen = User::factory()->create(['email' => 'c@example.com', 'password' => Hash::make('secret123')]);
        $this->actingAs($citizen)->get('/admin')->assertStatus(403);

        $admin = User::factory()->admin()->create(['email' => 'a@example.com', 'password' => Hash::make('secret123')]);
        $this->post('/admin/login', ['email' => 'a@example.com', 'password' => 'secret123'])->assertRedirect('/admin');
        $this->actingAs($admin)->get('/admin')->assertOk()->assertSee('Dashboard');
        $this->actingAs($admin)->get('/admin/settings')->assertOk()->assertSee('Gemini model');
    }

    public function test_settings_only_accept_known_keys(): void
    {
        $admin = User::factory()->admin()->create();

        $this->actingAs($admin)->post('/admin/settings', ['app_name' => 'Huru', 'bogus_key' => 'x'] + $this->defaults())->assertRedirect();
        $this->assertDatabaseMissing('system_settings', ['key' => 'bogus_key']);
        $this->assertSame('Huru', Settings::get('app_name'));
    }

    private function defaults(): array
    {
        $out = [];
        foreach (Settings::schema() as $k => $def) {
            $out[$k] = $def['default'];
        }

        return $out;
    }
}
```

108 **tests/TestCase.php** 10 lines

```php
<?php

namespace Tests;

use Illuminate\Foundation\Testing\TestCase as BaseTestCase;

abstract class TestCase extends BaseTestCase
{
    //
}
```

109 tests/Unit/LanguageAndLocationTest.php

59 lines

```php
<?php

namespace Tests\Unit;

use App\Services\LanguageDetector;
use App\Services\TanzaniaContext;
use App\Support\Phone;
use PHPUnit\Framework\TestCase;

class LanguageAndLocationTest extends TestCase
{
    public function test_language_detection(): void
    {
        $d = new LanguageDetector();
        $this->assertSame('sw', $d->detect('Naomba kujua haki zangu nikikamatwa'));
        $this->assertSame('en', $d->detect('What are my rights when arrested?'));
        $this->assertSame('sw', $d->detect('nimedhulumiwa shamba langu kijijini'));
        $this->assertNull($d->detect(''));
    }

    public function test_location_detection(): void
    {
        $tz = new TanzaniaContext();

        $loc = $tz->detectLocation('naomba msaada wa kisheria nipo Sinza Dar es Salaam');
        $this->assertSame('dar es salaam', $loc['region']);
        $this->assertSame('ubungo', $loc['district']);
        $this->assertSame('sinza', $loc['area']);

        $loc = $tz->detectLocation('Nipo Kahama Shinyanga');
        $this->assertSame('shinyanga', $loc['region']);
        $this->assertSame('kahama', $loc['district']);

        $loc = $tz->detectLocation('I live in Mwanza');
        $this->assertSame('mwanza', $loc['region']);

        $this->assertNull($tz->detectLocation('Hakuna mahali hapa'));
    }

    public function test_phone_normalisation(): void
    {
        $this->assertSame('+255712345678', Phone::normalize('0712 345 678'));
        $this->assertSame('+255712345678', Phone::normalize('255712345678'));
        $this->assertSame('+255712345678', Phone::normalize('+255712345678'));
        $this->assertSame('+255712345678', Phone::normalize('712345678'));
        $this->assertSame('+254700000000', Phone::normalize('+254700000000'));
        $this->assertNull(Phone::normalize('abc'));
        $this->assertTrue(Phone::isTanzanian('+255712345678'));
        $this->assertFalse(Phone::isTanzanian('+254700000000'));
    }

    public function test_locale_block_mentions_tanzania_and_currency(): void
    {
        $tz = new TanzaniaContext();
        $this->assertStringContainsString('Tanzania', $tz->localeBlock('en'));
        $this->assertStringContainsString('TZS', $tz->localeBlock('sw'));
        $this->assertStringContainsString('112', $tz->localeBlock('sw'));
    }
}
```

110 tests/Unit/PromptEngineTest.php

67 lines

```php
<?php

namespace Tests\Unit;

use App\Models\KnowledgeEntry;
use App\Models\LocalResource;
use App\Models\PromptTemplate;
use App\Models\ReferenceContact;
use App\Services\PromptEngine;
use Illuminate\Foundation\Testing\RefreshDatabase;
use Tests\TestCase;

class PromptEngineTest extends TestCase
{
    use RefreshDatabase;

    public function test_it_injects_matching_knowledge_and_country_context(): void
    {
        PromptTemplate::create(['name' => 'Legal SW', 'category' => 'legal', 'language' => 'sw', 'template' =>
'Wewe ni {app_name}, mwelimishaji wa sheria.', 'is_active' => true]);
        KnowledgeEntry::create([
            'title' => 'Haki zako ukikamatwa na polisi',
            'content' => 'Polisi wanapaswa kukufikisha mahakamani ndani ya saa 24.',
            'category' => 'legal', 'language' => 'sw', 'keywords' => ['kukamatwa', 'polisi', 'dhamana'],
'is_active' => true,
        ]);

        $built = app(PromptEngine::class)->build([
            'question' => 'Nimekamatwa na polisi, haki zangu ni zipi?',
            'language' => 'sw', 'category' => 'legal', 'channel' => 'sms',
        ]);

        $this->assertStringContainsString('saa 24', $built['system']);
        $this->assertStringContainsString('mwelimishaji wa sheria', $built['system']);
        $this->assertStringContainsString('Tanzania', $built['system']);
        $this->assertStringContainsString('TZS', $built['system']);
        $this->assertSame('user', $built['turns'][0]['role']);
        $this->assertCount(1, $built['knowledge']);
    }

    public function test_it_adds_nearby_services_when_location_is_mentioned(): void
    {
        LocalResource::create(['name' => 'KAHAMA PARALEGAL AID ORGANIZATION', 'category' => 'legal_aid', 'region'
=> 'shinyanga', 'district' => 'kahama', 'location' => 'Kahama mjini', 'phone' => '+255 767 994457', 'is_active' => true]);

        $built = app(PromptEngine::class)->build([
            'question' => 'naomba msaada wa kisheria nipo kahama shinyanga',
            'language' => 'sw', 'category' => 'legal', 'channel' => 'web',
            'location' => ['region' => 'shinyanga', 'district' => 'kahama', 'area' => null],
        ]);

        $this->assertStringContainsString('KAHAMA PARALEGAL AID ORGANIZATION', $built['system']);
        $this->assertStringContainsString('+255 767 994457', $built['system']);
    }

    public function test_emergency_puts_emergency_contacts_in_prompt_and_history_is_kept(): void
    {
        ReferenceContact::create(['name' => 'Ambulance', 'category' => 'health', 'phone' => '115', 'is_emergency'
=> true, 'is_active' => true]);

        $built = app(PromptEngine::class)->build([
            'question' => 'My father collapsed and is not breathing',
            'language' => 'en', 'category' => 'health', 'channel' => 'web', 'is_emergency' => true,
            'history' => [['role' => 'user', 'text' => 'hello'], ['role' => 'model', 'text' => 'hi']],
        ]);

        $this->assertStringContainsString('115', $built['system']);
        $this->assertStringContainsString('EMERGENCY', $built['system']);
        $this->assertCount(3, $built['turns']);
    }
}
```

111 tests/Unit/TopicClassifierTest.php

63 lines

```php
<?php

namespace Tests\Unit;

use App\Services\TopicClassifier;
use PHPUnit\Framework\TestCase;

class TopicClassifierTest extends TestCase
{
    private TopicClassifier $classifier;

    protected function setUp(): void
    {
        parent::setUp();
        $this->classifier = new TopicClassifier();
    }

    public function test_detects_legal_questions_in_swahili(): void
    {
        $r = $this->classifier->classify('Nimekamatwa na polisi bila sababu, naomba msaada wa kisheria');
        $this->assertSame('legal', $r['category']);
        $this->assertFalse($r['is_emergency']);
    }

    public function test_detects_health_questions_in_english(): void
    {
        $r = $this->classifier->classify('My child has fever and vomiting, is it malaria?');
        $this->assertSame('health', $r['category']);
    }

    public function test_detects_agriculture(): void
    {
        $r = $this->classifier->classify('Nipande mahindi lini na nitumie mbolea gani?');
        $this->assertSame('agriculture', $r['category']);
    }

    public function test_detects_government_services(): void
    {
        $r = $this->classifier->classify('How do I get a NIDA national id and a passport?');
        $this->assertSame('government', $r['category']);
    }

    public function test_falls_back_to_general(): void
    {
        $r = $this->classifier->classify('Habari za asubuhi');
        $this->assertSame('general', $r['category']);
    }

    public function test_flags_emergencies(): void
    {
        $r = $this->classifier->classify('Dharura! mtoto amezimia na hapumui');
        $this->assertTrue($r['is_emergency']);
        $this->assertSame('health', $r['category']);
    }

    public function test_labels_exist_for_every_category(): void
    {
        foreach (TopicClassifier::keys() as $key) {
            $this->assertNotEmpty(TopicClassifier::label($key, 'sw'));
            $this->assertNotEmpty(TopicClassifier::label($key, 'en'));
        }
    }
}
```

112 **vite.config.js** 18 lines

```
import { defineConfig } from 'vite';
import laravel from 'laravel-vite-plugin';
import tailwindcss from '@tailwindcss/vite';

export default defineConfig({
    plugins: [
        laravel({
            input: ['resources/css/app.css', 'resources/js/app.js'],
            refresh: true,
        }),
        tailwindcss(),
    ],
    server: {
        watch: {
            ignored: ['**/storage/framework/views/**'],
        },
    },
});
```