Battery Shipments Authorized for International Ocean Transport to/from US Packing Instruction P903

Customer Defined Shipment Specifications

• Lithium content is > 1 g/cell or > 2 g/battery

Packaging Requirements

- Cells and batteries protected to prevent short circuits, movement, and accidental activation
- Inner packagings completely enclose the cell or battery, and then be:
 - i. (Option 1) Placed in a packaging that meets packing group II standards and then further packed with the equipment in strong out packaging; OR
 - ii. (Option 2) Further packed with the equipment in an outer packaging that meets packing group II standards

Marking and Labeling Requirements



Option 1





Option 2

UN3091, LITHIUM METAL BATTERIES PACKED WITH EQUIPMENT	UNID, Proper Shipping Name	
u n	Appropriate UN Certification marking	
	Class 9 Lithium Battery Label	



Battery Shipments Authorized for International Ocean Transport to/from US Packing Instruction P903

Documentation Requirements

- 1. Include document (any form) with the following information:
 - Contains all of the information required by the IMDG code
 - Emergency response information required as per 49 CFR, Subpart G of Part 172
- 2. Additional emergency response information or documentation may be required as per carrier(s)

10 Vossol/Flight & Date 12 Port/Place of Discharge		11 Port/Place Handling 13 Destination	24 Hour Emergency Contact Name: XXXXX 24 Hour Emergency Contact Number: xxx-xxx-xxx		
145hipping Marks 1 box	UN3091, Lith	Packages Description of Goods nium Metal Batteries Equipment, 9, F-A, S-I	NW GW (kg)	CUBE (m/)	

