Battery Shipments Authorized for International Ocean Transport to/from US Packing Instruction P903

Customer Defined Shipment Specifications

Watt-hour rating is > 20 Wh/cell or 100 Wh/battery

Packaging Requirements

- Cells and batteries protected to prevent short circuits, movement, and accidental activation
- Inner packagings that completely enclose the cell or battery, and then be:
 - i. (Option 1) Placed in a packaging that meets packing group II standards and then further packed with the equipment in strong outer packaging; OR
 - ii. (Option 2) Further packed with the equipment in an outer packaging that meets packing group II standards

Marking and Labeling Requirements



Option 1





Option 2

| UN3481, LITHIUM ION BATTERIES PACKED WITH EQUIPMENT | UNID, Proper Shipping Name | | |
|---|--------------------------------------|--|--|
| un | Appropriate UN Certification marking | | |
| | Class 9 Lithium Battery Label | | |

Battery Shipments Authorized for International Ocean Transport to/from US Packing Instruction P903

Documentation Requirements

- 1. Include document (any form) with the following information:
 - Contains all of the information required by the IMDG code
 - Emergency response information required as per 49 CFR, Subpart G of Part 172
- 2. Additional emergency response information or documentation may be required as per carrier(s)

| 10 Vessel/Flight & Da | te | 11 Port/Place Handling | Additional Handling Information 4 Hour Emergency Co | ontact Name: XX | |
|-----------------------|-------------------|--------------------------------|---|-----------------|-------------|
| 12 Port/Place of Disc | harge | 13 Destination | 24 Hour Emergency Co | ontact Number: | XXX-XXX-XXX |
| 14 Shipping Marks | *Number & Kind of | Packages, Description of Goods | NW | GW (kg) | CUBE (m/) |
| 1 box UN3481, L | | ium Ion Batteries Packed | 8 kg | | |
| | with Equipm | ent, 9, F-A, S-I | | | |
| 5 | F | 7 IV | | | |

