Battery Shipments Authorized for Air Transport (US and Int'l) on Passenger Aircraft (PAX) Packing Instruction 969, Section I*

Customer Defined Shipment Specifications

- Lithium content is > 1 g/cell or > 2 g/battery
- Net quantity of lithium cells or batteries is ≤ 5 kg per package
- Package contains no more than the number of lithium cells or batteries necessary to power the intended piece of equipment plus 1 or 2 spare sets

Packaging Requirements

- Cells and batteries protected to prevent short circuits
- Inner packagings that completely enclose the cell or battery, and then:
 - i. Placed in a packaging that meets packing group II standards and then further packed with the equipment in strong outer packaging; OR
 - Further packed with the equipment in an outer packaging that meets packing group II standards
- Packed in intermediate or outer rigid metal packaging, surrounded by non-combustible, non-conductive cushioning material

Marking and Labeling Requirements



UN3091, LITHIUM METAL BATTERIES PACKED WITH EQUIPMENT	UNID, Proper Shipping Name
a n	Appropriate UN Certification marking
	Class 9 Lithium Battery label



Battery Shipments Authorized for Air Transport (US and Int'l) on Passenger Aircraft (PAX) Packing Instruction 969, Section I*

Documentation Requirements

1. Air Waybill with the details of the shipment.



- 2. Shipper's Declaration for Dangerous Goods with emergency response information and documentation required as per 49 CFR and U.S. State Variations.
- 3. State and/or Operator Variations may require additional documentation.



