Battery Shipments Authorized for Air Transport (US and Int'l) on Cargo Aircraft Only (CAO) Packing Instruction 966, Section I*

Customer Defined Shipment Specifications

- Watt-hour rating is ≤ 20 Wh/cell or ≤ 100 Wh/battery
- Net quantity of lithium cells or batteries is > 5 kg but ≤ 35 kg per package
- Package contains no more than the number of lithium cells or batteries necessary to power the intended piece of equipment plus 1 or 2 spare sets

Packaging Requirements

- Cells and batteries protected to prevent short circuits
- Inner packagings must completely enclose the cell or battery, and then be:
 - i. (Option 1) Placed in a packaging that meets packing group II standards and then further packed with the equipment in strong outer packaging; OR
 - ii. (Option 2) Further packed with the equipment in an outer packaging that meets packing group II standards
- Equipment must be secured against movement within the outer packaging
- Transport aboard PAX is not authorized

Marking and Labeling Requirements




Option 1



UN Packaging Inside



Option 2





*This sheet is only a summary of the requirements found in IATA Sec 3.9.2.6, SP A206, PI966 Sec I, Sec. 7.3.18.2, USG-12 and other State and Operator Variations as applicable; 49 CFR §171.22, §171.24, and Subpart G to Part 172

Page 1 of 2

Battery Shipments Authorized for Air Transport (US and Int'l) on Cargo Aircraft Only (CAO) Packing Instruction 966, Section I*

Documentation Requirements

1. Air Waybill with the details of the shipment.



- 2. Shipper's Declaration for Dangerous Goods with emergency response information and documentation required as per 49 CFR and U.S. State Variations.
- 3. State and/or Operator Variations may require additional documentation.

