```
****************************************************
*                                                  *
*           STAAD.Pro                              *
*           Version  2006    Bld 1002.US           *
*           Proprietary Program of                 *
*           Research Engineers,  Intl.             *
*           Date=    MAY  2, 2007                  *
*           Time=    15: 2:15                      *
*                                                  *
*      USER ID: Meinhardt Infrastructure Pte Ltd   *
****************************************************

     1. STAAD SPACE
INPUT FILE: Inflam-Mat_Store.STD
     2. START JOB INFORMATION
     3. ENGINEER DATE APRIL 2007
     4. END JOB INFORMATION
     5. INPUT WIDTH 79
     6. UNIT METER KN
     7. JOINT COORDINATES
     8. 102 -6.576 3.960 -7.500; 112 6.576 3.960 -7.500
     9. 502 -6.576 3.960  7.500; 512 6.576 3.960  7.500
    10. *
    11. 105 -5.1205 5.6355 -7.500; 106 -2.000 5.7665 -7.500
    12. 108   2.000 5.7665 -7.500; 109 5.1205 5.6355 -7.500
    13. 505 -5.1205 5.6355  7.500; 506 -2.000 5.7665  7.500
    14. 508   2.000 5.7665  7.500; 509 5.1205 5.6355  7.500
    16. 201  -6.230 0.000 -5.000; 202 -6.582  4.027 -5.000
    17. 203  -6.436 4.831 -5.000; 204 -5.900  5.448 -5.000
    18. 205  -5.124 5.705 -5.000; 206 -2.000  5.836 -5.000
    19. 207   0.000 5.861 -5.000; 208  2.000  5.836 -5.000
    20. 209   5.124 5.705 -5.000; 210  5.900  5.448 -5.000
    21. 211   6.436 4.831 -5.000; 212  6.582  4.027 -5.000
    22. 213   6.230 0.000 -5.000
    24. 301  -6.230 0.000 0.000; 302 -6.594  4.161 0.000
    25. 303  -6.447 4.967 0.000; 304 -5.909  5.586 0.000
    26. 305  -5.131 5.844 0.000; 306 -2.000  5.975 0.000
    27. 307   0.000 6.00  0.000; 308  2.000  5.975 0.000
    28. 309   5.131 5.844 0.000; 310  5.909  5.586 0.000
    29. 311   6.447 4.967 0.000; 312  6.594  4.161 0.000
    30. 313   6.230 0.000 0.000
    32. 401  -6.230 0.000 5.000; 402 -6.582  4.027 5.000
    33. 403  -6.436 4.831 5.000; 404 -5.900  5.448 5.000
    34. 405  -5.124 5.705 5.000; 406 -2.000  5.836 5.000
    35. 407   0.000 5.861 5.000; 408  2.000  5.836 5.000
    36. 409   5.124 5.705 5.000; 410  5.900  5.448 5.000
    37. 411   6.436 4.831 5.000; 412  6.582  4.027 5.000
    38. 413   6.230 0.000 5.000
    40. 2006  -2.000 0.000 -5.000; 2008 2.000 0.000 -5.000
    41. 3006  -2.000 0.000  0.000; 3008 2.000 0.000  0.000
    42. 4006  -2.000 0.000  5.000; 4008 2.000 0.000  5.000
    44. MEMBER INCIDENCES
    45. 26 2006 206; 28 2008 208
```



```
    46. 36 3006 306; 38 3008 308
    47. 46 4006 406; 48 4008 408
    48. 201 201 202 212; 301 301 302 312; 401 401 402 412
    49. *
    50. 1001 105 205; 1002 205 305; 1003 305 405; 1004 405 505
    51. 2001 106 206; 2002 206 306; 2003 306 406; 2004 406 506
    52. 3001 108 208; 3002 208 308; 3003 308 408; 3004 408 508
    53. 4001 109 209; 4002 209 309; 4003 309 409; 4004 409 509
    54. *
    55. 5001 102 202; 5002 202 302; 5003 302 402; 5004 402 502
    56. 6001 112 212; 6002 212 312; 6003 312 412; 6004 412 512
    57. *
    58. 7005 202 305; 7006 302 205; 7007 302 405; 7008 402 305
    59. *
    60. 8001 205 306; 8002 305 206; 8003 305 406; 8004 405 306
    61. 8005 206 308; 8006 208 306; 8007 306 408; 8008 308 406
    62. 8009 208 309; 8010 308 209; 8011 308 409; 8012 408 309
    63. *
    64. 9005 212 309; 9006 312 209; 9007 312 409; 9008 412 309
    66. DEFINE MATERIAL START
    67. ISOTROPIC STEEL
    68. E 2.05E+008
    69. POISSON 0.3
    70. DENSITY 76.8195
    71. ALPHA 1.2E-005
```



```
    72. DAMP 0.03
    73. END DEFINE MATERIAL
    74. MEMBER PROPERTY BRITISH
    75. 26 28 36 38 46 48 TAPERED 0.3 0.01 0.3 0.25 0.015 0.25 0.015
    76. 201 TO 212 301 TO 312 -
    77. 401 TO 412 TAPERED 0.3 0.01 0.3 0.25 0.015 0.25 0.015
    78. 1001 TO 1004 2001 2004 3001 3004 -
    79. 4001 TO 4004 TAPERED 0.3 0.006 0.3 0.15 0.008 0.15 0.008
    80. 2002 2003 3002 3003 TAPERED 0.3 0.006 0.3 0.2 0.010 0.2 0.010
    81. *
    82. 5001 TO 5004 TAPERED 0.3 0.01 0.3 0.25 0.015 0.25 0.015
    83. 6001 TO 6004 TAPERED 0.3 0.01 0.3 0.25 0.015 0.25 0.015
    84. *
    85. 7005 TO 7008 8001 TO 8012 9005 TO 9008 TABLE ST UA90X90X6
    86. *7001 TO 7008 9001 TO 9008 TABLE ST UA90X90X6
    87. CONSTANTS
    88. BETA 90 MEMB 26 28 36 38 46 48
    89. *
    90. BETA 90 MEMB 5001 TO 5004 6001 TO 6004
    91. MATERIAL STEEL ALL
    92. MEMBER TENSION
    93. *7001 TO 7008 8001 TO 8012 9001 TO 9008
    94. 7005 TO 7008 8001 TO 8012 9005 TO 9008
    95. SUPPORTS
    96. 201 213 301 313 401 413 2006 2008 3006 3008 4006 4008 PINNED
    98. LOAD 1 SELFWEIGHT
    99. SELFWEIGHT Y -1
   100. LOAD 2 SDL
   101. MEMBER LOAD
   102. 1001 TO 1004 4001 TO 4004 UNI GY -2.8
   103. 2001 TO 2004 3001 TO 3004 UNI GY -3.2
```



```
   104. 5001 TO 5004 6001 TO 6004 UNI GY -2.8
   105. LOAD 3 LL
   106. MEMBER LOAD
   107. 1001 TO 1004 4001 TO 4004 UNI GY -2.1
   108. 2001 TO 2004 3001 TO 3004 UNI GY -2.4
   109. JOINT LOAD
   110. 307 FY -5
   112. LOAD 11 WL1 (INTERNAL SUCTION, WIND ANGLE 0)
   113. MEMBER LOAD
   114. 1001 1002 4001 4002 UNI GY 2.8
   115. 1003 1004 4003 4004 UNI GY -1.4
   116. 2001 2002 3001 3002 UNI GY 3.2
   117. 2003 2004 3003 3004 UNI GY -1.6
   118. 201 TO 204 209 TO 212 UNI GZ 1.0
   119. 26 28 UNI GZ 5.4
   120. 401 TO 404 409 TO 412 UNI GZ 0.2
   121. 46 48 UNI GZ 1.0
   123. LOAD 12 WL2 (INTERNAL PRESSURE, WIND ANGLE 0)
   124. MEMBER LOAD
   125. 1001 1002 4001 4002 UNI GY 5.0
   126. 1003 1004 4003 4004 UNI GY 1.8
   127. 2001 2002 3001 3002 UNI GY 5.7
   128. 2003 2004 3003 3004 UNI GY 2.0
   129. 201 TO 204 209 TO 212 UNI GZ 0.6
   130. 26 28 UNI GZ 3.1
   131. 401 TO 404 409 TO 412 UNI GZ 0.6
   132. 46 48 UNI GZ 3.1
   134. LOAD 13 WL3 (INTERNAL SUCTION, WIND ANGLE 90)
   135. MEMBER LOAD
   136. 1001 1002 4001 4002 UNI GY -2.2
   137. 1003 1004 4003 4004 UNI GY -2.2
   138. 2001 2002 3001 3002 UNI GY -2.5
   139. 2003 2004 3003 3004 UNI GY -2.5
   140. 201 TO 204 401 TO 404 UNI GX -3.1
   141. 301 TO 304 UNI GX -6.2
   142. 209 TO 212 409 TO 412 UNI GX 3.1
   143. 309 TO 312 UNI GX 6.2
   145. LOAD 14 WL4 (INTERNAL PRESSURE, WIND ANGLE 90)
   146. MEMBER LOAD
   147. 1001 1002 4001 4002 UNI GY 3.9
   148. 1003 1004 4003 4004 UNI GY 3.9
   149. 2001 2002 3001 3002 UNI GY 4.5
   150. 2003 2004 3003 3004 UNI GY 4.5
   151. 201 TO 204 401 TO 404 UNI GX -0.9
   152. 301 TO 304 UNI GX -5.0
   153. 209 TO 212 409 TO 412 UNI GX 0.9
   154. 309 TO 312 UNI GX 5.0
   156. LOAD 21 EQ1 (EARTHQUAKE LOAD)
   157. JOINT LOAD
   158. 205 206 208 209 405 406 408 409 FX 15
   159. LOAD 22 EQ1 (EARTHQUAKE LOAD)
   160. JOINT LOAD
   161. 205 206 208 209 405 406 408 409 FZ 15
```

```
 163. LOAD COMB 1001 1.4DL + 1.6LL
 164. 1 1.4 2 1.4 3 1.6
 166. LOAD COMB 1011 1.2DL + 1.2LL + 1.2WL1
   STAAD SPACE                                              -- PAGE NO.    4

 167. 1 1.2 2 1.2 3 1.2 11 1.2
 168. LOAD COMB 1111 1.4DL + 1.4WL1
 169. 1 1.4 2 1.4 11 1.4
 170. LOAD COMB 1211 1.0DL + 1.4WL1
 171. 1 1.0 2 1.0 11 1.4
 172. LOAD COMB 1012 1.2DL + 1.2LL + 1.2WL2
 173. 1 1.2 2 1.2 3 1.2 12 1.2
 174. LOAD COMB 1112 1.4DL + 1.4WL2
 175. 1 1.4 2 1.4 12 1.4
 176. LOAD COMB 1212 1.0DL + 1.4WL2
 177. 1 1.0 2 1.0 12 1.4
 178. LOAD COMB 1013 1.2DL + 1.2LL + 1.2WL3
 179. 1 1.2 2 1.2 3 1.2 13 1.2
 180. LOAD COMB 1113 1.4DL + 1.4WL3
 181. 1 1.4 2 1.4 13 1.4
 182. LOAD COMB 1213 1.0DL + 1.4WL3
 183. 1 1.0 2 1.0 13 1.4
 184. LOAD COMB 1014 1.2DL + 1.2LL + 1.2WL4
 185. 1 1.2 2 1.2 3 1.2 14 1.2
 186. LOAD COMB 1114 1.4DL + 1.4WL4
 187. 1 1.4 2 1.4 14 1.4
 188. LOAD COMB 1214 1.0DL + 1.4WL4
 189. 1 1.0 2 1.0 14 1.4
 191. LOAD COMB 1021 1.2DL + 0.5LL + 1.0EQ1
 192. 1 1.2 2 1.2 3 0.5 21 1.0
 193. LOAD COMB 1022 1.2DL + 0.5LL + 1.0EQ2
 194. 1 1.2 2 1.2 3 0.5 22 1.0
 195. LOAD COMB 1121 1.2DL + 0.5LL - 1.0EQ1
 196. 1 1.2 2 1.2 3 0.5 21 -1.0
 197. LOAD COMB 1122 1.2DL + 0.5LL - 1.0EQ2
 198. 1 1.2 2 1.2 3 0.5 22 -1.0
 199. LOAD COMB 1221 0.9DL + 1.0EQ1
 200. 1 0.9 2 0.9 21 1.0
 201. LOAD COMB 1222 0.9DL + 1.0EQ2
 202. 1 0.9 2 0.9 22 1.0
 203. LOAD COMB 1321 0.9DL - 1.0EQ1
 204. 1 0.9 2 0.9 21 -1.0
 205. LOAD COMB 1322 0.9DL - 1.0EQ2
 206. 1 0.9 2 0.9 22 -1.0
 207. *SLS
 208. LOAD COMB 2001 1.0DL + 1.0LL
 209. 1 1.0 2 1.0 3 1.0
 210. LOAD COMB 2002 1.0DL + 0.5LL
 211. 1 1.0 2 1.0 3 0.5
 212. LOAD COMB 2011 DL + LL + WL1
 213. 1 1.0 2 1.0 3 1.0 11 1.0
 214. LOAD COMB 2012 DL + LL + WL2
 215. 1 1.0 2 1.0 3 1.0 12 1.0
 216. LOAD COMB 2013 DL + LL + WL3
 217. 1 1.0 2 1.0 3 1.0 13 1.0
 218. LOAD COMB 2014 DL + LL + WL4
 219. 1 1.0 2 1.0 3 1.0 14 1.0
 221. PERFORM ANALYSIS
   STAAD SPACE                                              -- PAGE NO.    5


          P R O B L E M   S T A T I S T I C S
          -----------------------------------

   NUMBER OF JOINTS/MEMBER+ELEMENTS/SUPPORTS =    57/    86/    12
   ORIGINAL/FINAL BAND-WIDTH=    46/    14/     84 DOF
   TOTAL PRIMARY LOAD CASES =     9, TOTAL DEGREES OF FREEDOM =     306
   SIZE OF STIFFNESS MATRIX =        26 DOUBLE  KILO-WORDS
   REQRD/AVAIL. DISK SPACE  =      12.5/ 416287.6 MB

 **START ITERATION NO.           2

 **NOTE-Tension/Compression converged after  2 iterations, Case=    1


 **START ITERATION NO.           2

 **NOTE-Tension/Compression converged after  2 iterations, Case=    2


 **START ITERATION NO.           2
```



```
 **START ITERATION NO.           3

 **NOTE-Tension/Compression converged after  3 iterations, Case=    3


 **START ITERATION NO.           2

 **NOTE-Tension/Compression converged after  2 iterations, Case=   11


 **START ITERATION NO.           2

 **NOTE-Tension/Compression converged after  2 iterations, Case=   12


 **START ITERATION NO.           2

 **NOTE-Tension/Compression converged after  2 iterations, Case=   13


 **START ITERATION NO.           2

 **NOTE-Tension/Compression converged after  2 iterations, Case=   14


 **START ITERATION NO.           2

 **NOTE-Tension/Compression converged after  2 iterations, Case=   21


 **START ITERATION NO.           2
   STAAD SPACE                                              -- PAGE NO.    6

 **NOTE-Tension/Compression converged after  2 iterations, Case=   22


  222. LOAD LIST 1001 1011 TO 1014 1021 1022 1111 TO 1114 1121 1122 -
  223. 1211 TO 1214 1221 1222 1321 1322
  224. PRINT SUPPORT REACTION ALL
 SUPPORT  REACTION ALL
   STAAD SPACE                                              -- PAGE NO.    7


  SUPPORT REACTIONS -UNIT KN   METE    STRUCTURE TYPE = SPACE
  -----------------
```

JOINT	LOAD	FORCE-X	FORCE-Y	FORCE-Z	MOM-X	MOM-Y	MOM Z
201	1001	-1.03	63.20	-0.50	0.00	0.00	0.00
	1011	-1.13	32.50	-6.88	0.00	0.00	0.00
	1111	-1.72	26.70	-8.05	0.00	0.00	0.00
	1211	-1.29	12.30	-7.90	0.00	0.00	0.00
	1012	-1.47	22.67	-5.98	0.00	0.00	0.00
	1112	-2.12	15.23	-6.99	0.00	0.00	0.00
	1212	-1.70	0.84	-6.85	0.00	0.00	0.00
	1013	8.32	60.09	-0.43	0.00	0.00	0.00
	1113	9.30	58.89	-0.52	0.00	0.00	0.00
	1213	9.73	44.50	-0.37	0.00	0.00	0.00
	1014	1.10	35.21	-0.47	0.00	0.00	0.00
	1114	0.89	29.86	-0.57	0.00	0.00	0.00
	1214	1.31	15.47	-0.42	0.00	0.00	0.00
	1021	-16.35	20.45	-0.44	0.00	0.00	0.00
	1022	-0.62	33.23	-8.54	0.00	0.00	0.00
	1121	14.08	73.92	-0.44	0.00	0.00	0.00
	1122	-1.64	61.13	7.65	0.00	0.00	0.00
	1221	-16.17	5.65	-0.34	0.00	0.00	0.00
	1222	-0.44	18.43	-8.43	0.00	0.00	0.00
	1321	14.26	59.12	-0.34	0.00	0.00	0.00
	1322	-1.47	46.33	7.76	0.00	0.00	0.00
213	1001	1.03	63.20	-0.50	0.00	0.00	0.00
	1011	1.13	32.50	-6.88	0.00	0.00	0.00
	1111	1.72	26.70	-8.05	0.00	0.00	0.00
	1211	1.29	12.30	-7.90	0.00	0.00	0.00
	1012	1.47	22.67	-5.98	0.00	0.00	0.00
	1112	2.12	15.23	-6.99	0.00	0.00	0.00