```
****************************************************
*                                                  *
*           STAAD.Pro                              *
*           Version  2007    Build 04              *
*           Proprietary Program of                 *
*           Research Engineers,  Intl.             *
*           Date=    JAN 18, 2013                  *
*           Time=    16:12:40                      *
*                                                  *
*      USER ID:                                    *
****************************************************
```

```
     1. STAAD SPACE
INPUT FILE: 20121120 T-Goal Post 037 FR.STD
     2. START JOB INFORMATION
     3. ENGINEER DATE 12-MAY-12
     4. END JOB INFORMATION
     5. INPUT WIDTH 79
     6. UNIT METER KN
     7. JOINT COORDINATES
     8. 2 5 1 -5.73; 3 5 4.495 -5.38; 4 5 4.495 -5.73; 6 5 4.495 -6.08
     9. MEMBER INCIDENCES
    10. 1 4 3; 3 2 4; 5 6 4
    11. DEFINE MATERIAL START
    12. ISOTROPIC STEEL
    13. E 2.05E+008
    14. POISSON 0.3
    15. DENSITY 76.8195
    16. ALPHA 1.2E-005
    17. DAMP 0.03
    18. END DEFINE MATERIAL
    19. MEMBER PROPERTY JAPANESE
    20. 1 5 TABLE ST H394X398X11
    21. 3 TABLE ST H394X398X11
    22. CONSTANTS
    23. BETA 90 MEMB 3
    24. MATERIAL STEEL ALL
    25. SUPPORTS
    26. 2 FIXED
    27. **************************** DEAD LOAD *****************************
    28. LOAD 1 LOADTYPE NONE  TITLE DL
    29. SELFWEIGHT Y -1
    30. JOINT LOAD
    31. 4 FY -19.6
    32. **************************** FRICTIONAL LOAD *****************************
    33. LOAD 2 LOADTYPE NONE  TITLE FL
    34. JOINT LOAD
    35. 4 FX -5.88
    36. **************************** WIND LOAD X-DIRECTION*****************************
    37. LOAD 3 LOADTYPE NONE  TITLE WLX
    38. MEMBER LOAD
    39. 1 5 UNI GX -0.34
    40. 3 UNI GX -0.34
    41. **************************** WIND LOAD Z-DIRECTION*****************************
    42. LOAD 4 LOADTYPE NONE  TITLE WLZ
    43. MEMBER LOAD
    44. 3 UNI GZ -0.34
    45. **************************** NOTIONAL LOAD X-DIRECTION*************************
    46. LOAD 5 LOADTYPE NONE  TITLE NLX
    47. SELFWEIGHT X -0.015
    48. JOINT LOAD
    49. 4 FX -0.294
    50. ****************************NOTIONAL LOAD Z-DIRECTION**************************
    51. LOAD 6 LOADTYPE NONE  TITLE NLZ
    52. SELFWEIGHT Z -0.015
    53. JOINT LOAD
```



```
    54. 4 FZ -0.294
    55. ************* LOAD COMBINATION - SERVICE *********
    56. LOAD COMB 7 1.0DL+1.0FL
    57. 1 1.0 2 1.0
    58. LOAD COMB 8 1.0DL+1.0FL+1.0WLX
    59. 1 1.0 2 1.0 3 1.0
    60. LOAD COMB 9 1.0DL+1.0FL+1.0WLX
    61. 1 1.0 2 1.0 4 1.0
    62. LOAD COMB 10 1.0DL+1.0FL+1.0NLX
    63. 1 1.0 2 1.0 5 1.0
    64. LOAD COMB 11 1.0DL+1.0FL+1.0NLZ
    65. 1 1.0 2 1.0 6 1.0
    66. ************ LOAD COMBINATION - ULTIMATE ********
    67. LOAD COMB 12 1.0DL+1.4FL
    68. 1 1.0 2 1.4
    69. LOAD COMB 13 1.4DL+1.4FL
    70. 1 1.4 2 1.4
    71. LOAD COMB 14 1.0DL+1.4FL+1.4WLX
    72. 1 1.0 2 1.4 3 1.4
    73. LOAD COMB 15 1.0DL+1.4FL+1.4WLZ
    74. 1 1.0 2 1.4 4 1.4
    75. LOAD COMB 16 1.0DL+1.4FL+1.4NLX
    76. 1 1.0 2 1.4 5 1.4
    77. LOAD COMB 17 1.0DL+1.4FL+1.4NLZ
    78. 1 1.0 2 1.4 6 1.4
    79. PERFORM ANALYSIS
```

P R O B L E M   S T A T I S T I C S

NUMBER OF JOINTS/MEMBER+ELEMENTS/SUPPORTS = 4/ 3/ 1

SOLVER USED IS THE IN-CORE ADVANCED SOLVER

TOTAL PRIMARY LOAD CASES = 6, TOTAL DEGREES OF FREEDOM = 18

```
    80. LOAD LIST 7 TO 11
    81. PRINT JOINT DISPLACEMENTS ALL
```

JOINT DISPLACEMENT (CM RADIANS)   STRUCTURE TYPE = SPACE

JOINT	LOAD	X-TRANS	Y-TRANS	Z-TRANS	X-ROTAN	Y-ROTAN	Z-ROTAN
2	7	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	8	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	9	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	10	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
	11	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
3	7	-0.2187	-0.0021	0.0000	0.0000	0.0000	0.0009
	8	-0.2442	-0.0021	0.0000	0.0000	0.0000	0.0010
	9	-0.2187	-0.0014	-0.0061	0.0000	0.0000	0.0009
	10	-0.2312	-0.0021	0.0000	0.0000	0.0000	0.0010
	11	-0.2187	-0.0015	-0.0045	0.0000	0.0000	0.0009
4	7	-0.2187	-0.0021	0.0000	0.0000	0.0000	0.0009
	8	-0.2442	-0.0021	0.0000	0.0000	0.0000	0.0010
	9	-0.2187	-0.0021	-0.0061	0.0000	0.0000	0.0009
	10	-0.2312	-0.0021	0.0000	0.0000	0.0000	0.0010
	11	-0.2187	-0.0021	-0.0045	0.0000	0.0000	0.0009
6	7	-0.2187	-0.0021	0.0000	0.0000	0.0000	0.0009
	8	-0.2442	-0.0021	0.0000	0.0000	0.0000	0.0010
	9	-0.2187	-0.0029	-0.0061	0.0000	0.0000	0.0009

11	-0.2187	-0.0028	-0.0045	0.0000	0.0000	0.0009

************** END OF LATEST ANALYSIS RESULT **************

82. PRINT SUPPORT REACTION ALL

SUPPORT REACTIONS -UNIT KN METE STRUCTURE TYPE = SPACE

JOINT	LOAD	FORCE-X	FORCE-Y	FORCE-Z	MOM-X	MOM-Y	MOM Z
2	7	5.88	25.62	0.00	0.00	0.00	-20.55
	8	7.31	25.62	0.00	0.00	0.00	-23.46
	9	5.88	25.62	1.19	2.08	0.00	-20.55
	10	6.26	25.62	0.00	0.00	0.00	-21.76
	11	5.88	25.62	0.38	1.21	0.00	-20.55

************** END OF LATEST ANALYSIS RESULT **************

83. LOAD LIST 12 TO 17
84. PRINT MEMBER FORCES ALL

MEMBER END FORCES STRUCTURE TYPE = SPACE

ALL UNITS ARE -- KN METE (LOCAL)

MEMBER	LOAD	JT	AXIAL	SHEAR-Y	SHEAR-Z	TORSION	MOM-Y	MOM-Z
1	12	4	0.00	0.50	0.00	0.00	0.00	0.09
		3	0.00	0.00	0.00	0.00	0.00	0.00
	13	4	0.00	0.70	0.00	0.00	0.00	0.12
		3	0.00	0.00	0.00	0.00	0.00	0.00
	14	4	0.00	0.50	-0.17	0.00	0.03	0.09
		3	0.00	0.00	0.00	0.00	0.00	0.00
	15	4	0.00	0.50	0.00	0.00	0.00	0.09
		3	0.00	0.00	0.00	0.00	0.00	0.00
	16	4	0.00	0.50	-0.01	0.00	0.00	0.09
		3	0.00	0.00	0.00	0.00	0.00	0.00
	17	4	0.01	0.50	0.00	0.00	0.00	0.09
		3	0.00	0.00	0.00	0.00	0.00	0.00
3	12	2	25.62	0.00	8.23	0.00	-28.77	0.00
		4	-20.60	0.00	-8.23	0.00	0.00	0.00
	13	2	35.87	0.00	8.23	0.00	-28.77	0.00
		4	-28.85	0.00	-8.23	0.00	0.00	0.00
	14	2	25.62	0.00	10.23	0.00	-32.84	0.00
		4	-20.60	0.00	-8.57	0.00	0.00	0.00
	15	2	25.62	1.66	8.23	0.00	-28.77	2.91
		4	-20.60	0.00	-8.23	0.00	0.00	0.00
	16	2	25.62	0.00	8.77	0.00	-30.47	0.00
		4	-20.60	0.00	-8.66	0.00	0.00	0.00
	17	2	25.62	0.54	8.23	0.00	-28.77	1.70
		4	-20.60	-0.43	-8.23	0.00	0.00	0.00
5	12	6	0.00	0.00	0.00	0.00	0.00	0.00
		4	0.00	0.50	0.00	0.00	0.00	-0.09
	13	6	0.00	0.00	0.00	0.00	0.00	0.00
		4	0.00	0.70	0.00	0.00	0.00	-0.12

		4	0.00	0.50	-0.17	0.00	-0.03	-0.09
	15	6	0.00	0.00	0.00	0.00	0.00	0.00
		4	0.00	0.50	0.00	0.00	0.00	-0.09
	16	6	0.00	0.00	0.00	0.00	0.00	0.00
		4	0.00	0.50	-0.01	0.00	0.00	-0.09
	17	6	0.00	0.00	0.00	0.00	0.00	0.00
		4	0.01	0.50	0.00	0.00	0.00	-0.09

************** END OF LATEST ANALYSIS RESULT **************

85. LOAD LIST ALL
86. PARAMETER 1
87. CODE BS5950
88. BEAM 2 ALL
89. CHECK CODE ALL

STAAD.Pro CODE CHECKING - (BSI)
****

PROGRAM CODE REVISION V2.12_5950-1_2000

ALL UNITS ARE - KN METE (UNLESS OTHERWISE NOTED)

MEMBER	TABLE	RESULT/ FX	CRITICAL COND/ MY	RATIO/ MZ	LOADING/ LOCATION
1 ST	H394X398X11	PASS	BS-4.2.3-(Y)	0.001	13
		0.00	0.00	0.12	0.00
3 ST	H394X398X11	PASS	BS-4.8.3.3.2	0.100	14
		25.62 C	32.84	0.00	-
5 ST	H394X398X11	PASS	BS-4.2.3-(Y)	0.001	13
		0.00	0.00	-0.12	0.35

************** END OF TABULATED RESULT OF DESIGN **************

90. FINISH

*********** END OF THE STAAD.Pro RUN ***********

**** DATE= JAN 18,2013 TIME= 16:12:41 ****

```
************************************************************
*        For questions on STAAD.Pro, please contact        *
*   Research Engineers Offices at the following locations  *
*                                                          *
*               Telephone                 Email            *
*  USA:      +1 (714)974-2500       support@bentley.com    *
*  CANADA    +1 (905)632-4771       detech@odandetech.com  *
*  UK        +44(1454)207-000       support@bentley.com    *
*  NORWAY    +47 67 57 21 30        staad@edr.no           *
*  SINGAPORE +65 6225-6158          support@bentley.com    *
*  INDIA     +91(033)4006-2021      support@bentley.com    *
*  JAPAN     +81(03)5952-6500       eng-eye@crc.co.jp      *
*  CHINA     +86(411)8479-1166      support@bentley.com    *
*  THAILAND  +66(0)2645-1018/19     support@bentley.com    *
*                                                          *
*  North America                   support@bentley.com     *
*  Europe                          support@bentley.com     *
*  Asia                            support@bentley.com     *
************************************************************
```