

BLDG-26

97. 107 WEIGHT 1136
 98. 108 WEIGHT 599
 99. 109 WEIGHT 739
 100. 110 WEIGHT 887
 101. 111 WEIGHT 895
 102. 112 WEIGHT 553
 103. 113 WEIGHT 446
 104. 114 WEIGHT 607
 105. 115 WEIGHT 625
 106. 116 WEIGHT 395
 107. 118 WEIGHT 129
 108. 119 WEIGHT 202
 109. 120 WEIGHT 203
 110. 121 WEIGHT 129
 111. 122 WEIGHT 233
 112. 123 WEIGHT 365
 113. 124 WEIGHT 368
 114. 125 WEIGHT 233
 115. 126 WEIGHT 232
 116. 127 WEIGHT 359
 117. 128 WEIGHT 368
 118. 129 WEIGHT 235
 119. 130 WEIGHT 125
 120. 131 WEIGHT 194
 121. 132 WEIGHT 194
 122. 133 WEIGHT 124
 123. *****
 124. LOAD 21 EQZ (EARTHQUAKE LOAD)
 125. UBC LOAD X
 126. *****
 127. LOAD 22 EQZ (EARTHQUAKE LOAD)
 128. UBC LOAD Z
 129. *****
 130. LOAD 1 SELFWEIGHT
 131. SELFWEIGHT Y -1
 132. *****SELFWEIGHT TRANSFER BY STEEL STRUCTURE TO RCC STRUCTURE *****
 133. JOINT LOAD
 134. 113 FX -0.154 FY -5.027 FZ -0.402
 135. 101 FX -0.088 FY -5.149 FZ 0.414
 136. 114 FX -0.006 FY -6.382 FZ -0.509
 137. 102 FX -0.04 FY -6.315 FZ 0.501
 138. 115 FX 0.006 FY -6.382 FZ -0.509
 139. 103 FX -0.029 FY -6.395 FZ 0.511
 140. 116 FX 0.154 FY -5.028 FZ -0.402
 141. 104 FX 0.122 FY -5.078 FZ 0.409
 142. 126 FX 0.159 FY -9.379 FZ 1.464
 143. 122 FX 0.2 FY -8.982 FZ -1.545
 144. 127 FX -0.001 FY -8.777 FZ 1.223
 145. 123 FX -0.001 FY -8.381 FZ -1.296
 146. 128 FX 0.001 FY -8.778 FZ 1.223

BLDG-26

147. 124 FX 0.001 FY -8.378 FZ -1.295
 148. 129 FX -0.163 FY -9.378 FZ 1.468
 149. 125 FX -0.163 FY -8.985 FZ -1.539
 150. 130 FX 0 FY -7.905 FZ 0
 151. 118 FX 0 FY -7.881 FZ 0
 152. 131 FX 0 FY -8.963 FZ 0
 153. 119 FX 0 FY -8.988 FZ 0
 154. 132 FX 0 FY -8.963 FZ 0
 155. 120 FX 0 FY -9.031 FZ 0
 156. 133 FX 0 FY -7.904 FZ 0
 157. 121 FX 0 FY -7.886 FZ 0
 158. 130 FX 0 FY -0.068 FZ -0.786
 159. 118 FX 0 FY -0.068 FZ 0.711
 160. 131 FX 0 FY -0.068 FZ -0.828
 161. 119 FX 0 FY -0.068 FZ 0.774
 162. 132 FX 0 FY -0.068 FZ -0.829
 163. 120 FX 0 FY -0.068 FZ 0.751
 164. 133 FX 0 FY -0.068 FZ -0.789
 165. 121 FX 0 FY -0.068 FZ 0.712
 166. LOAD 2 DL
 167. MEMBER LOAD
 168. *****
 169. *****WALL (T=250 MM,DENSITY=23 KN/M^3,H=6.1 M)=0.25X23X6.1=35.0 KN/M
 170. ***PROJECTION OF SLAB (0.62X0.225)=0.62X0.225X25=3.5 KN/M
 171. **PROJECTION OF SLAB (0.27X0.225)=0.27X0.225X25=1.52 KN/M
 172. **FLOOR DL (225 THICK+FIN+M & E)= 7.1 KN/M^2
 173. **ROOF DL (175 THICK+FIN+M & E)= 5.9 KN/M^2
 174. *****
 175. 1 TO 8 10 TO 14 16 TO 20 22 TO 30 33 37 39 45 46 48 TO 50 55 UNI GY -35
 176. 27 TO 30 46 TO 50 UNI GY -1.52
 177. 1 TO 5 22 TO 26 55 UNI GY -3.5
 178. 44 47 UNI GY -35 0 3.5
 179. FLOOR LOAD
 180. YRANGE 1.5 2 FLOAD -7.1 XRANGE 0 20 ZRANGE 0 20
 181. YRANGE 1.5 2 FLOAD 7.1 XRANGE 0 2 ZRANGE 0 3.3
 182. YRANGE 8 9 FLOAD -5.9 XRANGE 0 20 ZRANGE 0 20
 183. *****
 184. JOINT LOAD
 185. *****DEAD LOAD TRANSFER BY STEEL STRUCTURE TO RCC STRUCTURE *****
 186. 113 FX -0.767 FY -13.107 FZ -1.158
 187. 101 FX -0.415 FY -13.414 FZ 1.177
 188. 114 FX -0.011 FY -18.976 FZ -1.593
 189. 102 FX -0.168 FY -18.395 FZ 1.522
 190. 115 FX 0.011 FY -18.845 FZ -1.579
 191. 103 FX -0.142 FY -18.69 FZ 1.555
 192. 116 FX 0.768 FY -13.069 FZ -1.154
 193. 104 FX 0.623 FY -13.094 FZ 1.158
 194. 126 FX -1.893 FY -33.511 FZ 5.291
 195. 122 FX -1.823 FY -31.788 FZ -5.04
 196. 127 FX -0.004 FY -25.163 FZ -3.342
 197. 123 FX -0.003 FY -23.798 FZ 3.279
 198. 128 FX 0.005 FY -29.124 FZ 2.099
 199. 124 FX 0.005 FY -27.42 FZ -1.965

BLDG-26

200. 129 FX 1.873 FY -34.829 FZ 7.118
 201. 125 FX 1.942 FY -33.009 FZ -6.763
 202. 130 FX 0 FY -24.136 FZ 0
 203. 118 FX 0 FY -24.847 FZ 0
 204. 131 FX 0 FY -30.634 FZ 0
 205. 119 FX 0 FY -31.576 FZ 0
 206. 132 FX 0 FY -30.253 FZ 0
 207. 120 FX 0 FY -31.275 FZ 0
 208. 133 FX 0 FY -24.005 FZ 0
 209. 121 FX 0 FY -24.765 FZ 0
 210. 130 FX 0 FY 0 FZ -2.101
 211. 118 FX 0 FY 0 FZ 2.355
 212. 131 FX 0 FY 0 FZ -4.569
 213. 119 FX 0 FY 0 FZ 4.491
 214. 132 FX 0 FY 0 FZ -3.134
 215. 120 FX 0 FY 0 FZ 3.252
 216. 133 FX 0 FY 0 FZ -1.633
 217. 121 FX 0 FY 0 FZ 1.942
 218. *****
 219. LOAD 3 LL
 220. MEMBER LOAD
 221. **PROJECTION OF SLAB =0.62X10=6.2 KN/M
 222. **PROJECTION OF SLAB =0.27X10=2.7 KN/M
 223. **FLOOR LI1 = 15 KN/M^2
 224. **FLOOR LI2 = 10 KN/M^2
 225. **ROOF LI3 = 0.6 KN/M^2
 226. 27 TO 30 46 TO 50 UNI GY -2.7
 227. 1 TO 5 22 TO 26 55 UNI GY -6.2
 228. FLOOR LOAD
 229. YRANGE 1.5 2 FLOAD -10 XRANGE 0 20 ZRANGE 0 20
 230. YRANGE 1.5 2 FLOAD 10 XRANGE 0 2 ZRANGE 0 3.3
 231. YRANGE 1.5 2 FLOAD -5 XRANGE 1.5 11 ZRANGE 0 6
 232. YRANGE 1.5 2 FLOAD -5 XRANGE 0 15.2 ZRANGE 5.25 12
 233. YRANGE 8 9 FLOAD -0.6 XRANGE 0 20 ZRANGE 0 20
 234. JOINT LOAD
 235. ****LIVE LOAD TRANSFER BY STEEL STRUCTURE TO RCC STRUCTURE *****
 236. 113 FX -0.029 FY 1.422 FZ 0.196
 237. 101 FX -0.006 FY 1.623 FZ -0.206
 238. 114 FX 0.008 FY 1.47 FZ 0.206
 239. 102 FX 0.007 FY 1.586 FZ -0.22
 240. 115 FX -0.008 FY 1.564 FZ 0.216
 241. 103 FX -0.004 FY 1.651 FZ -0.228
 242. 116 FX 0.03 FY 1.455 FZ 0.2
 243. 104 FX 0.028 FY 1.497 FZ -0.206
 244. 126 FX -1.415 FY -25.094 FZ 3.298
 245. 122 FX -1.43 FY -23.837 FZ -3.079
 246. 127 FX 0 FY -18.917 FZ -3.336
 247. 123 FX -0.001 FY -17.912 FZ 3.288
 248. 128 FX 0.001 FY -21.85 FZ 0.701
 249. 124 FX 0 FY -20.605 FZ -0.583
 250. 129 FX 1.418 FY -26.072 FZ 4.641
 251. 125 FX 1.402 FY -24.73 FZ -4.379
 252. 130 FX 0 FY -12.817 FZ 0

BLDG-26

253. 118 FX 0 FY -13.507 FZ 0
 254. 131 FX 0 FY -15.389 FZ 0
 255. 119 FX 0 FY -16.127 FZ 0
 256. 132 FX 0 FY -15.104 FZ 0
 257. 120 FX 0 FY -15.768 FZ 0
 258. 133 FX 0 FY -12.724 FZ 0
 259. 121 FX 0 FY -13.295 FZ 0
 260. 130 FX 0 FY 0 FZ -3.021
 261. 118 FX 0 FY 0 FZ 3.235
 262. 131 FX 0 FY 0 FZ -5.267
 263. 119 FX 0 FY 0 FZ 5.192
 264. 132 FX 0 FY 0 FZ -4.211
 265. 120 FX 0 FY 0 FZ 4.31
 266. 133 FX 0 FY 0 FZ -2.663
 267. 121 FX 0 FY 0 FZ 2.933
 268. LOAD 4 PH(X-DIR)
 269. *****
 270. **PH =1.5% (1.4DL+1.6LL)
 271. JOINT LOAD
 272. 101 FX 9
 273. 102 FX 16
 274. 103 FX 18
 275. 104 FX 10
 276. 105 FX 18
 277. 106 FX 26
 278. 107 FX 31
 279. 108 FX 16
 280. 109 FX 19
 281. 110 FX 25
 282. 111 FX 25
 283. 112 FX 14
 284. 113 FX 11
 285. 114 FX 15
 286. 115 FX 16
 287. 116 FX 10
 288. 118 FX 3
 289. 119 FX 5
 290. 120 FX 5
 291. 121 FX 3
 292. 122 FX 5
 293. 123 FX 8
 294. 124 FX 8
 295. 125 FX 5
 296. 126 FX 5
 297. 127 FX 8
 298. 128 FX 8
 299. 129 FX 5
 300. 130 FX 3
 301. 131 FX 4
 302. 132 FX 4
 303. 133 FX 3
 304. LOAD 5 PH(Z-DIR)
 305. *****
 306. **PH =1.5% (1.4DL+1.6LL)
 307. JOINT LOAD
 308. 101 FZ 9

BLDG-26

309. 102 FZ 16
310. 103 FZ 18
311. 104 FZ 10
312. 105 FZ 18
313. 106 FZ 26
314. 107 FZ 31
315. 108 FZ 16
316. 109 FZ 19
317. 110 FZ 25
318. 111 FZ 25
319. 112 FZ 14
320. 113 FZ 11
321. 114 FZ 15
322. 115 FZ 16
323. 116 FZ 10
324. 118 FZ 3
325. 119 FZ 5
326. 120 FZ 5
327. 121 FZ 3
328. 122 FZ 5
329. 123 FZ 8
330. 124 FZ 8
331. 125 FZ 5
332. 126 FZ 5
333. 127 FZ 8
334. 128 FZ 8
335. 129 FZ 5
336. 130 FZ 3
337. 131 FZ 4
338. 132 FZ 4
339. 133 FZ 3
340. *****WIND LOAD TRANSFER BY STEEL STRUCTURE TO RCC STRUCTURE *****
341. LOAD 11 WL1 (0 DEG , INTERNAL SUCTION -0.3)
342. JOINT LOAD
343. 113 FX -0.013 FY 9.734 FZ 3.238
344. 101 FX -0.069 FY -59.253 FZ 16.499
345. 114 FX 0.009 FY 12.566 FZ 4.207
346. 102 FX -0.042 FY -61.947 FZ 21.772
347. 115 FX -0.009 FY 12.563 FZ 4.206
348. 103 FX -0.025 FY -62.121 FZ 21.792
349. 116 FX 0.013 FY 9.764 FZ 3.242
350. 104 FX 0.03 FY -48.056 FZ 16.743
351. 126 FX -1.467 FY -18.773 FZ -5.269
352. 122 FX 1.499 FY 17.639 FZ -5.131
353. 127 FX -0.001 FY -16.637 FZ -6.283
354. 123 FX 0.004 FY 15.65 FZ -5.823
355. 128 FX 0.001 FY -16.696 FZ -6.19
356. 124 FX -0.002 FY 15.605 FZ -5.88
357. 129 FX 1.467 FY -18.784 FZ -5.322
358. 125 FX -1.396 FY 17.539 FZ -5.141
359. 130 FX 0 FY -21.959 FZ 0
360. 118 FX 0 FY 70.832 FZ 0
361. 131 FX 0 FY -26.802 FZ 0
362. 119 FX 0 FY 76.204 FZ 0
363. 132 FX 0 FY -26.793 FZ 0
364. 120 FX 0 FY 76.069 FZ 0

BLDG-26

365. 133 FX 0 FY -21.981 FZ 0
366. 121 FX 0 FY 59.878 FZ 0
367. 130 FX 0 FY 0 FZ -10.23
368. 118 FX 0 FY 0 FZ -28.616
369. 131 FX 0 FY 0 FZ -12.193
370. 119 FX 0 FY 0 FZ -36.24
371. 132 FX 0 FY 0 FZ -12.185
372. 120 FX 0 FY 0 FZ -36.407
373. 133 FX 0 FY 0 FZ -10.159
374. 121 FX 0 FY 0 FZ -28.495
375. *****WIND LOAD TRANSFER BY STEEL STRUCTURE TO RCC STRUCTURE *****
376. LOAD 12 WL2 (0 DEG , INTERNAL PRESSURE +0.2)
377. JOINT LOAD
378. 113 FX 0.078 FY 29.442 FZ 10.688
379. 101 FX -0.037 FY -33.735 FZ 9.067
380. 114 FX -0.003 FY 38.854 FZ 14.015
381. 102 FX -0.034 FY -34.865 FZ 11.868
382. 115 FX 0.003 FY 38.696 FZ 13.999
383. 103 FX -0.011 FY -35.049 FZ 11.89
384. 116 FX -0.078 FY 29.399 FZ 10.684
385. 104 FX -0.026 FY -27.587 FZ 9.198
386. 126 FX 1.16 FY 24.46 FZ -8.189
387. 122 FX 2.951 FY 44.451 FZ 1.92
388. 127 FX 0 FY 16.787 FZ 0.591
389. 123 FX 0.005 FY 34.742 FZ -7.583
390. 128 FX -0.001 FY 20.939 FZ -5.067
391. 124 FX -0.004 FY 38.558 FZ -2.095
392. 129 FX -1.14 FY 25.852 FZ -10.112
393. 125 FX -2.863 FY 45.677 FZ 3.742
394. 130 FX 0 FY -20.623 FZ 0
395. 118 FX 0 FY 57.188 FZ 0
396. 131 FX 0 FY -27.716 FZ 0
397. 119 FX 0 FY 63.741 FZ 0
398. 132 FX 0 FY -28.099 FZ 0
399. 120 FX 0 FY 63.15 FZ 0
400. 133 FX 0 FY -20.758 FZ 0
401. 121 FX 0 FY 51.057 FZ 0
402. 130 FX 0 FY 0 FZ -14.168
403. 118 FX 0 FY 0 FZ -20.523
404. 131 FX 0 FY 0 FZ -15.506
405. 119 FX 0 FY 0 FZ -27.999
406. 132 FX 0 FY 0 FZ -17.06
407. 120 FX 0 FY 0 FZ -26.871
408. 133 FX 0 FY 0 FZ -14.67
409. 121 FX 0 FY 0 FZ -19.988
410. *****WIND LOAD TRANSFER BY STEEL STRUCTURE TO RCC STRUCTURE *****
411. LOAD 13 WL3 (90 DEG , INTERNAL SUCTION -0.3, WW&LW +0.2)
412. JOINT LOAD
413. 113 FX 0.011 FY 23.471 FZ 7.955
414. 101 FX 0.022 FY 28.783 FZ -7.846
415. 114 FX 0.01 FY 30.07 FZ 10.321
416. 102 FX 0.021 FY 30.088 FZ -10.323
417. 115 FX -0.01 FY 30.165 FZ 10.331
418. 103 FX 0.006 FY 30.231 FZ -10.339
419. 116 FX -0.011 FY 23.492 FZ 7.957
420. 104 FX -0.001 FY 23.514 FZ -7.961

BLDG-26

421. 126 FX -1.459 FY -25.855 FZ 3.322
 422. 122 FX -1.487 FY -24.628 FZ -3.143
 423. 127 FX -0.001 FY -19.532 FZ -3.477
 424. 123 FX -0.002 FY -18.528 FZ 3.402
 425. 128 FX 0.001 FY -22.538 FZ 0.662
 426. 124 FX 0 FY -21.291 FZ -0.563
 427. 129 FX 1.466 FY -26.861 FZ 4.735
 428. 125 FX 1.434 FY -25.509 FZ -4.483
 429. 130 FX 0 FY -34.632 FZ 0
 430. 118 FX 0 FY -40.347 FZ 0
 431. 131 FX 0 FY -43.839 FZ 0
 432. 119 FX 0 FY -44.553 FZ 0
 433. 132 FX 0 FY -43.546 FZ 0
 434. 120 FX 0 FY -44.147 FZ 0
 435. 133 FX 0 FY -34.526 FZ 0
 436. 121 FX 0 FY -35.07 FZ 0
 437. 130 FX 0 FY 0 FZ -13.417
 438. 118 FX 0 FY 0 FZ 13.712
 439. 131 FX 0 FY 0 FZ -18.921
 440. 119 FX 0 FY 0 FZ 18.819
 441. 132 FX 0 FY 0 FZ -17.84
 442. 120 FX 0 FY 0 FZ 17.924
 443. 133 FX 0 FY 0 FZ -13.08
 444. 121 FX 0 FY 0 FZ 13.352
 445. *****WIND LOAD TRANSFER BY STEEL STRUCTURE TO RCC STRUCTURE *****
 446. LOAD 14 WL4 (90 DEG , INTERNAL PRESSURE +0.2, WW&LW -0.7)
 447. JOINT LOAD
 448. 113 FX 0.126 FY 41.694 FZ 15.203
 449. 101 FX 0.064 FY 51.59 FZ -14.951
 450. 114 FX -0.009 FY 55.069 FZ 19.946
 451. 102 FX 0.016 FY 54.681 FZ -19.9
 452. 115 FX 0.009 FY 54.877 FZ 19.926
 453. 103 FX 0.027 FY 54.701 FZ -19.9
 454. 116 FX -0.127 FY 41.588 FZ 15.191
 455. 104 FX -0.105 FY 41.491 FZ -15.178
 456. 126 FX 2.647 FY 45.953 FZ -7.033
 457. 122 FX 2.663 FY 43.569 FZ 6.524
 458. 127 FX 0.002 FY 34.346 FZ 5.145
 459. 123 FX 0.002 FY 32.503 FZ -5.15
 460. 128 FX -0.003 FY 39.758 FZ -2.264
 461. 124 FX -0.002 FY 37.469 FZ 1.958
 462. 129 FX -2.653 FY 47.756 FZ -9.409
 463. 125 FX -2.657 FY 45.296 FZ 8.876
 464. 130 FX 0 FY -20.826 FZ 0
 465. 118 FX 0 FY -29.653 FZ 0
 466. 131 FX 0 FY -29.621 FZ 0
 467. 119 FX 0 FY -28.271 FZ 0
 468. 132 FX 0 FY -30.132 FZ 0
 469. 120 FX 0 FY -28.832 FZ 0
 470. 133 FX 0 FY -20.962 FZ 0
 471. 121 FX 0 FY -19.888 FZ 0
 472. 130 FX 0 FY 0 FZ -15.307
 473. 118 FX 0 FY 0 FZ 15.049
 474. 131 FX 0 FY 0 FZ -16.814
 475. 119 FX 0 FY 0 FZ 16.843
 476. 132 FX 0 FY 0 FZ -18.805

BLDG-26

477. 120 FX 0 FY 0 FZ 18.537
 478. 133 FX 0 FY 0 FZ -16.068
 479. 121 FX 0 FY 0 FZ 15.549
 480. *****WIND LOAD TRANSFER BY STEEL STRUCTURE TO RCC STRUCTURE *****
 481. LOAD 15 WL5 (0 DEG , INTERNAL SUCTION -0.3, LEE WARD -0.7, REVERSE)
 482. JOINT LOAD
 483. 113 FX -0.067 FY -48.036 FZ -16.739
 484. 101 FX 0.005 FY 12.045 FZ -3.204
 485. 114 FX -0.009 FY -62.129 FZ -21.795
 486. 102 FX 0.013 FY 12.55 FZ -4.204
 487. 115 FX 0.009 FY -62.129 FZ -21.795
 488. 103 FX 0 FY 12.609 FZ -4.213
 489. 116 FX 0.067 FY -48.039 FZ -16.74
 490. 104 FX 0.016 FY 9.823 FZ -3.25
 491. 126 FX 1.451 FY 18.022 FZ 5.818
 492. 122 FX -1.484 FY -18.256 FZ 4.686
 493. 127 FX 0.003 FY 16.18 FZ 6.615
 494. 123 FX -0.002 FY -16.051 FZ 5.502
 495. 128 FX -0.003 FY 16.122 FZ 6.699
 496. 124 FX 0 FY -16.108 FZ 5.431
 497. 129 FX -1.445 FY 18 FZ 5.857
 498. 125 FX 1.446 FY -18.256 FZ 4.65
 499. 130 FX 0 FY 59.36 FZ 0
 500. 118 FX 0 FY -24.708 FZ 0
 501. 131 FX 0 FY 75.628 FZ 0
 502. 119 FX 0 FY -27.439 FZ 0
 503. 132 FX 0 FY 75.635 FZ 0
 504. 120 FX 0 FY -27.392 FZ 0
 505. 133 FX 0 FY 59.365 FZ 0
 506. 121 FX 0 FY -22.553 FZ 0
 507. 130 FX 0 FY 0 FZ 28.46
 508. 118 FX 0 FY 0 FZ 10.268
 509. 131 FX 0 FY 0 FZ 36.289
 510. 119 FX 0 FY 0 FZ 12.243
 511. 132 FX 0 FY 0 FZ 36.307
 512. 120 FX 0 FY 0 FZ 12.239
 513. 133 FX 0 FY 0 FZ 28.459
 514. 121 FX 0 FY 0 FZ 10.238
 515. *****WIND LOAD TRANSFER BY STEEL STRUCTURE TO RCC STRUCTURE *****
 516. LOAD 16 WL6 (0 DEG , INTERNAL PRESSURE +0.2, LEE WARD -0.2, REVERSE)
 517. JOINT LOAD
 518. 113 FX -0.001 FY -27.449 FZ -9.18
 519. 101 FX 0.045 FY 36.52 FZ -10.52
 520. 114 FX -0.014 FY -34.803 FZ -11.861
 521. 102 FX 0.015 FY 38.577 FZ -13.982
 522. 115 FX 0.014 FY -34.948 FZ -11.876
 523. 103 FX 0.018 FY 38.593 FZ -13.983
 524. 116 FX 0 FY -27.528 FZ -9.188
 525. 104 FX -0.061 FY 29.363 FZ -10.678
 526. 126 FX 2.897 FY 46.462 FZ -1.877
 527. 122 FX 1.155 FY 22.943 FZ 7.512
 528. 127 FX 0.004 FY 36.472 FZ 8.075
 529. 123 FX 0 FY 15.713 FZ -1.041
 530. 128 FX -0.005 FY 40.622 FZ 2.389
 531. 124 FX -0.001 FY 19.521 FZ 4.405
 532. 129 FX -2.905 FY 47.846 FZ -3.705

BLDG-26

533. 125 FX -1.163 FY 24.265 FZ 9.314
534. 130 FX 0 FY 50.056 FZ 0
535. 118 FX 0 FY -27.166 FZ 0
536. 131 FX 0 FY 62.373 FZ 0
537. 119 FX 0 FY -27.052 FZ 0
538. 132 FX 0 FY 61.98 FZ 0
539. 120 FX 0 FY -27.468 FZ 0
540. 133 FX 0 FY 49.949 FZ 0
541. 121 FX 0 FY -20.279 FZ 0
542. 130 FX 0 FY 0 FZ 20.165
543. 118 FX 0 FY 0 FZ 13.929
544. 131 FX 0 FY 0 FZ 28.126
545. 119 FX 0 FY 0 FZ 15.579
546. 132 FX 0 FY 0 FZ 26.603
547. 120 FX 0 FY 0 FZ 16.905
548. 133 FX 0 FY 0 FZ 19.586
549. 121 FX 0 FY 0 FZ 14.314
550. *****
551. ** SERVICEABILITY*
552. *****
553. LOAD COMB 101 1.0DL+1.0LL
554. 1 1.0 2 1.0 3 1.0
555. LOAD COMB 102 1.0DL+0.5LL
556. 1 1.0 2 1.0 3 0.5
557. LOAD COMB 103 0.8DL+0.8LL+0.8WL1
558. 1 0.8 2 0.8 3 0.8 11 0.8
559. LOAD COMB 104 1.0DL+1.0WL1
560. 1 1.0 2 1.0 11 1.0
561. LOAD COMB 105 0.8DL+0.8LL+0.8WL2
562. 1 0.8 2 0.8 3 0.8 12 0.8
563. LOAD COMB 106 1.0DL+1.0WL2
564. 1 1.0 2 1.0 12 1.0
565. LOAD COMB 107 0.8DL+0.8LL+0.8WL3
566. 1 0.8 2 0.8 3 0.8 13 0.8
567. LOAD COMB 108 1.0DL+1.0WL3
568. 1 1.0 2 1.0 13 1.0
569. LOAD COMB 109 0.8DL+0.8LL+0.8WL4
570. 1 0.8 2 0.8 3 0.8 14 0.8
571. LOAD COMB 110 1.0DL+1.0WL4
572. 1 1.0 2 1.0 14 1.0
573. LOAD COMB 111 0.8DL+0.8LL+0.8WL5
574. 1 0.8 2 0.8 3 0.8 15 0.8
575. LOAD COMB 112 1.0DL+1.0WL4
576. 1 1.0 2 1.0 15 1.0
577. LOAD COMB 113 0.8DL+0.8LL+0.8WL6
578. 1 0.8 2 0.8 3 0.8 16 0.8
579. LOAD COMB 114 1.0DL+1.0WL6
580. 1 1.0 2 1.0 16 1.0
581. *****EQX & EQZ *****
582. **DL+EQL/1.4 = 1.0DL+0.72EQX+0.22 EQZ, EQL=EQX+0.3EQZ
583. **0.9 DL+EQL/1.4 =0.9 DL+0.72 EQX+0.22EQZ
584. **DL 0.75(LL+EQL/1.4) =1.0 DL+0.75 EQX+0.17EQZ
585. *****
586. LOAD COMB 115 DL+0.72EQX+0.22EQZ
587. 1 1.0 2 1.0 21 0.72 22 0.22
588. LOAD COMB 116 DL+0.72EQX-0.22EQZ

BLDG-26

589. 1 1.0 2 1.0 21 0.72 22 -0.22
590. LOAD COMB 117 DL-0.72EQX+0.22EQZ
591. 1 1.0 2 1.0 21 -0.72 22 0.22
592. LOAD COMB 118 DL-0.72EQX+0.22EQZ
593. 1 1.0 2 1.0 21 -0.72 22 -0.22
594. LOAD COMB 119 DL+0.72EQX+0.22EQX
595. 1 1.0 2 1.0 22 0.72 21 0.22
596. LOAD COMB 120 DL+0.72EQX-0.22EQX
597. 1 1.0 2 1.0 22 0.72 21 -0.22
598. LOAD COMB 121 DL-0.72EQX+0.22EQX
599. 1 1.0 2 1.0 22 -0.72 21 0.22
600. LOAD COMB 122 DL-0.72EQX-0.22EQX
601. 1 1.0 2 1.0 22 -0.72 21 -0.22
602. LOAD COMB 123 0.9DL+0.72EQX+0.22EQZ
603. 1 0.9 2 0.9 21 0.72 22 0.22
604. LOAD COMB 124 0.9DL+0.72EQX-0.22EQZ
605. 1 0.9 2 0.9 21 0.72 22 -0.22
606. LOAD COMB 125 0.9DL-0.72EQX+0.22EQZ
607. 1 0.9 2 0.9 21 -0.72 22 0.22
608. LOAD COMB 126 0.9DL-0.72EQX+0.22EQZ
609. 1 0.9 2 0.9 21 -0.72 22 -0.22
610. LOAD COMB 127 0.9DL+0.72EQX+0.22EQX
611. 1 0.9 2 0.9 22 0.72 21 0.22
612. LOAD COMB 128 0.9DL+0.72EQX-0.22EQX
613. 1 0.9 2 0.9 22 0.72 21 -0.22
614. LOAD COMB 129 0.9DL-0.72EQX+0.22EQX
615. 1 0.9 2 0.9 22 -0.72 21 0.22
616. LOAD COMB 130 0.9DL-0.72EQX-0.22EQX
617. 1 0.9 2 0.9 22 -0.72 21 -0.22
618. LOAD COMB 131 1.0DL+0.75LL+0.54EQX+0.17 EQZ
619. 1 1.0 2 1.0 3 0.75 21 0.54 22 0.17
620. LOAD COMB 132 1.0DL+0.75LL+0.54EQX-0.17 EQZ
621. 1 1.0 2 1.0 3 0.75 21 0.54 22 -0.17
622. LOAD COMB 133 1.0DL+0.75LL-0.54EQX+0.17 EQZ
623. 1 1.0 2 1.0 3 0.75 21 -0.54 22 0.17
624. LOAD COMB 134 1.0DL+0.75LL-0.54EQX-0.17 EQZ
625. 1 1.0 2 1.0 3 0.75 21 -0.54 22 -0.17
626. LOAD COMB 135 1.0DL+0.75LL+0.54EQZ+0.17 EQX
627. 1 1.0 2 1.0 3 0.75 22 0.54 21 0.17
628. LOAD COMB 136 1.0DL+0.75LL+0.54EQZ-0.17 EQX
629. 1 1.0 2 1.0 3 0.75 22 0.54 21 -0.17
630. LOAD COMB 137 1.0DL+0.75LL-0.54EQZ+0.17 EQX
631. 1 1.0 2 1.0 3 0.75 22 -0.54 21 0.17
632. LOAD COMB 138 1.0DL+0.75LL-0.54EQZ-0.17 EQX
633. 1 1.0 2 1.0 3 0.75 22 -0.54 21 -0.17
634. *****
635. ** CONCRETE DESIGN
636. *****
637. LOAD COMB 200 1.4DL+1.6LL
638. 1 1.4 2 1.4 3 1.6
639. *****WL1*****
640. LOAD COMB 201 1.2DL+1.2LL+1.2WL1
641. 1 1.2 2 1.2 3 1.2 11 1.2
642. LOAD COMB 202 1.4DL+1.4WL1
643. 1 1.4 2 1.4 11 1.4
644. LOAD COMB 203 1DL+1.4WL1

BLDG-26

645. 1 1.0 2 1.0 2 1.0 11 1.4
646. *****WL2*****
647. LOAD COMB 204 1.2DL+1.2LL+1.2WL2
648. 1 1.2 2 1.2 3 1.2 12 1.2
649. LOAD COMB 205 1.4DL+1.4WL2
650. 1 1.4 2 1.4 12 1.4
651. LOAD COMB 206 1DL+1.4WL2
652. 1 1.0 2 1.0 12 1.4
653. *****WL3*****
654. LOAD COMB 207 1.2DL+1.2LL+1.2WL3
655. 1 1.2 2 1.2 3 1.2 13 1.2
656. LOAD COMB 208 1.4DL+1.4WL3
657. 1 1.4 2 1.4 13 1.4
658. LOAD COMB 209 1DL+1.4WL3
659. 1 1.0 2 1.0 13 1.4
660. *****WL4*****
661. LOAD COMB 210 1.2DL+1.2LL+1.2WL4
662. 1 1.2 2 1.2 3 1.2 14 1.2
663. LOAD COMB 211 1.4DL+1.4WL4
664. 1 1.4 2 1.4 14 1.4
665. LOAD COMB 212 1DL+1.4WL4
666. 1 1.0 2 1.0 14 1.4
667. *****WL5*****
668. LOAD COMB 213 1.2DL+1.2LL+1.2WL5
669. 1 1.2 2 1.2 3 1.2 15 1.2
670. LOAD COMB 214 1.4DL+1.4WL5
671. 1 1.4 2 1.4 15 1.4
672. LOAD COMB 215 1DL+1.4WL5
673. 1 1.0 2 1.0 15 1.4
674. *****WL6*****
675. LOAD COMB 216 1.2DL+1.2LL+1.2WL6
676. 1 1.2 2 1.2 3 1.2 16 1.2
677. LOAD COMB 217 1.4DL+1.4WL6
678. 1 1.4 2 1.4 16 1.4
679. LOAD COMB 218 1DL+1.4WL6
680. 1 1.0 2 1.0 16 1.4
681. *****EQX & EQZ *****
682. LOAD COMB 219 1.32DL+1.1LL+1.1EQX+0.33 EQZ
683. 1 1.32 2 1.32 3 1.1 21 1.1 22 0.33
684. LOAD COMB 220 1.32DL+1.1LL+1.1EQX-0.33 EQZ
685. 1 1.32 2 1.32 3 1.1 21 1.1 22 -0.33
686. LOAD COMB 221 1.32DL+1.1LL-1.1EQX+0.33 EQZ
687. 1 1.32 2 1.32 3 1.1 21 -1.1 22 0.33
688. LOAD COMB 222 1.32DL+1.1LL-1.1EQX-0.33 EQZ
689. 1 1.32 2 1.32 3 1.1 21 -1.1 22 -0.33
690. LOAD COMB 223 1.32DL+1.1LL+1.1EQZ+0.33 EQX
691. 1 1.32 2 1.32 3 1.1 22 1.1 21 0.33
692. LOAD COMB 224 1.32DL+1.1LL+1.1EQZ-0.33 EQX
693. 1 1.32 2 1.32 3 1.1 22 1.1 21 -0.33
694. LOAD COMB 225 1.32DL+1.1LL-1.1EQZ+0.33 EQX
695. 1 1.32 2 1.32 3 1.1 22 -1.1 21 0.33
696. LOAD COMB 226 1.32DL+1.1LL-1.1EQZ-0.33 EQX
697. 1 1.32 2 1.32 3 1.1 22 -1.1 21 -0.33
698. LOAD COMB 227 0.99DL+1.1EQX+0.33EQZ
699. 1 0.99 2 0.99 21 1.1 22 0.33
700. LOAD COMB 228 0.99DL+1.1EQX-0.33EQZ

BLDG-26

701. 1 0.99 2 0.99 21 1.1 22 -0.33
702. LOAD COMB 229 0.99DL-1.1EQX+0.33EQZ
703. 1 0.99 2 0.99 21 -1.1 22 0.33
704. LOAD COMB 230 0.99DL-1.1EQX-0.33EQZ
705. 1 0.99 2 0.99 21 -1.1 22 -0.33
706. LOAD COMB 231 0.99DL+1.1EQZ+0.33EQX
707. 1 0.99 2 0.99 22 1.1 21 0.33
708. LOAD COMB 232 0.99DL+1.1EQZ-0.33EQX
709. 1 0.99 2 0.99 22 1.1 21 -0.33
710. LOAD COMB 233 0.99DL-1.1EQZ+0.33EQX
711. 1 0.99 2 0.99 22 -1.1 21 0.33
712. LOAD COMB 234 0.99DL-1.1EQZ-0.33EQX
713. 1 0.99 2 0.99 22 -1.1 21 -0.33
714. LOAD COMB 235 1.0DL+1.0LL+1.0PHX
715. 1 1.0 2 1.0 3 1.0 4 1.0
716. LOAD COMB 236 1.0DL+1.0LL+1.0PHZ
717. 1 1.0 2 1.0 3 1.0 5 1.0
718. *****DEFLECTION*****
719. LOAD COMB 301 SELF+DL
720. 1 1.0 2 1.0
721. LOAD COMB 302 LL
722. 3 1.0
723. LOAD COMB 303 0.8 (LL+WL1)
724. 3 0.8 11 0.8
725. LOAD COMB 304 0.8 (LL+WL2)
726. 3 0.8 12 0.8
727. LOAD COMB 305 0.8 (LL+WL3)
728. 3 0.8 13 0.8
729. LOAD COMB 306 0.8 (LL+WL4)
730. 3 0.8 14 0.8
731. LOAD COMB 307 0.8 (LL+WL5)
732. 3 0.8 15 0.8
733. LOAD COMB 308 0.8 (LL+WL6)
734. 3 0.8 16 0.8
735. LOAD COMB 309 0.8 (LL+EQX/1.4+0.3EQZ/1.4)
736. 3 0.8 21 0.57 22 0.17
737. LOAD COMB 310 0.8 (LL+EQX/1.4-0.3EQZ/1.4)
738. 3 0.8 21 0.57 22 -0.17
739. LOAD COMB 311 0.8 (LL-EQX/1.4+0.3EQZ/1.4)
740. 3 0.8 21 -0.57 22 0.17
741. LOAD COMB 312 0.8 (LL-EQX/1.4-0.3EQZ/1.4)
742. 3 0.8 21 -0.57 22 -0.17
743. LOAD COMB 313 0.8 (LL+EQZ/1.4+0.3EQX/1.4)
744. 3 0.8 22 0.57 21 0.17
745. LOAD COMB 314 0.8 (LL+EQZ/1.4-0.3EQX/1.4)
746. 3 0.8 22 0.57 21 -0.17
747. LOAD COMB 315 0.8 (LL-EQZ/1.4+0.3EQX/1.4)
748. 3 0.8 21 -0.57 22 0.17
749. LOAD COMB 316 0.8 (LL-EQZ/1.4-0.3EQX/1.4)
750. 3 0.8 21 -0.57 22 -0.17
751. PERFORM ANALYSIS

□

P R O B L E M S T A T I S T I C S

NUMBER OF JOINTS/MEMBER+ELEMENTS/SUPPORTS = 68/ 111/ 16
ORIGINAL/FINAL BAND-WIDTH= 46/ 13/ 75 DOF
TOTAL PRIMARY LOAD CASES = 13, TOTAL DEGREES OF FREEDOM = 360
SIZE OF STIFFNESS MATRIX = 27 DOUBLE KILO-WORDS
REQRD/AVAIL. DISK SPACE = 12.6/ 23533.2 MB

*
* X DIRECTION : Ta = 0.344 Tb = 0.610 Tuser = 0.480 *
* T = 0.480, LOAD FACTOR = 1.000 *
* UBC TYPE = 97 *
* UBC FACTOR V = 0.1571 x 14277.00 = 2243.53 KN *
*

*
* Z DIRECTION : Ta = 0.344 Tb = 0.590 Tuser = 0.480 *
* T = 0.480, LOAD FACTOR = 1.000 *
* UBC TYPE = 97 *
* UBC FACTOR V = 0.1571 x 14277.00 = 2243.53 KN *
*

752. LOAD LIST 101 103 TO 118
753. *****
754. LOAD LIST 201 TO 236
755. START CONCRETE DESIGN
[CONCRETE DESIGN]
756. CODE BS8110
PROGRAM CODE REVISION V1.5_8110_97/1
757. UNIT MMS NEWTON

758. FYMAIN 460 ALL

759. FC 40 ALL

760. CLEAR 50 MEMB 1001 TO 1016 2001 TO 2016

761. CLEAR 60 MEMB 1 TO 55 101 TO 124

762. MINSEC 10 ALL

763. TRACK 2 ALL

764. DESIGN COLUMN 1001 TO 1016 2001 TO 2016